

Package ‘enrichplot’

October 14, 2021

Title Visualization of Functional Enrichment Result

Version 1.12.3

Description The ‘enrichplot’ package implements several visualization methods for interpreting functional enrichment results obtained from ORA or GSEA analysis.

All the visualization methods are developed based on ‘ggplot2’ graphics.

Depends R (>= 3.5.0)

Imports cowplot, DOSE (>= 3.16.0), ggplot2, ggraph, graphics, grid, igraph, methods, plyr, purrr, RColorBrewer, reshape2, stats, utils, scatterpie, shadowtext, GOSemSim, magrittr, ggtree

Suggests clusterProfiler, dplyr, europePMC, ggupset, knitr, rmarkdown, org.Hs.eg.db, prettydoc, tibble, tidyverse, AnnotationDbi, ggplotify, ggridges, grDevices, gridExtra, ggnewscale, ggrepel (>= 0.9.0), ggstar, treeio, scales, tidytree

VignetteBuilder knitr

License Artistic-2.0

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/GuangchuangYu/enrichplot/issues>

biocViews Annotation, GeneSetEnrichment, GO, KEGG, Pathways, Software, Visualization

Encoding UTF-8

LazyData true

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/enrichplot>

git_branch RELEASE_3_13

git_last_commit 586391d

git_last_commit_date 2021-10-08

Date/Publication 2021-10-14

Author Guangchuang Yu [aut, cre] (<<https://orcid.org/0000-0002-6485-8781>>), Erqiang Hu [ctb]

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

R topics documented:

barplot.enrichResult	2
cnetplot	3
color_palette	5
dotplot	6
emaplot	9
emaplot_cluster	13
fortify.compareClusterResult	13
ggtable	15
goplot	15
gseadist	17
gseaplot	17
gseaplot2	19
gsrank	20
gsInfo	20
heatplot	21
pairwise_termsim	22
plotting.clusterProfile	23
pmcplot	24
ridgeplot	25
treeplot	26
upsetplot	29

Index

31

barplot.enrichResult *barplot*

Description

barplot of enrichResult

Usage

```
## S3 method for class 'enrichResult'
barplot(
  height,
  x = "Count",
  color = "p.adjust",
  showCategory = 8,
  font.size = 12,
  title = "",
  label_format = 30,
  ...
)
```

Arguments

height	enrichResult object
x	one of 'Count' and 'GeneRatio'
color	one of 'pvalue', 'p.adjust' and 'qvalue'
showCategory	number of categories to show
font.size	font size
title	plot title
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
...	other parameter, ignored

Value

ggplot object

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
barplot(x)
# use `showCategory` to select the displayed terms. It can be a number or a vector of terms.
barplot(x, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
              "breast ductal carcinoma", "non-small cell lung carcinoma")
barplot(x, showCategory = categorys)
```

cnetplot

cnetplot

Description

Gene-Concept Network

Usage

```
cnetplot(x, showCategory = 5, foldChange = NULL, layout = "kk", ...)
## S4 method for signature 'enrichResult'
cnetplot(x, showCategory = 5, foldChange = NULL, layout = "kk", ...)
## S4 method for signature 'gseaResult'
cnetplot(x, showCategory = 5, foldChange = NULL, layout = "kk", ...)
```

```

## S4 method for signature 'compareClusterResult'
cnetplot(x, showCategory = 5, foldChange = NULL, layout = "kk", ...)

cnetplot.enrichResult(
  x,
  showCategory = 5,
  foldChange = NULL,
  layout = "kk",
  colorEdge = FALSE,
  circular = FALSE,
  node_label = "all",
  cex_category = 1,
  cex_gene = 1,
  cex_label_category = 1,
  cex_label_gene = 1,
  color_category = "#E5C494",
  color_gene = "#B3B3B3",
  shadowtext = "all",
  ...
)

```

Arguments

x	Enrichment result.
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
foldChange	Fold Change of nodes, the default value is NULL. If the user provides the Fold Change value of the nodes, it can be used to set the color of the gene node.
layout	Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'.
...	Additional parameters
colorEdge	Logical, whether coloring edge by enriched terms, the default value is FALSE.
circular	Logical, whether using circular layout, the default value is FALSE.
node_label	Select which labels to be displayed. one of 'category', 'gene', 'all'(the default) and 'none'.
cex_category	Number indicating the amount by which plotting category nodes should be scaled relative to the default, the default value is 1.
cex_gene	Number indicating the amount by which plotting gene nodes should be scaled relative to the default, the default value is 1.
cex_label_category	Scale of category node label size, the default value is 1.
cex_label_gene	Scale of gene node label size, the default value is 1.
color_category	Color of category node.
color_gene	Color of gene node.
shadowtext	select which node labels to use shadow font, one of 'category', 'gene', 'all' and 'none', default is 'all' .

Details

plot linkages of genes and enriched concepts (e.g. GO categories, KEGG pathways)

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:  
library(DOSE)  
data(geneList)  
de <- names(geneList)[1:100]  
x <- enrichDO(de)  
x2 <- pairwise_termsim(x)  
cnetplot(x2)  
# use `layout` to change the layout of map  
cnetplot(x2, layout = "star")  
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.  
cnetplot(x2, showCategory = 10)  
categorys <- c("pre-malignant neoplasm", "intestinal disease",  
             "breast ductal carcinoma", "non-small cell lung carcinoma")  
cnetplot(x2, showCategory = categorys)  
# It can also graph compareClusterResult  
data(gcSample)  
library(clusterProfiler)  
library(DOSE)  
library(org.Hs.eg.db)  
data(gcSample)  
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")  
xx2 <- pairwise_termsim(xx)  
cnetplot(xx2)  
  
## End(Not run)
```

color_palette

color_palette

Description

create color palette for continuous data

Usage

color_palette(colors)

Arguments

colors colors of length >=2

Value

color vector

Author(s)

guangchuang yu

Examples

```
color_palette(c("red", "yellow", "green"))
```

dotplot

dotplot

Description

dotplot for enrichment result

Usage

```
dotplot(object, ...)

## S4 method for signature 'enrichResult'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  ...
)

## S4 method for signature 'gseaResult'
dotplot(
  object,
  x = "GeneRatio",
  color = "p.adjust",
  showCategory = 10,
```

```
size = NULL,
split = NULL,
font.size = 12,
title = "",
orderBy = "x",
label_format = 30,
...
)

## S4 method for signature 'compareClusterResult'
dotplot(
  object,
  x = "Cluster",
  color = "p.adjust",
  showCategory = 5,
  split = NULL,
  font.size = 12,
  title = "",
  by = "geneRatio",
  size = NULL,
  includeAll = TRUE,
  label_format = 30,
  ...
)

dotplot.enrichResult(
  object,
  x = "geneRatio",
  color = "p.adjust",
  showCategory = 10,
  size = NULL,
  split = NULL,
  font.size = 12,
  title = "",
  orderBy = "x",
  label_format = 30,
  decreasing = TRUE
)

dotplot.compareClusterResult(
  object,
  x = "Cluster",
  colorBy = "p.adjust",
  showCategory = 5,
  by = "geneRatio",
  size = "geneRatio",
  split = NULL,
  includeAll = TRUE,
```

```

font.size = 12,
title = "",
label_format = 30,
group = FALSE,
shape = FALSE
)

```

Arguments

<code>object</code>	compareClusterResult object
<code>...</code>	additional parameters
<code>x</code>	variable for x-axis, one of 'GeneRatio' and 'Count'
<code>color</code>	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
<code>showCategory</code>	A number or a list of terms. If it is a number, the first n terms will be displayed. If it is a list of terms, the selected terms will be displayed.
<code>size</code>	variable that used to scale the sizes of categories, one of "geneRatio", "Percentage" and "count"
<code>split</code>	ONTOLOGY or NULL
<code>font.size</code>	font size
<code>title</code>	figure title
<code>orderBy</code>	The order of the Y-axis
<code>label_format</code>	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters
<code>by</code>	one of "geneRatio", "Percentage" and "count"
<code>includeAll</code>	logical
<code>decreasing</code>	logical. Should the orderBy order be increasing or decreasing?
<code>colorBy</code>	variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'
<code>group</code>	a logical value, whether to connect the nodes of the same group with wires.
<code>shape</code>	a logical value, whether to use nodes of different shapes to distinguish the group it belongs to

Value

`plot`

Author(s)

guangchuang yu

Examples

```
## Not run:  
library(DOSE)  
data(geneList)  
de <- names(geneList)[1:100]  
x <- enrichD0(de)  
dotplot(x)  
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.  
dotplot(x, showCategory = 10)  
categorys <- c("pre-malignant neoplasm", "intestinal disease",  
               "breast ductal carcinoma", "non-small cell lung carcinoma")  
dotplot(x, showCategory = categorys)  
# It can also graph compareClusterResult  
data(gcSample)  
library(clusterProfiler)  
library(DOSE)  
library(org.Hs.eg.db)  
data(gcSample)  
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")  
xx2 <- pairwise_termsim(xx)  
library(ggstar)  
dotplot(xx2)  
dotplot(xx2, shape = TRUE)  
dotplot(xx2, group = TRUE)  
dotplot(xx2, x = "GeneRatio", group = TRUE, size = "count")  
  
## End(Not run)
```

emapplot

emapplot

Description

Enrichment Map for enrichment result of over-representation test or gene set enrichment analysis

Usage

```
emapplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'enrichResult'  
emapplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'gseaResult'  
emapplot(x, showCategory = 30, ...)  
  
## S4 method for signature 'compareClusterResult'  
emapplot(x, showCategory = 30, ...)  
  
emapplot.enrichResult(  
  ...)
```

```
x,
showCategory = 30,
layout = NULL,
coords = NULL,
color = "p.adjust",
min_edge = 0.2,
cex_label_category = 1,
cex_category = 1,
cex_line = 1,
shadowtext = TRUE,
label_style = "shadowtext",
repel = FALSE,
node_label = "category",
with_edge = TRUE,
group_category = FALSE,
group_legend = FALSE,
cex_label_group = 1,
nWords = 4,
label_format = 30,
clusterFunction = stats::kmeans,
nCluster = NULL,
...
)

emapplot.compareClusterResult(
  x,
  showCategory = 30,
  layout = NULL,
  coords = NULL,
  split = NULL,
  pie = "equal",
  legend_n = 5,
  cex_category = 1,
  cex_line = 1,
  min_edge = 0.2,
  cex_label_category = 1,
  shadowtext = TRUE,
  with_edge = TRUE,
  group_category = FALSE,
  label_format = 30,
  group_legend = FALSE,
  node_label = "category",
  label_style = "shadowtext",
  repel = FALSE,
  cex_label_group = 1,
  nWords = 4,
  clusterFunction = stats::kmeans,
  nCluster = NULL,
```

```
cex_pie2axis = 1,
...
)
```

Arguments

x	Enrichment result.
showCategory	A number or a vector of terms. If it is a number, the first n terms will be displayed. If it is a vector of terms, the selected terms will be displayed.
...	additional parameters additional parameters can refer the following parameters.
	<ul style="list-style-type: none"> • force Force of repulsion between overlapping text labels. Defaults to 1. • nudge_x,nudge_y Horizontal and vertical adjustments to nudge the starting position of each text label. • direction "both", "x", or "y" – direction in which to adjust position of labels. • ellipse_style style of ellipse, one of "ggforce" an "polygon". • ellipse_pro numeric indicating confidence value for the ellipses, it can be used only when ellipse_style = "polygon". • alpha the transparency of ellipse fill. • type The type of ellipse. The default "t" assumes a multivariate t-distribution, and "norm" assumes a multivariate normal distribution. "euclid" draws a circle with the radius equal to level, representing the euclidean distance from the center.
layout	Layout of the map, e.g. 'star', 'circle', 'gem', 'dh', 'graphopt', 'grid', 'mds', 'randomly', 'fr', 'kk', 'drl' or 'lgl'.
coords	a data.frame with two columns: 'x' for X-axis coordinate and 'y' for Y-axis coordinate.
color	Variable that used to color enriched terms, e.g. 'pvalue', 'p.adjust' or 'qvalue'.
min_edge	The minimum similarity threshold for whether two nodes are connected, should between 0 and 1, default value is 0.2.
cex_label_category	Scale of category node label size.
cex_category	Number indicating the amount by which plotting category nodes should be scaled relative to the default.
cex_line	Scale of line width
shadowtext	a logical value, whether to use shadow font.
label_style	style of group label, one of "shadowtext" and "ggforce".
repel	whether to correct the position of the label. Defaults to FALSE.
node_label	Select which labels to be displayed, one of 'category', 'group', 'all' and 'none'.
with_edge	Logical, if TRUE (the default), draw the edges of the network diagram.
group_category	a logical, if TRUE(the default), group the category.
group_legend	Logical, if TRUE, the grouping legend will be displayed. The default is FALSE.

cex_label_group	Numeric, scale of group labels size, the default value is 1.
nWords	Numeric, the number of words in the cluster tags, the default value is 4.
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
clusterFunction	function of Clustering method, such as stats::kmeans(the default), cluster::clara, cluster::fanny or cluster::pam.
nCluster	Numeric, the number of clusters, the default value is square root of the number of nodes.
split	separate result by 'category' variable
pie	proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'
legend_n	number of circle in legend
cex_pie2axis	It is used to adjust the relative size of the pie chart on the coordinate axis, the default value is 1.

Details

This function visualizes gene sets as a network (i.e. enrichment map). Mutually overlapping gene sets tend to cluster together, making it easier for interpretation. When the similarity between terms meets a certain threshold (default is 0.2, adjusted by parameter 'min_edge'), there will be edges between terms. The stronger the similarity, the shorter and thicker the edges. The similarity between terms is obtained by function 'pairwise_termsim', the details of similarity calculation can be found in its documentation: [pairwise_termsim](#).

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
## Not run:
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
x2 <- pairwise_termsim(x)
emapplot(x2)
# use `layout` to change the layout of map
emapplot(x2, layout = "star")
# use `showCategory` to select the displayed terms. It can be a number of a vector of terms.
emapplot(x2, showCategory = 10)
categorys <- c("pre-malignant neoplasm", "intestinal disease",
              "breast ductal carcinoma", "non-small cell lung carcinoma")
```

```

emapplot(x2, showCategory = categorys)

# It can also graph compareClusterResult
data(gcSample)
library(clusterProfiler)
library(DOSE)
library(org.Hs.eg.db)
data(gcSample)
xx <- compareCluster(gcSample, fun="enrichGO", OrgDb="org.Hs.eg.db")
xx2 <- pairwise_termsim(xx)
emapplot(xx2)

## End(Not run)

```

emapplot_cluster

Functional grouping network diagram for enrichment result of over-representation test or gene set enrichment analysis

Description

This function has been replaced by ‘emapplot’.

Usage

```
emapplot_cluster(x, ...)
```

Arguments

x	enrichment result
...	additional parameters. Please refer to: emapplot .

Value

ggplot2 object

fortify.compareClusterResult

fortify

Description

convert compareClusterResult to a data.frame that ready for plot
 convert enrichResult object for ggplot2

Usage

```
## S3 method for class 'compareClusterResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "geneRatio",
  split = NULL,
  includeAll = TRUE
)

## S3 method for class 'enrichResult'
fortify(
  model,
  data,
  showCategory = 5,
  by = "Count",
  order = FALSE,
  drop = FALSE,
  split = NULL,
  ...
)
```

Arguments

model	'enrichResult' or 'compareClusterResult' object
data	not use here
showCategory	Category numbers to show
by	one of Count and GeneRatio
split	separate result by 'split' variable
includeAll	logical
order	logical
drop	logical
...	additional parameter

Value

data.frame
data.frame

Author(s)

Guangchuang Yu

ggtab	<i>ggtab</i>
-------	--------------

Description

plot table

Usage

```
ggtab(d, p = NULL)
```

Arguments

d	data frame
p	ggplot object to extract color to color rownames(d), optional

Value

ggplot object

Author(s)

guangchuang yu

goplot	<i>goplot</i>
--------	---------------

Description

plot induced GO DAG of significant terms

Usage

```
goplot(  
  x,  
  showCategory = 10,  
  color = "p.adjust",  
  layout = "sugiyama",  
  geom = "text",  
  ...  
)  
  
## S4 method for signature 'enrichResult'  
goplot(  
  x,
```

```

showCategory = 10,
color = "p.adjust",
layout = "sugiyama",
geom = "text",
...
)

## S4 method for signature 'gseaResult'
goplot(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

goplot.enrichResult(
  x,
  showCategory = 10,
  color = "p.adjust",
  layout = "sugiyama",
  geom = "text",
  ...
)

```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
color	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
layout	layout of the map
geom	label geom, one of 'label' or 'text'
...	additional parameter

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```

## Not run:
library(clusterProfiler)
data(geneList, package = "DOSE")

```

```
de <- names(geneList)[1:100]
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
  goplot(yy)
  goplot(yy, showCategory = 5)

## End(Not run)
```

gseadist

gseadist

Description

plot logFC distribution of selected gene sets

Usage

```
gseadist(x, IDs, type = "density")
```

Arguments

x	GSEA result
IDs	gene set IDs
type	one of 'density' or 'boxplot'

Value

distribution plot

Author(s)

Guangchuang Yu

gseaplot

gseaplot

Description

visualize analyzing result of GSEA

Usage

```

gseaplot(x, geneSetID, by = "all", title = "", ...)

## S4 method for signature 'gseaResult'
gseaplot(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
  color.vline = "#FA5860",
  ...
)

gseaplot.gseaResult(
  x,
  geneSetID,
  by = "all",
  title = "",
  color = "black",
  color.line = "green",
  color.vline = "#FA5860",
  ...
)

```

Arguments

<code>x</code>	object of gsea result
<code>geneSetID</code>	geneSet ID
<code>by</code>	one of "runningScore" or "position"
<code>title</code>	plot title
<code>...</code>	additional parameters
<code>color</code>	color of line segments
<code>color.line</code>	color of running enrichment score line
<code>color.vline</code>	color of vertical line which indicating the maximum/minimal running enrichment score

Details

plotting function for gseaResult

Value

ggplot2 object
ggplot2 object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseD0(geneList)
gseaplot(x, geneSetID=1)
```

gseaplot2

gseaplot2

Description

GSEA plot that mimic the plot generated by broad institute's GSEA software

Usage

```
gseaplot2(
  x,
  geneSetID,
  title = "",
  color = "green",
  base_size = 11,
  rel_heights = c(1.5, 0.5, 1),
  subplots = 1:3,
  pvalue_table = FALSE,
  ES_geom = "line"
)
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title
color	color of running enrichment score line
base_size	base font size
rel_heights	relative heights of subplots
subplots	which subplots to be displayed
pvalue_table	whether add pvalue table
ES_geom	geom for plotting running enrichment score, one of 'line' or 'dot'

Value

plot

Author(s)

Guangchuang Yu

gsearank	<i>gsearank</i>
----------	-----------------

Description

plot ranked list of genes with running enrichment score as bar height

Usage

```
gsearank(x, geneSetID, title = "")
```

Arguments

x	gseaResult object
geneSetID	gene set ID
title	plot title

Value

ggplot object

Author(s)

Guangchuang Yu

gsInfo	<i>gsInfo</i>
--------	---------------

Description

extract gsea result of selected geneSet

Usage

```
gsInfo(object, geneSetID)
```

Arguments

object	gseaResult object
geneSetID	gene set ID

Value

data.frame

Author(s)

Guangchuang Yu

heatplot

heatplot

Description

heatmap like plot for functional classification

Usage

```
heatplot(x, showCategory = 30, foldChange = NULL)

## S4 method for signature 'enrichResult'
heatplot(x, showCategory = 30, foldChange = NULL)

## S4 method for signature 'gseaResult'
heatplot(x, showCategory = 30, foldChange = NULL)

heatplot.enrichResult(
  x,
  showCategory = 30,
  foldChange = NULL,
  label_format = 30
)
```

Arguments

x	enrichment result.
showCategory	number of enriched terms to display
foldChange	fold Change
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels. by default wraps names longer than 30 characters

Value

ggplot object

Author(s)

guangchuang yu
Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
de <- names(geneList)[1:100]
x <- enrichDO(de)
heatplot(x)
```

`pairwise_termsim` *pairwise_termsim*

Description

Get the similarity matrix

Usage

```
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'enrichResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'gseaResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

## S4 method for signature 'compareClusterResult'
pairwise_termsim(x, method = "JC", semData = NULL, showCategory = 200)

pairwise_termsim.enrichResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)

pairwise_termsim.compareClusterResult(
  x,
  method = "JC",
  semData = NULL,
  showCategory = 200
)
```

Arguments

<code>x</code>	enrichment result.
<code>method</code>	method of calculating the similarity between nodes, one of "Resnik", "Lin", "Rel", "Jiang", "Wang" and "JC"(Jaccard similarity coefficient) methods.

semData	GOSemSimDATA object, can be obtained through <code>godata</code> function in GOSemSim package.
showCategory	number of enriched terms to display, default value is 200.

Details

This function add similarity matrix to the termsim slot of enrichment result. Users can use the ‘method’ parameter to select the method of calculating similarity. The Jaccard correlation coefficient(JC) is used by default, and it applies to all situations. When users want to calculate the correlation between GO terms or DO terms, they can also choose "Resnik", "Lin", "Rel" or "Jiang" (they are semantic similarity calculation methods from GOSemSim packages), and at this time, the user needs to provide ‘semData‘ parameter, which can be obtained through `godata` function in GOSemSim package.

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
                 universe      = names(geneList),
                 OrgDb        = org.Hs.eg.db,
                 ont          = "BP",
                 pAdjustMethod = "BH",
                 pvalueCutoff  = 0.01,
                 qvalueCutoff  = 0.05,
                 readable     = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method="Wang", semData = d)
emapplot(ego2)
emapplot_cluster(ego2)

## End(Not run)
```

Description

Internal plot function for plotting compareClusterResult

Usage

```
plotting.clusterProfile(
  clProf.reshape.df,
  x = ~Cluster,
  type = "dot",
  colorBy = "p.adjust",
  by = "geneRatio",
  title = "",
  font.size = 12
)
```

Arguments

clProf.reshape.df	data frame of compareCluster result
x	x variable
type	one of dot and bar
colorBy	one of pvalue or p.adjust
by	one of percentage and count
title	graph title
font.size	graph font size

Value

ggplot object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

pmcplot

pmcplot

Description

PubMed Central Trend plot

Usage

```
pmcplot(query, period, proportion = TRUE)
```

Arguments

query	query terms
period	period of query in the unit of year
proportion	If TRUE, use query_hits/all_hits, otherwise use query_hits

Value

ggplot object

Author(s)

guangchuang yu

ridgeplot

ridgeplot

Description

ridgeline plot for GSEA result

Usage

```
ridgeplot(  
  x,  
  showCategory = 30,  
  fill = "p.adjust",  
  core_enrichment = TRUE,  
  label_format = 30,  
  ...  
)  
  
## S4 method for signature 'gseaResult'  
ridgeplot(  
  x,  
  showCategory = 30,  
  fill = "p.adjust",  
  core_enrichment = TRUE,  
  label_format = 30,  
  ...  
)  
  
ridgeplot.gseaResult(  
  x,  
  showCategory = 30,  
  fill = "p.adjust",  
  core_enrichment = TRUE,  
  label_format = 30,  
  orderBy = "NES",  
  decreasing = FALSE  
)
```

Arguments

x	gseaResult object
showCategory	number of categories for plotting
fill	one of "pvalue", "p.adjust", "qvalue"
core_enrichment	whether only using core_enriched genes
label_format	a numeric value sets wrap length, alternatively a custom function to format axis labels.
...	additional parameters by default wraps names longer than 30 characters
orderBy	The order of the Y-axis
decreasing	logical. Should the orderBy order be increasing or decreasing?

Value

ggplot object

Author(s)

Guangchuang Yu

Examples

```
library(DOSE)
data(geneList)
x <- gseD0(geneList)
ridgeplot(x)
```

treeplot

treeplot

Description

Functional grouping tree diagram for enrichment result of over-representation test or gene set enrichment analysis.

Usage

```
treeplot(x, showCategory = 30, color = "p.adjust", label_format = 30, ...)
## S4 method for signature 'enrichResult'
treeplot(x, showCategory = 30, color = "p.adjust", label_format = 30, ...)
## S4 method for signature 'gseaResult'
treeplot(x, showCategory = 30, color = "p.adjust", label_format = 30, ...)
```

```
## S4 method for signature 'compareClusterResult'
treeplot(x, showCategory = 5, color = "p.adjust", label_format = 30, ...)

treeplot.enrichResult(
  x,
  showCategory = 30,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  label_format = 30,
  xlim = NULL,
  fontsize = 4,
  offset = NULL,
  offset_tiplab = 0.35,
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  ...
)

treeplot.compareClusterResult(
  x,
  showCategory = 5,
  color = "p.adjust",
  nWords = 4,
  nCluster = 5,
  cex_category = 1,
  split = NULL,
  label_format = 30,
  xlim = NULL,
  fontsize = 4,
  offset = NULL,
  pie = "equal",
  legend_n = 3,
  offset_tiplab = 0.5,
  hclust_method = "ward.D",
  group_color = NULL,
  extend = 0.3,
  hilight = TRUE,
  ...
)
```

Arguments

- x enrichment result.
- showCategory number of enriched terms to display

<code>color</code>	variable that used to color enriched terms, e.g. pvalue, p.adjust or qvalue
<code>label_format</code>	a numeric value sets wrap length, alternatively a custom function to format axis labels.
<code>...</code>	additional parameters
<code>nWords</code>	The number of words in the cluster tags.
<code>nCluster</code>	The number of clusters, the default value is 5.
<code>cex_category</code>	Number indicating the amount by which plotting category. nodes should be scaled relative to the default.
<code>xlim</code>	Limits for the x axes, e.g. c(0, 40). If the picture is not displayed completely, the user can increase this value.
<code>fontsize</code>	The size of text, default is 4.
<code>offset</code>	Distance bar and tree, offset of bar and text from the clade.
<code>offset_tiplab</code>	Tiplab offset, the bigger the number, the farther the distance between the node and the branch. The default value is 0.35.
<code>hclust_method</code>	Method of hclust. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average" (= UPGMA), "mcquitty" (= WPGMA), "median" (= WPGMC) or "centroid" (= UPGMC).
<code>group_color</code>	A vector of group colors, the length of the vector should be the same as nCluster.
<code>extend</code>	Numeric, extend the length of bar, default is 0.3.
<code>hilight</code>	Logical value, if TRUE(default), add ggtree::geom_hilight() layer.
<code>split</code>	Separate result by 'category' variable.
<code>pie</code>	Proportion of clusters in the pie chart, one of 'equal' (default) and 'Count'.
<code>legend_n</code>	Number of circle in legend, the default value is 3.

Details

This function visualizes gene sets as a tree. Gene sets with high similarity tend to cluster together, making it easier for interpretation.

Value

ggplot object

Examples

```
## Not run:
library(clusterProfiler)
library(org.Hs.eg.db)
library(enrichplot)
library(GOSemSim)
library(DOSE)
data(geneList)
gene <- names(geneList)[abs(geneList) > 2]
ego <- enrichGO(gene = gene,
                 universe = names(geneList),
```

```

OrgDb      = org.Hs.eg.db,
ont        = "BP",
pAdjustMethod = "BH",
pvalueCutoff  = 0.01,
qvalueCutoff   = 0.05,
readable      = TRUE)
d <- godata('org.Hs.eg.db', ont="BP")
ego2 <- pairwise_termsim(ego, method = "Wang", semData = d)
treeplot(ego2, showCategory = 30)
# use `hilight = FALSE` to remove ggtree::geom_hilight() layer.
treeplot(ego2, showCategory = 30, hilight = FALSE)
# use `offset` parameter to adjust the distance of bar and tree.
treeplot(ego2, showCategory = 30, hilight = FALSE, offset = 8)
# use `offset_tiplab` parameter to adjust the distance of nodes and branches.
treeplot(ego2, showCategory = 30, hilight = FALSE, offset_tiplab = 0.3)
keep <- rownames(ego2@termsim)[c(1:10, 16:20)]
keep
treeplot(ego2, showCategory = keep)
treeplot(ego2, showCategory = 20,
         group_color = c("#999999", "#E69F00", "#56B4E9", "#009E73", "#F0E442"))

## End(Not run)

```

upsetplot*upsetplot method***Description**

upsetplot method generics

Usage

```

upsetplot(x, ...)

## S4 method for signature 'enrichResult'
upsetplot(x, n = 10, ...)

## S4 method for signature 'gseaResult'
upsetplot(x, n = 10, ...)

```

Arguments

x	object
...	additional parameters
n	number of categories to be plotted

Value

plot

Author(s)

Guangchuang Yu

Examples

```
require(DOSE)
data(geneList)
de=names(geneList)[1:100]
x <- enrichD0(de)
upsetplot(x, 8)
```

Index

barplot.enrichResult, 2
cnetplot, 3
cnetplot, compareClusterResult-method
(cnetplot), 3
cnetplot, enrichResult-method
(cnetplot), 3
cnetplot, gseaResult-method (cnetplot), 3
cnetplot.enrichResult (cnetplot), 3
color_palette, 5

dotplot, 6
dotplot, compareClusterResult, ANY-method
(dotplot), 6
dotplot, compareClusterResult-method
(dotplot), 6
dotplot, enrichResult-method (dotplot), 6
dotplot, gseaResult-method (dotplot), 6
dotplot.compareClusterResult (dotplot),
6
dotplot.enrichResult (dotplot), 6

emapplot, 9, 13
emapplot, compareClusterResult-method
(emapplot), 9
emapplot, enrichResult-method
(emapplot), 9
emapplot, gseaResult-method (emapplot), 9
emapplot.compareClusterResult
(emapplot), 9
emapplot.enrichResult (emapplot), 9
emapplot_cluster, 13

fortify.compareClusterResult, 13
fortify.enrichResult
(fortify.compareClusterResult),
13

ggtable, 15
godata, 23
goplot, 15

goplot, enrichResult-method (goplot), 15
goplot, gseaResult-method (goplot), 15
goplot.enrichResult (goplot), 15
gseadist, 17
gseaplot, 17
gseaplot, gseaResult-method (gseaplot),
17
gseaplot.gseaResult (gseaplot), 17
gseaplot2, 19
gsearank, 20
gsInfo, 20

heatplot, 21
heatplot, enrichResult-method
(heatplot), 21
heatplot, gseaResult-method (heatplot),
21
heatplot.enrichResult (heatplot), 21

pairwise_termsim, 12, 22
pairwise_termsim, compareClusterResult-method
(pairwise_termsim), 22
pairwise_termsim, enrichResult-method
(pairwise_termsim), 22
pairwise_termsim, gseaResult-method
(pairwise_termsim), 22
pairwise_termsim.compareClusterResult
(pairwise_termsim), 22
pairwise_termsim.enrichResult
(pairwise_termsim), 22
plotting.clusterProfile, 23
pmcplot, 24

ridgeplot, 25
ridgeplot, gseaResult-method
(ridgeplot), 25
ridgeplot.gseaResult (ridgeplot), 25

treeplot, 26
treeplot, compareClusterResult-method
(treeplot), 26

treeplot,enrichResult-method
 (treeplot), [26](#)
treeplot,gseaResult-method (treeplot),
 [26](#)
treeplot.compareClusterResult
 (treeplot), [26](#)
treeplot.enrichResult (treeplot), [26](#)

upsetplot, [29](#)
upsetplot,enrichResult,ANY-method
 (upsetplot), [29](#)
upsetplot,enrichResult-method
 (upsetplot), [29](#)
upsetplot,gseaResult (upsetplot), [29](#)
upsetplot,gseaResult-method
 (upsetplot), [29](#)