

Package ‘diffUTR’

July 23, 2025

Type Package

Title diffUTR: Streamlining differential exon and 3' UTR usage

Version 1.16.0

Depends R (>= 4.0)

Description The diffUTR package provides a uniform interface and plotting functions for limma/edgeR/DEXSeq -powered differential bin/exon usage. It includes in addition an improved version of the limma::diffSplice method. Most importantly, diffUTR further extends the application of these frameworks to differential UTR usage analysis using poly-A site databases.

Imports S4Vectors, SummarizedExperiment, limma, edgeR, DEXSeq, GenomicRanges, Rsubread, ggplot2, rtracklayer, ComplexHeatmap, ggrepel, stringi, methods, stats, GenomeInfoDb, dplyr, matrixStats, IRanges, ensemblDb, viridisLite

Suggests BiocStyle, knitr, rmarkdown

biocViews GeneExpression

BugReports <https://github.com/ETHZ-INS/diffUTR>

VignetteBuilder knitr

License GPL-3

Encoding UTF-8

RoxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/diffUTR>

git_branch RELEASE_3_21

git_last_commit 8ef8f45

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-07-23

Author Pierre-Luc Germain [cre, aut] (ORCID:
<<https://orcid.org/0000-0003-3418-4218>>),
Stefan Gerber [aut]

Maintainer Pierre-Luc Germain <pierre-luc.germain@hest.ethz.ch>

Contents

addNormalizedAssays	2
countFeatures	3
deuBinPlot	4
diffSplice2	5
diffSpliceDGEWrapper	6
example_bin_se	7
example_gene_annotation	8
geneBinHeatmap	8
geneLevelStats	9
plotTopGenes	11
prepareBins	12
rn6_PAS	13
simesAggregation	13
Index	14

addNormalizedAssays	<i>addNormalizedAssays</i>
---------------------	----------------------------

Description

addNormalizedAssays

Usage

addNormalizedAssays(se, readLength = 50L)

Arguments

- se A bin-wise ‘SummarizedExperiment’ as produced by [countFeatures](#)
- readLength Used as a minimum width to estimate read density (default 50).

Value

The ‘se’ object with populated ‘logcpm’ and ‘logNormDensity’ assays.

Examples

```
data(example_bin_se)
example_bin_se <- addNormalizedAssays(example_bin_se)
```

countFeatures	<i>countFeatures</i>
---------------	----------------------

Description

countFeatures

Usage

```
countFeatures(
  bamfiles,
  bins,
  strandSpecific = 0,
  readLength = 50L,
  allowMultiOverlap = TRUE,
  inclNormalized = TRUE,
  tmpDir = tempdir(),
  ...
)
```

Arguments

bamfiles	A vector of paths to bam files
bins	A GRanges of bins in which to count reads (or path to a rds file containing such an object)
strandSpecific	Passed to 'Rsubread::featureCounts'
readLength	Used as a minimum width to estimate read density.
allowMultiOverlap	Passed to 'Rsubread::featureCounts'
inclNormalized	Logical; whether to include normalized assays (needed for plotting)
tmpDir	Passed to 'Rsubread::featureCounts'
...	Passed to 'Rsubread::featureCounts'

Value

A [RangedSummarizedExperiment-class](#)

Examples

```
data("example_gene_annotation", package="diffUTR")
bins <- prepareBins(example_gene_annotation)
bam_files <- list.files(system.file("extdata", package="diffUTR"),
                        pattern="bam$", full=TRUE)

# not run
# se <- countFeatures(bam_files, bins, verbose=FALSE)
```

deuBinPlot

*deuBinPlot***Description**

deuBinPlot

Usage

```
deuBinPlot(
  se,
  gene,
  type = c("summary", "condition", "sample"),
  intronSize = 2,
  exonSize = c("sqrt", "linear", "log"),
  y = NULL,
  condition = NULL,
  size = "type",
  lineSize = 1,
  colour = NULL,
  alpha = NULL,
  removeAmbiguous = TRUE,
  minDensityRatio = 0.1
)
```

Arguments

se	A bin-wise SummarizedExperiment as produced by countFeatures and including bin-level tests (i.e. having been passed through one of the DEU wrappers such as diffSpliceWrapper or DEXSeqWrapper)
gene	The gene of interest
type	Either 'summary' (plot DEU summary), 'sample' (plot sample-wise data), or 'condition' (plot data aggregate by condition)
intronSize	Intron plot size. If ≤ 3 , intron size will be this fraction of the mean exon size. If > 3 , each intron will have the given size.
exonSize	Scaling for exon sizes, either 'sqrt', 'log', or 'linear'.
y	Value to plot on the y-axis. If 'type="summary"', this should be a column of 'rowData(se)', otherwise should be an assay name of 'se'.
condition	The colData column containing the samples' condition.
size	rowData variable to use to determine the thickness of the bins.
lineSize	Size of the line connecting the bins. Use 'lineSize=0' to omit the line.
colour	rowData variable to use to determine the colour of the bins. If 'type="condition"', can also be "condition"; if 'type="sample"' can be any colData column.
alpha	Alpha level, passed to ggplot.

`removeAmbiguous` Logical; whether to remove bins that are gene-ambiguous (i.e. overlap multiple genes).

`minDensityRatio` Minimum ratio of read density (with respect to the gene's average) for a bin to be plotted.

Value

A ggplot object

Examples

```
data(example_bin_se)
se <- diffSpliceWrapper(example_bin_se, ~condition)
deuBinPlot(se, "Jund")
```

diffSplice2	<i>diffSplice2</i>
-------------	--------------------

Description

This is a small improvement to the [diffSplice](#) function written by Gordon Smyth and Charity Law.

Usage

```
diffSplice2(fit, geneid, exonid = NULL, robust = FALSE, verbose = TRUE)
```

Arguments

<code>fit</code>	an MArrayLM-class fitted model object produced by lmFit or ‘ <code>contrasts.fit</code> ’, with rows corresponding to exons.
<code>geneid</code>	gene identifiers (as in diffSplice)
<code>exonid</code>	exon identifiers (as in diffSplice)
<code>robust</code>	logical, should the estimation of the empirical Bayes prior parameters be robustified against outlier sample variances?
<code>verbose</code>	logical, if TRUE will output some diagnostic information

Value

An [MArrayLM-class](#) object containing both exon level and gene level tests. Results are sorted by `geneid` and by `exonid` within gene.

Examples

```
library(SummarizedExperiment)
library(edgeR)
data(example_bin_se)
se <- example_bin_se
design <- model.matrix(~condition, data=as.data.frame(colData(se)))
dds <- calcNormFactors(DGEList(assays(se)$counts))
dds <- voom(dds, design)
dds <- lmFit(dds, design)
res <- diffSplice2(dds, geneid=rowData(se)$gene, exonid=row.names(se))
topSplice(res)
```

diffSpliceDGEWrapper *DEUwrappers*

Description

Wrappers around commonly-used DEU methods ([diffSpliceDGE](#), [DEXSeq](#) and an improved version of [diffSplice](#))

Usage

```
diffSpliceDGEWrapper(
  se,
  design,
  coef = NULL,
  QLF = TRUE,
  robust = TRUE,
  countFilter = TRUE,
  excludeTypes = NULL
)

diffSpliceWrapper(
  se,
  design,
  coef = NULL,
  robust = TRUE,
  improved = TRUE,
  countFilter = TRUE,
  excludeTypes = NULL
)

DEXSeqWrapper(
  se,
  design = ~sample + exon + condition:exon,
  reducedModel = ~sample + exon,
  excludeTypes = NULL,
```

```
    ...  
  )
```

Arguments

se	A bin-wise SummarizedExperiment as produced by countFeatures
design	A formula (using columns of 'colData(se)') or (for 'diffSpliceWrapper' or 'diffSpliceDGEWrapper' only) a model.matrix.
coef	The coefficient to be tested (ignored for 'DEXSeqWrapper').
QLF	Logical; whether to use edgeR's quasi-likelihood negative binomial (applicable only to 'diffSpliceDGEWrapper').
robust	Logical; whether to use robust fitting for the dispersion trend (ignored for 'DEXSeqWrapper').
countFilter	Logical; whether to filter out low-count bins (ignored for 'DEXSeqWrapper').
excludeTypes	A vector of bin types to ignore for testing. To test for any kind of differential usage, leave empty. To test for differential UTR usage, use 'excludeTypes=c("CDS","non-coding")' (or see geneLevelStats for more options).
improved	Logical; whether to use diffSplice2 instead of the original diffSplice (default TRUE).
reducedModel	A reduced formula (applicable only to 'DEXSeqWrapper').
...	Further arguments (passed to 'testForDEU' and 'estimateExonFoldChanges') of 'DEXSeq'. Can for instance be used to enable multithreading, by passing 'BPPARAM=BiocParallel::MulticoreParam(ncores)'.

Value

The 'se' object with additional rowData columns contain bin (i.e. exon) -level statistics, and a metadata slot containing gene level p-values.

Examples

```
library(SummarizedExperiment)  
data(example_bin_se)  
se <- diffSpliceWrapper(example_bin_se, ~condition)  
head(rowData(se))
```

example_bin_se	<i>Example bin-level 'RangedSummarizedExperiment'</i>
----------------	---

Description

An object produced by [countFeatures](#) containing small subset of genes from mouse hippocampal slices undergoing Forskolin-induced long-term potentiation (GSE84643).

Value

a ‘RangedSummarizedExperiment’

References

<https://www.nature.com/articles/s41598-017-17407-w>

example_gene_annotation

Example gene annotation

Description

An example gene annotation containing only a small subset of mouse genes.

Value

a ‘GRanges’ object

geneBinHeatmap

geneBinHeatmap

Description

A wrapper around ‘ComplexHeatmap’.

Usage

```
geneBinHeatmap(
  se,
  gene,
  what = NULL,
  anno_rows = c("type", "logWidth", "meanLogDensity", "log10PValue", "geneAmbiguous"),
  anno_columns = c(),
  anno_colors = list(),
  removeAmbiguous = FALSE,
  merge_legends = TRUE,
  cluster_columns = FALSE,
  minDensityRatio = 0.1,
  left_annotation = NULL,
  top_annotation = NULL,
  ...
)
```


Arguments

se	A bin-wise SummarizedExperiment as produced by countFeatures
gene	The gene of interest
what	Type of values (i.e. assay) to plot
anno_rows	Row annotation columns (i.e. columns of 'rowData(se)') to plot
anno_columns	Column annotation columns (i.e. columns of 'colData(se)') to plot
anno_colors	Annotation colors, as a list named with the row/column annotations, see ' SingleAnnotation ' for details. Ignored if 'left_annotation' and/or 'top_annotation' are given directly.
removeAmbiguous	Logical; whether to remove bins that are gene-ambiguous (i.e. overlap multiple genes).
merge_legends	Logical; whether to merge legends. This effectively calls 'draw(..., merge_legends=TRUE)' around the heatmap.
cluster_columns	Logical; whether to cluster columns (passed to Heatmap)
minDensityRatio	Minimum ratio of read density (with respect to the gene's average) for a bin to be plotted.
left_annotation	Passed to Heatmap , overrides 'anno_rows'.
top_annotation	Passed to Heatmap , overrides 'anno_columns'.
...	Passed to 'ComplexHeatmap' (see Heatmap)

Value

A [Heatmap](#)

Examples

```
data(example_bin_se)
se <- diffSpliceWrapper(example_bin_se, ~condition)
geneBinHeatmap(se, "Jund")
```

geneLevelStats	<i>geneLevelStats</i>
----------------	-----------------------

Description

Aggregates bin-level statistics to the gene-level

Usage

```
geneLevelStats(
  se,
  coef = NULL,
  excludeTypes = NULL,
  includeTypes = NULL,
  returnSE = TRUE,
  minDensityRatio = 0.1,
  minWidth = 20,
  excludeGeneAmbiguous = TRUE
)
```

Arguments

<code>se</code>	A ‘RangedSummarizedExperiment’ containing the results of one of the DEU wrappers.
<code>coef</code>	The coefficients tested (if the model included more than one term).
<code>excludeTypes</code>	Vector of bin types to exclude.
<code>includeTypes</code>	Vector of bin types to include (overrides ‘excludeTypes’)
<code>returnSE</code>	Logical; whether to return the updated ‘se’ object (default), or the gene-level table.
<code>minDensityRatio</code>	Minimum ratio of read density (with respect to the gene’s average) for a bin to be included.
<code>minWidth</code>	Minimum bin width to include
<code>excludeGeneAmbiguous</code>	Logical; whether to exclude bins which are ambiguous (i.e. can be from different genes)

Value

If ‘returnSE=TRUE’ (default), returns the ‘se’ object with an updated ‘metadata(se)\$geneLevel’ slot, otherwise returns the gene-level data.frame.

Examples

```
library(SummarizedExperiment)
data(example_bin_se)
se <- diffSpliceWrapper(example_bin_se, ~condition)
se <- geneLevelStats(se, includeTypes="3UTR")
head(metadata(se)$geneLevel)
```

`plotTopGenes`*plotTopGenes*

Description

`plotTopGenes`

Usage

```
plotTopGenes(se, n = 10, FDR = 0.05, diffUTR = FALSE, alpha = 1, ...)
```

Arguments

<code>se</code>	A bin-wise SummarizedExperiment as produced by countFeatures and including bin-level tests (i.e. having been passed through one of the DEU wrappers such as diffSpliceWrapper or DEXSeqWrapper)
<code>n</code>	The maximum number of genes for which to plot labels
<code>FDR</code>	The FDR threshold above which to plot labels
<code>diffUTR</code>	Logical; if FALSE, uses absolute coefficients (appropriate for normal differential exon usage); if TRUE, uses non-absolute (ie changes should be in the same direction across significant bins) and width-weighted scores (i.e. larger bins have more weight) – this is relevant only when testing UTR usage.
<code>alpha</code>	Points transparency
<code>...</code>	Passed to geom_label_repel ; this can for instance be used to increase ‘max.overlaps’ when not all desired gene labels are displayed)

Value

A `ggplot`

Examples

```
data(example_bin_se)
se <- diffSpliceWrapper(example_bin_se, ~condition)
plotTopGenes(se)
```

prepareBins	<i>prepareBins</i>
-------------	--------------------

Description

prepareBins

Usage

```
prepareBins(
  g,
  APA = NULL,
  onlyMainChr = TRUE,
  removeAntisense = TRUE,
  chrStyle = NULL,
  maxUTRbinSize = 15000,
  codingOnly = FALSE,
  genewise = FALSE,
  stranded = FALSE,
  verbose = TRUE
)
```

Arguments

<code>g</code>	A GRanges (or path to RDS file containing a GRanges) or path to a gtf file or EnsDb object containing the gene annotation.
<code>APA</code>	A GRanges (or path to a GRanges in RDS format) or bed file containing the alternative poly-A site database
<code>onlyMainChr</code>	Logical; whether to keep only main chromosomes
<code>removeAntisense</code>	Logical; whether to remove antisense APA sites
<code>chrStyle</code>	Chromosome notation to convert to (default no conversion)
<code>maxUTRbinSize</code>	Max width of new alternative UTR bins
<code>codingOnly</code>	Logical, whether to keep only coding transcripts
<code>genewise</code>	Logical, whether annotation should be flattened genewise
<code>stranded</code>	Logical, whether to perform disjoin in a stranded fashion.
<code>verbose</code>	Logical, whether to print run information

Details

See the vignette for more details.

Value

A ‘GRanges’ object.

Author(s)

Stefan Greber

Examples

```
data(example_gene_annotation)
bins <- prepareBins(example_gene_annotation)
```

rn6_PAS

*Poly-A sites compendium for Rattus Norvegicus (Rno6)***Description**

These are the sites from polyA_DB release 3.2, downloaded from https://exon.apps.wistar.org/PolyA_DB/v3/download/3.2/rat_pas.zip, and lifted over to Rno6.

Value

a 'GRanges' object

simesAggregation

*simesAggregation***Description**

Simes p-value correction and aggregation, adapted from `link[limma]{diffSplice}`

Usage

```
simesAggregation(p.value, geneid)
```

Arguments

p.value	A vector of p-values
geneid	A vector of group labels such as gene identifiers

Value

A named vector of aggregated p-values

Examples

```
p <- runif(50)
genes <- sample(LETTERS,50,replace=TRUE)
simesAggregation(p, genes)
```

Index

addNormalizedAssays, [2](#)

countFeatures, [2](#), [3](#), [4](#), [7](#), [9](#), [11](#)

deuBinPlot, [4](#)

DEUwrappers (diffSpliceDGEWrapper), [6](#)

DEXSeq, [6](#)

DEXSeqWrapper, [4](#), [11](#)

DEXSeqWrapper (diffSpliceDGEWrapper), [6](#)

diffSplice, [5–7](#)

diffSplice2, [5](#), [7](#)

diffSpliceDGE, [6](#)

diffSpliceDGEWrapper, [6](#)

diffSpliceWrapper, [4](#), [11](#)

diffSpliceWrapper
 (diffSpliceDGEWrapper), [6](#)

example_bin_se, [7](#)

example_gene_annotation, [8](#)

geneBinHeatmap, [8](#)

geneLevelStats, [7](#), [9](#)

geom_label_repel, [11](#)

Heatmap, [9](#)

lmFit, [5](#)

plotTopGenes, [11](#)

prepareBins, [12](#)

RangedSummarizedExperiment-class, [3](#)

rn6_PAS, [13](#)

simesAggregation, [13](#)

SingleAnnotation, [9](#)