

Package ‘InteractionSet’

December 10, 2025

Version 1.39.0

Date 2025-07-15

Title Base Classes for Storing Genomic Interaction Data

Depends GenomicRanges, SummarizedExperiment

Imports methods, Matrix, Rcpp, BiocGenerics, S4Vectors (>= 0.27.12),
IRanges, Seqinfo

Suggests testthat, knitr, rmarkdown, BiocStyle

LinkingTo Rcpp

biocViews Infrastructure, DataRepresentation, Software, HiC

Description Provides the GInteractions, InteractionSet and ContactMatrix
objects and associated methods for storing and manipulating genomic
interaction data from Hi-C and ChIA-PET experiments.

License GPL-3

NeedsCompilation yes

SystemRequirements C++11

VignetteBuilder knitr

Collate AllGenerics.R AllClasses.R ContactMatrix-methods.R
GInteractions-methods.R InteractionSet-methods.R
GRanges-methods.R getset.R swapAnchors.R pairs.R conversion.R
linearize.R boundingBox.R distances.R overlaps.R linkOverlaps.R
matching.R updateObject.R

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/InteractionSet>

git_branch devel

git_last_commit 3862179

git_last_commit_date 2025-10-29

Repository Bioconductor 3.23

Date/Publication 2025-12-09

Author Aaron Lun [aut, cre],
Malcolm Perry [aut],
Elizabeth Ing-Simmons [aut]
Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

Contents

boundingBox	2
ContactMatrix accessors	4
ContactMatrix class	7
ContactMatrix distances	10
ContactMatrix overlaps	11
ContactMatrix sorting	12
ContactMatrix subsetting	14
Convert classes	16
GInteractions class	19
GRanges methods	22
Interaction accessors	24
Interaction binding	30
Interaction compare	32
Interaction distances	36
Interaction overlaps	38
Interaction subsetting	41
InteractionSet class	44
Linearize interactions	45
linkOverlaps	46
pairs	49
updateObject	50
Index	51

boundingBox	<i>Get the bounding box</i>
-------------	-----------------------------

Description

Computing a minimum bounding box for groups of pairwise interactions.

Usage

```
## S4 method for signature 'GInteractions'
boundingBox(x, f)

# Note, the same call is used for the InteractionSet method.
```

Arguments

x	A GInteractions or InteractionSet object.
f	A factor or vector of length equal to that of x, indicating the group to which each pairwise interaction belongs.

Details

For any group of pairwise interactions, the minimum bounding box is the smallest rectangle in the interaction space that contains all interactions in the group. Each side of the box has coordinates spanning the most extreme anchor regions on the corresponding chromosome. This is often useful for summarizing clusters of interactions.

Grouping of interactions is specified using f, where interactions in x with the same level of f are considered to be in the same group. If f is not specified, all interactions in x are assumed to be in a single group (named as “1”). An error will be raised if a group spans multiple chromosomes for either the first or second anchor regions.

The function returns a GInteractions object containing the coordinates of the bounding boxes for all groups. Each interaction represents a bounding box for a group, where the anchor regions represent the sides of the box. Entries are named according to the levels of f, in order to specify which bounding box corresponds to which group.

It is recommended to run [swapAnchors](#) prior to computing the bounding box for intra-chromosomal groups. If all anchor1 >= anchor2 or all anchor1 <= anchor2, all interactions will lie on one side of the diagonal of the intra-chromosomal interaction space. This results in the smallest possible minimum bounding box, which will only increase in size if interactions are placed on the other side of the diagonal. Alternatively, users can specify a StrictGInteractions object as an input into x, in which anchor1 <= anchor2 is enforced automatically.

Value

A GInteractions object containing the coordinates of each bounding box.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE)

# Making up a sensible grouping.
gi <- sort(gi)
all.chrs <- as.character(seqnames(regions(gi)))
f <- paste0(all.chrs[anchors(gi, type="first", id=TRUE)], ".",
            all.chrs[anchors(gi, type="second", id=TRUE)])

boundingBox(gi, f)
boundingBox(swapAnchors(gi), f)

# Fails for multiple chromosomes
try(out <- boundingBox(gi))
```

```
in.A <- f=="chrA.chrA"
out <- boundingBox(gi[in.A])
```

ContactMatrix accessors

ContactMatrix accessors

Description

Methods to get and set fields in an ContactMatrix object.

Usage

```
## S4 method for signature 'ContactMatrix'
anchors(x, type="both", id=FALSE)
## S4 method for signature 'ContactMatrix'
anchorIds(x, type="both")
## S4 replacement method for signature 'ContactMatrix'
anchorIds(x, type="both") <- value

## S4 method for signature 'ContactMatrix'
regions(x)
## S4 replacement method for signature 'ContactMatrix'
regions(x) <- value
## S4 replacement method for signature 'ContactMatrix'
replaceRegions(x) <- value
## S4 replacement method for signature 'ContactMatrix'
appendRegions(x) <- value
## S4 method for signature 'ContactMatrix'
reduceRegions(x)

## S4 method for signature 'ContactMatrix'
show(x)
## S4 method for signature 'ContactMatrix'
as.matrix(x)
## S4 replacement method for signature 'ContactMatrix'
as.matrix(x) <- value
## S4 method for signature 'ContactMatrix'
t(x)

## S4 method for signature 'ContactMatrix'
dim(x)
## S4 method for signature 'ContactMatrix'
dimnames(x)
## S4 replacement method for signature 'ContactMatrix'
dimnames(x) <- value
## S4 method for signature 'ContactMatrix'
```

```
length(x)

## S4 method for signature 'ContactMatrix'
seqinfo(x)
## S4 replacement method for signature 'ContactMatrix'
seqinfo(x, new2old = NULL,
        pruning.mode = c("error", "coarse", "fine", "tidy")) <- value
```

Arguments

x	A ContactMatrix object.
type	A string specifying which anchors are to be extracted or replaced.
id	A scalar logical indicating whether indices should be returned. If FALSE, GRanges are returned instead.
value	For anchorIds<-, a list of two integer vectors when type="both". The first and second vectors must have length equal to the number of rows and columns of x, respectively. For type="row" or "column", only one vector needs to be supplied corresponding to either the rows or columns. For regions<-, a GRanges object of length equal to that of regions(x). For newRegions<-, a GRanges object that is a superset of all entries in regions(x) involved in interactions. For appendRegions<-, a GRanges of any length containing additional regions. For as.matrix<-, a matrix-like object of the same dimensions as that in the matrix slot. For dimnames<-, a list of two character vectors corresponding to the row and column names, respectively. These can also be passed separately via rownames<- and colnames<-. For seqinfo<-, a Seqinfo object containing the sequence information.
new2old, pruning.mode	See ?" seqinfo<- " for details.

Details

The return value of anchors varies depending on type and id:

- If id=FALSE, a GRanges object is returned containing the regions specified by the anchor1 or anchor2 slots in x, for type=="row" or "column", respectively.
- If id=FALSE and type="both", a list is returned with two entries row and column, containing regions specified by anchor1 and anchor2 respectively.
- If id=TRUE, the integer vectors in the anchor1 or anchor2 slots of x are returned directly, depending on type. A list of length two is returned for type="both", containing both of these vectors.

Note that anchorIds is equivalent to calling anchors with id=TRUE.

Replacement in anchorIds<- can only be performed using anchor indices. If type="both", a list of two integer vectors is required in value, specifying the indices of the row- and column-wise

interacting regions in `x`. If `type="row"` or `"column"`, an integer vector is required to replace the existing row- or column-wise indices in the `anchor1` or `anchor2` slot, respectively.

For regions, a `GRanges` is returned equal to the regions slot in `x`. For `regions<-`, the `GRanges` in `value` is used to replace the regions slot. Resorting of the replacement `GRanges` is performed automatically, along with re-indexing of the anchors. In addition, the input `GRanges` must be of the same length as the existing object in the regions slot. The `newRegions` replacement method can take variable length `GRanges`, but requires that the replacement contain (at least) all ranges contained in `anchors(x)`. The `appendRegions` replacement method appends extra intervals to the existing regions slot of `x`. The `reduceRegions` method removes unused entries in the regions slot, to save memory – see [reduceRegions, GInteractions-method](#) for more details.

The `show` method will print out various details of the object, such as the dimensions of the matrix slot and the length of the regions slot. The `as.matrix` method will return the value of the matrix slot, containing a matrix-like object of interaction data. Replacement with a matrix-like object of the same dimensions can be performed using the `as.matrix<-` function. The `t` method will transpose the matrix, i.e., switch the rows and columns (and switch the vectors in the `anchor1` and `anchor2` slots).

The `dim` method will return a vector of length 2, containing the dimensions of the matrix slot. The `dimnames` method will return a list of length 2, containing the row and column names of matrix (these can be modified with the `dimnames<-` method). The `length` method will return an integer scalar corresponding to the total number of entries in the matrix slot.

The `seqinfo` method will return the sequence information of the [GRanges](#) in the regions slot. This can be replaced with the `seqinfo<-` method.

As the `ContactMatrix` class inherits from the [Annotated](#) class, additional metadata can be stored in the metadata slot. This can be accessed or modified with `metadata<-`.

Value

For the getters, values in various slots of `x` are returned, while for the setters, the slots of `x` are modified accordingly – see Details.

Author(s)

Aaron Lun

Examples

```
example(ContactMatrix, echo=FALSE) # Generate a nice object.
show(x)

# Various matrix methods:
as.matrix(x)
t(x)

nrow(x)
ncol(x)
length(x)

# Accessing anchor ranges or indices:
anchors(x)
```

```

anchors(x, type="row")
anchors(x, id=TRUE)

anchors(x, id=TRUE, type="row")
anchors(x, id=TRUE, type="column")

# Modifying anchor indices:
nregs <- length(regions(x))
anchorIds(x) <- list(sample(nregs, nrow(x), replace=TRUE),
                     sample(nregs, ncol(x), replace=TRUE))
anchors(x, id=TRUE, type="row")
anchors(x, id=TRUE, type="column")

# Accessing or modifying regions:
regions(x)
regions(x)$score <- runif(length(regions(x)))

new.ranges <- c(regions(x), resize(regions(x), fix="center", width=50))
try(regions(x) <- new.ranges) # Fails
replaceRegions(x) <- new.ranges # Succeeds

length(regions(x))
appendRegions(x) <- GRanges("chrA", IRanges(5:10+1000, 1100+5:10), score=runif(6))
length(regions(x))

reduceRegions(x)

# Setting metadata
metadata(x)$name <- "I am a contact matrix"
metadata(x)

```

ContactMatrix class *ContactMatrix class and constructors*

Description

The ContactMatrix class contains a matrix where rows and columns represent genomic loci. Each entry of the matrix contains information about the interaction between the loci represented by the corresponding row/column, e.g., contact frequencies. Coordinates of the loci are also contained within this class.

Usage

```

## S4 method for signature 'ANY,numeric,numeric,GRanges'
ContactMatrix(matrix, anchor1, anchor2, regions, metadata=list())

## S4 method for signature 'ANY,GRanges,GRanges,GenomicRanges_OR_missing'
ContactMatrix(matrix, anchor1, anchor2, regions, metadata=list())

## S4 method for signature 'missing,missing,missing,GenomicRanges_OR_missing'
ContactMatrix(matrix, anchor1, anchor2, regions, metadata=list())

```

Arguments

matrix	Any matrix-like object containing interaction data.
anchor1, anchor2	Either a pair of numeric vectors containing indices to regions or a pair of GRanges objects. In both cases, anchor1 and anchor2 should have lengths equal to the number of rows and columns in matrix, respectively.
regions	A GRanges object containing the coordinates of the interacting regions. This argument is optional for InteractionSet, ANY, GRanges, GRanges-method.
metadata	A list containing experiment-wide metadata - see ?Annotated for more details.

Details

The ContactMatrix class inherits from the [Annotated](#) class, with several additional slots:

matrix: A matrix or matrix-like object from, e.g., the **Matrix** or **DelayedArray** packages.

anchor1: An integer vector specifying the index of the first interacting region.

anchor2: An integer vector specifying the index of the second interacting region.

regions: A sorted GRanges object containing the coordinates of all interacting regions.

Each entry of anchor1 corresponds to a row in matrix, while each entry of anchor2 corresponds to a column. Each entry of matrix represents an interaction between the corresponding entries in anchor1 and anchor2, i which point to the relevant coordinates in regions for each locus.

ContactMatrix objects can be constructed by specifying numeric vectors as anchor1 and anchor2 in the ContactMatrix function. These vectors will define the regions corresponding to the rows and columns of the matrix. Specifically, each value of the vector acts as an index to specify the relevant coordinates from regions. This means that the range of entries must lie within [1, length(regions)].

Alternatively, ContactMatrix objects can be constructed by directly supplying the GRanges of the interacting loci in ContactMatrix. If regions is not specified, this will be constructed automatically from the two sets of supplied GRanges. If regions is supplied, exact matching will be performed to identify the indices in regions corresponding to the regions in the supplied GRanges. Missing values are not tolerated and will cause an error to be raised.

Both methods will return a ContactMatrix object containing all of the specified information. Sorting of regions is also performed automatically, with re-indexing of all anchor indices to preserve the correct pairings between regions.

Value

For the constructors, a ContactMatrix object is returned.

Choosing between matrix classes

The ContactMatrix class provides support for any matrix-like object that implements dim, rbind, cbind, [, and t methods. The choice of class depends on the type of data and the intended application. Some of the common choices are described in more detail here:

- Base matrices are simple to generate and are most efficient for dense data. This is often sufficient for most use cases where small regions of the interaction space are being examined.
- Sparse matrices from the **Matrix** package are useful for large areas of the interaction space where most entries are zero. This reduces memory usage compared to a dense representation (though conversely, is less efficient for dense data). Note that all numeric values are coerced to double-precision types, which may take up more memory than a direct integer representation. Another issue is how missing values should be interpreted in the sparseMatrix – see [?inflate](#) for more details.
- Packed symmetric matrices from the **Matrix** package provide some memory savings for symmetric regions of the interaction space.
- Delayed or HDF5-backed matrices from the **DelayedArray** and **HDF5Array** packages allow very large matrices to be represented without loading into memory.

Author(s)

Aaron Lun

See Also

[?"ContactMatrix-access"](#), [?"ContactMatrix-subset"](#), [?"ContactMatrix-sort"](#)

Examples

```
set.seed(1000)
N <- 30
all.starts <- sample(1000, N)
all.ends <- all.starts + round(runif(N, 5, 20))
all.regions <- GRanges(rep(c("chrA", "chrB"), c(N-10, 10)),
  IRanges(all.starts, all.ends))

Nr <- 10
Nc <- 20
all.anchor1 <- sample(N, Nr)
all.anchor2 <- sample(N, Nc)
counts <- matrix(rpois(Nr*Nc, lambda=10), Nr, Nc)
x <- ContactMatrix(counts, all.anchor1, all.anchor2, all.regions)

# Equivalent construction:
ContactMatrix(counts, all.regions[all.anchor1],
  all.regions[all.anchor2])
ContactMatrix(counts, all.regions[all.anchor1],
  all.regions[all.anchor2], all.regions)

# Also works directly with Matrix objects.
counts2 <- Matrix::Matrix(counts)
x2 <- ContactMatrix(counts2, all.anchor1, all.anchor2, all.regions)
counts2 <- as(counts2, "dgCMatrix")
x2 <- ContactMatrix(counts2, all.anchor1, all.anchor2, all.regions)
```

ContactMatrix distances

Compute linear distances from ContactMatrix objects

Description

Methods to compute linear distances between pairs of interacting regions in a ContactMatrix object.

Usage

```
## S4 method for signature 'ContactMatrix'
pairedist(x, type="mid")
```

```
## S4 method for signature 'ContactMatrix'
intrachr(x)
```

Arguments

x	A ContactMatrix object.
type	A character string specifying the type of distance to compute. See ?" pairedist, GInteractions-method " for possible values.

Details

pairedist, ContactMatrix-method will return a matrix of integer (or, if type="intra", logical) values. Each entry of this matrix specifies the distance between the interacting loci that are represented by the corresponding row and column. If type="intra", each entry indicates whether the corresponding interaction is intra-chromosomal. Running intrachr(x) is equivalent to pairedist(x, type="intra") for any ContactMatrix object x. See [pairedist, InteractionSet-method](#) for more details on the type of distances that can be computed.

Value

An integer or logical matrix of the same dimensions as x, containing the specified distances.

Author(s)

Aaron Lun

Examples

```
example(ContactMatrix, echo=FALSE)
```

```
pairedist(x)
pairedist(x, type="gap")
pairedist(x, type="span")
pairedist(x, type="diag")
```

```
intrachr(x)
```

ContactMatrix overlaps

Find overlaps between GRanges and a ContactMatrix

Description

Find overlaps for the set of regions representing the rows or columns of a ContactMatrix.

Usage

```
## S4 method for signature 'ContactMatrix,Vector'
overlapsAny(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ...)

## S4 method for signature 'ContactMatrix,GInteractions'
overlapsAny(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ..., use.region="both")

## S4 method for signature 'ContactMatrix,InteractionSet'
overlapsAny(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ..., use.region="both")
```

Arguments

query	A ContactMatrix object.
subject	A GRanges , GRangesList , GInteractions or InteractionSet object.
maxgap, minoverlap, type, ..., ignore.strand	See ?findOverlaps in the GenomicRanges package.
use.region	A string specifying how the interacting regions are to be matched to row/column regions, see Details.

Details

When subject is a [GRanges](#), overlaps are identified between the row regions of query and the regions in subject. This is repeated for the column regions of query. A list of two logical vectors is returned, specifying the rows and columns in query that are overlapped by any region in subject. These vectors can be directly used to subset query. Alternatively, they can be used in `outer` to generate a logical matrix for masking – see Examples.

For all other classes of subject, two-dimensional overlaps are identified. A logical matrix is returned indicating which entries in the [ContactMatrix](#) have overlaps with the specified interactions. For any given entry, an overlap is only considered if the regions for the corresponding row and column both overlap anchor regions in the subject. See [?"findOverlaps,GInteractions,GInteractions-method"](#) for more details.

If `use.region="both"`, overlaps between any row/column region and the first/second interacting region of subject are considered. If `use.region="same"`, only overlaps between row regions and the first interacting regions, or between column regions and the second interacting regions are considered. If `use.region="reverse"`, only overlaps between row regions and the second interacting regions, or between row regions and the first interacting regions are considered.

Value

For `overlapsAny, ContactMatrix, GRanges-method`, a named list of two logical vectors is returned specifying the rows of columns of query overlapped by subject.

For the other `overlapsAny` methods, a logical matrix is returned indicating which entries in query are overlapped by subject.

Author(s)

Aaron Lun

Examples

```
example(ContactMatrix, echo=FALSE)

of.interest <- resize(sample(regions(x), 2), width=1, fix="center")
olap <- overlapsAny(x, of.interest)
olap
x[olap$row,]
x[,olap$column]
x[olap$row,olap$column]

keep <- outer(olap$row, olap$column, "|") # OR mask
temp <- as.matrix(x)
temp[!keep] <- NA

keep <- outer(olap$row, olap$column, "&") # AND mask
temp <- as.matrix(x)
temp[!keep] <- NA

# Two dimensional overlaps.
pairing <- GRangesList(first=regions(x), second=regions(x))
olap <- overlapsAny(x, pairing)
olap
olap <- overlapsAny(sort(x), pairing) # A bit prettier
olap
```

ContactMatrix sorting *ContactMatrix sorting and ordering*

Description

Methods to sort and order `ContactMatrix` objects, based on the anchor indices. Also, methods to remove duplicate rows or columns in each `ContactMatrix`.

Usage

```
## S4 method for signature 'ContactMatrix'
order(..., na.last=TRUE, decreasing=FALSE)
## S4 method for signature 'ContactMatrix'
sort(x, decreasing=FALSE, ...)
## S4 method for signature 'ContactMatrix'
duplicated(x, incomparables=FALSE, fromLast=FALSE, ...)
## S4 method for signature 'ContactMatrix'
unique(x, incomparables=FALSE, fromLast=FALSE, ...)
```

Arguments

...	For sort, one or more ContactMatrix objects with the same dimensions. Otherwise, ignored in all other methods.
x	A ContactMatrix object.
na.last	A logical scalar indicating whether NA values should be ordered last. This should not be relevant as anchor indices should be finite.
decreasing	A logical scalar indicating whether sorting should be performed in decreasing order.
incomparables	A logical scalar, ignored.
fromLast	A logical scalar indicating whether the last entry of a repeated set in x should be considered as a non-duplicate.

Details

Sorting is performed based on the anchor indices of the [ContactMatrix](#) object. Rows are ordered for increasing values of the anchor1 slot, while columns are ordered for increasing values of the anchor2 slot. This equates to ordering by the coordinates directly, as the [GRanges](#) in the regions slot is always sorted. Based on this, `sort,ContactMatrix-method` will return a sorted copy of x with permuted rows/columns in increasing order. This can be set to decreasing order by specifying `decreasing=TRUE`.

`order,ContactMatrix-method` returns a list of 2 integer vectors. The first vector contains the permutation to rearrange the rows of x in increasing order, while the second vector does the same for the columns of x. If multiple objects are supplied to `order`, ordering will be computed using anchor indices from successive objects. In other words, ordering will be performed using anchor indices from the first object; any rows with the same anchor1 or columns with the same anchor2 will be split using the corresponding indices in the second object; and so on.

`duplicated,ContactMatrix-method` returns a list of two logical vectors. The first vector indicates whether rows are duplicated, based on identical values in the anchor1 slot. The second does the same for columns based on the anchor2 slot. For a set of duplicated rows or columns, the first occurrence of that row/column is marked as the non-duplicate if `fromLast=FALSE`, and the last entry otherwise.

`unique,ContactMatrix-method` returns an [ContactMatrix](#) object where all duplicate rows and columns have been removed from x. This is equivalent to subsetting based on the non-duplicate rows and columns defined in `duplicated,ContactMatrix-method`.

Note that sorting and duplicate identification only use the anchor indices. The values of the `matrix` slot are *not* used in distinguishing between rows or columns with the same index.

Value

For sort and unique, a ContactMatrix object is returned with sorted or unique rows/columns, respectively.

For order, a list of two integer vectors is returned containing row/column permutations.

For duplicated, a list of logical vectors is returned specifying which rows/columns are duplicated.

Author(s)

Aaron Lun

Examples

```
example(ContactMatrix, echo=FALSE)

anchors(x)
x2 <- sort(x)
x2
anchors(x2)

# Can also order them.
o <- order(x)
o
stopifnot(all.equal(x[o$row,o$column], x2))

# Checking duplication.
duplicated(x)
duplicated(rbind(x, x))
stopifnot(all.equal(unique(x), unique(rbind(x, x))))
```

ContactMatrix subsetting

ContactMatrix subsetting and combining

Description

Methods to subset or combine ContactMatrix objects.

Usage

```
### Subsetting

## S4 method for signature 'ContactMatrix,ANY,ANY'
x[i, j, ..., drop=TRUE]
## S4 replacement method for signature 'ContactMatrix,ANY,ANY,ContactMatrix'
x[i, j] <- value
## S4 method for signature 'ContactMatrix'
subset(x, i, j)
```

```
### Combining

## S4 method for signature 'ContactMatrix'
cbind(..., deparse.level=1)
## S4 method for signature 'ContactMatrix'
rbind(..., deparse.level=1)
```

Arguments

<code>x</code>	A ContactMatrix object.
<code>i, j</code>	A vector of subscripts, indicating the rows and columns to be subsetting for <code>i</code> and <code>j</code> , respectively.
<code>...</code>	For <code>cbind</code> , <code>rbind</code> and <code>c</code> , ... contains ContactMatrix objects to be combined. Otherwise, this argument is ignored during subsetting.
<code>drop</code>	A logical scalar, ignored by <code>[, ContactMatrix, ANY, ANY-method</code> .
<code>value</code>	A ContactMatrix object with dimensions equal to the length of the two subscripts (or the corresponding dimensions of <code>x</code> , if either subscript is missing.
<code>deparse.level</code>	An integer scalar; see <code>?base:cbind</code> for a description of this argument.

Details

Subsetting of [ContactMatrix](#) objects behaves like that for standard matrices. Rows and columns can be selected and rearranged, with concomitant changes to the `anchor1` and `anchor2` slots. All subsetting operations will return an [ContactMatrix](#) with the specified rows and columns. However, note that the value of regions will not be modified by subsetting.

`cbind` will combines objects with the same rows but different columns. Errors will occur if the row regions are not identical between objects (i.e., must have same values in the slots for regions and `anchor1`). Conversely, `rbind` will combines objects with the same columns but different rows. Again, errors will occur if the columns are not identical (i.e., must have same values in the slots for regions and `anchor2`).

If subsetting anchors are required, see `?interaction-subset` for why subsetting should be done before calling the [anchors](#) method.

Value

A subsetting or combined [ContactMatrix](#) object.

Author(s)

Aaron Lun

Examples

```
example(ContactMatrix, echo=FALSE)

# Subsetting:
x[1:5,]
```

```

x[,10:15]
x[1:5,10:15]

x2 <- x
x2[1:5,] <- x[6:10,]
as.matrix(x2[,1]) <- 20

# Combining
cbind(x, x)
rbind(x, x)

```

Convert classes

Convert between classes

Description

Inflate a `GInteractions` or `InteractionSet` into a `ContactMatrix`, or deflate a `ContactMatrix` to an `InteractionSet`.

Usage

```

## S4 method for signature 'GInteractions'
inflate(x, rows, columns, fill=TRUE, swap=TRUE, sparse=FALSE, ...)

## S4 method for signature 'InteractionSet'
inflate(x, rows, columns, assay=1L, sample=1L, fill, swap=TRUE, sparse=FALSE, ...)

## S4 method for signature 'ContactMatrix'
deflate(x, collapse=TRUE, extract, use.zero, use.na, ...)

```

Arguments

<code>x</code>	A GInteractions or InteractionSet object for inflate, or a ContactMatrix object for deflate.
<code>rows, columns</code>	An integer, logical or character vector, a <code>GRanges</code> object or <code>NULL</code> , indicating the regions of interest to be used as the rows or columns of the <code>ContactMatrix</code> .
<code>assay</code>	A numeric scalar indicating the assay of the <code>InteractionSet</code> object, from which values are extracted to fill the <code>ContactMatrix</code> .
<code>sample</code>	A numeric scalar indicating the sample (i.e., column) of the assay to extract values to fill the <code>ContactMatrix</code> .
<code>fill</code>	A vector (usually logical or numeric) of length equal to <code>nrow(x)</code> , containing values with which to fill the <code>ContactMatrix</code> . If specified, this overrides extraction of assay values for <code>inflate</code> , <code>InteractionSet</code> -method.
<code>swap</code>	A logical scalar indicating whether filling should also be performed after swapping anchor indices.
<code>sparse</code>	A logical scalar indicating whether the inflated matrix should use a <code>sparseMatrix</code> representation.

<code>collapse</code>	A logical scalar indicating whether duplicated interactions should be removed from <code>x</code> prior to deflation.
<code>extract</code>	A logical vector or matrix indicating which entries of <code>x</code> to convert into pairwise interactions.
<code>use.zero, use.na</code>	A logical scalar indicating whether to convert zero or NA entries into pairwise interactions.
<code>...</code>	For <code>inflate</code> , additional arguments to pass to <code>overlapsAny</code> when rows or columns is a <code>GRanges</code> . For <code>deflate</code> , additional arguments to pass to the <code>InteractionSet</code> constructor.

Value

For `inflate`, a `ContactMatrix` is returned.

For `deflate`, an `InteractionSet` object is returned.

Inflating to a ContactMatrix

The `inflate` method will return a `ContactMatrix` where the rows and columns correspond to specified regions of interest in rows and columns. Regions can be specified by supplying an object of various types:

- If it is an integer vector, it is assumed to refer to intervals in the `regions` slot of the input object `x`. Values of the vector need not be sorted or unique, but must lie within `[1, regions(x)]`.
- If it is a logical vector, it will subset to retain intervals in `regions(x)` that are `TRUE`.
- If it is a character vector, it is assumed to contain the names of the reference sequences of interest (i.e., chromosome names).
- If it is a `GRanges` object, `overlapsAny` will be called to identify the overlapping intervals of `regions(x)`.
- If it is `NULL`, all regions in `regions(x)` will be used to construct that dimension of the `ContactMatrix`.

For the `GInteractions` method, values in the matrix are filled based on user-supplied values in `fill`. Each element of `fill` corresponds to an interaction in `x` and is used to set the matrix entry at the matching row/column. Some entries of the matrix will correspond to pairwise interactions that are not present in `x` - these are filled with NA values.

By default, filling is repeated after swapping the anchor indices. This means that the value of the matrix at (1, 2) will be the same as that at (2, 1), i.e., the matrix is symmetric around the diagonal of the interaction space. However, if `swap=FALSE`, filling is performed so that the first and second anchor indices correspond strictly to rows and columns, respectively. This may be preferable if the order of the anchors contains some relevant information. In all cases, if duplicated interactions are present in `x` (and redundant permutations, when `swap=TRUE`), one will be arbitrarily chosen to fill the matrix.

For the `InteractionSet` `inflate` method, entries in the matrix are filled in based on the values in the first sample of the first assay when `fill` is missing. For more complex `x`, values from different assays and samples can be extracted using the `assay` and `sample` arguments. Note that if `fill` is specified, it will override any extraction of values from the assays.

If `sparse=TRUE`, `inflate` will return a `ContactMatrix` containing a `sparseMatrix` in the `matrix` slot. Here, entries without a corresponding interaction in `x` are set to zero, not NA. See below for some considerations when interpreting zeroes and NAs in contact matrices.

The default `fill=TRUE` has the effect of producing a logical sparse matrix in the output `ContactMatrix`, indicating which pairs of regions were present in `x`.

Deflating from a ContactMatrix

The `deflate` method will return an `InteractionSet` where each relevant entry in the `ContactMatrix` is converted into a pairwise interaction. Relevant entries are defined as those that are non-zero, if `use.zero` is `FALSE`; and non-NA, if `use.na` is `FALSE`. If `x` contains a `sparseMatrix` representation, the former is set to `FALSE` while the latter is set to `TRUE`, if either are not specified. For all other matrices, `use.zero=TRUE` and `use.na=FALSE` by default.

If `extract` is specified, this overrides all values of `use.zero` and `use.na`. A typical application would be to deflate a number of `ContactMatrix` objects with the same `extract` matrix. This ensures that the resulting `InteractionSet` objects can be easily combined with `cbind`, as the interactions are guaranteed to be the same. Otherwise, different interactions may be extracted depending on the presence of zero or NA values.

The values of all matrix entries are stored as a one-sample assay, with each value corresponding to its pairwise interaction after conversion. Duplicate interactions are removed by default, along with redundant permutations of the anchor indices. These can be included in the returned object by setting `collapse=FALSE`. This setting will also store the pairs as a `GInteractions` object, rather than using the default `StrictGInteractions` object where duplicates are not stored.

Additional arguments can be used to specify the `colData` and `metadata`, which are stored in the `ContactMatrix` itself.

Interpreting zeroes in a sparse matrix

Storing data as a `sparseMatrix` may be helpful as it is more memory-efficient for sparse areas of the interaction space. However, users should keep in mind that the zero values in the `sparseMatrix` may not represent zeroes in `fill`. The majority of these values are likely to be zero just because there was no corresponding interaction in `x` to set it to a non-zero value.

Whether or not this is a problem depends on the application. For example, if `fill` represents count data and only interactions with non-zero counts are stored in `x`, then setting all other entries to zero is sensible. However, in other cases, it is not appropriate to fill entries corresponding to missing interactions with zero. If `fill` represents, e.g., log-fold changes, then setting missing entries to a value of zero will be misleading. One could simply ignore zeroes altogether, though this will also discard entries that are genuinely zero.

These problems are largely avoided with the default dense matrices, where missing entries are simply set to NA.

Author(s)

Aaron Lun

Examples

```

example(InteractionSet, echo=FALSE)

inflate(iset, 1:10, 1:10)
inflate(iset, 1:10, 1:10, sparse=TRUE)
inflate(iset, 1:10, 1:5+10)
inflate(iset, "chrA", 1:5+10)
inflate(iset, "chrA", "chrB")
inflate(iset, "chrA", GRanges("chrB", IRanges(1, 10)))

y <- inflate(iset, 1:10, 1:10)
iset2 <- deflate(y)
iset2
assay(iset2)

y <- inflate(iset, 1:10, 1:10, swap=FALSE)
iset2 <- deflate(y)
iset2
assay(iset2)

# Testing with different fillings:
y <- inflate(iset, 1:10, 1:10, sample=2)
iset2 <- deflate(y)
assay(iset2)

y <- inflate(iset, 1:10, 1:10, fill=rowSums(assay(iset)))
iset2 <- deflate(y)
assay(iset2)

y2 <- inflate(interactions(iset), 1:10, 1:10, rowSums(assay(iset)))
identical(y, y2) # should be TRUE

# Effect of 'collapse'
y <- inflate(iset, c(8, 1:10), 1:10)
deflate(y)
deflate(y, collapse=FALSE)

```

GInteractions class *GInteractions class and constructors*

Description

The GInteractions class stores pairwise genomic interactions, and is intended for use in data analysis from Hi-C or ChIA-PET experiments. Each row of the GInteractions corresponds to a pairwise interaction between two loci, with indexing to improve computational efficiency.

Usage

```
## S4 method for signature 'numeric,numeric,GRanges'
```

```
GInteractions(anchor1, anchor2, regions, metadata=list(), mode="normal", ...)

## S4 method for signature 'GRanges,GRanges,GenomicRanges_OR_missing'
GInteractions(anchor1, anchor2, regions, metadata=list(), mode="normal", ...)

## S4 method for signature 'missing,missing,GenomicRanges_OR_missing'
GInteractions(anchor1, anchor2, regions, metadata=list(), mode="normal", ...)
```

Arguments

<code>anchor1, anchor2</code>	Either a pair of numeric vectors containing indices to regions, or a pair of <code>GRanges</code> objects specifying the interacting loci. Lengths of both <code>anchor1</code> and <code>anchor2</code> must be equal.
<code>regions</code>	A <code>GRanges</code> object containing the coordinates of the interacting regions. This is only mandatory if <code>anchor1</code> and <code>anchor2</code> are numeric vectors.
<code>metadata</code>	An optional list of arbitrary content describing the overall experiment.
<code>mode</code>	A string indicating what type of <code>GInteractions</code> object should be constructed.
<code>...</code>	Optional metadata columns.

Value

For the constructors, a `GInteractions` (or `StrictGInteractions`, or `ReverseStrictGInteractions`) object is returned.

Description of the class

The `GInteractions` class inherits from the [Vector](#) class and has access to all of its data members and methods, e.g. `metadata` and `elementMetadata`. It also contains several additional slots:

anchor1: An integer vector specifying the index of the first interacting region.

anchor2: An integer vector specifying the index of the second interacting region.

regions: A sorted `GRanges` object containing the coordinates of all interacting regions.

Each interaction is defined by the corresponding entries in the `anchor1` and `anchor2` slots, which point to the relevant coordinates in `regions` for each locus.

The `StrictGInteractions` class inherits from the `GInteractions` class and has the same slots. The only difference is that, for each interaction, `anchor1` must be less than or equal to `anchor2`. This means that the first interacting region has a start position that is "lower" than the second interacting region. This condition is useful for comparing interactions within and between objects, as it ensures that redundant permutations of the same interaction are not being overlooked. However, it is not used by default as there may conceivably be instances where the order of interactions is informative. The `ReverseStrictGInteractions` class has the opposite behaviour, where `anchor1` must be greater than or equal to `anchor2`.

Class construction

GInteractions objects can be constructed by specifying integer vectors to define the pairwise interactions in the GInteractions call. For entry x , the corresponding interaction is defined between `regions[anchor1[x]]` and `regions[anchor2[x]]`. Obviously, coordinates of all of the interacting loci must be specified in the `regions` argument. Any metadata in `regions` will be preserved. Note that `regions` will be resorted in the returned object, so the anchor indices may not be equal to the input `anchor1` and `anchor2`.

Alternatively, GInteractions objects can be constructed by directly supplying the GRanges of the interacting loci to the GInteractions function. If `regions` is not specified, this will be constructed automatically from the two sets of supplied GRanges. If `regions` is supplied, exact matching will be performed to identify the indices in `regions` corresponding to the regions in the supplied anchor GRanges. Missing values are not tolerated and will cause an error to be raised. In both cases, any metadata in the input GRanges will be transferred to the `mcols` of the output GInteractions object.

All constructors will return a GInteractions object containing all of the specified information. Sorting of regions is performed automatically, with re-indexing of all anchor indices to preserve the correct pairings between regions. If `mode="strict"`, a StrictGInteractions object is returned with anchor indices swapped such that `anchor1 <= anchor2` for all interactions. If `mode="reverse"`, a ReverseStrictGInteractions object is returned with anchor indices swapped such that `anchor1 >= anchor2`. If both anchors are missing, the constructor will return an empty GInteractions object.

Author(s)

Aaron Lun, with contributions from Malcolm Perry and Liz Ing-Simmons.

See Also

[?"interaction-access"](#), [?"interaction-subset"](#), [?"interaction-compare"](#)

Examples

```
set.seed(1000)
N <- 30
all.starts <- sample(1000, N)
all.ends <- all.starts + round(runif(N, 5, 20))
all.regions <- GRanges(rep(c("chrA", "chrB"), c(N-10, 10)),
  IRanges(all.starts, all.ends))

Np <- 20
all.anchor1 <- sample(N, Np)
all.anchor2 <- sample(N, Np)
gi <- GInteractions(all.anchor1, all.anchor2, all.regions)

# Equivalent construction:
GInteractions(all.regions[all.anchor1], all.regions[all.anchor2])
GInteractions(all.regions[all.anchor1], all.regions[all.anchor2],
  all.regions)

# Putting in metadata, elementMetadata
temp.gi <- gi
metadata(temp.gi)$name <- "My GI object"
```

```

mcols(temp.gi)$score <- runif(Np)

# Strict construction
sgi <- GInteractions(all.regions[all.anchor1], all.regions[all.anchor2],
  all.regions, mode="strict")
rsgi <- GInteractions(all.regions[all.anchor1], all.regions[all.anchor2],
  all.regions, mode="reverse")

```

GRanges methods

Equivalents of GRanges methods

Description

Methods for GInteractions, InteractionSet and ContactMatrix that operate on the internal GenomicRanges.

Usage

```

## S4 method for signature 'GInteractions'
shift(x, shift=0L, use.names=TRUE)
## S4 method for signature 'InteractionSet'
shift(x, shift=0L, use.names=TRUE)
## S4 method for signature 'ContactMatrix'
shift(x, shift=0L, use.names=TRUE)

## S4 method for signature 'GInteractions'
narrow(x, start=NA, end=NA, width=NA, use.names=TRUE)
## S4 method for signature 'InteractionSet'
narrow(x, start=NA, end=NA, width=NA, use.names=TRUE)
## S4 method for signature 'ContactMatrix'
narrow(x, start=NA, end=NA, width=NA, use.names=TRUE)

## S4 method for signature 'GInteractions'
resize(x, width, fix="start", use.names=TRUE, ...)
## S4 method for signature 'InteractionSet'
resize(x, width, fix="start", use.names=TRUE, ...)
## S4 method for signature 'ContactMatrix'
resize(x, width, fix="start", use.names=TRUE, ...)

## S4 method for signature 'GInteractions'
flank(x, width, start=TRUE, both=FALSE, use.names=TRUE, ignore.strand=FALSE)
## S4 method for signature 'InteractionSet'
flank(x, width, start=TRUE, both=FALSE, use.names=TRUE, ignore.strand=FALSE)
## S4 method for signature 'ContactMatrix'
flank(x, width, start=TRUE, both=FALSE, use.names=TRUE, ignore.strand=FALSE)

## S4 method for signature 'GInteractions'

```

```

trim(x, use.names=FALSE)
## S4 method for signature 'InteractionSet'
trim(x, use.names=FALSE)
## S4 method for signature 'ContactMatrix'
trim(x, use.names=FALSE)

## S4 method for signature 'GInteractions'
width(x)
## S4 method for signature 'InteractionSet'
width(x)
## S4 method for signature 'ContactMatrix'
width(x)

```

Arguments

`x` A [GInteractions](#), [InteractionSet](#) or [ContactMatrix](#) object.

`shift`, `start`, `end`, `width`, `fix`, `both` Further interaction-specific arguments to pass to the relevant GenomicRanges methods, see details.

`use.names`, `ignore.strand`, ... Further overall arguments to pass to the relevant GenomicRanges methods.

Details

The `trim`, `resize`, `narrow` and `shift` methods will apply the GenomicRanges methods with the same name to the anchor regions of `x`. For example, `resize(x, width)` will produce an object that is equivalent to running `resize` on the first and second anchor regions directly. This is *not* the same as running the methods on the `regions` slot of `x`, which is an important distinction when the arguments are vectors.

The interaction-specific arguments can be scalars, vectors or a list of two scalars/vectors. Scalars and vectors will be recycled across the length of the first and second anchor regions. For lists, the first element will be applied to the first anchor regions, and the second element will be applied to the second anchor regions.

After any modifications are applied, resorting may be performed to ensure that the entries in the `regions` slot of the output object are ordered. This means that the order of the ranges in the `regions` slot may change between the input and output object. However, the number and order of the *interactions* will not change.

For `GInteractions` and `InteractionSet` objects, the `width` method will return a list with two integer vectors `first` and `second` with the same length as `x`. These contain the widths of the first or second anchor regions corresponding to each interaction. For `ContactMatrix` objects, the method will return a list with the vectors `row` and `column`, with lengths equal to the number of rows and column respectively.

Value

Depending on the method, an object of the same class as `x`, or information regarding the genomic regions – see Details.

Author(s)

Aaron Lun, based on suggestions from Liz Ing-Simmons.

See Also

[?"trim, GenomicRanges-method"](#), [?"resize, GenomicRanges-method"](#), [?"narrow, GenomicRanges-method"](#),
[?"shift, GenomicRanges-method"](#), [?"flank, GenomicRanges-method"](#), [?"width, GenomicRanges-method"](#)

Examples

```
example(GInteractions, echo=FALSE)

trim(gi)
width(gi)

# Functions are applied along the length of 'gi':
new.sizes <- round(runif(length(gi), 10, 50))
gi2 <- resize(gi, width=new.sizes)
gi2
resize(first(gi), width=new.sizes)
resize(second(gi), width=new.sizes)

# ... not along the length of 'regions(gi)': note the difference!
mod.regions <- suppressWarnings(resize(regions(gi), width=new.sizes))
mod.regions[anchors(gi, type="first", id=TRUE)] # not the same as first(gi2)!
mod.regions[anchors(gi, type="second", id=TRUE)] # not the same second(gi2)!

example(ContactMatrix, echo=FALSE)
trim(x)
width(x)
```

Interaction accessors *Interaction accessors*

Description

Methods to get and set fields in an InteractionSet or GInteractions object.

Usage

```
## S4 method for signature 'GInteractions'
anchors(x, type="both", id=FALSE)
## S4 method for signature 'InteractionSet'
anchors(x, type="both", id=FALSE)

## S4 method for signature 'GInteractions'
anchorIds(x, type="both")
## S4 method for signature 'InteractionSet'
anchorIds(x, type="both")
```

```
## S4 method for signature 'GInteractions'
first(x)
## S4 method for signature 'InteractionSet'
first(x)

## S4 method for signature 'GInteractions'
second(x)
## S4 method for signature 'InteractionSet'
second(x)

## S4 method for signature 'GInteractions'
regions(x)
## S4 method for signature 'InteractionSet'
regions(x)

## S4 method for signature 'GInteractions'
seqinfo(x)
## S4 method for signature 'InteractionSet'
seqinfo(x)

## S4 method for signature 'GInteractions'
show(x)
## S4 method for signature 'InteractionSet'
show(x)

## S4 replacement method for signature 'GInteractions'
anchorIds(x, type="both") <- value
## S4 replacement method for signature 'InteractionSet'
anchorIds(x, type="both") <- value

## S4 replacement method for signature 'GInteractions'
regions(x) <- value
## S4 replacement method for signature 'InteractionSet'
regions(x) <- value

## S4 replacement method for signature 'GInteractions'
seqinfo(x, new2old = NULL,
  pruning.mode = c("error", "coarse", "fine", "tidy")) <- value
## S4 replacement method for signature 'InteractionSet'
seqinfo(x, new2old = NULL,
  pruning.mode = c("error", "coarse", "fine", "tidy")) <- value

## S4 replacement method for signature 'GInteractions'
replaceRegions(x) <- value
## S4 replacement method for signature 'InteractionSet'
replaceRegions(x) <- value
```

```

## S4 replacement method for signature 'GInteractions'
appendRegions(x) <- value
## S4 replacement method for signature 'InteractionSet'
appendRegions(x) <- value

## S4 method for signature 'GInteractions'
reduceRegions(x)
## S4 method for signature 'InteractionSet'
reduceRegions(x)

## S4 method for signature 'GInteractions'
names(x)
## S4 method for signature 'InteractionSet'
names(x)

## S4 replacement method for signature 'GInteractions'
names(x) <- value
## S4 replacement method for signature 'InteractionSet'
names(x) <- value

## S4 replacement method for signature 'StrictGInteractions'
anchors(x, type="both") <- value
## S4 replacement method for signature 'ReverseStrictGInteractions'
anchors(x, type="both") <- value

## S4 method for signature 'GInteractions'
length(x)
## S4 method for signature 'GInteractions'
as.data.frame(x, row.names=NULL, optional=FALSE, ...)
## S4 method for signature 'GInteractions'
x$name
## S4 replacement method for signature 'GInteractions'
x$name <- value

## S4 method for signature 'InteractionSet'
interactions(x)
## S4 replacement method for signature 'InteractionSet'
interactions(x) <- value

## S4 method for signature 'InteractionSet'
mcols(x, use.names=FALSE)
## S4 replacement method for signature 'InteractionSet'
mcols(x) <- value

```

Arguments

x	An InteractionSet or GInteractions object.
type	a string specifying which anchors are to be extracted or replaced.

<code>id</code>	a scalar logical indicating whether indices or GRanges should be returned. If FALSE, GRanges are returned instead.
<code>new2old, pruning.mode</code>	Additional arguments to pass to seqinfo .
<code>name</code>	a string indicating the field of <code>mcols</code> to be accessed or modified for a <code>GInteractions</code> object.
<code>value</code>	For <code>anchorIds<-</code> and <code>type="first"</code> or <code>"second"</code> , an integer vector of length equal to the number of rows in <code>x</code> . For <code>type="both"</code> , a list of two such vectors must be supplied. For <code>regions<-</code> , a <code>GRanges</code> object of length equal to that of <code>regions(x)</code> . For <code>replaceRegions<-</code> , a <code>GRanges</code> object that is a superset of all entries in <code>regions(x)</code> involved in interactions. For <code>appendRegions<-</code> , a <code>GRanges</code> of any length containing additional regions. For <code>seqinfo<-</code> , a <code>SeqInfo</code> object containing chromosome length data for all regions. For <code>interactions<-</code> , a <code>GInteractions</code> object of length equal to that of <code>interactions(x)</code> . For <code>mcols<-</code> , a <code>DataFrame</code> with number of rows equal to the length of <code>x</code> . For <code>names<-</code> , a character vector of length equal to that of <code>x</code> .
<code>row.names, optional, ...</code>	Additional arguments, see ?as.data.frame for more details.
<code>use.names</code>	A logical scalar, see ?mcols for more details.

Value

For the getters, values in various slots of `x` are returned, while for the setters, the slots of `x` are modified accordingly – see Details.

Anchor manipulations for GInteractions

The return value of anchors varies depending on `type` and `id`:

- If `id=FALSE`, a `GRanges` object is returned containing the regions specified by the `anchor1` or `anchor2` slots in `x`, for `type=="first"` or `"second"`, respectively. The `first` and `second` methods are synonyms for `anchors` in these respective cases.
- If `id=FALSE` and `type="both"`, a list is returned with two entries `first` and `second`, containing regions specified by `anchor1` and `anchor2` respectively.
- If `id=TRUE` and `type="both"`, a list is returned containing the two integer vectors in the `anchor1` or `anchor2` slots of `x`. Otherwise, each vector is returned corresponding to the requested value of `type`.

Note that `anchorIds` is the same as calling `anchors` with `id=TRUE`.

Replacement in `anchorIds<-` requires anchor indices rather than a `GRanges` object. If `type="both"`, a list of two integer vectors is required in `value`, specifying the indices of the interacting regions in `regions(x)`. If `type="first"` or `"second"`, an integer vector is required to replace the existing values in the `anchor1` or `anchor2` slot, respectively. If the object is a `StrictGInteractions`, indices are automatically swapped so that `anchor1 >= anchor2` for each interaction. The opposite applies if the object is a `ReverseStrictGInteractions`.

Region manipulations for GInteractions

For regions, a GRanges is returned equal to the regions slot in `x`. For `regions<-`, the GRanges in value is used to replace the regions slot. Resorting of the replacement GRanges is performed automatically, along with re-indexing of the anchors. In addition, the replacement must be of the same length as the existing object in the regions slot.

The `replaceRegions` replacement method can take variable length GRanges, but requires that the replacement contain (at least) all ranges contained in `anchors(x)`. The `appendRegions` replacement method appends extra intervals to the existing regions slot of `x`. This is more efficient than calling `replaceRegions` on a concatenated object with `regions(x)` and the extra intervals.

The `reduceRegions` method will return a GInteractions object where the regions slot is reduced to only those entries used in `anchors(x)`. This may save some memory in each object by removing unused regions. However, this is not recommended for large workflows with many GInteractions objects. R uses a copy-on-write memory management scheme, so only one copy of the GRanges in regions should be stored so long as it is not modified in different objects.

Other methods for GInteractions

For access and setting of all other slots, see [Vector](#) for details on the appropriate methods. This includes `mcols` or `metadata`, to store interactions-specific or experiment-wide metadata, respectively. The `length` method will return the number of interactions stored in `x`.

The `show` method will print out the class, the number of pairwise interactions, and the total number of regions in the GInteractions object. The number and names of the various metadata fields will also be printed. The `as.data.frame` method will return a data.frame object containing the coordinates for the two anchor regions as well as any element-wise metadata.

The `seqinfo` method will return the sequence information of the [GRanges](#) in the regions slot. This can be replaced with the `seqinfo<-` method.

Details for InteractionSet

Almost all InteractionSet methods operate by calling the equivalent method for the GInteractions object, and returning the resulting value. The only exception is `interactions`, which returns the GInteractions object in the interactions slot of the InteractionSet object. This slot can also be set by supplying a valid GInteractions object in `interactions<-`.

The `show` method will print information equivalent to that done for a SummarizedExperiment object. An additional line is added indicating the number of regions in the regions slot of the object.

For access and setting of all other slots, see the documentation for the [SummarizedExperiment](#) class. This includes `assays`, `colData`, `mcols` or `metadata`, which can all be applied to InteractionSet objects.

Handling different metadata

Note that there are several options for metadata - experiment-wide metadata, which goes into `metadata(x)<-`; region-specific metadata (e.g., adjacent genes, promoter/enhancer identity, GC content), which goes into `mcols(regions(x))<-`; and interaction-specific metadata (e.g., interaction distance, interaction type), which goes directly into `mcols(x)<-`. This is applicable to both GInteractions and InteractionSet objects. In addition, library-specific data (e.g., library size) should be placed into `colData(x)<-` for InteractionSet objects.

Users should take care with the differences in the `$` and `$<-` operators between these two classes. For `GInteractions` objects, this will access or modify fields in the `mcols` slot, i.e., for interaction-specific metadata. For `InteractionSet` objects, this will access or modify fields in the `colData` slot, i.e., for library-specific data. The difference in behaviour is due to the concept of libraries in the `InteractionSet`, which is lacking in the `GInteractions` class.

For `InteractionSet` objects, the `mcols` getter and setter functions operate on the `GInteractions` object stored in `interactions` slot, rather than accessing the `elementMetadata` slot of the `SummarizedExperiment` base class. This makes no difference for practical usage in the vast majority of cases, except that any metadata stored in this manner is carried over when the `GInteractions` object is extracted with `interactions(x)`. Similarly, the `names` getter and setter will operate the names of the internal `GInteractions` object. However, the `metadata` getter and setter will operate on the `SummarizedExperiment` base class, *not* on the internal `GInteractions` object.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE) # Generate a nice object.
show(gi)

# Accessing anchor ranges or indices:
anchors(gi)
anchors(gi, type="first")
anchors(gi, id=TRUE)

anchors(gi, id=TRUE, type="first")
anchors(gi, id=TRUE, type="second")

# Modifying anchor indices:
nregs <- length(regions(gi))
mod <- list(sample(nregs, length(gi), replace=TRUE),
            sample(nregs, length(gi), replace=TRUE))
anchorIds(gi) <- mod
anchors(gi, id=TRUE, type="first")
anchors(gi, id=TRUE, type="second")

anchorIds(gi, type="both") <- mod
anchorIds(gi, type="first") <- mod[[1]]
anchorIds(gi, type="first") <- mod[[2]]

# Accessing or modifying regions:
regions(gi)
reduceRegions(gi)
regions(gi)$score <- runif(length(regions(gi)))

new.ranges <- c(regions(gi), resize(regions(gi), fix="center", width=50))
try(regions(gi) <- new.ranges) # Fails
replaceRegions(gi) <- new.ranges # Succeeds
```

```

length(regions(gi))
appendRegions(gi) <- GRanges("chrA", IRanges(5:10+1000, 1100+5:10), score=runif(6))
length(regions(gi))

seqinfo(gi)
seqinfo(gi) <- Seqinfo(seqnames=c("chrA", "chrB"), seqlengths=c(1000, 2000))

# Accessing or modifying metadata.
gi$score <- runif(length(gi))
mcols(gi)
as.data.frame(gi)

#####
# Same can be done for an InteractionSet object:

example(InteractionSet, echo=FALSE)

anchors(iset)
regions(iset)
reduceRegions(iset)
regions(iset)$score <- regions(gi)$score
replaceRegions(iset) <- new.ranges

seqinfo(iset)
seqinfo(iset) <- Seqinfo(seqnames=c("chrA", "chrB"), seqlengths=c(1000, 2000))

# Standard SE methods also available:
colData(iset)
metadata(iset)
mcols(iset)

# Note the differences in metadata storage:
metadata(iset)$name <- "metadata for SE0"
metadata(interactions(iset))$name <- "metadata for GI"

iset$lib.size <- runif(ncol(iset))*1e6
colData(iset)
mcols(iset) # untouched by "$" operator

mcols(iset)$whee <- runif(nrow(iset))
mcols(iset)
mcols(interactions(iset)) # preserved

names(iset) <- paste0("X", seq_along(iset))
names(iset)
names(interactions(iset))

```

Description

Methods to combine InteractionSet or GInteractions objects.

Usage

```
## S4 method for signature 'GInteractions'
c(x, ..., recursive=FALSE)

## S4 method for signature 'InteractionSet'
rbind(..., deparse.level=1)
## S4 method for signature 'InteractionSet'
cbind(..., deparse.level=1)
```

Arguments

<code>x</code>	A GInteractions or InteractionSet object.
<code>...</code>	For <code>rbind</code> and <code>c</code> , <code>...</code> contains <code>GInteractions</code> or <code>InteractionSet</code> objects to be combined row-wise. All objects must be of the same class. For <code>c</code> , any objects are additional to that already specified in <code>x</code> . For <code>cbind</code> , <code>...</code> contains <code>InteractionSet</code> objects to be combined column-wise.
<code>deparse.level</code>	An integer scalar; see <code>?base::cbind</code> for a description of this argument.
<code>recursive</code>	An integer scalar, ignored.

Value

A combined object of the same class as `x`.

Details for GInteractions

`c` will concatenate `GInteractions` objects. It will check whether the regions slot of all supplied objects are the same, in which case the regions and anchor indices are used directly. Otherwise, the regions slot is set to a new `GRanges` object consisting of the (sorted) union of all regions across the input objects. Anchor indices in each object are refactored appropriately to refer to the relevant entries in the new `GRanges`.

Note that the column names in `mcols` must be identical across all supplied objects. The column names of `mcols` for the regions slot must also be identical across objects. If `GInteractions` objects of different strictness (i.e., `StrictGInteractions` and `ReverseGInteractions`) are concatenated, the returned object will be of the same class as the first supplied object.

Details for InteractionSet

`cbind` will combine objects with the same interactions but different samples. Errors will occur if the interactions are not identical between objects (i.e., must have same values in the interactions slots). Additional restrictions apply on the column and assay names - see [cbind, SummarizedExperiment-method](#) for details.

`rbind` will combine objects with the same samples but different interactions. In this case, the interactions need not be identical, and will be concatenated using the methods described above for `GInteractions` objects. Again, additional restrictions apply - see [rbind, SummarizedExperiment-method](#) for details.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE)
c(gi, gi)

new.gi <- gi
regions(new.gi) <- resize(regions(new.gi), width=20, fix="start")
c(gi, new.gi)

#####
# Same can be done for an InteractionSet object:

example(InteractionSet, echo=FALSE)
cbind(iset, iset)
rbind(iset, iset)

new.iset <- iset
regions(new.iset) <- resize(regions(new.iset), width=20, fix="start")
rbind(iset, new.iset)
```

Interaction compare *Interaction comparisons*

Description

Methods to order, compare and de-duplicate `GInteractions` or `InteractionSet` objects, based on the anchor indices.

Usage

```
## S4 method for signature 'GInteractions'
order(..., na.last=TRUE, decreasing=FALSE)

## S4 method for signature 'GInteractions'
sort(x, decreasing=FALSE, ...)

## S4 method for signature 'GInteractions'
duplicated(x, incomparables=FALSE, fromLast=FALSE, ...)

## S4 method for signature 'GInteractions'
```

```

unique(x, incomparables=FALSE, fromLast=FALSE, ...)

## S4 method for signature 'GInteractions'
swapAnchors(x, mode=c("order", "reverse", "all"))

## Each of the above methods has an identical equivalent for
## InteractionSet objects (not shown for brevity).

## S4 method for signature 'GInteractions,GInteractions'
match(x, table, nomatch=NA_integer_, incomparables=NULL, ...)

## S4 method for signature 'GInteractions,InteractionSet'
match(x, table, nomatch=NA_integer_, incomparables=NULL, ...)

## S4 method for signature 'InteractionSet,GInteractions'
match(x, table, nomatch=NA_integer_, incomparables=NULL, ...)

## S4 method for signature 'InteractionSet,InteractionSet'
match(x, table, nomatch=NA_integer_, incomparables=NULL, ...)

## S4 method for signature 'GInteractions,GInteractions'
pcompare(x, y)

```

Arguments

...	For order, one or more InteractionSet or GInteractions objects with the same number of rows. Otherwise, ignored in all other methods.
x	An InteractionSet or GInteractions object. For pcompare, a GInteractions object only.
na.last	A logical scalar indicating whether NA values should be ordered last. This should not be relevant as anchor indices should be finite.
decreasing	A logical scalar indicating whether rows should be sorted in decreasing order.
incomparables	A logical scalar. See ?match for a description of this in match. Otherwise, it is ignored.
fromLast	A logical scalar indicating whether the last entry of a repeated set in x should be considered as a non-duplicate.
mode	A string indicating what type of swapping should be performed in swapAnchors.
table	A GInteractions or InteractionSet object.
nomatch	An integer scalar indicating the value to use for unmatched entries.
y	A GInteractions object, of the same length as x.

Value

For sort and unique, a GInteractions or InteractionSet object is returned, depending on the class of x.

For order and duplicated, an integer vector of permutations or a logical vector of duplicate specifications is returned, respectively.

Sorting and ordering

Sorting is performed based on the anchor indices of the `GInteraction` object. Rows are ordered for increasing values of the `anchor1` slot - if these are equal, ordering is performed with values of the `anchor2` slot. This equates to ordering by the coordinates directly, as the `GRanges` in the `regions` slot is always sorted. Based on this, `sort` will return a sorted copy of `x` with permuted rows in increasing order.

The `order` method returns an integer vector indicating the permutation to rearrange `x` in increasing order. If multiple objects are supplied to `order`, ordering will be computed using anchor indices from successive objects. For example, ordering is first performed using anchor indices from the first object; any rows with the same `anchor1` and `anchor2` will be split using the second object; and so on.

For both of these methods, the sorting can be reversed by setting `decreasing=TRUE`. This will sort or order for decreasing values of `anchor1` and `anchor2`, rather than for increasing values.

Removing duplicates

The `duplicated` method returns a logical vector indicating whether the rows of `x` are duplicated. Duplicated rows are identified on the basis of identical entries in the `anchor1` and `anchor2` slots. Values in other slots (e.g., in `mcols`) are ignored. For a set of duplicated rows, the first occurrence in `x` is marked as the non-duplicate if `fromLast=FALSE`, and the last entry otherwise.

`unique` returns a `GInteractions` object where all duplicate rows have been removed from `x`. This is equivalent to `x[!duplicated(x),]`, with any additional arguments passed to `duplicated` as specified.

Matching and comparing

The `match` function will return an integer vector of length equal to that of `x`. Each entry of the vector corresponds to an interaction in `x` and contains the index of the first interaction table with the same anchor regions. Interactions in `x` without any matches are assigned NA values by default. If the `regions` slot is not the same between `x` and `table`, `match` will call [findOverlaps](#) to identify exact two-dimensional overlaps.

The `pcompare` function will return an integer vector of length equal to `x` and `y`. This performs parallel comparisons between corresponding entries in two `GInteractions` objects, based on the values of the anchor indices (`anchor1` first, and then `anchor2` if `anchor1` is tied). Negative, zero and positive values indicate that the corresponding interaction in `x` is “lesser”, equal or “greater” than the corresponding interaction in `y`. If the `regions` slot is not the same between the two objects, the union of regions for both objects will be used to obtain comparable indices.

Swapping anchors

For `GInteractions` objects, `swapAnchors` returns a `GInteractions` object where `anchor1` and `anchor2` values are swapped. If `mode="order"`, this is done so that all values in the `anchor2` slot are not less than values in `anchor1` in the returned object. If `mode="reverse"`, all values in `anchor1` are not less than all values in `anchor2`. If `mode="all"`, the anchor indices in `x` are directly swapped without consideration of ordering.

It is recommended to apply this method before running methods like `order` or `duplicated`. This ensures that redundant permutations are coerced into the same format for a valid comparison. In

many applications, permutations of pairwise interactions are not of interest, i.e., an interaction between regions 1 and 2 is the same as that between 2 and 1. Application of `swapAnchors` with `mode="order"` ensures that all indices are arranged in a comparable manner. Alternatively, users can use a `(Reverse)StrictGInteractions` object which enforces a consistent arrangement of indices across interactions.

Methods for InteractionSet objects

For all `InteractionSet` methods, the corresponding method is called on the `GInteractions` object in the `interactions` slot of the `InteractionSet` object. Return values for each `InteractionSet` method is the same as those for the corresponding `GInteractions` method - except for `sort` and `unique`, which return a row-permuted or row-subsetted `InteractionSet`, respectively, instead of a `GInteractions` object; and `swapAnchors`, which returns an `InteractionSet` object where the internal `GInteractions` has its anchor indices swapped around.

Note that no additional information from the `InteractionSet` (beyond that in `interactions`) is used for sorting or duplicate marking, i.e., the assay or metadata values for each interaction are *not* used in distinguishing rows with the same interaction. For this reason, the `pcompare` method is not implemented for `InteractionSet` objects. It makes little sense to do a parallel comparison in an `InteractionSet` without examining the data.

Author(s)

Aaron Lun

See Also

[match](#), [pcompare](#)

Examples

```
example(GInteractions, echo=FALSE)

anchors(gi, id=TRUE)
anchors(swapAnchors(gi, mode="all"), id=TRUE)
gi <- swapAnchors(gi)

anchors(gi)
gi2 <- sort(gi)
gi2
anchors(gi2)

# Can also order them.
o <- order(gi)
o
stopifnot(all.equal(gi[o], gi2))

# Checking duplication.
summary(duplicated(gi))
summary(duplicated(c(gi, gi)))
stopifnot(all.equal(unique(gi), unique(c(gi, gi))))
```

```

# Matching and comparing.
another.gi <- gi[sample(length(gi))]
match(gi, another.gi)
match(gi, another.gi[1:5])

pcompare(gi, another.gi)

#####
# Same can be done for an InteractionSet object:

example(InteractionSet, echo=FALSE)
iset <- swapAnchors(iset)

anchors(iset)
anchors(sort(iset))
order(iset)
summary(duplicated(iset))
unique(iset)

```

Interaction distances *Get the linear distance for each interaction*

Description

Compute the distance between interacting regions on the linear genome, for each pairwise interaction contained in a `GInteractions` or `InteractionSet` object.

Usage

```

## S4 method for signature 'GInteractions'
pairdist(x, type="mid")
## S4 method for signature 'InteractionSet'
pairdist(x, type="mid")

## S4 method for signature 'GInteractions'
intrachr(x)
## S4 method for signature 'InteractionSet'
intrachr(x)

```

Arguments

<code>x</code>	A GInteractions or InteractionSet object.
<code>type</code>	A character string specifying the type of distance to compute. Can take values of "mid", "gap", "span", "diag" or "intra".

Details

For each interaction in `x`, the `pairdist` method computes the distance between the two interacting regions. An integer vector is returned, with values computed according to the specified value of `type`:

`"mid"`: The distance between the midpoints of the two regions (rounded down to the nearest integer) is returned.

`"gap"`: The length of the gap between the closest points of the two regions is computed - negative lengths are returned for overlapping regions, indicating the length of the overlap.

`"span"`: The distance between the furthestmost points of the two regions is computed.

`"diag"`: The difference between the anchor indices is returned. This corresponds to a diagonal on the interaction space when bins are used in the `regions` slot of `x`.

Interchromosomal interactions are marked with NA. Alternatively, if `type="intra"`, a logical vector is returned indicating whether the interaction occurs between two regions on the same chromosome. `intrachr(x)` is an alias for `pairdist(x, type="intra")`.

The return values of the assorted methods are the same for both `GInteractions` and `InteractionSet` objects. Methods for the latter operate on the `GInteractions` object in the `interactions` slot.

Value

An integer or logical vector of distances.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE)
```

```
pairdist(gi)
pairdist(gi, type="gap")
pairdist(gi, type="span")
pairdist(gi, type="diag")
intrachr(gi)
```

```
example(InteractionSet, echo=FALSE)
```

```
pairdist(iset)
pairdist(iset, type="gap")
pairdist(iset, type="span")
pairdist(iset, type="diag")
intrachr(iset)
```

Interaction overlaps *Find overlaps between interactions in one or two dimensions*

Description

Find overlaps between interactions and linear intervals, between interactions and pairs of intervals, and between interactions and other interactions in a `GInteractions` or `InteractionSet` object.

Usage

```
## S4 method for signature 'GInteractions,GInteractions'
findOverlaps(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  select=c("all", "first", "last", "arbitrary"),
  ignore.strand=TRUE, ..., use.region="both")

## S4 method for signature 'GInteractions,GInteractions'
overlapsAny(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ..., use.region="both")

## S4 method for signature 'GInteractions,GInteractions'
countOverlaps(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ..., use.region="both")

## S4 method for signature 'GInteractions,GInteractions'
subsetByOverlaps(query, subject, maxgap=-1L, minoverlap=0L,
  type=c("any", "start", "end", "within", "equal"),
  ignore.strand=TRUE, ..., use.region="both")
```

Arguments

<code>query, subject</code>	A Vector , GInteractions or InteractionSet object, depending on the specified method. At least one of these must be a <code>GInteractions</code> or <code>InteractionSet</code> object. Also, <code>subject</code> can be missing if <code>query</code> is a <code>GInteractions</code> or <code>InteractionSet</code> object.
<code>maxgap, minoverlap, type, select</code>	See ?findOverlaps in the GenomicRanges package.
<code>ignore.strand</code>	A logical scalar indicating whether strand information in <code>query</code> or <code>subject</code> should be ignored. Note that the default setting here is different to that in findOverlaps as genomic interactions are usually unstranded.
<code>...</code>	Further arguments to pass to findOverlaps . This includes <code>drop.self</code> and <code>drop.redundant</code> when <code>subject</code> is missing.
<code>use.region</code>	A string specifying the regions to be used to identify overlaps.

Value

For `findOverlaps`, a `Hits` object is returned if `select="all"`, and an integer vector of subject indices otherwise.

For `countOverlaps` and `overlapsAny`, an integer or logical vector is returned, respectively.

For `subsetByOverlaps`, a subsetted object of the same class as query is returned.

Overview of overlaps for GInteractions

All methods can be applied using a `GInteractions` as either the query or subject, and a `Vector` as the other argument. In such cases, the `Vector` is assumed to represent some region on the linear genome (e.g., `GRanges`) or set of such regions (`GRangesList`). An overlap will be defined between the interval and an `GInteractions` interaction if either anchor region of the latter overlaps the former. This is considered to be a one-dimensional overlap, i.e., on the linear genome.

The same methods can be applied using two `GInteractions` objects as the query and subject. In such cases, a two-dimensional overlap will be computed between the anchor regions of the two objects. An overlap is defined if each anchor region of the first object overlaps at least one anchor region of the second object, and each anchor region of the second object overlaps at least one anchor region of the first object, i.e., there are overlapping areas in the two-dimensional interaction space. If subject is missing, overlaps will be computed between interactions in query.

Description of overlap methods

When `select="all"`, `findOverlaps` returns a `Hits` object containing overlapping pairs of queries and subjects (or more specifically, their indices in the supplied objects - see `?findOverlaps` for more details). For other values of `select`, an integer vector is returned with one entry for each element of query, which specifies the index of the chosen (first, last or arbitrary) overlapping feature in subject for that query. Queries with no overlaps at all are assigned NA values.

For the other methods, `countOverlaps` returns an integer vector indicating the number of elements in subject that were overlapped by each element in query. `overlapsAny` returns a logical vector indicating which elements in query were overlapped by at least one element in subject. `subsetByOverlaps` returns a subsetted query containing only those elements overlapped by at least one element in subject.

Choice of regions to define overlaps

For one-dimensional overlaps, `use.region="both"` by default such that overlaps with either anchor region are considered. If `use.region="first"`, overlaps are only considered between the interval and the first anchor region. Similarly, if `use.region="second"`, only the second anchor region is used.

Equivalent choices are available for two-dimensional overlaps:

- By default, `use.region="both"` such that the order of first/second anchor regions in the query and subject is ignored. This means that the first anchor region in the query can overlap both the first *or* second anchor regions in the subject. Similarly, the second anchor region in the query can overlap both the first *or* second anchor regions in the subject.
- If `use.region="same"`, overlaps are only considered between the first anchor regions for the query and the subject, or between the second anchor regions for the query and subject.

Overlaps between the first query region and the second subject region, or the second query region and the first subject region, are ignored.

- If `use.region="reverse"`, overlaps are only considered between the first anchor regions for the query and the second anchor regions for the subject, and vice versa. Overlaps between the first query/subject regions or between the second query/subject regions are ignored.

The latter two options tend only to be useful if the order of first/second regions is informative.

Details for InteractionSet

Each method can also be applied with `InteractionSet` objects, and the behaviour is largely the same as that described for `GInteractions` objects. For a given `InteractionSet` object `x`, the corresponding method is called on the `GInteractions` object in the `interactions` slot of `x`. The return value is identical to that from calling the method on `interactions(x)`, except for `subsetByOverlaps` for `InteractionSet` queries (which returns a subsetted `InteractionSet` object, containing only those rows/interactions overlapping the subject).

Author(s)

Aaron Lun

See Also

[findOverlaps](#), [linkOverlaps](#)

Examples

```
example(GInteractions, echo=FALSE)

# Making a larger object, for more overlaps.
Np <- 100
N <- length(regions(gi))
all.anchor1 <- sample(N, Np, replace=TRUE)
all.anchor2 <- sample(N, Np, replace=TRUE)
gi <- GInteractions(all.anchor1, all.anchor2, regions(gi))

# GRanges overlaps:
of.interest <- resize(sample(regions(gi), 2), width=1, fix="center")
findOverlaps(of.interest, gi)
findOverlaps(gi, of.interest)
findOverlaps(gi, of.interest, select="first")
overlapsAny(gi, of.interest)
overlapsAny(of.interest, gi)
countOverlaps(gi, of.interest)
countOverlaps(of.interest, gi)
subsetByOverlaps(gi, of.interest)
subsetByOverlaps(of.interest, gi)

# GRangesList overlaps:
pairing <- GRangesList(first=regions(gi)[1:3], second=regions(gi)[4:6],
  third=regions(gi)[7:10], fourth=regions(gi)[15:17])
```

```

findOverlaps(pairing, gi)
findOverlaps(gi, pairing)
findOverlaps(gi, pairing, select="last")
overlapsAny(gi, pairing)
overlapsAny(pairing, gi)
countOverlaps(gi, pairing)
countOverlaps(pairing, gi)
subsetByOverlaps(gi, pairing)
subsetByOverlaps(pairing, gi)

# GInteractions overlaps (split into two):
first.half <- gi[1:(Np/2)]
second.half <- gi[Np/2+1:(Np/2)]
findOverlaps(first.half, second.half)
findOverlaps(first.half, second.half, select="arbitrary")
overlapsAny(first.half, second.half)
countOverlaps(first.half, second.half)
subsetByOverlaps(first.half, second.half)

findOverlaps(gi)
countOverlaps(gi)
overlapsAny(gi) # trivial result

#####
# Same can be done for an InteractionSet object:

Nlibs <- 4
counts <- matrix(rpois(Nlibs*Np, lambda=10), ncol=Nlibs)
colnames(counts) <- seq_len(Nlibs)
iset <- InteractionSet(counts, gi)

findOverlaps(of.interest, iset)
findOverlaps(iset, pairing)
findOverlaps(iset[1:(Np/2),], iset[Np/2+1:(Np/2),])

# Obviously returns InteractionSet objects instead
subsetByOverlaps(of.interest, iset)
subsetByOverlaps(iset, pairing)
subsetByOverlaps(iset[1:(Np/2),], iset[Np/2+1:(Np/2),])

# Self-overlaps
findOverlaps(iset)
countOverlaps(iset)
overlapsAny(iset) # trivial result

```

Description

Methods to subset or combine InteractionSet or GInteractions objects.

Usage

```
## S4 method for signature 'InteractionSet,ANY,ANY'
x[i, j, ..., drop=TRUE]

## S4 replacement method for signature 'InteractionSet,ANY,ANY,InteractionSet'
x[i, j] <- value

## S4 method for signature 'InteractionSet'
subset(x, i, j)

## S4 replacement method for signature 'GInteractions,ANY,GInteractions'
x[i] <- value
```

Arguments

<code>x</code>	A GInteractions or InteractionSet object.
<code>i, j</code>	A vector of logical or integer subscripts. For InteractionSet objects, these indicate the rows and columns to be subsetting for <code>i</code> and <code>j</code> , respectively. Rows correspond to pairwise interactions while columns correspond to samples. For GInteractions objects, <code>i</code> indicates the genomic interactions to be retained. <code>j</code> is ignored as there is no concept of samples in this class.
<code>..., drop</code>	Additional arguments that are ignored.
<code>value</code>	A GInteractions or InteractionSet object with length or number of rows equal to length of <code>i</code> (or that of <code>x</code> , if <code>i</code> is not specified). For InteractionSet objects, the number of columns must be equal to the length of <code>j</code> (or number of columns in <code>x</code> , if <code>j</code> is not specified).

Value

A subsetting object of the same class as `x`.

Details for GInteractions

Subsetting operations are not explicitly listed above as they inherit from the [Vector](#) class. They will return a GInteractions object containing the specified interactions. Values of the `anchor1` and `anchor2` slots will be appropriately subsetting in the returned object, along with any metadata in `mcols`. However, note that the value of `regions` will not be modified by subsetting.

For short index vectors, subsetting a GInteractions object prior to calling [anchors](#) may be much faster than the reverse procedure. This is because the [anchors](#) getter will construct a `GRanges(List)` containing the genomic loci for all pairwise interactions. Subsetting beforehand ensures that only loci for the desired interactions are included. This avoids constructing the entire object just to subset it later.

Subset assignment will check if the regions are identical between `x` and `value`. If not, the regions slot in the output object will be set to a sorted union of all regions from `x` and `value`. Indices are refactored appropriately to point to the entries in the new regions.

Details for InteractionSet

Subsetting behaves in much the same way as that for the `SummarizedExperiment` class. Interactions are treated as rows and will be subsetting as such. All subsetting operations will return an `InteractionSet` with the specified interactions (rows) or samples (columns). Again, note that the value of regions will not be modified by subsetting.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE)

# Subsetting:
gi[1,]
gi[1:2,]
gi[3]
gi[3:4]

temp.gi <- gi
temp.gi[3:4] <- gi[1:2]

# Splitting:
f <- sample(4, length(gi), replace=TRUE)
out <- split(gi, f)
out[[1]]

#####
# Same can be done for an InteractionSet object:

example(InteractionSet, echo=FALSE)

# Subsetting:
iset[1,]
iset[1:2,]
iset[,1]
iset[,1:2]
iset[3,3]
iset[3:4,3:4]

# Splitting:
out <- split(iset, f)
out[[1]]
```

InteractionSet class *InteractionSet class and constructors*

Description

The InteractionSet class stores information about pairwise genomic interactions, and is intended for use in data analysis from Hi-C or ChIA-PET experiments. Each row of the InteractionSet corresponds to a pairwise interaction between two loci, as defined in the GInteractions object. Each column corresponds to a library or sample. Each InteractionSet also contains one or more assays, intended to hold experimental data about interaction frequencies for each interaction in each sample.

Usage

```
## S4 method for signature 'ANY,GInteractions'
InteractionSet(assays, interactions, ...)

## S4 method for signature 'missing,missing'
InteractionSet(assays, interactions, ...)
```

Arguments

assays	A numeric matrix or a list or SimpleList of matrices, containing data for each interaction.
interactions	A GInteractions object of length equal to the number of rows in assays.
...	Other arguments to be passed to the SummarizedExperiment constructor.

Details

The InteractionSet class inherits from the [SummarizedExperiment](#) class and has access to all of its data members and methods. It also contains an additional interactions slot which holds a GInteractions object (or an object from any derived classes, e.g., StrictGInteractions). Each row of the InteractionSet object corresponds to a pairwise interaction between two genomic loci in interactions.

The constructor will return an InteractionSet object containing all of the specified information - for InteractionSet,missing,missing-method, an empty InteractionSet object is returned. Note that any metadata arguments will be placed in the metadata of the internal SummarizedExperiment object, *not* the metadata of the internal GInteractions object. This is consistent with the behaviour of similar classes like RangedSummarizedExperiment.

Value

For the constructors, an InteractionSet object is returned.

Author(s)

Aaron Lun

See Also

[?"interaction-access"](#), [?"interaction-subset"](#), [?"interaction-compare"](#)

Examples

```
example(GInteractions, echo=FALSE)
Nlibs <- 4
counts <- matrix(rpois(Np*Nlibs, lambda=10), ncol=Nlibs)
colnames(counts) <- seq_len(Nlibs)

iset <- InteractionSet(counts, gi)
iset <- InteractionSet(counts, gi, colData=DataFrame(lib.size=1:Nlibs*1000))
iset <- InteractionSet(counts, gi, metadata=list(name="My Hi-C data"))

# Note differences in metadata storage:
metadata(iset)
metadata(interactions(iset))
```

Linearize interactions

Linearize 2D interactions into 1D ranges

Description

Convert interactions in two-dimensional space to one-dimensional ranges on the linear genome.

Usage

```
## S4 method for signature 'GInteractions,numeric'
linearize(x, ref, internal=TRUE)

## S4 method for signature 'GInteractions,GRanges'
linearize(x, ref, ..., internal=TRUE)

## S4 method for signature 'InteractionSet,numeric'
linearize(x, ref, internal=TRUE)

## S4 method for signature 'InteractionSet,GRanges'
linearize(x, ref, ..., internal=TRUE)
```

Arguments

<code>x</code>	A GInteractions or InteractionSet object.
<code>ref</code>	A numeric vector or a GRanges object, specifying the reference region(s) to use for linearization. If numeric, the entries should be indices pointing to a genomic interval in <code>regions(x)</code> .
<code>internal</code>	A logical scalar specifying whether interactions within <code>ref</code> should be reported.
<code>...</code>	Other arguments, passed to overlapsAny in the GRanges methods.

Details

This method identifies all interactions with at least one anchor region overlapping the specified region(s) in `ref`. When `x` is a `GInteractions` object, the method returns a `GRanges` object with one entry per identified interaction, where the coordinates are defined as the *other* anchor region, i.e., the one that does *not* overlap the reference region.

If both of the anchor regions for an interaction overlap the reference regions, the genomic interval spanned by both anchor regions is returned. This is because it is not clear which region should be defined as the "other" anchor in such circumstances. Note that this will fail if the reference regions occur across multiple chromosomes. If `internal=FALSE`, interactions with both overlapping anchor regions are removed from the output.

When `x` is an `InteractionSet` object, a `RangedSummarizedExperiment` object is returned. Each entry corresponds to an identified interaction with the non-overlapping anchor region stored in the `rowRanges`. Experimental data associated with each identified interaction is stored in the various assays.

This method effectively converts two-dimensional interaction data into one-dimensional coverage across the linear genome. It is useful when a particular genomic region is of interest - this can be used as `ref`, to examine the behaviour of all other regions relative to it. For example, Hi-C data in `x` can be converted into pseudo-4C contact frequencies after linearization.

Disjoint ranges across multiple chromosomes are supported when `ref` is a `GRanges` object. However, it usually only makes sense to use contiguous ranges as a single bait region. Similarly, if `ref` is numeric, it should refer to consecutive entries in `regions(x)` to specify the bait region.

Value

A `GRanges` when `x` is a `GInteractions` object, and a `RangedSummarizedExperiment` when `x` is an `InteractionSet` object.

Examples

```
example(InteractionSet, echo=FALSE)

# With integers
out <- linearize(iset, 1)
linearize(iset, 10)
linearize(iset, 20)

# With ranges
linearize(iset, regions(iset)[1], type="equal")
linearize(iset, regions(iset)[10], type="equal")
linearize(iset, regions(iset)[20], type="equal")
```

Description

Identify interactions that link two sets of regions by having anchor regions overlapping one entry in each set.

Usage

```
## S4 method for signature 'GInteractions,Vector,Vector'
linkOverlaps(query, subject1, subject2, ...,
             ignore.strand=TRUE, use.region="both")

## S4 method for signature 'InteractionSet,Vector,Vector'
linkOverlaps(query, subject1, subject2, ...,
             ignore.strand=TRUE, use.region="both")
```

Arguments

query	A GInteractions or InteractionSet object.
subject1, subject2	A Vector object defining a set of genomic intervals, such as a GRanges or GRangesList . subject2 may be missing. Alternatively, both subject1 and subject2 may be Hits objects, see below.
..., ignore.strand	Additional arguments to be passed to findOverlaps . Note that ignore.strand=TRUE by default, as genomic interactions are usually unstranded.
use.region	A string specifying which query regions should be used to overlap which subject. Ignored if subject2 is missing.

Details

This function identifies all interactions in query where one anchor overlaps an entry in subject1 and the other anchor overlaps an entry in subject2. It is designed to be used to identify regions that are linked by interactions in query. For example, one might specify genes as subject1 and enhancers as subject2, to identify all gene-enhancer contacts present in query. This is useful when the exact pairings between subject1 and subject2 are undefined.

The function returns a DataFrame specifying the index of the interaction in query; the index of the overlapped region in subject1; and the index of the overlapped region in subject2. If multiple regions in subject1 and/or subject2 are overlapping the anchor regions of a particular interaction, all combinations of two overlapping regions (one from each subject* set) are reported for that interaction.

By default, use.region="both" such that overlaps will be considered between any first/second interacting region in query and either subject1 or subject2. If use.region="same", overlaps will only be considered between the first interacting region in query and entries in subject1, and between the second interacting region and subject2. The opposite applies with use.region="reverse", where the first and second interacting regions are overlapped with subject2 and subject1 respectively.

If subject2 is not specified, links within subject1 are identified instead, i.e., subject2 is set to subject1. In such cases, the returned DataFrame is such that the first subject index is always greater than the second subject index, to avoid redundant permutations.

Value

A `DataFrame` of integer indices indicating which elements of query link which elements of subject1 and subject2.

Using Hits as input

Hits objects can be used for the subject1 and subject2 arguments. These should be constructed using `findOverlaps` with `regions(query)` as the query and the genomic regions of interest as the subject. For example, the calls below:

```
> linkOverlaps(query, subject1) # 1
> linkOverlaps(query, subject1, subject2) # 2
```

will yield exactly the same output as:

```
> olap1 <- findOverlaps(regions(query), subject1)
> linkOverlaps(query, olap1) # 1
> olap2 <- findOverlaps(regions(query), subject2)
> linkOverlaps(query, olap1, olap2) # 2
```

This is useful in situations where `regions(query)` and the genomic regions in subject1 and subject2 are constant across multiple calls to `linkOverlaps`. In such cases, the overlaps only need to be calculated once, avoiding redundant work within `linkOverlaps`.

Author(s)

Aaron Lun

See Also

[findOverlaps](#), [GInteractions](#), [Vector-method](#)

Examples

```
example(GInteractions, echo=FALSE)

all.genes <- GRanges("chrA", IRanges(0:9*10, 1:10*10))
all.enhancers <- GRanges("chrB", IRanges(0:9*10, 1:10*10))

out <- linkOverlaps(gi, all.genes, all.enhancers)
head(out)

out <- linkOverlaps(gi, all.genes)
head(out)

# Same methods apply for InteractionSet objects.

example(InteractionSet, echo=FALSE)
out <- linkOverlaps(iset, all.genes, all.enhancers)
out <- linkOverlaps(iset, all.genes)
```

pairs	<i>Extract paired ranges</i>
-------	------------------------------

Description

Represent interactions in a `GInteractions` or `Interaction` object as a `Pairs`, `SelfHits` or `GRangesList` object.

Usage

```
## S4 method for signature 'GInteractions'
pairs(x, id=FALSE, as.grlist=FALSE)

## S4 method for signature 'InteractionSet'
pairs(x, id=FALSE, as.grlist=FALSE)

makeGInteractionsFromGRangesPairs(x)
```

Arguments

x	For <code>pairs</code> , a GInteractions or InteractionSet object. For <code>makeGInteractionsFromGRangesPairs</code> , a Pairs object containing two parallel GRanges .
id	A logical scalar specifying whether indices should be returned instead of regions.
as.grlist	A logical scalar specifying whether a <code>GRangesList</code> should be returned.

Details

Recall that the `GInteractions` object stores anchor regions for each interaction in two parallel `GRanges`, where corresponding entries between the two `GRanges` constitute the pair of regions for one interaction. These parallel ranges can be extracted and stored as a `Pairs` object for further manipulation. This is similar to the `GRangesList` reported by [anchors](#) with `type="both"` and `id=FALSE`. The reverse conversion is performed using `makeGInteractionsFromGRangesPairs`.

An alternative representation involves storing the two anchors for each interaction in a single `GRanges` of length 2. Multiple interactions are then stored as a `GRangesList`, along with any meta-data and sequence information. This is returned if `as.grlist=FALSE`, may be more useful in some applications where the two interacting regions must be in the same `GRanges`. Finally, if `id=TRUE`, the anchor indices are extracted and returned as a `SelfHits` object. This may be useful for graph construction.

Value

For `pairs`, if `id=TRUE`, a `SelfHits` object is returned. Otherwise, if `as.grlist=TRUE`, a [GRangesList](#) object is returned. Otherwise, a `Pairs` object is returned.

For `makeGInteractionsFromGRangesPairs`, a `GInteractions` object is returned.

Author(s)

Aaron Lun

Examples

```
example(GInteractions, echo=FALSE)
y <- pairs(gi)
y
makeGInteractionsFromGRangesPairs(y)

pairs(gi, id=TRUE)
pairs(gi, as.grlist=TRUE)

example(InteractionSet, echo=FALSE)
pairs(iset)
pairs(iset, id=TRUE)
pairs(iset, as.grlist=TRUE)
```

updateObject

Update a GInteractions object

Description

Update an old GInteractions object to the latest format.

Usage

```
## S4 method for signature 'GInteractions'
updateObject(object, ..., verbose = FALSE)
```

Arguments

object	A old GInteractions object.
...	Additional arguments that are ignored.
verbose	Logical scalar indicating whether a message should be emitted as the object is updated.

Value

An updated version of object.

Index

[\[,ContactMatrix,ANY,ANY,ANY-method \(ContactMatrix subsetting\), 14](#)
[\[,ContactMatrix,ANY,ANY-method \(ContactMatrix subsetting\), 14](#)
[\[,ContactMatrix,ANY-method \(ContactMatrix subsetting\), 14](#)
[\[,InteractionSet,ANY,ANY,ANY-method \(Interaction subsetting\), 41](#)
[\[,InteractionSet,ANY,ANY-method \(Interaction subsetting\), 41](#)
[\[,InteractionSet,ANY-method \(Interaction subsetting\), 41](#)
[\[<-,ContactMatrix,ANY,ANY,ContactMatrix-method \(ContactMatrix subsetting\), 14](#)
[\[<-,GInteractions,ANY,GInteractions-method \(Interaction subsetting\), 41](#)
[\[<-,InteractionSet,ANY,ANY,InteractionSet-method \(Interaction subsetting\), 41](#)
[\\$,GInteractions-method \(Interaction accessors\), 24](#)
[\\$<-,GInteractions-method \(Interaction accessors\), 24](#)

[anchorIds \(Interaction accessors\), 24](#)
[anchorIds,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[anchorIds,GInteractions-method \(Interaction accessors\), 24](#)
[anchorIds,InteractionSet-method \(Interaction accessors\), 24](#)
[anchorIds<- \(Interaction accessors\), 24](#)
[anchorIds<-,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[anchorIds<-,GInteractions-method \(Interaction accessors\), 24](#)
[anchorIds<-,InteractionSet-method \(Interaction accessors\), 24](#)
[anchorIds<-,ReverseStrictGInteractions-method \(Interaction accessors\), 24](#)

[anchorIds<-,StrictGInteractions-method \(Interaction accessors\), 24](#)
[anchors, 15, 42, 49](#)
[anchors \(Interaction accessors\), 24](#)
[anchors,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[anchors,GInteractions-method \(Interaction accessors\), 24](#)
[anchors,InteractionSet-method \(Interaction accessors\), 24](#)
[anchors<- \(Interaction accessors\), 24](#)
[anchors<-,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[anchors<-,GInteractions-method \(Interaction accessors\), 24](#)
[anchors<-,InteractionSet-method \(Interaction accessors\), 24](#)
[anchors<-,ReverseStrictGInteractions-method \(Interaction accessors\), 24](#)
[anchors<-,StrictGInteractions-method \(Interaction accessors\), 24](#)
[Annotated, 6, 8](#)
[appendRegions<- \(Interaction accessors\), 24](#)
[appendRegions<-,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[appendRegions<-,GInteractions-method \(Interaction accessors\), 24](#)
[appendRegions<-,InteractionSet-method \(Interaction accessors\), 24](#)
[as.data.frame, 27](#)
[as.data.frame,GInteractions-method \(Interaction accessors\), 24](#)
[as.matrix,ContactMatrix-method \(ContactMatrix accessors\), 4](#)
[as.matrix<- \(ContactMatrix accessors\), 4](#)
[as.matrix<-,ContactMatrix-method \(ContactMatrix accessors\), 4](#)

[boundingBox, 2](#)

- boundingBox, GInteractions-method
(boundingBox), [2](#)
- boundingBox, InteractionSet-method
(boundingBox), [2](#)
- c, GInteractions-method (Interaction
binding), [30](#)
- cbind, [15](#), [31](#)
- cbind, ContactMatrix-method
(ContactMatrix subsetting), [14](#)
- cbind, InteractionSet-method
(Interaction binding), [30](#)
- ContactMatrix, [5](#), [10](#), [11](#), [13](#), [15](#), [16](#), [23](#)
- ContactMatrix (ContactMatrix class), [7](#)
- ContactMatrix accessors, [4](#)
- ContactMatrix class, [7](#)
- ContactMatrix distances, [10](#)
- ContactMatrix overlaps, [11](#)
- ContactMatrix sorting, [12](#)
- ContactMatrix subsetting, [14](#)
- ContactMatrix, ANY, GRanges, GRanges, GenomicRanges_OR_missing-method
(ContactMatrix class), [7](#)
- ContactMatrix, ANY, numeric, numeric, GRanges-method
(ContactMatrix class), [7](#)
- ContactMatrix, missing, missing, missing, GenomicRanges_OR_missing-method
(ContactMatrix class), [7](#)
- ContactMatrix-access (ContactMatrix
accessors), [4](#)
- ContactMatrix-class (ContactMatrix
class), [7](#)
- ContactMatrix-dist (ContactMatrix
distances), [10](#)
- ContactMatrix-sort (ContactMatrix
sorting), [12](#)
- ContactMatrix-subset (ContactMatrix
subsetting), [14](#)
- Convert classes, [16](#)
- countOverlaps (Interaction overlaps), [38](#)
- countOverlaps, GInteractions, GInteractions-method
(Interaction overlaps), [38](#)
- countOverlaps, GInteractions, InteractionSet-method
(Interaction overlaps), [38](#)
- countOverlaps, GInteractions, missing-method
(Interaction overlaps), [38](#)
- countOverlaps, GInteractions, Vector-method
(Interaction overlaps), [38](#)
- countOverlaps, InteractionSet, GInteractions-method
(Interaction overlaps), [38](#)
- countOverlaps, InteractionSet, InteractionSet-method
(Interaction overlaps), [38](#)
- countOverlaps, InteractionSet, missing-method
(Interaction overlaps), [38](#)
- countOverlaps, InteractionSet, Vector-method
(Interaction overlaps), [38](#)
- countOverlaps, Vector, GInteractions-method
(Interaction overlaps), [38](#)
- countOverlaps, Vector, InteractionSet-method
(Interaction overlaps), [38](#)
- deflate (Convert classes), [16](#)
- deflate, ContactMatrix-method (Convert
classes), [16](#)
- dim, ContactMatrix-method
(ContactMatrix accessors), [4](#)
- dimnames, ContactMatrix-method
(ContactMatrix accessors), [4](#)
- dimnames<-, ContactMatrix, ANY-method
(ContactMatrix accessors), [4](#)
- dimnames<-, ContactMatrix-method
(ContactMatrix accessors), [4](#)
- duplicated, ContactMatrix-method
(ContactMatrix sorting), [12](#)
- duplicated, GInteractions-method
(Interaction compare), [32](#)
- duplicated, InteractionSet-method
(Interaction compare), [32](#)
- findOverlaps, [11](#), [34](#), [38–40](#), [47](#), [48](#)
- findOverlaps (Interaction overlaps), [38](#)
- findOverlaps, GInteractions, GInteractions-method
(Interaction overlaps), [38](#)
- findOverlaps, GInteractions, InteractionSet-method
(Interaction overlaps), [38](#)
- findOverlaps, GInteractions, missing-method
(Interaction overlaps), [38](#)
- findOverlaps, GInteractions, Vector-method
(Interaction overlaps), [38](#)
- findOverlaps, InteractionSet, GInteractions-method
(Interaction overlaps), [38](#)
- findOverlaps, InteractionSet, InteractionSet-method
(Interaction overlaps), [38](#)
- findOverlaps, InteractionSet, missing-method
(Interaction overlaps), [38](#)
- findOverlaps, InteractionSet, Vector-method
(Interaction overlaps), [38](#)
- findOverlaps, Vector, GInteractions-method
(Interaction overlaps), [38](#)

- findOverlaps, Vector, InteractionSet-method
(Interaction overlaps), 38
- first(Interaction accessors), 24
- first, GInteractions-method
(Interaction accessors), 24
- first, InteractionSet-method
(Interaction accessors), 24
- flank, ContactMatrix-method (GRanges
methods), 22
- flank, GInteractions-method (GRanges
methods), 22
- flank, InteractionSet-method (GRanges
methods), 22
- GInteractions, 3, 11, 16, 23, 26, 31, 33, 36,
38, 42, 45, 47, 49, 50
- GInteractions (GInteractions class), 19
- GInteractions class, 19
- GInteractions, GRanges, GRanges, GenomicRanges_OR_MISSING-method
(GInteractions class), 19
- GInteractions, missing, missing, GenomicRanges_OR_MISSING-method
(GInteractions class), 19
- GInteractions, numeric, numeric, GRanges-method
(GInteractions class), 19
- GInteractions-class (GInteractions
class), 19
- GRanges, 5, 6, 11, 27, 28, 45, 47, 49
- GRanges methods, 22
- GRangesList, 11, 47, 49
- inflate, 9
- inflate (Convert classes), 16
- inflate, GInteractions-method (Convert
classes), 16
- inflate, InteractionSet-method (Convert
classes), 16
- Interaction accessors, 24
- Interaction binding, 30
- Interaction compare, 32
- Interaction distances, 36
- Interaction overlaps, 38
- Interaction subsetting, 41
- interaction-access (Interaction
accessors), 24
- interaction-bind (Interaction binding),
30
- interaction-compare (Interaction
compare), 32
- Interaction-overlaps (Interaction
overlaps), 38
- interaction-subset (Interaction
subsetting), 41
- interactions (Interaction accessors), 24
- interactions, InteractionSet-method
(Interaction accessors), 24
- interactions<- (Interaction accessors),
24
- interactions<- , InteractionSet-method
(Interaction accessors), 24
- InteractionSet, 3, 11, 16, 23, 26, 31, 33, 36,
38, 42, 45, 47, 49
- InteractionSet (InteractionSet class),
44
- InteractionSet class, 44
- InteractionSet, ANY, GInteractions-method
(InteractionSet class), 44
- InteractionSet, missing, missing-method
(InteractionSet class), 44
- InteractionSet-class (InteractionSet
class), 44
- intrachr (Interaction distances), 36
- intrachr, ContactMatrix-method
(ContactMatrix distances), 10
- intrachr, GInteractions-method
(Interaction distances), 36
- intrachr, InteractionSet-method
(Interaction distances), 36
- length, ContactMatrix-method
(ContactMatrix accessors), 4
- length, GInteractions-method
(Interaction accessors), 24
- linearize (Linearize interactions), 45
- Linearize interactions, 45
- linearize, GInteractions, GRanges-method
(Linearize interactions), 45
- linearize, GInteractions, numeric-method
(Linearize interactions), 45
- linearize, InteractionSet, GRanges-method
(Linearize interactions), 45
- linearize, InteractionSet, numeric-method
(Linearize interactions), 45
- linkOverlaps, 40, 46
- linkOverlaps, GInteractions, Hits, Hits-method
(linkOverlaps), 46
- linkOverlaps, GInteractions, Hits, missing-method
(linkOverlaps), 46

- linkOverlaps,GInteractions,Vector,missing-method (linkOverlaps), 46
- linkOverlaps,GInteractions,Vector,Vector-method (linkOverlaps), 46
- linkOverlaps,InteractionSet,Hits,Hits-method (linkOverlaps), 46
- linkOverlaps,InteractionSet,Hits,missing-method (linkOverlaps), 46
- linkOverlaps,InteractionSet,Vector,missing-method (linkOverlaps), 46
- linkOverlaps,InteractionSet,Vector,Vector-method (linkOverlaps), 46
- makeGInteractionsFromGRangesPairs (pairs), 49
- match, 33, 35
- match,GInteractions,GInteractions-method (Interaction compare), 32
- match,GInteractions,InteractionSet-method (Interaction compare), 32
- match,InteractionSet,GInteractions-method (Interaction compare), 32
- match,InteractionSet,InteractionSet-method (Interaction compare), 32
- mcols, 27
- mcols,InteractionSet-method (Interaction accessors), 24
- mcols<-,InteractionSet-method (Interaction accessors), 24
- names,GInteractions-method (Interaction accessors), 24
- names,InteractionSet-method (Interaction accessors), 24
- names<-,GInteractions-method (Interaction accessors), 24
- names<-,InteractionSet-method (Interaction accessors), 24
- narrow,ContactMatrix-method (GRanges methods), 22
- narrow,GInteractions-method (GRanges methods), 22
- narrow,InteractionSet-method (GRanges methods), 22
- order,ContactMatrix-method (ContactMatrix sorting), 12
- order,GInteractions-method (Interaction compare), 32
- order,InteractionSet-method (Interaction compare), 32
- order,Vector-method (Interaction compare), 32
- overlapsAny, 17, 45
- overlapsAny (Interaction overlaps), 38
- overlapsAny,ContactMatrix,GInteractions-method (ContactMatrix overlaps), 11
- overlapsAny,ContactMatrix,InteractionSet-method (ContactMatrix overlaps), 11
- overlapsAny,ContactMatrix,Vector-method (ContactMatrix overlaps), 11
- overlapsAny,GInteractions,GInteractions-method (Interaction overlaps), 38
- overlapsAny,GInteractions,InteractionSet-method (Interaction overlaps), 38
- overlapsAny,GInteractions,missing-method (Interaction overlaps), 38
- overlapsAny,GInteractions,Vector-method (Interaction overlaps), 38
- overlapsAny,InteractionSet,GInteractions-method (Interaction overlaps), 38
- overlapsAny,InteractionSet,InteractionSet-method (Interaction overlaps), 38
- overlapsAny,InteractionSet,missing-method (Interaction overlaps), 38
- overlapsAny,InteractionSet,Vector-method (Interaction overlaps), 38
- overlapsAny,Vector,GInteractions-method (Interaction overlaps), 38
- overlapsAny,Vector,InteractionSet-method (Interaction overlaps), 38
- pairdist (Interaction distances), 36
- pairdist,ContactMatrix-method (ContactMatrix distances), 10
- pairdist,GInteractions-method (Interaction distances), 36
- pairdist,InteractionSet-method (Interaction distances), 36
- Pairs, 49
- pairs, 49
- pairs,GInteractions-method (pairs), 49
- pairs,InteractionSet-method (pairs), 49
- pcompare, 35
- pcompare,GInteractions,GInteractions-method (Interaction compare), 32
- rbind,ContactMatrix-method (ContactMatrix subsetting), 14

- rbind, InteractionSet-method
(Interaction binding), 30
- reduceRegions(Interaction accessors), 24
- reduceRegions, ContactMatrix-method
(ContactMatrix accessors), 4
- reduceRegions, GInteractions-method
(Interaction accessors), 24
- reduceRegions, InteractionSet-method
(Interaction accessors), 24
- regions(Interaction accessors), 24
- regions, ContactMatrix-method
(ContactMatrix accessors), 4
- regions, GInteractions-method
(Interaction accessors), 24
- regions, InteractionSet-method
(Interaction accessors), 24
- regions<- (Interaction accessors), 24
- regions<-, ContactMatrix-method
(ContactMatrix accessors), 4
- regions<-, GInteractions-method
(Interaction accessors), 24
- regions<-, InteractionSet-method
(Interaction accessors), 24
- replaceRegions<- (Interaction accessors), 24
- replaceRegions<-, ContactMatrix-method
(ContactMatrix accessors), 4
- replaceRegions<-, GInteractions-method
(Interaction accessors), 24
- replaceRegions<-, InteractionSet-method
(Interaction accessors), 24
- resize, ContactMatrix-method (GRanges methods), 22
- resize, GInteractions-method (GRanges methods), 22
- resize, InteractionSet-method (GRanges methods), 22
- ReverseStrictGInteractions-class
(GInteractions class), 19
- second(Interaction accessors), 24
- second, GInteractions-method
(Interaction accessors), 24
- second, InteractionSet-method
(Interaction accessors), 24
- Seqinfo, 5
- seqinfo, 27
- seqinfo, ContactMatrix-method
(ContactMatrix accessors), 4
- seqinfo, GInteractions-method
(Interaction accessors), 24
- seqinfo, InteractionSet-method
(Interaction accessors), 24
- seqinfo<-, ContactMatrix-method
(ContactMatrix accessors), 4
- seqinfo<-, GInteractions-method
(Interaction accessors), 24
- seqinfo<-, InteractionSet-method
(Interaction accessors), 24
- shift, ContactMatrix-method (GRanges methods), 22
- shift, GInteractions-method (GRanges methods), 22
- shift, InteractionSet-method (GRanges methods), 22
- show, ContactMatrix-method
(ContactMatrix accessors), 4
- show, GInteractions-method (Interaction accessors), 24
- show, InteractionSet-method
(Interaction accessors), 24
- sort, ContactMatrix-method
(ContactMatrix sorting), 12
- sort, GInteractions-method (Interaction compare), 32
- sort, InteractionSet-method
(Interaction compare), 32
- sparseMatrix, 18
- StrictGInteractions-class
(GInteractions class), 19
- subset, ContactMatrix-method
(ContactMatrix subsetting), 14
- subset, InteractionSet-method
(Interaction subsetting), 41
- subsetByOverlaps (Interaction overlaps), 38
- subsetByOverlaps, GInteractions, GInteractions-method
(Interaction overlaps), 38
- subsetByOverlaps, GInteractions, InteractionSet-method
(Interaction overlaps), 38
- subsetByOverlaps, GInteractions, Vector-method
(Interaction overlaps), 38
- subsetByOverlaps, InteractionSet, GInteractions-method
(Interaction overlaps), 38
- subsetByOverlaps, InteractionSet, InteractionSet-method

(Interaction overlaps), [38](#)
subsetByOverlaps, InteractionSet, Vector-method
(Interaction overlaps), [38](#)
subsetByOverlaps, Vector, GInteractions-method
(Interaction overlaps), [38](#)
subsetByOverlaps, Vector, InteractionSet-method
(Interaction overlaps), [38](#)
SummarizedExperiment, [28](#), [44](#)
swapAnchors, [3](#)
swapAnchors (Interaction compare), [32](#)
swapAnchors, GInteractions-method
(Interaction compare), [32](#)
swapAnchors, InteractionSet-method
(Interaction compare), [32](#)

t, ContactMatrix-method (ContactMatrix
accessors), [4](#)
trim, ContactMatrix-method (GRanges
methods), [22](#)
trim, GInteractions-method (GRanges
methods), [22](#)
trim, InteractionSet-method (GRanges
methods), [22](#)

unique, ContactMatrix-method
(ContactMatrix sorting), [12](#)
unique, GInteractions-method
(Interaction compare), [32](#)
unique, InteractionSet-method
(Interaction compare), [32](#)
updateObject, [50](#)
updateObject, GInteractions-method
(updateObject), [50](#)

Vector, [20](#), [28](#), [38](#), [42](#), [47](#)

width, ContactMatrix-method (GRanges
methods), [22](#)
width, GInteractions-method (GRanges
methods), [22](#)
width, InteractionSet-method (GRanges
methods), [22](#)