

# Package ‘wiggplotr’

December 10, 2025

**Title** Make read coverage plots from BigWig files

**Version** 1.35.0

**Author** Kaur Alasoo [aut, cre]

**Maintainer** Kaur Alasoo <kaur.alasoo@gmail.com>

**Description** Tools to visualise read coverage from sequencing experiments together with genomic annotations (genes, transcripts, peaks). Introns of long transcripts can be rescaled to a fixed length for better visualisation of exonic read coverage.

**Depends** R (>= 3.6)

**Imports** dplyr, ggplot2 (>= 2.2.0), GenomicRanges, rtracklayer, cowplot, assertthat, purrr, S4Vectors, IRanges, GenomeInfoDb

**License** Apache License 2.0

**LazyData** true

**RoxygenNote** 7.2.0

**Encoding** UTF-8

**Suggests** knitr, rmarkdown, biomaRt, GenomicFeatures, testthat, ensemblDb, EnsDb.Hsapiens.v86, org.Hs.eg.db, TxDb.Hsapiens.UCSC.hg38.knownGene, AnnotationDbi, AnnotationFilter

**VignetteBuilder** knitr

**biocViews** ImmunoOncology, Coverage, RNASeq, ChIPSeq, Sequencing, Visualization, GeneExpression, Transcription, AlternativeSplicing

**git\_url** <https://git.bioconductor.org/packages/wiggplotr>

**git\_branch** devel

**git\_last\_commit** 39b648a

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-12-09

Contents

|                                        |           |
|----------------------------------------|-----------|
| extractCoverageData . . . . .          | 2         |
| getGenotypePalette . . . . .           | 4         |
| makeManhattanPlot . . . . .            | 4         |
| ncoa7_cdss . . . . .                   | 5         |
| ncoa7_exons . . . . .                  | 6         |
| ncoa7_metadata . . . . .               | 6         |
| pasteFactors . . . . .                 | 7         |
| plotCoverage . . . . .                 | 7         |
| plotCoverageData . . . . .             | 10        |
| plotCoverageFromEnsemblDb . . . . .    | 11        |
| plotCoverageFromUCSC . . . . .         | 12        |
| plotTranscripts . . . . .              | 13        |
| plotTranscriptsFromEnsemblDb . . . . . | 14        |
| plotTranscriptsFromUCSC . . . . .      | 15        |
| wiggleplotr . . . . .                  | 16        |
| <b>Index</b>                           | <b>17</b> |

---

|                     |                                                         |
|---------------------|---------------------------------------------------------|
| extractCoverageData | <i>Extract read coverage data from the bigWig files</i> |
|---------------------|---------------------------------------------------------|

---

Description

Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

Usage

```
extractCoverageData(  
  exons,  
  cdss = NULL,  
  transcript_annotations = NULL,  
  track_data,  
  rescale_introns = TRUE,  
  new_intron_length = 50,  
  flanking_length = c(50, 50),  
  plot_fraction = 0.1,  
  mean_only = TRUE,  
  region_coords = NULL  
)
```

Arguments

|       |                                                                                                                                                                                  |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| exons | list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame. |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cdss                   | list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL).                                                                                                                                                                                                                                                                                                                                                                                                                |
| transcript_annotations | Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| track_data             | data.frame with the metadata for the bigWig read coverage files. Must contain the following columns: <ul style="list-style-type: none"> <li>• sample_id - unique id for each sample.</li> <li>• track_id - if multiple samples (bigWig files) have the same track_id they will be overlayed on the same plot, track_id is also used as the facet label on the right.</li> <li>• bigWig - path to the bigWig file.</li> <li>• scaling_factor - normalisation factor for each sample, useful if different samples sequenced to different depth and bigWig files not normalised for that.</li> <li>• colour_group - additional column to group samples into, is used as the colour of the coverage track.</li> </ul> |
| rescale_introns        | Specifies if the introns should be scaled to fixed length or not. (default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| new_intron_length      | length (bp) of introns after scaling. (default: 50)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| flanking_length        | Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| plot_fraction          | Size of the random sub-sample of points used to plot coverage (between 0 and 1). Smaller values make plotting significantly faster. (default: 0.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| mean_only              | Plot only mean coverage within each combination of track_id and colour_group values. Useful for example for plotting mean coverage stratified by genotype (which is specified in the colour_group column) (default: TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| region_coords          | Start and end coordinates of the region to plot, overrides flanking_length parameter. The 'both' option tends to give better results for wide regions. (default: area).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

## Value

List containing all of the necessary data for the plotCoverageData function ()

## Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
```

```
dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
extractCoverageData(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts], ncoa7_metadata, track_)

## End(Not run)
```

---

|                    |                                                                                                     |
|--------------------|-----------------------------------------------------------------------------------------------------|
| getGenotypePalette | <i>Returns a three-colour palette suitable for visualising read coverage stratified by genotype</i> |
|--------------------|-----------------------------------------------------------------------------------------------------|

---

### Description

Returns a three-colour palette suitable for visualising read coverage stratified by genotype

### Usage

```
getGenotypePalette(old = FALSE)
```

### Arguments

old                      Return old colour palette (now deprecated).

### Value

Vector of three colours.

### Examples

```
getGenotypePalette()
```

---

|                   |                                          |
|-------------------|------------------------------------------|
| makeManhattanPlot | <i>Make a Manhattan plot of p-values</i> |
|-------------------|------------------------------------------|

---

### Description

The Manhattan plots is compatible with wigglyplotr read coverage and transcript structure plots. Can be appended to those using the cowplot::plot\_grid() function.

**Usage**

```
makeManhattanPlot(
  pvalues_df,
  region_coords,
  color_R2 = FALSE,
  data_track = TRUE
)
```

**Arguments**

|                            |                                                                                                                                                                   |
|----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>pvalues_df</code>    | Data frame of association p-values (required columns: <code>track_id</code> , <code>p_nominal</code> , <code>pos</code> )                                         |
| <code>region_coords</code> | Start and end coordinates of the region to plot.                                                                                                                  |
| <code>color_R2</code>      | Color the points according to R2 from the lead variant. Require R2 column in the <code>pvalues_df</code> data frame.                                              |
| <code>data_track</code>    | If TRUE, then remove all information from x-axis. Makes it easy to append to read coverage or transcript strcture plots using <code>cowplot::plot_grid()</code> . |

**Value**

ggplot2 object

**Examples**

```
data = dplyr::data_frame(track_id = "GWAS", pos = sample(c(1:1000), 200), p_nominal = runif(200, min = 0.0000001, 1)
makeManhattanPlot(data, c(1,1000), data_track = FALSE)
```

---

ncoa7\_cdss

---

*Coding sequences from 9 protein coding transcripts of NCOA7*


---

**Description**

A dataset containing start and end coordinates of coding sequences (CDS) from nine protein coding transcripts of NCOA7.

**Usage**

```
ncoa7_cdss
```

**Format**

A GRangesList object with 9 elements:

**element** CDS start and end coordinates for a single transcript (GRanges object) ...

**Source**

<http://www.ensembl.org/>

---

|             |                                                         |
|-------------|---------------------------------------------------------|
| ncoa7_exons | <i>Exons from 9 protein coding transcripts of NCOA7</i> |
|-------------|---------------------------------------------------------|

---

**Description**

A dataset containing start and end coordinates of exons from nine protein coding transcripts of NCOA7.

**Usage**

```
ncoa7_exons
```

**Format**

A GRangesList object with 9 elements:

**element** Exon start and end coordinates for a single transcript (GRanges object) ...

**Source**

<http://www.ensembl.org/>

---

|                |                                |
|----------------|--------------------------------|
| ncoa7_metadata | <i>Gene metadata for NCOA7</i> |
|----------------|--------------------------------|

---

**Description**

A a list of transcripts for NCOA7.

**Usage**

```
ncoa7_metadata
```

**Format**

A data.frame object with 4 columns:

**transcript\_id** Ensembl transcript id.

**gene\_id** Ensembl gene id.

**gene\_name** Human readable gene name.

**strand** Strand of the transcript (either +1 or -1). ...

**Source**

<http://www.ensembl.org/>

---

|              |                                                                    |
|--------------|--------------------------------------------------------------------|
| pasteFactors | <i>Paste two factors together and preserved their joint order.</i> |
|--------------|--------------------------------------------------------------------|

---

**Description**

Paste two factors together and preserved their joint order.

**Usage**

```
pasteFactors(factor1, factor2)
```

**Arguments**

|         |               |
|---------|---------------|
| factor1 | First factor  |
| factor2 | Second factor |

**Value**

Factors factor1 and factor2 pasted together.

---

|              |                                                   |
|--------------|---------------------------------------------------|
| plotCoverage | <i>Plot read coverage across a genomic region</i> |
|--------------|---------------------------------------------------|

---

**Description**

Also supports rescaling introns to constant length. Extracts read coverage from bigWig files with extractCoverageData and plots it with plotCoverageData. Custom visualisations can be created by modifying the plotCoverageData function. Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

**Usage**

```
plotCoverage(
  exons,
  cdss = NULL,
  transcript_annotations = NULL,
  track_data,
  rescale_introns = TRUE,
  new_intron_length = 50,
  flanking_length = c(50, 50),
  plot_fraction = 0.1,
  heights = c(0.75, 0.25),
  alpha = 1,
  fill_palette = c("#a1dab4", "#41b6c4", "#225ea8"),
  mean_only = TRUE,
```

```

connect_exons = TRUE,
transcript_label = TRUE,
return_subplots_list = FALSE,
region_coords = NULL,
coverage_type = "area",
show_legend = FALSE
)

```

## Arguments

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| exons                  | list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| cdss                   | list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL).                                                                                                                                                                                                                                                                                                                                                                                                                |
| transcript_annotations | Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| track_data             | data.frame with the metadata for the bigWig read coverage files. Must contain the following columns: <ul style="list-style-type: none"> <li>• sample_id - unique id for each sample.</li> <li>• track_id - if multiple samples (bigWig files) have the same track_id they will be overlayed on the same plot, track_id is also used as the facet label on the right.</li> <li>• bigWig - path to the bigWig file.</li> <li>• scaling_factor - normalisation factor for each sample, useful if different samples sequenced to different depth and bigWig files not normalised for that.</li> <li>• colour_group - additional column to group samples into, is used as the colour of the coverage track.</li> </ul> |
| rescale_introns        | Specifies if the introns should be scaled to fixed length or not. (default: TRUE)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| new_intron_length      | length (bp) of introns after scaling. (default: 50)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| flanking_length        | Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| plot_fraction          | Size of the random sub-sample of points used to plot coverage (between 0 and 1). Smaller values make plotting significantly faster. (default: 0.1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| heights                | Specifies the proportion of the height that is dedicated to coverage plots (first value) relative to transcript annotations (second value). (default: c(0.75,0.25))                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| alpha                  | Transparency (alpha) value for the read coverage tracks. Useful to set to something < 1 when overlaying multiple tracks (see track_id). (default: 1)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |



|                      |                                                                                                                                                                                                                            |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fill_palette         | Vector of fill colours used for the coverage tracks. Length must be equal to the number of unique values in track_data\$colour_group column.                                                                               |
| mean_only            | Plot only mean coverage within each combination of track_id and colour_group values. Useful for example for plotting mean coverage stratified by genotype (which is specified in the colour_group column) (default: TRUE). |
| connect_exons        | Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).                                                                                                                                 |
| transcript_label     | If TRUE then transcript labels are printed above each transcript. (default: TRUE).                                                                                                                                         |
| return_subplots_list | Instead of a joint plot return a list of subplots that can be joined together manually.                                                                                                                                    |
| region_coords        | Start and end coordinates of the region to plot, overrides flanking_length parameter.                                                                                                                                      |
| coverage_type        | Specifies if the read coverage is represented by either 'line', 'area' or 'both'. The 'both' option tends to give better results for wide regions. (default: area).                                                        |
| show_legend          | display legend for the colour_group next to the read coverage plot (default: FALSE).                                                                                                                                       |

## Value

Either object from cow\_plot::plot\_grid() function or a list of subplots (if return\_subplots\_list == TRUE)

## Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
plotCoverage(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts],
  ncoa7_metadata, track_data,
  heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

|                  |                                                   |
|------------------|---------------------------------------------------|
| plotCoverageData | <i>Plot read coverage across a genomic region</i> |
|------------------|---------------------------------------------------|

---

## Description

Does not work on Windows, because rtracklayer cannot read BigWig files on Windows.

## Usage

```
plotCoverageData(
  coverage_data_list,
  heights = c(0.75, 0.25),
  alpha = 1,
  fill_palette = c("#a1dab4", "#41b6c4", "#225ea8"),
  connect_exons = TRUE,
  transcript_label = TRUE,
  return_subplots_list = FALSE,
  coverage_type = "area",
  show_legend = FALSE
)
```

## Arguments

|                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| coverage_data_list | <p>List of required from the extractCoverageData function:</p> <ul style="list-style-type: none"> <li>• exons - list of GRanges objects, each object containing exons for one transcript.</li> <li>• cdss - list of GRanges objects, each object containing the coding regions (CDS) of a single transcript.</li> <li>• plotting_annotations - Transcript labels for plotting.</li> <li>• tx_annotations - Transcript coordinates for plotting.</li> <li>• xlabel - Label of the x-axis.</li> <li>• coverage_df - Read coverage data frame.</li> <li>• limits - x-axis limits.</li> </ul> |
| heights            | Specifies the proportion of the height that is dedicated to coverage plots (first value) relative to transcript annotations (second value). (default: c(0.75,0.25))                                                                                                                                                                                                                                                                                                                                                                                                                       |
| alpha              | Transparency (alpha) value for the read coverage tracks. Useful to set to something < 1 when overlaying multiple tracks (see track_id). (default: 1)                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| fill_palette       | Vector of fill colours used for the coverage tracks. Length must be equal to the number of unique values in track_data\$colour_group column.                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| connect_exons      | Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| transcript_label   | If TRUE then transcript labels are printed above each transcript. (default: TRUE).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |

|                      |                                                                                                                                                                     |
|----------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| return_subplots_list | Instead of a joint plot return a list of subplots that can be joined together manually.                                                                             |
| coverage_type        | Specifies if the read coverage is represented by either 'line', 'area' or 'both'. The 'both' option tends to give better results for wide regions. (default: area). |
| show_legend          | display legend for the colour_group next to the read coverage plot (default: FALSE).                                                                                |

### Value

Either object from `cow_plot::plot_grid()` function or a list of subplots (if `return_subplots_list == TRUE`)

### Examples

```
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aibt_A", "aibt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)

selected_transcripts = c("ENST00000438495", "ENST00000392477") #Plot only two transcripts of the gens
## Not run:
cov_data = extractCoverageData(ncoa7_exons[selected_transcripts], ncoa7_cdss[selected_transcripts], ncoa7_metadata)
plotCoverageData(cov_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotCoverageFromEnsemblDb

*Plot read coverage directly from ensemblDb object.*

---

### Description

A wrapper around the `plotCoverage` function. See the documentation for ([plotCoverage](#)) for more information.

### Usage

```
plotCoverageFromEnsemblDb(ensemblDb, gene_names, transcript_ids = NULL, ...)
```

**Arguments**

ensemblldb      ensemblldb object.  
 gene\_names      List of gene names to be plotted.  
 transcript\_ids   Optional list of transcript ids to be plotted.  
 ...              Additional parameters to be passed to plotCoverage.

**Value**

ggplot2 object

**Examples**

```
require("EnsDb.Hsapiens.v86")
require("dplyr")
require("GenomicRanges")
sample_data = dplyr::data_frame(sample_id = c("aibt_A", "aibt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
plotCoverageFromEnsemblDb(EnsDb.Hsapiens.v86, "NCOA7", transcript_ids = c("ENST00000438495", "ENST00000392477"),
  track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotCoverageFromUCSC    *Plot read coverage directly from UCSC OrgDb and TxDb objects.*

---

**Description**

A wrapper around the plotCoverage function. See the documentation for ([plotCoverage](#)) for more information.

**Usage**

```
plotCoverageFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL, ...)
```

**Arguments**

orgdb              UCSC OrgDb object.  
 txdb              UCSC TxDb object.  
 gene\_names      List of gene names to be plotted.  
 transcript\_ids   Optional list of transcript ids to be plotted.  
 ...              Additional parameters to be passed to plotCoverage.

**Value**

ggplot2 object

**Examples**

```
require("dplyr")
require("GenomicRanges")
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")

orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

sample_data = dplyr::data_frame(sample_id = c("aipt_A", "aipt_C", "bima_A", "bima_C"),
  condition = factor(c("Naive", "LPS", "Naive", "LPS"), levels = c("Naive", "LPS")),
  scaling_factor = 1) %>%
  dplyr::mutate(bigWig = system.file("extdata", paste0(sample_id, ".str2.bw"), package = "wigglyplotr"))

track_data = dplyr::mutate(sample_data, track_id = condition, colour_group = condition)
## Not run:
#Note: This example does not work, because UCSC and Ensembl use different chromosome names
plotCoverageFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"),
  track_data, heights = c(2,1), fill_palette = getGenotypePalette())

## End(Not run)
```

---

plotTranscripts

*Quickly plot transcript structure without read coverage tracks*


---

**Description**

Quickly plot transcript structure without read coverage tracks

**Usage**

```
plotTranscripts(
  exons,
  cdss = NULL,
  transcript_annotations = NULL,
  rescale_introns = TRUE,
  new_intron_length = 50,
  flanking_length = c(50, 50),
  connect_exons = TRUE,
  transcript_label = TRUE,
  region_coords = NULL
)
```

**Arguments**

|                        |                                                                                                                                                                                                                                                                                                   |
|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| exons                  | list of GRanges objects, each object containing exons for one transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame.                                                                                                                  |
| cdss                   | list of GRanges objects, each object containing the coding regions (CDS) of a single transcript. The list must have names that correspond to transcript_id column in transcript_annotations data.frame. If cdss is not specified then exons list will be used for both arguments. (default: NULL) |
| transcript_annotations | Data frame with at least three columns: transcript_id, gene_name, strand. Used to construct transcript labels. (default: NULL)                                                                                                                                                                    |
| rescale_introns        | Specifies if the introns should be scaled to fixed length or not. (default: TRUE)                                                                                                                                                                                                                 |
| new_intron_length      | length (bp) of introns after scaling. (default: 50)                                                                                                                                                                                                                                               |
| flanking_length        | Lengths of the flanking regions upstream and downstream of the gene. (default: c(50,50))                                                                                                                                                                                                          |
| connect_exons          | Print lines that connect exons together. Set to FALSE when plotting peaks (default: TRUE).                                                                                                                                                                                                        |
| transcript_label       | If TRUE then transcript labels are printed above each transcript. (default: TRUE).                                                                                                                                                                                                                |
| region_coords          | Start and end coordinates of the region to plot, overrides flanking_length parameter.                                                                                                                                                                                                             |

**Value**

ggplot2 object

**Examples**

```
plotTranscripts(ncoa7_exons, ncoa7_cdss, ncoa7_metadata, rescale_introns = FALSE)
```

---

```
plotTranscriptsFromEnsemblDb
```

*Plot transcripts directly from ensemblDb object.*

---

**Description**

A wrapper around the plotTranscripts function. See the documentation for ([plotTranscripts](#)) for more information.

**Usage**

```
plotTranscriptsFromEnsemblDb(ensemldb, gene_names, transcript_ids = NULL, ...)
```

**Arguments**

|                |                                                       |
|----------------|-------------------------------------------------------|
| ensemldb       | ensemldb object.                                      |
| gene_names     | List of gene names to be plotted.                     |
| transcript_ids | Optional list of transcript ids to be plotted.        |
| ...            | Additional parameters to be passed to plotTranscripts |

**Value**

ggplot2 object

**Examples**

```
require("EnsDb.Hsapiens.v86")
plotTranscriptsFromEnsemblDb(EnsDb.Hsapiens.v86, "NC0A7", transcript_ids = c("ENST00000438495", "ENST00000392477"))
```

---

plotTranscriptsFromUCSC

*Plot transcripts directly from UCSC OrgDb and TxDb objects.*

---

**Description**

A wrapper around the plotTranscripts function. See the documentation for ([plotTranscripts](#)) for more information. Note that this function is much slower than ([plotTranscripts](#)) or ([plotTranscriptsFromEnsemblDb](#)) functions, because individually extracting exon coordinates from txdb objects is quite inefficient.

**Usage**

```
plotTranscriptsFromUCSC(orgdb, txdb, gene_names, transcript_ids = NULL, ...)
```

**Arguments**

|                |                                                              |
|----------------|--------------------------------------------------------------|
| orgdb          | UCSC OrgDb object.                                           |
| txdb           | UCSC TxDb object.                                            |
| gene_names     | List of gene names to be plot.                               |
| transcript_ids | Optional list of transcript ids to be plot. (default = NULL) |
| ...            | Additional parameters to be passed to plotTranscripts        |

**Value**

Transcript plot.

## Examples

```
#Load OrgDb and TxDb objects with UCSC gene annotations
require("org.Hs.eg.db")
require("TxDb.Hsapiens.UCSC.hg38.knownGene")
orgdb = org.Hs.eg.db
txdb = TxDb.Hsapiens.UCSC.hg38.knownGene

plotTranscriptsFromUCSC(orgdb, txdb, "NCOA7", transcript_ids = c("ENST00000438495.6", "ENST00000368357.7"))
```

---

wigglyplotr

*wigglyplotr*

---

## Description

wigglyplotr package provides tools to visualise transcript annotations ([plotTranscripts](#)) and plot sequencing read coverage over annotated transcripts ([plotCoverage](#)).

## Details

You can also use convenient wrapper functions ([plotTranscriptsFromEnsemblDb](#)), ([plotCoverageFromEnsemblDb](#)), ([plotTranscriptsFromUCSC](#)) and ([plotCoverageFromUCSC](#)).

To learn more about wigglyplotr, start with the vignette: `browseVignettes(package = "wigglyplotr")`



# Index

## \* datasets

- ncoa7\_cdss, [5](#)
- ncoa7\_exons, [6](#)
- ncoa7\_metadata, [6](#)

extractCoverageData, [2](#)

getGenotypePalette, [4](#)

makeManhattanPlot, [4](#)

ncoa7\_cdss, [5](#)

ncoa7\_exons, [6](#)

ncoa7\_metadata, [6](#)

pasteFactors, [7](#)

plotCoverage, [7](#), [11](#), [12](#), [16](#)

plotCoverageData, [10](#)

plotCoverageFromEnsemblDb, [11](#), [16](#)

plotCoverageFromUCSC, [12](#), [16](#)

plotTranscripts, [13](#), [14–16](#)

plotTranscriptsFromEnsemblDb, [14](#), [15](#), [16](#)

plotTranscriptsFromUCSC, [15](#), [16](#)

wiggleplotr, [16](#)