

Package ‘zenith’

December 10, 2025

Type Package

Title Gene set analysis following differential expression using linear (mixed) modeling with dream

Version 1.13.0

Date 2025-04-03

Description Zenith performs gene set analysis on the result of differential expression using linear (mixed) modeling with dream by considering the correlation between gene expression traits. This package implements the camera method from the limma package proposed by Wu and Smyth (2012). Zenith is a simple extension of camera to be compatible with linear mixed models implemented in `variancePartition::dream()`.

VignetteBuilder knitr

License Artistic-2.0

Encoding UTF-8

URL <https://DiseaseNeuroGenomics.github.io/zenith>

BugReports <https://github.com/DiseaseNeuroGenomics/zenith/issues>

Suggests BiocStyle, BiocGenerics, knitr, pander, rmarkdown, tseeDEseqCountData, edgeR, kableExtra, RUnit

biocViews RNASeq, GeneExpression, GeneSetEnrichment, DifferentialExpression, BatchEffect, QualityControl, Regression, Epigenetics, FunctionalGenomics, Transcriptomics, Normalization, Preprocessing, Microarray, ImmunoOncology, Software

Depends R (>= 4.2.0), limma, methods

Imports variancePartition (>= 1.26.0), EnrichmentBrowser (>= 2.22.0), GSEABase (>= 1.54.0), msigdb, Rfast, ggplot2, tidyr, dplyr, reshape2, progress, utils, Rdpack, stats

RdMacros Rdpack

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/zenith>

git_branch devel

git_last_commit d8b9255
git_last_commit_date 2025-10-29
Repository Bioconductor 3.23
Date/Publication 2025-12-09
Author Gabriel Hoffman [aut, cre] (ORCID:
 <<https://orcid.org/0000-0002-0957-0224>>)
Maintainer Gabriel Hoffman <gabriel.hoffman@mssm.edu>

Contents

.rankSumTestWithCorrelation	2
corInGeneSet	3
get_GeneOntology	3
get_MSigDB	4
plotZenithResults	5
zenith	7
zenithPR_gsa	9
zenith_gsa	11
Index	14

.rankSumTestWithCorrelation
<i>Two Sample Wilcoxon-Mann-Whitney Rank Sum Test Allowing For Correlation</i>

Description

Same as `limma::.rankSumTestWithCorrelation`, but returns effect size.

Usage

`.rankSumTestWithCorrelation(index, statistics, correlation = 0, df = Inf)`

Arguments

index	any index vector such that <code>statistics[index]</code> contains the values of the statistic for the test group.
statistics	numeric vector giving values of the test statistic.
correlation	numeric scalar, average correlation between cases in the test group. Cases in the second group are assumed independent of each other and other the first group.
df	degrees of freedom which the correlation has been estimated.

Details

See `limma::.rankSumTestWithCorrelation`

Value

data.frame storing results of hypothesis test

corInGeneSet	<i>Evaluate mean correlation between residuals in gene set</i>
--------------	--

Description

Evaluate mean correlation between residuals in gene set based on results from dream

Usage

```
corInGeneSet(fit, idx, squareCorr = FALSE)
```

Arguments

fit	result of differential expression with dream
idx	indices or rownames to extract
squareCorr	compute the mean squared correlation instead

Value

list storing correlation and variance inflation factor

get_GeneOntology	<i>Load Gene Ontology genesets</i>
------------------	------------------------------------

Description

Load Gene Ontology genesets

Usage

```
get_GeneOntology(  
  onto = c("BP", "MF", "CC"),  
  to = "ENSEMBL",  
  includeOffspring = TRUE,  
  org = "hsa"  
)
```

Arguments

- onto array of categories to load
- to convert gene names to this type using EnrichmentBrowser::idMap(). See EnrichmentBrowser::idTypes(org="hsa") for valid types
- includeOffspring if TRUE, follow the GO hierarchy down and include all genes in offspring sets for a given gene set
- org organism. human ('hsa'), mouse ('mmu'), etc

Details

This function loads the GO gene sets using the packages EnrichmentBrowser and GO.db It can take a mintute to load because converting gene name type is slow.

Value

Gene sets stored as GeneSetCollection

Examples

```
# load GO Biological Process
# gs = get_GeneOntology('BP')

# load all gene sets
# gs = get_GeneOntology()
```

get_MSigDB	<i>Load MSigDB genesets</i>
------------	-----------------------------

Description

Load MSigDB genesets

Usage

```
get_MSigDB(
  cat,
  to = c("ENSEMBL", "SYMBOL", "ENTREZ"),
  organism = c("HS", "MM")
)
```

Arguments

- cat array of categories to load.
- to return genes names as 'ENSEMBL' or 'SYMBOL'
- organism organism: human ('HS') or mouse ('MS')

Details

This function loads the MSigDB gene sets using the packages and msigdb. It can take a minute to load because converting gene name type is slow.

Value

Gene sets stored as GeneSetCollection

Examples

```
# load Hallmark gene sets
gs = get_MSigDB('H')

# load all gene sets
# gs = get_MSigDB()
```

plotZenithResults	<i>Heatmap of zenith results using ggplot2</i>
-------------------	--

Description

Heatmap of zenith results showing genesets that have the top and bottom t-statistics from each assay.

Usage

```
plotZenithResults(
  df,
  ntop = 5,
  nbottom = 5,
  label.angle = 45,
  zmax = NULL,
  transpose = FALSE,
  sortByGeneset = TRUE
)
```

Arguments

df	result data.frame from zenith_gsa
ntop	number of gene sets with highest t-statistic to show
nbottom	number of gene sets with lowest t-statistic to show
label.angle	angle of x-axis label
zmax	maximum of the color scales. If not specified, used range of the observed t-statistics
transpose	transpose the axes of the plot
sortByGeneset	use hierarchical clustering to sort gene sets. Default is TRUE

Value

Heatmap showing enrichment for gene sets and cell types

Examples

```
# Load packages
library(edgeR)
library(variancePartition)
library(tweedEseqCountData)

# Load RNA-seq data from LCL's
data(pickrell)
geneCounts = exprs(pickrell.eset)
df_metadata = pData(pickrell.eset)

# Filter genes
# Note this is low coverage data, so just use as code example
dsgn = model.matrix(~ gender, df_metadata)
keep = filterByExpr(geneCounts, dsgn, min.count=5)

# Compute library size normalization
dge = DGEList(counts = geneCounts[keep,])
dge = calcNormFactors(dge)

# Estimate precision weights using voom
vobj = voomWithDreamWeights(dge, ~ gender, df_metadata)

# Apply dream analysis
fit = dream(vobj, ~ gender, df_metadata)
fit = eBayes(fit)

# Load Hallmark genes from MSigDB
# use gene 'SYMBOL', or 'ENSEMBL' id
# use get_GeneOntology() to load Gene Ontology
gs = get_MSigDB("H", to="ENSEMBL")

# Run zenith analysis
res.gsa = zenith_gsa(fit, gs, 'gendermale', progressBar=FALSE )

# Show top gene sets
head(res.gsa, 2)

# for each cell type select 3 genesets with largest t-statistic
# and 1 geneset with the lowest
# Grey boxes indicate the gene set could not be evaluated because
#   to few genes were represented
plotZenithResults(res.gsa)
```

Description

Perform gene set analysis on the result of differential expression using linear (mixed) modeling with `variancePartition::dream` by considering the correlation between gene expression traits. This package is a slight modification of `limma::camera` to 1) be compatible with `dream`, and 2) allow identification of gene sets with log fold changes with mixed sign.

Usage

```
zenith(  
  fit,  
  coef,  
  index,  
  use.ranks = FALSE,  
  allow.neg.cor = FALSE,  
  progressbar = TRUE,  
  inter.gene.cor = 0.01  
)
```

Arguments

<code>fit</code>	result of differential expression with <code>dream</code>
<code>coef</code>	coefficient to test using <code>topTable(fit, coef)</code>
<code>index</code>	an index vector or a list of index vectors. Can be any vector such that <code>fit[index,]</code> selects the rows corresponding to the test set. The list can be made using <code>ids2indices</code> .
<code>use.ranks</code>	do a rank-based test (TRUE) or a parametric test ('FALSE')?
<code>allow.neg.cor</code>	should reduced variance inflation factors be allowed for negative correlations?
<code>progressbar</code>	if TRUE, show progress bar
<code>inter.gene.cor</code>	if NA, estimate correlation from data. Otherwise, use specified value

Details

`zenith` gives the same results as `camera(..., inter.gene.cor=NA)` which estimates the correlation with each gene set.

For differential expression with `dream` using linear (mixed) models see Hoffman and Roussos (2020). For the original `camera` gene set test see Wu and Smyth (2012).

Value

- NGenes: number of genes in this set
- Correlation: mean correlation between expression of genes in this set
- delta: difference in mean t-statistic for genes in this set compared to genes not in this set
- se: standard error of delta
- p.less: p-value for hypothesis test of $H_0: \text{delta} < 0$
- p.greater: p-value for hypothesis test of $H_0: \text{delta} > 0$
- PValue: p-value for hypothesis test $H_0: \text{delta} \neq 0$
- Direction: direction of effect based on $\text{sign}(\text{delta})$
- FDR: false discovery rate based on Benjamini-Hochberg method in `p.adjust`

References

Hoffman, G. E., & Roussos, P. (2021). Dream: powerful differential expression analysis for repeated measures designs. *Bioinformatics*, 37(2), 192-201.

Wu, Di, and Gordon K. Smyth. "Camera: a competitive gene set test accounting for inter-gene correlation." *Nucleic acids research* 40.17 (2012): e133-e133.

Examples

```
library(variancePartition)

# simulate meta-data
info <- data.frame(Age=c(20, 31, 52, 35, 43, 45),Group=c(0,0,0,1,1,1))

# simulate expression data
y <- matrix(rnorm(1000*6),1000,6)
rownames(y) = paste0("gene", 1:1000)
colnames(y) = rownames(info)

# First set of 20 genes are genuinely differentially expressed
index1 <- 1:20
y[index1,4:6] <- y[index1,4:6]+1

# Second set of 20 genes are not DE
index2 <- 21:40

# perform differential expression analysis with dream
fit = dream(y, ~ Age + Group, info)
fit = eBayes(fit)

# perform gene set analysis testing Age
res = zenith(fit, "Age", list(set1=index1,set2=index2) )

head(res)
```


zenithPR_gsa

*Gene set analysis using pre-computed test statistic***Description**

Perform gene set analysis on the result of a pre-computed test statistic. Test whether statistics in a gene set are larger/smaller than statistics not in the set.

Usage

```
zenithPR_gsa(
  statistics,
  ids,
  geneSets,
  use.ranks = FALSE,
  n_genes_min = 10,
  progressbar = TRUE,
  inter.gene.cor = 0.01,
  coef.name = "zenithPR"
)
```

Arguments

<code>statistics</code>	pre-computed test statistics
<code>ids</code>	name of gene for each entry in statistics
<code>geneSets</code>	GeneSetCollection
<code>use.ranks</code>	do a rank-based test TRUE or a parametric test FALSE? default: FALSE
<code>n_genes_min</code>	minumum number of genes in a geneset
<code>progressbar</code>	if TRUE, show progress bar
<code>inter.gene.cor</code>	correlation of test statistics with in gene set
<code>coef.name</code>	name of column to store test statistic

Details

This is the same as `zenith_gsa()`, but uses pre-computed test statistics. Note that `zenithPR_gsa()` may give slightly different results for small samples sizes, if `zenithPR_gsa()` is fed t-statistics instead of z-statistics.

Value

- `NGenes`: number of genes in this set
- `Correlation`: mean correlation between expression of genes in this set
- `delta`: difference in mean t-statistic for genes in this set compared to genes not in this set
- `se`: standard error of delta

- `p.less`: p-value for hypothesis test of $H_0: \delta < 0$
- `p.greater`: p-value for hypothesis test of $H_0: \delta > 0$
- `PValue`: p-value for hypothesis test $H_0: \delta \neq 0$
- `Direction`: direction of effect based on `sign(delta)`
- `FDR`: false discovery rate based on Benjamini-Hochberg method in `p.adjust`
- `coef.name`: name for pre-computed test statistics. Default: `zenithPR`

See Also

`zenith_gsa()`, `limma::cameraPR()`

Examples

```
# Load packages
library(edgeR)
library(variancePartition)
library(tweedEseqCountData)

# Load RNA-seq data from LCL's
data(pickrell)
geneCounts = exprs(pickrell.eset)
df_metadata = pData(pickrell.eset)

# Filter genes
# Note this is low coverage data, so just use as code example
dsgn = model.matrix(~ gender, df_metadata)
keep = filterByExpr(geneCounts, dsgn, min.count=5)

# Compute library size normalization
dge = DGEList(counts = geneCounts[keep,])
dge = calcNormFactors(dge)

# Estimate precision weights using voom
vobj = voomWithDreamWeights(dge, ~ gender, df_metadata)

# Apply dream analysis
fit = dream(vobj, ~ gender, df_metadata)
fit = eBayes(fit)

# Load Hallmark genes from MSigDB
# use gene 'SYMBOL', or 'ENSEMBL' id
# use get_GeneOntology() to load Gene Ontology
gs = get_MSigDB("H", to="ENSEMBL")

# Run zenithPR analysis with a test statistic for each gene
tab = topTable(fit, coef='gendermale', number=Inf)

res.gsa = zenithPR_gsa(tab$t, rownames(tab), gs)
```

zenith_gsa

*Perform gene set analysis using zenith***Description**

Perform a competitive gene set analysis accounting for correlation between genes.

Usage

```
zenith_gsa(
  fit,
  geneSets,
  coefs,
  use.ranks = FALSE,
  n_genes_min = 10,
  inter.gene.cor = 0.01,
  progressbar = TRUE,
  ...
)

## S4 method for signature 'MArrayLM, GeneSetCollection'
zenith_gsa(
  fit,
  geneSets,
  coefs,
  use.ranks = FALSE,
  n_genes_min = 10,
  inter.gene.cor = 0.01,
  progressbar = TRUE,
  ...
)
```

Arguments

<code>fit</code>	results from <code>dream()</code>
<code>geneSets</code>	<code>GeneSetCollection</code>
<code>coefs</code>	list of coefficients to test using <code>topTable(fit, coef=coefs[[i]])</code>
<code>use.ranks</code>	do a rank-based test TRUE or a parametric test FALSE? default: FALSE
<code>n_genes_min</code>	minumum number of genes in a geneset
<code>inter.gene.cor</code>	if NA, estimate correlation from data. Otherwise, use specified value
<code>progressbar</code>	if TRUE, show progress bar
<code>...</code>	other arguments

Details

This code adapts the widely used `camera()` analysis (Wu and Smyth, 2012) in the `limma` package (Ritchie, et al. 2015) to the case of linear (mixed) models used by `variancePartition::dream()`.

Value

`data.frame` of results for each gene set and cell type

References

Wu, Di, and Gordon K. Smyth. "Camera: a competitive gene set test accounting for inter-gene correlation." *Nucleic acids research* 40.17 (2012): e133-e133.

Ritchie, M. E., Phipson, B., Wu, D. I., Hu, Y., Law, C. W., Shi, W., & Smyth, G. K. (2015). `limma` powers differential expression analyses for RNA-sequencing and microarray studies. *Nucleic acids research*, 43(7), e47-e47.

See Also

`limma::camera`

Examples

```
# Load packages
library(edgeR)
library(variancePartition)
library(tweedEseqCountData)

# Load RNA-seq data from LCL's
data(pickrell)
geneCounts = exprs(pickrell.eset)
df_metadata = pData(pickrell.eset)

# Filter genes
# Note this is low coverage data, so just use as code example
dsgn = model.matrix(~ gender, df_metadata)
keep = filterByExpr(geneCounts, dsgn, min.count=5)

# Compute library size normalization
dge = DGEList(counts = geneCounts[keep,])
dge = calcNormFactors(dge)

# Estimate precision weights using voom
vobj = voomWithDreamWeights(dge, ~ gender, df_metadata)

# Apply dream analysis
fit = dream(vobj, ~ gender, df_metadata)
fit = eBayes(fit)

# Load Hallmark genes from MSigDB
# use gene 'SYMBOL', or 'ENSEMBL' id
# use get_GeneOntology() to load Gene Ontology
```

```
gs = get_MSigDB("H", to="ENSEMBL")

# Run zenith analysis
res.gsa = zenith_gsa(fit, gs, 'gendermale', progressbar=FALSE )

# Show top gene sets
head(res.gsa, 2)

# for each cell type select 3 genesets with largest t-statistic
# and 1 geneset with the lowest
# Grey boxes indicate the gene set could not be evaluated because
#   to few genes were represented
plotZenithResults(res.gsa)
```

Index

`.rankSumTestWithCorrelation`, [2](#)

`corInGeneSet`, [3](#)

`get_GeneOntology`, [3](#)

`get_MSigDB`, [4](#)

`plotZenithResults`, [5](#)

`zenith`, [7](#)

`zenith_gsa`, [5](#), [11](#)

`zenith_gsa`, `MArrayLM`, `GeneSetCollection`, ANY-method
 (`zenith_gsa`), [11](#)

`zenith_gsa`, `MArrayLM`, `GeneSetCollection`-method
 (`zenith_gsa`), [11](#)

`zenithPR_gsa`, [9](#)