

Package ‘clusterProfiler’

October 15, 2018

Type Package

Title statistical analysis and visualization of functional profiles
for genes and gene clusters

Version 3.8.1

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description This package implements methods to analyze and visualize
functional profiles (GO and KEGG) of gene and gene clusters.

Depends R (>= 3.4.0)

Imports AnnotationDbi, DOSE (>= 3.5.1), enrichplot (>= 0.99.7),
ggplot2, GO.db, GOSemSim, magrittr, methods, plyr, qvalue,
rvcheck, stats, tidyr, utils

Suggests AnnotationHub, GSEABase, KEGG.db, knitr, org.Hs.eg.db,
prettydoc, pathview, ReactomePA, testthat

Remotes GuangchuangYu/DOSE, GuangchuangYu/enrichplot

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

URL <https://guangchuangyu.github.io/software/clusterProfiler>

BugReports <https://github.com/GuangchuangYu/clusterProfiler/issues>

biocViews Annotation, Clustering, GeneSetEnrichment, GO, KEGG,
MultipleComparison, Pathways, Reactome, Visualization

RoxxygenNote 6.0.1

git_url <https://git.bioconductor.org/packages/clusterProfiler>

git_branch RELEASE_3_7

git_last_commit 81e1a7a

git_last_commit_date 2018-09-17

Date/Publication 2018-10-15

Author Guangchuang Yu [aut, cre, cph]
(<<https://orcid.org/0000-0002-6485-8781>>),
Li-Gen Wang [ctb],
Giovanni Dall'Olio [ctb] (formula interface of compareCluster)

R topics documented:

clusterProfiler-package	2
bitr	3
bitr_kegg	3
browseKEGG	4
buildGOmap	4
compareCluster	5
compareClusterResult-class	6
DataSet	6
dotplot,compareClusterResult-method	7
download_KEGG	7
dropGO	8
enrichDAVID	8
enricher	9
enrichGO	10
enrichKEGG	11
enrichMKEGG	12
fortify.compareClusterResult	13
getGOLevel	13
Gff2GeneTable	14
go2ont	14
go2term	15
gofilter	15
groupGO	16
groupGOResult-class	17
GSEA	17
gseGO	18
gseKEGG	19
gseMKEGG	20
idType	21
KEGG_path2extid	21
ko2name	22
merge_result	22
plotGOgraph	23
plotting.clusterProfile	23
read.gmt	24
search_kegg_organism	25
simplify	25
uniprot_get	26
viewKEGG	26

Index

28

clusterProfiler-package

statistical analysis and visualization of functional profiles for genes and gene clusters. The package implements methods to analyze and visualize functional profiles of gene and gene clusters.

Description

statistical analysis and visualization of functional profiles for genes and gene clusters The package implements methods to analyze and visualize functional profiles of gene and gene clusters.

bitr*bitr***Description**

Biological Id TRanslator

Usage

```
bitr(geneID, fromType, toType, OrgDb, drop = TRUE)
```

Arguments

geneID	input gene id
fromType	input id type
toType	output id type
OrgDb	annotation db
drop	drop NA or not

Value

data.frame

Author(s)

Guangchuang Yu

bitr_kegg*bitr_kegg***Description**

convert biological ID using KEGG API

Usage

```
bitr_kegg(geneID, fromType, toType, organism, drop = TRUE)
```

Arguments

geneID	input gene id
fromType	input id type
toType	output id type
organism	supported organism, can be search using search_kegg_organism function
drop	drop NA or not

Value

data.frame

Author(s)

Guangchuang Yu

browseKEGG

browseKEGG

Description

open KEGG pathway with web browser

Usage

`browseKEGG(x, pathID)`

Arguments

x	an instance of enrichResult or gseaResult
pathID	pathway ID

Value

url

Author(s)

Guangchuang Yu

buildGOMap

buildGOMap

Description

building GO mapping files

Usage

`buildGOMap(gomap)`

Arguments

gomap	data.frame with two columns of GO and gene ID
-------	---

Details

provided by a data.frame of GO (column 1) and gene (column 2) direct annotation this function will building gene to GO and GO to gene mapping, with directly and indirectly (ancestor GO term) annotation.

Value

data.frame, GO annotation with indirect annotation

Author(s)

Yu Guangchuang

compareCluster *Compare gene clusters functional profile*

Description

Given a list of gene set, this function will compute profiles of each gene cluster.

Usage

```
compareCluster(geneClusters, fun = "enrichGO", data = "", ...)
```

Arguments

- | | |
|--------------|---|
| geneClusters | a list of entrez gene id. Alternatively, a formula of type Entrez~group |
| fun | One of "groupGO", "enrichGO", "enrichKEGG", "enrichDO" or "enrichPathway". |
| data | if geneClusters is a formula, the data from which the clusters must be extracted. |
| ... | Other arguments. |

Value

A clusterProfResult instance.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[compareClusterResult-class](#), [groupGO](#) [enrichGO](#)

Examples

```
## Not run:  
data(gcSample)  
xx <- compareCluster(gcSample, fun="enrichKEGG",  
                      organism="hsa", pvalueCutoff=0.05)  
as.data.frame(xx)  
# plot(xx, type="dot", caption="KEGG Enrichment Comparison")  
  
## formula interface  
mydf <- data.frame(Entrez=c('1', '100', '1000', '100101467',  
                      '100127206', '100128071'),  
                    group = c('A', 'A', 'A', 'B', 'B', 'B'),  
                    othergroup = c('good', 'good', 'bad', 'bad', 'good', 'bad'))
```

```

xx.formula <- compareCluster(Entrez~group, data=mydf,
                             fun='groupGO', OrgDb='org.Hs.eg.db')
as.data.frame(xx.formula)

## formula interface with more than one grouping variable
xx.formula.twogroups <- compareCluster(Entrez~group+othergroup, data=mydf,
                                         fun='groupGO', OrgDb='org.Hs.eg.db')
as.data.frame(xx.formula.twogroups)

## End(Not run)

```

compareClusterResult-class

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Description

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Slots

- compareClusterResult cluster comparing result
- geneClusters a list of genes
- fun one of groupGO, enrichGO and enrichKEGG
- .call function call

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[groupGOResult](#) [enrichResult](#) [compareCluster](#)

DataSet

Datasets gcSample contains a sample of gene clusters.

Description

Datasets gcSample contains a sample of gene clusters.

Datasets kegg_species contains kegg species information

```
dotplot,compareClusterResult-method  
  dotplot
```

Description

dot plot method

Usage

```
## S4 method for signature 'compareClusterResult'  
dotplot(object, x = ~Cluster,  
        color = "p.adjust", showCategory = 5, split = NULL, font.size = 12,  
        title = "", by = "geneRatio", includeAll = TRUE)
```

Arguments

object	compareClusterResult object
x	x variable
color	one of pvalue or p.adjust
showCategory	category numbers
split	ONTOLOGY or NULL
font.size	font size
title	figure title
by	one of geneRatio, Percentage or count
includeAll	logical

```
download_KEGG          download_KEGG
```

Description

download the latest version of KEGG pathway/module

Usage

```
download_KEGG(species, keggType = "KEGG", keyType = "kegg")
```

Arguments

species	species
keggType	one of 'KEGG' or 'MKEGG'
keyType	supported keyType, see bitr_kegg

Value

list

Author(s)

Guangchuang Yu

dropGO

dropGO

Description

drop GO term of specific level or specific terms (mostly too general).

Usage

```
dropGO(x, level = NULL, term = NULL)
```

Arguments

x	an instance of 'enrichResult' or 'compareClusterResult'
level	GO level
term	GO term

Value

modified version of x

Author(s)

Guangchuang Yu

enrichDAVID

enrichDAVID

Description

enrichment analysis by DAVID

Usage

```
enrichDAVID(gene, idType = "ENTREZ_GENE_ID", universe, minGSSize = 10,
            maxGSSize = 500, annotation = "GOTERM_BP_FAT", pvalueCutoff = 0.05,
            pAdjustMethod = "BH", qvalueCutoff = 0.2, species = NA, david.user)
```

Arguments

gene	input gene
idType	id type
universe	background genes
minGSSize	minimal size of genes annotated for testing
maxGSSize	maximal size of genes annotated for testing
annotation	david annotation
pvalueCutoff	pvalueCutoff
pAdjustMethod	one of "BH" and "bonferroni"
qvalueCutoff	qvalueCutoff
species	species
david.user	david user

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

enricher

enricher

Description

A universal enrichment analyzer

Usage

```
enricher(gene, pvalueCutoff = 0.05, pAdjustMethod = "BH", universe,
         minGSSize = 10, maxGSSize = 500, qvalueCutoff = 0.2, TERM2GENE,
         TERM2NAME = NA)
```

Arguments

gene	a vector of gene id
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated for testing
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff
TERM2GENE	user input annotation of TERM TO GENE mapping, a data.frame of 2 column with term and gene
TERM2NAME	user input of TERM TO NAME mapping, a data.frame of 2 column with term and name

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

`enrichGO`

GO Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment GO categories after FDR control.

Description

GO Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment GO categories after FDR control.

Usage

```
enrichGO(gene, OrgDb, keyType = "ENTREZID", ont = "MF",
         pvalueCutoff = 0.05, pAdjustMethod = "BH", universe, qvalueCutoff = 0.2,
         minGSSize = 10, maxGSSize = 500, readable = FALSE, pool = FALSE)
```

Arguments

<code>gene</code>	a vector of entrez gene id.
<code>OrgDb</code>	<code>OrgDb</code>
<code>keyType</code>	keytype of input gene
<code>ont</code>	One of "MF", "BP", and "CC" subontologies.
<code>pvalueCutoff</code>	Cutoff value of pvalue.
<code>pAdjustMethod</code>	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
<code>universe</code>	background genes
<code>qvalueCutoff</code>	qvalue cutoff
<code>minGSSize</code>	minimal size of genes annotated by Ontology term for testing.
<code>maxGSSize</code>	maximal size of genes annotated for testing
<code>readable</code>	whether mapping gene ID to gene Name
<code>pool</code>	If <code>ont='ALL'</code> , whether pool 3 GO sub-ontologies

Value

An `enrichResult` instance.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[enrichResult-class](#), [compareCluster](#)

Examples

```
## Not run:
data(geneList, package = "DOSE")
de <- names(geneList)[1:100]
yy <- enrichGO(de, 'org.Hs.eg.db', ont="BP", pvalueCutoff=0.01)
head(yy)

## End(Not run)
```

enrichKEGG

KEGG Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG categories with FDR control.

Description

KEGG Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG categories with FDR control.

Usage

```
enrichKEGG(gene, organism = "hsa", keyType = "kegg", pvalueCutoff = 0.05,
           pAdjustMethod = "BH", universe, minGSSize = 10, maxGSSize = 500,
           qvalueCutoff = 0.2, use_internal_data = FALSE)
```

Arguments

gene	a vector of entrez gene id.
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
pvalueCutoff	Cutoff value of pvalue.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff
use_internal_data	logical, use KEGG.db or latest online KEGG data

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <http://ygc.name>

See Also

[enrichResult-class](#), [compareCluster](#)

Examples

```
data(geneList, package='DOSE')
de <- names(geneList)[1:100]
yy <- enrichMKEGG(de, pvalueCutoff=0.01)
head(yy)
```

enrichMKEGG

KEGG Module Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG Module categories with FDR control.

Description

KEGG Module Enrichment Analysis of a gene set. Given a vector of genes, this function will return the enrichment KEGG Module categories with FDR control.

Usage

```
enrichMKEGG(gene, organism = "hsa", keyType = "kegg", pvalueCutoff = 0.05,
            pAdjustMethod = "BH", universe, minGSSize = 10, maxGSSize = 500,
            qvalueCutoff = 0.2)
```

Arguments

gene	a vector of entrez gene id.
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
pvalueCutoff	Cutoff value of pvalue.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of genes annotated for testing
qvalueCutoff	qvalue cutoff

Value

A `enrichResult` instance.

```
fortify.compareClusterResult  
  fortify
```

Description

convert compareClusterResult to a data.frame that ready for plot

Usage

```
## S3 method for class 'compareClusterResult'  
fortify(model, data, showCategory = 5,  
        by = "geneRatio", split = NULL, includeAll = TRUE)
```

Arguments

model	compareClusterResult object
data	not use here
showCategory	category numbers
by	one of geneRatio, Percentage or count
split	ONTOLOGY or NULL
includeAll	logical

Value

data.frame

Author(s)

Guangchuang Yu

```
getGOLevel           get GOIDs at a specific level
```

Description

query GOIDs at a specific level.

Usage

```
getGOLevel(ont, level)
```

Arguments

ont	Ontology
level	GO level

Value

a vector of GOIDs

Author(s)

Guangchuang Yu <http://guangchuangyu.github.io>

Gff2GeneTable

Gff2GeneTable

Description

read GFF file and build gene information table

Usage

```
Gff2GeneTable(gffFile, compress = TRUE)
```

Arguments

gffFile	GFF file
compress	compress file or not

Details

given a GFF file, this function extracts information from it and save it in working directory

Value

file save.

Author(s)

Yu Guangchuang

go2ont

go2ont

Description

convert goid to ontology (BP, CC, MF)

Usage

```
go2ont(goid)
```

Arguments

goid	a vector of GO IDs
------	--------------------

Value

data.frame

Author(s)

Guangchuang Yu

go2term

go2term

Description

convert goid to descriptive term

Usage

`go2term(goid)`

Arguments

goid a vector of GO IDs

Value

data.frame

Author(s)

Guangchuang Yu

gofilter

gofilter

Description

filter GO enriched result at specific level

Usage

`gofilter(x, level = 4)`

Arguments

x output from enrichGO or compareCluster
level GO level

Value

updated object

Author(s)

Guangchuang Yu

groupGO	<i>Functional Profile of a gene set at specific GO level. Given a vector of genes, this function will return the GO profile at a specific level.</i>
---------	--

Description

Functional Profile of a gene set at specific GO level. Given a vector of genes, this function will return the GO profile at a specific level.

Usage

```
groupGO(gene, OrgDb, keyType = "ENTREZID", ont = "CC", level = 2,
        readable = FALSE)
```

Arguments

gene	a vector of entrez gene id.
OrgDb	OrgDb
keyType	key type of input gene
ont	One of "MF", "BP", and "CC" subontologies.
level	Specific GO Level.
readable	if readable is TRUE, the gene IDs will mapping to gene symbols.

Value

A groupGOResult instance.

Author(s)

Guangchuang Yu <http://ygc.name>

See Also

[groupGOResult-class](#), [compareCluster](#)

Examples

```
data(gcSample)
yy <- groupGO(gcSample[[1]], 'org.Hs.eg.db', ont="BP", level=2)
head(summary(yy))
#plot(yy)
```

groupGOResult-class	<i>Class "groupGOResult" This class represents the result of functional Profiles of a set of gene at specific GO level.</i>
---------------------	---

Description

Class "groupGOResult" This class represents the result of functional Profiles of a set of gene at specific GO level.

Slots

- result GO classification result
- ontology Ontology
- level GO level
- organism one of "human", "mouse" and "yeast"
- gene Gene IDs
- readable logical flag of gene ID in symbol or not.

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

See Also

[compareClusterResult](#) [compareCluster](#) [groupGO](#)

GSEA	<i>GSEA</i>
------	-------------

Description

a universal gene set enrichment analysis tools

Usage

```
GSEA(geneList, exponent = 1, nPerm = 1000, minGSSize = 10,
      maxGSSize = 500, pvalueCutoff = 0.05, pAdjustMethod = "BH", TERM2GENE,
      TERM2NAME = NA, verbose = TRUE, seed = FALSE, by = "fgsea")
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
nPerm	number of permutations
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
pvalueCutoff	pvalue cutoff

pAdjustMethod	p value adjustment method
TERM2GENE	user input annotation of TERM TO GENE mapping, a data.frame of 2 column with term and gene
TERM2NAME	user input of TERM TO NAME mapping, a data.frame of 2 column with term and name
verbose	logical
seed	logical
by	one of 'fgsea' or 'DOSE'

Value

`gseaResult` object

Author(s)

Guangchuang Yu

`gseGO`

gseGO

Description

Gene Set Enrichment Analysis of Gene Ontology

Usage

```
gseGO(geneList, ont = "BP", OrgDb, keyType = "ENTREZID", exponent = 1,
      nPerm = 1000, minGSSize = 10, maxGSSize = 500, pvalueCutoff = 0.05,
      pAdjustMethod = "BH", verbose = TRUE, seed = FALSE, by = "fgsea")
```

Arguments

geneList	order ranked geneList
ont	one of "BP", "MF", "CC" or "GO"
OrgDb	OrgDb
keyType	keytype of gene
exponent	weight of each step
nPerm	permutation numbers
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'

Value

gseaResult object

Author(s)

Yu Guangchuang

gseKEGG

gseKEGG

Description

Gene Set Enrichment Analysis of KEGG

Usage

```
gseKEGG(geneList, organism = "hsa", keyType = "kegg", exponent = 1,
nPerm = 1000, minGSSize = 10, maxGSSize = 500, pvalueCutoff = 0.05,
pAdjustMethod = "BH", verbose = TRUE, use_internal_data = FALSE,
seed = FALSE, by = "fgsea")
```

Arguments

geneList	order ranked geneList
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
exponent	weight of each step
nPerm	permutation numbers
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
use_internal_data	logical, use KEGG.db or latest online KEGG data
seed	logical
by	one of 'fgsea' or 'DOSE'

Value

gseaResult object

Author(s)

Yu Guangchuang

gseMKEGG

gseMKEGG

Description

Gene Set Enrichment Analysis of KEGG Module

Usage

```
gseMKEGG(geneList, organism = "hsa", keyType = "kegg", exponent = 1,
          nPerm = 1000, minGSSize = 10, maxGSSize = 500, pvalueCutoff = 0.05,
          pAdjustMethod = "BH", verbose = TRUE, seed = FALSE, by = "fgsea")
```

Arguments

geneList	order ranked geneList
organism	supported organism listed in ' http://www.genome.jp/kegg/catalog/org_list.html '
keyType	one of "kegg", 'ncbi-geneid', 'ncib-proteinid' and 'uniprot'
exponent	weight of each step
nPerm	permutation numbers
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of genes annotated for testing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	pvalue adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'

Value

gseaResult object

Author(s)

Yu Guangchuang

<i>idType</i>	<i>idType</i>
---------------	---------------

Description

list ID types supported by annoDb

Usage

```
idType(orgDb = "org.Hs.eg.db")
```

Arguments

orgDb	annotation db
-------	---------------

Value

character vector

Author(s)

Guangchuang Yu

KEGG_path2extid	<i>KEGG_path2extid</i>
-----------------	------------------------

Description

query all genes in a KEGG pathway or module

Usage

```
KEGG_path2extid(keggID, species = sub("\d+$", "", keggID),  
keggType = "Path", keyType = "kegg")
```

Arguments

keggID	KEGG ID, path or module ID
species	species
keggType	one of 'Path' or 'Module'
keyType	KEGG gene type, one of "ncbi-proteinid", "ncbi-geneid", "uniprot", or "kegg"

Value

extid vector

Author(s)

guangchuang yu

ko2name	<i>ko2name</i>
---------	----------------

Description

convert ko ID to descriptive name

Usage

```
ko2name(ko)
```

Arguments

ko	ko ID
----	-------

Value

data.frame

Author(s)

guangchuang yu

merge_result	<i>merge_result</i>
--------------	---------------------

Description

merge a list of enrichResult objects to compareClusterResult

Usage

```
merge_result(enrichResultList)
```

Arguments

enrichResultList	a list of enrichResult objects
------------------	--------------------------------

Value

a compareClusterResult instance

Author(s)

Guangchuang Yu

`plotGOgraph`*plotGOgraph*

Description

plot GO graph

Usage

```
plotGOgraph(x, firstSigNodes = 10, useInfo = "all", sigForAll = TRUE,  
useFullNames = TRUE, ...)
```

Arguments

<code>x</code>	output of enrichGO or gseGO
<code>firstSigNodes</code>	number of significant nodes (retangle nodes in the graph)
<code>useInfo</code>	additional info
<code>sigForAll</code>	if TRUE the score/p-value of all nodes in the DAG is shown, otherwise only score will be shown
<code>useFullNames</code>	logical
<code>...</code>	additional parameter of showSigOfNodes, please refer to topGO

Value

GO DAG graph

Author(s)

Guangchuang Yu

See Also

[showSigOfNodes](#)

`plotting.clusterProfile`*plotting-clusterProfile*

Description

Internal plot function for plotting compareClusterResult

Usage

```
plotting.clusterProfile(clProf.reshape.df, x = ~Cluster, type = "dot",  
colorBy = "p.adjust", by = "geneRatio", title = "", font.size = 12)
```

Arguments

<code>clProf.reshape.df</code>	data frame of compareCluster result
<code>x</code>	x variable
<code>type</code>	one of dot and bar
<code>colorBy</code>	one of pvalue or p.adjust
<code>by</code>	one of percentage and count
<code>title</code>	graph title
<code>font.size</code>	graph font size

Value

ggplot object

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

`read.gmt`

read.gmt

Description

parse gmt file to a data.frame

Usage

```
read.gmt(gmtfile)
```

Arguments

<code>gmtfile</code>	gmt file
----------------------	----------

Value

data.frame

Author(s)

Guangchuang Yu

search_kegg_organism *search_kegg_organism*

Description

search kegg organism, listed in http://www.genome.jp/kegg/catalog/org_list.html

Usage

```
search_kegg_organism(str, by = "scientific_name", ignore.case = FALSE)
```

Arguments

str	string
by	one of 'kegg.code', 'scientific_name' and 'common_name'
ignore.case	TRUE or FALSE

Value

data.frame

Author(s)

Guangchuang Yu

simplify *simplify method*

Description

simplify output from enrichGO by removing redundancy of enriched GO terms
simplify output from compareCluster by removing redundancy of enriched GO terms

Usage

```
## S4 method for signature 'enrichResult'  
simplify(x, cutoff = 0.7, by = "p.adjust",  
         select_fun = min, measure = "Wang", semData = NULL)  
  
## S4 method for signature 'compareClusterResult'  
simplify(x, cutoff = 0.7, by = "p.adjust",  
         select_fun = min, measure = "Wang", semData = NULL)
```

Arguments

x	output of enrichGO
cutoff	similarity cutoff
by	feature to select representative term, selected by 'select_fun' function
select_fun	function to select feature passed by 'by' parameter
measure	method to measure similarity
semData	GOSemSimDATA object

Value

updated enrichResult object
 updated compareClusterResult object

Author(s)

Guangchuang Yu
 Guangchuang Yu

References

issue #28 <https://github.com/GuangchuangYu/clusterProfiler/issues/28>

uniprot_get	uniprot_get
-------------	-------------

Description

retreve annotation data from uniprot

Usage

```
uniprot_get(taxID)
```

Arguments

taxID	taxonomy ID
-------	-------------

Value

gene table data frame

Author(s)

guangchuang yu

viewKEGG	<i>viewKEGG function is for visualize KEGG pathways works with enrichResult object to visualize enriched KEGG pathway</i>
----------	---

Description

viewKEGG function is for visualize KEGG pathways works with enrichResult object to visualize enriched KEGG pathway

Usage

```
viewKEGG(obj, pathwayID, foldChange, color.low = "green",
         color.high = "red", kegg.native = TRUE, out.suffix = "clusterProfiler")
```

Arguments

obj	enrichResult object
pathwayID	pathway ID or index
foldChange	fold change values
color.low	color of low foldChange genes
color.high	color of high foldChange genes
kegg.native	logical
out.suffix	suffix of output file

References

Luo et al. (2013) Pathview: an R/Bioconductor package for pathway-based data integration and visualization. *Bioinformatics* (Oxford, England), 29:14 1830–1831, 2013. ISSN 1367-4803 <http://bioinformatics.oxfordjournals.org/content/abstract/29/14/1830.abstract> PMID: 23740750

Index

*Topic **classes**
 compareClusterResult-class, 6
 groupGOResult-class, 17

*Topic **datasets**
 DataSet, 6

*Topic **manip**
 compareCluster, 5
 enrichGO, 10
 enrichKEGG, 11
 groupGO, 16

bitr, 3
bitr_kegg, 3
browseKEGG, 4
buildGOmap, 4

clusterProfiler
 (clusterProfiler-package), 2

clusterProfiler-package, 2

compareCluster, 5, 6, 10, 11, 16, 17
compareClusterResult, 17
compareClusterResult-class, 6

DataSet, 6
dotplot, compareClusterResult, ANY-method
 (dotplot, compareClusterResult-method), 7

dotplot, compareClusterResult-method, 7
download_KEGG, 7
dropGO, 8

enrichDAVID, 8
enricher, 9
enrichGO, 5, 10
enrichKEGG, 11
enrichMKEGG, 12
enrichResult, 6

fortify.compareClusterResult, 13

gcSample (DataSet), 6
getGOLevel, 13
Gff2GeneTable, 14
go2ont, 14
go2term, 15

gofilter, 15
groupGO, 5, 16, 17
groupGOResult, 6
groupGOResult-class, 17
GSEA, 17
gseGO, 18
gseKEGG, 19
gseMKEGG, 20

idType, 21

KEGG_path2extid, 21
kegg_species (DataSet), 6
ko2name, 22

merge_result, 22

plot, compareClusterResult-method
 (compareClusterResult-class), 6

plotGOgraph, 23
plotting.clusterProfile, 23

read.gmt, 24

search_kegg_organism, 25
show, compareClusterResult-method
 (compareClusterResult-class), 6

show, groupGOResult-method
 (groupGOResult-class), 17

showSigOfNodes, 23
simplify, 25
simplify, compareClusterResult-method
 (simplify), 25

simplify, enrichResult-method
 (simplify), 25

summary, compareClusterResult-method
 (compareClusterResult-class), 6

uniprot_get, 26

viewKEGG, 26