

# Package ‘pfamAnalyzeR’

January 1, 2026

**Type** Package

**Title** Identification of domain isotypes in pfam data

**Version** 1.11.0

**Description** Protein domains is one of the most import annoation of proteins we have with the Pfam database/tool being (by far) the most used tool. This R package enables the user to read the pfam prediction from both webserver and stand-alone runs into R. We have recently shown most human protein domains exist as multiple distinct variants termed domain isotypes. Different domain isotypes are used in a cell, tissue, and disease-specific manner. Accordingly, we find that domain isotypes, compared to each other, modulate, or abolish the functionality of a protein domain. This R package enables the identification and classification of such domain isotypes from Pfam data.

**License** MIT + file LICENSE

**Depends** R (>= 4.3.0), readr, stringr, dplyr

**Imports** utils, tibble, magrittr

**Encoding** UTF-8

**LazyData** false

**RoxygenNote** 7.2.1

**Suggests** BiocStyle, knitr, rmarkdown

**VignetteBuilder** knitr

**biocViews** AlternativeSplicing, TranscriptomeVariant,  
BiomedicalInformatics, FunctionalGenomics, SystemsBiology,  
Annotation, FunctionalPrediction, GenePrediction, DataImport

**BugReports** <https://github.com/kvittingseerup/pfamAnalyzeR/issues>

**git\_url** <https://git.bioconductor.org/packages/pfamAnalyzeR>

**git\_branch** devel

**git\_last\_commit** 52a663f

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-12-31

**Author** Kristoffer Vitting-Seerup [cre, aut] (ORCID:  
    <https://orcid.org/0000-0002-6450-0608>)  
**Maintainer** Kristoffer Vitting-Seerup <k.vitting.seerup@gmail.com>

Contents

|                                 |          |
|---------------------------------|----------|
| analyse_pfam_isotypes . . . . . | 2        |
| augment_pfam . . . . .          | 3        |
| pfamAnalyzeR . . . . .          | 3        |
| read_pfam . . . . .             | 4        |
| <b>Index</b>                    | <b>5</b> |

---

|                       |                                 |
|-----------------------|---------------------------------|
| analyse_pfam_isotypes | <i>Determine domain isotype</i> |
|-----------------------|---------------------------------|

---

Description

Determine domain isotype

Usage

```
analyse_pfam_isotypes(pfamRes, fracCutoff = 0.1)
```

Arguments

- |            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| pfamRes    | A data frame with pfam augmneted with indel and truncation info (as produced by augment_pfam).      |
| fracCutoff | The fraction of a protein domain that must be affected before classifying it a truncation or indel. |

Value

The data.frame with the Pfam results now augmented with info about domain domain isotype

Examples

```
### Load pfam data
pfamResultFile <- system.file("extdata/pfam_results.txt", package = "pfamAnalyzeR")
pfamRes <- read_pfam(pfamResultFile)

### Augment the pfam data
pfamRes <- augment_pfam(pfamRes)

### Predict domain isotype
pfamRes <- analyse_pfam_isotypes(pfamRes)
```

---

|              |                                                                |
|--------------|----------------------------------------------------------------|
| augment_pfam | <i>Augment pfam domains with truncation/indel calculations</i> |
|--------------|----------------------------------------------------------------|

---

**Description**

Augment pfam domains with truncation/indel calculations

**Usage**

```
augment_pfam(pfamRes)
```

**Arguments**

pfamRes            A data frame with pfam results as produced by read\_pfam.

**Value**

The data.frame with the Pfam results now augmented with info on trunkation and indel sizes

**Examples**

```
### Load pfam data
pfamResultFile <- system.file("extdata/pfam_results.txt", package = "pfamAnalyzeR")
pfamRes <- read_pfam(pfamResultFile)

### Augment the pfam data
pfamRes <- augment_pfam(pfamRes)
```

---

|              |                                                  |
|--------------|--------------------------------------------------|
| pfamAnalyzeR | <i>Read in and analyze pfam domains isotypes</i> |
|--------------|--------------------------------------------------|

---

**Description**

Read in and analyze pfam domains isotypes

**Usage**

```
pfamAnalyzeR(path, fracCutoff = 0.1)
```

**Arguments**

path            A string indicating the full path to the Pfam result file

fracCutoff      The fraction of a protein domain that must be affected before classifying it a truncation or indel.

**Value**

The data.frame with the Pfam results now augmented with info about domain structural variation

**Examples**

```
### Predict domain isotypes in pfam results
pfamResultFile <- system.file("extdata/pfam_results.txt", package = "pfamAnalyzeR")
pfamRes <- pfamAnalyzeR(pfamResultFile)
```

---

|           |                              |
|-----------|------------------------------|
| read_pfam | <i>Read Pfam file into R</i> |
|-----------|------------------------------|

---

**Description**

Read Pfam result file into R. Supports both result files from local and web-server

**Usage**

```
read_pfam(path)
```

**Arguments**

path                      A string indicating the full path to the Pfam result file

**Details**

The pfam webserver can be found at <https://www.ebi.ac.uk/Tools/hmmer/search/hmmsearch>.

**Value**

A data.frame with the Pfam results

**Examples**

```
pfamResultFile <- system.file("extdata/pfam_results.txt", package = "pfamAnalyzeR")
pfamRes <- read_pfam(pfamResultFile)
```

# Index

`analyse_pfam_isotypes`, [2](#)

`augment_pfam`, [3](#)

`pfamAnalyzeR`, [3](#)

`read_pfam`, [4](#)