

Package ‘proBAMr’

August 28, 2025

Type Package
Title Generating SAM file for PSMs in shotgun proteomics data
Version 1.42.0
Date 2024-03-19
Author Xiaojing Wang
Maintainer Xiaojing Wang <xiaojing.wang@vanderbilt.edu>
Description Mapping PSMs back to genome. The package builds SAM file from shotgun proteomics data The package also provides function to prepare annotation from GTF file.
License Artistic-2.0
Depends R (>= 3.0.1), IRanges, AnnotationDbi
Imports GenomicRanges, Biostrings, GenomicFeatures, txdbmaker, rtracklayer
Suggests RUnit, BiocGenerics
biocViews ImmunoOncology, Proteomics, MassSpectrometry, Software, Visualization
NeedsCompilation no
git_url <https://git.bioconductor.org/packages/proBAMr>
git_branch RELEASE_3_21
git_last_commit fb3cc99
git_last_commit_date 2025-04-15
Repository Bioconductor 3.21
Date/Publication 2025-08-27

Contents

PrepareAnnotationGENCODE	2
PSMtab2SAM	3
Index	4

PrepareAnnotationGENCODE

prepare annotation from GENCODE

Description

prepare the annotation from GENCODE. Download GTF and FASTA files from GENCODE ftp first. Read introduction for more information.

Usage

```
PrepareAnnotationGENCODE(gtffile, CDSfasta, pepfasta, annotation_path,
  dbsnp = NULL, splice_matrix = FALSE, COSMIC = FALSE, ...)
```

Arguments

gtffile	specify GTF file location.
CDSfasta	path to the fasta file of coding sequence.
pepfasta	path to the fasta file of protein sequence.
annotation_path	specify a folder to store all the annotations.
dbsnp	specify a snp dataset to be used for the SNP annotation, default is NULL. (e.g. "snp135")
splice_matrix	whether generate a known exon splice matrix from the annotation. this is not necessary if you don't want to analyse junction results, default is FALSE.
COSMIC	whether to download COSMIC data, default is FALSE.
...	additional arguments

Value

several .RData files containing annotations needed for further analysis.

Author(s)

Xiaoqing Wang

Examples

```
gtffile <- system.file("extdata", "test.gtf", package="proBAMr")
CDSfasta <- system.file("extdata", "coding_seq.fasta", package="proBAMr")
pepfasta <- system.file("extdata", "pro_seq.fasta", package="proBAMr")
annotation_path <- tempdir()
PrepareAnnotationGENCODE(gtffile, CDSfasta, pepfasta,
  annotation_path, dbsnp=NULL,
  splice_matrix=FALSE, COSMIC=FALSE)
```

PSMtab2SAM

*Generate SAM files from PSMs.***Description**

Generate SAM files from confident peptide-spectrum-matches (PSMs).

Usage

```
PSMtab2SAM(passedPSM, XScolumn = "mvh", exon_anno, proteinseq, procodingseq,
...)
```

Arguments

passedPSM	a data frame of PSMs passed FDR.
XScolumn	specify the column which represents the matching score.
exon_anno	a dataframe of exon annotations.
proteinseq	a dataframe containing protein ids and protein sequences.
procodingseq	a data frame cotaining coding sequence for each protein.
...	additional arguments

Value

a dataframe containing

Author(s)

Xiaojing Wang

Examples

```
load(system.file("extdata/GENCODE", "exon_anno.RData", package="proBAMr"))
load(system.file("extdata/GENCODE", "proseq.RData", package="proBAMr"))
load(system.file("extdata/GENCODE", "procodingseq.RData",
  package="proBAMr"))
options(stringsAsFactors=FALSE)
passedPSM <- read.table(system.file("extdata", "passedPSM.tab",
  package="proBAMr"), sep='\t', header=TRUE)
SAM <- PSMtab2SAM(passedPSM, XScolumn='mvh', exon, proteinseq,
  procodingseq)
write.table(SAM, file=paste(tempdir(), '/test.sam', sep=''),
  sep='\t', quote=FALSE, row.names=FALSE, col.names=FALSE)
```

Index

PrepareAnnotationGENCODE, [2](#)
PSMtab2SAM, [3](#)