

Package ‘ReportingTools’

October 9, 2013

Title Tools for making reports in various formats

Version 2.0.1

Author Jason A. Hackney, Melanie Huntley, Jessica L. Larson, Christina Chaivorapol, Gabriel Becker, and Josh Kaminker

Maintainer Jason A. Hackney <hackney.jason@gene.com>, Gabriel Becker <gmbecker@ucdavis.edu>

Depends methods

Imports

Biobase,hwriter,Category,GOstats,limma,lattice,AnnotationDbi,edgeR,annotate,PFAM.db,GSEABase,BiocGenerics(>= 0.1.6), grid, XML,R.utils, ggplot2, ggbio

Suggests RUnit, ggplot2, ggbio, ALL, hgu95av2.db, org.Mm.eg.db, knitr

Type Package

LazyLoad yes

License Artistic-2.0

Description The ReportingTools software package enables users to easily display reports of analysis results generated from sources such as microarray and sequencing data. The package allows users to create HTML pages that may be viewed on a web browser such as Safari, or in other formats readable by programs such as Excel. Users can generate tables with sortable and filterable columns, make and display plots, and link table entries to other data sources such as NCBI or larger plots within the HTML page. Using the package, users can also produce a table of contents page to link various reports together for a particular project that can be viewed in a web browser.

ByteCompile TRUE

biocViews Bioinformatics, Software, Visualization, Microarray, RNAseq,GO

VignetteBuilder utils, knitr

R topics documented:

BaseReport-class	2
CSVFile	3
CSVFile-class	4
DataPackage	5
DataPackage-class	6
filename-methods	7
finish-methods	7
HTMLReport-class	8
HTMLReportRef-class	9
Link	10
makeDESeqDF	11
makeOldHTMLReport	12
mockRnaSeqData	13
modifyReportDF-methods	14
objectToHTML-methods	14
publish-methods	15
readReport	17
ReportHandlers-class	18
reporting.theme	19
reporting.theme.alternate	20
toReportDF-methods	20
validConnection	21
Index	22

BaseReport-class	<i>Class "BaseReport"</i>
------------------	---------------------------

Description

A ReportType defines a way of representing an R object in a different, ordered format. Several ReportTypes have been detailed in this package, including classes for HTML reports and R data packages.

Objects from the Class

Objects can be created by calls of the form `new("BaseReport", ...)`. This is an abstract class that is inherited by other ReportTypes, and should not be used directly.

Slots

shortName: A character string generally used as the filename for reports

title: A character string that gives a longer description of what the report shows.

reportDirectory: A file path that details where the report will be saved.

Methods

name signature(object = "BaseReport"): Get the shortName assigned to the report.

reportDirectory signature(object = "BaseReport"): Get the directory where the report will be generated.

reportDirectory<- signature(object = "BaseReport", value = "character"): Set the directory where the report will be generated.

show signature(object = "BaseReport"): ...

title signature(main = "BaseReport"): Return the title of the report

title<- signature(object = "BaseReport", value = "character"): Set the title of the report.

path signature(object = "BaseReport"): Get the filesystem location of the report.

See Also

[HTMLReport DataPackage CSVFile](#)

Examples

```
showClass("BaseReport")
```

CSVFile

Function for creating and initializing a CSVFile for publishing results

Description

A CSVFile is a pointer to a comma separated value file on the file system. Publishing to a CSVFile overwrites the current contents of the given CSVFile.

Usage

```
CSVFile(shortName, title = "", reportDirectory = ".")
```

Arguments

shortName	A character string giving a short title for the report. Used as the base of the filename.
reportDirectory	A character string giving the location of the report.
title	A character string giving a longer description of the report.

Value

An object of class CSVFile, which will represents a file to be written to. There are no open filehandles, and calling publish multiple times will result in the file being overwritten.

See Also

[CSVFile-class](#), [HTMLReport-class](#)

Examples

```
my.df <- data.frame(EGID = c("103", "104", "105", "106", "107"),
                   RPKM = c(4, 5, 3, 100, 75),
                   DE = c("Yes", "Yes", "No", "No", "No"))
csv.file <- CSVFile(shortName = "my_csv_file",
                   reportDirectory = "reportDirectory")
publish(my.df, csv.file)
```

CSVFile-class

Class "CSVFile"

Description

A CSVFile is a pointer to a comma separated value file on the file system. Publishing to a CSVFile overwrites the current contents of the given CSVFile.

Objects from the Class

Objects from this class...

Slots

shortName: A character string used as the base of the filename. '.csv' is appended to the shortName to make the full file name.

title: The title of the report. This doesn't appear anywhere in the output, but can be used to track the report in an R session.

reportDirectory: A file path that details where the csv file will be saved.

Extends

Class "[BaseReport](#)", directly.

Methods

filename The name of the csv file, including extension

name<- Set the name of the CSVFile object

Examples

```
showClass("CSVFile")
```

DataPackage	<i>Function for creating and initializing an object of class DataPackage.</i>
-------------	---

Description

This is a function for creating a DataPackage. Calls to publish an object to the package serialize the object to disk, adding a file to the data directory, and adding a stubbed .Rd documentation file for the dataset.

Usage

```
DataPackage(shortName, title = "", reportDirectory = ".", version = "0.0.1", dependencies = c("Biobase"
```

Arguments

shortName	A character string giving the title of the DataPackage. This is used as both the title in the DESCRIPTION file and as the directory name for the package.
reportDirectory	Where the DataPackage directory will be created.
title	A character string giving the title of the package.
version	A character string giving the version of the DataPackage.
dependencies	A character vector listing what packages the DataPackage depends on.
license	A character string detailing the license the DataPackage published under.
description	A character string giving the description of the DataPackage.
author	A character string giving the author of the package.
maintainer	A character string giving the maintainer of the package.

Value

An object of class DataPackage. As a side effect, the directory structure of the data package will also be created in the location given by reportDirectory. On publication, objects are saved to the data directory of the package, and whatever dependencies the objects imply are added to the list of package dependencies.

See Also

[DataPackage-class](#)

Examples

```
my.df <- data.frame(EGID = c("103", "104", "105", "106", "107"),
                    RPKM = c(4, 5, 3, 100, 75),
                    DE = c("Yes", "Yes", "No", "No", "No"))
data.package <- DataPackage('MyPackage', title = "My awesome package",
                           author = "J.J. Nobody", maintainer = "J.J. Nobody <nobody@nowhere.net>")
publish('my.df', data.package)
```

DataPackage-class	Class "DataPackage"
-------------------	---------------------

Description

This is a pointer to an R data package. The result should be an installable R data package, with documentation for the data objects published therein.

Objects from the Class

Objects can be created by calls of the form `new("DataPackage", ...)`.

Slots

version: The current version of the generated data package

dependencies: A character vector of packages that the data package depends on.

author: The author(s) of the data package.

maintainer: The maintainer(s) of the data package. Defaults to the same person as the author.

license: What license to use when creating the data package.

description: The description of the data package.

package.Rd: Rd string for package-level help for the generated data package.

shortName: Name of the data package.

title: The title of the package

reportDirectory: The directory in which the data package is generated.

Extends

Class "[BaseReport](#)", directly.

Methods

dependencies Retrieve the list of dependencies for the data package.

dependencies<- Set the list of dependencies for the data package.

finish This is the final step in publishing objects to the data package. It recreates the DESCRIPTION file for the data package. The package name, title, version, author, maintainer, dependencies, license and description are set from the appropriate slots in the DataPackage object.

Examples

```
my.df <- data.frame(EGID = c("103", "104", "105", "106", "107"),
  RPKM = c(4, 5, 3, 100, 75),
  DE = c("Yes", "Yes", "No", "No", "No"))
data.package <- DataPackage('MyPackage', title = "My awesome package",
  author = "J.J. Nobody", maintainer = "J.J. Nobody <nobody@nowhere.net>")
publish('my.df', data.package)

dependencies(data.package) # Returns "Biobase"
dependencies(data.package) <- c('Biobase', 'GSEABase')

finish(data.package)
```

filename-methods *Methods for getting the name of a file for a CSVFile or HTMLReport.*

Description

These methods return the filename for a report, for report types where a single file is produced.

Methods

`signature(object = "CSVFile")` Return the file name of the CSVFile. This is generated by adding '.csv' to the `shortName` of the report.

`signature(object = "HTMLReport")` Return the file name of the HTMLReport. This is generated by adding '.html' to the `shortName` of the report.

finish-methods *Finalizing reports after publishing results*

Description

This is a method for finalizing a report after results have been published. The exact nature of finalizing depends on the report type, as detailed below.

Methods

`signature(publicationType = "DataPackage")` Calling `finish` on a `DataPackage` object rewrites the `DESCRIPTION` file, making sure that all of the dependencies for the objects in the `DataPackage` are listed.

`signature(publicationType = "HTMLReport")` Calling `finish` on an `HTMLReport` calls the `hwrite` function `closePage`, which closes the body and html tags on the page and closes the connection to the file.

`signature(publicationType = "HTMLReportRef")` Calling `finish` on an `HTMLReportRef` calls all the finish handler for all `ReportHandlers` attached to the report. These handlers perform various actions depending on the desired behavior of the report.

Examples

```
my.df <- data.frame()
## html.report <- HTMLReport(shortName = "my_html_file",
##   reportDirectory = "reportDirectory")
# publish(my.df, html.report)
## finish(html.report)
```

HTMLReport-class	Class "HTMLReport"
------------------	--------------------

Description

This class has been superseded by `HTMLReportRef` and is deprecated. The `HTMLReport` constructor function now creates an `HTMLReportRef` object.

Objects from the Class

Objects can be created by calls of the form `new("HTMLReport", ...)`.

Slots

baseUrl: What is the base URL to which the `HTMLReport`'s filename is appended.

basePath: What is the base file system URI to which the `HTMLReport`'s filename is appended.

page: The connection to the html file. See `openPage` in the `hwriter` package.

shortName: A character string used as the base of the filename. `'.html'` is appended to the shortName to make the full file name.

title: The title of the `HTMLReport`. This is used as the page title in the header, and is also printed on the page.

reportDirectory: A file path that details where the report will be saved.

Extends

Class `"BaseReport"`, directly.

Methods

basePath Return the `basePath` for the `HTMLReport`

baseUrl Return the `baseUrl` for the `HTMLReport`

filename Return the file name of the `HTMLReport`. This is generated by adding `'.html'` to the `shortName` of the report.

finish This is the final step in publishing results to an `HTMLReport`. It prints the closing tags for the html body, and then closes the connection to the html file. Further calls to `publish` will fail because the connection is closed.

name<- Set the short name for the html file.

page Returns the connection to the html file.

page<- Set the connection to the html file.

validConnection Is the connection to the html file still open? If finish has been called, this will return FALSE.

HTMLReportRef-class *Class "HTMLReportRef"*

Description

A referenceClass-based representation of an HTML report generated using R objects. This class is based around a persistent, DOM-based representation of the HTML page being created, which is created during initialization and updated as the report is manipulated. `HTMLReport` is the constructor function for the class.

Details

Publication behavior of `HTMLReportRef` reports is controlled via an event-observer paradigm. Developers specify behavior in the form of one or more `ReportHandlers` objects. These objects contain instructions (in the form of R functions) to be carried out whenever certain actions are taken. These actions are: initial report creation ("init"), elements being added to the report ("addElement"), elements being removed from the report ("removeElement"), and the report being finalized ("finish"). See [ReportHandlers](#) for more detail.

Methods

[[<- signature(x = "HTMLReportRef", i = "ANY", j = "ANY", value = "ANY"): Place an element representing value into the report. This will replace any existing element by the same name in the report. `x$addElement` is used to perform the actual report manipulation.

[[signature(x = "HTMLReportRef", i = "ANY"): Access an element within the report. The element will be returned in its DOM/HTML representation.

publish signature(object = "ANY", publicationType = "HTMLReportRef"): Place an element representing object into the report. `publicationType$addElement` is used to perform the actual report manipulation.

path signature(object = "HTMLReportRef"): The paths returned by each of the `ReportHandlers` for the report.

Fields

shortName: Short version of report name.

title: Title of the report.

reportDirectory: Directory (relative to `basePath`) in which to publish the report.

basePath: Base path to publish to.

handlers: A list of `ReportHandlers` objects specifying actions to be taken in response specific events during the report creation/manipulation process. See [Details](#).

Class-Based Methods

`prepare(obj, ...)`: Prepare an R object to be added to the report by converting it to an HTML representation. Currently this is done by calling the `objectToHTML` function on the object, though this is likely to change in the future.

`initialize(...)`: Initialize the report, including generating the base HTML structure. The `init` function for each `ReportHandlers` object in `handlers` is called at the end of this process.

`addElement(name, value, ...)`: Add an element to the report. `prepare` is called to generate an HTML representation for `value`. That representation is then added to the internal DOM representation of the report. The `addElement` function for each `ReportHandlers` object in `handlers` is called at the end of this process.

`finish()`: Finalize a report. This causes the `finish` function on each element of `handlers` to be called. This is something of a misnomer in that the report can be further manipulated and "finished" again after this function has been called.

Author(s)

Gabriel Becker <gmbecker@ucdavis.edu>

See Also

[ReportHandlers](#)

Examples

```
showClass("HTMLReportRef")
```

Link

Create a table of Links

Description

This is a convenience function for creating tables of links (eg for an index page).

Usage

```
Link(obj, target = NA, report = NULL)
```

Arguments

<code>obj</code>	An object to be turned into one or more links. Typically a character vector of link text or a list of <code>HTMLReportRef</code> objects
<code>target</code>	The link targets for each created link.
<code>report</code>	«««« HEAD An optional report giving the relative path of the link target, when constructing the target path. ===== A report (<code>HTMLReportRef</code> object) whose location the generated links should be relative to. »»»» preparing to rebase for jason's changes

Details

If target is NA, Link attempts to infer the link target(s) based on obj

Value

An XMLInternalNode corresponding to HTML for either a single link or a div containing multiple links separated each on separate lines

Author(s)

Gabriel Becker

Examples

```
mylinks = Link(c("Link1", "Link2"), c("www.google.com", "www.cnn.com"))
```

makeDESeqDF

Converts DESeq results into a data frame to be published

Description

Manipulates DESeq output to a data frame of significant observations. Draws corresponding box and whisker plots.

Usage

```
makeDESeqDF(object, countTable, pvalueCutoff, conditions, annotation.db,
            expName, reportDir, ...)
```

Arguments

object	Output from nbinomTest; see DESeq manual for details
countTable	A table of the raw counts, where rows indicate genes and columns are samples
pvalueCutoff	A threshold value for what is considered a significantly different gene. Only genes with p-values less than this will be included.
conditions	A vector indicating the groupings of the samples, for image purposes.
annotation.db	A character string, indicating the species of the samples
expName	The name of the experiment
reportDir	Directory to which the report (and figures) will be written
...	Unused arguments passed in from the publish method

Details

This function converts DESeq output into a data frame and draws the corresponding images

Value

ret, A data frame with the following values: Entrez Id, Symbol, Gene Name, Image, Log2 Fold Change, P-value and Adjusted p-value.

Author(s)

Jessica Larson

Examples

```
#library(DESeq)
#library(lattice)
#data(mockRnaSeqData)
#conditions <- c(rep("case",3), rep("control", 3))
#cds<-newCountDataSet(mockRnaSeqData, conditions)
#cds<-estimateSizeFactors(cds)
#cds<-estimateDispersions(cds)
#res<-nbinomTest(cds,"control", "case" )

#desReport <- HTMLReport(shortName = 'RNAseq_analysis_with_DESeq',
  #title = 'RNA-seq analysis of differential expression using DESeq',
  #reportDirectory = "./reports")
#publish(res,desReport,name="df",countTable=mockRnaSeqData, pvalueCutoff=0.05, #conditions=conditions,annotat
#finish(desReport)
```

makeOldHTMLReport *Creating and initializing an HTMLReport object*

Description

This is the function one should use to instantiate an HTMLReport. It basically creates the report in the appropriate place, creating directories if needed. Special care should be taken if non-default javascript or css files are used, as detailed below.

Usage

```
makeOldHTMLReport(shortName, title = NULL, reportDirectory = ".", baseUrl = "localhost", basePath = NUL
```

Arguments

shortName	A short name for the report. It is used as the base of the HTML file.
title	The title for the page. It will be used in the title element in the page head, and will also be written at the top of the page.
reportDirectory	A character string giving the directory where the report will be written.
baseUrl	A character string giving the location of the page in terms of HTML locations.

basePath	A character string giving the location of the page in terms of filesystem locations.
page	The file handle for the html page, returned from the <code>hwriter</code> function <code>openPage</code> .
link.css	A character vector of file URLs detailing where to get style sheets. If unset, the default styling for ReportingTools is used.
link.javascript	A character vector of file URLs detailing where to get javascript. If unset, the default javascript libraries for ReportingTools are used.
overwrite.js	logical whether css and javascript files should be overwritten when copied into the report directory.

Details

Care should be used if `link.javascript` or `link.css` are set. If the javascript libraries for ReportingTools aren't linked, then it is likely that the resulting pages will not be as interactive as the default. The default css files are found in the `extdata/csslib` directory of the ReportingTools package, while the default javascript libraries are found in the `extdata/jslib` directory of the ReportingTools package. The default behavior is for the css and js files to be copied from the package directory into the `reportDirectory` of the HTMLReport. If these are copied to an alternate location, then the user can set the environment variables `REPORTINGTOOLSCSSLIB` and `REPORTINGTOOLSJSLIB` to point to the locations of the css and javascript files, respectively.

Value

An HTMLReport object with an open file handle to an HTML page.

See Also

[HTMLReport-class](#), [publish](#)

Examples

```
my.df <- data.frame(EGID = c("103", "104", "105", "106", "107"),
                  RPKM = c(4, 5, 3, 100, 75),
                  DE = c("Yes", "Yes", "No", "No", "No"))
html.report <- makeOldHTMLReport(shortName = "my_html_file",
                                reportDirectory = "reportDirectory")
publish(my.df, html.report)
```

mockRnaSeqData

A counts table of mock RNA-seq data in mouse.

Description

Expression data from an RNA-seq experiment. Rows were randomly assigned mouse Entrez ids.

Usage

```
data(mockRnaSeqData)
```

Examples

```
data(mockRnaSeqData)
```

```
modifyReportDF-methods
```

Decorate the Basic data.frame Representation of an Object

Description

This function is called after toReportDF (or the overriding.toDF if it is specified) in order to transform the basic data.frame into the form that will appear in the report. This typically includes transforming columns into links, adding image columns, etc. Each class publishable by ReportingTools should have either a custom objectToHTML method (which supercedes toReportDF and modifyReportDF) or a custom toReportDF and modifyReportDF methods which construct a dataframe to be placed in the report as an HTML table.

Methods

signature(df = "ANY", htmlRep = "ANY", object = "ANY") The default method is simply a placeholder, and returns the data.frame unchanged.

```
objectToHTML-methods    Transform R objects into HTML form to be inserted in HTML reports
```

Description

Unless overridden by a .toHTML argument, this function is called to transform objects being published into HTML form before they are inserted into a report.

Methods

signature(object = "ANY") The default method for objectToHTML calls toReportDF (or the overriding .toDF) then modifyReportDF (or the overriding .modifyDF) to create a data.frame to be published. The data.frame method of objectToHTML is then called.

signature(object = "character") If the character vector contains HTML code (determined by attempted parsing), it is parsed but otherwise unchanged. If not, it is added as content to a new <p> HTML node.

signature(object = "data.frame") The data.frame is transformed into a filterable, sortable HTML table

signature(object = "ggbio") The graphic is written to the report's figure directory and an <image> tag to display the image is returned

signature(object = "ggplot") The graphic is written to the report's figure directory and an <image> tag to display the image is returned

signature(object = "recordedplot") The graphic is written to the report's figure directory and an <image> tag to display the image is returned

signature(object = "trellis") The graphic is written to the report's figure directory and an <image> tag to display the image is returned

publish-methods	<i>Methods for publishing a variety of data types in selected output formats</i>
-----------------	--

Description

These are a series of methods for taking various data types and coercing them into selected output formats.

Methods

Data types can be output in several formats. Exactly what is done to coerce a data type into the given output format is described below.

data.frame:

publish(object, htmlReport, tableTitle = NULL, ...) The most basic object to publish to an HTMLReport is a data.frame. Most other methods involve coercing their objects to a data.frame and then calling publish on that data.frame. As such, this is where all styling for publishing tables can be centrally controlled. If tableTitle is specified, the title is printed above the table.

MArrayLM:

publish(object, htmlReport, eSet, factor, n = 1000, pvalueCutoff = 0.01, lfc = 0, coef = NULL, ...) An MArrayLM object is coerced to a data.frame using a method similar to the topTable function from the limma package. The resulting table includes some selected feature data, and the log fold change and adjusted p-value from the linear model. The p-value adjustment method is set using the "adjust.method" argument. A glyph showing expression levels of each gene are also optionally plotted, based on the expression values from the ExpressionSet given in eSet, and the levels set in factor.

DGEEExact:

publish(object, htmlReport, countTable, conditions, annotation.db = "org.Hs.eg", n = 1000, pvalueCutoff = 0.01, lfc = 0, coef = NULL, ...) DGEEExact objects are coerced to a data.frame using the topTags function from the edgeR package and filtered based on pvalueCutoff and lfc. The resulting table includes feature data, derived from the annotation package defined in annotation.db, along with the fold change and adjusted p-value. For this to work, the feature names in the DGEEExact object and the countTable have to be the primary identifier from the annotation package. In most cases, the primary identifier will be Entrez Gene IDs. If no valid annotation package name is provided in annotation.db, then feature data will come from the "genes" slot in the DGEEExact object. The counts stored in countTable should be in units of counts per million provided by the cpm function

in the edgeR package. The p-value adjustment method can be set using the “adjust.method” argument.

DGELRT:

```
publish(object, htmlReport, countTable, conditions, annotation.db = "org.Hs.eg", n = 1000, pva
```

DGELRT objects are coerced to a data.frame using the topTags function from the edgeR package and filtered based on pvalueCutoff and lfc. The resulting table includes feature data, derived from the annotation package defined in annotation.db, along with the fold change and adjusted p-value. For this to work, the feature names in the DGELRT object and the countTable have to be the primary identifier from the annotation package. In most cases, the primary identifier will be Entrez Gene IDs. If no valid annotation package name is provided in annotation.db, then feature data will come from the “genes” slot in the DGEEExact object. The counts stored in countTable should be in units of counts per million provided by the cpm function in the edgeR package. The p-value adjustment method can be set using the “adjust.method” argument.

HyperGResultBase, GOHyperGResult, PFAMHyperGResult:

```
publish(object, htmlReport, selectedIDs, annotation.db, pvalueCutoff = 0.01, categorySize=10,
```

A HyperGResult object is coerced to a data.frame using a method similar to the summary function from the Category package. The resulting table includes for each classification the id, name, odds ratio of enrichment and p-value from the hypergeometric test. A glyph showing the level of overlap of each classification with the selected genes is also plotted. The number of genes found in this classification is listed in the table and links to another page with a table of the corresponding genes, symbols and names. An additional page listing the overlap genes is also linked to the main output. For a GOHyperGResult object, a plot depicting the relationship between the significant ontologies and their parents is also plotted if makePlot is TRUE. The selectedIDs are the Entrez ids of the genes of interest (i.e. from the gene universe); annotation.db is the species of the ids.

GeneSetCollection:

```
publish(object, htmlReport, annotation.db, setStats=NULL, setPValues=NULL,...)
```

A GeneSetCollection object is coerced to a data.frame. The resulting table of set names includes links to additional pages containing the ids, names and symbols of each gene in the corresponding set. If GSEA statistics and/or p-values are provided, then they are also included in the gene set table. The genes within the GeneSetCollection must be Entrez ids and annotation.db is the species of the ids.

trellis:

```
publish(object, publicationType, figureTitle = NULL, filename = NULL, png.height = 480, png.wi
```

Trellis objects, as created by lattice functions are published to an HTMLReport by first printing a pdf and png version of the object, and then including the png image in the HTML page, linking it to the pdf version of the plot.

Special cases:

There are a few special types that can be published to a HTMLReport. Publishing an HTMLReport to another HTMLReport will create a link from one report to the other, using the title of the published report as the link text.

HTMLReport or HTMLReportDataPackage There are two ways to publish R objects to a DataPackage: by using a character vector of object names, or by calling publish on the object directly, providing a name to use in saving the object. For most object types, basic documentation is created for the object in the data package, using the promptData function.

CSVFile data.frames can be published directly to csv files. Other data types, such as MArrayLM, DGEEExact, GOHyperGResult, PFAMHyperGResult can be output as CSVFile, by means of coercion to a data.frame first.

Examples

```
my.df <- data.frame()
## html.report <- HTMLReport(shortName = "my_html_file",
##   reportDirectory = "reportDirectory")
# publish(my.df, html.report)
## finish(html.report)
```

readReport	<i>Read in an Existing Report</i>
------------	-----------------------------------

Description

This function is used to read an existing Report (previously created using ReportingTools) into R so that it can be modified or computed on.

Usage

```
readReport(reportFile, handlers = fileHandlers(reportFile),
  .toHTML = NULL, .toDF = NULL, .modifyDF = NULL, title)
```

Arguments

reportFile	A character value pointing to the HTML file containing an existing Report.
handlers	The ReportHandlers object(s) to attach to the resulting HTMLReportRef object.
.toHTML	The list of .toHTML overrides to attach to the HTMLReportRef object
.toDF	The list of .toDF overrides to attach to the HTMLReportRef object
.modifyDF	The list of .modifyDF overrides to attach to the HTMLReportRef object
title	Title to assign to the new HTMLReportRef object. If not specified this value is inferred from the file.

Value

An HTMLReportRef object representing the Report.

Note

Attempting to write the modified report to a new location without updating any report elements involving figures will result in broken image links because image locations are assumed to be relative to the location of the HTML file.

Author(s)

Gabriel Becker

See Also

[HTMLReportRef](#)

 ReportHandlers-class *Class "ReportHandlers"*

Description

A set of event-handler functions to be called when certain actions are performed on a HTMLReportRef object.

Details

ReportingTools ships with a number of predefined ReportHandlers constructorslo functions which generate ReportHandlers objects which implement commonly desired behaviors:

fileHandlers Accepts destination file location in the form of a character value, which is stored in the object's location slot. Report is built up internally and written to a file via the finish observer.

fileWIndexHandlers As with fileHandlers except that a table of contents is appended to the beginning of the report with links to each element within the page. Link text is the element names

connectionHandlers Accepts a connection to which the report should be streamed (which is stored in the location slot). Report is streamed out to the provided connection as elements are added to the report. codefinish completes the page and closes the connection.

knitrHandlers Accepts an option filename argument which will be stored as the location slot, but is not used internally. Elements are streamed in HTML form to standard output, which is captured by knitr and inserted into the page, allowing ReportingTools to be used as a formatting mechanism to publish objects within a knitr document and have them displayed correctly. Note: location MUST match the output file actually generated by the knitr/knit2html call (at least up to destination directory). If it does not the resulting page will not function properly.

shinyHandlers These handlers allow ReportingTools to be used as a formatting mechanism within a shiny Web application. Note in this case there is no meaningful HTML file being created that represents the report. location is set to NULL as no meaningful location exists in the shiny case.

Objects from the Class

Objects can be created by calls of the form `new("ReportHandlers", ...)`.

Slots

init: A function to be called when the report is initialized/created

addElement: A function to be called when an element is added/published to the report

removeElement: A function to be called when an element is removed from the report

finish: A function to be called when the report is "finished"

args: A named list containing zero or more of the elements "init", "addElement", "removeElement", and "finish", which contain additional arguments to be passed to the respective functions when called.

location: An R object indicating the location these handlers will publish the report to. The exact meaning of this argument depends on the behavior of the handlers.

Methods

path signature(object = "ReportHandlers"): For file handlers, the file system location where the file will be written. For all others, NULL.

Methods

path Returns the location associated with these ReportHandlers

Author(s)

Gabriel Becker <gmbecker@ucdavis.edu>

See Also

[HTMLReportRef](#)

Examples

```
showClass("ReportHandlers")
```

reporting.theme

Color theme for use in ReportingTools

Description

Getting some attractive colors for use in lattice graphics

Usage

```
reporting.theme()
```

Value

A list with slots as defined by the lattice function `standard.theme`

See Also

[standard.theme](#)

Examples

```
library(lattice)
theme <- reporting.theme()
lattice.options(default.theme = theme)
```

```
reporting.theme.alternate
```

Alternate color theme for use in ReportingTools

Description

Getting some alternate attractive colors for use in lattice graphics

Usage

```
reporting.theme.alternate()
```

Value

A list with slots as defined by the lattice function `standard.theme`

See Also

[standard.theme](#)

Examples

```
library(lattice)
theme <- reporting.theme.alternate()
lattice.options(default.theme = theme)
```

```
toReportDF-methods
```

Class Specific Default Behavior for Transforming Objects to data.frames

Description

The `toReportDF` generic and its methods are used to transform objects into a basic tabular (`data.frame`) form as part of the two step process of preparing to insert them into a report. This function (and functions passed to the `.toDF` argument used to override it) will only be called during the default ("ANY") `objectToHTML` method. Non-default `objectToHTML` methods are expected to perform the entire process of creating HTML code from an R object.

Note

The default `toReportDF` method is equivalent to calling `as.data.frame`.

See Also

[modifyReportDF](#)

validConnection	<i>Determine connection validity</i>
-----------------	--------------------------------------

Description

Determine if a connection to an HTML page can be written to or not.

Usage

```
validConnection(htmlRep)
```

Arguments

htmlRep An object of class HTMLReport.

Value

Returns TRUE if the page can be written to. If the file handle has been closed, then FALSE.

See Also

```
link{HTMLReport-class}
```

Examples

```
my.df <- data.frame(EGID = c("103", "104", "105", "106", "107"),
                   RPKM = c(4, 5, 3, 100, 75),
                   DE = c("Yes", "Yes", "No", "No", "No"))
html.report <- makeOldHTMLReport(shortName = "my_html_file",
                                reportDirectory = "reportDirectory")
publish(my.df, html.report)
validConnection(html.report) # Returns TRUE

finish(html.report)
validConnection(html.report) # Returns FALSE
```

Index

- *Topic **HTML**
 - Link, 10
 - objectToHTML-methods, 14
- *Topic **Link**
 - Link, 10
- *Topic **Report**
 - objectToHTML-methods, 14
- *Topic **\textasciitilde\textasciitilde**
other possible keyword(s)
\textasciitilde\textasciitilde
 - modifyReportDF-methods, 14
- *Topic **\textasciitildekw1**
 - readReport, 17
- *Topic **\textasciitildekw2**
 - readReport, 17
- *Topic **classes**
 - BaseReport-class, 2
 - CSVFile-class, 4
 - DataPackage-class, 6
 - HTMLReport-class, 8
 - HTMLReportRef-class, 9
 - ReportHandlers-class, 18
- *Topic **data.frame**
 - toReportDF-methods, 20
- *Topic **datasets**
 - mockRnaSeqData, 13
- *Topic **methods**
 - filename-methods, 7
 - finish-methods, 7
 - modifyReportDF-methods, 14
 - publish-methods, 15
 - toReportDF-methods, 20
- *Topic **publish**
 - objectToHTML-methods, 14
- *Topic **report**
 - toReportDF-methods, 20
- [[, HTMLReportRef, ANY-method
(HTMLReportRef-class), 9
- [[<- , HTMLReportRef, ANY, ANY, ANY-method
(HTMLReportRef-class), 9
- basePath (HTMLReport-class), 8
- basePath, HTMLReport-method
(HTMLReport-class), 8
- BaseReport, 4, 6, 8
- BaseReport-class, 2
- baseUrl (HTMLReport-class), 8
- baseUrl, HTMLReport-method
(HTMLReport-class), 8
- connectionHandlers
(ReportHandlers-class), 18
- CSVFile, 3, 3
- CSVFile-class, 4
- DataPackage, 3, 5
- DataPackage-class, 6
- dependencies (DataPackage-class), 6
- dependencies, DataPackage-method
(DataPackage-class), 6
- dependencies<- (DataPackage-class), 6
- dependencies<- , DataPackage, character-method
(DataPackage-class), 6
- fileHandlers (ReportHandlers-class), 18
- filename (filename-methods), 7
- filename, CSVFile-method
(filename-methods), 7
- filename, HTMLReport-method
(filename-methods), 7
- filename-methods, 7
- fileWIndexHandlers
(ReportHandlers-class), 18
- finish (finish-methods), 7
- finish, DataPackage-method
(finish-methods), 7
- finish, HTMLReport-method
(finish-methods), 7
- finish, HTMLReportRef-method
(finish-methods), 7

- finish-methods, 7
- HTMLReport, 3
- HTMLReport (HTMLReportRef-class), 9
- HTMLReport-class, 8
- HTMLReportRef, 17, 19
- HTMLReportRef-class, 9
- knitrHandlers (ReportHandlers-class), 18
- Link, 10
- Link, character-method (Link), 10
- Link, HTMLReportRef-method (Link), 10
- Link, list-method (Link), 10
- Link-methods (Link), 10
- makeDESeqDF, 11
- makeOldHTMLReport, 12
- mockRnaSeqData, 13
- modifyReportDF, 20
- modifyReportDF
 - (modifyReportDF-methods), 14
- modifyReportDF, ANY, ANY, ANY-method
 - (modifyReportDF-methods), 14
- modifyReportDF, ANY, ANY, DGEEexact-method
 - (modifyReportDF-methods), 14
- modifyReportDF, ANY, ANY, DGELRT-method
 - (modifyReportDF-methods), 14
- modifyReportDF, ANY, ANY, GOHyperGResult-method
 - (modifyReportDF-methods), 14
- modifyReportDF, ANY, ANY, MArrayLM-method
 - (modifyReportDF-methods), 14
- modifyReportDF-methods, 14
- name (BaseReport-class), 2
- name, BaseReport-method
 - (BaseReport-class), 2
- name<-, BaseReport, character-method
 - (BaseReport-class), 2
- name<-, CSVFile, character-method
 - (CSVFile-class), 4
- name<-, HTMLReport, character-method
 - (HTMLReport-class), 8
- objectToHTML (objectToHTML-methods), 14
- objectToHTML, ANY-method
 - (objectToHTML-methods), 14
- objectToHTML, character-method
 - (objectToHTML-methods), 14
- objectToHTML, data.frame-method
 - (objectToHTML-methods), 14
- objectToHTML, ggbio-method
 - (objectToHTML-methods), 14
- objectToHTML, ggplot-method
 - (objectToHTML-methods), 14
- objectToHTML, recordedplot-method
 - (objectToHTML-methods), 14
- objectToHTML, trellis-method
 - (objectToHTML-methods), 14
- objectToHTML, XMLInternalNode-method
 - (objectToHTML-methods), 14
- objectToHTML-methods, 14
- page (HTMLReport-class), 8
- page, HTMLReport-method
 - (HTMLReport-class), 8
- page<- (HTMLReport-class), 8
- page<-, HTMLReport, character-method
 - (HTMLReport-class), 8
- path (BaseReport-class), 2
- path, BaseReport-method
 - (BaseReport-class), 2
- path, DataPackage-method
 - (DataPackage-class), 6
- path, HTMLReport-method
 - (HTMLReport-class), 8
- path, HTMLReportRef-method
 - (HTMLReportRef-class), 9
- path, ReportHandlers-method
 - (ReportHandlers-class), 18
- publish, 13
- publish (publish-methods), 15
- publish, ANY, DataPackage-method
 - (publish-methods), 15
- publish, ANY, HTMLReport-method
 - (publish-methods), 15
- publish, ANY, HTMLReportRef-method
 - (HTMLReportRef-class), 9
- publish, ANY, list-method
 - (publish-methods), 15
- publish, character, DataPackage-method
 - (publish-methods), 15
- publish, data.frame, CSVFile-method
 - (publish-methods), 15
- publish, data.frame, DataPackage-method
 - (publish-methods), 15
- publish, data.frame, HTMLReport-method
 - (publish-methods), 15

- publish, data.frame, HTMLReportRef-method
(publish-methods), 15
- publish, DGEEExact, ANY-method
(publish-methods), 15
- publish, DGEEExact, HTMLReport-method
(publish-methods), 15
- publish, DGEEExact, HTMLReportRef-method
(publish-methods), 15
- publish, DGELRT, ANY-method
(publish-methods), 15
- publish, DGELRT, HTMLReport-method
(publish-methods), 15
- publish, DGELRT, HTMLReportRef-method
(publish-methods), 15
- publish, GeneSetCollection, ANY-method
(publish-methods), 15
- publish, GeneSetCollection, HTMLReport-method
(publish-methods), 15
- publish, GeneSetCollection, HTMLReportRef-method
(publish-methods), 15
- publish, GOHyperGResult, ANY-method
(publish-methods), 15
- publish, GOHyperGResult, HTMLReport-method
(publish-methods), 15
- publish, GOHyperGResult, HTMLReportRef-method
(publish-methods), 15
- publish, HTMLReport, HTMLReport-method
(publish-methods), 15
- publish, HTMLReport, HTMLReportRef-method
(publish-methods), 15
- publish, HyperGResultBase, HTMLReport-method
(publish-methods), 15
- publish, HyperGResultBase, HTMLReportRef-method
(publish-methods), 15
- publish, list, HTMLReport-method
(publish-methods), 15
- publish, list, HTMLReportRef-method
(publish-methods), 15
- publish, MArrayLM, ANY-method
(publish-methods), 15
- publish, MArrayLM, HTMLReport-method
(publish-methods), 15
- publish, MArrayLM, HTMLReportRef-method
(publish-methods), 15
- publish, PFAMHyperGResult, ANY-method
(publish-methods), 15
- publish, PFAMHyperGResult, HTMLReport-method
(publish-methods), 15
- publish, PFAMHyperGResult, HTMLReportRef-method
(publish-methods), 15
- publish, trellis, HTMLReport-method
(publish-methods), 15
- publish, trellis, HTMLReportRef-method
(publish-methods), 15
- publish-methods, 15
- readReport, 17
- reportDirectory (BaseReport-class), 2
- reportDirectory, BaseReport-method
(BaseReport-class), 2
- reportDirectory<- (BaseReport-class), 2
- reportDirectory<-, BaseReport, character-method
(BaseReport-class), 2
- ReportHandlers, 9, 10
- ReportHandlers-class, 18
- reporting.theme, 19
- reporting.theme.alternate, 20
- shinyHandlers (ReportHandlers-class), 18
- show, BaseReport-method
(BaseReport-class), 2
- show, HTMLReport-method
(HTMLReport-class), 8
- standard.theme, 19, 20
- title (BaseReport-class), 2
- title, BaseReport-method
(BaseReport-class), 2
- title<- (BaseReport-class), 2
- title<-, BaseReport, character-method
(BaseReport-class), 2
- toReportDF (toReportDF-methods), 20
- toReportDF, ANY-method
(toReportDF-methods), 20
- toReportDF, data.frame-method
(toReportDF-methods), 20
- toReportDF, DGEEExact-method
(toReportDF-methods), 20
- toReportDF, DGELRT-method
(toReportDF-methods), 20
- toReportDF, GeneSetCollection-method
(toReportDF-methods), 20
- toReportDF, GOHyperGResult-method
(toReportDF-methods), 20
- toReportDF, MArrayLM-method
(toReportDF-methods), 20

toReportDF, PFAMHyperGResult-method
 (toReportDF-methods), [20](#)
toReportDF-methods, [20](#)

url, HTMLReport-method
 (HTMLReport-class), [8](#)

validConnection, [21](#)