

# Package ‘quantsmooth’

October 9, 2013

**Type** Package

**Title** Quantile smoothing and genomic visualization of array data

**Version** 1.26.0

**Date** 2012-08-18

**Author** Jan Oosting, Paul Eilers, Renee Menezes

**Maintainer** Jan Oosting <j.oosting@lumc.nl>

**Depends** R(>= 2.10.0), quantreg, grid

**Description** Implements quantile smoothing as introduced in: Quantile smoothing of array CGH data; Eilers PH, de Menezes RX; Bioinformatics. 2005 Apr 1;21(7):1146-53.

**License** GPL-2

**biocViews** Visualization, CopyNumberVariants

## R topics documented:

chrom.bands . . . . .	2
Chromosome14 . . . . .	3
drawSimpleChrom . . . . .	3
getChangedRegions . . . . .	4
getLambdaMin . . . . .	5
grid.chromosome . . . . .	6
lengthChromosome . . . . .	7
numericCHR . . . . .	8
paintCytobands . . . . .	9
plotChromosome . . . . .	10
plotSmoothed . . . . .	11
position2Cytoband . . . . .	12
prepareGenomePlot . . . . .	13
quantsmooth . . . . .	14
quantsmooth.cv . . . . .	14
quantsmooth.seg . . . . .	15
scaleto . . . . .	16

**chrom.bands***Dataset of human chromosomes and their banding patterns***Description**

Dataset used to produce human chromosomal ideograms for plotting purposes.

**Usage**

```
data(chrom.bands)
```

**Format**

A data frame with 4068 observations on the following 12 variables.

chr	a character vector
arm	a character vector
band	a character vector
ISCN.top	a numeric vector
ISCN.bot	a numeric vector
bases.top	a numeric vector
bases.bot	a numeric vector
stain	a character vector
cM.top	a numeric vector
cM.bot	a numeric vector
n.markers	a numeric vector
p.markers	a numeric vector

**Details**

The original file gives only the physical map positions. The genetic map positions are interpolated from the Rutgers linkage map (Kong et al 2004).

**Source**

[ftp://ftp.ncbi.nlm.nih.gov/genomes/H<sub>sapiens</sub>/maps/mapview/BUILD.35.1/ideogram.gz](ftp://ftp.ncbi.nlm.nih.gov/genomes/H_sapiens/maps/mapview/BUILD.35.1/ideogram.gz).

**References**

Kong X, Murphy K, Raj T, He C, White PS, Matise TC. 2004. A Combined Linkage-Physical Map of the Human Genome. *American Journal of Human Genetics*, 75(6):1143-8.

---

**Chromosome14***Example data from several quantitative genomic methods*

---

**Description**

A collection of arrays that contains data of chromosome 14 of 3 colorectal tumors. The first tumor shows 1 region of loss, the second tumor shows no abberation, while the third tumor shows loss of 1 copy of the chromosome.

**affy.cn** Copy number values of 358 probes from Affymetrix 10K genechip. Data was obtained from DChip

**affy.pos** corresponding probe positions

**bac.cn** Copy number values of 112 probes from a 1 mb spaced BAC array-CGH

**bac.pos** corresponding probe positions

**ill.cn** Copy number values of 207 probes from Illumina GoldenGate Linkage IV data

**ill.pos** corresponding probe positions

**Usage**

```
data(chr14)
```

**Format**

Matrices of copy number values and vectors of chromosomal probe positions

**Author(s)**

Jan Oosting

---

**drawSimpleChrom***Draw chromosome-like icons*

---

**Description**

This function paints chromosomal icons on an existing plot

**Usage**

```
drawSimpleChrom(x, y, len = 3, width = 1, fill, col, orientation = c("h", "v"), centromere.size = 0.6)
```

**Arguments**

x	start x-position
y	start y-position
len	total length of the chromosome
width	width of the chromosome
fill	character, {"a","p","q","q[1-3]","p[1-3]"} . Events to a chromosome can be depicted by coloring "a"ll of the chromosome, the complete p or q-arm, or a sub-segment of the arms
col	color(s) of fill
orientation	either "h"orizontal or "v"ertical
centromere.size	The size of the centromere as fraction of the width

**Value**

This function is executed for its side effects

**Author(s)**

Jan Oosting

**Examples**

```
plot(c(0,4),c(0,3),type="n",xaxt="n",yaxt="n",xlab="",ylab="")
drawSimpleChrom(2,3,fill=c("p","q3"),col=c("red","blue"),orientation="v")
```

`getChangedRegions`      *getChangedRegions*

**Description**

retrieve regions of interest in a vector of intensities using quantile smoothing

**Usage**

```
getChangedRegions(intensities, positions, normalized.to=1, interval, threshold, minlength=2, ...)
```

**Arguments**

intensities	numeric vector
positions	numeric vector of the same length as intensities. If this argument is not given the results contain the indexes of the <code>intensities</code> vector, else the values in <code>positions</code> are used. Both vectors are sorted in the order of <code>positions</code> .
normalized.to	numeric, reference value. Changes are compared to this value

interval	numeric [0,1], bandwidth around reference. If the smoothed line at the higher quantile drops below the normalized.to value, a deleted region is recognized, and vice versa.
threshold	numeric, if the median smoothed value drops below normalized.to - threshold, or above normalized.to + threshold a changed region is called
minlength	integer, not used currently
...	extra arguments for <code>quantsmooth</code> function

## Details

This function uses `quantsmooth` to detect regions in the genome that are abnormal. If `interval` is set then a smoothed line is calculated for  $\tau = 0.5 - \text{interval}/2$ , and a region is determined as upregulated if this line is above the reference. Down regulation is determined when the smoothed line for  $\tau = 0.5 + \text{interval}/2$  is below the reference value. If `threshold` is set then a smoothed line is calculated for  $\tau = 0.5$  and up- or down regulation are determined when this line is outside the range `[normalized.t - threshold:normalized.to + threshold]`

## Value

A `data.frame` with 3 columns is returned. Each row contains a region with columns `up`, `start` and `end`. `start` and `end` indicate positions in the vector of the first and last position that were up- or downregulated

## Author(s)

Jan Oosting

## Examples

```
data(chr14)
getChangedRegions(ill.cn[,1], ill.pos, normalized.to=2, interval=0.5)
```

`getLambdaMin`

*getLambdaMin*

## Description

Test a set of smoothing parameters to find best fit to data

## Usage

```
getLambdaMin(intensities, lambdas, ...)
```

## Arguments

intensities	numeric vector
lambdas	numeric vector; see <code>quantsmooth</code>
...	extra parameters for <code>quantsmooth.cv</code> ; currently only <code>ridge.kappa</code>

## Details

Cross validation is performed using a set of lambda values in order to find the lambda value that shows the best fit to the data.

## Value

This function returns the lambda value that has the lowest cross validation value on this dataset

## Author(s)

Jan Oosting

## See Also

[quantsmooth.cv](#)

## Examples

```
data(chr14)
lambda <- 2^seq(from=-2, to=5, by=0.25)
getLambdaMin(bac.cn[,1], lambda)
```

*grid.chromosome*

*Draw a chromosome using the grid package*

## Description

A chromosme is drawn including the cytobands

## Usage

```
grid.chromosome(chrom, side = 1, units = c("cM", "bases", "ISCN"), chrom.width = 0.5, length.out,
bands = "major", legend = c("chrom", "band", "none"), cex.leg = 0.7, bleach = 0, ...)
```

## Arguments

chrom	numeric or character, id of chromosome to plot
side	numeric [1:4], side of rectangle to draw, 4 sides, side 2 and 4 are vertical
units	character, type of unit to use
chrom.width	numeric [0,1], The width relative to the width (sides 2 and 4) or height(sides 1 and 3) of the viewport
length.out	numeric, size of native units of viewport
bands	character, draw either major or minor bands
legend	character, type of legend
cex.leg	numeric, relative size of legend text
bleach	numeric [0,1], proportion by which to bleach the chromosome
...	arguments for viewport(), especially x,y, width, and height

**Details**

The chromosome is drawn within a rectangle defined by x, y, width, and height, which is pushed as a viewport. The legend is drawn within the same rectangle in the space left over by chrom.width.

**Value**

This function is executed for its side effects

**Author(s)**

David L Duffy ,Jan Oosting

**References**

lodplot package

**See Also**

[paintCytobands](#)

**Examples**

```
grid.newpage()  
grid.chromosome(1,units="bases",height=0.15)
```

---

*lengthChromosome*

*Retrieve chromosomal length*

---

**Description**

Retrieve human chromosomal length from NCBI data

**Usage**

```
lengthChromosome(chrom, units = c("cM", "bases", "ISCN"))
```

**Arguments**

chrom	vector of chromosomal id, 1:22,X,Y
units	character, one of "cM", "bases", "ISCN"

**Value**

A vector numeric in the requested units

**Author(s)**

Jan Oosting

**Examples**

```
# Show length of chromosome 1 in several types of units
lengthChromosome(1,"cM")
lengthChromosome(1,"bases")
lengthChromosome(1,"ISCN")
```

**numericCHR**

*Conversion of chromosome IDs between numeric and character*

**Description**

The function converts chromosomal ids to their numeric form, and the sex chromosomes to values between 98 and 100. This simplifies sorting on chromosome ID

**Usage**

```
numericCHR(CHR, prefix="chr")
characterCHR(CHR, prefix="")
```

**Arguments**

CHR	character/numeric vector for both functions the mode of the input is not forced. For numericCHR strings "X","Y" and "XY" are converted to 98,99 and 100 respectively.
prefix	character, string is excluded from (numericCHR) or prepended to (characterCHR) all items of the output

**Value**

numericCHR returns a numeric vector of same length as CHR characterCHR returns a character vector of same length as CHR

**Author(s)**

Jan Oosting

**Examples**

```
chroms<-c("3","2","8","X","7","Y","5","1","9","10","11","12","4","6")
sort(chroms)
sort(numericCHR(chroms))
characterCHR(sort(numericCHR(chroms)),prefix="chr")
```

---

paintCytobands	<i>Paint a chromosomal idiogram</i>
----------------	-------------------------------------

---

## Description

Paints a human chromosomal idiogram in an existing plot Adapted from the paint.chromosome function in the lodplot package by David L Duffy

## Usage

```
paintCytobands(chrom, pos = c(0, 0), units = c("cM", "bases", "ISCN"), width = 0.4,
               length.out, bands = "major", orientation = c("h", "v"), legend = TRUE,
               cex.leg = 0.7, bleach = 0, ...)
```

## Arguments

chrom	chromosomal id, chromosome to plot 1:22,X,Y
pos	numeric vector of length 2, position in the plot to start the plot
units	units along which to plot the chromosome
width	numeric, width of the chromosome, the chromosome is plotted between pos[2] and pos[2]-width
length.out	numeric, if given, the chromosome will have this length in the plot
bands	if not equal to "major", then also the minor bands will be plotted
orientation	chromosome is plotted either Horizontally to the right of the starting point or Vertically down from the starting point
legend	logical, if TRUE then the bandnames are plotted next to the chromosome
cex.leg	numeric, relative size of legend text
bleach	numeric [0,1], proportion by which to bleach the chromosome
...	extra parameters for plot

## Value

This function is executed for its side effects

## Author(s)

David L Duffy , Jan Oosting

## References

lodplot package

## Examples

```
plot(c(0,lengthChromosome(14,"bases")),c(-2,2),type="n",xaxt="n",yaxt="n",xlab="",ylab="")
paintCytobands(14,units="bases")
```

---

**plotChromosome***Wrapper for plotSmoothed*

---

## Description

This function is a wrapper for `plotSmoothed`, to make data subsetting easier

## Usage

```
plotChromosome(gendata, chrompos, chromosome, dataselection = NULL, ylim = NULL, normalized.to = NULL, ...)
```

## Arguments

<code>gendata</code>	numeric matrix or data.frame
<code>chrompos</code>	chrompos object with same numer of rows as <code>gendata</code>
<code>chromosome</code>	numeric, chromosme to show
<code>dataselection</code>	optional, subset of samples/columns in <code>gendata</code>
<code>ylim</code>	limits for plot
<code>normalized.to</code>	y-value(s) for line
<code>grid</code>	x-value(s) for line
<code>smooth.lambda</code>	smoothing parameter, see <a href="#">quantsmooth</a>
<code>interval</code>	position of extra lines besides median, see <a href="#">plotSmoothed</a>
<code>...</code>	extra arguments for <a href="#">plotSmoothed</a>

## Value

The function is used for its side effects

## Author(s)

Jan Oosting

## See Also

[plotSmoothed](#), [quantsmooth](#)

---

plotSmoothed

*plotSmoothed*

---

## Description

Plot a smoothed line together with the original data values

## Usage

```
plotSmoothed(intensities, position, ylim=NULL, ylab="intensity", xlab="position", normalized.to=NULL)
```

## Arguments

intensities	numeric vector or matrix, data are plotted by column
position	numeric vector; the length should be the number of rows in intensities
ylim	numeric vector of length 2, limits for plot. If NULL then the minimal and maximal value in intensities is used
ylab	character, label for y-position
xlab	character, label for x-position
normalized.to	numeric, a line(s) is drawn at this horizontal position
grid	numeric, a line(s) is drawn at this vertical position
smooth.lambda	numeric, smoothing parameter see quantsmooth
interval	numeric (0..1), plotting of extra smoothed lines around median. With interval = 0.5 the 0.25 and 0.75 quartiles are plotted, with interval = 0.9 the 0.05 and 0.95 quantiles are plotted,
plotnew	logical, if TRUE a new plot is created, else the data are plotted into an existing plot
cols	color vector, colors for columns in intensities
cex.pts	size of the dots in the plot. Set to 0 to skip plotting the dots
...	extra parameters for plot

## Details

This function plots the raw data values as dots and the median smoothed values as a continuous line. If interval is supplied these are plotted as lines in different line types. More than 1 interval can be given.

## Value

This function is used for its side effects

## Author(s)

Jan Oosting

**See Also**

[quantsmooth](#)

**Examples**

```
data(chr14)
plotSmoothed(bac.cn,bac.pos,ylim=c(1,2.5),normalized.to=2,smooth.lambda=2.5)
```

position2Cytoband      *Determine cytoband position based on location of probe*

**Description**

Determine cytoband position based on location of probe

**Usage**

```
position2Cytoband(chrom, position, units = c("cM", "bases", "ISCN"), bands = c("major", "minor"))
```

**Arguments**

chrom	chromosomal id, chromosome to plot 1:22,X,Y
position	numeric vector
units	character, type of positional unit
bands	chararcter, type of cytoband

**Value**

Character vector with cytobands, if an illegal position was used, the value "-" is returned. All positions within a single function call should be for a single chromosome

**Author(s)**

Jan Oosting

**See Also**

[lengthChromosome](#)

**Examples**

```
position2Cytoband(1,c(50e6,125e6,200e6),units="bases")
position2Cytoband(1,c(50,125,200),units="cM",bands="minor")
```

---

prepareGenomePlot      *Set up a full genome plot*

---

## Description

This function starts up a plot consisting of all chromosomes of a genome, including axes with chromosome names.

## Usage

```
prepareGenomePlot(chrompos, cols = "grey50", paintCytobands = FALSE, bleach = 0, topspace = 1, organism,
                  sexChromosomes = FALSE, units = c("bases", "cM", "ISCN"), ...)
```

## Arguments

chrompos	chrompos object, data.frame with CHR column identifying the chromosome of probes, and a MapInfo column identifying the position on the chromosome
cols	color(s) for the chromosome lines
paintCytobands	logical, use paintCytoband to plot ideograms for all chromosomes
bleach	numeric [0,1], proportion by which to bleach the ideograms
topspace	numerical, extra space on top of plot, i.e. for legends
organism	character, if given a 2 column plot is created with the chromosomes for the given species. Currently "hsa", "mmu", and "rno" are supported
sexChromosomes	logical, if TRUE then also the sex chromosomes X and Y are plotted
units	character, type of units for genomic data
...	extra arguments for plot function

## Details

If `organism` is not supplied then a single column is plotted of the available chromosomes in `chrompos$CHR`. The arguments `paintCytobands`, `bleach`, and `sexChromosomes` are not used in that case.

## Value

A matrix with 2 columns that contain the Y and X positions for the probes on the plot

## Author(s)

Jan Oosting

quantsmooth

*quantsmooth***Description**

Quantile smoothing of array data

**Usage**

```
quantsmooth(intensities, smooth.lambda=2, tau=0.5, ridge.kappa=0, smooth.na=TRUE, segment)
```

**Arguments**

intensities	numeric vector
smooth.lambda	numeric
tau	numeric [0..1], the quantile desired; see <a href="#">rq.fit</a>
ridge.kappa	fudge parameter; see details
smooth.na	logical; handling of NA
segment	integer, length of overlapping segments

**Value**

This function returns a vector of the same length as `intensities`, or a matrix if the length of `tau` is greater than 1.

**Author(s)**

Jan Oosting

**Examples**

```
data(chr14)
plot(quantsmooth(bac.cn[,1], smooth.lambda=2.8), type="l")
```

quantsmooth.cv

*quantsmooth.cv***Description**

Cross validation of smoothing parameters

**Usage**

```
quantsmooth.cv(intensities, smooth.lambda=2, ridge.kappa=0)
```

**Arguments**

intensities	numeric vector
smooth.lambda	numeric; see <a href="#">quantsmooth</a>
ridge.kappa	fudge parameter; see <a href="#">quantsmooth</a>

**Details**

Cross validation is performed by calculating the fit from the even indices on the odd indices and vice versa.

**Value**

This function returns the sum of squared differences or NA if the fitting function gave an error

**Author(s)**

Jan Oosting

**See Also**

[getLambdaMin](#)

**Examples**

```
data(chr14)
# A low value is indicative of a better fit to the data
quantsmooth.cv(bac.cn[,1],1)
quantsmooth.cv(bac.cn[,1],2.8)
```

quantsmooth(seg)      *quantsmooth(seg)*

**Description**

segmented Quantile smoothing of array data

**Usage**

```
quantsmooth(seg(y, x = 1:length(y), lambda = 2, tau = 0.5, kappa = 0, nb = length(x)))
```

**Arguments**

y	numeric vector
x	numeric vector of same length as y. Position of values
lambda	numeric
tau	numeric [0..1], the quantile desired; see <a href="#">rq.fit</a>
kappa	fudge parameter; see details
nb	integer, basis

**Value**

This function returns a vector of the same length as *y*

**Author(s)**

Jan Oosting

**Examples**

```
data(chr14)
plot(quantsmooth.seg(bac.cn[,1],lambda=2.8,nb=50),type="l")
```

*scaleto*

*Scales data within a range to a new range*

**Description**

This function scales data to a new range while enforcing the boundaries. This can be helpful in preventing overlap between chromosomal plots that display multiple chromosomes in the same plot

**Usage**

```
scaleto(x, fromlimits = c(0, 50), tolimits = c(0.5, -0.5), adjust = TRUE)
```

**Arguments**

<i>x</i>	numeric
<i>fromlimits</i>	numeric vector with length 2, original range of data
<i>tolimits</i>	numeric vector with length 2, target range of data
<i>adjust</i>	logical, if TRUE then the target values are clipped to the target range

**Value**

numeric of same size as *x*

**Author(s)**

Jan Oosting

# Index

- \*Topic **aplot**
  - drawSimpleChrom, 3
  - grid.chromosome, 6
  - paintCytobands, 9
- \*Topic **attribute**
  - getChangedRegions, 4
- \*Topic **datasets**
  - chrom.bands, 2
  - Chromosome14, 3
- \*Topic **data**
  - lengthChromosome, 7
- \*Topic **hplot**
  - plotChromosome, 10
  - plotSmoothed, 11
  - prepareGenomePlot, 13
- \*Topic **htest**
  - quantsmooth.cv, 14
- \*Topic **manip**
  - numericCHR, 8
  - position2Cytoband, 12
  - scaleto, 16
- \*Topic **smooth**
  - getLambdaMin, 5
  - quantsmooth, 14
  - quantsmooth.cv, 14
  - quantsmooth.seg, 15

affy.cn (Chromosome14), 3  
affy.pos (Chromosome14), 3

bac.cn (Chromosome14), 3  
bac.pos (Chromosome14), 3

characterCHR (numericCHR), 8  
chr14 (Chromosome14), 3  
chrom.bands, 2  
Chromosome14, 3

drawSimpleChrom, 3

getChangedRegions, 4

- getLambdaMin, 5, 15
- grid.chromosome, 6
- ill.cn (Chromosome14), 3
- ill.pos (Chromosome14), 3
- lengthChromosome, 7, 12
- numericCHR, 8
- paintCytobands, 7, 9
- plotChromosome, 10
- plotSmoothed, 10, 11
- position2Cytoband, 12
- prepareGenomePlot, 13
- quantsmooth, 5, 10, 12, 14, 15
- quantsmooth.cv, 6, 14
- quantsmooth.seg, 15
- rq.fit, 14, 15
- scaleto, 16