

# pumadata

April 13, 2009

## R topics documented:

affybatch.estrogen . . . . .	1
eset_estrogen_comb . . . . .	2
eset_estrogen_mmgmos . . . . .	2
eset_estrogen_rma . . . . .	3
pumapca_estrogen . . . . .	4
<b>Index</b>	<b>5</b>

---

`affybatch.estrogen` *The data from the estrogen package as an AffyBatch object*

---

### Description

This data is taken from the **estrogen** package. It was created to be used in the vignette for the **puma** pacakge. It can be produced using the following code:

```
library(estrogen)
datadir <- file.path(.find.package("estrogen"), "extdata")
estrogenFilenames <- c("low10-1.cel", "low10-2.cel", "high10-1.cel",
, "low48-1.cel", "low48-2.cel", "high48-1.cel", "high48-2.cel")
affybatch.estrogen <- ReadAffy(
  filenames=estrogenFilenames
, celfile.path=datadir
)
pData(affybatch.estrogen) <- data.frame(
"estrogen"=c("absent", "absent", "present", "present"
, "absent", "absent", "present", "present")
, "time.h"=c("10", "10", "10", "10", "48", "48", "48",
, row.names=rownames(pData(affybatch.estrogen))
)
```

### Usage

```
data(affybatch.estrogen)
```

## Format

An [AffyBatch](#) object containing 8 HG\_U95Av2 arrays, in a 2 x 2 factorial design, with 2 replicates for each combination of factors. The factors are estrogen (absent or present) and time.h (10 or 48).

**eset\_estrogen\_comb** *The data from the estrogen package processed using the multi-mgMOS and PUMAcomb algorithms*

## Description

This data is taken from the **estrogen** package. It was created to be used in the vignette for the **puma** package. It can be produced using the following code (note this could take a long time to run):

```
data(eset_estrogen_mmgmos)
eset_estrogen_mmgmos_normd <- PUMAnormalize(eset_estrogen_mmgmos)
eset_estrogen_comb <- PUMAcomb(eset_estrogen_mmgmos_normd)
```

## Usage

```
data(eset_estrogen_comb)
```

## Format

An [ExpressionSet](#) object containing the expression levels and standard errors from combining the replicates for each combination of levels of factors from 8 HG\_U95Av2 arrays, in a 2 x 2 factorial design, with 2 replicates for each combination of factors. The factors are estrogen (absent or present) and time.h (10 or 48).

## See Also

[eset\\_estrogen\\_mmgmos](#)

## Examples

```
data(eset_estrogen_comb)
exprs(eset_estrogen_comb)[1:3,1:3]
assayDataElement(eset_estrogen_comb,"se.exprs")[1:3,1:3]
```

---

`eset_estrogen_mmgmos`

*The data from the **estrogen** package processed using the multi-mgMOS algorithm*

---

## Description

This data is taken from the **estrogen** package. It was created to be used in the vignette for the **puma** pacakge. It can be produced using the following code (note this could take a long time to run):

```
data(affybatch.estrogen)
eset_estrogen_mmgmos <- mmgmos(affybatch.estrogen)
```

## Usage

```
data(eset_estrogen_mmgmos)
```

## Format

An `exprReslt` object containing expression levels and standard errors for 8 HG\_U95Av2 arrays, in a 2 x 2 factorial design, with 2 replicates for each combination of factors. The factors are estrogen (absent or present) and time.h (10 or 48).

## See Also

[affybatch.estrogen](#) [eset\\_estrogen\\_rma](#)

## Examples

```
data(eset_estrogen_mmgmos)
show(eset_estrogen_mmgmos)
exprs(eset_estrogen_mmgmos)[1:3,1:3]
assayDataElement(eset_estrogen_mmgmos,"se.exprs")[1:3,1:3]
```

---

`eset_estrogen_rma`

*The data from the **estrogen** package processed using the RMA algorithm*

---

## Description

This data is taken from the **estrogen** package. It was created to be used in the vignette for the **puma** pacakge. It can be produced using the following code:

```
data(affybatch.estrogen)
eset_estrogen_mmgmos <- rma(affybatch.estrogen)
```

## Usage

```
data(eset_estrogen_rma)
```

## Format

An `ExpressionSet` object containing expression levels for 8 HG\_U95Av2 arrays, in a 2 x 2 factorial design, with 2 replicates for each combination of factors. The factors are estrogen (absent or present) and time.h (10 or 48).

## See Also

[affybatch.estrogen](#) [eset\\_estrogen\\_mmgmos](#)

## Examples

```
data(eset_estrogen_rma)
show(eset_estrogen_rma)
exprs(eset_estrogen_rma)[1:3,1:3]
assayDataElement(eset_estrogen_rma, "se.exprs")[1:3,1:3]
```

<code>pumapca_estrogen</code>	<i>The data from the <b>estrogen</b> package processed using the <b>pumaPCA</b> algorithm</i>
-------------------------------	---

## Description

This data is taken from the **estrogen** package. It was created to be used in the vignette for the **puma** pacakge. It can be produced using the following code (note this could take a long time to run):

```
data(eset_estrogen_mmgmos)
pumapca_estrogen <- pumaPCA(eset_estrogen_mmgmos)
```

## Usage

`data(pumapca_estrogen)`

## Format

An `pumaPCARes` object containing principal components (created using `pumaPCA`) of 8 HG\_U95Av2 arrays, in a 2 x 2 factorial design, with 2 replicates for each combination of factors. The factors are estrogen (absent or present) and time.h (10 or 48).

## See Also

[eset\\_estrogen\\_mmgmos](#)

## Examples

```
data(pumapca_estrogen)
plot(pumapca_estrogen, legend1pos="right", legend2pos="top")
```

# Index

## \*Topic datasets

affybatch.estrogen, 1  
eset\_estrogen\_comb, 2  
eset\_estrogen\_mmgmos, 2  
eset\_estrogen\_rma, 3  
pumapca\_estrogen, 4

AffyBatch, *I*  
affybatch.estrogen, 1, 3

eset\_estrogen\_comb, 2  
eset\_estrogen\_mmgmos, 2, 2–4  
eset\_estrogen\_rma, 3, 3  
ExpressionSet, 2, 3  
exprReslt, 3

pumapca\_estrogen, 4  
pumaPCARes, 4