

# RpsiXML

November 11, 2009

## R topics documented:

availableXrefs-methods . . . . .	2
availableXrefs . . . . .	2
bait . . . . .	3
BIOGRID.PSIMI25 . . . . .	4
buildPCHypergraph . . . . .	5
complexes . . . . .	6
complexName . . . . .	7
eListHandler . . . . .	8
getAbstractByPMID . . . . .	8
graphConverter . . . . .	9
interactions . . . . .	10
interactionType . . . . .	11
interactorInfo-methods . . . . .	12
interactorInfo . . . . .	12
interactors-methods . . . . .	13
interactors . . . . .	14
list2Matrix . . . . .	15
null2na . . . . .	15
numInteractions-methods . . . . .	16
numInteractors-methods . . . . .	16
organismName-methods . . . . .	16
parseComplex . . . . .	17
parsePsimi25Interaction . . . . .	17
psimi25Complex-class . . . . .	19
psimi25ComplexEntry-class . . . . .	20
psimi25Experiment-class . . . . .	21
psimi25Graph-class . . . . .	21
psimi25Hypergraph-class . . . . .	22
psimi25Interaction-class . . . . .	24
psimi25InteractionEntry-class . . . . .	25
psimi25Interactor-class . . . . .	26
psimi25Source-class . . . . .	27
psimi25XML2Graph . . . . .	28
releaseDate . . . . .	29
separateXMLDataByExpt . . . . .	30
sourceDb-methods . . . . .	31
sourceDb . . . . .	31

sourceId-methods . . . . .	32
sourceId . . . . .	32
taxId-methods . . . . .	33
taxId . . . . .	33
translateID-methods . . . . .	34
translateID . . . . .	34
uniprot-methods . . . . .	35
uniprot . . . . .	36
validatePSIMI25 . . . . .	36
<b>Index</b>	<b>38</b>

---

availableXrefs-methods  
*Methods for function availableXrefs*

---

## Description

Methods for function `availableXrefs`. See [availableXrefs](#) for more details

### Methods

- x = "list"** A list of `psimi25Interactor-class` objects, an logical option "intersect" can be set to tell the function whether to return the intersected or the unioned cross ref databases.
  - x = "psimi25InteractionEntry"** Similar to that of "list", "intersect" option is also provided
  - x = "psimi25Interactor"** returns the avaialble cross refences of the given interactor, "intersect" option not available
- 

availableXrefs      *Get cross reference(s) of interactors from PSI-MI 2.5 files*

---

## Description

PSI-MI 2.5 data exchange format encourages data providers to encode cross referenes of the interactors into the file, which prove valuable for annotating the data. These functions help finding out the available cross references of interactors.

### Usage

```
availableXrefs(x, ...)  
xref(x, ...)
```

### Arguments

- x** for `availableXrefs`, 'x' can either be an object of `psimi25Interactor-class`, `link{psimi25InteractionEntry}` or a list of `psimi25Interactor-class` objects.
- for `xref`, 'x' should be an object of `psimi25Interactor-class`
- ...** intersect, logical option. If set to TRUE then only the cross references available for every interactor are returned (intersected), otherwise all the cross references are unioned and returned. See the examples

## Details

If `psimi25InteractionEntry` is provided as the parameter of `availableXrefs`, an option named "intersect" can be set to extract only those cross references intersected among all the interactors, namely the ones assigned in every interactor. Please see the examples.

## Value

<code>xref</code>	Returns a matrix with two columns: <code>db</code> (external database name) and <code>id</code> (external database index)
<code>availableXrefs</code>	A vector of characters, the names of external databases referenced in the file

## Author(s)

Jitao David Zhang

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)
hprdInteractors <- interactors(hprdSet)

availableXrefs(hprdSet)
xref(hprdInteractors[[1]])
availableXrefs(hprdInteractors[[1]])
```

`bait`

*Extract bait, prey, participant, inhibitor, pubmed, confidence value, interaction type, or neutral component information from an object of `psimi25Interaction-class`*

## Description

The functions return bait/prey UniProt identifier of the given `psimi25Interaction` object.

## Usage

```
bait(x,...)
prey(x,...)
participant(x,...)
inhibitor(x,...)
pubmedID(x,...)
confidenceValue(x,...)
neutralComponent(x,...)
```

## Arguments

<code>x</code>	An object of <code>psimi25Interaction-class</code> , see example
<code>...</code>	Other parameters to control the identifier returned, not implemented yet

**Value**

The source database identifier is returned.

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**References**

The UniProt database <http://www.expasy.uniprot.org/>

**See Also**

[psimi25Interaction-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")  
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)  
  
interExp <- interactions(gridSet) [[1]]  
bait(interExp)  
prey(interExp)
```

---

BIOGRID.PSIMI25

*Supported PSI-MI 2.5 XML data sources*

---

**Description**

Objects representing supported PSI-MI 2.5 XML data sources. They are implicitly used in interaction and/or complex parsers. The supporting list will grow as soon as there are new PSI-MI 2.5 compatible data sources available.

For usage see examples of [parsePsimi25Interaction](#), [parsePsimi25Complex](#) and [psimi25XML2Graph](#).

**Details**

If a new repository is added manually by the user, please read the notes in [psimi25Source-class](#) before coding

**References**

**PSI-MI XML v2.5 data exchange format** <http://www.psidev.info/index.php?q=node/60>  
**BioGRID** <http://www.thebiogrid.com>  
**DIP** <http://dip.doe-mbi.ucla.edu/>  
**HPRD** <http://www.hprd.org/>  
**IntAct** <http://www.ebi.ac.uk/intact>

**MINT** <http://mint.bio.uniroma2.it/mint>  
**MIPS/CORUM** <http://mips.gsf.de/>  
**MPact** <http://mips.gsf.de/genre/proj/mpact>

---

buildPCHypergraph *Build protein complex hypergraph from PSI-MI 2.5 files*

---

## Description

The protein complexes can be represented by hypergraph models, with proteins as nodes and complexes as hypergraphs. This function builds protein complex hypergraph from one or more PSI-MI 2.5 files (complex mode), with the option to split the dataset by organism name or taxonomy ID of the complexes.

## Usage

```
buildPCHypergraph(xmlFiles, psimi25source, split.by = c("none", "organismName",
```

## Arguments

xmlFiles	PSI-MI 2.5 files, must be of complex mode.
psimi25source	PSI-MI 2.5 source indicator, for example INTACT.PSIMI25 for files from IntAct database
split.by	The qualifier to split the dataset, none specifies not to split the dataset, organismName and taxId splits the dataset according to organism name or taxonomy ID respectively. In the case of splitting, the results are a list of hypergraphs indexed by respective split qualifier
...	other parameters passed to parsePsimi25Complex

## Details

See [psimi25Hypergraph-class](#) for the use of resulting hypergraphs and examples.

## Value

In case the dataset is not split (by setting the option `split.by` as `none`, the result is a [psimi25Hypergraph-class](#) object. If the dataset was split, a list of [psimi25Hypergraph-class](#) is returned, which is indexed by either the organism name or the taxonomy ID.

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

## See Also

[psimi25Hypergraph-class](#) for the use of hypergraph objects, [separateXMLDataByExpt](#) for similar functionality but for interaction mode files

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")

pc2 <- buildPCHypergraph(intactComplexxml,
INTACT.PSIMI25, split.by="organismName")

pc2[2]
complexes(pc2[[2]])[1:3]
```

complexes

*Extract complexes from psimi25ComplexEntry*

## Description

Extract complexes from an object of [psimi25ComplexEntry-class](#)

## Usage

```
complexes(x)
```

## Arguments

x	An object of <a href="#">psimi25ComplexEntry-class</a>
---	--

## Value

A list of [psimi25Complex](#)

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## References

PSI-MI 2.5 XML data exchange format <http://www.psi-dev.info/index.php?q=node/60>

## See Also

[psimi25Complex-class](#)

## Examples

```
## Not run:
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml,
INTACT.PSIMI25)

complexes(intactComplexSet)
## End(Not run)
```

---

`complexName`*Accessor functions for complex*

---

## Description

These functions are used to extract useful information of complex in the form of `psimi25Complex-class` object.

## Usage

```
complexName(x, ...)  
complexMembers(x, ...)  
complexAttributes(x, ...)
```

## Arguments

<code>x</code>	An object of <code>psimi25Complex-class</code>
<code>...</code>	Not implemented yet

## Details

See examples

## Value

<code>complexName</code>	Returns the name of the complex in characters
<code>complexMembers</code>	A data frame of protein members building the complex and their information
<code>complexAttributes</code>	A named vector of character strings, the names are the attribute names while the values are attributes documented in the PSI-MI 2.5 file

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## See Also

`psimi25Complex-class`

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")  
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)  
complexSample <- complexes(intactComplexSet) [[2]]  
  
complexName(complexSample)  
complexAttributes(complexSample)  
complexMembers(complexSample)
```

**eListHandler***xmlEventParse handlers for PSI-MI XML documents***Description**

`xmlEventParse` handlers for PSI-MI XML documents

**Usage**

```
eListHandler()
iListHandler()
```

**Details**

A `dump()` method is supplied to deliver the list.

**Value**

list; see examples for structure

**Author(s)**

Vince Carey <[stvjc@channing.harvard.edu](mailto:stvjc@channing.harvard.edu)>

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
fn <- file.path(xmlDir, "hprd_200709_test.xml")
XML:::xmlEventParse(fn, eListHandler())$dump()
```

**getAbstractByPMID** *A function to obtain the abstract information via a Pubmed ID***Description**

This function takes a character vector of pubmed IDs and returns a list of pubMedAbst objects indexed by each ID.

**Usage**

```
getAbstractByPMID (pmID)
```

**Arguments**

pmID	A character vector of pubmed IDs
------	----------------------------------

**Value**

A list of pubMedAbst objects.

**Author(s)**

Tony Chiang

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsixML")
intactxml <- file.path(xmlDir, "intact_2008_test.xml")
x <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25)
y <- interactions(x) [[1]]
getAbstractByPMID(pubmedID(y))
```

graphConverter	<i>maps one type of graph onto another</i>
----------------	--

**Description**

The graphConverter function takes a graphNEL object, along with some information about what species that graphNEL is from and what species you wish to convert it into, and then uses the mappings in the inparanoid packages to convert that graph into an equivalent graph from the other species. The hyperGraphConverter performs the same service for either an incidence matrix or a Hypergraph.

**Usage**

```
graphConverter(graph, srcSpecies, destSpecies,
              srcIDType, destIDType, keepMultGeneMatches=FALSE,
              keepMultProtMatches=FALSE)
hyperGraphConverter(graph, srcSpecies, destSpecies, srcIDType,
                    destIDType, mapCols=FALSE, keepMultGeneMatches=FALSE,
                    keepMultProtMatches=FALSE)
```

**Arguments**

graph	If calling graphConverter, then this is a graphNEL object. Otherwise, it will be an incidence matrix or a hyperGraph
srcSpecies	The original source species in in paranoid format. In other words, the 3 letters of the genus followed by 2 letters of the species in all caps. Ie. 'HOMSA' is for Homo sapiens etc.
destSpecies	the destination species in in paranoid format
srcIDType	The source ID type written exactly as it would be used in a mapping name for an eg package. So for example, 'UNIPROT' is how the uniprot mappings are always written, so we keep that convention here.
destIDType	the destination ID, written the same way as you would write the srcIDType.
mapCols	For hyperGraphConverter set to true if the cols are gene names so that they too will be mapped.
keepMultGeneMatches	Do you want to try and keep the 1st ID in those ambiguous cases where more than one protein is suggested? (You probably want to filter them out - hence the default is FALSE)
keepMultProtMatches	Do you want to try and keep the 1st ID in those ambiguous cases where more than one protein is suggested? (default = FALSE)

**Value**

a graphNEL containing as many nodes as it was possible to find matches for.

**Author(s)**

Marc Carlson

**Examples**

```
##Set up a graphNEL object to convert
library(RpsiXML)
directory <- system.file("/extdata/psi25files",
                        package="RpsiXML")
mintXML <- file.path(directory,
                      "mint_200711_test.xml")
mintGraph <- separateXMLDataByExpt(xmlFiles=mintXML,
                                     psimi25source = MINT.PSIMI25,
                                     type = "indirect",
                                     directed=TRUE,
                                     abstract=FALSE)

if(require("hom.Mm.inp.db")) {
  ##convert it
  newGraph = graphConverter(mintGraph[[1]], "MUSMU", "HOMSA")
}

##Get a hypergraph
xmlDir <- system.file("/extdata/psi25files",package="RpsiXML")
intactComplexxml <- file.path(xmlDir,"intact_complexSample.xml")
hyperGraph <- buildPCHypergraph(intactComplexxml, INTACT.PSIMI25)

if(require("hom.Hs.inp.db")) {
  ##Convert it
  newHyper = hyperGraphConverter(hyperGraph, "HOMSA", "MUSMU", "UNIPROT",
                                 "UNIPROT")
}

##Get a incidence matrix from ScISI
if(require(ScISI)) {
  data(ScISIC)

  if(require("org.Sc.cgi.db")) {
    ##Convert it
    newScISIC = hyperGraphConverter(ScISIC, "SACCE", "MUSMU",
                                    srcIDType="ORF", destIDType = "EG")
  }
}
```

*interactions*

*List interactions in the given psimi25InteractionEntry object*

**Description**

List interactions from an object of the [psimi25InteractionEntry-class](#) object

**Usage**

```
interactions(x)
```

**Arguments**

x An object of [psimi25InteractionEntry-class](#), see example

**Value**

A list of interactions

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**See Also**

[psimi25InteractionEntry-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")  
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)  
  
interactions(hprdSet)
```

---

interactionType      *Type of the interaction*

---

**Description**

Return the interaction type of the [psimi25Interaction](#)

**Usage**

```
interactionType(x)
```

**Arguments**

x An object of [psimi25Interaction-class](#)

**Value**

A character string representing the interaction type

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**See Also**

[psimi25Interaction-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

interExp <- interactions(hprdSet) [[1]]
interExpTyp <- interactionType(interExp)
```

interactorInfo-methods

*Methods for Function interactorInfo in Package ‘RpsiXML’*

**Description**

See `interactorInfo`

**Methods**

```
x = "list" A list of psimi25Interactor-class objects
x = "psimi25ComplexEntry" Object of psimi25ComplexEntry-class, parsed from PSI-
MI 2.5 complex files
x = "psimi25Graph" Object of psimi25Graph-class, parsed by psimi25XML2Graph
by psimi25XML2Graph
x = "psimi25InteractionEntry" Object of psimi25InteractionEntry-class, parsed from
PSI-MI 2.5 interaction files
```

interactorInfo

*Interactor info in a matrix*

**Description**

The function returns the essential information of interactors in a matrix. Xrefs are left out since they have arbitrary numbers of annotation and cannot be summarized into a matrix.

**Usage**

```
interactorInfo(x)
```

**Arguments**

<code>x</code>	An object which contains psimi25Interactor information, for example objects of <a href="#">psimi25InteractionEntry-class</a> , <a href="#">psimi25Graph-class</a> , <a href="#">psimi25Hypergraph-class</a> or <a href="#">psimi25ComplexEntry-class</a>
----------------	--

.

**Value**

A matrix of interactor information, each row represents an interactor. The columns are

sourceDb	source database
sourceId	source database index
shortLabel	short label assigned by the source database
uniprotId	UniProt ID, NA if not available
organismName	the organism of the interactor protein

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

[xref](#), [availableXrefs](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

hprdInteractorInfo <- interactorInfo(hprdSet)
```

**Description**

Methods to extract interactors from various data structures

**Methods**

**x = "psimi25ComplexEntry"** Object of [psimi25ComplexEntry-class](#), parsed from PSI-MI 2.5 complex files

**x = "psimi25Graph"** Object of [psimi25Graph-class](#), parsed by [psimi25XML2Graph](#)

**x = "psimi25Hypergraph"** Object of [psimi25Hypergraph-class](#), parsed by [psimi25XML2Graph](#)

**x = "psimi25InteractionEntry"** Object of [psimi25InteractionEntry-class](#), parsed from PSI-MI 2.5 interaction files

interactors	<i>Interactors of the given object</i>
-------------	--

## Description

Return the interactors of the given object

## Usage

```
interactors(x)
```

## Arguments

x	either an object of <a href="#">psimi25InteractionEntry-class</a> or <a href="#">psimi25ComplexEntry-class</a>
---	--

## Value

A matrix of interactor information

## Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

## See Also

[psimi25InteractionEntry-class](#), [psimi25ComplexEntry-class](#)

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

interactors(hprdSet)

## Not run:
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml,
INTACT.PSIMI25)

interactors(intactComplexSet)
## End(Not run)
```

---

list2Matrix	<i>Converts list into matrix</i>
-------------	----------------------------------

---

**Description**

Converts a named list representation of a graph into matrix

**Usage**

```
list2Matrix(namedList, type="interaction")
```

**Arguments**

namedList      Named list.

type            Character: either interaction or complex

**Value**

A matrix. A bait-prey matrix if type is "interaction" with baits indexing the columns and prey the rows or a protein complex incidence graph with complexes indexing the columns and proteins, the rows.

If type is interaction, the names of the list are the baits and the entries of the list correspond the prey found by each bait.

If type is complex, the names of the list are the names of the protein complex and the entries are the members of each corresponding complex.

**Author(s)**

Tony Chiang <tchiang@ebi.ac.uk>

---

null2na	<i>Turns null or NA into character "NA"</i>
---------	---

---

**Description**

The functions turns NULL or NA into character "NA"

**Usage**

```
null2na(x)
```

**Arguments**

x                A vector

**Value**

Either the original vector (if not NULL or logical NA) or character NA

**Author(s)**

Tony Chiang <tchiang@ebi.ac.uk>

**Examples**

```
null2na(NA)
null2na(NULL)
```

---

## numInteractions-methods

*Get interaction number of the given object*

---

**Description**

Get the interaction number of the given object

**Methods**

**x = "psimi25InteractionEntry"** Returns the interactio number of the interactionEntry

---

## numInteractors-methods

*Get interactor number of the given item*

---

**Description**

Get the number of interactors in the given item

**Methods**

**x = "psimi25Hypergraph"** Get the protein number in the hypergraph object

**x = "psimi25InteractionEntry"** Get the interactor number in the entry

---

## organismName-methods

*Returns the organism name(s) of the given item*

---

**Description**

The method serves as accessor to retrieve the organism name of the given item, in most cases these are common names of the species as character string.

**Methods**

**x = "psimi25Complex"** An object of [psimi25Complex-class](#), indicating the complex belongs to which organism(s). Heterogeneous complex is possible, which contains proteins from two or more species. In this case the returned vector has length larger than one

**x = "psimi25Interactor"** An object of [psimi25Interactor-class](#), returns the organism of the protein, this value is normally of length 1.

---

parseComplex      *Parse complex, interactor and experiment from PSI-MI 2.5 XML node*

---

## Description

Wrappers of internal functions ("parsePsimi25Complex", "parsePsimi25Interactor", ".parsePsimi25Experiment") to parse nodes from PSI-MI 2.5 XML node. By default these parsers are used in objects of `psimi25Source-class` without any modification. Though they can be overwritten in these objects in special cases, it is not advisory to do so due to the compatibility.

## Usage

```
parseComplex(x, ...)  
parseInteractor(x, ...)  
parseExperiment(x, ...)
```

## Arguments

x	An object of the <code>psimi25Source-class</code>
...	Parameters passed to internal functions

## Value

Object of `psimi25Complex-class`, `\code{psimi25Complex-class}` or `\code{psimi25Complex-class}`

## Note

An newly initialized instance of `psimi25Source-class` contains the default form of these functions. Though they are allowed to be overwritten, it is not advisory to do so since this means the file to parse is not fully compatible with PSI-MI 2.5 standard. It is more sensible to contact the data provider before modifying or overwriting these functions.

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

---

parsePsimi25Interaction  
    *Parsing PSI-MI 2.5 XML documents into interactions*

---

## Description

The PSI-MI 2.5 XML format is used widely by many repositories to record protein-protein interaction data as well as protein complex data. This function parses such files into interactions or complexes.

`parsePsimi25Interaction` is the parser for interaction data and `parsePsimi25Complex` is the parser for complex data.

## Usage

```
parsePsimi25Interaction(psimi25file, psimi25source, verbose=TRUE)
parsePsimi25Complex(psimi25file, psimi25source, verbose=FALSE)
```

## Arguments

psimi25file	character, file name or URL of the XML document
psimi25source	A supported data repository source, see also <a href="#">psimi25Source-class</a>
verbose	logical, whether the parsing state should be displayed verbosely.

## Value

`psimi25Interaction` returns a list of `psimi25InteractionEntry` objects, each represents one entry in the XML document `psimi25Complex` returns a `psimi25ComplexEntry` objects, representing the complex data from one XML document.

## Author(s)

Jitao David Zhang <j.zhang@dkfz-heidelberg.de>, Tony Chiang <tchiang@ebi.ac.uk>

## References

**PSI-MI XML v2.5 data exchange format** <http://www.psi-dev.info/index.php?q=node/60>  
**BioGRID** <http://www.thebiogrid.com>  
**DIP** <http://dip.doe-mbi.ucla.edu/>  
**HPRD** <http://www.hprd.org/>  
**IntAct** <http://www.ebi.ac.uk/intact>  
**MINT** <http://mint.bio.uniroma2.it/mint>  
**MIPS/CORUM** <http://mips.gsf.de/>

## See Also

[psimi25Interaction-class](#), [psimi25InteractionEntry-class](#), [psimi25Complex-class](#), [psimi25ComplexEntry-class](#),

## Examples

```
# parse interaction data
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)

intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactSet <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25, verbose=TRUE)

# parse complex data
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)
```

---

psimi25Complex-class  
Class "psimi25Complex"

---

## Description

A class representing complex data

## Objects from the Class

Objects can be created by calls of `parsePsimi25Complex`

## Slots

**sourceDb:** Object of class "character", short label of the source database  
**sourceId:** Object of class "character", complex ID of the source database  
**shortLabel:** Object of class "character", short label of the complex  
**fullName:** Object of class "character", full name of the complex  
**organismName:** Object of class "character", orgnism name  
**taxId:** Object of class "character", taxonomy ID  
**members:** Object of class "data.frame", members (UniProt ID if available)  
**attributes:** Object of class "character", attributes of the complex

## Methods

**show** signature(object = "psimi25Complex") : shows information of the complex  
**sourceDb** signature(x = "psimi25Complex") : returns source database  
**sourceId** signature(x = "psimi25Complex") : returns source ID  
**complexAttributes** signature(x = "psimi25Complex") : returns attributes of the complex  
**complexMembers** signature(x = "psimi25Complex") : returns members of the complex  
**complexName** signature(x = "psimi25Complex") : returns complex name

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## See Also

[parsePsimi25Complex](#)

## Examples

```
showClass("psimi25Complex")
```

---

```
psimi25ComplexEntry-class  
  Class "psimi25ComplexEntry"
```

---

## Description

A class representing the complex data extracted from file in PSI-MI 2.5 format.

## Objects from the Class

Objects can be created by calls of the form `parsePsimi25Complex`

## Slots

**releaseDate:** Object of class "character", release date  
**interactors:** Object of class "matrix", interactors involved  
**complexes:** Object of class "list", complexes

## Methods

**complexes** signature(x = "psimi25ComplexEntry") : returns all complexes  
**interactors** signature(x = "psimi25ComplexEntry") : returns information of interactors  
**show** signature(object = "psimi25ComplexEntry") : shows information of all the complexes

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## See Also

`parsePsimi25Complex` `psimi25ComplexEntry`

## Examples

```
showClass("psimi25ComplexEntry")
```

---

```
psimi25Experiment-class  
  Class "psimi25Experiment"
```

---

## Description

Representing an experiment recorded in PSI-MI 2.5 XML files

## Objects from the Class

Objects can be created by calls of the form [parseExperiment](#)

## Slots

**sourceDb:** Object of class "character", source database short label

**expSourceId:** Object of class "character", experiment ID of the source database

**interactionType:** Object of class "character", interaction type, "Y2H", "vv", etc

**expPubMed:** Object of class "character", PubMed ID of the experiment

## Methods

No methods defined with class "psimi25Experiment" in the signature.

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## See Also

[parseExperiment](#)

## Examples

```
showClass("psimi25Experiment")
```

---

```
psimi25Graph-class  Class "psimi25Graph" ~~~
```

---

## Description

A graph object representing data extracted from PSI-MI 2.5 files

## Objects from the Class

Objects can be created by calls of the form [psimi25XML2Graph](#)

**Slots**

**interactors:** Object of class "matrix", interactor information in a matrix, Each row represents one interactor. Source IDs are used as row names. Each column represents one annotation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy ID. Only those interactors which are the nodes of the psimi25Graph is given.

**Extends**

Class [graphNEL](#), directly. Class [graphNEL](#), by class "graphNEL", distance 2.

**Methods**

```
show signature(object = "psimi25Graph") : show method
translateSourceID signature(r = "psimi25Graph") : translate the source ID into other
IDs
abstract signature(object="psimi25Graph") : get the abstract information for the dataset
from NCBI
```

**Author(s)**

Tony Chiang <tchiang@ebi.ac.uk> , Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

[psimi25XML2Graph](#),[S4classpsimi25Hypergraph-class](#)

**Examples**

```
showClass("psimi25Graph")
```

---

<i>psimi25Hypergraph-class</i>	<i>Class "psimi25Hypergraph"</i>
--------------------------------	----------------------------------

---

**Description**

Class to present PSI-MI 2.5 XML data as hypergraph. Proteins are projected as hypergraph nodes and complex composition as hyperedges.

**Objects from the Class**

Objects can be created by calls of the form [psimi25XML2Graph](#)

**Slots**

**interactors:** Object of class "matrix", Object of class "matrix", interactor information in a matrix, Each row represents one interactor. Source IDs are used as row names. Each column represents one annotation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy ID. Only those interactors which are the nodes of the psimi25Graph is given.

**Extends**

Class Hypergraph, directly

**Methods**

```
initialize signature(.Object = "psimi25Hypergraph")
show signature(object = "psimi25Hypergraph"): show method,print complex and
protein number
interactors signature(object = "psimi25Hypergraph"): list of psimi25Interactor
objects, providing full information of complex members
edgeLabel signature(object = "psimi25Hypergraph"): returns complex names (as
hyperedge label), as a character vector
hyperedgeNodes signature(object = "Hypergraph"): returns a list of characters: names
of the list are complex names and character vector in each list item are the members of that
complex
complexes signature(object = "psimi25Hypergraph"): a wrapper of hyperedgeNodes
translateSourceID signature(r = "psimi25Hypergraph"): translate source ID into
other IDs
numInteractors signature(r = "psimi25Hypergraph"): returns the number of pro-
teins
interactorInfo signature(r = "psimi25Hypergraph"): returns a data frame contain-
ing essential information of the interactors
numEdges signature(r = "psimi25Hypergraph"): returns the number of complexes
revInciMat signature(r = "matrix"): returns the hypergraph built from the incidence
matrix
```

**Author(s)**

Tony Chiang <tchiang@ebi.ac.uk> , Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

[psimi25XML2Graph](#),[S4classpsimi25Graph-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")
pc1 <- buildPCHypergraph(intactComplexxml, INTACT.PSIMI25)

## print number of proteins and complexes (edges)
numNodes(pc1)
## the same as numInteractors(pc1)
numEdges(pc1)

## print proteins (nodes)
nodes(pc1)[1:3]

## print complex names
edgeLabel(pc1)[1:3]
```

```

## print complexes (not so informative with 'hyperedges')
hyperedges(pc1)[1:3]
## better with 'complexes' or 'hyperedgeNodes'
complexes(pc1)[1:3]

## get interactor detailed information
interactors(pc1)[[1]]

```

psimi25Interaction-class  
*Class "psimi25Interaction"*

## Description

A class representing interaction data

## Objects from the Class

Objects can be created by calls of the form `parsePsimi25Interaction`

## Slots

**sourceDb:** Object of class "character", source database  
**sourceId:** Object of class "character", source database ID  
**interactionType:** Object of class "character", character, the method used for detecting the interaction ,such as "pull down"  
**expPubMed:** Object of class "character", PubMed ID of the publication that describes the experiment  
**expSourceId:** Object of class "character", source database ID of the experiment  
**confidenceValue:** Object of class "character", confidence value of the experimental interaction  
**participant:** Object of class "character", UniProt IDs of the participants. Important when no bait/prey information is available  
**bait:** Object of class "character", UniProt ID of the bait  
**prey:** Object of class "character", UniProt ID(s) of the prey(s)  
**inhibitor:** Object of class "character", UniProt ID of the inhibitor, NA when missing  
**neutralComponent:** Object of class "character", UniProt ID of the neutral components, NA when missing

## Methods

**interactionType** signature(x = "psimi25Interaction") : finds out interaction type  
**show** signature(object = "psimi25Interaction") : a print method  
**sourceDb** signature(x = "psimi25Interaction") : finds out source database  
**sourceId** signature(x = "psimi25Interaction") : returns ID of the source database  
**bait** signature(x = "psimi25Interaction") : returns the UniProt ID of the bait  
**prey** signature(x = "psimi25Interaction") : returns the UniProt ID(s) of the prey(s)  
**confidenceValue** signature(x = "psimi25Interaction") : returns the confidence value of the interaction

**Author(s)**

Tony Chiang <tchiang@ebi.ac.uk> , Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

[parsePsimi25Interaction](#), [S4CLASSpsimi25Interactor-class](#), [S4CLASSpsimi25Experiment-class](#), [S4classpsimi25InteractionEntry-class](#)

**Examples**

```
showClass("psimi25Interaction")
```

---

psimi25InteractionEntry-class  
Class "psimi25InteractionEntry"

---

**Description**

A class representing interaction data parsed from PSI-MI 2.5 XML files

**Objects from the Class**

Objects can be created by calls of the form `parsePsimi25Interaction`

**Slots**

**organismName:** Object of class "character", the unique organism name(s) of the interactors  
**taxId:** Object of class "character", the unique NCBI taxonomy ID(s) of the interactors  
**releaseDate:** Object of class "character", character, release date of the data entry, recorded in the `entry` element of the XML file  
**interactors:** Object of class "matrix", interactor information in a matrix, Each row represents one interactor. Source IDs are used as row names. Each column represents one annotation. Annotations include: UniProt ID, short label, organism name, and NCBI taxonomy ID  
**interactions:** Object of class "list", list, a list of `psimi25Interaction-class` objects, each represents one interaction.

**Methods**

**interactions** signature(`x = "psimi25InteractionEntry"`): return a list of `psimi25Interaction` objects, each representing one interaction  
**interactors** signature(`x = "psimi25InteractionEntry"`): a method to find all the interactors within the `psimi25InteractionEntry` and print them  
**organismName** signature(`x = "psimi25InteractionEntry"`): returns organism names of the interactors  
**releaseDate** signature(`x = "psimi25InteractionEntry"`): returns the release date, serving as a proxy for versioning  
**show** signature(`object = "psimi25InteractionEntry"`): a print method  
**taxId** signature(`x = "psimi25InteractionEntry"`): returns NCBI taxonomy ID

**numInteractors** signature(x = "psimi25InteractionEny") : returns the number of interactors  
**numInteractions** signature(x = "psimi25InteractionEny") : returns the number of interactions

### Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

### See Also

[parsePsimi25Interaction](#), S4 class [psimi25Interaction-class](#)

### Examples

```
showClass("psimi25InteractionEntry")
```

**psimi25Interactor-class**

*A class representing interactor from PSI-MI 2.5 XML files*

### Description

A class representing interactor from PSI-MI 2.5 XML files

### Slots

**sourceDb**: Object of class "character", source database  
**sourceId**: Object of class "character", ID of the source database  
**shortLabel**: Object of class "character", short label of the interactor, if not available the slot will be filled with "fullName" node of the file  
**uniprotId**: Object of class "character", UniProt ID of the interactor  
**organismName**: Object of class "character", the unique name of the organism name  
**taxId**: Object of class "character", the NCBI taxonomy ID

### Methods

**show** signature(x = "psimi25Interactor") : a print method  
**sourceDb** signature(x = "psimi25Interactor") : finds out source database  
**sourceId** signature(x = "psimi25Interactor") : returns ID of the source database  
**xref** signature(x = "psimi25Interactor") : returns cross-references of the given interactor

### Author(s)

Jitao David Zhang <j.zhang@dkfz.de>

### See Also

[parseInteractor](#)

## Examples

```
showClass("psimi25Interactor")
```

---



---

psimi25Source-class	<i>Class "psimi25Source"</i>
---------------------	------------------------------

---

## Description

A class representing data source compatible with PSI-MI 2.5 XML data exchange format

## Objects from the Class

Objects can be created by calls of the form `new ("psimi25Source", ...)`

## Slots

**label:** Object of class "character", a meaningful unique label of the database, does not necessarily have to be the identifier used in the PSI-MI files. The value is advised to be overwritten by the objects

**sourceDb:** Object of class "character", the character string used in the PSI-MI files to identify the source database. The value must be overwritten by the object, depending on the database identifier used in the PSI-MI file.

**uniprotSymbol:** Object of class "character", the identifier of UniProt reference in "primaryRef" or "secondaryRef" attributes of the interactors, telling the parser where to find UniProt symbol of the interactors. The value must be overwritten by the objects.

**parseExperiment:** Object of class "function", the function to parse experiment from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the experiment node strictly according the PSI-MI standard

**parseInteractor:** Object of class "function", the function to parse interactor from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the interactor node strictly according the PSI-MI standard

**parseComplex:** Object of class "function", the function to parse complex from the PSI-MI 2.5 file. Except for special need this function should not be overwritten by the objects, since it parses the complex node strictly according the PSI-MI standard

## Methods

**parseComplex** signature(x = "psimi25Source"): parse complex node of PSI-MI 2.5 file

**parseExperiment** signature(x = "psimi25Source"): parse experiment node of PSI-MI 2.5 file

**parseInteractor** signature(x = "psimi25Source"): parse interactor node of PSI-MI 2.5 file

**sourceDb** signature(x = "psimi25Source"): returns the source database

**uniprot** signature(x = "psimi25Source"): returns the uniprot identifier of the PSI-MI 2.5 XML file

**Note**

In case of a new data repository, you can first try creating a new object of the class with `label`, `sourceDb` and `uniprotSymbol` adjusted as needed. Try parsing a function with this new `psimi25Source` object. In case of warnings or errors, it may mean that the file provided is not strictly compatible with PSI-MI 2.5 data exchange format standard, please then contact the data provider.

By 02.06.08, six sources have been registered in the release version of RpsiXML: BIOGRID.PSIMI25, DIP.PSIMI25, HPRD.PSIMI25, INTACT.PSIMI25,, MINT.PSIMI25,MIPS.PSIMI25. Along the development we will implement more data sources under PSI-MI 25 standard.

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

`parsePsimi25Interaction`, `parsePsimi25Complex`, `psimi25XML2Graph`

**Examples**

```
showClass("psimi25Source")
```

`psimi25XML2Graph`    *Convert a vector of PSI-MI 2.5 XML files into graph objects*

**Description**

The function `psimi25XML2Graph` take a vector of XML 2.5 files from te same data source and generates a graph object based on the type of the files. `psimi25XML2Graph` is a wrapper for `interactionEntry2graph` and `complexEntry2graph`, which transform `interactionEntry` list and `complexEntry` list into graphs respectively.

**Usage**

```
psimi25XML2Graph(psimi25files, psimi25source, type = "interaction",
directed = TRUE, ...)
```

**Arguments**

`psimi25files` Single file name or a vector of PSI-MI 2.5 XML file names or URLs. In case of splitted data the latter form is preferred. Different datasets or datasets from different sources should not be put into the same vector.

`psimi25source` Source of the PSI-MI 2.5 XML file, see [psimi25Source-class](#)

`type` A character string which is either "interaction" or "complex". As the value suggests, use "interaction" if the XML file contains experimental physical data, and "complex" if the file contains curated protein complex membership data.

`directed` Logical, whehter the returned graph object should be directed or undirected

`...` Other parameters passed to [parsePsimi25Interaction](#)

**Value**

If type is "interaction", then a resulting psimi25Graph object is generated on the aggregation of the XML files. Otherwise if type is "complex,", a resulting psimi25HyperGraph object is generated on the aggregate of the XML files.

**Author(s)**

Jitao David Zhang, Tony Chiang

**See Also**

[psimi25Source-class](#), [psimi25Graph-class](#), [psimi25Hypergraph-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
intactxml <- file.path(xmlDir, "intact_2008_test.xml")  
intactGraph <- psimi25XML2Graph(intactxml, INTACT.PSIMI25, type="interaction")  
  
intactComplexxml <- file.path(xmlDir, "intact_complexSample.xml")  
intactComplexGraph <- psimi25XML2Graph(intactComplexxml, INTACT.PSIMI25, type="complex")
```

---

releaseDate

*Release date of the psimi25InteractionEntry object*

---

**Description**

The function returns the release date of the [psimi25InteractionEntry-class](#) object, which can serve as a proxy for versioning

**Usage**

```
releaseDate(x)
```

**Arguments**

x An object of [psimi25InteractionEntry-class](#)

**Value**

A character string indicating the release date

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**See Also**

[psimi25InteractionEntry-class](#)

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsixML")

gridxml <- file.path(xmlDir, "biogrid_200804_test.xml")
gridSet <- parsePsimi25Interaction(gridxml, BIOGRID.PSIMI25)

gridRD <- releaseDate(gridSet)
```

**separateXMLDataByExpt**

*Convert a vector of PSI-MI 2.5 XML files into graph objects based on pubmedID*

## Description

The function `psimi25XML2Graph` take a vector of XML 2.5 files from te same data source and generates a graph object based on the type of the files.

## Usage

```
separateXMLDataByExpt (xmlFiles, psimi25source, type = "direct", directed = TRUE,
```

## Arguments

<code>xmlFiles</code>	Single file name or a vector of PSI-MI 2.5 XML file names or URLs.
<code>type</code>	A character. Currently the user can specify to cull either "direct" interactions or "indirect" interactions.
<code>psimi25source</code>	Source of the PSI-MI 2.5 XML file, see <a href="#">psimi25Source-class</a>
<code>directed</code>	Logical, whehter the returned graph object should be directed or undirected.
<code>abstract</code>	Logical; if TRUE, the abstract information will be appended to the graph object.
<code>...</code>	Other parameters passed to <a href="#">parsePsimi25Interaction</a> , for example <code>verbose=TRUE</code>

## Value

A list of [psimi25Graph-class](#) are generated indexed by the pubmedID of each bait-prey interaction. WARNING - the abstract information is obtained using the pubmed and buildPubMedAbst functions from the annotate package which warns the user that NCBI may block access to their site. The default is to not obtain the abstract for this reason.

## Author(s)

Jitao David Zhang, Tony Chiang

## See Also

[psimi25Source-class](#), [psimi25Graph-class](#), [psimi25Hypergraph-class](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")  
  
intactxml <- file.path(xmlDir, "intact_2008_test.xml")  
intactGraph <- separateXMLDataByExpt(intactxml, INTACT.PSIMI25, type="indirect")
```

---

sourceDb-methods     *Get source database name*

---

**Description**

The method returns source database name of the given parameter

**Methods**

**x = "psimi25Complex"** An object of [psimi25Complex-class](#)  
**x = "psimi25Interaction"** An object of [psimi25Interaction-class](#)  
**x = "psimi25Interactor"** An object of [psimi25Interactor-class](#)  
**x = "psimi25Source"** An object of [psimi25Source-class](#)

---

sourceDb               *Extracts the source database of the given parameter*

---

**Description**

Returns the name of the source database of the given object

**Usage**

```
sourceDb(x)
```

**Arguments**

**x**                    see [sourceDb-methods](#)

**Value**

A character string presenting the source database

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**See Also**

see [sourceDb-methods](#)

---

`sourceId-methods`    *Extracting ID in the source database*

---

## Description

The method extracts source database IDs of the given parameter

## Methods

**x = "psimi25Complex"** An object of `psimi25Complex-class`  
**x = "psimi25Interaction"** An object of `psimi25Interaction-class`  
**x = "psimi25Interactor"** An object of `psimi25Interactor-class`

---

`sourceId`                  *Extracts the source database ID of the given parameter*

---

## Description

see `sourceDb-methods`

## Usage

`sourceId(x)`

## Arguments

**x**                  `sourceDb-methods`

## Value

A character string presenting ID in the source database

## Author(s)

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

## See Also

see `sourceId-methods`

---

taxId-methods      *Methods for function taxId*

---

**Description**

Returns the NCBI Taxonomy ID of the given object

**Methods**

**x = "psimi25Complex"** An `psimi25Complex-class` object

**x = "psimi25Interactor"** An `psimi25Interactor-class` object

**x = "psimi25InteractionEntry"** An object of `psimi25InteractionEntry-class`

---

taxId      *The taxonomy ID of the given parameter*

---

**Description**

Returns the taxonomy ID of the object

**Usage**

`taxId(x)`

**Arguments**

**x**      An object of `psimi25InteractionEntry-class` or `psimi25Complex-class`

**Value**

A character string of taxIDs

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**References**

PSI-MI 2.5 XML data exchange format, <http://www.psi-dev.info/index.php?q=node/60>

**See Also**

S4CLASS `psimi25InteractionEntry-class`

## Examples

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

taxId(hprdSet)
```

### `translateID-methods`

*Translate interactors into other identifiers*

## Description

The method finds any annotation IDs of of `psimi25Graph-class` or `psimi25Hypergraph-class` or `psimi25Interactor-class`

## Methods

- r = "psimi25Graph"** An object of `psimi25Graph-class`. It replaces the nodes with translated IDs and returns a new psimi25Graph object back.
- r = "psimi25Hypergraph"** An object of `psimi25Hypergraph-class`. Since the nodes of psimi25Hypergraph are not mutable, this method accepts a UniProt ID of interactors and returns the translated ID back. NA is also acceptable, which can be used to check interactors without mapping to UniProt
- r = "list"** A list of `psimi25Interactor-class`, returns a vector of translated identifiers back
- r = "psimi25Interactor"** An object of `psimi25Interactor-class`, returns translated identifier. Before using the method it is advisable to used `xref(x)` method to check which cross references are provided.

### `translateID`

*Finds identifiers of a given object*

## Description

see `translateID-methods`

## Usage

```
translateID(r, ...)
```

## Arguments

- |                  |  |
|------------------|--|
| <code>r</code>   | An object of psimi25Graph, psimi25Hypergraph, psimi25Interactor or a list of psimi25Interactor |
| <code>...</code> | the symbol of the ID to translate  |

**Details**

see [translateID-methods](#)

**Value**

The object of the same class as the parameter

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>

**See Also**

see [translateID-methods](#)

**Examples**

```
xmlDir <- system.file("/extdata/psi25files", package="RpsiXML")

hprdxml <- file.path(xmlDir, "hprd_200709_test.xml")
hprdSet <- parsePsimi25Interaction(hprdxml, HPRD.PSIMI25)

it <- interactors(hprdSet)[[1]]
translateID(it, "uniprot")
translateID(it, "entrezgene")

##Not run
intactxml <- file.path(xmlDir, "intact_2008_test.xml")
intactSet <- parsePsimi25Interaction(intactxml, INTACT.PSIMI25)
intactGraph <- psimi25XML2Graph(intactxml, INTACT.PSIMI25)
intactGraphNew <- translateID(intactGraph,"sourceId")## translate the nodes of the graph

intactSetInteractors <- interactors(intactSet)
intactXrefExample <- xref(intactSetInteractors[[1]])
translateID(intactSetInteractors,"intact")
translateID(intactSetInteractors[[1]],"intact")

intactComplexxml <- file.path(xmlDir,"intact_complexSample.xml")
intactComplexSet <- parsePsimi25Complex(intactComplexxml, INTACT.PSIMI25)
intactComplexGraph <- psimi25XML2Graph(intactComplexxml, INTACT.PSIMI25, type="complex")
translateID(intactComplexGraph, "intact", "P49432")
translateID(intactComplexGraph, "intact", NA)
## End(Not run)
```

**Description**

if the given parameter is an object of [psimi25Interactor-class](#), then the UniProt ID of this protein is returned. In case it is an object of [psimi25Source-class](#), the character string representing the path to UniProt is returned.

## Methods

**x = "psimi25Interactor"** An object of `psimi25Interactor-class`  
**x = "psimi25Source"** An object of `psimi25Source-class`

uniprot

*The UniProt Identifier in the PSI-MI 2.5 XML file*

## Description

A character string representing the UniProt identifier in primaryRef or secondaryRef attributes

## Usage

```
uniprot(x)
```

## Arguments

**x** An object of `psimi25Source-class`

## Value

A character string of the identifier

## Author(s)

Tony Chiang <tchiang@ebi.ac.uk>, Jitao David Zhang <j.zhang@dkfz.de>

## See Also

`psimi25Source-class`

## Examples

```
uniprot(HPRD.PSIMI25)
```

validatePSIMI25

*Validating PSI-MI 2.5 file with MIF25 XML schema*

## Description

The function validates given PSI-MI 2.5 file with MIF25 XML schema provided by the Molecular Interactions Workgroup of HUPO Proteomics Standards Initiative

## Usage

```
validatePSIMI25(file,
schema = system.file("extdata/schemas/MIF25.xsd", package = "RpsiXML"),
ignore.stderr = TRUE)
```

**Arguments**

file	The name or the URL of the file to be validated
schema	The schema file of PSI-MI 2.5 file format by default
ignore.stderr	Whether to print out errors in the console

**Details**

We advice to set "ignore.stderr=FALSE" for the first time of validating. The error number of the file will be printed in the console. When the number is not 0, one can set "ignore.stderr=TRUE" and see the errors produced during the validation.

**Value**

The number of errors in validating the file

**Note**

This function sofar depends on the tool "xmllint" bundled with libxml2 library. We plan to compile it later to run independent of the tool.

**Author(s)**

Jitao David Zhang <j.zhang@dkfz.de>, Tony Chiang <tchiang@ebi.ac.uk>

**References**

libxml2 library <http://xmlsoft.org/> PSI-MI 2.5 XML schema <http://psidev.sourceforge.net/mi/rel25/src/MIF25.xsd>

**Examples**

```
okFile <- system.file("extdata/psi25files/intact_2008_test.xml",
                      package="RpsiXML")
validatePSIMI25(okFile)
```

# Index

## \*Topic classes

psimi25Complex-class, 18  
psimi25ComplexEntry-class, 19  
psimi25Experiment-class, 20  
psimi25Graph-class, 21  
psimi25Hypergraph-class, 22  
psimi25Interaction-class, 23  
psimi25InteractionEntry-class,  
    24  
psimi25Interactor-class, 26  
psimi25Source-class, 27

## \*Topic manip

graphConverter, 8

## \*Topic methods

availableXrefs-methods, 1  
interactorInfo-methods, 11  
interactors-methods, 13  
numInteractions-methods, 15  
numInteractors-methods, 15  
organismName-methods, 16  
sourceDb-methods, 31  
sourceId-methods, 32  
taxId-methods, 33  
translateID-methods, 34  
uniprot-methods, 35

## \*Topic models

availableXrefs, 1  
availableXrefs-methods, 1  
bait, 2  
BIOGRID.PSIMI25, 3  
complexes, 5  
complexName, 6  
eListHandler, 7  
getAbstractByPMID, 8  
interactions, 10  
interactionType, 11  
interactorInfo, 12  
interactors, 13  
list2Matrix, 14  
null2na, 15  
parseComplex, 16  
parsePsimi25Interaction, 17  
psimi25XML2Graph, 28

releaseDate, 29  
separateXMLDataByExpt, 30  
sourceDb, 31  
sourceDb-methods, 31  
sourceId, 32  
sourceId-methods, 32  
taxId, 33  
translateID, 34  
translateID-methods, 34  
uniprot, 36  
validatePSIMI25, 36

abstract, psimi25Graph-method  
    (*psimi25Graph-class*), 21  
availableXrefs, 1, 1, 12  
availableXrefs, list-method  
    (*availableXrefs-methods*), 1  
availableXrefs, psimi25InteractionEntry-method  
    (*availableXrefs-methods*), 1  
availableXrefs, psimi25Interactor-method  
    (*availableXrefs-methods*), 1  
availableXrefs-methods, 1  
  
bait, 2  
bait, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23  
BIOGRID.PSIMI25, 3  
buildPCHypergraph, 4  
  
complexAttributes (*complexName*), 6  
complexAttributes, psimi25Complex-method  
    (*psimi25Complex-class*), 18  
complexEntry2graph  
    (*psimi25XML2Graph*), 28  
complexes, 5  
complexes, psimi25ComplexEntry-method  
    (*psimi25ComplexEntry-class*),  
    19  
complexes, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
complexMembers (*complexName*), 6

complexMembers, psimi25Complex-method  
    (*psimi25Complex-class*), 18  
complexName, 6  
complexName, psimi25Complex-method  
    (*psimi25Complex-class*), 18  
confidenceValue (*bait*), 2  
confidenceValue, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23  
CORUM.PSIMI25 (*BIOGRID.PSIMI25*), 3  
DIP.PSIMI25 (*BIOGRID.PSIMI25*), 3  
edgeLabel  
    (*psimi25Hypergraph-class*),  
    22  
edgeLabel, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
eListHandler, 7  
getAbstractByPMID, 8  
graphConverter, 8  
graphNEL, 21  
HPRD.PSIMI25 (*BIOGRID.PSIMI25*), 3  
hyperedgeNodes  
    (*psimi25Hypergraph-class*),  
    22  
hyperedgeNodes, Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
hyperedgeNodes, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
hyperGraphConverter  
    (*graphConverter*), 8  
iListHandler (*eListHandler*), 7  
inhibitor (*bait*), 2  
inhibitor, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23  
initialize, Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
initialize, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
INTACT.PSIMI25 (*BIOGRID.PSIMI25*),  
    3  
interactionEntry2graph  
    (*psimi25XML2Graph*), 28  
interactions, 10  
interactions, psimi25InteractionEntry-method  
    (*psimi25InteractionEntry-class*),  
    24  
interactionType, 11  
interactionType, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23  
interactorInfo, 12  
interactorInfo, list-method  
    (*interactorInfo-methods*),  
    11  
interactorInfo, psimi25ComplexEntry-method  
    (*interactorInfo-methods*),  
    11  
interactorInfo, psimi25Graph-method  
    (*interactorInfo-methods*),  
    11  
interactorInfo, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22  
interactorInfo, psimi25InteractionEntry-method  
    (*interactorInfo-methods*),  
    11  
interactorInfo-methods, 11  
interactors, 13  
interactors, psimi25ComplexEntry-method  
    (*psimi25ComplexEntry-class*),  
    19  
interactors, psimi25Graph-method  
    (*interactors-methods*), 13  
interactors, psimi25Hypergraph-method  
    (*interactors-methods*), 13  
interactors, psimi25InteractionEntry-method  
    (*psimi25InteractionEntry-class*),  
    24  
interactors-methods, 13  
list2Matrix, 14  
MATRIXDB.PSIMI25  
    (*BIOGRID.PSIMI25*), 3  
MINT.PSIMI25 (*BIOGRID.PSIMI25*), 3  
MIPS.PSIMI25 (*BIOGRID.PSIMI25*), 3  
MPACT.PSIMI25 (*BIOGRID.PSIMI25*), 3  
neutralComponent (*bait*), 2  
neutralComponent, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23  
null2na, 15  
numEdges, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22

numInteractions  
     (*numInteractions-methods*),  
     15  
 numInteractions, psimi25InteractionEntry-method  
     (*numInteractions-methods*),  
     15  
 numInteractions-methods, 15  
 numInteractors  
     (*numInteractors-methods*),  
     15  
 numInteractors, psimi25Hypergraph-method  
     (*numInteractors-methods*),  
     15  
 numInteractors, psimi25InteractionEntry  
     (*numInteractors-methods*),  
     15  
 numInteractors-methods, 15  
 organismName  
     (*organismName-methods*), 16  
 organismName, psimi25Complex-method  
     (*organismName-methods*), 16  
 organismName, psimi25Hypergraph-method  
     (*psimi25Hypergraph-class*),  
     22  
 organismName, psimi25InteractionEntry-method  
     (*psimi25InteractionEntry-class*),  
     24  
 organismName, psimi25Interactor-method  
     (*organismName-methods*), 16  
 organismName-methods, 16  
 parseComplex, 16  
 parseComplex, psimi25Source-method  
     (*psimi25Source-class*), 27  
 parseExperiment, 20  
 parseExperiment (*parseComplex*), 16  
 parseExperiment, psimi25Source-method  
     (*psimi25Source-class*), 27  
 parseInteractor, 26  
 parseInteractor (*parseComplex*), 16  
 parseInteractor, psimi25Source-method  
     (*psimi25Source-class*), 27  
 parsePsimi25Complex, 3, 19, 28  
 parsePsimi25Complex  
     (*parsePsimi25Interaction*),  
     17  
 parsePsimi25Interaction, 3, 17, 24,  
     25, 28, 30  
 participant (*bait*), 2  
 participant, psimi25Interaction-method  
     (*psimi25Interaction-class*),  
     23  
         prey (*bait*), 2  
         prey, psimi25Interaction-method  
             (*psimi25Interaction-class*),  
             23  
         psimi25Complex-class, 6, 7, 16, 18, 33  
         psimi25Complex-class, 16, 18, 31–33  
         psimi25ComplexEntry, 19  
         psimi25ComplexEntry-class, 5,  
             12–14, 18  
         psimi25ComplexEntry-class, 12, 13,  
             19  
         psimi25Experiment-class, 24  
         psimi25Experiment-class, 20  
         psimi25Graph-class, 12, 23, 29, 30, 34  
         psimi25Graph-class, 12, 13, 21, 34  
         psimi25Hypergraph-class, 4, 5, 12,  
             21, 29, 30, 34  
         psimi25Hypergraph-class, 13, 22, 34  
         psimi25Interaction-class, 3, 11, 18,  
             25  
         psimi25Interaction-class, 23, 31, 32  
         psimi25InteractionEntry-class,  
             10, 12–14, 18, 24, 29, 33  
         psimi25InteractionEntry-class,  
             12, 13, 24, 33  
         psimi25Interactor-class, 2, 24, 34,  
             35  
         psimi25Interactor-class, 1, 12, 16,  
             26, 31–34, 36  
         psimi25Source-class, 4, 16, 17, 28–30,  
             35, 36  
         psimi25Source-class, 27, 31, 36  
         psimi25XML2Graph, 3, 12, 13, 21, 23, 28,  
             28  
         pubmedID (*bait*), 2  
         pubmedID, psimi25Interaction-method  
             (*psimi25Interaction-class*),  
             23  
         releaseDate, 29  
         releaseDate, psimi25InteractionEntry-method  
             (*psimi25InteractionEntry-class*),  
             24  
         revInciMat  
             (*psimi25Hypergraph-class*),  
             22  
         revInciMat, matrix-method  
             (*psimi25Hypergraph-class*),  
             22  
         separateXMLDataByExpt, 5, 30  
         show, psimi25Complex-method  
             (*psimi25Complex-class*), 18

show, psimi25ComplexEntry-method  
    (*psimi25ComplexEntry-class*),  
    19

show, psimi25Graph-method  
    (*psimi25Graph-class*), 21

show, psimi25Hypergraph-method  
    (*psimi25Hypergraph-class*),  
    22

show, psimi25Interaction-method  
    (*psimi25Interaction-class*),  
    23

show, psimi25InteractionEntry-method  
    (*psimi25InteractionEntry-class*),  
    24

show, psimi25Interactor-method  
    (*psimi25Interactor-class*),  
    26

sourceDb, 31

sourceDb, psimi25Complex-method  
    (*sourceDb-methods*), 31

sourceDb, psimi25Interaction-method  
    (*sourceDb-methods*), 31

sourceDb, psimi25Interactor-method  
    (*sourceDb-methods*), 31

sourceDb, psimi25Source-method  
    (*sourceDb-methods*), 31

sourceDb-methods, 31, 32

sourceDb-methods, 31

sourceId, 32

sourceId, psimi25Complex-method  
    (*sourceId-methods*), 32

sourceId, psimi25Interaction-method  
    (*sourceId-methods*), 32

sourceId, psimi25Interactor-method  
    (*sourceId-methods*), 32

sourceId-methods, 32

sourceId-methods, 32

taxId, 33

taxId, psimi25Complex-method  
    (*taxId-methods*), 33

taxId, psimi25InteractionEntry-method  
    (*psimi25InteractionEntry-class*),  
    24

taxId, psimi25Interactor-method  
    (*taxId-methods*), 33

taxId-methods, 33

translateID, 34

translateID, list-method  
    (*translateID-methods*), 34

translateID, psimi25Graph-method  
    (*translateID-methods*), 34

translateID, psimi25Hypergraph-method  
    (*translateID-methods*), 34

translateID, psimi25Interactor-method  
    (*translateID-methods*), 34

translateID-methods, 34, 35

translateID-methods, 34

uniprot, 36

uniprot, psimi25Interactor-method  
    (*uniprot-methods*), 35

uniprot, psimi25Source-method  
    (*psimi25Source-class*), 27

uniprot-methods, 35

validatePSIMI25, 36

xref, 12

xref(availableXrefs), 1

xref, psimi25Interactor-method  
    (*psimi25Interactor-class*),  
    26