

# Package ‘eisa’

April 9, 2015

**Version** 1.18.0

**Date** 2014-03-26

**Title** Expression data analysis via the Iterative Signature Algorithm

**Author** Gabor Csardi <csardi.gabor@gmail.com>

**Maintainer** Gabor Csardi <csardi.gabor@gmail.com>

**Description** The Iterative Signature Algorithm (ISA) is a biclustering method; it finds correlated blocks (transcription modules) in gene expression (or other tabular) data. The ISA is capable of finding overlapping modules and it is resilient to noise. This package provides a convenient interface to the ISA, using standard BioConductor data structures; and also contains various visualization tools that can be used with other biclustering algorithms.

**Depends** isa2, Biobase (>= 2.17.8), AnnotationDbi, methods

**Imports** BiocGenerics, Category, genefilter, DBI

**Suggests** igraph (>= 0.6), Matrix, GOstats, GO.db, KEGG.db, biclust, MASS, xtable, ALL, hgu95av2.db, targetscan.Hs.eg.db, org.Hs.eg.db

**License** GPL (>= 2)

**biocViews** Classification, Visualization, Microarray, GeneExpression

**Collate** AllClasses.R AllGenerics.R ISAExpressionSet-methods.R ISAModules-methods.R enrichment.R CHR.R GO.R KEGG.R miRNA.R util.R autogen.R biclust.R eisa.R viz.R zzz.R generalenrichment.R

## R topics documented:

ALLModules	2
condPlot	3
enrichment	5
expPlot	6
gograph	8

ISA . . . . .	10
ISA-Biclust conversion . . . . .	12
ISA2heatmap . . . . .	13
ISACHR . . . . .	15
ISAExpressionSet-class . . . . .	16
ISAFilterRobust . . . . .	18
ISAGO . . . . .	19
ISAHTML . . . . .	21
ISAIterate . . . . .	23
ISAKEGG . . . . .	25
ISAmiRNA . . . . .	26
ISAModules-class . . . . .	28
ISANormalize . . . . .	33
ISASweep . . . . .	34
ISAUnique . . . . .	36
ListHyperGParams-class . . . . .	38
ListHyperGResult-class . . . . .	41
mnplot . . . . .	44
overlap . . . . .	46
profilePlot . . . . .	47
<b>Index</b>	<b>50</b>

---

ALLModules

*ISA transcription modules for the ALL data*

---

## Description

The Iterative Signature Algorithm (ISA) is a biclustering method. ALLModules and ALLModulesSmall are example ISA biclusters (=modules) found in the ALL data set.

## Usage

```
ALLModules
ALLModulesSmall
```

## Format

Both ALLModules and ALLModulesSmall are instances of the ISAModules class.

## Source

ISAModules was generated by calling ISA on the ALL data set, using the default parameters. ISAModulesSmall was generated the same way, but with gene threshold 2.7 and condition threshold 1.4 only.

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

The ALL BioConductor package.

## Examples

```
data(ALLModules)
ALLModules
```

---

condPlot	<i>Plot sample scores of a transcription module</i>
----------	---

---

## Description

Creates a barplot of sample (=condition) scores, for a given transcription module. See details below.

## Usage

```
condPlot (modules, number, eset, col = "white", all = TRUE, sep = NULL,
         sepcol = "grey", val = TRUE, srt = 90, adj.above = c(0, 0.5),
         adj.below = c(1, 0.5), plot.only = seq_len(ncol(eset)), ...)
```

## Arguments

modules	An ISAModules object.
number	An integer scalar, the module to plot.
eset	An ExpressionSet or ISAExpressionSet object. This is needed for calculating the scores of the samples that are not in the module, see the all argument. If an ExpressionSet object is supplied, then it is normalised by calling <a href="#">ISANormalize</a> on it.
col	Color of the bars, it is passed to <a href="#">barplot</a> , so it can be any format <a href="#">barplot</a> accepts. E.g. it can be a character vector with different colors for the different bars.
all	Logical scalar, whether to plot all samples (if TRUE, the default), or just the ones that are included in the module.
sep	NULL or a numeric vector. If not NULL, then the bars are separated at the given positions with vertical lines. This is useful if you want to subdivide the samples into groups.
sepcol	The color of the separating lines (see the sep argument), if they are plotted.
val	Logical scalar, whether to add labels with the actual score values.

<code>srt</code>	Numeric scalar, the rotation angle of the text labels, this is passed to the <code>text</code> function.
<code>adj.above</code>	Adjustment of the text labels that are above the bars. This is passed to <code>text</code> , see its manual for details.
<code>adj.below</code>	Adjustments of the text labels that are below the bars. This is passed to <code>text</code> , see its manual for details.
<code>plot.only</code>	Numeric vector, if supplied it is used to plot a subset of samples only. By default all samples are plotted.
<code>...</code>	Additional argument, to be passed to <code>barplot</code> .

### Details

`condPlot` creates a barplot for the sample scores of an ISA transcription module. Each sample is represented as a bar.

These plots are useful if you want to show that a given transcription module separates the samples into two (or more) groups. You can assign different colors to the samples, based on some external information, e.g. case and control samples can be colored differently.

In most cases the scores are between minus one and one, but this is not necessarily true.

It is possible to assign scores to samples that are not part of the module, but this requires performing one (more precisely half) ISA iteration step. Currently the function always performs this extra step, even if the out-of-module samples are not plotted. Because the sample scores in a module are only approximately constant during ISA iteration, it might be possible that the plotted scores are slightly different than the ones stored in the `modules` variable.

### Value

None.

### Author(s)

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

### References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### See Also

[ISA](#) and [ISAModules](#).

### Examples

```
data(ALLModulesSmall)
library(ALL)
data(ALL)
```

```
col <- ifelse(grepl("^B", ALL$BT), "darkolivegreen", "orange")
condPlot(ALLModulesSmall, 1, ALL, col=col)
```

---

enrichment	<i>Enrichment analysis for transcription modules, based on user-defined categories</i>
------------	--

---

## Description

This function performs enrichment analysis for each ISA module separately, comparing it to user-defined categories. It is useful to test against other databases and annotations than the Gene Ontology or KEGG pathways.

## Usage

```
ISAEnrichment (modules, categories, ann = annotation(modules),
  features = featureNames(modules), hgCutoff = 0.05,
  correction = TRUE, correction.method = "holm")
```

## Arguments

modules	An ISAModules object, a set of ISA modules.
categories	A named list of gene categories. The names of the entries are used as category names. Each entry of the list must be a character vector containing Entrez gene ids.
ann	Character scalar. The annotation package to be used. By default it is taken from the modules argument.
features	Character vector. The names of the features. By default it is taken from the modules argument.
hgCutoff	Numeric scalar. The cutoff value to be used for the enrichment significance. This can be changed later, without recalculating the test.
correction	Logical scalar, whether to perform multiple hypothesis testing correction.
correction.method	Character scalar, the multiple testing correction method to use. Possible values: "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none". See the <a href="#">p.adjust</a> function for details on these.

## Details

This function performs enrichment analysis, based on user defined gene labels. It is useful if one want to test ISA modules against databases, other than GO and KEGG.

The hypergeometric test, a version Fisher's exact test, takes a gene label and a gene set (in our case coming from an ISA module) and asks whether the number of genes in the set labelled by the label is significantly more (or less) than what one would expect by chance.

ISAEnrichment performs the hypergeometric test for every module, for all user supplied gene labels. The mapping from the probe ids on the array to Entrez Ids is done using the appropriate chip annotation package.

ISAEnrichment currently cannot test for under-representation.

**Value**

A `GeneralListHyperGResult` object.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

[ISAGO](#), [ISACHR](#), [ISAKEGG](#) and [ISAmiRNA](#) for other enrichment calculations.

The `Category` package.

**Examples**

```
data(ALLModulesSmall)
library(hgu95av2.db)
entrez <- unique(unlist(mget(featureNames(ALLModulesSmall), hgu95av2ENTREZID)))
categories <- lapply(letters, function(x) sample(entrez, 100))
names(categories) <- letters
fakeEnrichment1 <- ISAEnrichment(ALLModulesSmall, categories, correction=FALSE)
fakeEnrichment2 <- ISAEnrichment(ALLModulesSmall, categories, correction=TRUE)
```

---

expPlot

*Expression matrix plots for ISA modules*

---

**Description**

These functions create an expression matrix plot for an ISA module. The gene and sample scores are also plotted.

**Usage**

```
expPlotCreate (eset, modules, which, norm = c("sample", "raw", "feature"))
expPlot (epo, scores = TRUE)
expPlotColbar (epo)
```

**Arguments**

eset	An ExpressionSet or ISAExpressionSet object. If an ExpressionSet object is supplied (and the norm argument is not set to 'raw'), then it is normalised by calling <a href="#">ISANormalize</a> on it. A subset of eset is selected that corresponds to the features included in modules.
norm	Character constant, specifies whether and how to normalize the expression values to plot. 'raw' plots the raw expression values, 'feature' the expression values scaled and centered for each feature (=gene) separately and if 'sample' is specified then the expression values are centered and scaled separately for each sample.
modules	An <a href="#">ISAModules</a> object.
which	Numeric scalar, which module to plot.
scores	Logical scalar, whether to plot the scores as well.
epo	An object returned by expPlotCreate.

**Details**

expPlotCreate creates an object that contains all data for performing the image plot and returns it. The reason for not plotting it directly is, that the size of the plot is usually different in different cases, and the opening of the graphics device is delayed until expPlotCreate returns.

In the returned object, the weight and height entries give the optimal size of the image, in pixels.

expPlot creates the expression plot.

expPlotColbar plots a color bar for the expression plot.

**Value**

expPlotCreate returns an ISAexpPlot object. It is a named list and has several entries, the important ones:

width            Numeric scalar, the optimal width of the plot.

height           Numeric scalar, the optimal height of the plot.

expPlot returns, invisibly, a named list with members:

coords           A list with two entries: x and y, both numeric vectors of length two. They give the position of the actual expression matrix on the plot.

gene.width       Numeric scalar, the width of one box on the image plot, in pixels; if the image size is exactly the suggested one.

cond.height      Numeric scalar, the height of one box on the image plot, in pixels; if the image size is exactly the suggested one.

expPlotColbar returns NULL, invisibly.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

The vignette in the `eisa` package for other ISA visualizations. The `ExpressionView` package for an interactive version.

## Examples

```
data(ALLModulesSmall)
library(ALL)
data(ALL)

ep <- expPlotCreate(ALL, ALLModulesSmall, 1)
ep

if (interactive()) {
  expPlot(ep)
}
```

---

gograph

*Plot part of the Gene Ontology hierarchy*

---

## Description

These functions help creating a plot of the Gene Ontology hierarchy.

## Usage

```
gograph (table, colbar.length = 30, label.cex = 1, alpha=1, abbrev=5,
         GOGRAPHS = NULL, go.terms = NULL)
gographPlot (graph, coords = FALSE, ...)
```

## Arguments

<code>table</code>	A data frame with one column, containing the $p$ -values of the enriched GO terms. The row names of the data frame should contain the GO ids.
<code>colbar.length</code>	Numeric scalar, the length of the color bar.
<code>label.cex</code>	Numeric scalar, factor for the label sizes, e.g. '2' means double size compared to the default.
<code>alpha</code>	Alpha channel for the fill color of the vertices.
<code>abbrev</code>	Numeric scalar, the minimum length for the abbreviated GO ids.
<code>GOGRAPHS, go.terms</code>	These are for internal use only.

graph	An igraph graph, as returned by the gograph function.
coords	Logical scalar, whether to return the coordinates of the vertices on the plot.
...	Additional arguments. These are passed to plot.igraph.

### Details

A GO plot can be created in two steps. `gograph` creates an igraph graph object that contains all the information about the plot; `gographPlot` creates the actual plot.

The two steps are needed, because `gograph` calculates the optimal size of the plot, and then a graphics device of this size can be created before calling `gographPlot`.

The optimal size is returned by `gograph` in the `width` and `height` graph attributes, these can be queried with

```
G <- gograph(...)
G$width
G$height
```

### Value

`gograph` returns an igraph object.

`gographPlot` by default returns NULL, invisibly. If the `coords` argument is TRUE, then it returns the coordinates of the vertices on the plot.

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### References

The Gene Ontology Consortium. Gene ontology: tool for the unification of biology. *Nat. Genet.* May 2000;25(1):25-9.

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### See Also

The `igraph0` package for more about igraph graphs.

### Examples

```
data(ALLModulesSmall)
GO <- ISAGO(ALLModulesSmall)
gotab <- summary(GO$BP)[[1]][, "Pvalue", drop=FALSE]

G <- gograph(gotab)
if (interactive()) {
  x11(width=G$width/15, height=G$height/15)
```

```

    gographPlot(G)
}

```

---

ISA

*Iterative Signature Algorithm on Gene Expression data*


---

## Description

Run ISA on an ExpressionSet with the default parameters.

## Usage

```

ISA (data, flist = filterfun(function(x) IQR(x) > 0.5),
     uniqueEntrez = TRUE, thr.gene = seq(2, 4, by = 0.5),
     thr.cond = seq(1, 3, by = 0.5), no.seeds = 100)

```

## Arguments

<code>data</code>	The input, an ExpressionSet object.
<code>flist</code>	A 'list' of filter functions to apply to the array. This is passed to the <a href="#">genefilter</a> function without touching it. Supply NA here if you don't want to filter the expression set before running ISA on it.
<code>uniqueEntrez</code>	Logical scalar, whether to filter the input expression set to keep exactly one probeset for each Entrez gene. Probesets that are not mapped to an Entrez gene are dropped.
<code>thr.gene</code>	Numeric vector. The threshold parameters for the ISA, for features (=probesets or genes). All combinations of <code>thr.gene</code> and <code>thr.cond</code> will be used to run ISA.
<code>thr.cond</code>	Numeric vector. The threshold parameters for the ISA, for samples. All combinations of <code>thr.gene</code> and <code>thr.cond</code> will be used to run ISA.
<code>no.seeds</code>	Number of seeds to run ISA from.

## Details

Please read tutorial vignette included in this package for an introduction on ISA. The `isa2`-package manual page in the `isa2` package is also useful.

The ISA function performs the ISA algorithm on the supplied expression data. This involves the following steps:

1. Filtering the features (i.e. probe sets) according to their variance. You will need the `genefilter` package for this. The default filtering function keeps the features that have an [IQR](#) of 0.5 or more. See [genefilter](#) for details on how to create filtering functions. If NA is given as the `flist` argument, then no filtering is performed.
2. Filtering the features by mapping them to Entrez genes. Features that do not map to Entrez genes are removed from the data set. If more features map to the same Entrez gene, then only the one with the highest variance will be kept.

3. Calling the `isa` function in the `isa2` package to perform the Iterative Signature Algorithm. This itself performs the following steps:
  - (a) Normalizing the data by calling `isa.normalize`.
  - (b) Generating random input seeds via `generate.seeds`.
  - (c) Running ISA with all combinations of given feature and sample thresholds, by calling `isa.iterate`.
  - (d) Merging similar modules, separately for each threshold combination, by calling `isa.unique`.
  - (e) Filtering the modules separately for each threshold combination, by calling `isa.filter.robust` in the `isa2` package.
  - (f) Putting all modules from the runs with different thresholds into a single object.
  - (g) Merging similar modules, across all threshold combinations, if two modules are similar, then the one with the milder thresholds is kept.
4. Creates an `ISAModules` object from the ISA results.

**Value**

An `ISAModules-class` object.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

Ihmels J, Friedlander G, Bergmann S, Sarig O, Ziv Y, Barkai N: Revealing modular organization in the yeast transcriptional network *Nat Genet.* 2002 Aug;31(4):370-7. Epub 2002 Jul 22

Ihmels J, Bergmann S, Barkai N: Defining transcription modules using large-scale gene expression data *Bioinformatics* 2004 Sep 1;20(13):1993-2003. Epub 2004 Mar 25.

**See Also**

The vignette included in the `eisa` package.

**Examples**

```
library(ALL)
data(ALL)
modules <- ISA(ALL, thr.gene=2.7, thr.cond=1.4)
modules
```

---

ISA-Biclust conversion

*Convert ISA modules to a Biclust object, or the opposite*

---

## Description

The biclust package implements several biclustering algorithms in a unified framework. The result of the biclustering is a **Biclust** object. These functions allow the conversion between **Biclust** and **ISAModules** objects.

## Usage

```
annotate(biclusters, data)
```

## Arguments

biclusters	A Biclust object.
data	An ExpressionSet object.

## Details

To convert an ISAModules object (mods) to a Biclust object (bc), you can do:

```
bc <- as(mods, "Biclust")
```

The seed data and run data of the ISAModules object is stored in the Parameters slot of the Biclust object. The ISA scores are binarized by the conversion.

To convert a Biclust object (bc) to an ISAModules object (mods), you can call:

```
mods <- as(bc, "ISAModules")
```

The Parameters slot of the Biclust object is used as the run data of the ISAModules object. The seed data of the new object will be an empty data frame.

The annotate function puts biological annotation into a Biclust object. It is suggested to use it before converting the Biclust object to ISAModules, so that ISA visualization functions and enrichment calculations can make use of this information.

## Value

annotate returns a Biclust object.

## Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

Sebastian Kaiser, Rodrigo Santamaria, Roberto Theron, Luis Quintales and Friedrich Leisch. (2009). biclust: BiCluster Algorithms. R package version 0.8.1. <http://CRAN.R-project.org/package=biclust>

## Examples

```
if (require(biclust)) {

  library(ALL)
  data(ALL)
  ALL.filtered <- ALL[sample(1:nrow(ALL), 1000),]

  # Biclust -> ISAModules
  set.seed(1)
  Bc <- biclust(exprs(ALL.filtered), BCPlaid(),
               fit.model = ~m + a + b, verbose = FALSE)
  Bc <- annotate(Bc, ALL.filtered)
  modules <- as(Bc, "ISAModules")
  Bc
  modules
  getNoFeatures(modules)
  getNoSamples(modules)

  # ISAModules -> Biclust
  data(ALLModulesSmall)
  Bc2 <- as(ALLModulesSmall, "Biclust")
  ALLModulesSmall
  getNoFeatures(ALLModulesSmall)
  getNoSamples(ALLModulesSmall)
  Bc2

}
```

---

ISA2heatmap

*Heatmap of a transcription module*

---

## Description

Create a heatmap plot for an ISA module.

## Usage

```
ISA2heatmap (modules, module, eset, norm = c("raw", "feature", "sample"),
            scale = c("none", "row", "column"), ...)
```

**Arguments**

modules	An <a href="#">ISAModules</a> object.
module	Numeric scalar, the number of the module to plot.
eset	An ExpressionSet or ISAExpressionSet object. If an ExpressionSet object is supplied (and the norm argument is not set to 'raw'), then it is normalised by calling <a href="#">ISANormalize</a> on it. A subset of eset is selected that corresponds to the features included in modules.
norm	Character constant, specifies whether and how to normalize the expression values to plot. 'raw' plots the raw expression values, 'feature' the expression values scaled and centered for each feature (=gene) separately and if 'sample' is specified then the expression values are centered and scaled separately for each sample.
scale	Character scalar, passed to the <a href="#">heatmap</a> function.
...	Additional arguments, they are passed to the <a href="#">heatmap</a> function.

**Value**

The same as [heatmap](#).

**Author(s)**

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

[heatmap](#)

**Examples**

```
library(ALL)
data(ALL)
data(ALLModulesSmall)

if (interactive()) {
  ISA2heatmap(ALLModulesSmall, 1, ALL, norm="feature")
}
```

ISACHR

*Calculate chromosome enrichment for transcription modules***Description**

Hypergeometric test(s) to check whether significantly many genes of an ISA module are on the same chromosome.

**Usage**

```
ISACHR (modules, ann = annotation(modules), features = featureNames(modules),
        hgCutoff = 0.05, correction = TRUE, correction.method = "holm")
```

**Arguments**

modules	An ISAModules object, a set of ISA modules.
ann	Character scalar. The annotation package to be used. By default it is taken from the modules argument.
features	Character vector. The names of the features. By default it is taken from the modules argument.
hgCutoff	Numeric scalar. The cutoff value to be used for the enrichment significance. This can be changed later, without recalculating the test.
correction	Logical scalar, whether to perform multiple hypothesis testing correction.
correction.method	Character scalar, the multiple testing correction method to use. Possible values: "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none". See the <a href="#">p.adjust</a> function for details on these.

**Details**

The hypergeometric test, a version Fisher's exact test, takes a chromosome and a gene set (in our case coming from an ISA module) and asks whether the number of genes in the set that are on the given chromosome is significantly more (or less) than what one would expect by chance.

ISACHR performs the hypergeometric test for every module, for every chromosome. The chromosome mapping is taken from the annotation package of the chip.

ISACHR currently cannot test for under-representation.

**Value**

A [CHRListHyperGResult](#) object.

**Author(s)**

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

[ISAGO](#), [ISAKEGG](#) and [ISAmiRNA](#) for other enrichment calculations.

The Category package.

**Examples**

```
data(ALLModulesSmall)
CHR <- ISACHR(ALLModulesSmall)
CHR
sigCategories(CHR)[[2]]
geneIdsByCategory(CHR)[[2]][[1]]
```

---

ISAExpressionSet-class

*Expression Set, normalized for using with ISA*

---

**Description**

An ExpressionSet object (Biobase package) that contains expression values normalized for use with the Iterative Signature Algorithm.

**Usage**

```
## S4 method for signature ISAExpressionSet
featExprs(object)
## S4 method for signature ISAExpressionSet
sampExprs(object)

## S4 method for signature ISAExpressionSet
hasNA(object)
## S4 replacement method for signature ISAExpressionSet
hasNA(object) <- value

## S4 method for signature ISAExpressionSet
prenormalized(object)
## S4 replacement method for signature ISAExpressionSet
prenormalized(object) <- value
```

**Arguments**

object            An ISAExpressionSet object.  
value             A logical scalar, new value of the hasNA or prenormalized attribute.

## Details

An ISAEExpressionSet contains three expression matrices.

In most cases, when then ISAEExpressionSet was produced by the [ISANormalize](#) function, these are: the original, raw data, the feature-wise scaled and centered data and the sample-wise scaled and centered data.

Two additional methods were defined to access the extra matrices: `featExprs` returns the feature-wise standardized data, `sampExprs` the sample-wise standardized one.

The `hasNA` function returns TRUE if NA or NaN values appear in at least one of the expression matrices.

The `prenormalized` function returns TRUE if the data was prenormalized, see [ISANormalize](#) for details.

## Value

`featExprs` and `sampExprs` both return a matrix.

`hasNA` and `prenormalized` return a logical vector of length one.

## Author(s)

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

[ISANormalize](#), `ExpressionSet` in the Biobase package.

## Examples

```
library(ALL)
data(ALL)

# Do the normalization
ALL.normed <- ISANormalize(ALL)
class(ALL.normed)
dim(exprs(ALL.normed))
dim(featExprs(ALL.normed))
dim(sampExprs(ALL.normed))

# Check that we indeed have Z-scores
all(abs(apply(featExprs(ALL.normed), 2, mean) ) < 1e-12)
all(abs(1-apply(featExprs(ALL.normed), 2, sd)) < 1e-12)

all(abs(apply(sampExprs(ALL.normed), 1, mean) ) < 1e-12)
all(abs(1-apply(sampExprs(ALL.normed), 1, sd)) < 1e-12)
```

---

ISAFilterRobust	<i>Robustness of ISA biclusters</i>
-----------------	-------------------------------------

---

### Description

Robustness of ISA biclusters. The more robust biclusters are more significant, in the sense that they are less likely to be found in random data.

### Usage

```
ISARobustness(data, isaresult)
ISAFilterRobust(data, isaresult, ...)
```

### Arguments

data	An ExpressionSet or ISAEExpressionSet object. If an ExpressionSet object is supplied, then it is normalised by calling <a href="#">ISANormalize</a> on it.
isaresult	An ISAModules object, a set of modules.
...	Additional arguments, they are passed to the <code>isa.filter.robust</code> function in the <code>isa2</code> package.

### Details

ISARobustness calculates robustness scores for ISA modules. The higher the score, the more robust the module.

ISAFilterRobust filters a set of ISA modules, by running ISA on the randomized expression data and then eliminating all modules that have a robustness score that is lower than at least one robustness score found in the randomized data.

The same feature and sample thresholds are used to calculate the randomized robustness scores. In other words the limit for the filtering depends on the feature and sample thresholds.

You can find more details in the manual of the [robustness](#) function in the `isa2` package.

### Value

ISARobustness returns a numeric vector, the robustness scores of the biclusters.

ISAFilterRobust returns the filtered ISAModules instance.

### Author(s)

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

### References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

The [robustness](#) function in the `isa2` package.

**Examples**

```
data(ALLModules)
library(ALL)
data(ALL)
rob <- ISARobustness(ALL, ALLModules)
summary(rob)
```

---

 ISAGO

---

*Calculate Gene Ontology enrichment for transcription modules*


---

**Description**

Gene Ontology enrichment is calculated for each ISA module separately. In the end the result is corrected for multiple hypothesis testing.

**Usage**

```
ISAGO (modules, ann = annotation(modules), features = featureNames(modules),
      hgCutoff = 0.05, correction = TRUE, correction.method = "holm")
```

**Arguments**

<code>modules</code>	An ISAModules object, a set of ISA modules.
<code>ann</code>	Character scalar. The annotation package to be used. By default it is taken from the <code>modules</code> argument.
<code>features</code>	Character vector. The names of the features. By default it is taken from the <code>modules</code> argument.
<code>hgCutoff</code>	Numeric scalar. The cutoff value to be used for the enrichment significance. This can be changed later, without recalculating the test.
<code>correction</code>	Logical scalar, whether to perform multiple hypothesis testing correction.
<code>correction.method</code>	Character scalar, the multiple testing correction method to use. Possible values: "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none". See the <a href="#">p.adjust</a> function for details on these.

**Details**

The Gene Ontology is a database of gene annotation. The annotating labels (these are called terms) are standardized and organized into a directed acyclic graph. In other words terms may have more specific sub-terms, that can have even more specific sub-sub-terms, and so on.

The Gene Ontology database has three big sub-graphs, the root nodes (the most general terms) of these are the direct children of the root term of the whole ontology: biological process, cellular component, molecular function. They are usually referred to as ontologies.

The hypergeometric test, a version Fisher's exact test, takes a GO term and a gene set (in our case coming from an ISA module) and asks whether the number of genes in the set annotated by the term is significantly more (or less) than what one would expect by chance.

ISAGO performs the hypergeometric test for every module, for all GO terms of the three GO ontologies. The GO data is taken from the GO.db package and the annotation package of the chip.

ISAGO currently cannot test for under-representation and the conditional test, as implemented in the GOstats package, is not available either.

### Value

A list with three `GOListHyperGResult` objects, for the three Gene Ontologies, named

BP	aka Biological Processes
CC	aka Cellular Components
MF	aka Molecular Function

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### References

The Gene Ontology Consortium. Gene ontology: tool for the unification of biology. *Nat. Genet.* May 2000;25(1):25-9.

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### See Also

[ISAKEGG](#), [ISACHR](#), [ISAmiRNA](#) for other enrichment calculations.

The GO.db, GOstats and Category packages.

### Examples

```
data(ALLModulesSmall)
GO <- ISAGO(ALLModulesSmall)
GO
summary(GO$BP)[[1]][,1:5]
```

**Description**

These functions create various sophisticated HTML pages from a set of ISA biclusters.

**Usage**

```
ISAHTMLTable (modules, target.dir, which = NULL,
  template = system.file("autogen", package = "eisa"), GO = NULL,
  KEGG = NULL, miRNA = NULL, CHR = NULL, htmltitle = NULL,
  notes = NULL, seed = NULL, extra = list())
```

```
ISAHTMLModules (eset, modules, which = NULL, target.dir,
  template = system.file("autogen", package = "eisa"), GO = NULL,
  KEGG = NULL, miRNA = NULL, CHR = NULL, cond.to.include = NULL,
  cond.col = "white", sep = NULL, seed = NULL, condPlot = TRUE)
```

```
ISAHTML (eset, modules, target.dir, template = system.file("autogen",
  package = "eisa"), GO, KEGG, miRNA = NULL, CHR = NULL, htmltitle = NULL,
  notes = NULL, seed = NULL, table.extra = list(), cond.to.include = NULL,
  cond.col = "white", sep = NULL, condPlot = TRUE, which = NULL)
```

**Arguments**

modules	An ISAModules object.
target.dir	Character vector of length one, the directory in which the result is placed. It is created if it does not exist.
which	Numeric vector, which modules to include in the table (ISAHTMLTable); or, which modules to create HTML pages for (ISAHTML and ISAHTMLModules). All modules are used if this argument is NULL, which is the default.
template	The directory containing the HTML template files. By default the template included in the eisa package is used.
GO	List of three <a href="#">GOListHyperGResult</a> objects, as returned by the <a href="#">ISAGO</a> function.
KEGG	A <a href="#">KEGGListHyperGResult</a> object, usually the output of the <a href="#">ISAKEGG</a> function.
miRNA	A <a href="#">miRNAListHyperGResult</a> object, or NULL. See also the <a href="#">ISAmiRNA</a> function.
CHR	A <a href="#">CHRListHyperGResult</a> object or NULL, see also the <a href="#">ISACHR</a> function.
htmltitle	Character vector of length one, the title of the HTML page.
notes	Character vector of length one. Optional HTML text, on the default template it is placed on the top of the page, above the table.
seed	Either NULL, or a character vector, with an optional column that is added to the module table.

<code>extra</code>	Extra columns to put in the HTML table. It should be a named list of character vectors, each with the same length as the number of modules.
<code>table.extra</code>	This is passed to <code>ISAHTMLTable</code> as the <code>extra</code> argument.
<code>eset</code>	An <code>ExpressionSet</code> or <code>ISAExpressionSet</code> object. If an <code>ExpressionSet</code> object is supplied, then it is normalised by calling <code>ISANormalize</code> on it.
<code>cond.to.include</code>	Numeric or character vector, specifies which columns of the phenotype data of the original expression matrix are included in the tables of samples. By default the first six columns are included.
<code>cond.col</code>	This is passed to <code>condPlot</code> as the <code>col</code> argument.
<code>sep</code>	This is passed to <code>condPlot</code> as the <code>sep</code> argument.
<code>condPlot</code>	Logical scalar, whether to create condition plots. If an alternative biclustering method was used to find the modules, then probably it makes no sense creating condition plots for them.

### Details

`ISAHTMLTable` creates an HTML page, a summary of the results of the modular analysis, including enrichment analysis of the modules.

`ISAHTMLModules` creates a separate HTML page for each module, including the following elements:

- An expression plot of the genes and samples in the module, including the ISA scores. This is done by calling `expPlot`.
- Gene Ontology tree plots for the enriched GO terms, separately for the three ontologies. These are produced by calling `gograph`.
- Tables for the enriched Gene Ontology terms, separately for the three ontologies.
- A table for the enriched KEGG pathways.
- A table for the enriched miRNA families.
- The list of genes in the module.
- The list of samples in the module.
- A condition plot (if the `condPlot` argument is `TRUE`), see `condPlot`.

By default, clicking on the rows of the table generated by `ISAHTMLTable` is linked to the HTML page of the module, generated by `ISAHTMLModules`.

`ISAHTML` calls both `ISAHTMLTable` and `ISAHTMLModules`.

### Value

These functions do not return a value. (They return `NULL`, invisibly.)

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

The vignette included in the eisa package.

## Examples

```
# Load data
library(ALL)
data(ALL)
data(ALLModulesSmall)

# Calculate enrichment
GO <- ISAGO(ALLModulesSmall)
KEGG <- ISAKEGG(ALLModulesSmall)
CHR <- ISACHR(ALLModulesSmall)

# Generate HTML summary
htmlmdir <- tempdir()
ISAHTML(ALL, modules=ALLModulesSmall, target.dir=htmlmdir,
        GO=GO, KEGG=KEGG, CHR=CHR)

# Open a browser to view the summary
if (interactive()) {
  browseURL(URLEncode(paste("file://", htmlmdir, "/maintable.html", sep="")))
}
```

---

ISAIterate

*Perform the Iterative Signature Algorithm*

---

## Description

ISAIterate performs the ISA on an ExpressionSet object, from the given input seeds.

## Usage

```
ISAIterate(data, feature.seeds, sample.seeds, thr.feats,
           thr.samp = thr.feats, ...)
```

## Arguments

**data** An ExpressionSet or ISAExpressionSet object. If an ExpressionSet object is supplied, then it is normalised by calling [ISANormalize](#) on it.

<code>feature.seeds</code>	A matrix of feature seeds. The number of rows should match the number of features in the <code>ExpressionSet</code> , each column is a seed. Either this, or the <code>sample.seeds</code> argument must be given.
<code>sample.seeds</code>	A matrix of sample seeds. The number of rows should match the number of samples in the <code>ExpressionSet</code> , each column in a seed. Either this, or the <code>feature.seeds</code> argument must be given.
<code>thr.feat</code>	Numeric scalar or vector giving the threshold parameter for the features. Higher values indicate a more stringent threshold and the result biclusters will contain less features on average. The threshold is measured by the number of standard deviations from the mean, over the values of the feature vector. If it is a vector, then it must contain an entry for each seed.
<code>thr.samp</code>	Numeric scalar or vector giving the threshold parameter for the columns. The analogue of <code>thr.feat</code> .
<code>...</code>	Additional arguments, these are passed to the <code>isa.iterate</code> function in the <code>isa2</code> package. See also details below.

### Details

Performs the ISA from the given seeds. It is allowed to specify both type of seeds, then a half-iteration is performed on the `sample.seeds` and they are appended to the `feature.seeds`.

The `isa.iterate` function of the `isa2` package is called to do all the work, this has the following extra parameters: `direction`, `convergence`, `cor.limit`, `eps`, `corx`, `oscillation`, `maxiter`. Please see the `isa.iterate` manual for details about them.

### Value

An `ISAModules` object.

### Author(s)

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

### References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### See Also

The `ISA` function for an easier interface with parameters.

### Examples

```
library(ALL)
data(ALL)

# Only use a small sample, to make this example finish faster
ALL.normed <- ISANormalize(ALL)[sample(1:nrow(ALL), 1000),]
```

```
# Generate seeds and do ISA
seeds <- generate.seeds(nrow(ALL.normed), count=100)
modules <- ISAIterate(ALL.normed, seeds, thr.feat=3, thr.samp=2)
modules
```

ISAKEGG

*Calculate KEGG Pathway enrichment for transcription modules***Description**

KEGG pathway enrichment is calculated for each ISA module separately. In the end the result is corrected for multiple hypothesis testing.

**Usage**

```
ISAKEGG (modules, ann = annotation(modules), features = featureNames(modules),
        hgCutoff = 0.05, correction = TRUE, correction.method = "holm")
```

**Arguments**

modules	An ISAModules object, a set of ISA modules.
ann	Character scalar. The annotation package to be used. By default it is taken from the modules argument.
features	Character vector. The names of the features. By default it is taken from the modules argument.
hgCutoff	Numeric scalar. The cutoff value to be used for the enrichment significance. This can be changed later, without recalculating the test.
correction	Logical scalar, whether to perform multiple hypothesis testing correction.
correction.method	Character scalar, the multiple testing correction method to use. Possible values: "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none". See the <a href="#">p.adjust</a> function for details on these.

**Details**

KEGG (Kyoto Encyclopedia of Genes and Genomes) is a collection of online databases dealing with genomes, enzymatic pathways, and biological chemicals. The PATHWAY database records networks of molecular interactions in the cells, and variants of them specific to particular organisms.

The hypergeometric test, a version Fisher's exact test, takes a KEGG pathway and a gene set (in our case coming from an ISA module) and asks whether the number of genes in the set participating in the pathway, is significantly more (or less) than what one would expect by chance.

ISAKEGG performs the hypergeometric test for every module, for all KEGG pathways. The KEGG data is taken from the KEGG.db package and the annotation package of the chip.

ISAKEGG currently cannot test for under-representation.

**Value**

A `KEGGListHyperGResult` object.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

<http://www.genome.jp/kegg/>

Kanehisa M, Goto S, Kawashima S, Okuno Y, Hattori M., The KEGG resource for deciphering the genome, *Nucleic Acids Res.* 2004 Jan 1;32(Database issue):D277-80.

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

[ISAGO](#), [ISACHR](#), [ISAmiRNA](#) for other enrichment calculations.

The `KEGG.db` and `Category` packages.

**Examples**

```
data(ALLModulesSmall)
KEGG <- ISAKEGG(ALLModulesSmall)
KEGG
sigCategories(KEGG)[[1]]
summary(KEGG)[[1]][,1:5]
```

---

ISAmiRNA

*Calculate (predicted) miRNA target enrichment for transcription modules*

---

**Description**

This function performs enrichment calculations with respect to predicted miRNA targets to check whether an ISA module contains many genes that are targets of the same miRNA.

**Usage**

```
ISAmiRNA (modules, ann = annotation(modules), features = featureNames(modules),
          hgCutoff = 0.05, correction = TRUE, correction.method = "holm")
```

**Arguments**

modules	An ISAModules object, a set of ISA modules.
ann	Character scalar. The annotation package to be used. By default it is taken from the modules argument.
features	Character vector. The names of the features. By default it is taken from the modules argument.
hgCutoff	Numeric scalar. The cutoff value to be used for the enrichment significance. This can be changed later, without recalculating the test.
correction	Logical scalar, whether to perform multiple hypothesis testing correction.
correction.method	Character scalar, the multiple testing correction method to use. Possible values: “holm”, “hochberg”, “hommel”, “bonferroni”, “BH”, “BY”, “fdr”, “none”. See the <a href="#">p.adjust</a> function for details on these.

**Details**

miRNAs are short RNA fragments that specifically regulate (usually inhibit) the expression of genes. Some genes have been experimentally validated as targets of a given miRNA, but we currently don't know the target genes of most miRNAs.

TargetScan is a database of predicted miRNA targets. The predictions are done based many factors, including the conservation of the target region during evolution.

The hypergeometric test, a version Fisher's exact test, takes a miRNA and a gene set (in our case coming from an ISA module) and asks whether the number of genes in the set regulated by the miRNA is significantly more (or less) than what one would expect by chance.

ISAmiRNA performs the hypergeometric test for every module, for all miRNAs in the TargetScan database.

In order to use this function, TargetScan annotation packages are needed.

**Value**

A [miRNAListHyperGResult](#) object.

**Author(s)**

Gabor Csardi <[csardi.gabor@gmail.com](mailto:csardi.gabor@gmail.com)>

**References**

Conserved Seed Pairing, Often Flanked by Adenosines, Indicates that Thousands of Human Genes are MicroRNA Targets Benjamin P Lewis, Christopher B Burge, David P Bartel. *Cell*, 120:15-20 (2005).

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

[ISAGO](#), [ISAKEGG](#) and [ISACHR](#) for other enrichment calculations.

The `Category` package.

**Examples**

```
data(ALLModulesSmall)

if (require(targetscan.Hs.eg.db)) {
  miRNA <- ISAmiRNA(ALLModulesSmall)
  summary(miRNA, p=0.1)[[7]]
}
```

---

ISAModules-class	<i>A set of ISA modules</i>
------------------	-----------------------------

---

**Description**

An ISAModules object stores the results of one ISA run. It contains a set of biclusters (=modules or transcription modules) and some meta information about the ISA run and the input data.

**Usage**

```
## S4 method for signature ISAModules
dim(x)
## S4 method for signature ISAModules
featureNames(modules)
## S4 method for signature ISAModules
sampleNames(modules)
## S4 method for signature ISAModules
annotation(modules)
## S4 method for signature ISAModules
getOrganism(modules)
## S4 method for signature ISAModules
pData(modules)

## S4 method for signature ISAModules
seedData(modules)
## S4 method for signature ISAModules
runData(modules)
## S4 method for signature ISAModules
featureThreshold(modules, mods)
## S4 method for signature ISAModules
sampleThreshold(modules, mods)

## S4 method for signature ISAModules
length(x)
```

```

## S4 method for signature ISAModules
getNoFeatures(modules, mods)
## S4 method for signature ISAModules
getNoSamples(modules, mods)

## S4 method for signature ISAModules
getFeatures(modules, mods)
## S4 method for signature ISAModules
getSamples(modules, mods)
## S4 method for signature ISAModules
getFeatureNames(modules, mods)
## S4 method for signature ISAModules
getSampleNames(modules, mods)
## S4 method for signature ISAModules
getFeatureScores(modules, mods)
## S4 method for signature ISAModules
getSampleScores(modules, mods)
## S4 method for signature ISAModules
getFeatureMatrix(modules, binary = FALSE,
                  sparse = FALSE, mods)
## S4 method for signature ISAModules
getSampleMatrix(modules, binary = FALSE,
                sparse = FALSE, mods)
## S4 method for signature ISAModules
getFullFeatureMatrix(modules, eset, mods)
## S4 method for signature ISAModules
getFullSampleMatrix(modules, eset, mods)

## S4 method for signature ISAModules,ANY,ANY
x[i, j, ..., drop = FALSE]
## S4 method for signature ISAModules,ANY,ANY
x[[i, j, ..., drop = FALSE]]

```

### Arguments

<code>x, modules</code>	An ISAModules object.
<code>mods</code>	An optional numeric index vector for the modules. If given, the information is only returned only for the specified modules.
<code>binary</code>	Logical scalar. Whether to binarize the feature or sample scores.
<code>sparse</code>	Logical scalar. Whether to return a sparse matrix. The <code>Matrix</code> package is required for sparse matrices.
<code>eset</code>	An ExpressionSet or ISAExpressionSet object. This is needed for calculating the scores of the features/samples that are not in the module. If an ExpressionSet object is supplied, then it is normalised by calling <code>ISANormalize</code> on it.
<code>i</code>	For '[' an index vector for selecting features (=probes, genes). For '['[ an index vector for selecting modules.
<code>j</code>	For '[' an index vector for selecting samples. It is ignored for '['[.

... Additional indexing arguments, they are not used, just ignored.  
 drop This argument is currently not used, just silently ignored.

### Details

An ISAModules object contains a set of biclusters, obtained using one run of the Iterative Signature Algorithm.

Various operations are defined such an object, here we document all of them, in several groups.

### Value

dim returns a numeric vector of length two. featureNames and sampleNames return a character vector. annotation and getOrganism return a character vector of length one. pData returns a data frame.

seedData returns a data frame, see more below. runData returns a named list, see more below. featureThreshold and sampleThreshold return a numeric vector.

length returns a numeric scalar. getNoFeatures and getNoSamples return a numeric vector.

getFeatures and getSamples return a list of named numeric vectors. getFeatureNames and getSampleNames return a list of character vectors. getFeatureScores and getSampleScores return a list of named numeric vectors. getFeatureMatrix, getSampleMatrix, getFullFeatureMatrix and getFullSampleMatrix return a numeric matrix.

### Information about the input data.

dim returns the dimension of the input expression matrix, number of features times number of samples.

featureNames returns a character vector, the names of the features in the original input matrix. I.e. in the input was an ExpressionSet for an Affymetrix array, then the Affymetrix probe IDs are returned.

sampleNames returns a character vector, the names of the samples in the original expression set.

annotation returns a character scalar, the name of the array for the input expression set. More precisely, the annotation slot of the input ExpressionSet is returned, this is the name of the annotation package to use for the ExpressionSet.

getOrganism returns the scientific name of the organism for which the input expression data was measures. This is obtained by loading the annotation package of the input ExpressionSet object, so that must be installed.

pData returns the phenotypic data attached to the input ExpressionSet object, in a data frame, samples as rows and various phenotypic variables as columns.

### Information about the ISA run

seedData returns information about the modules. Each row of the returned data frame corresponds to one module, the columns are various variables:

**iterations** The number of ISA iterations needed to find the module.

**oscillation** The length of the oscillation cycle for oscillating modules, zero for others.

- thr.row** The feature (=gene) threshold used for finding the module.
- thr.col** The sample (=condition) threshold used for finding the module.
- freq** The number of times the module was found. This is always one, unless [ISAUnique](#) was performed.
- rob** The robustness score of the module. See [ISARobustness](#) for details.
- rob.limit** The robustness limit that was used for filtering the modules. As this depends of the feature and sample thresholds, it may be different for different modules.

runData returns information about the ISA runs, it is a named list with elements:

- annotation** The annotation package corresponding to the input expression set.
- organism** The scientific name of the organism.
- direction** The direction parameter of the ISA. Please see [ISAIterate](#) for details.
- convergence** The method to determine ISA convergence, a character scalar. Please see [ISAIterate](#) for details.
- cor.limit** Correlation limit for the “cor” convergence criterium, see [ISAIterate](#) for details.
- eps** Difference limit for the “eps” convergence criterium, see [ISAIterate](#) for details.
- corx** Size of the time window for the “corx” convergence criterium, see [ISAIterate](#) for details.
- maxiter** The maximum number of ISA iterations that was allowed.
- oscillation** Logical, whether oscillating modules were considered during the ISA iteration.
- N** Numeric scalar, the number of input seeds that were used to find the modules.
- unique** Logical scalar, whether [ISAUnique](#) was run on the modules.
- prenormalize** Logical scalar, whether the input data was prenormalized during ISA normalization, see [ISANormalize](#).
- hasNA** Logical scalar, whether the normalized input data contained some NA or NaN values.
- rob.perms** Numeric scalar, the number of times the input data was scrambled when the modules were filtered according to robustness.

Note that some of these might be missing, i.e. rob.perms is only present if [ISAFILTERRobust](#) was performed.

featureThreshold returns the feature thresholds that were used to find the modules.

sampleThreshold returns the sample thresholds that were used to find the modules.

### Information about the modules

length returns the number of modules.

getNoFeatures returns the number of features (=genes) in the input data. The number of features *after* filtering is returned if the input data was filtered.

getNoSamples returns the number of samples (=conditions) in the input data.

### Retrieve the modules

`getFeatures` returns the indices of the features included in the modules. It returns a list, with one entry for each module. Each entry contains the indices of the features (=genes) in the corresponding module.

`getSamples` does the same as `getFeatures`, but for samples.

`getFeatureNames` is similar to `getFeatures`, but returns feature names instead of feature indices.

`getSampleNames` is similar to `getSamples`, but returns sample names instead of sample indices.

`getFeatureScores` returns the feature scores for the selected modules (all modules by default). It returns a list, with one entry for each module. Each list entry contains the feature scores for one module, in a named numeric vector.

`getSampleScores` is similar to `getFeatureScores`, but for samples and sample scores.

`getFeatureMatrix` returns feature scores for the specified modules (all modules by default) in a matrix form. The number of rows is the number of features and the number of columns is the number of modules requested. It can optionally binarize the values.

`getSampleMatrix` is similar to `getFeatureMatrix`, but for sample scores.

`getFullFeatureMatrix` is similar to `getFeatureMatrix`, but is also calculates scores for the features that were not included in the module. For this it performs one ISA iteration and omits the thresholding step. You need to supply the normalized (or the original) expression data to make this possible.

`getFullSampleMatrix` is the same as `getFullFeatureMatrix`, but for sample scores.

### Indexing

A couple of indexing operations were defined to make it easier selecting subsets of modules, features or samples from an `ISAModules` object.

The `'[['` double bracket indexing operator can be used with a single index vector to select a subset of modules.

The `'['` single bracket indexing operator can be used to restrict an `ISAModules` object to a subset of features and/or samples. The first index corresponds to features, the second to samples. Indices can be numeric, logical or character vectors, for the latter feature and sample names are used.

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### See Also

The vignette included in the `eisa` package.

**Examples**

```
data(ALLModulesSmall)
ALLModulesSmall

length(ALLModulesSmall)
dim(ALLModulesSmall)
annotation(ALLModulesSmall)
getOrganism(ALLModulesSmall)

seedData(ALLModulesSmall)

getNoFeatures(ALLModulesSmall)
getNoSamples(ALLModulesSmall)

getFeatureScores(ALLModulesSmall, 1)[[1]]
```

---

ISANormalize

*Normalize expression data for the Iterative Signature Algorithm*

---

**Description**

ISA works best if the input data is centered and scaled. ISANormalize performs this transformation.

**Usage**

```
ISANormalize (data, prenormalize = FALSE)
```

**Arguments**

data	An ExpressionSet object.
prenormalize	If this argument is set to TRUE, then feature-wise scaling is calculated on the sample-wise scaled matrix and not on the input matrix directly.

**Details**

It was observed that the ISA works better if the input matrix is scaled and its rows have mean zero and standard deviation one.

An ISA step consists of two sub-steps, and this implies two different normalizations, in the first the rows (=features), in the second the columns (=samples) of the input matrix will be scaled and centered.

**Value**

An [ISAExpressionSet](#) object.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

The [ISA](#) function for an easier ISA workflow.

## Examples

```
library(ALL)
data(ALL)

# Do the normalization
ALL.normed <- ISANormalize(ALL)
class(ALL.normed)
dim(exprs(ALL.normed))
dim(feateExprs(ALL.normed))
dim(sampExprs(ALL.normed))

# Check that we indeed have Z-scores
all(abs(apply(feateExprs(ALL.normed), 2, mean) ) < 1e-12)
all(abs(1-apply(feateExprs(ALL.normed), 2, sd)) < 1e-12)

all(abs(apply(sampExprs(ALL.normed), 1, mean) ) < 1e-12)
all(abs(1-apply(sampExprs(ALL.normed), 1, sd)) < 1e-12)
```

---

ISASweep

*Create an ISA module tree*

---

## Description

These functions create and plot the hierarchical description of an expression data set, by applying the ISA with various thresholds, and connecting the related modules. See details below.

## Usage

```
ISASweep (expset, modules, ...)
ISASweepGraph (sweep.result)
ISASweepGraphPlot (graph, vertex.label=V(graph)$id,
  vertex.label.topleft=NA, vertex.label.topright=NA,
  vertex.label.bottomleft=NA, vertex.label.bottomright=NA,
  vertex.label.cex=0.8, edge.label=NA, asp=FALSE, rescale=FALSE,
  xlim=range(graph$layout[,1]), ylim=range(graph$layout[,2]),
  thresholds=TRUE, xlab=NA, ylab=NA, ...)
```

**Arguments**

<code>expset</code>	The expression set object, if it is not an <code>ISAExpressionSet</code> , then <code>ISANormalize</code> is called on it.
<code>modules</code>	An <code>ISAModules</code> object.
<code>...</code>	Additional arguments. <code>ISASweep</code> passes these to <code>isa.sweep</code> ; <code>ISASweepGraphPlot</code> passes additional arguments to <code>plot.igraph</code> .
<code>sweep.result</code>	An <code>ISAModules</code> object that contains the sweep tree information as well.
<code>graph</code>	An <code>igraph</code> graph object, the sweep tree.
<code>vertex.label</code>	Vertex labels, by default the ids of the modules.
<code>vertex.label.topleft</code>	Vertex labels to put at the top left corner.
<code>vertex.label.topright</code>	Vertex labels to put at the top right corner.
<code>vertex.label.bottomleft</code>	Vertex labels to put at the bottom left corner.
<code>vertex.label.bottomright</code>	Vertex labels to put at the bottom right corner.
<code>vertex.label.cex</code>	Magnification factor for the vertex labels.
<code>edge.label</code>	Edge labels.
<code>asp</code>	Logical scalar, whether the plot should have 1:1 aspect ratio.
<code>rescale</code>	Logical scalar, whether to rescale the layout coordinates to the <code>[-1,1]</code> interval.
<code>xlim</code>	Numeric vector of length two, the X limits of the plot.
<code>ylim</code>	Numeric vector of length two, the Y limits of the plot.
<code>thresholds</code>	Logical scalar, whether to add the (non-constant) thresholds to the plot.
<code>xlab</code>	The label of the horizontal axis, by default omitted.
<code>ylab</code>	The label of the vertical axis, by default omitted.

**Details**

The ISA uses two threshold parameters that tune the sizes of the transcription modules. The sweep graph of an expression set is defined as the following. It is a directed graph, where the vertices are ISA modules, found at some threshold parameter values. There is an edge from module A to module B, if using 1) (the genes of) module A as the seed vector and 2) the threshold parameters used to find module B, the ISA converges to module B.

The `ISASweep` function creates an ISA sweep tree, in which one threshold parameter is kept fixed and the other varies. It starts from the modules found at the most stringent (=highest) threshold parameters, and uses them individually as seeds at the next less stringent threshold level. If this ISA iteration converges to an already known module, then an edge of the sweep tree is found. If the iteration converges to a new module, then this is added to the module list, together with the sweep tree edge. Then we proceed with the next level of modules, towards the less stringent threshold parameters.

The `ISASweepGraph` function creates a graph object that corresponds to the sweep tree of the expression set.

The `ISASweepGraphPlot` function plots a graph created with `ISASweepGraph`.

**Value**

ISASweep returns an ISAModules object, with some seed data added.

ISASweepGraph returns an igraph graph object.

ISASweepGraphPlot returns NULL, invisibly.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**Examples**

```
library(genefilter)
library(ALL)
data(ALL)

varLimit <- 0.5
kLimit <- 4
ALimit <- 5
flist <- filterfun(function(x) var(x)>varLimit, kOverA(kLimit,ALimit))
ALL.filt <- ALL[genefilter(ALL, flist), ]
ALL.filt2 <- ALL.filt[, grepl("^B", ALL.filt$BT)]

# Run ISA
set.seed(2)
modules <- ISA(ALL.filt2, flist=NA, thr.gene=seq(2,4,by=0.5), thr.cond=1)

# Do the sweep
modules2 <- ISASweep(ALL.filt2, modules)
modules2

# Plot it
## Not run:
G <- ISASweepGraph(modules2)
ISASweepGraphPlot(G)

## End(Not run)
```

**Description**

From a potentially non-unique set of ISA modules remove all modules that are similar to another module that was found earlier.

**Usage**

```
ISAUnique(data, isareult, ...)
```

**Arguments**

<code>data</code>	An ExpressionSet or ISAExpressionSet object. If an ExpressionSet object is supplied, then it is normalised by calling <code>ISANormalize</code> on it.
<code>isareult</code>	An ISAModules object to be filtered.
<code>...</code>	Additional arguments, these are passed to the <code>isa.unique</code> function in the <code>isa2</code> package. See also details below.

**Details**

The ISA algorithm might very well find the same modules from many different input seeds, so the output of the `ISAIterate` function is usually not unique: many modules are very similar to each other.

ISAUnique eliminates the duplicates and potentially also the non-convergent modules.

The work is performed by calling the `isa.iterate` function in the `isa2` package. The following additional arguments can be specified to be passed to this function:

**method** Character scalar giving the method to be used to determine if two biclusters are similar. Right now only 'cor' is implemented, this keeps both biclusters if their Pearson correlation is less than `cor.limit`, both for their row and column scores. See also the `neg.cor` argument.

**ignore.div** Logical scalar, if TRUE, then the divergent biclusters will be removed.

**cor.limit** Numeric scalar, giving the correlation limit for the 'cor' method.

**neg.cor** Logical scalar, if TRUE, then the 'cor' method considers the absolute value of the correlation.

**drop.zero** Logical scalar, whether to drop biclusters that have all zero scores.

**Value**

Another ISAModules object, with unique modules.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

The [ISA](#) function for an easier ISA workflow.

**Examples**

```
library(ALL)
data(ALL)

# Only use a small sample, to make this example finish faster
ALL.normed <- ISANormalize(ALL)[sample(1:nrow(ALL), 1000),]

# Generate seeds and do ISA
seeds <- generate.seeds(nrow(ALL.normed), count=100)
modules <- ISAIterate(ALL.normed, seeds, thr.feas=3, thr.samp=2)
modules

# Merge the modules
modules2 <- ISAUnique(ALL.normed, modules)
modules2
```

---

**ListHyperGParams-class**

*Classes for quick GO/KEGG/CHR/miRNA target or other enrichment calculation of multiple gene sets.*

---

**Description**

These classes extend the HyperGParams class from the Category package to perform enrichment calculation quickly for multiple gene sets.

**Usage**

```
## S4 method for signature ListHyperGParams
makeValidParams(object)
## S4 method for signature ListHyperGParams
drive(p)
## S4 replacement method for signature ListHyperGParams,logical
drive(p) <- dri

## S4 method for signature GOListHyperGParams
ontology(object)
## S4 replacement method for signature GOListHyperGParams,character
ontology(object) <- go
## S4 method for signature GOListHyperGParams
conditional(r)
## S4 replacement method for signature GOListHyperGParams,logical
conditional(r) <- cond
```

```
## S4 method for signature ListHyperGParams
hyperGTest(p)
```

### Arguments

object, p, r	A ListHyperGParams object.
dri	Logical scalar, whether to store the genes that are in the intersection of the specified gene set and the annotation category.
go	Character scalar, the ontology for GO, possible values: 'BP', 'CC', 'MF'.
cond	Logical scalar, whether to perform conditional enrichment calculation. Currently this option is ignored.

### Details

The ListHyperGParams abstract class extends HyperGParams and allows to specify a list of gene sets for the enrichment calculation instead of a single set.

ListHyperGParams calculates the enrichment much faster than the original HyperGParams classes in the Category package, especially if the calculation is performed against the same gene universe for many gene sets.

ListHyperGParams is an abstract class, it is not possible to instantiate objects from it. Instead, its various extensions must be used: GOListHyperGParams, KEGGListHyperGParams, CHRListHyperGParams and miRNAListHyperGParams.

The various ListHyperGParams objects can be created with the standard new command, by giving all necessary arguments. Please see the examples below.

### Value

makeValidParmas returns another ListHyperGParams instance that has the same class as its arguments'.

ontology returns a character vector of length one.

conditional returns a logical vector of length one.

drive returns a logical vector of length one.

### Member functions

Most of these functions are analogous to the ones defined in the Category package, the only difference is that they handle ListHyperGParams objects.

makeValidParams validates ListHyperGParams object, in particular, it removes duplicate genes, both from the gene universe and the specified gene sets; and it also makes sure that all genes in the gene sets are included in the universe.

ontology can be used to query or set the ontology for enrichment calculated against the GO database.

conditional queries or sets whether conditional GO enrichment will be performed. This feature is not implemented yet, see the Category and GOstats packages for a working implementation and more information.

drive queries or sets whether the intersections of the gene sets and the universe are stored in the result object. This information can be calculated later as well, but it is faster to store it at the same time when the hypergeometric test is performed.

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### See Also

Functions for enrichment calculation of ISA modules: [ISAGO](#), [ISAKEGG](#), [ISACHR](#), [ISAmiRNA](#).

Perhaps see also the vignette in the GOstats package.

### Examples

```
# GO enrichment, "by hand"
# Load data first
data(ALLModulesSmall)

# Create gene sets
library(hgu95av2.db)
genes <- getFeatureNames(ALLModulesSmall)
entrez <- lapply(genes, function(x) na.omit(unlist(mget(x,
  hgu95av2ENTREZID))))

# Create universe
universe <- na.omit(unlist(mget(featureNames(ALLModulesSmall),
  hgu95av2ENTREZID)))

# Create parameter object
param <- new("GOListHyperGParams", geneIds=entrez, universeGeneIds=universe,
  pvalueCutoff=0.01, drive=FALSE, ontology="BP",
  conditional=FALSE, testDirection="over",
  annotation=annotation(ALLModulesSmall))

# Do the calculation
GOBP <- hyperGTest(param)

# Inspect the result
GOBP
summary(GOBP)[[1]]

# How to create other parameter objects
paramKEGG <- new("KEGGListHyperGParams", geneIds=entrez,
  universeGeneIds=universe, drive=FALSE,
  annotation=annotation(ALLModulesSmall))
paramCHR <- new("CHRListHyperGParams", geneIds=entrez,
  universeGeneIds=universe, drive=FALSE,
  annotation=annotation(ALLModulesSmall))

# Enrichment with user-supplied categories, we use a list of
# hand-picked genes that are involved in myelin formation
```

```

mygenes <- c("YARS", "NFKB2", "NGFR", "CDH1", "NFAT5", "NDRG1", "GAP43",
"EGR2", "MSN", "ROCK1", "SREBF2", "SOX10", "FIG4", "EGR1", "PIK3R1",
"CDC42", "EDN3", "EDNRB", "NCAM1", "DHH", "OMG", "PMP22", "LAMA4",
"MPDZ", "MTMR2", "REL", "S100A1", "ITGA4", "GFAP", "FGF2", "RPSA",
"CADM1", "CDH19", "DNM2", "PAX3", "SREBF1", "DAG1", "DRP2", "SDC2",
"MBP", "RELA", "RELB", "JUN", "NAB1", "MOBP", "SKI", "COL5A2", "RHOA",
"NFASC", "NEFL", "MPZ", "MAG", "EDNRA", "ERBB4", "LITAF", "MMP2",
"PLP1", "CDKN1A", "PAK1", "RDX", "GJB1", "LAMA5", "JAM3", "ITGB1",
"PAR3", "FABP7", "LAMA2", "ERBB3", "CADM4", "FOXO4", "TSPAN31",
"GPR126", "PTK2", "RAC1", "CDKN2A", "CLDN5", "ID2", "LAMC1", "SOX2",
"CNTN2", "ERBB2", "NFKB1", "NAB2", "EDN2", "MMP9", "CCND1", "L1CAM",
"MOG")

library(org.Hs.eg.db)
myentrez <- na.omit(unlist(mget(mygenes, revmap(org.Hs.egSYMBOL))))
categories <- list(myelin=myentrez)

data(ALLModules)
genes2 <- getFeatureNames(ALLModules)
entrez2 <- lapply(genes2, function(x) na.omit(unlist(mget(x,
hgu95av2ENTREZID))))

# Create universe
universe2 <- na.omit(unlist(mget(featureNames(ALLModules),
hgu95av2ENTREZID)))

paramMY <- new("GeneralListHyperGParams", geneIds=entrez2,
universeGeneIds=universe2, drive=FALSE,
annotation=annotation(ALLModulesSmall),
categories=categories)
MY <- hyperGTest(paramMY)
MY
summary(MY)[[1]]

```

---

ListHyperGResult-class

*Classes for quick GO/KEGG/CHR/miRNA target or other enrichment calculation for multiple gene sets*

---

**Description**

These classes extend the HyperGResult class from the Category package to perform enrichment calculation quickly for multiple gene sets.

**Usage**

```

## S4 method for signature ListHyperGResult
summary(object, pvalue = pvalueCutoff(object),
categorySize = NULL)
## S4 method for signature ListHyperGResult

```

```

htmlReport(r, file = "", append = FALSE,
  label = "", digits = 3, summary.args = NULL)
## S4 method for signature ListHyperGResult
pvalues(r)
## S4 method for signature ListHyperGResult
sigCategories(r, p)

## S4 method for signature ListHyperGResult
geneCounts(r)
## S4 method for signature ListHyperGResult
expectedCounts(r)
## S4 method for signature ListHyperGResult
oddsRatios(r)
## S4 method for signature ListHyperGResult
universeCounts(r)
## S4 method for signature ListHyperGResult
geneMappedCount(r)
## S4 method for signature ListHyperGResult
universeMappedCount(r)
## S4 method for signature ListHyperGResult
geneIdsByCategory(r, catids = NULL)

## S4 method for signature ListHyperGResult
geneIdUniverse(r, cond = FALSE)

```

### Arguments

object,r	A ListHyperGResult object.
pvalue,p	Numeric vector of length one, the $p$ -value limit, up to which the terms are listed.
categorySize	A numeric vector of length one, or NULL. If not NULL, then it gives the minimum number of annotated genes in the universe, in order to list the term.
file	A file name, or a connection object. The result is written here. If it is "", then the result is written to the standard output. If it is NULL, then the result is not written anywhere. (But it is always returned, invisibly, see below.)
append	Logical scalar, whether to append the HTML code to the given file, or remove its previous contents if it already exists.
label	An HTML label (<A LABEL=""> tag) to add.
digits	The number of digits to use for the numeric columns.
summary.args	A list of arguments to pass to the summary method.
catids	The categories for which the genes are listed. All categories will be listed if this argument is NULL.
cond	Currently not used.

### Details

A ListHyperGResult object can store the results of hypergeometric tests, several gene sets against the same universe. ListHyperGRresult is an extension of HyperGResult, as defined in the Category

package.

More precisely, ListHyperGResult is an abstract class, it is not possible to instantiate objects from it. Its extensions are be used instead: GOListHyperGResult, KEGGListHyperGResult, CHRListHyperGResult and miRNAListHyperGResult.

## Value

pvalues, geneCounts, expectedCounts, oddsRatios and universeCounts return a list of named numeric vectors.

geneMappedCount returns a numeric vector, universeMappedCount returns a numeric vector of length one.

sigCategories returns a list of character vectors.

geneIdsByCategory returns a list of lists of character vectors.

geneIdUniverse returns a list of character vectors.

summary returns a list of data frames with columns: 'Pvalue', 'OddsRatio', 'ExpCount', 'Count', 'Size' and optionally 'drive'.

htmlReport returns a list of chracter vectors, invisibly.

conditional returns a logical vector of length one. ontology returns a character vector of length one.

## Member functions

Most of the member functions are analogous to the ones defined for HyperGResult in the Category package. Usually the only difference is that they return a list of vectors, with one entry for each gene set, instead of just a single vector.

pvalues returns the  $p$ -values of the hypergeomatic tests. A list is returned, with one numeric vector entry for each input gene set. The  $p$ -values for each gene set are ordered according to decreasing significance.

geneCounts returns the number of genes from the gene set that are annotated with the given term. This is returned for all input gene sets, in a list.

expectedCounts returns the number of genes that are expected to be annotated with the given term, just by chance. This is calculated for all input gene sets, and returned as a list.

oddsRatios returns the odds ratios for each term tested, for all gene sets, in a list of numeric vectors.

universeCounts returns the number of genes from the universe that are annotated with the given term, for all gene sets, in a list.

geneMappedCount gives the size of the gene sets, as used in the algorithm. This can be different than the size of the input gene sets, because of the elimination of duplicates and genes that are not in the universe, before the actual computation.

universeMappedCount gives the size of the gene universe, as used in the computation. This can be different than the size given by the user, because duplicates are eliminated before the computation.

sigCategories returns the significant terms, at the given  $p$ -value threshold, for all gene sets, as a list.

geneIdsByCategory returns a list of lists, one entry for each input gene set. Every entry is a list itself and for each tested term it gives the gene ids from the gene set that are annotated with the given term.

geneIdUniverse returns a list of character vectors, one for each term that was tested, giving the ids of the genes from the universe that are annotated with that term.

summary returns a list of data frames, one for each input gene set. Each data frame has columns: 'Pvalue', 'OddsRatio', 'ExpCount', 'Count', 'Size' and optionally 'drive'. Each row of the data frame corresponds to a tested term.

htmlReport creates a HTML summary from a ListHyperGParams object. This consists of one table for each input gene set. The summary can be written to a file, but it is also returned in a list of character vectors. There is one list entry for each input gene set, and each element of the character vector corresponds to one line of HTML code. You need the xtable package to use this function.

The following functions are defined for GOListHyperGResult objects only.

conditional returns a logical vector of length one, whether the test was conditional or not. Conditional testing is currently not implemented, please see the GOstats package for a working implementation.

ontology returns a character vector of length one, the name of the ontology for the GO test.

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### See Also

Functions for enrichment calculation of ISA modules: [ISAGO](#), [ISAKEGG](#), [ISACHR](#), [ISAmiRNA](#), [ISAEEnrichment](#).

Perhaps see also the vignette in the GOstats package.

### Examples

```
data(ALLModulesSmall)
GO <- ISAGO(ALLModulesSmall)
GO$CC
sigCategories(GO$CC)[[1]]
summary(GO$CC)[[1]][,1:5]
```

---

mnplot

*Plot group means against each other, for an ISA module*

---

### Description

Plot mean expression values for two sets of samples, against each other.

### Usage

```
mnplot(x, expset, group, ...)
ISAmnplot(modules, number, eset, norm = c("raw", "feature", "sample"),
           group, ...)
```

**Arguments**

x	A character vector, the feature names for which the plot is created.
expset	An ExpressionSet object (Biobase package), or an expression matrix, with row names as feature names.
eset	An ExpressionSet or ISAExpressionSet object. If an ExpressionSet object is supplied (and the norm argument is not set to 'raw'), then it is normalised by calling <a href="#">ISANormalize</a> on it. A subset of eset is selected that corresponds to the features included in modules.
norm	Character constant, specifies whether and how to normalize the expression values to plot. 'raw' plots the raw expression values, 'feature' the expression values scaled and centered for each feature (=gene) separately and if 'sample' is specified then the expression values are centered and scaled separately for each sample.
group	A factor that defines two groups to plot one against the other.
modules	An <a href="#">ISAModules</a> object.
number	A numeric scalar, the number of the module for which the plot is created.
...	Additional arguments, they are passed to the <a href="#">plot</a> function.

**Details**

mnplot plots two group-means against each other, the mean expression of all the specified probes. The two groups are specified as a factor with two levels.

ISAmnplot calls mnplot and plots the mean expression of genes in an ISA module, again, for two groups.

**Value**

Both functions return invisibly a matrix with two lines, the mean expression values for the two groups, for all the specified genes.

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

**References**

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

**See Also**

The [G0mnplot](#) and [KEGGmnplot](#) functions in the [annotate](#) package.

**Examples**

```

data(ALLModulesSmall)
library(ALL)
data(ALL)
group <- ifelse(grepl("^B", ALL$BT), "B-cell", "T-cell")
ISAmnplot(ALLModulesSmall, 2, ALL, norm="feature", group=group)

```

---

 overlap

*Overlap of ISA biclusters*


---

**Description**

Plots a network, where each node is a module and modules that overlap are closer to each other.

**Usage**

```

overlap (modules, algorithm = c("mds", "fr", "drl"), edge.limit = 0.5)
overlapPlot (graph, xsize = 400, ysize = 400, vertex.size = 20,
             vertex.size2 = 10, ...)

```

**Arguments**

modules	An <a href="#">ISAModules</a> object.
algorithm	The algorithm to use for placing the vertices, a character scalar. See details below.
edge.limit	Numeric constant between zero and one, only edges between modules that have a Pearson correlation higher than <code>edge.limit</code> will be drawn.
graph	An <code>igraph</code> object, as returned by <code>overlap</code> .
xsize	The width of the plot in pixels, only used to calculate the return value, it does not influence the plot itself.
ysize	The height of the plot in pixels, only used to calculate the return value, it does not influence the plot itself.
vertex.size	The width of the vertices on the plot.
vertex.size2	The height of the vertices on the plot.
...	Additional arguments, these are passed to the <code>plot.igraph</code> function from the <code>igraph</code> package.

**Details**

An [ISAModules](#) object may potentially contain many modules that overlap. These functions visualize the overlapping relationships of a set of modules.

`overlap` creates an `igraph` graph with additional information on how to plot this graph in a way that nodes representing overlapping modules are close to each other.

`overlapPlot` takes such a graph and plots it.

overlap can use various algorithms, depending on the `algorithm` argument. If it is 'mds', then multi-dimensional scaling is used, by calling the `isaMDS` function in the MASS package. If it is 'fr', then the Fruchterman-Reingold algorithm is used, through the `layout.fruchterman.reingold` function of the igraph package. If it is 'dr1', then the DrL graph layout algorithm is used, see the `layout.dr1` function in the igraph0 package.

### Value

`overlap` returns an igraph graph.

`overlapPlot` returns the coordinates of the vertices in a two-column matrix, invisibly.

### Author(s)

Gabor Csardi <csardi.gabor@gmail.com>

### References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

### Examples

```
data(ALLModulesSmall)
G <- overlap(ALLModulesSmall, algorithm="dr1", edge.limit=0.3)
if (interactive()) {
  overlapPlot(G)
}
```

---

profilePlot

*Profile plots for ISA biclusters*

---

### Description

Line plots to compare biclusters to the background, i.e. the rest of the expression matrix.

### Usage

```
profilePlot (modules, module, eset, plot = c("samples", "features",
  "both"), norm = "default", background = TRUE,
  col = gray(0.7), col.mod = 1, type = "l", type.mod = type,
  mean = TRUE, meancol = "green", meancol.mod = "red",
  xlabs = c("Features", "Samples"), ylab = "Expression",
  ...)
```

**Arguments**

modules	An ISAModules object.
module	Numeric scalar, the module to plot.
eset	An ExpressionSet or ISAEExpressionSet object. If an ExpressionSet object is supplied (and the norm argument is not set to 'raw'), then it is normalised by calling <a href="#">ISANormalize</a> on it. A subset of eset is selected that corresponds to the features included in modules.
plot	Character constant, specifies what to plot. 'sample' plots sample scores, 'features' plots feature scores. If 'both' is given, then the plot is divided into two subplots and both scores are plotted.
norm	Character constant, specifies how to normalize the expression matrix for plotting. It can be of length one or two, the latter for the case when plots are made both for features and samples. Possible values: 'raw' uses the raw expression values; 'feature' uses <a href="#">featExprs</a> to extract the expression values from the expression set object; 'sample' uses <a href="#">sampExprs</a> ; 'default' means 'feature' for sample plots and 'sample' for feature plots.
background	Logical scalar, whether to plot the features/samples that are not in the module.
col	Color of lines corresponding to the background features/samples.
col.mod	Color of the lines corresponding to the features/samples included in the module.
type	Type of the plot, for the background features/samples. It is passed to <a href="#">plot</a> .
type.mod	Type of the plot, for the features/samples included in the module. It is passed to <a href="#">plot</a> .
mean	Logical scalar, whether to plot the mean expression for each feature/sample, separately for the samples/features that are in the module and the ones that are not.
meancol	Color of the line for the mean expression values, background.
meancol.mod	Color of the line for the mean expression values, module.
xlabs	Character vector of length one or two. The labels of the horizontal axes of the plot, the second value is used if both the feature and the sample plots are drawn.
ylab	Character vector of length one. The label of the vertical axes.
...	Additional graphical arguments. They are passed to the <a href="#">lines</a> function that creates the lines of the plot.

**Details**

plot="both" uses the mfrow graphical parameter to create the two subplots. This does not work properly if you already have subplots.

**Value**

None. (Well, NULL, invisibly.)

**Author(s)**

Gabor Csardi <csardi.gabor@gmail.com>

## References

Bergmann S, Ihmels J, Barkai N: Iterative signature algorithm for the analysis of large-scale gene expression data *Phys Rev E Stat Nonlin Soft Matter Phys.* 2003 Mar;67(3 Pt 1):031902. Epub 2003 Mar 11.

## See Also

The similar [parallelCoordinates](#) function in the biclust package.

## Examples

```
data(ALLModulesSmall)
library(ALL)
data(ALL)
if (interactive()) {
  profilePlot(ALLModulesSmall, 2, ALL, plot="samples")
}
```

# Index

- \*Topic **classes**
  - ISAEExpressionSet-class, 16
- \*Topic **cluster**
  - condPlot, 3
  - enrichment, 5
  - expPlot, 6
  - gograph, 8
  - ISA, 10
  - ISA-Biclust conversion, 12
  - ISA2heatmap, 13
  - ISACHR, 15
  - ISAFilterRobust, 18
  - ISAGO, 19
  - ISAHTML, 21
  - ISAIterate, 23
  - ISAKEGG, 25
  - ISAmiRNA, 26
  - ISAModules-class, 28
  - ISANormalize, 33
  - ISASweep, 34
  - ISAUnique, 36
  - ListHyperGParams-class, 38
  - ListHyperGResult-class, 41
  - mnplot, 44
  - overlap, 46
  - profilePlot, 47
- \*Topic **datasets**
  - ALLModules, 2
  - [, ISAModules, ANY, ANY, ANY-method  
(ISAModules-class), 28
  - [, ISAModules, ANY, ANY-method  
(ISAModules-class), 28
  - [, ISAModules, ANY-method  
(ISAModules-class), 28
  - [[, ISAModules, ANY, ANY-method  
(ISAModules-class), 28
  - [[, ISAModules, ANY-method  
(ISAModules-class), 28
- ALLModules, 2
- ALLModulesSmall (ALLModules), 2
- annotate (ISA-Biclust conversion), 12
- annotation, ISAModules-method  
(ISAModules-class), 28
- anrichment (enrichment), 5
  
- barplot, 3, 4
- Biclust, 12
  
- CHRListHyperGParams  
(ListHyperGParams-class), 38
- CHRListHyperGParams-class  
(ListHyperGParams-class), 38
- CHRListHyperGResult, 15, 21
- CHRListHyperGResult  
(ListHyperGResult-class), 41
- CHRListHyperGResult-class  
(ListHyperGResult-class), 41
- class: ISAModules (ISAModules-class), 28
- coerce, Biclust, ISAModules-method  
(ISA-Biclust conversion), 12
- coerce, ISAModules, Biclust-method  
(ISA-Biclust conversion), 12
- condGeneIdUniverse, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- condGeneIdUniverse, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- condGeneIdUniverse, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- condGeneIdUniverse, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- condGeneIdUniverse, ListHyperGResult-method  
(ListHyperGResult-class), 41
- condGeneIdUniverse, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
- conditional, GOListHyperGParams-method  
(ListHyperGParams-class), 38
- conditional, GOListHyperGResult-method  
(ListHyperGResult-class), 41

- conditional<- ,GOListHyperGParams,logical-method (ListHyperGParams-class), 38
- condPlot, 3, 22
- dim, ISAModules-method (ISAModules-class), 28
- drive (ListHyperGParams-class), 38
- drive,CHRListHyperGParams-method (ListHyperGParams-class), 38
- drive,GeneralListHyperGParams-method (ListHyperGParams-class), 38
- drive,GOListHyperGParams-method (ListHyperGParams-class), 38
- drive,KEGGListHyperGParams-method (ListHyperGParams-class), 38
- drive,ListHyperGParams-method (ListHyperGParams-class), 38
- drive,miRNAListHyperGParams-method (ListHyperGParams-class), 38
- drive<- (ListHyperGParams-class), 38
- drive<- ,CHRListHyperGParams,logical-method (ListHyperGParams-class), 38
- drive<- ,GeneralListHyperGParams,logical-method (ListHyperGParams-class), 38
- drive<- ,GOListHyperGParams,logical-method (ListHyperGParams-class), 38
- drive<- ,KEGGListHyperGParams,logical-method (ListHyperGParams-class), 38
- drive<- ,ListHyperGParams,logical-method (ListHyperGParams-class), 38
- drive<- ,miRNAListHyperGParams,logical-method (ListHyperGParams-class), 38
- enrichment, 5
- expectedCounts,CHRListHyperGResult-method (ListHyperGResult-class), 41
- expectedCounts,GeneralListHyperGResult-method (ListHyperGResult-class), 41
- expectedCounts,GOListHyperGResult-method (ListHyperGResult-class), 41
- expectedCounts,KEGGListHyperGResult-method (ListHyperGResult-class), 41
- expectedCounts,ListHyperGResult-method (ListHyperGResult-class), 41
- expectedCounts,miRNAListHyperGResult-method (ListHyperGResult-class), 41
- expPlot, 6, 22
- expPlotColbar (expPlot), 6
- expPlotCreate (expPlot), 6
- featExprs, 48
- featExprs (ISAExpressionSet-class), 16
- featExprs,ISAExpressionSet-method (ISAExpressionSet-class), 16
- featureNames,ISAModules-method (ISAModules-class), 28
- featureThreshold (ISAModules-class), 28
- featureThreshold,ISAModules-method (ISAModules-class), 28
- geneCounts,CHRListHyperGResult-method (ListHyperGResult-class), 41
- geneCounts,GeneralListHyperGResult-method (ListHyperGResult-class), 41
- geneCounts,GOListHyperGResult-method (ListHyperGResult-class), 41
- geneCounts,KEGGListHyperGResult-method (ListHyperGResult-class), 41
- geneCounts,ListHyperGResult-method (ListHyperGResult-class), 41
- geneCounts,miRNAListHyperGResult-method (ListHyperGResult-class), 41
- genefilter, 10
- geneIdsByCategory,CHRListHyperGResult-method (ListHyperGResult-class), 41
- geneIdsByCategory,GeneralListHyperGResult-method (ListHyperGResult-class), 41
- geneIdsByCategory,GOListHyperGResult-method (ListHyperGResult-class), 41
- geneIdsByCategory,KEGGListHyperGResult-method (ListHyperGResult-class), 41
- geneIdsByCategory,ListHyperGResult-method (ListHyperGResult-class), 41
- geneIdsByCategory,miRNAListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,CHRListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,GeneralListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,GOListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,KEGGListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,ListHyperGResult-method (ListHyperGResult-class), 41
- geneIdUniverse,miRNAListHyperGResult-method (ListHyperGResult-class), 41
- geneMappedCount,CHRListHyperGResult-method (ListHyperGResult-class), 41

- geneMappedCount, GeneralListHyperGResult-method  
 (ListHyperGResult-class), 41
- geneMappedCount, GOListHyperGResult-method  
 (ListHyperGResult-class), 41
- geneMappedCount, KEGGListHyperGResult-method  
 (ListHyperGResult-class), 41
- geneMappedCount, ListHyperGResult-method  
 (ListHyperGResult-class), 41
- geneMappedCount, miRNAListHyperGResult-method  
 (ListHyperGResult-class), 41
- GeneralListHyperGParams  
 (ListHyperGParams-class), 38
- GeneralListHyperGParams-class  
 (ListHyperGParams-class), 38
- GeneralListHyperGResult, 6
- GeneralListHyperGResult  
 (ListHyperGResult-class), 41
- GeneralListHyperGResult-class  
 (ListHyperGResult-class), 41
- generate.seeds, 11
- getFeatureMatrix (ISAModules-class), 28
- getFeatureMatrix, ISAModules-method  
 (ISAModules-class), 28
- getFeatureNames (ISAModules-class), 28
- getFeatureNames, ISAModules-method  
 (ISAModules-class), 28
- getFeatures (ISAModules-class), 28
- getFeatures, ISAModules-method  
 (ISAModules-class), 28
- getFeatureScores (ISAModules-class), 28
- getFeatureScores, ISAModules-method  
 (ISAModules-class), 28
- getFullFeatureMatrix  
 (ISAModules-class), 28
- getFullFeatureMatrix, ISAModules-method  
 (ISAModules-class), 28
- getFullSampleMatrix (ISAModules-class),  
 28
- getFullSampleMatrix, ISAModules-method  
 (ISAModules-class), 28
- getNoFeatures (ISAModules-class), 28
- getNoFeatures, ISAModules-method  
 (ISAModules-class), 28
- getNoSamples (ISAModules-class), 28
- getNoSamples, ISAModules-method  
 (ISAModules-class), 28
- getOrganism (ISAModules-class), 28
- getOrganism, ISAModules-method  
 (ISAModules-class), 28
- getSampleMatrix (ISAModules-class), 28
- getSampleMatrix, ISAModules-method  
 (ISAModules-class), 28
- getSampleNames (ISAModules-class), 28
- getSampleNames, ISAModules-method  
 (ISAModules-class), 28
- getSamples (ISAModules-class), 28
- getSamples, ISAModules-method  
 (ISAModules-class), 28
- getSampleScores (ISAModules-class), 28
- getSampleScores, ISAModules-method  
 (ISAModules-class), 28
- gograph, 8, 22
- gographPlot (gograph), 8
- GOListHyperGParams  
 (ListHyperGParams-class), 38
- GOListHyperGParams-class  
 (ListHyperGParams-class), 38
- GOListHyperGResult, 20, 21
- GOListHyperGResult  
 (ListHyperGResult-class), 41
- GOListHyperGResult-class  
 (ListHyperGResult-class), 41
- GOmplot, 45
- hasNA (ISAEExpressionSet-class), 16
- hasNA, ISAEExpressionSet-method  
 (ISAEExpressionSet-class), 16
- hasNA<- (ISAEExpressionSet-class), 16
- hasNA<-, ISAEExpressionSet-method  
 (ISAEExpressionSet-class), 16
- heatmap, 14
- htmlReport, CHRListHyperGResult-method  
 (ListHyperGResult-class), 41
- htmlReport, GeneralListHyperGResult-method  
 (ListHyperGResult-class), 41
- htmlReport, GOListHyperGResult-method  
 (ListHyperGResult-class), 41
- htmlReport, KEGGListHyperGResult-method  
 (ListHyperGResult-class), 41
- htmlReport, ListHyperGResult-method  
 (ListHyperGResult-class), 41
- htmlReport, miRNAListHyperGResult-method  
 (ListHyperGResult-class), 41
- hyperGTest, CHRListHyperGParams-method  
 (ListHyperGParams-class), 38
- hyperGTest, GeneralListHyperGParams-method  
 (ListHyperGParams-class), 38

- hyperGTest, GOListHyperGParams-method  
(ListHyperGParams-class), 38
- hyperGTest, KEGGListHyperGParams-method  
(ListHyperGParams-class), 38
- hyperGTest, ListHyperGParams-method  
(ListHyperGParams-class), 38
- hyperGTest, miRNAListHyperGParams-method  
(ListHyperGParams-class), 38
  
- IQR, 10
- ISA, 4, 10, 24, 34, 38
- isa, 11
- ISA-Biclust conversion, 12
- isa.iterate, 11, 24, 37
- isa.normalize, 11
- isa.unique, 11, 37
- ISA2heatmap, 13
- ISACHR, 6, 15, 20, 21, 26, 28, 40, 44
- ISAEnrichment, 44
- ISAEnrichment (enrichment), 5
- ISAEExpressionSet, 33
- ISAEExpressionSet  
(ISAEExpressionSet-class), 16
- ISAEExpressionSet-class, 16
- ISAFilterRobust, 18, 31
- ISAGO, 6, 16, 19, 21, 26, 28, 40, 44
- ISAHTML, 21
- ISAHTMLModules (ISAHTML), 21
- ISAHTMLTable (ISAHTML), 21
- ISAIterate, 23, 31, 37
- ISAKEGG, 6, 16, 20, 21, 25, 28, 40, 44
- ISAmiRNA, 6, 16, 20, 21, 26, 26, 40, 44
- ISAmnplot (mnplot), 44
- ISAModules, 4, 7, 12, 14, 24, 45, 46
- ISAModules (ISAModules-class), 28
- ISAModules-class, 28
- ISANormalize, 3, 7, 14, 17, 18, 22, 23, 29, 31,  
33, 37, 45, 48
- ISARobustness, 31
- ISARobustness (ISAFilterRobust), 18
- ISASweep, 34
- ISASweepGraph (ISASweep), 34
- ISASweepGraphPlot (ISASweep), 34
- ISAUnique, 31, 36
  
- KEGGListHyperGParams  
(ListHyperGParams-class), 38
- KEGGListHyperGParams-class  
(ListHyperGParams-class), 38
  
- KEGGListHyperGResult, 21, 26
- KEGGListHyperGResult  
(ListHyperGResult-class), 41
- KEGGListHyperGResult-class  
(ListHyperGResult-class), 41
  
- length, ISAModules-method  
(ISAModules-class), 28
- lines, 48
- ListHyperGParams  
(ListHyperGParams-class), 38
- ListHyperGParams-class, 38
- ListHyperGResult  
(ListHyperGResult-class), 41
- ListHyperGResult-class, 41
  
- makeValidParams, CHRListHyperGParams-method  
(ListHyperGParams-class), 38
- makeValidParams, GeneralListHyperGParams-method  
(ListHyperGParams-class), 38
- makeValidParams, GOListHyperGParams-method  
(ListHyperGParams-class), 38
- makeValidParams, KEGGListHyperGParams-method  
(ListHyperGParams-class), 38
- makeValidParams, ListHyperGParams-method  
(ListHyperGParams-class), 38
- makeValidParams, miRNAListHyperGParams-method  
(ListHyperGParams-class), 38
- miRNAListHyperGParams  
(ListHyperGParams-class), 38
- miRNAListHyperGParams-class  
(ListHyperGParams-class), 38
- miRNAListHyperGResult, 21, 27
- miRNAListHyperGResult  
(ListHyperGResult-class), 41
- miRNAListHyperGResult-class  
(ListHyperGResult-class), 41
- mnplot, 44
  
- oddsRatios, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- oddsRatios, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- oddsRatios, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- oddsRatios, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- oddsRatios, ListHyperGResult-method  
(ListHyperGResult-class), 41

- oddsRatios, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
- ontology, GOListHyperGParams-method  
(ListHyperGParams-class), 38
- ontology, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- ontology<-, GOListHyperGParams, character-method  
(ListHyperGParams-class), 38
- overlap, 46
- overlapPlot (overlap), 46
  
- p.adjust, 5, 15, 19, 25, 27
- parallelCoordinates, 49
- pData, ISAModules-method  
(ISAModules-class), 28
- plot, 45, 48
- prenormalized (ISAEExpressionSet-class),  
16
- prenormalized, ISAEExpressionSet-method  
(ISAEExpressionSet-class), 16
- prenormalized<-  
(ISAEExpressionSet-class), 16
- prenormalized<-, ISAEExpressionSet-method  
(ISAEExpressionSet-class), 16
- print.ISAexpPlot (expPlot), 6
- profilePlot, 47
- pvalues, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- pvalues, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- pvalues, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- pvalues, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- pvalues, ListHyperGResult-method  
(ListHyperGResult-class), 41
- pvalues, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
  
- robustness, 18, 19
- runData (ISAModules-class), 28
- runData, ISAModules-method  
(ISAModules-class), 28
  
- sampExprs, 48
- sampExprs (ISAEExpressionSet-class), 16
- sampExprs, ISAEExpressionSet-method  
(ISAEExpressionSet-class), 16
  
- sampleNames, ISAModules-method  
(ISAModules-class), 28
- sampleThreshold (ISAModules-class), 28
- sampleThreshold, ISAModules-method  
(ISAModules-class), 28
- seedData (ISAModules-class), 28
- seedData, ISAModules-method  
(ISAModules-class), 28
- sigCategories, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- sigCategories, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- sigCategories, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- sigCategories, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- sigCategories, ListHyperGResult-method  
(ListHyperGResult-class), 41
- sigCategories, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, ListHyperGResult-method  
(ListHyperGResult-class), 41
- summary, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
  
- text, 4
  
- universeCounts, CHRListHyperGResult-method  
(ListHyperGResult-class), 41
- universeCounts, GeneralListHyperGResult-method  
(ListHyperGResult-class), 41
- universeCounts, GOListHyperGResult-method  
(ListHyperGResult-class), 41
- universeCounts, KEGGListHyperGResult-method  
(ListHyperGResult-class), 41
- universeCounts, ListHyperGResult-method  
(ListHyperGResult-class), 41
- universeCounts, miRNAListHyperGResult-method  
(ListHyperGResult-class), 41
- universeMappedCount, CHRListHyperGResult-method  
(ListHyperGResult-class), 41

universeMappedCount, GeneralListHyperGResult-method  
(ListHyperGResult-class), [41](#)

universeMappedCount, GOListHyperGResult-method  
(ListHyperGResult-class), [41](#)

universeMappedCount, KEGGListHyperGResult-method  
(ListHyperGResult-class), [41](#)

universeMappedCount, ListHyperGResult-method  
(ListHyperGResult-class), [41](#)

universeMappedCount, miRNAListHyperGResult-method  
(ListHyperGResult-class), [41](#)