

Package ‘ggtut’

April 8, 2015

Title support for tutorial on genetics of gene expression ISMB 2011

Version 0.3.2

Author VJ Carey <stvjc@channing.harvard.edu>

Description various resources for genetics of expression with R/bioc

Suggests rtracklayer, GenomicFeatures, ChIPpeakAnno,
TxDb.Hsapiens.UCSC.hg18.knownGene

Depends R (>= 2.14.0), GGtools (>= 3.11.32), ff, GenomicRanges,
snpStats, GGdata, GenomicFeatures, ChIPpeakAnno, Rsamtools(>= 1.5.35), cheung2010, SNPLocs.Hsapiens.dbSNP.20120608, hmyriB36

Maintainer VJ Carey <stvjc@channing.harvard.edu>

License Artistic-2.0

LazyLoad yes

R topics documented:

ggtut-package	1
c17imp	2
g17rngsnr	3
observed17ceu	4
rules.n43	5
snpgr17	6

Index

8

ggtut-package *support for tutorial on genetics of gene expression ISMB 2011*

Description

various resources for genetics of expression with R/bioc

Details

Package:

Version:

Suggests:

Depends:

License:

LazyLoad:

Built:

CPS17 is a cisProxScores instance, as is PERMCPS17, serialized to reduce vignette computation time. SVA1 is an sva() output

Index:

observed17ceu	obtain access to ff-based archives of eQTL test results
hg18tx	a function that returns a reference to a transcriptDb instance for hg18
getFixedBFL	retrieve a BamFileList of 41 small RNA seq extracts with nicely formatted HapMap names

Further information is available in the following vignettes:

[tut11](#) (source, pdf)

Author(s)

VJ Carey <stvjc@channing.harvard.edu>

Maintainer: VJ Carey <stvjc@channing.harvard.edu>

Examples

```
library(ggtut)
o17 = observed17ceu()
o17
ch41 = getFixedBFL()
ch41
```

c17imp

SnpMatrix instance with imputations from 1KG to CEU chr 17

Description

SnpMatrix instance with imputations from 1KG to CEU chr 17

Usage

`data(c17imp)`

Format

The format is:

```
Formal class 'SnpMatrix' [package "snpStats"] with 1 slots
..@ .Data: raw [1:90, 1:175170] 77 d6 77 2d ...
... -- attr(*, "dimnames")=List of 2
... ... $ : chr [1:90] "NA06985" "NA06991" "NA06993" "NA06994" ...
... ... $ : chr [1:175170] "chr17:1869" "rs17055023" "rs6565733" "rs34663111" ...
```

Source

uses rules.n43

Examples

```
library(snpStats)
data(c17imp)
c17imp
```

g17rngsnr

ranges of genes on chrom 17 (uses hg18)

Description

ranges of genes on chrom 17 (uses hg18)

Usage

```
data(g17rngsnr)
```

Format

The format is:

```
Formal class 'GRanges' [package "GenomicRanges"] with 6 slots
..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots
... ...@ values : Factor w/ 1 level "chr17": 1
... ...@ lengths : int 475
... ...@ elementMetadata: NULL
... ...@ metadata : list()
..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
... ...@ start : int [1:475] 39509647 50333051 46294586 77439016 38229969 37098653 45133689
58981554 44263371 17349602 ...
... ...@ width : int [1:475] 46894 61277 5753 3743 19335 2772 6839 43820 33858 86118 ...
... ...@ NAMES : chr [1:475] "GI_21237796-A" "GI_4885638-S" "GI_22035666-S" "GI_17572809-
S" ...
... ...@ elementType : chr "integer"
... ...@ elementMetadata: NULL
```

```

... .. @ metadata : list()
.. @ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
... .. @ values : Factor w/ 3 levels "+","-","*": 3
... .. @ lengths : int 475
... .. @ elementMetadata: NULL
... .. @ metadata : list()
.. @ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
... .. @ rownames : NULL
... .. @ nrows : int 475
... .. @ listData :List of 1
... .. $ probeid: chr [1:475] "GI_21237796-A" "GI_4885638-S" "GI_22035666-S" "GI_17572809-
S" ...
... .. @ elementType : chr "ANY"
... .. @ elementMetadata: NULL
... .. @ metadata : list()
.. @ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
... .. @ seqnames : chr "chr17"
... .. @ seqlengths : int NA
... .. @ is_circular: logi NA
.. @ metadata : list()

```

Examples

```

data(g17rngsnr)
g17rngsnr
## maybe str(g17rngsnr) ; plot(g17rngsnr) ...

```

observed17ceu

obtain access to ff-based archives of eQTL test results

Description

obtain access to ff-based archives of eQTL test results

Usage

```

observed17ceu()
onePerm17ceu()

```

Details

The underlying ff data were obtained as follows

```

dropMonomorphies = function(sms) { sl = smList(sms) summs = lapply(sl, col.summary)
todrop = lapply(summs, function(x) which(x[,"RAF"]==1 | x[,"RAF"]==0)) for (i in 1:length(todrop))
if (length(todrop[[i]])>0) sl[[i]][,-todrop[[i]]] sms@smList = sl
sms } library(GGdata) library(multicore) data(eset) ex library(genefilter) exf1 = nsFilter(ex)

```

```

length(get("17", revmap(illuminaHumanv1CHR))->ZZ) kp = intersect(ZZ, featureNames(exf1[[1]]))
c17 = getSS("GGdata", "17", renameChrs="chr17", probesToKeep=kp, wrapperEndo=dropMonomorphies)
f1dm = eqtlTests(c17, ~male, targdir="c17c", genegran=1, geneApply=mclapply)
save(f1dm, file="f1dm.rda") set.seed(1234); permf1dm = eqtlTests(permEx(c17), ~male, targdir="c17c_per")
save(permf1dm, file="permf1dm.rda")

```

Value

an instance of [eqtlTestsManager-class](#)

Examples

```

f1 = observed17ceu()
f1
f1@call
f1[ rsid("rs7502145"), probeId("GI_10190685-S")]
pf1 = onePerm17ceu()
pf1[ rsid("rs7502145"), probeId("GI_10190685-S")]

```

rules.n43

*snpStats imputation rules instance***Description**

snpStats imputation rules instance

Usage

```
data(rules.n43)
```

Format

The format is:

```

Formal class 'ImputationRules' [package "snpStats"] with 1 slots
..@ .Data:List of 470806
... ...$ : NULL
... ...$ :List of 4
... ...$ maf : num 0.128
... ...$ r.squared: num 0.901
... ...$ snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs7225087"
... ...$ hap.probs: num [1:32] 0.00 1.02e-21 0.00 1.45e-07 1.52e-07 ...
... ...$ :List of 4
... ...$ maf : num 0.163
... ...$ r.squared: num 0.802
... ...$ snps : chr [1:4] "rs11654695" "rs12449775" "rs8078223" "rs9907102"
... ...$ hap.probs: num [1:32] 0.02863 0.0253 0.00342 0.07866 0.01717 ...
... ...$ :List of 4
... ...$ maf : num 0.116

```

```

... .$.r.squared: num 0.881
... .$.snps : chr [1:4] "rs11654695" "rs9789059" "rs8073513" "rs4968164"
... .$.hap.probs: num [1:32] 0.00 1.96e-13 0.00 4.91e-05 1.05e-06 ...
... .$.NULL.
... [list output truncated]

```

Examples

```

library(snpStats)
data(rules.n43)
rules.n43[1:4]
## maybe str(rules.n43) ; plot(rules.n43) ...

```

snpgr17

SNP locations for chr 17: hg18 coordinates

Description

SNP locations for chr 17: hg18 coordinates

Usage

```
data(snpgr17)
```

Format

The format is:

```

Formal class 'GRanges' [package "GenomicRanges"] with 6 slots
..@ seqnames :Formal class 'Rle' [package "IRanges"] with 4 slots
... .@ values : Factor w/ 1 level "chr17": 1
... .@ lengths : int 316396
... .@ elementMetadata: NULL
... .@ metadata : list()
..@ ranges :Formal class 'IRanges' [package "IRanges"] with 6 slots
... .@ start : int [1:316396] 6934 7214 7242 8611 11743 11830 13546 13905 14122 14300 ...
... .@ width : int [1:316396] 1 1 1 1 1 1 1 1 1 ...
... .@ NAMES : chr [1:316396] "rs1106176" "rs6420494" "rs6420495" "rs62054996" ...
... .@ elementType : chr "integer"
... .@ elementMetadata: NULL
... .@ metadata : list()
..@ strand :Formal class 'Rle' [package "IRanges"] with 4 slots
... .@ values : Factor w/ 3 levels "+","-","*": 3
... .@ lengths : int 316396
... .@ elementMetadata: NULL
... .@ metadata : list()
..@ elementMetadata:Formal class 'DataFrame' [package "IRanges"] with 6 slots
... .@ rownames : NULL

```

```
... ..@ nrows : int 316396
... ..@ listData : Named list()
... ..@ elementType : chr "ANY"
... ..@ elementMetadata: NULL
... ..@ metadata : list()
..@ seqinfo :Formal class 'Seqinfo' [package "GenomicRanges"] with 3 slots
... ..@ seqnames : chr "chr17"
... ..@ seqlengths : int NA
... ..@ is_circular: logi NA
..@ metadata : list()
```

Examples

```
data(snpgr17)
snpgr17
## maybe str(snpgr17) ; plot(snpgr17) ...
```

Index

*Topic **datasets**

`c17imp`, [2](#)
`g17rngsnr`, [3](#)
`rules.n43`, [5](#)
`snpgr17`, [6](#)

*Topic **models**

`observed17ceu`, [4](#)

*Topic **package**

`ggtut-package`, [1](#)

`bestGenesPerSNP_obs` (`ggtut-package`), [1](#)
`bestGenesPerSNP_perm` (`ggtut-package`), [1](#)

`c17imp`, [2](#)

`CPS17` (`ggtut-package`), [1](#)

`g17rngsnr`, [3](#)

`getFixedBFL` (`ggtut-package`), [1](#)

`ggtut` (`ggtut-package`), [1](#)

`ggtut-package`, [1](#)

`hg18tx` (`ggtut-package`), [1](#)

`observed17ceu`, [4](#)

`onePerm17ceu` (`observed17ceu`), [4](#)

`PERMCPS17` (`ggtut-package`), [1](#)

`permsb1` (`ggtut-package`), [1](#)

`rsb2_list` (`ggtut-package`), [1](#)

`rsb2_perm_list` (`ggtut-package`), [1](#)

`rules.n43`, [5](#)

`sb1` (`ggtut-package`), [1](#)

`snpgr17`, [6](#)

`SVA1` (`ggtut-package`), [1](#)

`tr17_1_9` (`observed17ceu`), [4](#)

`tr17_1_9_perm` (`observed17ceu`), [4](#)