

Package ‘compcoder’

October 8, 2015

Type Package

Title RNAseq data simulation, differential expression analysis and performance comparison of differential expression methods

Version 1.4.0

Author Charlotte Soneson

Maintainer Charlotte Soneson <Charlotte.Soneson@isb-sib.ch>

Description This package provides extensive functionality for comparing results obtained by different methods for differential expression analysis of RNAseq data. It also contains functions for simulating count data and interfaces to several packages for performing the differential expression analysis.

Depends R (>= 3.0.2), sm

Imports tcltk, knitr (>= 1.2), markdown, ROCR, lattice (>= 0.16), gplots, gtools, gdata, caTools, grid, KernSmooth, MASS, ggplot2, stringr, modeest, edgeR, limma, vioplot, methods

Suggests BiocStyle, EBSeq, DESeq, DESeq2 (>= 1.1.31), baySeq (>= 1.16.0), genefilter, NOISeq, TCC, samr, NBPSeq

Enhances rpanel, DSS

License GPL (>= 2)

VignetteBuilder knitr

biocViews RNASeq, DifferentialExpression

NeedsCompilation no

R topics documented:

compcoder-package	2
baySeq.createRmd	3
checkDataObject	4
checkTableConsistency	5
check_compData	6

check_compData_results	7
compData	8
compData-class	11
convertcompDataToList	13
convertListTocompData	14
DESeq.GLM.createRmd	14
DESeq.nbinom.createRmd	16
DESeq2.createRmd	17
DSS.createRmd	19
EBSeq.createRmd	20
edgeR.exact.createRmd	21
edgeR.GLM.createRmd	22
generateCodeHTMLs	24
generateSyntheticData	25
listcreateRmd	28
logcpm.limma.createRmd	28
NBPSeq.createRmd	30
NOISeq.prenorm.createRmd	31
runComparison	33
runComparisonGUI	36
runDiffExp	37
SAMseq.createRmd	40
show,compData-method	41
sqrtpm.limma.createRmd	42
summarizeSyntheticDataSet	43
TCC.createRmd	44
ttest.createRmd	45
voom.limma.createRmd	46
voom.ttest.createRmd	48
vst.limma.createRmd	49
vst.ttest.createRmd	50

Index **52**

compcodeR-package *RNAseq data simulation, differential expression analysis and performance comparison of differential expression methods*

Description

RNAseq data simulation, differential expression analysis and performance comparison of differential expression methods

Details

This package provides extensive functionality for comparing results obtained by different methods for differential expression analysis of RNAseq data. It also contains functions for simulating count data and interfaces to several packages for performing the differential expression analysis.

Author(s)

Charlotte Soneson

baySeq.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with baySeq</i>
------------------	---

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the baySeq package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
baySeq.createRmd(data.path, result.path, codefile, norm.method, distr.choice,
  equaldisp, sample.size = 5000, estimation = "QL", pET = "BIC")
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "quantile", "total" and "edgeR".
distr.choice	The choice of underlying distribution assumption for the observed counts. Possible values are "NB", "Poisson" and "Dirichlet".
equaldisp	Logical parameter indicating whether or not equal dispersion should be assumed across all conditions.
sample.size	The size of the sample used to estimate the priors (default 5000).
estimation	The approach used to estimate the priors. Possible values are "QL" (default), "ML" and "edgeR".
pET	The method used to re-estimate the priors. Possible values are "BIC" (default), "none" and "iteratively".

Details

For more information about the methods and the interpretation of the parameters, see the baySeq package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Hardcastle TJ (2012): baySeq: Empirical Bayesian analysis of patterns of differential expression in count data. R package

Hardcastle TJ and Kelly KA (2010): baySeq: Empirical Bayesian methods for identifying differential expression in sequence count data. BMC Bioinformatics 11:422

Examples

```
try(
  if (require(baySeq)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    ## Note! In the interest of speed, we set sample.size=10 in this example.
    ## In a real analysis, much larger sample sizes are recommended (the default is 5000).
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "baySeq",
              Rmdfunction = "baySeq.createRmd",
              output.directory = tmpdir, norm.method = "edgeR",
              distr.choice = "NB", equaldisp = TRUE,
              sample.size = 10)
  })
```

checkDataObject	<i>Check a list or a compData object for compatibility with the differential expression functions interfaced by compcodeR</i>
-----------------	---

Description

Check if a list or a compData object contains the necessary slots for applying the differential expression functions interfaced by the compcodeR package. This function is provided for backward compatibility, see also [check_compData](#) and [check_compData_results](#).

Usage

```
checkDataObject(data.obj)
```

Arguments

data.obj A list containing data and condition information, or a compData object.

Author(s)

Charlotte Soneson

Examples

```
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100)
checkDataObject(mydata.obj)
```

checkTableConsistency *Check consistency of input table to* [runComparison](#)

Description

Check that the dataset, nbr.samples, repl and de.methods columns of a data frame are consistent with the information provided in the input files (given in the input.files column of the data frame). If there are inconsistencies or missing information in any of the columns, replace the given information with the information in the input files.

Usage

```
checkTableConsistency(file.table)
```

Arguments

file.table A data frame with columns named input.files and (optionally) datasets, nbr.samples, repl, de.methods.

Value

Returns a consistent file table defining the result files that will be used as the basis for a method comparison.

Author(s)

Charlotte Soneson

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.limma",
           Rmdfunction = "voom.limma.createRmd", output.directory = tmpdir,
           norm.method = "TMM")
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "edgeR.exact",
           Rmdfunction = "edgeR.exact.createRmd", output.directory = tmpdir,
           norm.method = "TMM",
```

```
trend.method = "movingave", disp.type = "tagwise")

## A correct table
file.table <- data.frame(input.files = file.path(tmpdir,
  c("mydata_voom.limma.rds", "mydata_edgeR.exact.rds")),
  datasets = c("mydata", "mydata"),
  nbr.samples = c(5, 5),
  repl = c(1, 1),
  stringsAsFactors = FALSE)
new.table <- checkTableConsistency(file.table)
new.table

## An incorrect table
file.table <- data.frame(input.files = file.path(tmpdir,
  c("mydata_voom.limma.rds", "mydata_edgeR.exact.rds")),
  datasets = c("mydata", "mydata"),
  nbr.samples = c(5, 3),
  repl = c(2, 1),
  stringsAsFactors = FALSE)
new.table <- checkTableConsistency(file.table)
new.table

## A table with missing information
file.table <- data.frame(input.files = file.path(tmpdir,
  c("mydata_voom.limma.rds", "mydata_edgeR.exact.rds")),
  stringsAsFactors = FALSE)
new.table <- checkTableConsistency(file.table)
new.table
```

check_compData

Check the validity of a compData object

Description

Check the validity of a compData object. An object that passes the check can be used as the input for the differential expression analysis methods interfaced by compcodeR.

Usage

```
check_compData(object)
```

Arguments

object A compData object

Author(s)

Charlotte Soneson

Examples

```
mydata <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                               samples.per.cond = 5, n.diffexp = 100)  
check_compData(mydata)
```

check_compData_results

Check the validity of a compData result object

Description

Check the validity of a compData object containing differential expression results. An object that passes the check can be used as the input for the method comparison functions in compcodeR.

Usage

```
check_compData_results(object)
```

Arguments

object A compData object

Author(s)

Charlotte Soneson

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")  
mydata <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                               samples.per.cond = 5, n.diffexp = 100,  
                               output.file = file.path(tmpdir, "mydata.rds"))  
## Check an object without differential expression results  
check_compData_results(mydata)  
  
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"),  
           result.extent = "voom.limma",  
           Rmdfunction = "voom.limma.createRmd",  
           output.directory = tmpdir, norm.method = "TMM")  
resdata <- readRDS(file.path(tmpdir, "mydata_voom.limma.rds"))  
## Check an object containing differential expression results  
check_compData_results(resdata)
```

 compData

Create a compData object

Description

The `compData` class is used to store information about the experiment, such as the count matrix, sample and variable annotations, information regarding the generation of the data and results from applying a differential expression analysis to the data. This constructor function creates a `compData` object.

Usage

```
compData(count.matrix, sample.annotations, info.parameters,
         variable.annotations = data.frame(), filtering = "no info",
         analysis.date = "", package.version = "", method.names = list(),
         code = "", result.table = data.frame())
```

Arguments

`count.matrix` A count matrix, with genes as rows and observations as columns.

`sample.annotations`

A data frame, containing at least one column named 'condition', encoding the grouping of the observations into two groups. The row names should be the same as the column names of the `count.matrix`.

`info.parameters`

A list containing information regarding simulation parameters etc. The only mandatory entries are `dataset` and `uID`, but it may contain entries such as the ones listed below (see `generateSyntheticData` for more detailed information about each of these entries).

- `dataset`: an informative name or identifier of the data set (e.g., summarizing the simulation settings).
- `samples.per.cond`
- `n.diffexp`
- `repl.id`
- `seqdepth`
- `minfact`
- `maxfact`
- `fraction.upregulated`
- `between.group.diffdisp`
- `filter.threshold.total`
- `filter.threshold.mediacpm`
- `fraction.non.overdispersed`
- `random.outlier.high.prob`
- `random.outlier.low.prob`

- `single.outlier.high.prob`
- `single.outlier.low.prob`
- `effect.size`
- `uID`: a unique ID for the data set. In contrast to `dataset`, the `uID` is unique e.g. for each instance of replicated data sets generated with the same simulation settings.

`variable.annotations`

A data frame with variable annotations (with number of rows equal to the number of rows in `count.matrix`, that is, the number of variables in the data set). Not mandatory, but may contain columns such as the ones listed below. If present, the row names should be the same as the row names of the `count.matrix`.

- `truedispersions.S1`: the true dispersion for each gene in condition S1.
- `truedispersions.S2`: the true dispersion for each gene in condition S2.
- `truemeans.S1`: the true mean value for each gene in condition S1.
- `truemeans.S2`: the true mean value for each gene in condition S2.
- `n.random.outliers.up.S1`: the number of 'random' outliers with extremely high counts for each gene in condition S1.
- `n.random.outliers.up.S2`: the number of 'random' outliers with extremely high counts for each gene in condition S2.
- `n.random.outliers.down.S1`: the number of 'random' outliers with extremely low counts for each gene in condition S1.
- `n.random.outliers.down.S2`: the number of 'random' outliers with extremely low counts for each gene in condition S2.
- `n.single.outliers.up.S1`: the number of 'single' outliers with extremely high counts for each gene in condition S1.
- `n.single.outliers.up.S2`: the number of 'single' outliers with extremely high counts for each gene in condition S2.
- `n.single.outliers.down.S1`: the number of 'single' outliers with extremely low counts for each gene in condition S1.
- `n.single.outliers.down.S2`: the number of 'single' outliers with extremely low counts for each gene in condition S2.
- `M.value`: the M-value (observed log₂ fold change between condition S1 and condition S2) for each gene.
- `A.value`: the A-value (observed average expression level across condition S1 and condition S2) for each gene.
- `truelog2foldchanges`: the true (simulated) log₂ fold changes between condition S1 and condition S2.
- `upregulation`: a binary vector indicating which genes are simulated to be upregulated in condition S2 compared to condition S1.
- `downregulation`: a binary vector indicating which genes are simulated to be downregulated in condition S2 compared to condition S1.
- `differential.expression`: a binary vector indicating which genes are simulated to be differentially expressed in condition S2 compared to condition S1.

<code>filtering</code>	A character string containing information about the filtering that has been applied to the data set.
<code>analysis.date</code>	If a differential expression analysis has been performed, a character string detailing when it was performed.
<code>package.version</code>	If a differential expression analysis has been performed, a character string giving the version of the differential expression packages that were applied.
<code>method.names</code>	If a differential expression analysis has been performed, a list with entries <code>full.name</code> and <code>short.name</code> , giving the full name of the differential expression method (may including version number and parameter settings) and a short name or abbreviation.
<code>code</code>	If a differential expression analysis has been performed, a character string containing the code that was run to perform the analysis. The code should be in R markdown format, and can be written to an HTML file using the generateCodeHTMLs function.
<code>result.table</code>	<p>If a differential expression analysis has been performed, a data frame containing the results of the analysis. The number of rows should be equal to the number of rows in <code>count.matrix</code> and if present, the row names should be identical. The only mandatory column is <code>score</code>, which gives a score for each gene, where a higher score suggests a "more highly differentially expressed" gene. Different comparison functions use different columns of this table, if available. The list below gives the columns that are used by the interfaced methods.</p> <ul style="list-style-type: none"> • <code>pvalue</code> nominal p-values • <code>adjpvalue</code> p-values adjusted for multiple comparisons • <code>logFC</code> estimated log-fold changes between the two conditions • <code>score</code> the score that will be used to rank the genes in order of significance. Note that high scores always signify differential expression, that is, a strong association with the predictor. For example, for methods returning a nominal p-value the score can be defined as $1 - \text{pvalue}$. • <code>FDR</code> false discovery rate estimates • <code>posterior.DE</code> posterior probabilities of differential expression • <code>prob.DE</code> conditional probabilities of differential expression • <code>lfdr</code> local false discovery rates • <code>statistic</code> test statistics from the differential expression analysis • <code>dispersion.S1</code> dispersion estimates in condition S1 • <code>dispersion.S2</code> dispersion estimates in condition S2

Value

A `compData` object.

Author(s)

Charlotte Soneson

Examples

```
count.matrix <- round(matrix(1000*runif(4000), 1000))
sample.annotations <- data.frame(condition = c(1, 1, 2, 2))
info.parameters <- list(dataset = "mydata", uID = "123456")
cpd <- compData(count.matrix, sample.annotations, info.parameters)
```

 compData-class

Class compData

Description

The `compData` class is used to store information about the experiment, such as the count matrix, sample and variable annotations, information regarding the generation of the data and results from applying a differential expression analysis to the data.

Slots

count.matrix: The read count matrix, with genes as rows and samples as columns. Class `matrix`

sample.annotations: A data frame containing sample annotation information for all samples in the data set. Must contain at least a column named `condition`, encoding the division of the samples into two classes. The row names should be the same as the column names of `count.matrix`. Class `data.frame`

info.parameters: A list of parameters detailing the simulation process used to generate the data. Must contain at least two entries, named `dataset` (an informative name for the data set/simulation setting) and `uID` (a unique ID for the specific data set instance). Class `list`

filtering: A character string detailing the filtering process that has been applied to the data. Class `character`

variable.annotations: Contains information regarding the variables, such as the differential expression status, the true mean, dispersion and effect sizes. If present, the row names should be the same as those of `count.matrix`. Class `data.frame`

analysis.date: (If a differential expression analysis has been performed and the results are included in the `compData` object). Gives the date when the differential expression analysis was performed. Class `character`

package.version: (If a differential expression analysis has been performed and the results are included in the `compData` object). Gives the version numbers of the package(s) used for the differential expression analysis. Class `character`

method.names: (If a differential expression analysis has been performed and the results are included in the `compData` object). A list, containing the name of the method used for the differential expression analysis. The list should have two entries: `full.name` and `short.name`, where the `full.name` is the full (potentially long) name identifying the method, and `short.name` may be an abbreviation. Class `list`

code: (If a differential expression analysis has been performed and the results are included in the `compData` object). A character string containing the code that was used to run the differential expression analysis. The code should be in R markdown format. Class `character`

result.table: (If a differential expression analysis has been performed and the results are included in the `compData` object). Contains the results of the differential expression analysis, in the form of a data frame with one row per gene. Must contain at least one column named `score`, where a higher value corresponds to 'more strongly differentially expressed genes'.
Class `data.frame`

Methods

count.matrix signature(`x="compData"`)

count.matrix<- signature(`x="compData"`, `value="matrix"`): Get or set the count matrix in a `compData` object. `value` should be a numeric matrix.

sample.annotations signature(`x="compData"`)

sample.annotations<- signature(`x="compData"`, `value="data.frame"`): Get or set the sample annotations data frame in a `compData` object. `value` should be a data frame with at least a column named `'condition'`.

info.parameters signature(`x="compData"`)

info.parameters<- signature(`x="compData"`, `value="list"`): Get or set the list with info parameters in a `compData` object. `value` should be a list with at least elements named `'dataset'` and `'uID'`.

filtering signature(`x="compData"`)

filtering<- signature(`x="compData"`, `value="character"`): Get or set the information about the filtering in a `compData` object. `value` should be a character string describing the filtering that has been performed.

variable.annotations signature(`x="compData"`)

variable.annotations<- signature(`x="compData"`, `value="data.frame"`): Get or set the variable annotations data frame in a `compData` object. `value` should be a data frame.

analysis.date signature(`x="compData"`)

analysis.date<- signature(`x="compData"`, `value="character"`): Get or set the analysis date in a `compData` object. `value` should be a character string describing when the differential expression analysis of the data was performed.

package.version signature(`x="compData"`)

package.version<- signature(`x="compData"`, `value="character"`): Get or set the information about the package version in a `compData` object. `value` should be a character string detailing which packages and versions were used to perform the differential expression analysis of the data.

method.names signature(`x="compData"`)

method.names<- signature(`x="compData"`, `value="list"`): Get or set the method names in a `compData` object. `value` should be a list with slots `full.name` and `short.name`, giving the full name and an abbreviation for the method that was used to perform the analysis of the data.

code signature(`x="compData"`)

code<- signature(`x="compData"`, `value="character"`): Get or set the code slot in a `compData` object. `value` should be a character string in R markdown format, giving the code that was run to obtain the results from the differential expression analysis.

result.table signature(x="compData")

result.table<- signature(x="compData", value="data.frame"): Get or set the result table in a compData object. value should be a data frame with one row per gene, and at least a column named 'score'.

Construction

An object of the class compData can be constructed using the [compData](#) function.

Author(s)

Charlotte Soneson

convertcompDataToList *Convert a compData object to a list*

Description

Given a compData object, convert it to a list.

Usage

```
convertcompDataToList(cpd)
```

Arguments

cpd A compData object

Author(s)

Charlotte Soneson

Examples

```
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 12500,  
                                   samples.per.cond = 5, n.diffexp = 1250)  
mydata.list <- convertcompDataToList(mydata.obj)
```

`convertListTocompData` *Convert a list with data and results to a compData object*

Description

Given a list with data and results (resulting e.g. from `compcodeR` version 0.1.0), convert it to a `compData` object.

Usage

```
convertListTocompData(inp.list)
```

Arguments

`inp.list` A list with data and results, e.g. generated by `compcodeR` version 0.1.0.

Author(s)

Charlotte Soneson

Examples

```
convertListTocompData(list(count.matrix = matrix(round(1000*runif(4000)), 1000),
  sample.annotations = data.frame(condition = c(1,1,2,2)),
  info.parameters = list(dataset = "mydata",
  uID = "123456")))
```

`DESeq.GLM.createRmd` *Generate a .Rmd file containing code to perform differential expression analysis with the DESeq GLM approach*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the GLM functionality from the `DESeq` package. The code is written to a `.Rmd` file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
DESeq.GLM.createRmd(data.path, result.path, codefile, sharing.mode, disp.method,
  fit.type)
```

Arguments

<code>data.path</code>	The path to a <code>.rds</code> file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>sharing.mode</code>	The method used to select between the individually estimated dispersion and the dispersion estimate obtained by fitting a dispersion-mean relationship to the estimated values for all genes. Possible values are "fit-only" (use the fitted value), "maximum" (take the maximum of the fitted and the estimated value) and "gene-est-only" (use the estimated value).
<code>disp.method</code>	The method used to estimate the dispersion. Possible values are "pooled", "per-condition" and "blind".
<code>fit.type</code>	The fitting method used to get the dispersion-mean relationship. Possible values are "parametric" and "local".

Details

For more information about the methods and the interpretation of the parameters, see the DESeq package and the corresponding publications.

Value

The function generates a `.Rmd` file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Anders S and Huber W (2010): Differential expression analysis for sequence count data. *Genome Biology* 11:R106

Examples

```
try(
  if (require(DESeq)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "DESeq.GLM",
              Rmdfunction = "DESeq.GLM.createRmd",
              output.directory = tmpdir, sharing.mode = "maximum",
              disp.method = "pooled", fit.type = "parametric")
  })
```

`DESeq.nbinom.createRmd`

Generate a .Rmd file containing code to perform differential expression analysis with the DESeq nbinom approach

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the nbinom test from the DESeq package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
DESeq.nbinom.createRmd(data.path, result.path, codefile, sharing.mode,  
  disp.method, fit.type)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>sharing.mode</code>	The method used to select between the individually estimated dispersion and the dispersion estimate obtained by fitting a dispersion-mean relationship to the estimated values for all genes. Possible values are "fit-only" (use the fitted value), "maximum" (take the maximum of the fitted and the estimated value) and "gene-est-only" (use the estimated value).
<code>disp.method</code>	The method used to estimate the dispersion. Possible values are "pooled", "per-condition" and "blind".
<code>fit.type</code>	The fitting method used to get the dispersion-mean relationship. Possible values are "parametric" and "local".

Details

For more information about the methods and the interpretation of the parameters, see the DESeq package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Anders S and Huber W (2010): Differential expression analysis for sequence count data. *Genome Biology* 11:R106

Examples

```
try(
  if (require(DESeq)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                      samples.per.cond = 5, n.diffexp = 100,
                                      output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "DESeq.nbinom",
              Rmdfunction = "DESeq.nbinom.createRmd",
              output.directory = tmpdir, sharing.mode = "maximum",
              disp.method = "pooled", fit.type = "parametric")
  })
```

DESeq2.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with DESeq2</i>
------------------	---

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the DESeq2 package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
DESeq2.createRmd(data.path, result.path, codefile, fit.type, test,
  beta.prior = TRUE, independent.filtering = TRUE, cooks.cutoff = TRUE,
  impute.outliers = TRUE)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
fit.type	The fitting method used to get the dispersion-mean relationship. Possible values are "parametric", "local" and "mean".
test	The test to use. Possible values are "Wald" and "LRT".
beta.prior	Whether or not to put a zero-mean normal prior on the non-intercept coefficients. Default is TRUE.

<code>independent.filtering</code>	Whether or not to perform independent filtering of the data. With independent filtering=TRUE, the adjusted p-values for genes not passing the filter threshold are set to NA.
<code>cooks.cutoff</code>	The cutoff value for the Cook's distance to consider a value to be an outlier. Set to Inf or FALSE to disable outlier detection. For genes with detected outliers, the p-value and adjusted p-value will be set to NA.
<code>impute.outliers</code>	Whether or not the outliers should be replaced by a trimmed mean and the analysis rerun.

Details

For more information about the methods and the interpretation of the parameters, see the DESeq2 package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Anders S and Huber W (2010): Differential expression analysis for sequence count data. *Genome Biology* 11:R106

Examples

```
try(
  if (require(DESeq2)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "DESeq2",
              Rmdfunction = "DESeq2.createRmd",
              output.directory = tmpdir, fit.type = "parametric",
              test = "Wald")
  })
```

DSS.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with DSS</i>
---------------	--

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the DSS package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
DSS.createRmd(data.path, result.path, codefile, norm.method, disp.trend)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "quantile", "total" and "median".
disp.trend	A logical parameter indicating whether or not to include a trend in the dispersion estimation.

Details

For more information about the methods and the interpretation of the parameters, see the DSS package and the corresponding publications.

Author(s)

Charlotte Soneson

References

Wu H, Wang C and Wu Z (2013): A new shrinkage estimator for dispersion improves differential expression detection in RNA-seq data. *Biostatistics* 14(2), 232-243

Examples

```
try(
  if (require(DSS)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "DSS",
              Rmdfunction = "DSS.createRmd",
              output.directory = tmpdir, norm.method = "quantile",
              disp.trend = TRUE)
  })
```

EBSeq.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with EBSeq</i>
-----------------	--

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the EBSeq package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
EBSeq.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "median" and "quantile".

Details

For more information about the methods and the meaning of the parameters, see the EBSeq package and the corresponding publications.

Value

The function generates a .Rmd file containing the differential expression code. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Leng N, Dawson JA, Thomson JA, Ruotti V, Rissman AI, Smits BMG, Haag JD, Gould MN, Stewart RM and Kendzierski C (2013): EBSeq: An empirical Bayes hierarchical model for inference in RNA-seq experiments. *Bioinformatics*

Examples

```
try(
  if (require(EBSeq)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "EBSeq",
              Rmdfunction = "EBSeq.createRmd",
              output.directory = tmpdir, norm.method = "median")
  }
)
```

edgeR.exact.createRmd *Generate a .Rmd file containing code to perform differential expression analysis with the edgeR exact test*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the exact test functionality from the edgeR package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
edgeR.exact.createRmd(data.path, result.path, codefile, norm.method,
  trend.method, disp.type)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "TMM", "RLE", "upperquartile" and "none".

trend.method	The method used to estimate the trend in the mean-dispersion relationship. Possible values are "none", "movingave" and "loess"
disp.type	The type of dispersion estimate used. Possible values are "common", "trended" and "tagwise".

Details

For more information about the methods and the interpretation of the parameters, see the edgeR package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Robinson MD, McCarthy DJ and Smyth GK (2010): edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "edgeR.exact",
           Rmdfunction = "edgeR.exact.createRmd",
           output.directory = tmpdir, norm.method = "TMM",
           trend.method = "movingave", disp.type = "tagwise")
```

edgeR.GLM.createRmd *Generate a .Rmd file containing code to perform differential expression analysis with the edgeR GLM approach*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the GLM functionality from the edgeR package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
edgeR.GLM.createRmd(data.path, result.path, codefile, norm.method, disp.type,  
  disp.method, trended)
```

Arguments

<code>data.path</code>	The path to a <code>.rds</code> file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>norm.method</code>	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "TMM", "RLE", "upperquartile" and "none".
<code>disp.type</code>	The type of dispersion estimate used. Possible values are "common", "trended" and "tagwise".
<code>disp.method</code>	The method used to estimate the dispersion. Possible values are "CoxReid", "Pearson" and "deviance".
<code>trended</code>	Logical parameter indicating whether or not a trended dispersion estimate should be used.

Details

For more information about the methods and the interpretation of the parameters, see the `edgeR` package and the corresponding publications.

Value

The function generates a `.Rmd` file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Robinson MD, McCarthy DJ and Smyth GK (2010): `edgeR`: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")  
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
  samples.per.cond = 5, n.diffexp = 100,  
  output.file = file.path(tmpdir, "mydata.rds"))  
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "edgeR.GLM",  
  Rmdfunction = "edgeR.GLM.createRmd",  
  output.directory = tmpdir, norm.method = "TMM",
```

```
disp.type = "tagwise", disp.method = "CoxReid",  
trended = TRUE)
```

generateCodeHTMLs	<i>Generate HTML file(s) containing code used to run differential expression analysis.</i>
-------------------	--

Description

A function to extract the code used to generate differential expression results from saved compData result objects (typically obtained by `runDiffExp`), and to write the code to HTML files. This requires that the code was saved as a character string in R markdown format in the code slot of the result object, which is done automatically by `runDiffExp`. If the differential expression analysis was performed with functions outside compcodeR, the code has to be added manually to the result object.

Usage

```
generateCodeHTMLs(input.files, output.directory)
```

Arguments

`input.files` A vector with paths to one or several .rds files containing compData objects with the results from differential expression analysis. One code HTML file is generated for each file in the vector.

`output.directory`
The path to the directory where the code HTML files will be saved.

Author(s)

Charlotte Soneson

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")  
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                                   samples.per.cond = 5, n.diffexp = 100,  
                                   output.file = file.path(tmpdir, "mydata.rds"))  
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.limma",  
           Rmdfunction = "voom.limma.createRmd", output.directory = tmpdir,  
           norm.method = "TMM")  
generateCodeHTMLs(file.path(tmpdir, "mydata_voom.limma.rds"), tmpdir)
```

generateSyntheticData *Generate synthetic count data sets*

Description

Generate synthetic count data sets, following the simulation strategy detailed in Sonesson and DeIorenzi (2013).

Usage

```
generateSyntheticData(dataset, n.vars, samples.per.cond, n.diffexp,
  repl.id = 1, seqdepth = 1e+07, minfact = 0.7, maxfact = 1.4,
  relmeans = "auto", dispersions = "auto", fraction.upregulated = 1,
  between.group.diffdisp = FALSE, filter.threshold.total = 1,
  filter.threshold.mediancpm = 0, fraction.non.overdispersed = 0,
  random.outlier.high.prob = 0, random.outlier.low.prob = 0,
  single.outlier.high.prob = 0, single.outlier.low.prob = 0,
  effect.size = 1.5, output.file = NULL)
```

Arguments

dataset	A name or identifier for the data set/simulation settings.
n.vars	The initial number of genes in the simulated data set. Based on the filtering conditions (<code>filter.threshold.total</code> and <code>filter.threshold.mediancpm</code>), the number of genes in the final data set may be lower than this number.
samples.per.cond	The number of samples in each of the two conditions.
n.diffexp	The number of genes simulated to be differentially expressed between the two conditions.
repl.id	A replicate ID for the specific simulation instance. Useful for example when generating multiple count matrices with the same simulation settings.
seqdepth	The base sequencing depth (total number of mapped reads). This number is multiplied by a value drawn uniformly between <code>minfact</code> and <code>maxfact</code> for each sample to generate data with different actual sequencing depths.
minfact,maxfact	The minimum and maximum for the uniform distribution used to generate factors that are multiplied with <code>seqdepth</code> to generate individual sequencing depths for the simulated samples.
relmeans	A vector of mean values to use in the simulation of data from the Negative Binomial distribution, or "auto". Note that these values may be scaled in order to comply with the given sequencing depth. With the default value ("auto"), the mean values are sampled from values estimated from the Pickrell and Cheung data sets. If <code>relmeans</code> is a vector, the provided values will be used as mean values in the simulation for the samples in the first condition. The mean values for the samples in the second condition are generated by combining the <code>relmeans</code> and <code>effect.size</code> arguments.

<code>dispersions</code>	A vector or matrix of dispersions to use in the simulation of data from the Negative Binomial distribution, or "auto". With the default value ("auto"), the dispersion values are sampled from values estimated from the Pickrell and Cheung data sets. If both <code>relmeans</code> and <code>dispersions</code> are set to "auto", the means and dispersion values are sampled in pairs from the values in these data sets. If <code>dispersions</code> is a single vector, the provided dispersions will be used for simulating data from both conditions. If it is a matrix with two columns, the values in the first column are used for condition 1, and the values in the second column are used for condition 2.
<code>fraction.upregulated</code>	The fraction of the differentially expressed genes that is upregulated in condition 2 compared to condition 1.
<code>between.group.diffdisp</code>	Whether or not the dispersion should be allowed to be different between the conditions. Only applicable if <code>dispersions</code> is "auto".
<code>filter.threshold.total</code>	The filter threshold on the total count for a gene across all samples. All genes for which the total count across all samples is less than the threshold will be filtered out.
<code>filter.threshold.mediancpm</code>	The filter threshold on the median count per million (cpm) for a gene across all samples. All genes for which the median cpm across all samples is less than the threshold will be filtered out.
<code>fraction.non.overdispersed</code>	The fraction of the genes that should be simulated according to a Poisson distribution, without overdispersion. The non-overdispersed genes will be divided proportionally between the upregulated, downregulated and non-differentially expressed genes.
<code>random.outlier.high.prob</code>	The fraction of 'random' outliers with unusually high counts.
<code>random.outlier.low.prob</code>	The fraction of 'random' outliers with unusually low counts.
<code>single.outlier.high.prob</code>	The fraction of 'single' outliers with unusually high counts.
<code>single.outlier.low.prob</code>	The fraction of 'single' outliers with unusually low counts.
<code>effect.size</code>	The strength of the differential expression, i.e., the effect size, between the two conditions. If this is a single number, the effect sizes will be obtained by simulating numbers from an exponential distribution (with rate 1) and adding the results to the <code>effect.size</code> . For genes that are upregulated in the second condition, the mean in the first condition is multiplied by the effect size. For genes that are downregulated in the second condition, the mean in the first condition is divided by the effect size. It is also possible to provide a vector of effect sizes (one for each gene), which will be used as provided. In this case, the <code>fraction.upregulated</code> and <code>n.diffexp</code> arguments will be ignored and the values will be derived from the <code>effect.size</code> vector.
<code>output.file</code>	If not NULL, the path to the file where the data object should be saved. The extension should be <code>.rds</code> , if not it will be changed.

Details

In the comparison function, only results obtained for data sets with the same value of the dataset parameter will be compared. Hence, it is important to give the same value of this parameter e.g. to different replicates generated with the same simulation settings.

For more detailed information regarding the different types of outliers, see Sonesson and Delorenzi (2013).

Mean and dispersion parameters (if relmeans and/or dispersions is set to "auto") are sampled from values estimated from the data sets by Pickrell et al (2010) and Cheung et al (2010). The data sets were downloaded from the ReCount web page (Frazee et al (2011)) and processed as detailed by Sonesson and Delorenzi (2013).

To get the actual mean value for the Negative Binomial distribution used for the simulation of counts for a given sample, take the column truemeans.S1 (or truemeans.S2, if the sample is in condition S2) of the variable.annotations slot, divide by the sum of the same column and multiply with the base sequencing depth (provided in the info.parameters list) and the depth factor for the sample (given in the sample.annotations data frame). Thus, if you have a vector of mean values that you want to provide as the relmeans argument and make sure to use it 'as-is' in the simulation (for condition S1), make sure to set the seqdepth argument to the sum of the values in the relmeans vector, and to set minfact and maxfact equal to 1.

Value

A `compData` object. If output.file is not NULL, the object is saved in the given output.file (which should have an .rds extension).

Author(s)

Charlotte Sonesson

References

- Sonesson C and Delorenzi M (2013): A comparison of methods for differential expression analysis of RNA-seq data. *BMC Bioinformatics* 14:91
- Cheung VG, Nayak RR, Wang IX, Elwyn S, Cousins SM, Morley M and Spielman RS (2010): Polymorphic cis- and trans-regulation of human gene expression. *PLoS Biology* 8(9):e1000480
- Frazee AC, Langmead B and Leek JT (2011): ReCount: a multi-experiment resource of analysis-ready RNA-seq gene count datasets. *BMC Bioinformatics* 12:449
- Pickrell JK, Marioni JC, Pai AA, Degner JF, Engelhardt BE, Nkadori E, Veyrieras JB, Stephens M, Gilad Y and Pritchard JK (2010): Understanding mechanisms underlying human gene expression variation with RNA sequencing. *Nature* 464, 768-772
- Robles JA, Qureshi SE, Stephen SJ, Wilson SR, Burden CJ and Taylor JM (2012): Efficient experimental design and analysis strategies for the detection of differential expression using RNA-sequencing. *BMC Genomics* 13:484

Examples

```
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100)
```

listcreateRmd *List available *.createRmd functions*

Description

Print a list of all *.createRmd functions that are available in the search path. These functions can be used together with the `runDiffExp` function to perform differential expression analysis. Consult the help pages for the respective functions for more information.

Usage

```
listcreateRmd()
```

Author(s)

Charlotte Soneson

Examples

```
listcreateRmd()
```

logcpm.limma.createRmd
Generate a .Rmd file containing code to perform differential expression analysis with limma after log-transforming the counts per million (cpm)

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using limma, after preprocessing the counts by computing the counts per million (cpm) and applying a logarithmic transformation. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
logcpm.limma.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>norm.method</code>	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the <code>calcNormFactors</code> function from the <code>edgeR</code> package. Possible values are "TMM", "RLE", "upperquartile" and "none"

Details

For more information about the methods and the interpretation of the parameters, see the `edgeR` and `limma` packages and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `kni tr` package.

Author(s)

Charlotte Soneson

References

- Smyth GK (2005): Limma: linear models for microarray data. In: 'Bioinformatics and Computational Biology Solutions using R and Bioconductor'. R. Gentleman, V. Carey, S. Dudoit, R. Irizarry, W. Huber (eds), Springer, New York, pages 397-420
- Robinson MD, McCarthy DJ and Smyth GK (2010): edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140
- Robinson MD and Oshlack A (2010): A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11:R25

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "logcpm.limma",
            Rmdfunction = "logcpm.limma.createRmd",
            output.directory = tmpdir, norm.method = "TMM")
```

NBPSeq.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with NBPSeq</i>
------------------	---

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using NBPSeq. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
NBPSeq.createRmd(data.path, result.path, codefile, norm.method, disp.method)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>norm.method</code>	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the <code>calcNormFactors</code> function from the <code>edgeR</code> package. Possible values are "TMM", "RLE", "upperquartile" and "none".
<code>disp.method</code>	The method to use to estimate the dispersion values. Possible values are "NBP" and "NB2".

Details

For more information about the methods and the interpretation of the parameters, see the NBPSeq and edgeR packages and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Robinson MD, McCarthy DJ and Smyth GK (2010): edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140

Robinson MD and Oshlack A (2010): A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11:R25

Di Y, Schafer DW, Cumbie JS, and Chang JH (2011): The NBP Negative Binomial Model for Assessing Differential Gene Expression from RNA-Seq. *Statistical Applications in Genetics and Molecular Biology* 10(1), 1-28

Examples

```
try(  
  if (require(NBPSeq)) {  
    tmpdir <- normalizePath(tmpdir(), winslash = "/")  
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                                       samples.per.cond = 5, n.diffexp = 100,  
                                       output.file = file.path(tmpdir, "mydata.rds"))  
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "NBPSeq",  
              Rmdfunction = "NBPSeq.createRmd",  
              output.directory = tmpdir, norm.method = "TMM", disp.method = "NBP")  
  })
```

NOISeq.prenorm.createRmd

Generate a .Rmd file containing code to perform differential expression analysis with NOISeq

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using NOISeq. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
NOISeq.prenorm.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.

`norm.method` The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the `calcNormFactors` function from the `edgeR` package. Possible values are "TMM", "RLE", "upperquartile" and "none".

Details

For more information about the methods and the interpretation of the parameters, see the NOISeq package and the corresponding publications.

Value

The function generates a `.Rmd` file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Sonesson

References

Robinson MD, McCarthy DJ and Smyth GK (2010): `edgeR`: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140

Robinson MD and Oshlack A (2010): A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11:R25

Tarazona S, Furio-Tari P, Ferrer A and Conesa A (2012): NOISeq: Exploratory analysis and differential expression for RNA-seq data. R package

Tarazona S, Garcia-Alcalde F, Dopazo J, Ferrer A and Conesa A (2011): Differential expression in RNA-seq: a matter of depth. *Genome Res* 21(12), 2213-2223

Examples

```
try(  
  if (require(NOISeq)) {  
    tmpdir <- normalizePath(tmpdir(), winslash = "/")  
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                                       samples.per.cond = 5, n.diffexp = 100,  
                                       output.file = file.path(tmpdir, "mydata.rds"))  
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "NOISeq",  
              Rmdfunction = "NOISeq.prenorm.createRmd",  
              output.directory = tmpdir, norm.method = "TMM")  
  })
```

runComparison	<i>Run the performance comparison between differential expression methods.</i>
---------------	--

Description

The main function for performing comparisons among differential expression methods and generating a report in HTML format. It is assumed that all differential expression results have been generated in advance (using e.g. the function `runDiffExp`) and that the result `compData` object for each data set and each differential expression method is saved separately in files with the extension `.rds`. Note that the function can also be called via the `runComparisonGUI` function, which lets the user set parameters and select input files using a graphical user interface.

Usage

```
runComparison(file.table, parameters, output.directory, check.table = TRUE,
              out.width = NULL)
```

Arguments

- | | |
|-------------------------|--|
| <code>file.table</code> | A data frame with at least a column <code>input.files</code> , potentially also columns named <code>datasets</code> , <code>nbr.samples</code> , <code>repl</code> and <code>de.methods</code> . |
| <code>parameters</code> | A list containing parameters for the comparison study. The following entries are supported, and used by different comparison methods: <ul style="list-style-type: none"> • <code>incl.nbr.samples</code> An array with sample sizes (number of samples per condition) to consider in the comparison. If set to <code>NULL</code>, all sample sizes will be included. • <code>incl.dataset</code> A dataset name (corresponding to the dataset slot of the results or data objects), indicating the dataset that will be used for the comparison. Only one dataset can be chosen. • <code>incl.replicates</code> An array with replicate numbers to consider in the comparison. If set to <code>NULL</code>, all replicates will be included. • <code>incl.de.methods</code> An array with differential expression methods to be compared. If set to <code>NULL</code>, all differential expression methods will be included. • <code>fdr.threshold</code> The adjusted p-value threshold for FDR calculations. Default 0.05. • <code>tpr.threshold</code> The adjusted p-value threshold for TPR calculations. Default 0.05. • <code>mcc.threshold</code> The adjusted p-value threshold for MCC calculations. Default 0.05. • <code>typeI.threshold</code> The nominal p-value threshold for type I error calculations. Default 0.05. • <code>fdc.maxvar</code> The maximal number of variables to include in false discovery curve plots. Default 1500. |

- `overlap.threshold` The adjusted p-value for overlap analysis. Default 0.05.
- `fracsign.threshold` The adjusted p-value for calculation of the fraction of genes called significant. Default 0.05.
- `ma.threshold` The adjusted p-value threshold for coloring genes in MA plots. Default 0.05.
- `signal.measure` Either 'mean' or 'snr', determining how to define the signal strength for a gene which is expressed in only one condition.
- `upper.limits, lower.limits` Lists that can be used to manually set the upper and lower plot limits for boxplots of `fdr`, `tpr`, `auc`, `mcc`, `fracsign` and `typeIerror`.
- `comparisons` Array containing the comparison methods to be applied. The entries must be chosen among the following abbreviations:
 - "auc" - Compute the area under the ROC curve
 - "mcc" - Compute Matthew's correlation coefficient
 - "tpr" - Compute the true positive rate at a given adjusted p-value threshold (`tpr.threshold`)
 - "fdr" - Compute the false discovery rate at a given adjusted p-value threshold (`fdr.threshold`)
 - "fdrvsexpr" - Compute the false discovery rate as a function of the expression level.
 - "typeIerror" - Compute the type I error rate at a given nominal p-value threshold (`typeI.threshold`)
 - "fracsign" - Compute the fraction of genes called significant at a given adjusted p-value threshold (`fracsign.threshold`)
 - "maplot" - Construct MA plots, depicting the average expression level and the log fold change for the genes and indicating the genes called differentially expressed at a given adjusted p-value threshold (`ma.threshold`)
 - "fdcurvesall" - Construct false discovery curves for each of the included replicates
 - "fdcurvesone" - Construct false discovery curves for a single replicate only
 - "rocall" - Construct ROC curves for each of the included replicates
 - "rocone" - Construct ROC curves for a single replicate only
 - "overlap" - Compute the overlap between collections of genes called differentially expressed by the different methods at a given adjusted p-value threshold (`overlap.threshold`)
 - "sorensen" - Compute the Sorensen index, quantifying the overlap between collections of genes called differentially expressed by the different methods, at a given adjusted p-value threshold (`overlap.threshold`)
 - "correlation" - Compute the Spearman correlation between gene scores assigned by different methods
 - "scorevsoutlier" - Visualize the distribution of the gene scores as a function of the number of outlier counts introduced for the genes
 - "scorevsexpr" - Visualize the gene scores as a function of the average expression level of the genes

- "scorevssignal" - Visualize the gene score as a function of the 'signal strength' (see the signal.measure parameter above) for genes that are expressed in only one condition

output.directory	The directory where the results should be written. The subdirectory structure will be created automatically. If the directory already exists, it will be overwritten.
check.table	Logical, should the input table be checked for consistency. Default TRUE.
out.width	The width of the figures in the final report. Will be passed on to knitr when the HTML is generated.

Details

The input to `runComparison` is a data frame with at least a column named `input.files`, containing paths to `.rds` files containing result objects (of the class `compData`), such as those generated by `runDiffExp`. Other columns that can be included in the data frame are `datasets`, `nbr.samples`, `repl` and `de.methods`. They have to match the information contained in the corresponding result objects. If these columns are not present, they will be added to the data frame automatically.

Value

The function will create a comparison report, named `compcodeR_report<timestamp>.html`, in the `output.directory`. It will also create subfolders named `compcodeR_code` and `compcodeR_figure`, where the code used to perform the differential expression analysis and the figures contained in the report, respectively, will be stored. Note that if these directories already exist, they will be overwritten.

Author(s)

Charlotte Sonesson

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.limma",
            Rmdfunction = "voom.limma.createRmd", output.directory = tmpdir,
            norm.method = "TMM")
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "edgeR.exact",
            Rmdfunction = "edgeR.exact.createRmd", output.directory = tmpdir,
            norm.method = "TMM",
            trend.method = "movingave", disp.type = "tagwise")
file.table <- data.frame(input.files = file.path(tmpdir,
                                                c("mydata_voom.limma.rds", "mydata_edgeR.exact.rds")),
                        stringsAsFactors = FALSE)
parameters <- list(incl.nbr.samples = 5, incl.replicates = 1, incl.dataset = "mydata",
                  incl.de.methods = NULL,
                  fdr.threshold = 0.05, tpr.threshold = 0.05, typeI.threshold = 0.05,
```

```

ma.threshold = 0.05, fdc.maxvar = 1500, overlap.threshold = 0.05,
fracsign.threshold = 0.05, mcc.threshold = 0.05,
comparisons = c("auc", "fdr", "tpr", "ma", "correlation"))
runComparison(file.table = file.table, parameters = parameters, output.directory = tmpdir)

```

runComparisonGUI	<i>A GUI to the main function for running the performance comparison between differential expression methods.</i>
------------------	---

Description

This function provides a GUI to the main function for performing comparisons among differential expression methods and generating a report in HTML format ([runComparison](#)). It is assumed that all differential expression results have been generated in advance (using e.g. the function [runDiffExp](#)) and that the result `compData` object for each data set and each differential expression method is saved separately in files with the extension `.rds`. The function opens a graphical user interface where the user can set parameter values and choose the files to be used as the basis of the comparison. It is, however, possible to circumvent the GUI and call the comparison function [runComparison](#) directly.

Usage

```

runComparisonGUI(input.directories, output.directory, recursive,
  out.width = NULL, upper.limits = NULL, lower.limits = NULL)

```

Arguments

<code>input.directories</code>	A list of directories containing the result files (<code>*.rds</code>). All results in the provided directories will be available for inclusion in the comparison, and the selection is performed through a graphical user interface. All result objects saved in the files should be of the <code>compData</code> class, although list objects created by earlier versions of <code>compcodeR</code> are supported.
<code>output.directory</code>	The directory where the results should be written. The subdirectory structure will be created automatically. If the directory already exists, it will be overwritten.
<code>recursive</code>	A logical parameter indicating whether or not the search should be extended recursively to subfolders of the <code>input.directories</code> .
<code>out.width</code>	The width of the figures in the final report. Will be passed on to <code>knitr</code> when the HTML is generated. Can be for example "800px" (see <code>knitr</code> documentation for more information)
<code>upper.limits, lower.limits</code>	Lists that can be used to manually set upper and lower limits for boxplots of <code>fdr</code> , <code>tpr</code> , <code>auc</code> , <code>mcc</code> , <code>fracsign</code> and <code>typeIerror</code> .

Details

This function requires that the `rpanel` package is installed. If this package can not be installed, please use the `runComparison` function directly.

Value

The function will create a comparison report, named `compcodeR_report<timestamp>.html`, in the `output.directory`. It will also create subfolders named `compcodeR_code` and `compcodeR_figure`, where the code used to perform the differential expression analysis and the figures contained in the report, respectively, will be saved. Note that if these directories already exist they will be overwritten.

Author(s)

Charlotte Soneson

Examples

```
## Not run:
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 12500,
                                   samples.per.cond = 5, n.diffexp = 1250,
                                   output.file = "mydata.rds")
runDiffExp(data.file = "mydata.rds", result.extent = "voom.limma",
           Rmdfunction = "voom.limma.createRmd", output.directory = ".",
           norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "ttest",
           Rmdfunction = "ttest.createRmd", output.directory = ".",
           norm.method = "TMM")
runComparisonGUI(input.directories = ".", output.directory = ".", recursive = FALSE)

## End(Not run)
```

runDiffExp

The main function to run differential expression analysis

Description

The main function for running differential expression analysis (comparing two conditions), using one of the methods interfaced through `compcodeR` or a user-defined method.

Usage

```
runDiffExp(data.file, result.extent, Rmdfunction, output.directory = ".",
           norm.path = TRUE, ...)
```

Arguments

data.file	The path to a .rds file containing the data on which the differential expression analysis will be performed, for example a compData object returned from generateSyntheticData .
result.extent	The extension that will be added to the data file name in order to construct the result file name. This can be for example the differential expression method together with a version number.
Rmdfunction	A function that creates an Rmd file containing the code that should be run to perform the differential expression analysis. All functions available through compcodeR can be listed using the listcreateRmd function.
output.directory	The directory in which the result object will be saved.
norm.path	Logical, whether to include the full (absolute) path to the output object in the saved code.
...	Additional arguments that will be passed to the Rmdfunction, such as parameter choices for the differential expression method.

Author(s)

Charlotte Soneson

Examples

```

tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))

listcreateRmd()
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.limma",
           Rmdfunction = "voom.limma.createRmd",
           output.directory = tmpdir, norm.method = "TMM")

## Not run:
## The following list covers the currently available
differential expression methods:
runDiffExp(data.file = "mydata.rds", result.extent = "baySeq",
           Rmdfunction = "baySeq.createRmd",
           output.directory = ".", norm.method = "edgeR",
           distr.choice = "NB", equaldisp = TRUE)
runDiffExp(data.file = "mydata.rds", result.extent = "DESeq.GLM",
           Rmdfunction = "DESeq.GLM.createRmd",
           output.directory = ".", sharing.mode = "maximum",
           disp.method = "pooled", fit.type = "parametric")
runDiffExp(data.file = "mydata.rds", result.extent = "DESeq.nbinom",
           Rmdfunction = "DESeq.nbinom.createRmd",
           output.directory = ".", sharing.mode = "maximum",
           disp.method = "pooled", fit.type = "parametric")
runDiffExp(data.file = "mydata.rds", result.extent = "DESeq2",
           Rmdfunction = "DESeq2.createRmd",

```

```

        output.directory = ".", fit.type = "parametric",
        test = "Wald", beta.prior = TRUE,
        independent.filtering = TRUE, cooks.cutoff = TRUE,
        impute.outliers = TRUE)
runDiffExp(data.file = "mydata.rds", result.extent = "DSS",
           Rmdfunction = "DSS.createRmd",
           output.directory = ".", norm.method = "quantile",
           disp.trend = TRUE)
runDiffExp(data.file = "mydata.rds", result.extent = "EBSseq",
           Rmdfunction = "EBSseq.createRmd",
           output.directory = ".", norm.method = "median")
runDiffExp(data.file = "mydata.rds", result.extent = "edgeR.exact",
           Rmdfunction = "edgeR.exact.createRmd",
           output.directory = ".", norm.method = "TMM",
           trend.method = "movingave", disp.type = "tagwise")
runDiffExp(data.file = "mydata.rds", result.extent = "edgeR.GLM",
           Rmdfunction = "edgeR.GLM.createRmd",
           output.directory = ".", norm.method = "TMM",
           disp.type = "tagwise", disp.method = "CoxReid",
           trended = TRUE)
runDiffExp(data.file = "mydata.rds", result.extent = "logcpm.limma",
           Rmdfunction = "logcpm.limma.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "NBPSseq",
           Rmdfunction = "NBPSseq.createRmd",
           output.directory = ".", norm.method = "TMM",
           disp.method = "NBP")
runDiffExp(data.file = "mydata.rds", result.extent = "NOISseq",
           Rmdfunction = "NOISseq.prenorm.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "SAMseq",
           Rmdfunction = "SAMseq.createRmd",
           output.directory = ".")
runDiffExp(data.file = "mydata.rds", result.extent = "sqrtcpm.limma",
           Rmdfunction = "sqrtcpm.limma.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "TCC",
           Rmdfunction = "TCC.createRmd",
           output.directory = ".", norm.method = "tmm",
           test.method = "edger", iteration = 3,
           normFDR = 0.1, floorPDEG = 0.05)
runDiffExp(data.file = "mydata.rds", result.extent = "ttest",
           Rmdfunction = "ttest.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "voom.limma",
           Rmdfunction = "voom.limma.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "voom.ttest",
           Rmdfunction = "voom.ttest.createRmd",
           output.directory = ".", norm.method = "TMM")
runDiffExp(data.file = "mydata.rds", result.extent = "vst.limma",
           Rmdfunction = "vst.limma.createRmd",
           output.directory = ".", fit.type = "parametric")

```

```
runDiffExp(data.file = "mydata.rds", result.extent = "vst.ttest",
           Rmdfunction = "vst.ttest.createRmd",
           output.directory = ".", fit.type = "parametric")

## End(Not run)
```

SAMseq.createRmd *Generate a .Rmd file containing code to perform differential expression analysis with SAMseq*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using SAMseq. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
SAMseq.createRmd(data.path, result.path, codefile)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.

Details

For more information about the methods and the interpretation of the parameters, see the SAMseq package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `kni tr` package.

Author(s)

Charlotte Soneson

References

Li J and Tibshirani R (2011): Finding consistent patterns: a nonparametric approach for identifying differential expression in RNA-Seq data. *Statistical Methods in Medical Research*

Examples

```
try(  
  if (require(samr)) {  
    tmpdir <- normalizePath(tmpdir(), winslash = "/")  
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                                       samples.per.cond = 5, n.diffexp = 100,  
                                       output.file = file.path(tmpdir, "mydata.rds"))  
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "SAMseq",  
              Rmdfunction = "SAMseq.createRmd",  
              output.directory = tmpdir)  
  })
```

show,compData-method *Show method for compData object*

Description

Show method for compData object.

Usage

```
## S4 method for signature 'compData'  
show(object)
```

Arguments

object A compData object

Author(s)

Charlotte Soneson

Examples

```
mydata <- generateSyntheticData(dataset = "mydata", n.vars = 12500,  
                               samples.per.cond = 5, n.diffexp = 1250)  
mydata
```

sqrtpm.limma.createRmd

Generate a .Rmd file containing code to perform differential expression analysis with limma after square root-transforming the counts per million (cpm)

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using limma, after preprocessing the counts by computing the counts per million (cpm) and applying a square-root transformation. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
sqrtpm.limma.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the calcNormFactors function from the edgeR package. Possible values are "TMM", "RLE", "upperquartile" and "none".

Details

For more information about the methods and the interpretation of the parameters, see the edgeR and limma packages and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

- Smyth GK (2005): Limma: linear models for microarray data. In: 'Bioinformatics and Computational Biology Solutions using R and Bioconductor'. R. Gentleman, V. Carey, S. Dudoit, R. Irizarry, W. Huber (eds), Springer, New York, pages 397-420
- Robinson MD, McCarthy DJ and Smyth GK (2010): edgeR: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140
- Robinson MD and Oshlack A (2010): A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11:R25

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "sqrtcpm.limma",
           Rmdfunction = "sqrtcpm.limma.createRmd",
           output.directory = tmpdir, norm.method = "TMM")
```

summarizeSyntheticDataSet

Summarize a synthetic data set by some diagnostic plots

Description

Summarize a synthetic data set (generated by [generateSyntheticData](#)) by some diagnostic plots.

Usage

```
summarizeSyntheticDataSet(data.set, output.filename)
```

Arguments

- `data.set` A data set, either a [compData](#) object or a path to an `.rds` file where such an object is stored.
- `output.filename` The filename of the resulting html report (including the path).

Author(s)

Charlotte Soneson

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
summarizeSyntheticDataSet(data.set = file.path(tmpdir, "mydata.rds"),
                          output.filename = file.path(tmpdir, "mydata_check.html"))
```

TCC.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with TCC</i>
---------------	--

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using the TCC package. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
TCC.createRmd(data.path, result.path, codefile, norm.method, test.method,
              iteration = 3, normFDR = 0.1, floorPDEG = 0.05)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>norm.method</code>	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. Possible values are "tmm", and "deseq".
<code>test.method</code>	The method used in TCC to find differentially expressed genes. Possible values are "edger", "deseq" and "bayseq".
<code>iteration</code>	The number of iterations used to find the normalization factors. Default value is 3.
<code>normFDR</code>	The FDR cutoff for calling differentially expressed genes in the computation of the normalization factors. Default value is 0.1.
<code>floorPDEG</code>	The minimum value to be eliminated as potential differentially expressed genes before performing step 3 in the TCC algorithm. Default value is 0.05.

Details

For more information about the methods and the interpretation of the parameters, see the TCC package and the corresponding publications.

Author(s)

Charlotte Soneson

References

Kadota K, Nishiyama T, and Shimizu K. A normalization strategy for comparing tag count data. *Algorithms Mol Biol.* 7:5, 2012.

Sun J, Nishiyama T, Shimizu K, and Kadota K. TCC: an R package for comparing tag count data with robust normalization strategies. *BMC Bioinformatics* 14:219, 2013.

Examples

```
try(
  if (require(TCC)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "TCC",
              Rmdfunction = "TCC.createRmd",
              output.directory = tmpdir, norm.method = "tmm",
              test.method = "edger")
  })
```

ttest.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with a t-test</i>
-----------------	---

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) using a t-test, applied to the normalized counts. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
ttest.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.

norm.method The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the `calcNormFactors` function from the `edgeR` package. Possible values are "TMM", "RLE", "upperquartile" and "none"

Details

For more information about the methods and the interpretation of the parameters, see the `edgeR` package and the corresponding publications.

Value

The function generates a `.Rmd` file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Robinson MD, McCarthy DJ and Smyth GK (2010): `edgeR`: a Bioconductor package for differential expression analysis of digital gene expression data. *Bioinformatics* 26, 139-140

Robinson MD and Oshlack A (2010): A scaling normalization method for differential expression analysis of RNA-seq data. *Genome Biology* 11:R25

Examples

```
try(
  if (require(genefilter)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "ttest",
              Rmdfunction = "ttest.createRmd",
              output.directory = tmpdir, norm.method = "TMM")
  })
```

voom.limma.createRmd *Generate a .Rmd file containing code to perform differential expression analysis with voom+limma*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) by applying the voom transformation (from the limma package) followed by differential expression analysis with limma. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
voom.limma.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>norm.method</code>	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the <code>calcNormFactors</code> of the <code>edgeR</code> package. Possible values are "TMM", "RLE", "upperquartile" and "none"

Details

For more information about the methods and the interpretation of the parameters, see the `limma` package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Sonesson

References

Smyth GK (2005): Limma: linear models for microarray data. In: 'Bioinformatics and Computational Biology Solutions using R and Bioconductor'. R. Gentleman, V. Carey, S. Dudoit, R. Irizarry, W. Huber (eds), Springer, New York, pages 397-420

Law CW, Chen Y, Shi W and Smyth GK (2014): voom: precision weights unlock linear model analysis tools for RNA-seq read counts. *Genome Biology* 15, R29

Examples

```
tmpdir <- normalizePath(tmpdir(), winslash = "/")
mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                   samples.per.cond = 5, n.diffexp = 100,
                                   output.file = file.path(tmpdir, "mydata.rds"))
runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.limma",
           Rmdfunction = "voom.limma.createRmd",
           output.directory = tmpdir, norm.method = "TMM")
```

voom.ttest.createRmd *Generate a .Rmd file containing code to perform differential expression analysis with voom+t-test*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) by applying the voom transformation (from the limma package) followed by differential expression analysis with a t-test. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
voom.ttest.createRmd(data.path, result.path, codefile, norm.method)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.
norm.method	The between-sample normalization method used to compensate for varying library sizes and composition in the differential expression analysis. The normalization factors are calculated using the calcNormFactors function from the edgeR package. Possible values are "TMM", "RLE", "upperquartile" and "none".

Details

For more information about the methods and the interpretation of the parameters, see the limma and edgeR packages and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the knitr package.

Author(s)

Charlotte Soneson

References

Smyth GK (2005): Limma: linear models for microarray data. In: 'Bioinformatics and Computational Biology Solutions using R and Bioconductor'. R. Gentleman, V. Carey, S. Dudoit, R. Irizarry, W. Huber (eds), Springer, New York, pages 397-420

Law CW, Chen Y, Shi W and Smyth GK (2014): voom: precision weights unlock linear model analysis tools for RNA-seq read counts. *Genome Biology* 15, R29

Examples

```
try(
  if (require(genefilter)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                      samples.per.cond = 5, n.diffexp = 100,
                                      output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "voom.ttest",
              Rmdfunction = "voom.ttest.createRmd",
              output.directory = tmpdir, norm.method = "TMM")
  })
```

vst.limma.createRmd	<i>Generate a .Rmd file containing code to perform differential expression analysis with limma after the variance-stabilizing transformation provided in DESeq</i>
---------------------	--

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq (comparing two conditions) by applying the variance-stabilizing transformation of the DESeq package followed by differential expression analysis using limma. The code is written to a .Rmd file. This function is generally not called by the user, the main interface for performing differential expression analysis is the [runDiffExp](#) function.

Usage

```
vst.limma.createRmd(data.path, result.path, codefile, fit.type)
```

Arguments

data.path	The path to a .rds file containing the compData object that will be used for the differential expression analysis.
result.path	The path to the file where the result object will be saved.
codefile	The path to the file where the code will be written.

`fit.type` The fitting method used to get the dispersion-mean relationship. Possible values are "parametric" and "local".

Details

For more information about the methods and the interpretation of the parameters, see the `limma` and `DESeq` packages and the corresponding publications.

Value

The function generates a `.Rmd` file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Smyth GK (2005): `Limma`: linear models for microarray data. In: 'Bioinformatics and Computational Biology Solutions using R and Bioconductor'. R. Gentleman, V. Carey, S. Dudoit, R. Irizarry, W. Huber (eds), Springer, New York, pages 397-420

Anders S and Huber W (2010): Differential expression analysis for sequence count data. *Genome Biology* 11:R106

Examples

```
try(
  if (require(DESeq)) {
    tmpdir <- normalizePath(tmpdir(), winslash = "/")
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,
                                       samples.per.cond = 5, n.diffexp = 100,
                                       output.file = file.path(tmpdir, "mydata.rds"))
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "vst.limma",
              Rmdfunction = "vst.limma.createRmd",
              output.directory = tmpdir, fit.type = "parametric")
  })
```

`vst.ttest.createRmd` *Generate a .Rmd file containing code to perform differential expression analysis with a t-test after the variance-stabilizing transformation provided in DESeq*

Description

A function to generate code that can be run to perform differential expression analysis of RNAseq data (comparing two conditions) by applying the variance-stabilizing transformation of the `DESeq` package followed by differential expression analysis using a t-test. The code is written to a `.Rmd` file. This function is generally not called by the user, the main interface for performing differential expression analysis is the `runDiffExp` function.

Usage

```
vst.ttest.createRmd(data.path, result.path, codefile, fit.type)
```

Arguments

<code>data.path</code>	The path to a .rds file containing the <code>compData</code> object that will be used for the differential expression analysis.
<code>result.path</code>	The path to the file where the result object will be saved.
<code>codefile</code>	The path to the file where the code will be written.
<code>fit.type</code>	The fitting method used to get the dispersion-mean relationship. Possible values are "parametric" and "local".

Details

For more information about the methods and the interpretation of the parameters, see the DESeq package and the corresponding publications.

Value

The function generates a .Rmd file containing the code for performing the differential expression analysis. This file can be executed using e.g. the `knitr` package.

Author(s)

Charlotte Soneson

References

Anders S and Huber W (2010): Differential expression analysis for sequence count data. *Genome Biology* 11:R106

Examples

```
try(  
  if (require(DESeq) && require(genefilter)) {  
    tmpdir <- normalizePath(tmpdir(), winslash = "/")  
    mydata.obj <- generateSyntheticData(dataset = "mydata", n.vars = 1000,  
                                       samples.per.cond = 5, n.diffexp = 100,  
                                       output.file = file.path(tmpdir, "mydata.rds"))  
    runDiffExp(data.file = file.path(tmpdir, "mydata.rds"), result.extent = "vst.ttest",  
              Rmdfunction = "vst.ttest.createRmd",  
              output.directory = tmpdir, fit.type = "parametric")  
  }  
)
```

Index

*Topic **package**

- compcodeR-package, 2
- baySeq.createRmd, 3
- check_compData, 4, 6
- check_compData_results, 4, 7
- checkDataObject, 4
- checkTableConsistency, 5
- compcodeR (compcodeR-package), 2
- compcodeR-package, 2
- compData, 8, 13, 27, 43
- compData-class, 11
- convertcompDataToList, 13
- convertListTocompData, 14
- DESeq.GLM.createRmd, 14
- DESeq.nbinom.createRmd, 16
- DESeq2.createRmd, 17
- DSS.createRmd, 19
- EBSeq.createRmd, 20
- edgeR.exact.createRmd, 21
- edgeR.GLM.createRmd, 22
- generateCodeHTMLs, 10, 24
- generateSyntheticData, 25, 38, 43
- listcreateRmd, 28, 38
- logcpm.limma.createRmd, 28
- NBPSeq.createRmd, 30
- NOISeq.prenorm.createRmd, 31
- runComparison, 5, 33, 35–37
- runComparisonGUI, 33, 36
- runDiffExp, 3, 14, 16, 17, 19–22, 24, 28, 30, 31, 33, 35, 36, 37, 40, 42, 44, 45, 47–50
- SAMseq.createRmd, 40
- show, compData-method, 41
- sqrtpm.limma.createRmd, 42
- summarizeSyntheticDataSet, 43
- TCC.createRmd, 44
- ttest.createRmd, 45
- voom.limma.createRmd, 46
- voom.ttest.createRmd, 48
- vst.limma.createRmd, 49
- vst.ttest.createRmd, 50