

Package ‘specL’

October 9, 2015

Type Package

Title specL - Prepare Peptide Spectrum Matches for Use in Targeted Proteomics

Version 1.2.0

Author Christian Trachsel <christian.trachsel@fgcz.uzh.ch>, Christian Panse <cp@fgcz.ethz.ch>, Jonas Grossmann <jg@fgcz.ethz.ch>

Maintainer Christian Panse <cp@fgcz.ethz.ch>

Depends R (>= 3.0.2), methods, DBI, RSQLite, seqinr, protViz (>= 0.2.5),

LinkingTo Rcpp (>= 0.9.9)

Suggests RUnit, BiocGenerics, BiocStyle, BiocParallel, plotrix

Description specL provides a function for generating spectra libraries which can be used for MRM SRM MS workflows in proteomics. The package provides a BiblioSpec reader, a function which can add the protein information using a FASTA formatted amino acid file, and an export method for using the created library in the Spectronaut software.

License GPL-3

URL <http://www.bioconductor.org/packages/devel/bioc/html/specL.html>

Collate read.bibliospec.R genSwathIonLib.R annotate.protein_id.R
AllGenerics.R specL.R specLSet.R

biocViews MassSpectrometry, Proteomics

LazyData true

NeedsCompilation yes

R topics documented:

annotate.protein_id	2
genSwathIonLib	3
iRTpeptides	6
peptideStd	7

plot-methods	8
read.bibliospec	8
show-methods	9
specL-class	10
specLSet-class	11
write.spectronaut-methods	12

Index	13
--------------	-----------

annotate.protein_id *Annotate protein_id*

Description

This function assigns the protein identifier for a list of tandem mass specs having a peptide sequence assigned.

Usage

```
annotate.protein_id(data, file = NULL, fasta = read.fasta(file = file,
              as.string = TRUE, seqtype = "AA"), digestPattern = "(([RK])|(^)|(^M))")
```

Arguments

- data** list of records containing mZ and peptide sequences.
- file** file name of a FASTA file.
- fasta** a fasta object as returned by the `seqinr::read.fasta(...)` method.
- digestPattern** a regex pattern which can be used by the grep command. the default regex pattern assumes a tryptic digest.

Details

The protein sequences are read by the `read.fasta` function of the `seqinr` package. The protein identifier is written to the protein `proteinInformation` variable.

If the function is called on a multi-core architecture it uses `mclapply`.

It is recommended to load the FASTA file prior to running `annotate.protein_id` using
`myFASTA <- read.fasta(file = file, as.string = TRUE, seqtype = "AA")`
instead of providing the FASTA file name to the function.

Value

it returns a list object.

Author(s)

Jonas Grossmann and Christian Panse, 2014

See Also

?read.fasta of the seqinr package.

<http://www.uniprot.org/help/fasta-headers>

Examples

```
# annotate.protein_id

# our Fasta sequence
irtFASTAseq <- paste(">zz|ZZ_FGCZCont0260|",
  "iRT_Protein_with_AAAAK_spacers concatenated Biognosys\n",
  "LGGNEQVTRAAAAGKAGSSEPVTGLDAAKAAKVEATFGVDESNAAAACYILAGVENS",
  "KAAAAKTPVISGGPYEYRAAAAKTPVITGAPYEYRAAAAKDGLDAASYYAPVRAAAAKAD",
  "VTPADFSEWSKAAAAGTFIIDPGGVIRAAAAGTFIIDPAAVIRAAAALKFLQFGAQGS",
  "PFLK\n")

# be realistic, do it from file
Tfile <- file(); cat(irtFASTAseq, file = Tfile);

#use read.fasta from seqinr
fasta.irtFASTAseq <-read.fasta(Tfile, as.string=TRUE, seqtype="AA")
close(Tfile)

#annotate with proteinID
# -> here we find all psms from the one proteinID above
peptideStd <- specL::annotate.protein_id(peptideStd,
  fasta=fasta.irtFASTAseq)

#show indices for all PSMs where we have a proteinInformation
which(unlist(lapply(peptideStd,
  function(x){nchar(x$proteinInformation)>0})))
```

Description

This function generates an ion library for SWATH analysis. It takes a R data object which contains a peak list. The R data object can be generated using the `read.bibliospec` function.

Usage

```
genSwathIonLib(data,
  data.fit = data,
  mascotIonScoreCutOFF=20,
  proteinIDPattern='',
  max.mZ.Da.error = 0.1,
  ignoreMascotIonScore = TRUE,
  topN = 10,
  fragmentIonMzRange = c(300, 1800),
  fragmentIonRange = c(5,100),
  fragmentIonFUN = .defaultSwathFragmentIon,
  iRT = specL::iRTpeptides,
  AminoAcids = protViz::AA,
  breaks=NULL)
```

Arguments

data data set containing mZ and peptide sequence.

mascotIonScoreCutOFF a value for filtering the specs.

proteinIDPattern a filter for protein.

max.mZ.Da.error the mZ error in Dalton on ms2 level.

ignoreMascotIonScore Boolean if mascot score is considered or not.

topN returns the most N intense fragment ion only.

fragmentIonMzRange mZ range filter of fragment ion.

fragmentIonRange range filter of the number of identified fragment ion which are assigned in the spectrum library set in **fragmentIonTyp**. Use this option to generate a library with a minimum of five transitions for all peptides using **c(5,100)**, all peptides where at least not five transmissions found were omitted.

fragmentIonFUN function (b, y) which derives all requested fragment ion out a given tuple of b and y ion. If the parameter is not specified the method uses an internal function similar as the example below.

iRT optional table which contains iRT peptides. If an iRT table is provided (default) a lm is applied to normalize the rt in data. See also ?iRT. A necessary condition is that data contains at least two iRT peptides.

AminoAcids a list containing of 1-letter code and mono-isotopic mass of the amino acids. Default uses the **protViz::AA** data set.

data.fit data set containing mZ and peptide sequence which is used for normalizing rt using a linear model **lm(formula = rt ~ aggregateInputRT * fileName, data)**. The rt aggregation for the model uses median.

breaks provides a vector of SWATH windows. If q1 (precursor mass) and q3 (fragment ion) fall into the same SWATH window the fragment ion is ignored in the resulting ion library. The following code shows an example `breaks=seq(400, 2000, by=25)`.

Details

The function is the main contribution of the `specL` package. It generates the spectra library used in a SWATH analysis workflow out of a mass spectrometric measurement.

`genSwathIonLib` uses the core functions `protViz::findNN`, `protViz::fragmentIon`, and `protViz::aa2mass`.

The input is read by using `read.bibliospec` function of this package and passed by the `data` function parameter. If no BiblioSpec files are available also Mascot DAT files can be read using scripts contained in the `protViz` package exec folder.

If the protein information is lost you can benefit for the `specL::annotate.protein_id.Rd` method.

The function first appear in the `protViz` 0.1.45 package. It has been removed in `protViz` 0.2.6 to avoid package dependencies.

Value

The output is a data structure defined as `specLSet` object. The generic method `ionlibrary` returns a list of `specL` objects, `specLSet` also stores the input and normalized retention times.

Author(s)

Christian Panse, Christian Trachsel, and Jonas Grossmann 2012, 2013, 2014

See Also

The S4 class definition: `showClass("specL")` `showClass("specLSet")`
and the package vignette file. `vignette('specL')`

Examples

```
myFragmentIon <- function (b, y) {
  Hydrogen <- 1.007825
  Oxygen <- 15.994915
  Nitrogen <- 14.003074

  b1_ <- (b )
  y1_ <- (y )

  b2_ <- (b + Hydrogen) / 2
  y2_ <- (y + Hydrogen) / 2

  b3_ <- (b + 2 * Hydrogen) / 3
  y3_ <- (y + 2 * Hydrogen) / 3

  return( cbind(b1_, y1_, b2_, y2_, b3_, y3_) )
}
```

```

peptideStd.ionLib <- genSwathIonLib(data=peptideStd,
  data.fit=peptideStd.redundant,
  fragmentIonFUN=myFragmentIon)

summary(peptideStd.ionLib)

idx<-40

op <- par(mfrow = c(2,1))

plot(peptideStd.ionLib)

text(rt.input(peptideStd.ionLib)[idx],
  rt.normalized(peptideStd.ionLib)[idx],
  "X", cex=1.5)

plot(ionlibrary(peptideStd.ionLib)[[idx]])

## Not run:
# write.spectronaut(peptideStd.ionLib,
#   file="peptideStd.ionLib.csv")

## End(Not run)

```

iRTpeptides*iRT peptides - independent retention time peptides*

Description

iRTpeptides data are used for `genSwathIonLib` rt normalization assuming. **iRTpeptides** first appear in the `protViz` 0.1.45 package. It has been removed in `protViz` 0.2.10 to avoid package dependencies.

Format

contains a table

Author(s)

Jonas Grossmann and Christian Panse 2013

References

Using iRT, a normalized retention time for more targeted measurement of peptides. Escher C, Reiter L, MacLean B, Ossola R, Herzog F, Chilton J, MacCoss MJ, Rinner O. Source Proteomics. 2012 Apr;12(8):1111-21. doi: 10.1002/pmic.201100463.

Examples

```
plot(sort(iRTpeptides$rt))

plot(pim<-protViz::parentIonMass(as.character(iRTpeptides$peptide)) ~ iRTpeptides$rt)
```

peptideStd

Peptide standard

Description

This dataset is a list of a peptide spectrum matches (protein identification result) from two standard runs.

Format

contains a list of peptide spectrum assignments.

Details

These standard runs (LCMS experiments) are routinely run on well maintained instruments. In this case a standard run consists of a digest of the FETUIN_BOVINE protein (400 amol) and iRT peptides.

Author(s)

Christian Panse, Christian Trachsel and Jonas Grossmann 2014

See Also

<http://fgcz-data.uzh.ch/~cpanse/specL/data/>

Examples

```
peakplot(peptideStd[[40]]$peptideSequence, peptideStd[[40]])

## Not run:

download.file("http://fgcz-data.uzh.ch/~cpanse/specL/data/peptideStd.blib",
              destfile="peptideStd.blib")

download.file("http://fgcz-data.uzh.ch/~cpanse/specL/data/peptideStd.redundant.blib",
              destfile="peptideStd.redundant.blib")

# checksum

if (require(tools)){
```

```

md5sum(c("peptideStd.blib", "peptideStd.redundant.blib")) ==
  c("3f231931e54efd6516d7aa302073b17f",
    "8bab829d9e99344136613a17c0374b90")
}

peptideStd <- read.bibliospec("peptideStd.blib")
peptideStd.redundant <- read.bibliospec("peptideStd.redundant.blib")

## End(Not run)

```

plot-methods*Method for Function plot in Package specL***Description**

This methode has no additional arguments.

Value

The method plots on the current device.

Methods

`signature(x = "specL")` Plots the specL determined ions.

`signature(x = "specLSet")` Plots retention time versus retention time.

read.bibliospec*BiblioSpec Reader***Description**

This function reads a BiblioSpec generated file and returns a list of tandem mass specs (psm objects), peptide assignments, retention times, and modifications records. The type of the data structire which is returned is called psmSet.

Usage

```
read.bibliospec(file)
```

Arguments

<code>file</code>	the name of the BiblioSpec generated SQLite file.
-------------------	---

Details

The function performs a SQL query on the SQLite files generated by `bibliospec` using the `RSQLite` package. The function is required for generating spec libraries used in a SWATH workflow.

`BiblioSpec` files are generated by using Skyline.

Value

It returns a list which can be read by the `genSwathIonLib` function and the `protViz::peakplot` function.

Author(s)

Christian Panse, 2014, 2015

See Also

<https://skyline.gs.washington.edu/labkey/project/home/software/Skyline/begin.view>
<https://skyline.gs.washington.edu/labkey/project/home/software/BiblioSpec/begin.view>
<http://www.sqlite.org/>
?SQLite

Examples

```
read.bibliospec
```

show-methods

*Methods for Function show in Package **specL** ~~*

Description

Methods for function `show` in package `specL` ~~ writes `specL` or `specLSet` objects to a file or console.

Methods

`signature(x = "specL")` Prints `specL` object data to the console.
`signature(x = "specLSet")` Prints `specL` object data to the console.

specL-class	<i>Class "specL"</i>
-------------	----------------------

Description

This class is used to store, print, and plot the generated results of the package.

Objects from the Class

Objects can be created by calls of the form `new("specL", ...)`.

Slots

`group_id`: Object of class "character" just an id
`peptide_sequence`: Object of class "character" AA sequence
`proteinInformation`: Object of class "character" a string contains the protein identifier.
`q1`: Object of class "numeric" peptide weight m/Z as measured by the MS device
`q1.in_silico`: Object of class "numeric" peptide weight m/Z computed in-silico.
`q3`: Object of class "numeric" measured fragment ions.
`q3.in_silico`: Object of class "numeric" in-silico derived fragment ions.
`decoy`: Object of class "character" is this a decoy hit? 1 or 0.
`prec_z`: Object of class "numeric" pre-cursor charge.
`frg_type`: Object of class "character" fragment ion type, e.g., b or y ion.
`frg_nr`: Object of class "numeric" fragment ion number
`frg_z`: Object of class "numeric" fragment ion charge.
`relativeFragmentIntensity`: Object of class "numeric" percentage base peaks of fragment ions.
`irt`: Object of class "numeric" independent retention time in seconds.
`peptideModSeq`: Object of class "numeric" a vector contains the mass diff between AA and mod AA.
`mZ.error`: Object of class "numeric" a string contains the protein identifier.
`filename`: Object of class "character" a string contains the filename of the ions.

Methods

plot `signature(x = "specL")`: plots the fragment ions of specL object.
show `signature(x = "specL")`: shows the content of specL object.
write.spectronaut `signature(x = "specL")`: writes the specL object to a ASCII file.

Note

No notes yet.

Author(s)

Christian Panse 2014

See Also

[genSwathIonLib](#)

Examples

```
showClass("specL")
```

specLSet-class *Class "specLSet"*

Description

This class is used to store, show, and write generated results of the package.

Objects from the Class

Objects can be created by calls of the form `new("specLSet", ...)`.

Slots

input.parameter: A list of parameter values.
ionlibrary: A list of "specL" objects.
rt.normalized: A numeric vector of normalized retention time values.
rt.input: A numeric vector of retention time values.

Methods

show `signature(x = "specLSet")`: shows the object content.
summary `signature(x = "specLSet")`: print summary of object content.
plot `signature(x = "specLSet")`: plots normalized versus input rt.
write.spectronaut `signature(x = "specLSet")`: writes object to ASCII file.
generate.consensus `signature(x = "specLSet")`: generates consensus specLSet object by combining all specL objects having a redundant group_id which is defined by `paste(x@q1.in_silico, x@peptideModSeq)`.
merge.specLSet `signature(x = "specLSet")`: merges two specLSet objects.
ionlibrary `signature(x = "specLSet")`: returns a list of specL objects.
rt.input `signature(x = "specLSet")`: returns a numeric vector of input rt values.
rt.normalized `signature(x = "specLSet")`: returns a numeric vector of normalized rt values.

Note

No notes yet.

Author(s)

Christian Panse 2014

See Also

[genSwathIonLib](#)

Examples

```
showClass("specL")
showClass("specLSet")
```

write.spectronaut-methods

*Methods for Function write.spectronaut in Package **specL***

Description

Methods for function **write.spectronaut** in package **specL** ~~ writes specL objects to a file in a format which can be read by the 'Spectronaut' software. additional arguments are

file A file name. default is `file='spec.txt'`.

Methods

`signature(x = "specL")` Prints specL object data to to a file.

`signature(x = "specLSet")` Prints specL object data to to a file.

Index

*Topic **classes**
 specL-class, 10
 specLSet-class, 11

*Topic **methods**
 plot-methods, 8
 show-methods, 9
 write.spectronaut-methods, 12

annotate.protein_id, 2

BiblioSpec (read.bibliospec), 8
bibliospec (read.bibliospec), 8

generate.consensus (specLSet-class), 11
generate.consensus, specLSet-method
 (specLSet-class), 11

genSwathIonLib, 3, 11, 12

ionlibrary (specLSet-class), 11
ionlibrary, specLSet-method
 (specLSet-class), 11

iRT (iRTpeptides), 6
irt (iRTpeptides), 6
iRTpeptides, 6

merge.specLSet (specLSet-class), 11
merge.specLSet, specLSet-method
 (specLSet-class), 11

MRM (genSwathIonLib), 3

peptideStd, 7
plot (specLSet-class), 11
plot, ANY-method (plot-methods), 8
plot, specL-method (specL-class), 10
plot, specL-methods (plot-methods), 8
plot, specLSet-method (specLSet-class),
 11
plot, specLSet-methods (plot-methods), 8
plot-methods, 8
plot.psm (read.bibliospec), 8
plot.psmSet (read.bibliospec), 8

read.bibliospec, 8
rt.input (specLSet-class), 11
rt.input, specLSet-method
 (specLSet-class), 11
rt.normalized (specLSet-class), 11
rt.normalized, specLSet-method
 (specLSet-class), 11

show, ANY-method (show-methods), 9
show, specL-method (specL-class), 10
show, specLSet-method (specLSet-class),
 11
show-methods, 9
Skyline (read.bibliospec), 8
skyline (read.bibliospec), 8
specL (genSwathIonLib), 3
specL-class, 10
specLSet-class, 11
summary, specLSet-method
 (specLSet-class), 11
summary.psmSet (read.bibliospec), 8
SWATH (genSwathIonLib), 3
swath (genSwathIonLib), 3

write.spectronaut
 (write.spectronaut-methods), 12
write.spectronaut, ANY-method
 (write.spectronaut-methods), 12
write.spectronaut, specL-method
 (specL-class), 10
write.spectronaut, specL-methods
 (write.spectronaut-methods), 12
write.spectronaut, specLSet-method
 (specLSet-class), 11
write.spectronaut, specLSet-methods
 (write.spectronaut-methods), 12
write.spectronaut-methods, 12