

Package ‘rWikiPathways’

October 17, 2020

Type Package

Title rWikiPathways - R client library for the WikiPathways API

Version 1.8.5

Date 2020-09-09

Imports httr, utils, XML, rjson, data.table, tidyverse

Suggests testthat, BiocStyle, knitr, rmarkdown

Description Use this package to interface with the WikiPathways API.

License MIT + file LICENSE

URL <https://github.com/wikipathways/rwikipathways>

BugReports <https://github.com/wikipathways/rwikipathways/issues>

LazyLoad yes

biocViews Visualization, GraphAndNetwork, ThirdPartyClient, Network,
Metabolomics

NeedsCompilation no

VignetteBuilder knitr

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/rWikiPathways>

git_branch RELEASE_3_11

git_last_commit 510f995

git_last_commit_date 2020-09-09

Date/Publication 2020-10-16

Author Egon Willighagen [aut, cre] (<<https://orcid.org/0000-0001-7542-0286>>),
Alex Pico [aut] (<<https://orcid.org/0000-0001-5706-2163>>)

Maintainer Egon Willighagen <egon.willighagen@gmail.com>

R topics documented:

downloadPathwayArchive	2
findPathwayIdsByLiterature	3
findPathwayIdsByText	4
findPathwayIdsByXref	5
findPathwayNamesByLiterature	5

findPathwayNamesByText	6
findPathwayNamesByXref	7
findPathwaysByLiterature	7
findPathwaysByText	8
findPathwaysByXref	9
findPathwayUrlsByLiterature	9
findPathwayUrlsByText	10
findPathwayUrlsByXref	11
getColoredPathway	11
getCurationTagNames	12
getCurationTags	13
getEveryCurationTag	13
getOntologyTermIds	14
getOntologyTermNames	14
getOntologyTerms	15
getPathway	15
getPathwayHistory	16
getPathwayIdsByCurationTag	16
getPathwayIdsByOntologyTerm	17
getPathwayIdsByParentOntologyTerm	17
getPathwayInfo	18
getPathwaysByCurationTag	18
getPathwaysByOntologyTerm	19
getPathwaysByParentOntologyTerm	19
getRecentChanges	20
getRecentChangesIds	20
getRecentChangesNames	21
getXrefList	21
listOrganisms	22
listPathwayIds	22
listPathwayNames	23
listPathways	24
listPathwayUrls	24
readPathwayGMT	25
wikipathwaysAPI	26
wikipathwaysGET	26

Index**28**

downloadPathwayArchive

*Download Pathway Archive***Description**

Access the monthly archives of pathway content from WikiPathways.

Usage

```
downloadPathwayArchive(
  date = "current",
  organism = NULL,
  format = c("gpml", "gmt", "svg"),
  destpath = "./"
)
```

Arguments

<code>date</code>	(optional) The timestamp for a monthly release (e.g., 20171010) or "current" (default) for latest release.
<code>organism</code>	(optional) A particular species. See listOrganisms .
<code>format</code>	(optional) Either gpml (default), gmt or svg.
<code>destpath</code>	(optional) Destination path for file to be downloaded to. Default is current working directory.

Details

If you do not specify an organism, then an archive file will not be downloaded. Rather, the archive will be opened in a tab in your default browser.

Value

Filename of downloaded file or an opened tab in default browser

See Also

[readPathwayGMT](#)

Examples

```
downloadPathwayArchive() ## open in browser
downloadPathwayArchive(format="gmt") ## open in browser
downloadPathwayArchive(date="20171010", format="svg") ## open in browser
downloadPathwayArchive(date="20171010", organism="Mus musculus", format="svg") ## download file
downloadPathwayArchive(organism="Mus musculus") ## download file
```

findPathwayIdsByLiterature

Find Pathway WPIDs By Literature

Description

Retrieve list of pathway WPIDs containing the query citation.

Usage

```
findPathwayIdsByLiterature(query)
```

Arguments

query The character string to search for, e.g., a PMID, title keyword or author name.

Value

A list of WPIDs

See Also

[findPathwaysByLiterature](#)

Examples

```
{
  findPathwayIdsByText('19649250')
  findPathwayIdsByText('smith')
  findPathwayIdsByText('cancer')
}
```

findPathwayIdsByText *Find Pathway WPIDs By Text*

Description

Retrieve list of pathway WPIDs containing the query text.

Usage

`findPathwayIdsByText(query)`

Arguments

query A character string to search for, e.g., "cancer"

Value

A list of WPIDs

See Also

[findPathwaysByText](#)

Examples

```
{
  findPathwayIdsByText('cancer')
}
```

findPathwayIdsByXref *Find Pathway WPIDs By Xref*

Description

Retrieve list of pathway WPIDs containing the query Xref by identifier and system code.

Usage

```
findPathwayIdsByXref(identifier, systemCode)
```

Arguments

identifier	(character) The official ID specified by a data source or system
systemCode	(character) The BridgeDb code associated with the data source or system, e.g., En (Ensembl), L (Entrez), Ch (HMDB), etc. See column two of https://github.com/bridgedb/BridgeDb

Details

Note: there will be multiple listings of the same pathway if the Xref is present multiple times.

Value

A list of WPIDs

See Also

`findPathwaysByXref`

Examples

```
{  
  findPathwayIdsByXref('ENSG00000232810', 'En')  
}
```

findPathwayNamesByLiterature *Find Pathway Names By Literature*

Description

Retrieve list of pathway names containing the query citation.

Usage

```
findPathwayNamesByLiterature(query)
```

Arguments

query	The character string to search for, e.g., a PMID, title keyword or author name.
-------	---

Details

Note: there will be multiple listings of the same pathway name if copies exist for multiple species.

Value

A list of lists

See Also

[findPathwaysByLiterature](#)

Examples

```
{  
  findPathwayNamesByLiterature('19649250')  
  findPathwayNamesByLiterature('smith')  
  findPathwayNamesByLiterature('cancer')  
}
```

findPathwayNamesByText

Find Pathway Names By Text

Description

Retrieve list of pathway names containing the query text.

Usage

`findPathwayNamesByText(query)`

Arguments

`query` A character string to search for, e.g., "cancer"

Details

Note: there will be multiple listings of the same pathway name if copies exist for multiple species.

Value

A list of pathway names

See Also

[findPathwaysByText](#)

Examples

```
{  
  findPathwayNamesByText('cancer')  
}
```

findPathwayNamesByXref

Find Pathway Names By Xref

Description

Retrieve list of pathway names containing the query Xref by identifier and system code.

Usage

```
findPathwayNamesByXref(identifier, systemCode)
```

Arguments

identifier (character) The official ID specified by a data source or system

systemCode (character) The BridgeDb code associated with the data source or system, e.g., En (Ensembl), L (Entrez), Ch (HMDB), etc. See column two of <https://github.com/bridgedb/BridgeDb>

Details

Note: there will be multiple listings of the same pathway if the Xref is present multiple times.

Value

A list of lists

See Also

[findPathwaysByXref](#)

Examples

```
{  
  findPathwayNamesByXref('ENSG00000232810', 'En')  
}
```

findPathwaysByLiterature

Find Pathways By Literature

Description

Retrieve pathways containing the query citation.

Usage

```
findPathwaysByLiterature(query)
```

Arguments

query The character string to search for, e.g., a PMID, title keyword or author name.

Details

The score is from a lucene index search engine, ranging from 0 to 1 with higher scores for better matches. The two literature columns are lists of pubmed ids and titles for the citations matching the query per pathway. The graphId column lists the id for any objects in the GPML pathway model that have been specifically annotated with the matching citations.

Value

A datafram of pathway attributes in addition to query result score and literature details

Examples

```
{
  findPathwaysByLiterature('19649250')
  findPathwaysByLiterature('smith')
  findPathwaysByLiterature('cancer')
}
```

findPathwaysByText *Find Pathways By Text*

Description

Retrieve pathways containing the query text.

Usage

```
findPathwaysByText(query)
```

Arguments

query	A character string to search for, e.g., "cancer"
-------	--

Details

The score is from a lucene index search engine, ranging from 0 to 1 with higher scores for better matches.

Value

A datafram of pathway attributes in addition to query result score

Examples

```
{
  findPathwaysByText('cancer')
}
```

```
findPathwaysByXref      Find Pathways By Xref
```

Description

Retrieve pathways containing the query Xref by identifier and system code.

Usage

```
findPathwaysByXref(identifier, systemCode)
```

Arguments

identifier	(character) The official ID specified by a data source or system
systemCode	(character) The BridgeDb code associated with the data source or system, e.g., En (Ensembl), L (Entrez), Ch (HMDB), etc. See column two of https://github.com/bridgedb/BridgeDB

Details

Note: there will be multiple listings of the same pathway if the Xref is present mutiple times.

The score is from a lucene index search engine, ranging from 0 to 1 with higher scores for better matches.

Value

A dataframe of pathway attributes in addition to query result score

Examples

```
{  
  findPathwaysByXref('ENSG00000232810', 'En')  
}
```

```
findPathwayUrlsByLiterature  
Find Pathway URLs By Literature
```

Description

Retrieve list of pathway URLs containing the query citation.

Usage

```
findPathwayUrlsByLiterature(query)
```

Arguments

query	The character string to search for, e.g., a PMID, title keyword or author name.
-------	---

Value

A list of lists

See Also

[findPathwaysByLiterature](#)

Examples

```
{  
  findPathwayUrlsByLiterature('19649250')  
  findPathwayUrlsByLiterature('smith')  
  findPathwayUrlsByLiterature('cancer')  
}
```

findPathwayUrlsByText *Find Pathway URLs By Text*

Description

Retrieve list of pathway URLs containing the query text.

Usage

`findPathwayUrlsByText(query)`

Arguments

query	A character string to search for, e.g., "cancer"
-------	--

Value

A list of urls

See Also

[findPathwaysByText](#)

Examples

```
{  
  findPathwayUrlsByText('cancer')  
}
```

findPathwayUrlsByXref *Find Pathway URLs By Xref*

Description

Retrieve list of pathway URLs containing the query Xref by identifier and system code.

Usage

```
findPathwayUrlsByXref(identifier, systemCode)
```

Arguments

identifier	(character) The official ID specified by a data source or system
systemCode	(character) The BridgeDb code associated with the data source or system, e.g., En (Ensembl), L (Entrez), Ch (HMDB), etc. See column two of https://github.com/bridgedb/BridgeDb

Details

Note: there will be multiple listings of the same pathway if the Xref is present multiple times.

Value

A list of lists

See Also

[findPathwaysByXref](#)

Examples

```
{  
  findPathwayUrlsByXref('ENSG00000232810', 'En')  
}
```

getColoredPathway *Deprecated: Get Colored Pathway*

Description

This function is no longer working and has been deprecated in this release and will be defunct at the next release.

Usage

```
getColoredPathway(  
  pathway,  
  revision = 0,  
  graphId = NULL,  
  color = NULL,  
  fileType = c("svg", "png", "pdf")  
)
```

Arguments

pathway	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
revision	(integer, optional) Number to indicate a specific revision to download
graphId	A character string or vector indicating the nodes to color
color	(optional) String or vector indicating the highlighting color, e.g., #FF8855. Default is red. You can provide a single color for multiple nodes; otherwise color list and graphId must be the same length.
fileType	(optional) Image file format, e.g., svg (default), png or pdf.

Value

Image file

Examples

```
{
  svg = getColoredPathway(pathway="WP554", graphId="ef1f3")
  svg = getColoredPathway(pathway="WP554", graphId=c("ef1f3", "e68e0"))
  svg = getColoredPathway(pathway="WP554", graphId=c("ef1f3", "e68e0"),
                         color="00FF00")
  svg = getColoredPathway(pathway="WP554", graphId=c("ef1f3", "e68e0"),
                         color=c("FF0000", "0000FF"))
  # writeLines(svg, "pathway.svg")
}
```

getCurationTagNames *Get Curation Tag Names on a Pathway***Description**

Retrieve names of curation tags for a specific pathway.

Usage

```
getCurationTagNames(pathway)
```

Arguments

pathway	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
---------	--

Value

A list of tag names

Examples

```
{
  getCurationTagNames('WP554')
}
```

`getCurationTags`

Get Curation Tags on a Pathway

Description

Retrieve information about curation tags for a specific pathway.

Usage

```
getCurationTags(pathway)
```

Arguments

pathway WikiPathways identifier (WPID) for the pathway to download, e.g. WP4

Value

A list of tag name, display name, revision, text, timestamp and user

Examples

```
{
  getCurationTags('WP554')
}
```

`getEveryCurationTag`

Get Every Instance of a Curation Tag

Description

Retrieve information about every instance of a given curation tag.

Usage

```
getEveryCurationTag(tag)
```

Arguments

tag (character) Official name of curation tag, e.g., "Curation:FeaturedPathway"

Value

A list of tag name, display name, revision, text, timestamp and user

Examples

```
{
  getEveryCurationTag('Curation:FeaturedPathway')
}
```

```
getOntologyTermIds      Get Ontology Term IDs by Pathway
```

Description

Retrieve identifiers of ontology terms for a specific pathway.

Usage

```
getOntologyTermIds(pathway)
```

Arguments

pathway WikiPathways identifier (WPID) for the pathway to download, e.g. WP4

Value

A list of term identifiers

Examples

```
{
  getOntologyTermIds('WP554')
}
```

```
getOntologyTermNames      Get Ontology Term Names by Pathway
```

Description

Retrieve names of ontology terms for a specific pathway.

Usage

```
getOntologyTermNames(pathway)
```

Arguments

pathway WikiPathways identifier (WPID) for the pathway to download, e.g. WP4

Value

A list of term names

Examples

```
{
  getOntologyTermNames('WP554')
}
```

getOntologyTerms	<i>Get Ontology Terms by Pathway</i>
------------------	--------------------------------------

Description

Retrieve information about ontology terms for a specific pathway.

Usage

```
getOntologyTerms(pathway)
```

Arguments

pathway	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
---------	--

Value

A list of tag name, display name, revision, text, timestamp and user

Examples

```
{
  getOntologyTerms('WP554')
}
```

getPathway	<i>Get Pathway</i>
------------	--------------------

Description

Retrieve a specific pathway in the GPML format

Usage

```
getPathway(pathway, revision = 0)
```

Arguments

pathway	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
revision	(integer, optional) Number to indicate a specific revision to download

Value

GPML

Examples

```
{
  getPathway('WP554')
}
```

`getPathwayHistory` *Get Pathway History*

Description

Retrieve the revision history of a pathway.

Usage

```
getPathwayHistory(pathway, timestamp)
```

Arguments

<code>pathway</code>	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
<code>timestamp</code>	(integer) Limit by time, only history items after the given time, e.g., 20180201 for revisions since Feb 1st, 2018. Any length of timestamp is accepted, upto 14 digits, e.g., 2018, 201802, 20180201063011, etc.

Value

A list of revisions, including user and comment

Examples

```
{
  getPathwayHistory('WP554', 20180201)
}
```

`getPathwayIdsByCurationTag` *Get Pathway WPIDs by Curation Tag*

Description

Retrieve pathway WPIDs for every pathway with a given curation tag.

Usage

```
getPathwayIdsByCurationTag(tag)
```

Arguments

<code>tag</code>	(character) Official name of curation tag, e.g., "Curation:FeaturedPathway"
------------------	---

Value

A list of pathway WPIDs

Examples

```
{
  getPathwayIdsByCurationTag('Curation:FeaturedPathway')
}
```

```
getPathwayIdsByOntologyTerm  
Get Pathway WPIDs by Ontology Term
```

Description

Retrieve pathway WPIDs for every pathway with a given ontology term.

Usage

```
getPathwayIdsByOntologyTerm(term)
```

Arguments

term	(character) Official name of ontology term, e.g., "PW:0000045"
------	--

Value

A list of pathway WPIDs

Examples

```
{  
  getPathwayIdsByOntologyTerm('PW:0000045')  
}
```

```
getPathwayIdsByParentOntologyTerm  
Get Pathway WPIDs by Parent Ontology Term
```

Description

Retrieve pathway WPIDs for every pathway with a child term of given ontology term

Usage

```
getPathwayIdsByParentOntologyTerm(term)
```

Arguments

term	(character) Official name of ontology term, e.g., "PW:0000045"
------	--

Value

A list of pathway WPIDs

Examples

```
{  
  getPathwayIdsByParentOntologyTerm('PW:0000045')  
}
```

getPathwayInfo	<i>Get Pathway Info</i>
----------------	-------------------------

Description

Retrieve information for a specific pathway

Usage

```
getPathwayInfo(pathway)
```

Arguments

pathway	WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
---------	--

Value

A dataframe of pathway WPID, URL, name, species and latest revision

Examples

```
{
  getPathwayInfo('WP554')
}
```

getPathwaysByCurationTag	<i>Get Pathways by Curation Tag</i>
--------------------------	-------------------------------------

Description

Retrieve pathway information for every pathway with a given curation tag.

Usage

```
getPathwaysByCurationTag(tag)
```

Arguments

tag	(character) Official name of curation tag, e.g., "Curation:FeaturedPathway"
-----	---

Value

A list of pathway information, including WPID, url, name, species and revision

Examples

```
{
  getPathwaysByCurationTag('Curation:FeaturedPathway')
}
```

```
getPathwaysByOntologyTerm
```

Get Pathways by Ontology Term

Description

Retrieve pathway information for every pathway with a given ontology term.

Usage

```
getPathwaysByOntologyTerm(term)
```

Arguments

term	(character) Official name of ontology term, e.g., "PW:0000045"
------	--

Value

A list of pathway information, including WPID, url, name, species and revision

Examples

```
{  
  getPathwaysByOntologyTerm('PW:0000045')  
}
```

```
getPathwaysByParentOntologyTerm
```

Get Pathways by Parent Ontology Term

Description

Retrieve pathway information for every pathway with a child term of given ontology term.

Usage

```
getPathwaysByParentOntologyTerm(term)
```

Arguments

term	(character) Official name of ontology term, e.g., "PW:0000045"
------	--

Value

A list of pathway information, including WPID, url, name, species and revision

Examples

```
{  
  getPathwaysByParentOntologyTerm('PW:0000045')  
}
```

getRecentChanges *Get Recent Changes*

Description

Retrieve recent changes to pathways at WikiPathways.

Usage

```
getRecentChanges(timestamp)
```

Arguments

timestamp (14 digits, YYYYMMDDhhmmss) Limit by time, only history items after the given time, e.g., 20180201000000 for changes since Feb 1st, 2018.

Value

A list of changes, including pathway WPID, name, url, species and revision

Examples

```
{
  getRecentChanges('20180201000000')
}
```

getRecentChangesIds *Get WPIDs of Recent Changes*

Description

Retrieve WPIDs of recently changed pathways at WikiPathways.

Usage

```
getRecentChangesIds(timestamp)
```

Arguments

timestamp (14 digits, YYYYMMDDhhmmss) Limit by time, only history items after the given time, e.g., 20180201000000 for changes since Feb 1st, 2018.

Value

A list of WPIDs

Examples

```
{
  getRecentChangesIds('20180201000000')
}
```

getRecentChangesNames *Get Pathway Names of Recent Changes*

Description

Retrieve names of recently changed pathways at WikiPathways.

Usage

```
getRecentChangesNames(timestamp)
```

Arguments

timestamp (14 digits, YYYYMMDDhhmmss) Limit by time, only history items after the given time, e.g., 20180201000000 for changes since Feb 1st, 2018.

Value

A list of pathway names. Note: pathway deletions will be listed as blank names.

Examples

```
{
  getRecentChangesNames('20180201000000')
}
```

getXrefList *Get Xref List*

Description

Retrieve the Xref identifiers for a specific pathway in a particular system code

Usage

```
getXrefList(pathway, systemCode)
```

Arguments

pathway WikiPathways identifier (WPID) for the pathway to download, e.g. WP4
systemCode (character) The BridgeDb code associated with the data source or system, e.g., En (Ensembl), L (Entrez), Ch (HMDB), etc. See column two of <https://github.com/bridgedb/BridgeDB>

Value

A list of Xrefs identifiers

Examples

```
{
  xrefs = getXrefList("WP2338", "L")
}
```

listOrganisms *List Organisms*

Description

Retrieve the list of organisms supported by WikiPathways

Usage

```
listOrganisms()
```

Value

A list of organisms

Examples

```
{
  listOrganisms()
}
```

listPathwayIds *List Pathway WPIDs*

Description

Retrieve list of pathway WPIDs per species.

Usage

```
listPathwayIds(organism = "")
```

Arguments

organism (character, optional) A particular species. See [listOrganisms](#). Default is all species.

Details

Basically returns a subset of [listPathways](#) result

Value

A list of WPIDs

See Also

[listPathways](#)

Examples

```
{  
  listPathwayIds('Mus musculus')  
}
```

listPathwayNames *List Pathway Names*

Description

Retrieve list of pathway names per species.

Usage

```
listPathwayNames(organism = "")
```

Arguments

organism (character, optional) A particular species. See [listOrganisms](#). Default is all species.

Details

Basically returns a subset of [listPathways](#) result

Value

A list of names

See Also

[listPathways](#)

Examples

```
{  
  listPathwayNames('Mus musculus')  
}
```

`listPathways`*List Pathways*

Description

Retrieve list of pathways per species, including WPID, name, species, URL and latest revision number.

Usage

```
listPathways(organism = "")
```

Arguments

`organism` (character, optional) A particular species. See [listOrganisms](#). Default is all species.

Value

A dataframe of pathway information

Examples

```
{  
  listPathways('Mus musculus')  
}
```

`listPathwayUrls`*List Pathway URLs*

Description

Retrieve list of pathway URLs per species.

Usage

```
listPathwayUrls(organism = "")
```

Arguments

`organism` (character, optional) A particular species. See [listOrganisms](#). Default is all species.

Details

Basically returns a subset of [listPathways](#) result

Value

A list of URLs

See Also`listPathways`**Examples**

```
{  
  listPathwayUrls('Mus musculus')  
}
```

`readPathwayGMT`*Read Pathway GMT File*

Description

Reads a WikiPathways GMT file to produce a data frame of pathway-gene associations useful in enrichment analyses and other applications.

Usage`readPathwayGMT(file)`**Arguments**

`file` Path to GMT file

Details

The returned data frame includes pathway name, version, identifier, and organism. The gene content is provided as NCBI Entrez Gene identifiers. The input file can be retrieved by using `downloadPathwayArchive(organism="Homo sapiens", format="gmt")`.

Value

Data frame of pathway-gene associations

References

Adapted from the generic GMT reader provided by clusterProfiler, <https://github.com/YuLab-SMU/clusterProfiler/blob/master/R/GMT.R>

See Also`downloadPathwayArchive`**Examples**`readPathwayGMT(gmt.file)`

wikopathwaysAPI *Open Swagger docs for WikiPathways API*

Description

Opens swagger docs in default browser for available API calls.

Usage

```
wikopathwaysAPI(base.url = .baseUrl)
```

Arguments

base.url (optional) Ignore unless you need to specify a custom domain.

Value

New tab in default browser

Examples

```
{
  wikopathwaysAPI()
}
```

wikopathwaysGET *WikiPathways GET*

Description

Constructs the query, makes GET call and processes the result

Usage

```
wikopathwaysGET(
  operation,
  parameters = NULL,
  format = c("json", "xml", "html", "jpg", "pdf", "dump"),
  base.url = .baseUrl
)
```

Arguments

operation	A character string to be converted to the query namespace
parameters	A named list of values to be converted to query parameters
format	(character) The format of the return, e.g., json (default), xml, html, jpg, pdf, dump
base.url	(optional) Ignore unless you need to specify a custom domain.

Value

query result content

Examples

```
{  
wikipathwaysGET('listOrganisms')  
}
```

Index

downloadPathwayArchive, 2
findPathwayIdsByLiterature, 3
findPathwayIdsByText, 4
findPathwayIdsByXref, 5
findPathwayNamesByLiterature, 5
findPathwayNamesByText, 6
findPathwayNamesByXref, 7
findPathwaysByLiterature, 7
findPathwaysByText, 8
findPathwaysByXref, 9
findPathwayUrlsByLiterature, 9
findPathwayUrlsByText, 10
findPathwayUrlsByXref, 11

getColoredPathway, 11
getCurationTagNames, 12
getCurationTags, 13
getEveryCurationTag, 13
getOntologyTermIds, 14
getOntologyTermNames, 14
getOntologyTerms, 15
getPathway, 15
getPathwayHistory, 16
getPathwayIdsByCurationTag, 16
getPathwayIdsByOntologyTerm, 17
getPathwayIdsByParentOntologyTerm, 17
getPathwayInfo, 18
getPathwaysByCurationTag, 18
getPathwaysByOntologyTerm, 19
getPathwaysByParentOntologyTerm, 19
getRecentChanges, 20
getRecentChangesIds, 20
getRecentChangesNames, 21
getXrefList, 21

listOrganisms, 3, 22, 22, 23, 24
listPathwayIds, 22
listPathwayNames, 23
listPathways, 22–24, 24
listPathwayUrls, 24

readPathwayGMT, 25

wikopathwaysAPI, 26