

Package ‘RegParallel’

October 12, 2020

Type Package

Title Standard regression functions in R enabled for parallel processing over large data-frames

Version 1.6.0

Maintainer Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Description In many analyses, a large amount of variables have to be tested independently against the trait/endpoint of interest, and also adjusted for covariates and confounding factors at the same time. The major bottleneck in these is the amount of time that it takes to complete these analyses. With RegParallel, a large number of tests can be performed simultaneously. On a 12-core system, 144 variables can be tested simultaneously, with 1000s of variables processed in a matter of seconds via 'nested' parallel processing. Works for logistic regression, linear regression, conditional logistic regression, Cox proportional hazards and survival models, and Bayesian logistic regression.

License GPL-3

Depends doParallel, foreach, parallel, iterators, data.table, stringr, survival, arm, stats, utils, methods

Imports

Suggests RUnit, BiocGenerics, knitr, DESeq2, airway, magrittr, Biobase, GEOquery, biomaRt, survminer

URL <https://github.com/kevinblighe/RegParallel>

biocViews DiseaseModel

VignetteBuilder knitr

git_url https://git.bioconductor.org/packages/RegParallel

git_branch RELEASE_3_11

git_last_commit 4853a92

git_last_commit_date 2020-04-27

Date/Publication 2020-10-12

Author Kevin Blighe [aut, cre],
Jessica Lasky-Su [aut, ctb]

R topics documented:

RegParallel-package	2
bayesglmParallel	2
clogitParallel	4
coxphParallel	6
glmParallel	9
lmParallel	11
RegParallel	13

Index	20
--------------	-----------

RegParallel-package	<i>RegParallel: Standard regression functions in R enabled for parallel processing over large data-frames.</i>
---------------------	--

Description

In many analyses, a large amount of variables have to be tested independently against the trait/endpoint of interest, and also adjusted for covariates and confounding factors at the same time. The major bottleneck in these is the amount of time that it takes to complete these analyses. With RegParallel, a large number of tests can be performed simultaneously. On a 12-core system, 144 variables can be tested simultaneously, with 1000s of variables processed in a matter of seconds via 'nested' parallel processing. Works for logistic regression, linear regression, conditional logistic regression, Cox proportional hazards and survival models, and Bayesian logistic regression.

bayesglmParallel	<i>Standard regression functions in R enabled for parallel processing over large data-frames - Bayesian logistic regression</i>
------------------	---

Description

This is a non-user function that is managed by RegParallel, the primary function.

Usage

```
bayesglmParallel(
  data,
  formula.list,
  FUN,
  variables,
  terms,
  startIndex,
  blocksize,
  blocks,
  APPLYFUN,
  conlevel,
  excludeTerms,
  excludeIntercept)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula.list</code>	A list containing formulae that can be coerced to formula class via <code>as.formula()</code> . REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: <code>function(formula, data) glm(formula = formula, family = binomial, data = data)</code> . REQUIRED.
<code>variables</code>	Vector of variable names in data to be tested independently. Each variable will have its own formula in <code>formula.list</code> . REQUIRED.
<code>terms</code>	Vector of terms used in the formulae in <code>formula.list</code> , excluding the primary variable of interest. REQUIRED.
<code>startIndex</code>	Starting column index in data object from which processing can commence. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. REQUIRED.
<code>blocks</code>	Total number of blocks required to complete analysis. REQUIRED.
<code>APPLYFUN</code>	The apply function to be used within each block during processing. Will be one of: ' <code>mclapply(...)</code> ', system=linux/mac and <code>nestedParallel=TRUE</code> ; ' <code>parLapply(cl, ...)</code> ', system=windows and <code>nestedParallel=TRUE</code> ; ' <code>lapply(...)</code> ', <code>nestedParallel=FALSE</code> . REQUIRED.
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. REQUIRED.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. REQUIRED.
<code>excludeIntercept</code>	Remove intercept terms from the final output. REQUIRED.

Details

This is a non-user function that is managed by `RegParallel`, the primary function.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```
options(scipen=10)
options(digits=6)

col <- 20000
row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))
```

```

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

data <- modelling[,1:5000]
variables <- colnames(data)[4:ncol(data)]
res6 <- RegParallel(
  data = data,
  formula = 'as.numeric(factor(cell)) ~ [*]:dosage',
  FUN = function(formula, data)
    bayesglm(formula = formula,
              data = data,
              prior.mean = 2),
  FUNtype = 'bayesglm',
  variables = variables,
  blocksize = 500,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "none",
  conflevel = 99,
  excludeTerms = NULL,
  excludeIntercept = FALSE
)

# spot checks
m <- bayesglm(formula = as.numeric(factor(cell)) ~ gene1645:dosage, data = data, prior.mean = 2)
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res6[which(res6$Variable == 'gene1645'),]

m <- bayesglm(formula = as.numeric(factor(cell)) ~ gene3664:dosage, data = data, prior.mean = 2)
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res6[which(res6$Variable == 'gene3664'),]
```

clogitParallel

Standard regression functions in R enabled for parallel processing over large data-frames - conditional logistic regression.

Description

This is a non-user function that is managed by RegParallel, the primary function.

Usage

```
clogitParallel(
  data,
  formula.list,
  FUN,
  variables,
```

```
terms,
startIndex,
blocksize,
blocks,
APPLYFUN,
conflevel,
excludeTerms)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula.list</code>	A list containing formulae that can be coerced to formula class via <code>as.formula()</code> . REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: <code>function(formula, data) glm(formula = formula, family = binomial, data = data)</code> . REQUIRED.
<code>variables</code>	Vector of variable names in <code>data</code> to be tested independently. Each variable will have its own formula in <code>formula.list</code> . REQUIRED.
<code>terms</code>	Vector of terms used in the formulae in <code>formula.list</code> , excluding the primary variable of interest. REQUIRED.
<code>startIndex</code>	Starting column index in <code>data</code> object from which processing can commence. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. REQUIRED.
<code>blocks</code>	Total number of blocks required to complete analysis. REQUIRED.
<code>APPLYFUN</code>	The apply function to be used within each block during processing. Will be one of: ' <code>mclapply(...)</code> ', system=linux/mac and <code>nestedParallel=TRUE</code> ; ' <code>parLapply(cl, ...)</code> ', system=windows and <code>nestedParallel=TRUE</code> ; ' <code>lapply(...)</code> ', <code>nestedParallel=FALSE</code> . REQUIRED.
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. REQUIRED.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. REQUIRED.

Details

This is a non-user function that is managed by `RegParallel`, the primary function.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```
options(scipen=10)
options(digits=6)

col <- 20000
```

```

row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res5 <- RegParallel(
  data = data,
  formula = 'as.integer(factor(group)) ~ [*] * strata(cell) + dosage',
  FUN = function(formula, data)
    clogit(formula = formula,
           data = data,
           ties = 'breslow',
           singular.ok = TRUE),
  FUNtype = 'clogit',
  variables = variables,
  blocksize = 200,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "none",
  conflevel = 50,
  excludeTerms = 'non-existent term',
  excludeIntercept = FALSE
)
# spot checks
m <- clogit(formula = as.integer(factor(group)) ~ gene145 * strata(cell) + dosage, data = data, ties = 'breslow')
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.5)))
res5[which(res5$Variable == 'gene145'),]

m <- clogit(formula = as.integer(factor(group)) ~ gene34 * strata(cell) + dosage, data = data, ties = 'breslow')
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.5)))
res5[which(res5$Variable == 'gene34'),]

```

Description

This is a non-user function that is managed by `RegParallel`, the primary function.

Usage

```
coxphParallel(
  data,
  formula.list,
  FUN,
  variables,
  terms,
  startIndex,
  blocksize,
  blocks,
  APPLYFUN,
  conflevel,
  excludeTerms)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula.list</code>	A list containing formulae that can be coerced to formula class via <code>as.formula()</code> . REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: <code>function(formula, data) glm(formula = formula, family = binomial, data = data)</code> . REQUIRED.
<code>variables</code>	Vector of variable names in data to be tested independently. Each variable will have its own formula in <code>formula.list</code> . REQUIRED.
<code>terms</code>	Vector of terms used in the formulae in <code>formula.list</code> , excluding the primary variable of interest. REQUIRED.
<code>startIndex</code>	Starting column index in data object from which processing can commence. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. REQUIRED.
<code>blocks</code>	Total number of blocks required to complete analysis. REQUIRED.
<code>APPLYFUN</code>	The apply function to be used within each block during processing. Will be one of: ' <code>mclapply(...)</code> ', system=linux/mac and <code>nestedParallel=TRUE</code> ; ' <code>parLapply(cl, ...)</code> ', system=windows and <code>nestedParallel=TRUE</code> ; ' <code>lapply(...)</code> ', <code>nestedParallel=FALSE</code> . REQUIRED.
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. REQUIRED.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. REQUIRED.

Details

This is a non-user function that is managed by `RegParallel`, the primary function.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```

options(scipen=10)
options(digits=6)

col <- 20000
row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

require(survival)
data <- modelling[,1:800]
variables <- colnames(data)[4:ncol(data)]
data$time <- c(100,200,400,300,200,250,600,1000,886,450,
  c(100,200,400,300,200,250,600,1000,886,450)*1.5)
data$alive <- c(0,0,0,0,0,0,1,1,1,0,0,1,1,1,1,1,1,1,1,1)
res4 <- RegParallel(
  data = data,
  formula = 'Surv(time, as.integer(alive)) ~ group * [*] + cell',
  FUN = function(formula, data)
    coxph(formula = formula,
      data = data,
      ties = 'breslow',
      singular.ok = TRUE),
  FUNtype = 'coxph',
  variables = variables,
  blocksize = 399,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "none",
  conflevel = 97.5,
  excludeTerms = c('group', 'cell'),
  excludeIntercept = FALSE
)
# spot checks
m <- coxph(formula = Surv(time, as.integer(factor(alive))) ~ group * gene12 + cell, data = data, ties = 'breslow')
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.975)))
res4[which(res4$Variable == 'gene12'),]

m <- coxph(formula = Surv(time, as.integer(factor(alive))) ~ group * gene267 + cell, data = data, ties = 'breslow')
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.975)))
res4[which(res4$Variable == 'gene267'),]
```

<code>glmParallel</code>	<i>Standard regression functions in R enabled for parallel processing over large data-frames - generalised linear model</i>
--------------------------	---

Description

This is a non-user function that is managed by RegParallel, the primary function.

Usage

```
glmParallel(
  data,
  formula.list,
  FUN,
  variables,
  terms,
  startIndex,
  blocksize,
  blocks,
  APPLYFUN,
  conflevel,
  excludeTerms,
  excludeIntercept)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula.list</code>	A list containing formulae that can be coerced to formula class via as.formula(). REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: function(formula, data) glm(formula = formula, family = binomial, data = data). REQUIRED.
<code>variables</code>	Vector of variable names in data to be tested independently. Each variable will have its own formula in formula.list. REQUIRED.
<code>terms</code>	Vector of terms used in the formulae in formula.list, excluding the primary variable of interest. REQUIRED.
<code>startIndex</code>	Starting column index in data object from which processing can commence. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. REQUIRED.
<code>blocks</code>	Total number of blocks required to complete analysis. REQUIRED.
<code>APPLYFUN</code>	The apply function to be used within each block during processing. Will be one of: 'mclapply(...)', system=linux/mac and nestedParallel=TRUE; 'parLapply(cl, ...)', system=windows and nestedParallel=TRUE; 'lapply(...)', nestedParallel=FALSE. REQUIRED.
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. REQUIRED.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. REQUIRED.
<code>excludeIntercept</code>	Remove intercept terms from the final output. REQUIRED.

Details

This is a non-user function that is managed by `RegParallel`, the primary function.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```
options(scipen=10)
options(digits=6)

col <- 20000
row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

data <- modelling[,1:2000]
variables <- colnames(data)[4:ncol(data)]
res1 <- RegParallel(
  data = data,
  formula = 'factor(group) ~ [*] + (cell:dosage) ^ 2',
  FUN = function(formula, data)
    glm(formula = formula,
        data = data,
        family = binomial(link = 'logit'),
        method = 'glm.fit'),
  FUNtype = 'glm',
  variables = variables,
  blocksize = 700,
  cores = 2,
  nestedParallel = TRUE,
  p.adjust = "none",
  conflevel = 99,
  excludeTerms = NULL,
  excludeIntercept = TRUE
)
# spot checks
m <- glm(factor(group) ~ gene265 + (cell:dosage) ^ 2, data=data, family=binomial)
summary(m)$coefficients
```

```

exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res1[which(res1$Variable == 'gene265'),]

m <- glm(factor(group) ~ gene1688 + (cell:dosage) ^ 2, data=data, family=binomial)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res1[which(res1$Variable == 'gene1688'),]

####

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res2 <- RegParallel(
  data = data,
  formula = '[*] ~ cell:dosage',
  FUN = function(formula, data)
    glm(formula = formula,
        data = data,
        family = gaussian,
        method = 'glm.fit'),
  FUNtype = 'glm',
  variables = variables,
  blocksize = 496,
  cores = 2,
  nestedParallel = TRUE,
  p.adjust = "none",
  conflevel = 90,
  excludeTerms = NULL,
  excludeIntercept = FALSE
)
# spot checks
m <- glm(gene29 ~ cell:dosage, data=data, family=gaussian)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.90)))
res2[which(res2$Variable == 'gene29'),]

```

lmParallel

Standard regression functions in R enabled for parallel processing over large data-frames - linear model.

Description

This is a non-user function that is managed by `RegParallel`, the primary function.

Usage

```
lmParallel(
  data,
  formula.list,
  FUN,
  variables,
```

```
terms,
startIndex,
blocksize,
blocks,
APPLYFUN,
conflevel,
excludeTerms,
excludeIntercept)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula.list</code>	A list containing formulae that can be coerced to formula class via <code>as.formula()</code> . REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: <code>function(formula, data) glm(formula = formula, family=binomial, data = data)</code> . REQUIRED.
<code>variables</code>	Vector of variable names in data to be tested independently. Each variable will have its own formula in <code>formula.list</code> . REQUIRED.
<code>terms</code>	Vector of terms used in the formulae in <code>formula.list</code> , excluding the primary variable of interest. REQUIRED.
<code>startIndex</code>	Starting column index in data object from which processing can commence. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. REQUIRED.
<code>blocks</code>	Total number of blocks required to complete analysis. REQUIRED.
<code>APPLYFUN</code>	The apply function to be used within each block during processing. Will be one of: ' <code>mclapply(...)</code> ', system=linux/mac and <code>nestedParallel=TRUE</code> ; ' <code>parLapply(cl, ...)</code> ', system=windows and <code>nestedParallel=TRUE</code> ; ' <code>lapply(...)</code> ', <code>nestedParallel=FALSE</code> . REQUIRED.
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. REQUIRED.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. REQUIRED.
<code>excludeIntercept</code>	Remove intercept terms from the final output. REQUIRED.

Details

This is a non-user function that is managed by `RegParallel`, the primary function.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```

options(scipen=10)
options(digits=6)

col <- 20000
row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res3 <- RegParallel(
  data = data,
  formula = 'as.numeric([*]) ~ dosage ^ 3',
  FUN = function(formula, data)
    lm(formula = formula,
        data = data),
  FUNtype = 'lm',
  variables = variables,
  blocksize = 200,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "none",
  conflevel = 99.999,
  excludeTerms = NULL,
  excludeIntercept = FALSE
)

# spot checks
m <- lm(as.numeric(gene454) ~ dosage ^ 3, data=data)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99999)))
res3[which(res3$Variable == 'gene454'),]

```

RegParallel

Standard regression functions in R enabled for parallel processing over large data-frames

Description

In many analyses, a large amount of variables have to be tested independently against the trait/endpoint of interest, and also adjusted for covariates and confounding factors at the same time. The major bottleneck in these is the amount of time that it takes to complete these analyses. With RegParallel,

a large number of tests can be performed simultaneously. On a 12-core system, 144 variables can be tested simultaneously, with 1000s of variables processed in a matter of seconds via 'nested' parallel processing. Works for logistic regression, linear regression, conditional logistic regression, Cox proportional hazards and survival models, and Bayesian logistic regression.

Usage

```
RegParallel(
  data,
  formula,
  FUN,
  FUNtype,
  variables,
  blocksize = 500,
  cores = 3,
  nestedParallel = FALSE,
  p.adjust = 'none',
  conflevel = 95,
  excludeTerms = NULL,
  excludeIntercept = TRUE)
```

Arguments

<code>data</code>	A data-frame that contains all model terms to be tested. Variables that have all zeros will, automatically, be removed. REQUIRED.
<code>formula</code>	A valid formula. Excluding the '[*]' term, which is reserved for RegParallel and indicates the position in the formula for the variable of interest, must pass <code>as.formula()</code> check. REQUIRED.
<code>FUN</code>	Regression function. Must be of form, for example: <code>function(formula, data) glm(formula = formula, family=binomial, data = data)</code> . REQUIRED.
<code>FUNtype</code>	Regression function type. Must be one of 'glm', 'lm', 'coxph', 'clogit', 'bayesglm', or 'glm.nb'. REQUIRED.
<code>variables</code>	Vector of variable names in data to be tested independently. Each variable will take the place of '[*]' in the supplied formula. REQUIRED.
<code>blocksize</code>	Number of variables to test in each foreach loop. DEFAULT = 500. OPTIONAL.
<code>cores</code>	CPU cores / threads. DEFAULT = 3. OPTIONAL.
<code>nestedParallel</code>	In RegParallel, parallelisation initially occurs at the block level, ie., multiple blocks of models are processed in parallel. If <code>nestedParallel</code> is enabled, a second level of parallelisation occurs within each block in addition. Warning! - this doubles the usage of cores. DEFAULT = FALSE. OPTIONAL.
<code>p.adjust</code>	Method for adjusting p-values for false discovery rate. Must be one of 'holm', 'hochberg', 'hommel', 'bonferroni', 'BH', 'BY', 'fdr', 'none'. See <code>?p.adjust</code> for further details. DEFAULT = 'none'. OPTIONAL
<code>conflevel</code>	Confidence level for calculating odds or hazard ratios. DEFAULT = 95. OPTIONAL.
<code>excludeTerms</code>	Remove these terms from the final output. These will simply be grepped out. DEFAULT = NULL. OPTIONAL.
<code>excludeIntercept</code>	Remove intercept terms from the final output. DEFAULT = TRUE. OPTIONAL.

Details

In many analyses, a large amount of variables have to be tested independently against the trait/endpoint of interest, and also adjusted for covariates and confounding factors at the same time. The major bottleneck in these is the amount of time that it takes to complete these analyses. With RegParallel, a large number of tests can be performed simultaneously. On a 12-core system, 144 variables can be tested simultaneously, with 1000s of variables processed in a matter of seconds via 'nested' parallel processing. Works for logistic regression, linear regression, conditional logistic regression, Cox proportional hazards and survival models, and Bayesian logistic regression.

Value

A `data.table` object.

Author(s)

Kevin Blighe <kevin@clinicalbioinformatics.co.uk>

Examples

```
options(scipen=10)
options(digits=6)

col <- 20000
row <- 20
mat <- matrix(
  rexp(col*row, rate = .1),
  ncol = col)
colnames(mat) <- paste0('gene', 1:ncol(mat))
rownames(mat) <- paste0('sample', 1:nrow(mat))

modelling <- data.frame(
  cell = rep(c('B', 'T'), nrow(mat) / 2),
  group = c(rep(c('treatment'), nrow(mat) / 2), rep(c('control'), nrow(mat) / 2)),
  dosage = t(data.frame(matrix(rexp(row, rate = 1), ncol = row))),
  mat,
  row.names = rownames(mat))

data <- modelling[,1:2000]
variables <- colnames(data)[4:ncol(data)]
res1 <- RegParallel(
  data = data,
  formula = 'factor(group) ~ [*] + (cell:dosage) ^ 2',
  FUN = function(formula, data)
    glm(formula = formula,
        data = data,
        family = binomial(link = 'logit'),
        method = 'glm.fit'),
  FUNtype = 'glm',
  variables = variables,
  blocksize = 700,
  cores = 2,
  nestedParallel = TRUE,
  #p.adjust = "bonferroni",
  conflevel = 99,
  excludeTerms = NULL,
```

```

    excludeIntercept = TRUE
  )

# spot checks
m <- glm(factor(group) ~ gene265 + (cell:dosage) ^ 2, data=data, family=binomial)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res1[which(res1$Variable == 'gene265'),]

m <- glm(factor(group) ~ gene1688 + (cell:dosage) ^ 2, data=data, family=binomial)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res1[which(res1$Variable == 'gene1688'),]

###

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res2 <- RegParallel(
  data = data,
  formula = '[*] ~ cell:dosage',
  FUN = function(formula, data)
    glm(formula = formula,
        data = data,
        family = gaussian,
        method = 'glm.fit'),
  FUNtype = 'glm',
  variables = variables,
  blocksize = 496,
  cores = 2,
  nestedParallel = TRUE,
  p.adjust = "none",
  conflevel = 90,
  excludeTerms = NULL,
  excludeIntercept = FALSE
)

# spot checks
m <- glm(gene29 ~ cell:dosage, data=data, family=gaussian)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.90)))
res2[which(res2$Variable == 'gene29'),]

###

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res3 <- RegParallel(
  data = data,
  formula = 'as.numeric([*]) ~ dosage ^ 3',
  FUN = function(formula, data)
    lm(formula = formula,
        data = data),

```

```

    FUNtype = 'lm',
    variables = variables,
    blocksize = 200,
    cores = 2,
    nestedParallel = FALSE,
    p.adjust = "holm",
    conflevel = 99.999,
    excludeTerms = NULL,
    excludeIntercept = FALSE
  )

# spot checks
m <- lm(as.numeric(gene454) ~ dosage ^ 3, data=data)
summary(m)$coefficients
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99999)))
res3[which(res3$Variable == 'gene454'),]

####

require(survival)
data <- modelling[,1:800]
variables <- colnames(data)[4:ncol(data)]
data$time <- c(100,200,400,300,200,250,600,1000,886,450,
  c(100,200,400,300,200,250,600,1000,886,450)*1.5)
data$alive <- c(0,0,0,0,0,0,0,1,1,1,0,0,1,1,1,1,1,1,1)
res4 <- RegParallel(
  data = data,
  formula = 'Surv(time, as.integer(alive)) ~ group * [*] + cell',
  FUN = function(formula, data)
    coxph(formula = formula,
      data = data,
      ties = 'breslow',
      singular.ok = TRUE),
  FUNtype = 'coxph',
  variables = variables,
  blocksize = 399,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "hommel",
  conflevel = 97.5,
  excludeTerms = c('group', 'cell'),
  excludeIntercept = FALSE
)

# spot checks
m <- coxph(formula = Surv(time, as.integer(factor(alive))) ~ group * gene12 + cell, data = data, ties = 'breslow')
summary(m)
exp(cbind("Hazard ratio" = coef(m), confint.default(m, level = 0.975)))
res4[which(res4$Variable == 'gene12'),]

m <- coxph(formula = Surv(time, as.integer(factor(alive))) ~ group * gene267 + cell, data = data, ties = 'breslow')
summary(m)
exp(cbind("Hazard ratio" = coef(m), confint.default(m, level = 0.975)))
res4[which(res4$Variable == 'gene267'),]

```

```

####

data <- modelling[,1:500]
variables <- colnames(data)[4:ncol(data)]
res5 <- RegParallel(
  data = data,
  formula = 'as.integer(factor(group)) ~ [*] * strata(cell) + dosage',
  FUN = function(formula, data)
    clogit(formula = formula,
           data = data,
           ties = 'breslow',
           singular.ok = TRUE),
  FUNtype = 'clogit',
  variables = variables,
  blocksize = 200,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "fdr",
  conflevel = 50,
  excludeTerms = 'non-existent term',
  excludeIntercept = FALSE
)
# spot checks
m <- clogit(formula = as.integer(factor(group)) ~ gene145 * strata(cell) + dosage, data = data, ties = 'breslow')
summary(m)
exp(cbind("Hazards ratio" = coef(m), confint.default(m, level = 0.5)))
res5[which(res5$Variable == 'gene145'),]

m <- clogit(formula = as.integer(factor(group)) ~ gene34 * strata(cell) + dosage, data = data, ties = 'breslow')
summary(m)
exp(cbind("Hazards ratio" = coef(m), confint.default(m, level = 0.5)))
res5[which(res5$Variable == 'gene34'),]

####

data <- modelling[,1:5000]
variables <- colnames(data)[4:ncol(data)]
res6 <- RegParallel(
  data = data,
  formula = 'as.numeric(factor(cell)) ~ [*]:dosage',
  FUN = function(formula, data)
    bayesglm(formula = formula,
              data = data,
              prior.mean = 2),
  FUNtype = 'bayesglm',
  variables = variables,
  blocksize = 500,
  cores = 2,
  nestedParallel = FALSE,
  p.adjust = "fdr",
  conflevel = 99,
  excludeTerms = NULL,
)

```

```
    excludeIntercept = FALSE
  )

# spot checks
m <- bayesglm(formula = as.numeric(factor(cell)) ~ gene1645:dosage, data = data, prior.mean = 2)
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res6[which(res6$Variable == 'gene1645'),]

m <- bayesglm(formula = as.numeric(factor(cell)) ~ gene3664:dosage, data = data, prior.mean = 2)
summary(m)
exp(cbind("Odds ratio" = coef(m), confint.default(m, level = 0.99)))
res6[which(res6$Variable == 'gene3664'),]
```

Index

bayesglmParallel, 2
clogitParallel, 4
coxphParallel, 6
data.table, 3, 5, 7, 10, 12, 15
glmParallel, 9
lmParallel, 11
RegParallel, 13
RegParallel-package, 2