

Package ‘SEtools’

October 14, 2021

Type Package

Title SEtools: tools for working with SummarizedExperiment

Version 1.6.0

Depends R (>= 4.0)

Description This includes a set of tools for working with the SummarizedExperiment class, including merging, melting, aggregation and plotting functions. In particular, SEtools offers a simple interface for plotting complex heatmaps from SE objects.

Imports S4Vectors, SummarizedExperiment, data.table, seriation, ComplexHeatmap, circlize, methods, BiocParallel, randomcoloR, edgeR, openxlsx, sva, stats, DESeq2, Matrix, grid

Suggests BiocStyle, knitr, rmarkdown, ggplot2, pheatmap

biocViews GeneExpression, Visualization

VignetteBuilder knitr

License GPL

Encoding UTF-8

RoxygenNote 7.1.1

BugReports <https://github.com/plger/SEtools>

git_url <https://git.bioconductor.org/packages/SEtools>

git_branch RELEASE_3_13

git_last_commit 486c252

git_last_commit_date 2021-05-19

Date/Publication 2021-10-14

Author Pierre-Luc Germain [cre, aut] (<<https://orcid.org/0000-0003-3418-4218>>)

Maintainer Pierre-Luc Germain <pierre-luc.germain@hest.ethz.ch>

R topics documented:

aggSE	2
castSE	3

crossHm	4
data	6
flattenPB	6
getBreaks	7
log2FC	7
meltSE	8
mergeSEs	9
qualitativeColors	10
resetAllSEtoolsOptions	11
scale2	11
SE-heatmap	12
se2xls	14
sortRows	15
svacor	16

Index**17****aggSE***aggSE***Description**

Aggregates the rows of a ‘SummarizedExperiment’.

Usage

```
aggSE(x, by, assayFun = NULL, rowDatFuns = list())
```

Arguments

- x An object of class ‘SummarizedExperiment’
- by Vector by which to aggregate, or column of ‘rowData(x)’
- assayFun Function by which to aggregate, or a list of such functions (or vector of function names) of the same length as there are assays. If NULL will attempt to use an appropriate function (and notify the functions used), typically the mean.
- rowDatFuns A named list providing functions by which to aggregate each rowData columns. If a given column has no specified function, the default will be used, i.e. logical are transformed into a proportion, numerics are aggregated by median, and unique factors/characters are pasted together. Use ‘rowDataFuns=NULL’ to discard rowData.

Value

An object of class ‘SummarizedExperiment’

Examples

```
library(SummarizedExperiment)
data("SE", package="S E tools")
# arbitrary IDs for example aggregation:
rowData(SE)$otherID <- rep(LETTERS[1:10], each=10)
SE <- aggSE(SE, "otherID")
```

castSE

castSE

Description

Casts a data.frame as a [SummarizedExperiment-class](#)

Usage

```
castSE(
  x,
  rowNames = NULL,
  colNames = NULL,
  assayNames = NULL,
  colData = NULL,
  rowData = NULL,
  sparse = FALSE
)
```

Arguments

x	A data.frame
rowNames	Column of ‘x’ containing the row.names (if omitted, will build from ‘rowData’)
colNames	Column of ‘x’ containing the column names (if omitted, will build from ‘colData’)
assayNames	Columns of ‘x’ to turn into assays
colData	Columns of ‘x’ to use as colData
rowData	Columns of ‘x’ to use as rowData
sparse	Logical, whether to keep the assays sparse.

Value

A [SummarizedExperiment-class](#)

Examples

```
d <- data.frame(transcript=rep(LETTERS[1:10],each=2), gene=rep(LETTERS[1:5],each=4),
                 count=rpois(20, 10), sample=letters[1:2])
head(d)
castSE(d, rowData=c("transcript", "gene"), colNames="sample")
```

`crossHm`*crossHm*

Description

These functions have been moved and will be deprecated from this package; please use the [sechm](<https://bioconductor.org/packages/sechm>) package instead.

Usage

```
crossHm(
  ses,
  genes,
  do.scale = TRUE,
  uniqueScale = FALSE,
  assayName = .getDef("assayName"),
  sortBy = seq_along(ses),
  only.common = TRUE,
  cluster_cols = FALSE,
  cluster_rows = is.null(sortBy),
  toporder = NULL,
  hmcols = NULL,
  breaks = .getDef("breaks"),
  gaps_at = .getDef("gaps_at"),
  gaps_row = NULL,
  anno_rows = .getDef("anno_rows"),
  anno_columns = .getDef("anno_columns"),
  name = NULL,
  anno_colors = list(),
  show_rownames = NULL,
  merge_legends = FALSE,
  show_colnames = FALSE,
  rel.width = NULL,
  ...
)
```

Arguments

<code>ses</code>	A (named) list of SummarizedExperiment-class .
<code>genes</code>	A vector of genes/row.names to plot.
<code>do.scale</code>	Logical; whether to scale rows in each SE (default TRUE).
<code>uniqueScale</code>	Logical; whether to force the same colorscale for each heatmap.
<code>assayName</code>	The name of the assay to use; if multiple names are given, the first available will be used. Defaults to "logcpm", "lognorm".
<code>sortBy</code>	Names or indexes of 'ses' to use for sorting rows (default all)

only.common	Logical; whether to plot only rows common to all SEs (default TRUE).
cluster_cols	Logical; whether to cluster columns (default FALSE).
cluster_rows	Logical; whether to cluster rows (default TRUE if ‘do.sortRows=FALSE’, FALSE otherwise).
toporder	Optional vector of categories on which to supra-order when sorting rows, or name of a ‘rowData’ column to use for this purpose.
hmcols	Colors for the heatmap.
breaks	Breaks for the heatmap colors. Alternatively, symmetrical breaks can be generated automatically by setting ‘breaks’ to a numerical value between 0 and 1. The value is passed as the ‘split.prop’ argument to the getBreaks function, and indicates the proportion of the points to map to a linear scale, while the more extreme values will be plotted on a quantile scale. ‘breaks=FALSE’ will disable symmetrical scale and quantile capping, while retaining automatic breaks. ‘breaks=1’ will produce a symmetrical scale without quantile capping.
gaps_at	Columns of ‘colData’ to use to establish gaps between columns.
gaps_row	A named vector according to which rows will be split.
anno_rows	Columns of ‘rowData’ to use for annotation.
anno_columns	Columns of ‘colData’ to use for annotation.
name	The title of the heatmap key.
anno_colors	List of colors to use for annotation.
show_rownames	Whether to show row names (default TRUE if 50 rows or less).
merge_legends	Logical; passed to draw-HeatmapList-method
show_colnames	Whether to show column names (default FALSE).
rel.width	Relative width of the heatmaps
...	Any other parameter passed to each call of Heatmap .

Details

Plot a multi-panel heatmap from a list of [SummarizedExperiment-class](#).

Value

A Heatmap list.

Examples

```
data("SE", package="S E tools")
se1 <- SE[,1:10]
se2 <- SE[,11:20]
se3 <- mergeSEs( list(se1=se1, se2=se2) )
```

data	<i>Example dataset</i>
-------------	------------------------

Description

A [SummarizedExperiment-class](#) containing (a subset of) whole-hippocampus RNAseq of mice after different stressors.

Value

a [SummarizedExperiment-class](#).

References

Floriou-Servou et al. (2018). Distinct Proteomic, Transcriptomic, and Epigenetic Stress Responses in Dorsal and Ventral Hippocampus. *Biological Psychiatry*, **84**(7): 531-541. DOI: 10.1016/j.biopsych.2018.02.003.

flattenPB	<i>flattenPB</i>
------------------	------------------

Description

Flattens a pseudo-bulk SummarizedExperiment as produced by ‘muscat::aggregateData’ so that all cell types are represented in a single assay. Optionally normalizes the data and calculates per-sample logFCs.

Usage

```
flattenPB(pb, norm = TRUE, lfc_group = NULL)
```

Arguments

- | | |
|------------------|--|
| pb | a pseudo-bulk SummarizedExperiment as produced by ‘muscat::aggregateData’, with different celltypes/clusters are assays. |
| norm | Logical; whether to calculate logcpm (TMM normalization). |
| lfc_group | the colData column to use to calculate foldchange. If NULL (default), no fold-change assay will be computed. |

Value

A SummarizedExperiment

`getBreaks``getBreaks`

Description

Produces symmetrical breaks for a color scale, with the scale steps increasing for large values, which is useful to avoid outliers influencing too much the color scale.

Usage

```
getBreaks(x, n, split.prop = 0.98, symmetric = TRUE)
```

Arguments

<code>x</code>	A matrix of log2FC (or any numerical values centered around 0)
<code>n</code>	The desired number of breaks.
<code>split.prop</code>	The proportion of the data points to plot on a linear scale; the remaining will be plotted on a scale with regular frequency per step (quantile).
<code>symmetric</code>	Logical; whether breaks should be symmetric around 0 (default TRUE)

Value

A vector of breaks of length = ‘n’

Examples

```
dat <- rnorm(100, sd = 10)
getBreaks(dat, 10)
```

`log2FC``log2FC`

Description

Generates log2(foldchange) matrix/assay, eventually on a per-batch fashion.

Usage

```
log2FC(
  x,
  fromAssay = NULL,
  controls,
  by = NULL,
  isLog = NULL,
  agFun = rowMeans,
  toAssay = "log2FC"
)
```

Arguments

<code>x</code>	A numeric matrix, or a ‘SummarizedExperiment‘ object
<code>fromAssay</code>	The assay to use if ‘x‘ is a ‘SummarizedExperiment‘
<code>controls</code>	A vector of which samples should be used as controls for foldchange calculations.
<code>by</code>	An optional vector indicating groups/batches by which the controls will be averaged to calculate per-group foldchanges.
<code>isLog</code>	Logical; whether the data is log-transformed. If NULL, will attempt to figure it out from the data and/or assay name
<code>agFun</code>	Aggregation function for the baseline (default rowMeans)
<code>toAssay</code>	The name of the assay in which to save the output.

Value

An object of same class as ‘x‘; if a ‘SummarizedExperiment‘, will have the additional assay named from ‘toAssay‘.

Examples

```
log2FC( matrix(rnorm(40), ncol=4), controls=1:2 )
```

Description

Melts a SE object into a [ggplot](#)-ready long data.frame.

Usage

```
meltSE(x, genes, assayName = NULL, colDat.columns = NULL, rowDat.columns = NA)
```

Arguments

<code>x</code>	An object of class SummarizedExperiment-class
<code>genes</code>	A vector of genes to include. Use ‘genes=NULL‘ to include all.
<code>assayName</code>	The name(s) of the assay(s) to use. If NULL and the assays are named, all of them will be included (if they are not named, the first one will be used).
<code>colDat.columns</code>	The colData columns to include (defaults includes all). Use ‘colDat.columns=NA‘ in order not to include any.
<code>rowDat.columns</code>	The rowData columns to include (none included by default). Use ‘rowData=NULL‘ to include all.

Value

A data.frame.

Examples

```
data("SE", package="S Etools")
head(meltSE(SE, "Fos"))
```

mergeSEs

*mergeSEs***Description**

Merges a list of [SummarizedExperiment-class](#), either by row.names or through specified rowData fields. In cases of many-to-many (or one-to-many) mappings, ‘aggFun’ determines whether the records are aggregated by linking ID (if an aggregation method is given) or all combinations are returned (if ‘aggFun=NULL’ - default).

Usage

```
mergeSEs(
  ll,
  use.assays = NULL,
  do.scale = TRUE,
  commonOnly = TRUE,
  colColumns = NULL,
  mergeBy = NULL,
  aggFun = NULL,
  addDatasetPrefix = TRUE,
  defValues = list(),
  keepRowData = TRUE,
  BPPARAM = SerialParam()
)
```

Arguments

ll	A (named) list of SummarizedExperiment-class
use.assays	Names (or indexes) of the assays to use. By default, all common assays are used.
do.scale	A logical vector indicating (globally or for each assay) whether to perform row unit-variance scaling on each dataset before merging (default TRUE).
commonOnly	Logical; whether to restrict to rows present in all datasets (default TRUE).
colColumns	A character vector specifying ‘colData’ columns to include (if available in at least one of the datasets). If NULL, everything is kept.
mergeBy	The ‘rowData’ column to merge with. If NULL, row.names are used.

<code>aggFun</code>	The aggregation function to use when multiple rows have the same ‘mergeBy‘ value. If merging multiple assays, a different function per assay can be passed as a named list (see aggSE). If NULL (default), entries will be reused to have each combination.
<code>addDatasetPrefix</code>	Logical; whether the name of the dataset should be appended to the sample names (default TRUE).
<code>defValues</code>	An optional named list of default ‘colData‘ values when some columns are missing from some SEs.
<code>keepRowData</code>	Logical, whether to keep the rowData (default TRUE).
<code>BPPARAM</code>	For multithreading the aggregation step.

Value

An object of class [SummarizedExperiment-class](#)

Examples

```
data("SE", package="S Etools")
mergeSEs( list( se1=SE[,1:10], se2=SE[,11:20] ) )
```

<code>qualitativeColors</code>	<i>qualitativeColors</i>
--------------------------------	--------------------------

Description

`qualitativeColors`

Usage

```
qualitativeColors(names, ...)
```

Arguments

<code>names</code>	The names to which the colors are to be assigned, or an integer indicating the desired number of colors
...	passed to ‘randomcoloR::distinctColorPalette‘

Value

A vector (eventually named) of colors

```
resetAllSEtoolsOptions  
resetAllSEtoolsOptions
```

Description

Resets all global options relative to SEtools.

Usage

```
resetAllSEtoolsOptions()
```

Value

None

Examples

```
resetAllSEtoolsOptions()
```

```
scale2          scale2
```

Description

A wrapper for non-centered unit-variance scaling

Usage

```
scale2(x)
```

Arguments

x A matrix whose rows are to be scaled.

Value

A matrix of dimensions like x

Examples

```
scale2(matrix(1:9,nrow=3))
```

SE-heatmap*Heatmap wrappers for SummarizedExperiment-class.*

Description

These functions have been moved and will be deprecated from this package; please use the [sechm](<https://bioconductor.org/packages/sechm>) package instead.

Usage

```
sechm(
  se,
  genes,
  do.scale = FALSE,
  assayName = .getDef("assayName"),
  sortRowsOn = seq_len(ncol(se)),
  cluster_cols = FALSE,
  cluster_rows = is.null(sortRowsOn),
  toporder = NULL,
  hmcols = NULL,
  breaks = .getDef("breaks"),
  gaps_at = .getDef("gaps_at"),
  gaps_row = NULL,
  anno_rows = .getDef("anno_rows"),
  anno_columns = .getDef("anno_columns"),
  name = NULL,
  anno_colors = list(),
  show_rownames = NULL,
  show_colnames = FALSE,
  isMult = FALSE,
  show_heatmap_legend = !isMult,
  show_annotation_legend = TRUE,
  annorow_title_side = ifelse(show_colnames, "bottom", "top"),
  mark = NULL,
  right_annotation = NULL,
  includeMissing = FALSE,
  sort.method = "MDS_angle",
  ...
)

sehm(
  se,
  genes,
  do.scale = FALSE,
  assayName = .getDef("assayName"),
  sortRowsOn = seq_len(ncol(se)),
  cluster_cols = FALSE,
```

```

cluster_rows = is.null(sortRowsOn),
toporder = NULL,
hmcols = NULL,
breaks = .getDef("breaks"),
gaps_at = .getDef("gaps_at"),
gaps_row = NULL,
anno_rows = .getDef("anno_rows"),
anno_columns = .getDef("anno_columns"),
anno_colors = .getAnnoCols(se),
show_rownames = NULL,
show_colnames = FALSE,
...
)

```

Arguments

se	A SummarizedExperiment-class .
genes	An optional vector of genes (i.e. row names of ‘se’)
do.scale	Logical; whether to scale rows (default FALSE).
assayName	An optional vector of assayNames to use. The first available will be used, or the first assay if NULL.
sortRowsOn	Sort rows by MDS polar order using the specified columns (default all)
cluster_cols	Whether to cluster columns (default F)
cluster_rows	Whether to cluster rows; default FALSE if ‘do.sortRows=TRUE’.
toporder	Optional vector of categories on which to supra-order when sorting rows, or name of a ‘rowData’ column to use for this purpose.
hmcols	Colors for the heatmap.
breaks	Breaks for the heatmap colors. Alternatively, symmetrical breaks can be generated automatically by setting ‘breaks’ to a numerical value between 0 and 1. The value is passed as the ‘split.prop’ argument to the getBreaks function, and indicates the proportion of the points to map to a linear scale, while the more extreme values will be plotted on a quantile scale. ‘breaks=FALSE’ will disable symmetrical scale and quantile capping, while retaining automatic breaks. ‘breaks=1’ will produce a symmetrical scale without quantile capping.
gaps_at	Columns of ‘colData’ to use to establish gaps between columns.
gaps_row	Passed to the heatmap function; if missing, will be set automatically according to toporder.
anno_rows	Columns of ‘rowData’ to use for annotation.
anno_columns	Columns of ‘colData’ to use for annotation.
name	The name of the heatmap, eventually appearing as title of the color scale.
anno_colors	List of colors to use for annotation.
show_rownames	Whether to show row names (default TRUE if 50 rows or less).
show_colnames	Whether to show column names (default FALSE).

```

isMult      Logical; used to silence labels when plotting mulitple heatmaps
show_heatmap_legend
            Logical; whether to show heatmap legend
show_annotation_legend
            Logical; whether to show the annotation legend.
mark        An optional vector of gene names to highlight.
right_annotation
            Passed to ‘ComplexHeatmap::Heatmap‘
includeMissing Logical; whether to include missing genes (default FALSE)
sort.method   Method to use for row sorting (see sortRows)
...          Further arguments passed to ‘pheatmap‘ ('sehm') or ‘Heatmap‘ ('sechm').
annorows_title_side
            Side (top or bottom) of row annotation names

```

Value

A a [Heatmap-class](#).

Examples

```

data("SE", package="S E tools")
sehm(SE, row.names(SE)[1:10], do.scale=TRUE)

```

se2xls

se2xlsx

Description

Writes a SummarizedExperiment to an excel/xlsx file. Requires the ‘openxlsx‘ package.

Usage

```
se2xls(se, filename, addSheets = NULL)
```

Arguments

se	The ‘SummarizedExperiment‘
filename	xlsx file name
addSheets	An optional list of additional tables to save as sheets.

Value

Saves to file.

Examples

```
data("SE", package="SEtools")
# not run
# se2xls(SE, filename="SE.xlsx")
```

sortRows

*sortRows***Description**

sortRows

Usage

```
sortRows(
  x,
  z = FALSE,
  toporder = NULL,
  na.rm = FALSE,
  method = "MDS_angle",
  toporder.meth = "before"
)
```

Arguments

x	A numeric matrix or data.frame.
z	Whether to scale rows for the purpose of calculating order (default FALSE).
toporder	Optional vector of categories (length=nrow(x)) on which to supra-order when sorting rows.
na.rm	Whether to remove missing values and invariant rows (default FALSE).
method	Seriation method; 'MDS_angle' (default) or 'R2E' recommended.
toporder.meth	Whether to perform higher-order sorting 'before' (default) or 'after' the lower-order sorting.

Value

A reordered matrix or data.frame.

Examples

```
# random data
m <- matrix( round(rnorm(100,mean=10, sd=2)), nrow=10,
             dimnames=list(LETTERS[1:10], letters[11:20]) )
m
sortRows(m)
```

svacorsvacor

Description

A wrapper around SVA-based correction, providing a corrected assay. If this is RNAseq data or similar, use a count assay assay with ‘useVST=TRUE’; otherwise (e.g. proteomics) a log-normalized assay is recommended.

Usage

```
svacor(
  SE,
  form,
  form0 = ~1,
  assayName = NULL,
  regressOutNull = TRUE,
  useVST = TRUE,
  n.sv = NULL,
  ...
)
```

Arguments

SE	An object of class ‘SummarizedExperiment’.
form	The formula of the differential expression model
form0	An optional formula for the null model
assayName	The name (or index) of the assay to use.
regressOutNull	Logical; whether to regress out the variables of ‘form0’.
useVST	Logical; whether to use DESeq2’s variance-stabilizing transformation; (for count data!)
n.sv	The number of surrogate variables (if omitted, sva will attempt to estimate it)
...	Any other argument passed to the sva command.

Value

Returns the ‘SummarizedExperiment’ with a ‘corrected’ assay and the surrogate variables in ‘colData’.

Index

aggSE, 2, 10
castSE, 3
crossHm, 4
data, 6
flattenPB, 6
getBreaks, 5, 7, 13
ggplot, 8
Heatmap, 5
log2FC, 7
meltSE, 8
mergeSEs, 9
qualitativeColors, 10
resetAllSEtoolsOptions, 11
scale2, 11
SE (data), 6
SE-heatmap, 12
se2xls, 14
sechm (SE-heatmap), 12
sehm (SE-heatmap), 12
sortRows, 14, 15
SummarizedExperiment-class, 12
sva, 16
svacor, 16