

Package ‘SPONGE’

October 14, 2021

Type Package

Title Sparse Partial Correlations On Gene Expression

Version 1.14.0

Author Markus List, Azim Dehghani Amirabad, Dennis Kostka, Marcel H. Schulz

Maintainer Markus List <markus.list@wzw.tum.de>

Description This package provides methods to efficiently detect competitive endogeneous RNA interactions between two genes. Such interactions are mediated by one or several miRNAs such that both gene and miRNA expression data for a larger number of samples is needed as input.

License GPL (>=3)

LazyData TRUE

RoxxygenNote 6.1.1

Depends R (>= 3.4)

Suggests testthat, knitr, rmarkdown, visNetwork, ggplot2, ggrepel,
gridExtra, digest, doParallel, bigmemory

Imports Biobase, stats, ppcor, logging, foreach, doRNG, data.table,
MASS, expm, gRbase, glmnet, igraph, iterators,

VignetteBuilder knitr

biocViews GeneExpression, Transcription, GeneRegulation,
NetworkInference, Transcriptomics, SystemsBiology, Regression

git_url <https://git.bioconductor.org/packages/SPONGE>

git_branch RELEASE_3_13

git_last_commit 30cc6aa

git_last_commit_date 2021-05-19

Date/Publication 2021-10-14

R topics documented:

ceRNA_interactions	2
check_and_convert_expression_data	3

fn_elasticnet	3
fn_gene_miRNA_F_test	4
fn_get_model_coef	4
fn_get_rss	5
fn_get_shared_miRNAs	5
genes_pairwise_combinations	6
gene_expr	6
mircode_ensg	7
mircode_symbol	7
mir_expr	8
mir_interactions	8
precomputed_cov_matrices	8
precomputed_null_model	9
sample_zero_mscor_cov	9
sample_zero_mscor_data	10
sponge	11
sponge_build_null_model	12
sponge_compute_p_values	13
sponge_edge_centralities	14
sponge_gene_miRNA_interaction_filter	14
sponge_network	16
sponge_node_centralities	17
sponge_plot_network	18
sponge_plot_network_centralities	18
sponge_plot_simulation_results	19
sponge_run_benchmark	20
sponge_subsampling	21
targetscan_ensg	22
targetscan_symbol	22

Index	23
--------------	-----------

ceRNA_interactions *ceRNA interactions*

Description

ceRNA interactions

Usage

ceRNA_interactions

Format

A data table of ceRNA interactions typically provided by sponge

check_and_convert_expression_data

Checks if expression data is in matrix or ExpressionSet format and converts the latter to a standard matrix. Alternatively, a big.matrix descriptor object can be supplied to make use of shared memory between parallelized workers through the bigmemory package.

Description

Checks if expression data is in matrix or ExpressionSet format and converts the latter to a standard matrix. Alternatively, a big.matrix descriptor object can be supplied to make use of shared memory between parallelized workers through the bigmemory package.

Usage

```
check_and_convert_expression_data(expr_data)
```

Arguments

expr_data	expr_data as matrix or ExpressionSet
-----------	--------------------------------------

Value

expr_data as matrix

Examples

```
## Not run: check_and_convert_expression_data(gene_expr)
```

fn_elasticnet *Computes an elastic net model*

Description

Computes an elastic net model

Usage

```
fn_elasticnet(x, y, alpha.step = 0.1)
```

Arguments

x	miRNA expression matrix
y	gene expression vector
alpha.step	Step size for alpha, the tuning parameter for elastic net.

Value

The best model, i.e. the one for which the selected alpha yielded the smallest residual sum of squares error

fn_gene_miRNA_F_test *Perform F test for gene-miRNA elastic net model*

Description

Perform F test for gene-miRNA elastic net model

Usage

```
fn_gene_miRNA_F_test(g_expr, m_expr, model, p.adj.threshold = NULL)
```

Arguments

<code>g_expr</code>	A gene expression matrix with samples in rows and genes in columns
<code>m_expr</code>	A miRNA expression matrix with samples in rows and genes in columns. Sample number and order has to agree with above gene expression matrix
<code>model</code>	A nested elastic net model to be tested
<code>p.adj.threshold</code>	Threshold for FDR corrected p-value

Value

return data frame with miRNA, fstat and adjusted p.value (BH).

fn_get_model_coef *Extract the model coefficients from an elastic net model*

Description

Extract the model coefficients from an elastic net model

Usage

```
fn_get_model_coef(model)
```

Arguments

<code>model</code>	An elastic net model
--------------------	----------------------

Value

A data frame with miRNAs and coefficients

fn_get_rss	<i>Compute the residual sum of squares error for an elastic net model</i>
------------	---

Description

Compute the residual sum of squares error for an elastic net model

Usage

```
fn_get_rss(model, x, y)
```

Arguments

model	The elastic net model
x	The miRNA expression
y	The gene expression

Value

the RSS

fn_get_shared_miRNAs	<i>Identify miRNAs for which both genes have miRNA binding sites aka miRNA response elements in the competing endogeneous RNA hypothesis</i>
----------------------	--

Description

Identify miRNAs for which both genes have miRNA binding sites aka miRNA response elements in the competing endogeneous RNA hypothesis

Usage

```
fn_get_shared_miRNAs(geneA, geneB, mir_interactions)
```

Arguments

geneA	The first gene
geneB	The second gene
mir_interactions	A named list of genes, where for each gene all miRNA interacting partners are listed

Value

A vector with shared RNAs of the two genes.

genes_pairwise_combinations

Compute all pairwise interactions for a number of genes as indices

Description

Compute all pairwise interactions for a number of genes as indices

Usage

```
genes_pairwise_combinations(number.of.genes)
```

Arguments

number.of.genes

Number of genes for which all pairwise interactions are needed

Value

data frame with one row per unique pairwise combination. To be used as input for the sponge method.

gene_expr

Gene expression test data set

Description

Gene expression test data set

Usage

```
gene_expr
```

Format

A data frame of expression values with samples in columns and genes in rows

mircode_ensg

mircode predicted miRNA gene interactions

Description

mircode predicted miRNA gene interactions

Usage

mircode_ensg

Format

A matrix gene ensembl ids vs miRNA family names. >=1 if interaction is predicted, 0 otherwise

Source

<http://www.mircode.org/download.php>

mircode_symbol

mircode predicted miRNA gene interactions

Description

mircode predicted miRNA gene interactions

Usage

mircode_symbol

Format

A matrix gene symbols vs miRNA family names. >=1 if interaction is predicted, 0 otherwise

Source

<http://www.mircode.org/download.php>

<code>mir_expr</code>	<i>miRNA expression test data set</i>
-----------------------	---------------------------------------

Description

miRNA expression test data set

Usage

```
mir_expr
```

Format

A data frame of expression values with samples in columns and miRNA in rows

<code>mir_interactions</code>	<i>miRNA / gene interactions</i>
-------------------------------	----------------------------------

Description

miRNA / gene interactions

Usage

```
mir_interactions
```

Format

A data frame of regression coefficients typically provided by sponge_gene_miRNA_interaction_filter

<code>precomputed_cov_matrices</code>	
---------------------------------------	--

<code>precomputed_cov_matrices</code>	<i>covariance matrices under the null hypothesis that sensitivity correlation is zero</i>
---------------------------------------	---

Description

covariance matrices under the null hypothesis that sensitivity correlation is zero

Usage

```
precomputed_cov_matrices
```

Format

A list (different gene-gene correlations k) of lists (different number of miRNAs m) of covariance matrices

```
precomputed_null_model
```

A null model for testing purposes

Description

A null model for testing purposes

Usage

```
precomputed_null_model
```

Format

A list (different gene-gene correlations k) of lists (different number of miRNAs m) of sampled mscor values (100 each, computed from 100 samples)

```
sample_zero_mscor_cov  Sampling zero multiple miRNA sensitivity covariance matrices
```

Description

Sampling zero multiple miRNA sensitivity covariance matrices

Usage

```
sample_zero_mscor_cov(m, number_of_solutions, number_of_attempts = 1000,  
                      gene_gene_correlation = NULL, random_seed = NULL,  
                      log.level = "ERROR")
```

Arguments

m	number of miRNAs, i.e. number of columns of the matrix
number_of_solutions	stop after this many instances have been samples
number_of_attempts	give up after that many attempts
gene_gene_correlation	optional, define the correlation of the first two elements, i.e. the genes.
random_seed	A random seed to be used for reproducible results
log.level	the log level, typically set to INFO, set to DEBUG for verbose logging

Value

a list of covariance matrices with zero sensitivity correlation

Examples

```
sample_zero_mscor_cov(m = 1,
number_of_solutions = 1,
gene_gene_correlation = 0.5)
```

sample_zero_mscor_data

Sample mscor coefficients from pre-computed covariance matrices

Description

Sample mscor coefficients from pre-computed covariance matrices

Usage

```
sample_zero_mscor_data(cov_matrices, number_of_samples = 100,
number_of_datasets = 100)
```

Arguments

cov_matrices	a list of pre-computed covariance matrices
number_of_samples	the number of samples available in the expression data
number_of_datasets	the number of mscor coefficients to be sampled from each covariance matrix

Value

a vector of mscor coefficients

See Also

`sample_zero_mscor_cov`

Examples

```
#we select from the pre-computed covariance matrices in SPONGE
#100 for m = 5 miRNAs and gene-gene correlation 0.6
cov_matrices_selected <- precomputed_cov_matrices[["5"]][["0.6"]]
sample_zero_mscor_data(cov_matrices = cov_matrices_selected,
number_of_samples = 200, number_of_datasets = 10)
```

sponge	<i>Compute competing endogeneous RNA interactions using Sparse Partial correlations ON Gene Expression (SPONGE)</i>
--------	---

Description

Compute competing endogeneous RNA interactions using Sparse Partial correlations ON Gene Expression (SPONGE)

Usage

```
sponge(gene_expr, mir_expr, mir_interactions = NULL,
       log.level = "ERROR", log.every.n = 1e+05, log.file = NULL,
       selected.genes = NULL, gene.combinations = NULL,
       each.miRNA = FALSE, min.cor = 0.1, parallel.chunks = 1000,
       random.seed = NULL, result_as_dt = FALSE)
```

Arguments

gene_expr	A gene expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
mir_expr	A miRNA expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
mir_interactions	A named list of genes, where for each gene we list all miRNA interaction partners that should be considered.
log.level	The log level, can be one of "info", "debug", "error"
log.every.n	write to the log after every n steps
log.file	write log to a file, particularly useful for parallelization
selected.genes	Operate only on a subset of genes, particularly useful for bootstrapping
gene.combinations	A data frame of combinations of genes to be tested. Gene names are taken from the first two columns and have to match the names used for gene_expr
each.miRNA	Whether to consider individual miRNAs or pooling them.
min.cor	Consider only gene pairs with a minimum correlation specified here.
parallel.chunks	Split into this number of tasks if parallel processing is set up. The number should be high enough to guarantee equal distribution of the work load in parallel execution. However, if the number is too large, e.g. in the worst case one chunk per computation, the overhead causes more computing time than can be saved by parallel execution. Register a parallel backend that is compatible with foreach to use this feature. More information can be found in the documentation of the foreach / doParallel packages.
random.seed	A random seed to be used for reproducible results
result_as_dt	whether to return results as data table or data frame

Value

A data frame with significant gene-gene competitive endogenous RNA or 'sponge' interactions

Examples

```
#First, extract miRNA candidates for each of the genes
#using sponge_gene_miRNA_interaction_filter. Here we use a prepared
#dataset mir_interactions.

#Second we compute ceRNA interactions for all pairwise combinations of genes
#using all miRNAs remaining after filtering through elasticnet.
cerNA_interactions <- sponge(
  gene_expr = gene_expr,
  mir_expr = mir_expr,
  mir_interactions = mir_interactions)
```

sponge_build_null_model

Build null model for p-value computation

Description

Build null model for p-value computation

Usage

```
sponge_build_null_model(number_of_datasets = 1e+05, number_of_samples,
  cov_matrices = precomputed_cov_matrices, ks = seq(0.2, 0.9, 0.1),
  m_max = 8, log.level = "ERROR")
```

Arguments

number_of_datasets	the number of datasets defining the precision of the p-value
number_of_samples	the number of samples in the expression data
cov_matrices	pre-computed covariance matrices
ks	a sequence of gene-gene correlation values for which null models are computed
m_max	null models are build for each elt in ks for 1 to m_max miRNAs
log.level	The log level of the logging package

Value

a list (for various values of m) of lists (for various values of k) of lists of simulated data sets, drawn from a set of precomputed covariance matrices

Examples

```
sponge_build_null_model(100, 100,  
cov_matrices = precomputed_cov_matrices[1:3], m_max = 3)
```

```
sponge_compute_p_values
```

Compute p-values for SPONGE interactions

Description

This method uses pre-computed covariance matrices that were created for various gene-gene correlations (0.2 to 0.9 in steps of 0.1) and number of miRNAs (between 1 and 8) under the null hypothesis that the sensitivity correlation is zero. Datasets are sampled from this null model and allow for an empirical p-value to be computed that is only significant if the sensitivity correlation is higher than can be expected by chance given the number of samples, correlation and number of miRNAs. p-values are adjusted independently for each parameter combination using Benjamini-Hochberg FDR correction.

Usage

```
sponge_compute_p_values(sponge_result, null_model, log.level = "ERROR")
```

Arguments

- sponge_result A data frame from a sponge call
- null_model optional, pre-computed simulated data
- log.level The log level of the logging package

Value

A data frame with sponge results, now including p-values and adjusted p-value

See Also

`sponge_build_null_model`

Examples

```
sponge_compute_p_values(ceRNA_interactions,  
null_model = precomputed_null_model)
```

`sponge_edge_centralities`

Computes edge centralities

Description

Computes edge betweenness centrality for the ceRNA interaction network induced by the results of the SPONGE method.

Usage

`sponge_edge_centralities(sponge_result)`

Arguments

`sponge_result` The output generated by the sponge method.

Value

data table or data frame with gene, degree, eigenvector and betweenness

See Also

`sponge`

Examples

`sponge_edge_centralities(ceRNA_interactions)`

`sponge_gene_miRNA_interaction_filter`

Determine miRNA-gene interactions to be considered in SPONGE

Description

The purpose of this method is to limit the number of miRNA-gene interactions we need to consider in SPONGE. There are 3 filtering steps: 1. variance filter (optional). Only consider genes and miRNAs with variance > var.threshold. 2. miRNA target database filter (optional). Use a miRNA target database provided by the user to filter for those miRNA gene interactions for which evidence exists. This can either be predicted target interactions or experimentally validated ones. 3. For each remaining interaction of a gene and its regulating miRNAs use elastic net regression to achieve a) Feature selection: We only retain miRNAs that influence gene expression b) Effect strength: The sign of the coefficients allows us to filter for miRNAs that down-regulate gene expression. Moreover, we can use the coefficients to rank the miRNAs by their relative effect strength. We strongly recommend setting up a parallel backend compatible with the foreach package. See example and the documentation of the foreach and doParallel packages.

Usage

```
sponge_gene_miRNA_interaction_filter(gene_expr, mir_expr,
mir_predicted_targets, elastic.net = TRUE, log.level = "ERROR",
log.file = NULL, var.threshold = NULL, F.test = FALSE,
F.test.p.adj.threshold = 0.05, coefficient.threshold = -0.05,
coefficient.direction = "<", select.non.targets = FALSE,
random.seed = NULL, parallel.chunks = 100)
```

Arguments

gene_expr	A gene expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
mir_expr	A miRNA expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
mir_predicted_targets	A data frame with miRNA in cols and genes in rows. A 0 indicates the miRNA is not predicted to target the gene, >0 otherwise. If this parameter is NULL all miRNA-gene interactions are tested
elastic.net	Whether to apply elastic net regression filtering or not.
log.level	One of 'warn', 'error', 'info'
log.file	Log file to write to
var.threshold	Only consider genes and miRNA with variance > var.threshold. If this parameter is NULL no variance filtering is performed.
F.test	If true, an F-test is performed on each model parameter to assess its importance for the model based on the RSS of the full model vs the RSS of the nested model without the miRNA in question. This is time consuming and has the potential disadvantage that correlated miRNAs are removed even though they might play a role in ceRNA interactions. Use at your own risk.
F.test.p.adj.threshold	If F.test is TRUE, threshold to use for miRNAs to be included.
coefficient.threshold	threshold to cross for a regression coefficient to be called significant. depends on the parameter coefficient.direction.
coefficient.direction	If "<", coefficient has to be lower than coefficient.threshold, if ">", coefficient has to be larger than threshold. If NULL, the absolute value of the coefficient has to be larger than the threshold.
select.non.targets	For testing effect of miRNA target information. If TRUE, the method determines as usual which miRNAs are potentially targeting a gene. However, these are then replaced by a random sample of non-targeting miRNAs (without seeds) of the same size. Useful for testing if observed effects are caused by miRNA regulation.
random.seed	A random seed to be used for reproducible results

parallel.chunks

Split into this number of tasks if parallel processing is set up. The number should be high enough to guarantee equal distribution of the work load in parallel execution. However, if the number is too large, e.g. in the worst case one chunk per computation, the overhead causes more computing time than can be saved by parallel execution. Register a parallel backend that is compatible with foreach to use this feature. More information can be found in the documentation of the foreach / doParallel packages.

Value

A list of genes, where for each gene, the regulating miRNA are included as a data frame. For F.test = TRUE this is a data frame with fstat and p-value for each miRNA. Else it is a data frame with the model coefficients.

See Also

`sponge`

Examples

```
#library(doParallel)
#cl <- makePSOCKcluster(2)
#registerDoParallel(cl)
genes_miRNA_candidates <- sponge_gene_miRNA_interaction_filter(
  gene_expr = gene_expr,
  mir_expr = mir_expr,
  mir_predicted_targets = targetscan_symbol)
#stopCluster(cl)

#If we also perform an F-test, only few of the above miRNAs remain
genes_miRNA_candidates <- sponge_gene_miRNA_interaction_filter(
  gene_expr = gene_expr,
  mir_expr = mir_expr,
  mir_predicted_targets = targetscan_symbol,
  F.test = TRUE,
  F.test.p.adj.threshold = 0.05)
```

`sponge_network`

Prepare a sponge network for plotting

Description

Prepare a sponge network for plotting

Usage

```
sponge_network(sponge_result, mir_data, target.genes = NULL,
  show.sponge.interaction = TRUE, show.mirnas = "none",
  min.interactions = 3)
```

Arguments

```
sponge_result    ceRNA interactions as produced by the sponge method.  
mir_data        miRNA interactions as produced by sponge_gene_miRNA_interaction_filter  
target.genes    a character vector to select a subset of genes  
show.sponge.interaction  
                  whether to connect ceRNAs  
show.mirnas     one of none, shared, all  
min.interactions  
                  minimum degree of a gene to be shown
```

Value

a list of nodes and edges

Examples

```
sponge_network(ceRNA_interactions, mir_interactions)
```

sponge_node_centralities

Computes various node centralities

Description

Computes degree, eigenvector centrality and betweenness centrality for the ceRNA interaction network induced by the results of the SPONGE method

Usage

```
sponge_node_centralities(sponge_result, directed = FALSE)
```

Arguments

```
sponge_result    output of the sponge method  
directed        Whether to consider the input network as directed or not.
```

Value

data table or data frame with gene, degree, eigenvector and betweenness

See Also

sponge

Examples

```
sponge_node_centralities(ceRNA_interactions)
```

`sponge_plot_network` *Plot a sponge network*

Description

Plot a sponge network

Usage

```
sponge_plot_network(sponge_result, mir_data,  
    layout = "layout.fruchterman.reingold", force.directed = FALSE, ...)
```

Arguments

sponge_result	ceRNA interactions as produced by the sponge method.
mir_data	miRNA interactions as produced by sponge_gene_miRNA_interaction_filter
layout	one of the layout methods supported in the visNetwork package
force.directed	whether to produce a force directed network, gets slow for large networks
...	further params for sponge_network

Value

shows a plot

Examples

```
sponge_plot_network(ceRNA_interactions, mir_interactions)
```

sponge_plot_network_centralities

Description

plot node network centralities

Usage

```
sponge_plot_network_centralities(network_centralities, measure = "all",
  x = "degree", top = 5, base_size = 18)
```

Arguments

network_centralities	a result from sponge_node_centralities()
measure	one of 'all', 'degree', 'ev' or 'btw'
x	plot against another column in the data table, defaults to degree
top	label the top x samples in the plot
base_size	size of the text in the plot

Value

a plot

Examples

```
## Not run:
network_centralities <- sponge_node_centralities(ceRNA_interactions)
sponge_plot_network_centralities(network_centralities)
## End(Not run)
```

sponge_plot_simulation_results

Plot simulation results for different null models

Description

Plot simulation results for different null models

Usage

```
sponge_plot_simulation_results(null_model_data)
```

Arguments

null_model_data	the output of sponge_build_null_model
-----------------	---------------------------------------

Value

a ggplot2 object

Examples

```
sponge_plot_simulation_results(precomputed_null_model)
```

sponge_run_benchmark *run sponge benchmark where various settings, i.e. with or without regression, single or pooled miRNAs, are compared.*

Description

run sponge benchmark where various settings, i.e. with or without regression, single or pooled miRNAs, are compared.

Usage

```
sponge_run_benchmark(gene_expr, mir_expr, mir_predicted_targets,
  number_of_samples = 100, number_of_datasets = 100,
  number_of_genes_to_test = c(25), compute_significance = FALSE,
  folder = NULL)
```

Arguments

<code>gene_expr</code>	A gene expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
<code>mir_expr</code>	A miRNA expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
<code>mir_predicted_targets</code>	(a list of) mir interaction sources such as targetscan, etc.
<code>number_of_samples</code>	number of samples in the null model
<code>number_of_datasets</code>	number of datasets to sample from the null model
<code>number_of_genes_to_test</code>	a vector of numbers of genes to be tested, e.g. c(250,500)
<code>compute_significance</code>	whether to compute p-values
<code>folder</code>	where the results should be saved, if NULL no output to disk

Value

a list (regression, no regression) of lists (single miRNA, pooled miRNAs) of benchmark results

Examples

```
sponge_run_benchmark(gene_expr = gene_expr, mir_expr = mir_expr,
  mir_predicted_targets = targetscan_symbol,
  number_of_genes_to_test = c(10), folder = NULL)
```

sponge_subsampling *Sponge subsampling*

Description

Sponge subsampling

Usage

```
sponge_subsampling(subsample.n = 100, subsample.repeats = 10,  
subsample.withreplacement = FALSE, subsample.plot = FALSE,  
gene_expr, mir_expr, ...)
```

Arguments

subsample.n the number of samples to be drawn in each round
subsample.repeats
 how often should the subsampling be done?
subsample.withreplacement
 logical, should we allow samples to be used repeatedly
subsample.plot logical, should the results be plotted as box plots
gene_expr A gene expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
mir_expr A miRNA expression matrix with samples in rows and features in columns. Alternatively an object of class ExpressionSet.
... parameters passed on to the sponge function

Value

a summary of the results with mean and standard deviations of the correlation and sensitive correlation.

References

sponge

Examples

```
sponge_subsampling(gene_expr = gene_expr,  
mir_expr = mir_expr, mir_interactions = mir_interactions,  
subsample.n = 10, subsample.repeats = 1)
```

targetscan_ensg *targetscan predicted miRNA gene interactions*

Description

targetscan predicted miRNA gene interactions

Usage

targetscan_ensg

Format

A matrix gene ensembl ids vs miRNA family names. >=1 if interaction is predicted, 0 otherwise

Source

http://www.targetscan.org/vert_71/

targetscan_symbol *targetscan predicted miRNA gene interactions*

Description

targetscan predicted miRNA gene interactions

Usage

targetscan_symbol

Format

A matrix gene symbols vs miRNA family names. >=1 if interaction is predicted, 0 otherwise

Source

http://www.targetscan.org/vert_71/

Index

* datasets

ceRNA_interactions, 2
gene_expr, 6
mir_expr, 8
mir_interactions, 8
mircode_ensg, 7
mircode_symbol, 7
precomputed_cov_matrices, 8
precomputed_null_model, 9
targetscan_ensg, 22
targetscan_symbol, 22

ceRNA_interactions, 2
check_and_convert_expression_data, 3

fn_elasticnet, 3
fn_gene_miRNA_F_test, 4
fn_get_model_coef, 4
fn_get_rss, 5
fn_get_shared_miRNAs, 5

gene_expr, 6
genes_pairwise_combinations, 6

mir_expr, 8
mir_interactions, 8
mircode_ensg, 7
mircode_symbol, 7

precomputed_cov_matrices, 8
precomputed_null_model, 9

sample_zero_mscor_cov, 9
sample_zero_mscor_data, 10
sponge, 11
sponge_build_null_model, 12
sponge_compute_p_values, 13
sponge_edge_centralities, 14
sponge_gene_miRNA_interaction_filter,
 14
sponge_network, 16

sponge_node_centralities, 17
sponge_plot_network, 18
sponge_plot_network_centralities, 18
sponge_plot_simulation_results, 19
sponge_run_benchmark, 20
sponge_subsampling, 21

targetscan_ensg, 22
targetscan_symbol, 22