

Package ‘HiCDCPlus’

April 12, 2022

Type Package

Title Hi-C Direct Caller Plus

Version 1.2.1

Description Systematic 3D interaction calls and differential analysis for Hi-C and HiChIP. The HiC-DC+ (Hi-C/HiChIP direct caller plus) package enables principled statistical analysis of Hi-C and HiChIP data sets – including calling significant interactions within a single experiment and performing differential analysis between conditions given replicate experiments – to facilitate global integrative studies. HiC-DC+ estimates significant interactions in a Hi-C or HiChIP experiment directly from the raw contact matrix for each chromosome up to a specified genomic distance, binned by uniform genomic intervals or restriction enzyme fragments, by training a background model to account for random polymer ligation and systematic sources of read count variation.

License GPL-3

Encoding UTF-8

biocViews HiC, DNA3DStructure, Software, Normalization

RoxygenNote 7.1.1

SystemRequirements JRE 8+

LinkingTo Rcpp

Imports

Rcpp, InteractionSet, GenomicInteractions, bbmle, pscl, BSgenome, data.table, dplyr, tidyR, GenomeInfoDb, rlang, splines, MASS

Suggests BSgenome.Mmusculus.UCSC.mm9, BSgenome.Mmusculus.UCSC.mm10,

BSgenome.Hsapiens.UCSC.hg19, BSgenome.Hsapiens.UCSC.hg38,

RUnit, BiocGenerics, knitr, rmarkdown, HiTC, DESeq2, Matrix,

BiocFileCache, rappdirs

Enhances parallel

VignetteBuilder knitr

NeedsCompilation yes

git_url <https://git.bioconductor.org/packages/HiCDCPlus>

git_branch RELEASE_3_14

git_last_commit 0d0adfa

git_last_commit_date 2022-01-23

Date/Publication 2022-04-12

Author Merve Sahin [cre, aut] (<<https://orcid.org/0000-0003-3858-8332>>)

Maintainer Merve Sahin <merve.sahn@gmail.com>

R topics documented:

add_1D_features	3
add_2D_features	4
add_hicpro_allvalidpairs_counts	5
add_hicpro_matrix_counts	6
add_hic_counts	6
construct_features	7
construct_features_chr	8
construct_features_parallel	10
expand_1D_features	11
extract_hic_eigenvectors	12
generate_binned_gi_list	13
generate_bintolen_gi_list	14
generate_df_gi_list	15
get_chrs	16
get_chr_sizes	16
get_enzyme_cutsites	17
gi_list2HTClist	17
gi_list_binsize_detect	18
gi_list_Dthreshold.detect	19
gi_list_read	19
gi_list_topdom	20
gi_list_validate	21
gi_list_write	22
hic2icenorm_gi_list	23
hicdc2hic	24
hicdcdiff	25
HiCDCPlus	27
HiCDCPlus_chr	28
HiCDCPlus_parallel	30
HTClist2gi_list	31
straw	32
straw_dump	33

add_1D_features *add_1D_features*

Description

Adds 1D features to the gi_list instance. If any bin on gi_list overlaps with multiple feature records, feature values are aggregated for the bin according to the vector valued function agg (e.g., sum, mean)

Usage

```
add_1D_features(gi_list, df, chrs = NULL, features = NULL, agg = mean)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (see ?gi_list_validate for a detailed explanation of valid gi_list instances).
df	DataFrame with columns named 'chr', and 'start' and features to be added with their respective names.
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in the data frame df.
features	features to be added. Needs to be a subset of colnames(df). Defaults to all columns in df other than 'chr', 'start', and 'end'.
agg	any vector valued function with one data argument: defaults to mean.

Value

a gi_list instance with 1D features stored in regions metadata handle of each list element (e.g., gi_list[[1]]@regions@elementMetadata) in the instance

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),end=seq(2e6,11e6,1e6))
gi_list<-generate_df_gi_list(df)
feats<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),gc=rnorm(10))
gi_list<-add_1D_features(gi_list,feats)
```

add_2D_features	<i>add_2D_features</i>
-----------------	------------------------

Description

Adds 2D features to a `gi_list` instance. If any bin on `gi_list` overlaps with multiple feature records, features are aggregated among matches according to the univariate vector valued function `agg` (e.g., `sum`, `mean`). For efficient use of memory, using `add/expand 1D features` (see `?add_1D_features` and `expand_1D_features`) in sequence is recommended instead of using `add_2D_features` directly for each chromosome.

Usage

```
add_2D_features(gi, df, features = NULL, agg = sum)
```

Arguments

<code>gi</code>	Element of a valid <code>gi_list</code> instance (restricted to a single chromosome e.g., <code>gi_list[['chr9']]</code> —see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
<code>df</code>	data frame for a single chromosome containing columns named <code>chr</code> , <code>startI</code> and <code>startJ</code> and features to be added with their respective names (if <code>df</code> contains multiple chromosomes, you can convert it into a list of smaller data.frames for each chromosome and apply this function with <code>sapply</code>).
<code>features</code>	features to be added. Needs to be subset of <code>colnames(df)</code> . Defaults to all columns in <code>df</code> other than ' <code>chr</code> ', ' <code>start</code> ', and ' <code>end</code> '.
<code>agg</code>	any vector valued function with one data argument: defaults to <code>mean</code> .

Value

a `gi_list` element with 2D features stored in metadata handle (i.e., `mcols(gi)`).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6))
gi_list<-generate_df_gi_list(df,Dthreshold=500e3)
feats<-data.frame(chr='chr9',
startI=seq(1e6,10e6,1e6),startJ=seq(1e6,10e6,1e6),counts=rpois(10,lambda=5))
gi_list[['chr9']]<-add_2D_features(gi_list[['chr9']],feats)
```

```
add_hicpro_allvalidpairs_counts
    add_hicpro_allvalidpairs_counts
```

Description

This function converts HiC-Pro outputs in allValidPairs format into a gi_list instance.

Usage

```
add_hicpro_allvalidpairs_counts(
  gi_list,
  allvalidpairs_path,
  chrs = NULL,
  binned = TRUE,
  add_inter = FALSE
)
```

Arguments

gi_list	valid gi_list instance. See ?gi_list_validate for details. You can also detect whether a gi_list instance is uniformly binned, along with its bin size using gi_list_binsize_detect.
allvalidpairs_path	allValidPairsfile obtained from HiC-Pro (e.g., 'GSM2572593_con_rep1.allvalidPairs.txt')
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list instance.
binned	TRUE if the gi_list instance is uniformly binned (helps faster execution). Defaults to TRUE.
add_inter	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each gi_list element (e.g., gi_list[[1]]@regions@elementMetadata or not; default FALSE

Value

gi_list instance with counts on the metadata (e.g., mcols(gi_list[[1]])) handle on each list element, and 'inter' on regions metadata handle of each element if add_inter=TRUE.

```
add_hicpro_matrix_counts
    add_hicpro_matrix.counts
```

Description

This function converts HiC-Pro matrix and bed outputs into a `gi_list` instance.

Usage

```
add_hicpro_matrix_counts(
  gi_list,
  absfile_path,
  matrixfile_path,
  chrs = NULL,
  add_inter = FALSE
)
```

Arguments

<code>gi_list</code>	valid, uniformly binned <code>gi_list</code> instance. See <code>?gi_list_validate</code> and <code>gi_list_binsize_detect</code> for details.
<code>absfile_path</code>	absfile BED out of HiC-Pro (e.g., <code>'rawdata_10000_abs.bed'</code>)
<code>matrixfile_path</code>	matrix count file out of HiC-Pro (e.g., <code>'rawdata_10000.matrix'</code>)
<code>chrs</code>	a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes in the <code>gi_list</code> instance.
<code>add_inter</code>	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each <code>gi_list</code> element (e.g., <code>gi_list[[1]]@regions@elementMetadata</code> or not; default FALSE

Value

`gi_list` instance with counts on the metadata (e.g., `mcols(gi_list[[1]])`) handle on each list element, and 'inter' on regions metadata handle of each element if `add_inter=TRUE`.

<code>add_hic_counts</code>	<i>add_hic_counts</i>
-----------------------------	-----------------------

Description

This function adds counts from a .hic file into a valid, binned, `gi_list` instance.

Usage

```
add_hic_counts(gi_list, hic_path, chrs = NULL, add_inter = FALSE)
```

Arguments

gi_list	valid, uniformly binned gi_list instance. See ?gi_list_validate and gi_list_binsize_detect for details.
hic_path	path to the .hic file
chrs	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes in the gi_list instance.
add_inter	Interchromosomal interaction counts added as a 1D feature named 'inter' on regions metadata handle of each gi_list element (e.g., gi_list[[1]]@regions@elementMetadata or not; default FALSE

Value

gi_list instance with counts on the metadata (e.g., mcols(gi_list[[1]]) handle on each list element, and 'inter' on regions metadata handle of each element if add_inter=TRUE.

Examples

```
gi_list<-generate_binned_gi_list(50e3, chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
```

construct_features	<i>construct_features</i>
--------------------	---------------------------

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) <https://www.nature.com/articles/ncomms15454>; GC content, mappability, and effective length

Usage

```
construct_features(
  output_path,
  gen = "Hsapieins",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
  wg_file = NULL,
  chrs = NULL,
  feature_type = "RE-based"
)
```

Arguments

<code>output_path</code>	the path to the folder and name prefix you want to place feature files into. The feature file will have the suffix '_bintolen.txt.gz'.
<code>gen</code>	name of the species: e.g., default 'Hsapiens'.
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'.
<code>sig</code>	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
<code>bin_type</code>	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
<code>binsize</code>	binsize in bp if bin_type='Bins-uniform' (or number of RE fragment cut sites if bin_type='Bins-RE-sites'), defaults to 5000.
<code>wg_file</code>	path to the bigWig file containing mappability values across the genome of interest.
<code>chrs</code>	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified.
<code>feature_type</code>	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. bin_type has to be 'Bins-uniform' if feature_type='RE-agnostic'.

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
outdir<-paste0(tempdir(check=TRUE),'/')
construct_features(output_path=outdir,gen='Hsapiens',
gen_ver='hg19',sig=c('GATC','GANTC'),bin_type='Bins-uniform',binsize=100000,
wg_file=NULL,chrs=c('chr21'))
```

`construct_features_chr`

construct_features_chr

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) for a single chromosome. <https://www.nature.com/articles/ncomms15454>; GC content, mappability, and effective length

Usage

```
construct_features_chr(
  chrom,
  gen = "Hsapiens",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
  wg_file = NULL,
  feature_type = "RE-based"
)
```

Arguments

<code>chrom</code>	select a chromosome.
<code>gen</code>	name of the species: e.g., default 'Hsapiens'.
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'.
<code>sig</code>	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
<code>bin_type</code>	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
<code>binsize</code>	binsize in bp if <code>bin_type='Bins-uniform'</code> (or number of RE fragment cut sites if <code>bin_type='Bins-RE-sites'</code>), defaults to 5000.
<code>wg_file</code>	path to the bigWig file containing mappability values across the genome of interest.
<code>feature_type</code>	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. <code>bin_type</code> has to be 'Bins-uniform' if <code>feature_type='RE-agnostic'</code> .

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
df<-construct_features_chr(chrom='chr22',
  gen='Hsapiens', gen_ver='hg19', sig=c('GATC','GANTC'), bin_type='Bins-uniform',
  binsize=100000, wg_file=NULL)
```

`construct_features_parallel`
construct_features_parallel

Description

This function lists all restriction enzyme cutsites of a given genome and genome version with genomic features outlined in Carty et al. (2017) <https://www.nature.com/articles/ncomms15454>; GC content, mappability, and effective length

Usage

```
construct_features_parallel(
  output_path,
  gen = "Hsapiens",
  gen_ver = "hg19",
  sig = "GATC",
  bin_type = "Bins-uniform",
  binsize = 5000,
  wg_file = NULL,
  chrs = NULL,
  feature_type = "RE-based",
  ncore = NULL
)
```

Arguments

<code>output_path</code>	the path to the folder and name prefix you want to place feature files into. The feature file will have the suffix '_bintolen.txt.gz'.
<code>gen</code>	name of the species: e.g., default 'Hsapiens'.
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'.
<code>sig</code>	restriction enzyme cut pattern (or a vector of patterns; e.g., 'GATC' or c('GATC','GANTC')).
<code>bin_type</code>	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragments.
<code>binsize</code>	binsize in bp if <code>bin_type='Bins-uniform'</code> (or number of RE fragment cut sites if <code>bin_type='Bins-RE-sites'</code>), defaults to 5000.
<code>wg_file</code>	path to the bigWig file containing mappability values across the genome of interest.
<code>chrs</code>	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified.
<code>feature_type</code>	'RE-based' if features are to be computed based on restriction enzyme fragments. 'RE-agnostic' ignores restriction enzyme cutsite information and computes features gc and map based on binwide averages. <code>bin_type</code> has to be 'Bins-uniform' if <code>feature_type='RE-agnostic'</code> .
<code>ncore</code>	Number of cores to parallelize. Defaults to <code>parallel::detectCores()-1</code> .

Value

a features 'bintolen' file that contains GC, mappability and length features.

Examples

```
outdir<-paste0(tempdir(check=TRUE), '/')
construct_features_parallel(output_path=outdir, gen='Hsapiens',
gen_ver='hg19', sig=c('GATC', 'GANTC'), bin_type='Bins-uniform', binsize=100000,
wg_file=NULL, chrs=c('chr21'), ncore=2)
```

expand_1D_features	<i>expand_1D_features</i>
--------------------	---------------------------

Description

Expands 1D features on the regions metadata handle of each list element (e.g., `gi_list[[1]]@regions@elementMetadata`) to the 2D metadata e.g., `mcols(gi_list[[1]])`). Two feature values corresponding to each anchor is summarized as a score using a vector valued function `agg` that takes two vector valued arguments of the same size and outputs a vector of the same size as the input vectors. This defaults to the `transform.vec` function outlined in (Carty et al., 2017). For efficient use of memory, using add/expand 1D features (see `?add_1D_features` and `expand_1D_features`) in sequence is recommended instead of using `add_2D_features` directly for each chromosome.

Usage

```
expand_1D_features(gi_list, chrs = NULL, features = NULL, agg = transform.vec)
```

Arguments

<code>gi_list</code>	List of <code>GenomicInteractions</code> objects where each object named with chromosomes contains intra-chromosomal interaction information (see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
<code>chrs</code>	a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes in the <code>gi_list</code> instance.
<code>features</code>	features to be added. Defaults to all 1D features in elements of <code>gi_list[[1]]@regions@elementMetadata</code> .
<code>agg</code>	any vector valued function with two data arguments: defaults to <code>transform.vec</code> described in HiC-DC (Carty et al., 2017).

Value

a `gi_list` element with 2D features stored in metadata handle (i.e., `mcols(gi)`).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),end=seq(2e6,11e6,1e6))
gi_list<-generate_df_gi_list(df)
feats<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6),gc=rnorm(10))
gi_list<-add_1D_features(gi_list,feats)
gi_list<-expand_1D_features(gi_list)
```

```
extract_hic_eigenvectors
    extract_hic_eigenvectors
```

Description

This function uses Juicer command line tools to extract first eigenvectors across chromosomes from counts data in a .hic file and outputs them to text file of the structure chr start end score where the score column contains the eigenvector elements.

Usage

```
extract_hic_eigenvectors(
  hicfile,
  mode = "KR",
  binsize = 1e+05,
  chrs = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

<code>hicfile</code>	path to the input .hic file.
<code>mode</code>	Normalization mode to extract first eigenvectors from Allowable options are: 'NONE' for raw (normalized counts if .hic file is written using hicdc2hic or hic2icenorm_gi_list), 'KR' for Knight-Ruiz normalization, 'VC' for Vanilla-Coverage normalization and 'VC_SQRT' for square root vanilla coverage. Defaults to 'KR'.
<code>binsize</code>	the uniform binning size for compartment scores in bp. Defaults to 100e3.
<code>chrs</code>	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes except "Y", and "M" for the specified gen and gen_ver.
<code>gen</code>	name of the species: e.g., default 'Hsapiens'.
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'.

Value

path to the eigenvector text files for each chromosome containing chromosome, start, end and compartment score values that may need to be flipped signs for each chromosome. File paths follow gsub('.hic', '_<chromosome>_eigenvectors.txt', hicfile)

Examples

```
eigenvector_filepaths<-extract_hic_eigenvectors(
  hicfile=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
  package = "HiCDCPlus"),
  chrs=c("chr22"), binsize=50e3)
```

```
generate_binned_gi_list
generate_binned_gi_list
```

Description

Generates a valid uniformly binned gi_list instance.

Usage

```
generate_binned_gi_list(
  binsize,
  chrs = NULL,
  Dthreshold = 2e+06,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

<code>binsize</code>	Desired binsize in bp, e.g., 5000, 25000.
<code>chrs</code>	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes except "Y", and "M" for the specified <code>gen</code> and <code>gen_ver</code> .
<code>Dthreshold</code>	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is smaller.
<code>gen</code>	name of the species: e.g., default 'Hsapiens'.
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'.

Value

a valid, uniformly binned gi_list instance.

Examples

```
gi_list<-generate_binned_gi_list(1e6, chrs='chr22')
```

```
generate_bintolen_gi_list
    generate_bintolen_gi_list
```

Description

Generates a gi_list instance from a bintolen file generated by generate.features (see ?generate.features) for details).

Usage

```
generate_bintolen_gi_list(
  bintolen_path,
  chrs = NULL,
  Dthreshold = 2e+06,
  binned = TRUE,
  binsize = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

bintolen_path	path to the flat file containing columns named bins and features
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in the bintolen file.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is smaller.
binned	TRUE if the bintolen file is uniformly binned. Defaults to TRUE.
binsize	bin size in bp to be generated for the object. Defaults to the binsize in the bintolen file, if exists.
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'

Value

a valid gi_list instance with genomic features derived from specified restriction enzyme cut patterns when generating the bintolen file using construct_features (see ?construct_features for help). Genomic 1D features are stored in the regions metadata handle of each list element (e.g., gi_list[[1]]@regions@elementMetadata).

Examples

```
chrs<-'chr22'
bintolen_path<-system.file("extdata", "test_bintolen.txt.gz",
package = "HiCDCPlus")
gi_list<-generate_bintolen_gi_list(bintolen_path, chrs)
```

```
generate_df_gi_list    generate_df_gi_list
```

Description

Generates a gi_list instance from a data frame object describing the regions.

Usage

```
generate_df_gi_list(  
  df,  
  chrs = NULL,  
  Dthreshold = 2e+06,  
  gen = "Hsapiens",  
  gen_ver = "hg19"  
)
```

Arguments

df	DataFrame with columns named 'chr', 'start', (and optionally 'end', if the regions have gaps) and 1D features with their respective column names.
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes specified in df.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data, whichever is smaller.
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'

Value

a valid gi_list instance with genomic features supplied from df. Genomic 1D features are stored in the regions metadata handle of each list element (e.g., gi_list[[1]]@regions@elementMetadata).

Examples

```
df<-data.frame(chr='chr9',start=seq(1e6,10e6,1e6))  
gi_list<-generate_df_gi_list(df)
```

`get_chrs`*get_chrs***Description**

This function finds all chromosomes of a given genome and genome version except for Y and M.

Usage

```
get_chrs(gen = "Hsapiens", gen_ver = "hg19")
```

Arguments

- | | |
|----------------------|--|
| <code>gen</code> | name of the species: e.g., default 'Hsapiens' |
| <code>gen_ver</code> | genomic assembly version: e.g., default 'hg19' |

Value

string vector of chromosomes.

Examples

```
get_chrs('Hsapiens', 'hg19')
```

`get_chr_sizes`*get_chr_sizes***Description**

This function finds all chromosome sizes of a given genome, genome version and set of chromosomes.

Usage

```
get_chr_sizes(gen = "Hsapiens", gen_ver = "hg19", chrs = NULL)
```

Arguments

- | | |
|----------------------|---|
| <code>gen</code> | name of the species: e.g., default 'Hsapiens' |
| <code>gen_ver</code> | genomic assembly version: e.g., default 'hg19' |
| <code>chrs</code> | select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified. |

Value

named vector containing names as chromosomes and values as chromosome sizes.

Examples

```
get_chr_sizes('Hsapiens','hg19',c('chr21','chr22'))
```

`get_enzyme_cutsites` *get_enzyme_cutsites*

Description

This function finds all restriction enzyme cutsites of a given genome, genome version, and set of cut patterns

Usage

```
get_enzyme_cutsites(sig, gen = "Hsapiens", gen_ver = "hg19", chrs = NULL)
```

Arguments

<code>sig</code>	a set of restriction enzyme cut patterns (e.g., 'GATC' or c('GATC','GANTC'))
<code>gen</code>	name of the species: e.g., default 'Hsapiens'
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'
<code>chrs</code>	a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes (except Y and M) in the genome specified by <code>gen</code> and <code>gen_ver</code> .

Value

list of chromosomes.

Examples

```
get_enzyme_cutsites(gen='Hsapiens',gen_ver='hg19',
sig=c('GATC','GANTC'),chrs=c('chr22'))
```

`gi_list2HTClist` *gi_list2HTClist*

Description

This function converts a `gi_list` instance into a `HTClist` instance compatible for use with the R Bioconductor package HiTC <https://bioconductor.org/packages/HiTC/>

Usage

```
gi_list2HTClist(gi_list, chrs = NULL)
```

Arguments

<code>gi_list</code>	List of GenomicInteractions objects with a counts column where each object named with chromosomes contains intra-chromosomal interaction information (minimally containing counts and genomic distance in <code>mcols(gi_list)</code>)— see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
<code>chrs</code>	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to chromosomes in <code>gi_list</code> .

Value

a HTClist instance compatible for use with HiTC

Examples

```
gi_list<-generate_binned_gi_list(50e3, chrs=c('chr22'))
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
htc_list<-gi_list2HTClist(gi_list)
```

`gi_list_binsize_detect`
gi_list_binsize_detect

Description

This function finds the bin size of a uniformly binned valid `gi_list` instance in bp. It raises an error if the `gi_list` instance is not uniformly binned.

Usage

```
gi_list_binsize_detect(gi_list)
```

Arguments

<code>gi_list</code>	<code>gi_list</code> object to be verified. In order to pass without errors, a <code>gi_list</code> object (1) has to be a list of <code>InteractionSet::GInteractions</code> objects,(2) each list element has to be named as chromosomes and only contain intra-chromosomal interaction information, (3) <code>mcols(.)</code> for each list element should at least contain pairwise genomic distances in a column named 'D' and (4) each list element needs to be uniformly binned
----------------------	--

Value

uniform binsize in base pairs or an error if the `gi_list` instance is not uniformly binned.

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrss='chr22')
gi_list_binsize_detect(gi_list)
```

```
gi_list_Dthreshold.detect
gi_list_Dthreshold_detect
```

Description

This function finds the maximum genomic distance in a valid *gi_list* object.

Usage

```
gi_list_Dthreshold.detect(gi_list)
```

Arguments

gi_list A valid *gi_list* instance. See *?gi_list_validate* for more details about the attributes of a valid *gi_list* instance.

Value

maximum genomic distance in the object

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrss='chr22')
gi_list_Dthreshold.detect(gi_list)
```

```
gi_list_read          gi_list_read
```

Description

Reads a written *gi_list* instance using *gi_list_write* into a valid *gi_list* instance.

Usage

```
gi_list_read(
  fname,
  chrss = NULL,
  Dthreshold = NULL,
  features = NULL,
  gen = "Hsapiens",
  gen_ver = "hg19"
)
```

Arguments

fname	path to the file to read from (can end with .txt, .rds, or .txt.gz).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to all chromosomes contained in the fname.
Dthreshold	maximum distance (included) to check for significant interactions, defaults to the maximum in the data.
features	Select the subset of features (1-D or 2-D) to be added to the <i>gi_list</i> instance (without the trailing I or J), defaults to all features (score column gets ingested as 'score').
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'

Value

A valid *gi_list* instance with 1D features stored in regions metadata handle of each list element (e.g., *gi_list*[1]@regions@elementMetadata) in the instance and with 2D features stored in metadata handle (i.e., *mcols(gi)*).

Examples

```
outputdir<-paste0(tempdir(check=TRUE),'/')
gi_list<-generate_binned_gi_list(1e6,chrs='chr22')
gi_list_write(gi_list,paste0(outputdir,'testgiread.txt'))
gi_list2<-gi_list_read(paste0(outputdir,'testgiread.txt'))
```

gi_list_topdom *gi_list_topdom*

Description

This function converts a *gi_list* instance with ICE normalized counts into TAD annotations through an implementation of TopDom v0.0.2 (<https://github.com/HenrikBengtsson/TopDom>) adapted as TopDom at this package. If you're using this function, please cite TopDom according to the documentation at <https://github.com/HenrikBengtsson/TopDom/blob/0.0.2/docs/>

Usage

```
gi_list_topdom(
  gi_list,
  chrs = NULL,
  file_out = FALSE,
  fpath = NULL,
  window.size = 5,
  verbose = FALSE
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (see ?gi_list_validate for a detailed explanation of valid gi_list instances).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in gi_list.
file_out	If true, outputs TAD annotations into files with paths beginning with fpath. Defaults to FALSE
fpath	Outputs TAD annotations into files with paths beginning in fpath.
window.size	integer, number of bins to extend. Defaults to 5.
verbose	TRUE if you would like to troubleshoot TopDom.

Value

a list instance with TAD annotation reporting for each chromosome

Examples

```
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus")
gi_list<-hic2icenorm_gi_list(hic_path,binsize=50e3,chrs='chr22')
tads<-gi_list_topdom(gi_list)
```

gi_list_validate	<i>gi_list_validate</i>
------------------	-------------------------

Description

This function validates a gi_list instance.

Usage

```
gi_list_validate(gi_list)
```

Arguments

gi_list	gi_list object to be verified. In order to pass without errors, a gi_list object (1) has to be a list of InteractionSet::GInteractions objects, (2) each list element has to be named as chromosomes and only contain intra-chromosomal interaction information, (3) <code>mcols(.)</code> for each list element should at least contain pairwise genomic distances in a column named 'D'.
---------	--

Value

invisible value if the gi_list instance is valid. Otherwise, an error is raised.

Examples

```
gi_list<-generate_binned_gi_list(1e6,chrss='chr22')
gi_list_validate(gi_list)
```

gi_list_write	<i>gi_list_write</i>
---------------	----------------------

Description

Writes a valid `gi_list` instance into a file.

Usage

```
gi_list_write(
  gi_list,
  fname,
  chrss = NULL,
  columns = "minimal",
  rows = "all",
  significance_threshold = 0.05,
  score = NULL
)
```

Arguments

<code>gi_list</code>	List of <code>GenomicInteractions</code> objects where each object named with chromosomes contains intra-chromosomal interaction information (see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
<code>fname</code>	path to the file to write to (can end with .txt, or .txt.gz).
<code>chrss</code>	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes in the <code>gi_list</code> .
<code>columns</code>	Can be 'minimal', which is just distance and counts (and <code>HiCDCPlus</code> result columns 'qvalue','pvalue','mu',and 'sdev', if exists; see <code>?HiCDCPlus</code>) information, 'minimal_plus_features', which is distance, counts, and other calculated 2D features, 'minimal_plus_score', which generates a .hic pre compatible text file, or 'all', which is distance, counts, calculated 2D features, as well as all 1D features. Defaults to 'minimal'.
<code>rows</code>	Can be 'all' or 'significant', which filters rows according to FDR adjusted pvalue column 'qvalue' (this has to exist in <code>mcols(.)</code>) at <code>significance_threshold</code> . Defaults to 'all'.
<code>significance_threshold</code>	Row filtering threshold on 'qvalue'. Defaults to 0.05.
<code>score</code>	Score column to extract to .hic pre compatible file. See <code>mode</code> options in <code>?hicdc2hic</code> for more details.

Value

a tab separated flat file concatenating all intra-chromosomal interaction information.

Examples

```
outputdir<-paste0(tempdir(check=TRUE), '/')
gi_list<-generate_binned_gi_list(1e6, chrs='chr22')
gi_list_write(gi_list,paste0(outputdir,'test.txt'))
```

```
hic2icenorm_gi_list    hic2icenorm_gi_list
```

Description

This function converts a .hic file into a gi_list instance with ICE normalized counts on the counts column for TAD annotation using a copy of TopDom (see ?TopDom_0.0.2) as well as an (optional) .hic file with ICE normalized counts for visualization with Juicebox. This function requires installing the Bioconductor package HiTC.

Usage

```
hic2icenorm_gi_list(
  hic_path,
  binsize = 50000,
  chrs = NULL,
  hic_output = FALSE,
  gen = "Hsapiens",
  gen_ver = "hg19",
  Dthreshold = Inf
)
```

Arguments

hic_path	Path to the .hic file.
binsize	Desired bin size in bp (default 50000).
chrs	select a subset of chromosomes' e.g., c('chr21','chr22'). Defaults to chromosomes in gen and gen_ver except 'chrY' and 'chrM'.
hic_output	If TRUE, a .hic file with the name gsub("\.hic\$","_icenorm.hic",hic_path) is generated containing the ICE normalized counts under 'NONE' normalization.
gen	name of the species: e.g., default 'Hsapiens'
gen_ver	genomic assembly version: e.g., default 'hg19'
Dthreshold	maximum distance (included) to check for significant interactions, defaults to maximum in the data.

Value

a thresholded `gi_list` instance with ICE normalized intra-chromosomal counts for further use with this package, HiCDCPlus.

Examples

```
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus")
gi_listgi_list(hic_path,binsize=50e3,chr=c('chr22'))
```

hicdc2hic

*hicdc2hic***Description**

This function converts various modes from HiCDCPlus `gi_list` (uniformly binned) instance back into a .hic file with the mode passed as counts that can be retrieved using Juicer Dump (<https://github.com/aidenlab/juicer/wiki/Extraction>) with 'NONE' normalization.

Usage

```
hicdc2hic(
  gi_list,
  hicfile,
  mode = "normcounts",
  chrs = NULL,
  gen_ver = "hg19",
  memory = 8
)
```

Arguments

<code>gi_list</code>	List of <code>GenomicInteractions</code> objects where each object named with chromosomes contains intra-chromosomal interaction information (minimally containing counts and genomic distance in <code>ncols(gi_list)</code>)—see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
<code>hicfile</code>	the path to the .hic file
<code>mode</code>	What to put to the .hic file as score. Allowable options are: 'pvalue' for -log10 significance p-value, 'qvalue' for -log10 FDR corrected p-value, 'normcounts' for raw counts/expected counts, and 'zvalue' for standardized counts (raw counts-expected counts)/modeled standard deviation of expected counts and 'raw' to pass-through 'raw counts'. Defaults to 'normcounts'.
<code>chrs</code>	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to chromosomes in <code>gi_list</code> .
<code>gen_ver</code>	genomic assembly version: e.g., default 'hg19'
<code>memory</code>	Java memory to generate .hic files. Defaults to 8. Up to 64 is recommended for higher resolutions.

Value

path of the .hic file.

Examples

```
outdir<-paste0(tempdir(check=TRUE), '/')
gi_list<-generate_binned_gi_list(50e3, chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
hicdc2hic(gi_list,hicfile=paste0(outdir,'out.hic'),
mode='raw')
```

hiccdiff

hiccdiff

Description

This function calculates differential interactions for a set of chromosomes across conditions and replicates. You need to install DESeq2 from Bioconductor to use this function.

Usage

```
hiccdiff(
  input_paths,
  filter_file,
  output_path,
  bin_type = "Bins-uniform",
  binsize = 5000,
  granularity = 5000,
  chrs = NULL,
  Dmin = 0,
  Dmax = 2e+06,
  diagnostics = FALSE,
  DESeq.save = FALSE,
  fitType = "local"
)
```

Arguments

<code>input_paths</code>	a list with names as condition names and values as paths to <code>gi_list</code> RDS objects (see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances) saved with <code>saveRDS</code> or paths to .hic files for each replicate. e.g., <code>list(CTCF=c('~/Downloads/GM_CTCF_rep1_MAPQ30_10kb.rds', '~/Downloads/GM_CTCF_rep2_MAPQ30_10kb.rds'))</code>
<code>filter_file</code>	path to the text file containing columns chr', startI, and startJ denoting the name of the chromosomes and starting coordinates of 2D interaction bins to be compared across conditions, respectively.

<code>output_path</code>	the path to the folder and name prefix you want to place DESeq-processed matrices (in a .txt file), plots (if <code>diagnostics=TRUE</code>) and DESeq2 objects (if <code>DESeq.save=TRUE</code>). Files will be generated for each chromosome.
<code>bin_type</code>	'Bins-uniform' if uniformly binned by binsize in bp, or 'Bins-RE-sites' if binned by number of restriction enzyme fragment cutsites!
<code>binsize</code>	binsize in bp if <code>bin_type='Bins-uniform'</code> (or number of RE fragments if <code>bin_type='Bins-RE-sites'</code>), e.g., default 5000
<code>granularity</code>	Desired distance granularity to base dispersion parameters on in bp. For uniformly binned analysis (i.e., <code>bin_type=='Bins-uniform'</code>), this defaults to the bin size. Otherwise, it is 5000.
<code>chrs</code>	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes (except Y and M) in the <code>filter_file</code> .
<code>Dmin</code>	minimum distance (included) to check for significant interactions, defaults to 0. Put <code>Dmin=1</code> to ignore D=0 bins in calculating normalization factors.
<code>Dmax</code>	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
<code>diagnostics</code>	if TRUE, generates diagnostic plots of the normalization factors, geometric means of such factors by distance bin, as well as MA Plots (see DESeq documentation for details about MA plots). Defaults to FALSE.
<code>DESeq.save</code>	if TRUE, saves the DESeq objects for each chromosome as an .rds file in the <code>output_path</code> . Defaults to FALSE.
<code>fitType</code>	follows fitType in <code>DESeq2::estimateDispersions</code> . Allowable options are 'parametric' (parametric regression), 'local' (local regression), and 'mean' (constant across interaction bins). Default is 'local'.

Value

paths of a list of three entities. `outputpaths` will have differential bins among those in `filter_file`. `deseq2paths` will have the DESeq2 object stored as an .rds file. Available if `DESeq.save=TRUE` `plotpaths` will have diagnostic plots (e.g., MA, dispersion, PCA) if `diagnostics=TRUE`.

Examples

```
outputdir<-paste0(tempdir(check=TRUE), '/')
hiccdiff(input_paths=list(NSD2=c(
  system.file("extdata", "GSE131651_NS2_LOW_arima_example.hic",
  package = "HiCDCPlus"),
  system.file("extdata", "GSE131651_NS2_HIGH_arima_example.hic",
  package = "HiCDCPlus")),
  TKO=c(system.file("extdata", "GSE131651_TKOCTCF_new_example.hic",
  package = "HiCDCPlus"),
  system.file("extdata", "GSE131651_NTKOCTCF_new_example.hic",
  package = "HiCDCPlus"))),
  filter_file=system.file("extdata", "GSE131651_analysis_indices.txt.gz",
  package = "HiCDCPlus"),
  chrs='chr22',
  output_path=outputdir,
```

```
fitType = 'mean',
binsize=50000,
diagnostics=FALSE)
```

HiCDCPlus

HiCDCPlus

Description

This function finds significant interactions in a HiC-DC readable matrix and expresses statistical significance of counts through the following: 'pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, 'mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Usage

```
HiCDCPlus(
  gi_list,
  covariates = NULL,
  chrs = NULL,
  distance_type = "spline",
  model_distribution = "nb",
  binned = TRUE,
  df = 6,
  Dmin = 0,
  Dmax = 2e+06,
  ssize = 0.01,
  splineknotting = "uniform",
  model_filepath = NULL
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (minimally containing counts and genomic distance in <code>mcols(gi_list[[1]])</code>)—see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
covariates	covariates to be considered in addition to genomic distance <i>D</i> . Defaults to all covariates besides 'D', 'counts', 'mu', 'sdev', 'pvalue', 'qvalue' in <code>mcols(gi_list[[1]])</code>
chrs	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes in the <code>gi_list</code> .
distance_type	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.
model_distribution	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiCDC model.

binned	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cutsites
df	degrees of freedom for the genomic distance spline function if <i>distance_type</i> ='spline'. Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
Dmin	minimum distance (included) to check for significant interactions, defaults to 0
Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
ssize	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
splineknotting	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
model_filepath	Outputs fitted HiC-DC model object as an .rds file per chromosome. Defaults to NULL (no output).

Value

A valid *gi_list* instance with additional *mcols(.)* for each chromosome: *pvalue*: significance *P*-value, *'qvalue'*: FDR corrected *P*-value, *mu*: expected counts, *'sdev'*: modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3, chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi_list<-HiCDCPlus(gi_list)
```

Description

This function finds significant interactions in a HiC-DC readable matrix restricted to a single chromosome and expresses statistical significance of counts through the following: *'pvalue'*: significance *P*-value, *'qvalue'*: FDR corrected *P*-value, *mu*: expected counts, *'sdev'*: modeled standard deviation of expected counts.

Usage

```
HiCDCPlus_chr(
  gi,
  covariates = NULL,
  distance_type = "spline",
```

```

model_distribution = "nb",
binned = TRUE,
df = 6,
Dmin = 0,
Dmax = 2e+06,
ssize = 0.01,
splineknotting = "uniform",
model_filepath = NULL
)

```

Arguments

<code>gi</code>	Instance of a single chromosome GenomicInteractions object containing intra-chromosomal interaction information (minimally containing counts and genomic distance).
<code>covariates</code>	covariates to be considered in addition to genomic distance D. Defaults to all covariates besides 'D','counts','mu','sdev','pvalue','qvalue' in <code>mcols(gi)</code>
<code>distance_type</code>	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.
<code>model_distribution</code>	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiC-DC model.
<code>binned</code>	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cut sites.
<code>df</code>	degrees of freedom for the genomic distance spline function if <code>distance_type='spline'</code> . Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
<code>Dmin</code>	minimum distance (included) to check for significant interactions, defaults to 0
<code>Dmax</code>	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
<code>ssize</code>	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
<code>splineknotting</code>	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
<code>model_filepath</code>	Outputs fitted HiC-DC model object as an .rds file with chromosome name indicated on it. Defaults to NULL (no output).

Value

A valid `gi` instance with additional `mcols(.)`: `pvalue`: significance *P*-value, `qvalue`: FDR corrected *P*-value, `mu`: expected counts, `sdev`: modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3, chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path<-system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi<-HiCDCPlus_chr(gi_list[[1]])
```

HiCDCPlus_parallel *HiCDCPlus_parallel*

Description

This function finds significant interactions in a HiC-DC readable matrix and expresses statistical significance of counts through the following with a parallel implementation (using sockets; compatible with Windows): 'pvalue': significance *P*-value, 'qvalue': FDR corrected *P*-value, 'mu': expected counts, 'sdev': modeled standard deviation of expected counts.

Usage

```
HiCDCPlus_parallel(
  gi_list,
  covariates = NULL,
  chrs = NULL,
  distance_type = "spline",
  model_distribution = "nb",
  binned = TRUE,
  df = 6,
  Dmin = 0,
  Dmax = 2e+06,
  ssize = 0.01,
  splineknotting = "uniform",
  ncore = NULL
)
```

Arguments

gi_list	List of GenomicInteractions objects where each object named with chromosomes contains intrachromosomal interaction information (minimally containing counts and genomic distance in <code>mcols(gi_list[[1]])</code>)—see <code>?gi_list_validate</code> for a detailed explanation of valid <code>gi_list</code> instances).
covariates	covariates to be considered in addition to genomic distance <code>D</code> . Defaults to all covariates besides 'D', 'counts', 'mu', 'sdev', 'pvalue', 'qvalue' in <code>mcols(gi)</code>
chrs	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to all chromosomes in the <code>gi_list</code> .
distance_type	distance covariate form: 'spline' or 'log'. Defaults to 'spline'.

model_distribution	'nb' uses a Negative Binomial model, 'nb_vardisp' uses a Negative Binomial model with a distance specific dispersion parameter inferred from the data, 'nb_hurdle' uses the legacy HiC-DC model.
binned	TRUE if uniformly binned or FALSE if binned by restriction enzyme fragment cutsites
df	degrees of freedom for the genomic distance spline function if <code>distance_type='spline'</code> . Defaults to 6, which corresponds to a cubic spline as explained in Carty et al. (2017)
Dmin	minimum distance (included) to check for significant interactions, defaults to 0
Dmax	maximum distance (included) to check for significant interactions, defaults to 2e6 or maximum in the data; whichever is minimum.
ssize	Distance stratified sampling size. Can decrease for large chromosomes. Increase recommended if model fails to converge. Defaults to 0.01.
splineknotting	Spline knotting strategy. Either "uniform", uniformly spaced in distance, or placed based on distance distribution of counts "count-based" (i.e., more closely spaced where counts are more dense).
ncore	Number of cores to parallelize. Defaults to <code>parallel::detectCores()-1</code> .

Value

A valid `gi_list` instance with additional `mcols(.)` for each chromosome: `pvalue`: significance *P*-value, `qvalue`: FDR corrected *P*-value, `mu`: expected counts, `sdev`: modeled standard deviation of expected counts.

Examples

```
gi_list<-generate_binned_gi_list(50e3, chrs='chr22')
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
gi<-HiCDCPlus_parallel(gi_list,ncore=1)
```

HTClist2gi_list *HTClist2gi_list*

Description

This function converts a `HTClist` instance into a `gi_list` instance with counts for further use with this package, `HiCDCPlus`

Usage

```
HTClist2gi_list(htc_list, chrs = NULL, Dthreshold = 2e+06)
```

Arguments

<code>htc_list</code>	A valid HTClist instance (see <code>vignette("HiTC")</code>)
<code>chrs</code>	select a subset of chromosomes' e.g., <code>c('chr21','chr22')</code> . Defaults to chromosomes in <code>htc_list</code> .
<code>Dthreshold</code>	maximum distance (included) to check for significant interactions, defaults to <code>2e6</code> or maximum in the data; whichever is smaller.

Value

a thresholded gi_list instance with intra-chromosomal counts for further use with HiCDCPlus

Examples

```
gi_list<-generate_binned_gi_list(50e3,chrs=c('chr22'))
gi_list<-add_hic_counts(gi_list,
hic_path=system.file("extdata", "GSE63525_HMEC_combined_example.hic",
package = "HiCDCPlus"))
htc_list<-gi_list2HTClist(gi_list)
gi_list2<-HTClist2gi_list(htc_list,Dthreshold=Inf)
```

Description

Adapted C++ implementation of Juicer's dump. Reads the .hic file, finds the appropriate matrix and slice of data, and outputs as an R DataFrame.

Usage

```
straw(norm, fn, ch1, ch2, u, bs)
```

Arguments

<code>norm</code>	Normalization to apply. Must be one of NONE/VC/VC_SQRT/KR. VC is vanilla coverage, VC_SQRT is square root of vanilla coverage, and KR is Knight-Ruiz or Balanced normalization.
<code>fn</code>	path to the .hic file
<code>ch1</code>	first chromosome location (e.g., "1")
<code>ch2</code>	second chromosome location (e.g., "8")
<code>u</code>	BP (BasePair) or FRAG (restriction enzyme FRAGment)
<code>bs</code>	The bin size. By default, for BP, this is one of <2500000, 1000000, 500000, 250000, 100000, 50000, 25000, 10000, 5000> and for FRAG this is one of <500, 200, 100, 50, 20, 5, 2, 1>.

Details

Usage: straw <NONE/VC/VC_SQRT/KR> <hicFile(s)> <chr1>[:x1:x2] <chr2>[:y1:y2] <BP/FRAG> <binsize>

Value

Data.frame of a sparse matrix of data from hic file. x,y,counts

straw_dump

straw_dump

Description

Interface for Juicer's dump in case C++ straw fails (known to fail on Windows due to zlib compression not being OS agnostic and particularly not preserving null bytes, which .hic files are delimited with). This function reads the .hic file, finds the appropriate matrix and slice of data, writes it to a temp file, reads and modifies it, and outputs as an R DataFrame (and also deletes the temp file).

Usage

```
straw_dump(norm, fn, ch1, ch2, u, bs)
```

Arguments

norm	Normalization to apply. Must be one of NONE/VC/VC_SQRT/KR. VC is vanilla coverage, VC_SQRT is square root of vanilla coverage, and KR is Knight-Ruiz or Balanced normalization.
fn	path to the .hic file
ch1	first chromosome location (e.g., "1")
ch2	second chromosome location (e.g., "8")
u	BP (BasePair) or FRAG (restriction enzyme FRAGment)
bs	The bin size. By default, for BP, this is one of <2500000, 1000000, 500000, 250000, 100000, 50000, 25000, 10000, 5000> and for FRAG this is one of <500, 200, 100, 50, 20, 5, 2, 1>.

Details

Usage: straw_dump <oe/observed> <NONE/VC/VC_SQRT/KR> <hicFile(s)> <chr1>[:x1:x2] <chr2>[:y1:y2] <BP/FRAG> <binsize> <outfile>

Value

Data.frame of a sparse matrix of data from hic file. x,y,counts

Index

add_1D_features, 3
add_2D_features, 4
add_hic_counts, 6
add_hicpro_allvalidpairs_counts, 5
add_hicpro_matrix_counts, 6

construct_features, 7
construct_features_chr, 8
construct_features_parallel, 10

expand_1D_features, 11
extract_hic_eigenvectors, 12

generate_binned_gi_list, 13
generate_bintolen_gi_list, 14
generate_df_gi_list, 15
get_chr_sizes, 16
get_chrs, 16
get_enzyme_cutsites, 17
gi_list2HTClist, 17
gi_list_binsize_detect, 18
gi_list_Dthreshold.detect, 19
gi_list_read, 19
gi_list_topdom, 20
gi_list_validate, 21
gi_list_write, 22

hic2icenorm_gi_list, 23
hicdc2hic, 24
hicdcdiff, 25
HiCDCPlus, 27
HiCDCPlus_chr, 28
HiCDCPlus_parallel, 30
HTClist2gi_list, 31

straw, 32
straw_dump, 33