

Package ‘contiBAIT’

April 12, 2022

Type Package

Title Improves Early Build Genome Assemblies using Strand-Seq Data

Version 1.22.0

Date 2019-10-03

Author Kieran O'Neill, Mark Hills, Mike Gottlieb

Maintainer Kieran O'Neill <koneill@bccrc.ca>

Description Using strand inheritance data from multiple single cells from the organism whose genome is to be assembled, contiBAIT can cluster unbridged contigs together into putative chromosomes, and order the contigs within those chromosomes.

License BSD_2_clause + file LICENSE

Depends BH (>= 1.51.0-3), Rsamtools (>= 1.21)

LinkingTo Rcpp, BH

Imports data.table, grDevices, clue, cluster, gplots, BiocGenerics (>= 0.31.6), S4Vectors, IRanges, GenomicRanges, Rcpp, TSP, GenomicFiles, gtools, rtracklayer, BiocParallel, DNAcopy, colorspace, reshape2, ggplot2, methods, exomeCopy, GenomicAlignments, diagram

Suggests BiocStyle

biocViews ImmunoOncology, CellBasedAssays, QualityControl, WholeGenome, Genetics, GenomeAssembly

Collate 'AllClasses.R' 'AllGenerics.R' 'BAIT.R'
'barplotLinkageGroupCalls.R' 'clusterContigs.R'
'computeConsensus.R' 'computeSim.R' 'contiBAIT.R'
'findSexGroups.R' 'findSimilarLibraries.R' 'fixLinkageGroups.R'
'flipOrderedLinkageGroups.R' 'highlightAssemblyErrors.R'
'ideogramPlot.R' 'locateMisorientations.R' 'makeBoxPlot.R'
'makeChrTable.R' 'mapGapFromOverlap.R' 'mergeFlankedLGs.R'
'orderAllLinkageGroups.R' 'orderContigsGreedy.R'
'orderContigsTSP.R' 'plotContigOrder.R' 'plotLGDistances.R'
'plotWCdistribution.R' 'preprocessStrandTable.R'
'reorientAndMergeLGs.R' 'strandSeqFreqTable.R' 'thoroughBed.R'
'writeBed.R'

RoxygenNote 6.0.1.9000

NeedsCompilation yes

git_url <https://git.bioconductor.org/packages/contiBAIT>

git_branch RELEASE_3_14

git_last_commit 7642d19

git_last_commit_date 2021-10-26

Date/Publication 2022-04-12

R topics documented:

BAIT	3
barplotLinkageGroupCalls,LinkageGroupList,ChrTable-method	4
ChrTable-class	5
clusterContigs,StrandStateMatrix-method	6
contiBAIT	7
ContigOrdering-class	8
exampleChrTable	9
exampleContigOrder	9
exampleCrickFreq	9
exampleDividedChr	9
exampleLGLList	10
exampleLibList	10
exampleReadCounts	10
exampleStrandFreq	10
exampleWatsonFreq	10
exampleWCMMatrix	11
findSexGroups,LinkageGroupList,StrandStateMatrix-method	11
findSimilarLibraries,StrandStateMatrix,StrandReadMatrix,ChrTable-method	12
fixLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList-method	13
flipOrderedLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList,StrandStateMatrix-method	14
highlightAssemblyErrors	15
ideogramPlot,StrandReadMatrix,StrandReadMatrix,ChrTable-method	16
LibraryGroupList-class	17
LinkageGroupList-class	18
locateMisoriens,GRanges-method	18
makeBoxPlot,ChrTable,LinkageGroupList-method	19
makeChrTable	20
mapGapFromOverlap	21
mergeFlankedLGs,LinkageGroupList,StrandStateMatrix-method	21
orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method	22
orderContigsGreedy	24
orderContigsTSP	24
plotContigOrder,ContigOrdering-method	25
plotLGDistances,LinkageGroupList,StrandStateMatrix-method	26

plotWCdistribution,StrandFreqMatrix-method	27
preprocessStrandTable,StrandFreqMatrix-method	27
reorientAndMergeLGs,LinkageGroupList,StrandStateMatrix-method	28
show,ContigOrdering-method	29
show,LibraryGroupList-method	30
show,LinkageGroupList-method	30
show,OrientationFrame-method	31
show,StrandFreqMatrix-method	31
show,StrandReadMatrix-method	32
show,StrandStateList-method	32
show,StrandStateMatrix-method	33
StrandFreqMatrix-class	33
StrandReadMatrix-class	34
strandSeqFreqTable	34
StrandStateList-class	36
StrandStateMatrix-class	36
thoroughBed,ANY,LibraryGroupList-method	37
writeBed,ANY,ChrTable,ContigOrdering-method	38

Index	39
--------------	-----------

BAIT	<i>BAIT – master function to process strand-seq libraries into BAIT ideograms</i>
------	---

Description

BAIT – master function to process strand-seq libraries into BAIT ideograms

Usage

```
BAIT(path = ".", splitBy = 2e+05, readQual = 10, pairedEnd = TRUE,
      plotBy = "lib", plotName = NULL, chroms = "all", verbose = TRUE)
```

Arguments

path	String denoting location of Strand-seq bam files (default is ".")
splitBy	numeric value of binsize for plotting. default is 200000
readQual	Integer dictating the minimal mapping quality required for a read to be accepted. Default is 10.
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note,
plotBy	Whether to plot by library ('lib') or chromosome ('chr')
plotName	character which determines file name to be saved. Default is to open an R plot from the terminal
chroms	vector of chromosome number to prevent contig plotting. eg for humans use 1:24. Default is 'all'
verbose	prints messages to the terminal (default is TRUE)

Value

ideogram plots

Examples

```
## Not run:

#Not run because this takes a minute or two:
bamPath=file.path(system.file(package='contibAIT'), 'extdata')

BAIT(bamPath, pairedEnd = FALSE) #our example data is single-end

## End(Not run)
```

barplotLinkageGroupCalls,LinkageGroupList,ChrTable-method

Bar plot all linkage groups, with the true chromosomes of contigs coloured.

Description

Bar plot all linkage groups, with the true chromosomes of contigs coloured.

Usage

```
## S4 method for signature 'LinkageGroupList,ChrTable'
barplotLinkageGroupCalls(object, chrTable,
  by = "lg", bySize = TRUE, returnTable = NULL, whichGroup = NULL,
  percentage = NULL)
```

Arguments

object	LinkageGroupList, as generated by clusterContigs
chrTable	GRanges object containing assembly information about the contigs, including a meta column called 'name' that has names matching the object. Note that the rownames of chrTable should be the contig names, as they are used in object, and the first column (chromosome name) will be used to order by chromosome if 'chr' option used in by parameter. To use a bam file header, the product of makeChrTable(bamFile) is suitable for input
by	whether to plot by linkage group (if 'lg') or chromosomes ('chr')
bySize	logical value to return barplot either with LGs sorted by number of contigs or size (in Mb). Default is TRUE.
returnTable	Logical to return chromosome length matrix. Default is NULL

whichGroup	Numeric vector of groups to analyse. If by='lg', then only the subset of LGs selected by whichGroup will be analyzed. If by='chr', then only subset of chromosomes selected by whichGroup will be analyzed. Note to include legend, use legend=rownames(chr.table) for by='lg', and legend=colnames(chr.table) for by='chr'
percentage	Logical that returns the percentage of different chromosomes or LG within the barplot. Default is NULL

Value

a matrix of lengths of each chromosome (rows) in each linkage group (columns)

Examples

```
data("exampleLGList")
data("exampleDividedChr")

barplotLinkageGroupCalls(exampleLGList, exampleDividedChr)
```

Description

This class is a GRanges object with a meta column called name, which represents the fragment name.

Usage

```
ChrTable(chrRanges = GRanges())
```

Arguments

chrRanges	a GRanges object with a meta column called name, which represents the fragment name
-----------	---

Value

a ChrTable

clusterContigs,StrandStateMatrix-method

clusterContigs – agglomeratively clusters contigs into linkage groups based on strand inheritance

Description

clusterContigs – agglomeratively clusters contigs into linkage groups based on strand inheritance

Usage

```
## S4 method for signature 'StrandStateMatrix'
clusterContigs(object, similarityCutoff = 0.7,
               recluster = NULL, minimumLibraryOverlap = 5, randomise = TRUE,
               randomSeed = NULL, randomWeight = NULL, clusterParam = NULL,
               clusterBy = "hetero", verbose = TRUE)
```

Arguments

object	data.frame containing strand inheritance information for every contig (rows) in every library (columns). This should be the product of strandSeqFreqTable
similarityCutoff	place contigs in a cluster when their strand state is at least this similar
recluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
minimumLibraryOverlap	for two contigs to be clustered together, the strand inheritance must be present for both contigs in at least this many libraries (in addition to their similarity being at least similarityCutoff)
randomise	whether to reorder contigs before clustering
randomSeed	random seed to initialize clustering
randomWeight	vector of weights for contigs for resampling. If NULL, uniform resampling is used. Typically this should be a measure of contig quality, such as library coverage, so that clustering tends to start from the better quality contigs.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
clusterBy	Method for performing clustering. Default is 'hetero' (for comparing heterozygous calls to homozygous). Alternative is 'homo' (for comparison between the two homozygous calls)
verbose	prints function progress

Details

Note that a more stringent similarity cutoff will result in more clusters, and a longer run time, since at every iteration a distance is computed to the existing clusters. However, in lower-quality data, a more stringent cutoff may be necessary to reduce the number of contigs that are erroneously grouped.

Note that `clusterParam` requires `BiocParallel` to be installed.

Value

`LinkageGroupList` of vectors containing labels of contigs belonging to each linkage group

Examples

```
data("exampleWCMatrix")

clusteredContigs <- clusterContigs(exampleWCMatrix, verbose=FALSE)
show(clusteredContigs)
show(clusteredContigs[[1]])
```

`contiBAIT`

contiBAIT – master function to process strand-seq libraries into ordered linkage groups

Description

`contiBAIT` – master function to process strand-seq libraries into ordered linkage groups

Usage

```
contiBAIT(path = ".", cluster = 1, clusterParam = NULL,
          saveName = FALSE, filter = FALSE, readQual = 10, readLimit = 10,
          pairedEnd = TRUE, makePlots = FALSE, verbose = TRUE)
```

Arguments

<code>path</code>	String denoting location of Strand-seq bam files (default is ".")
<code>cluster</code>	Integer denoting the number of reclustering to be performed for creating linkage groups (default is 1)
<code>clusterParam</code>	Number of parallel processors to use when clustering contigs. Default is NULL.
<code>saveName</code>	String denoting the file name for saved data. If FALSE, no intermediate files are saved (default is FALSE)
<code>filter</code>	additional file to split chromosomes based on locations. If this parameter is blank, a filter table will be automatically generated from the header of the first file in <code>bamFileList</code>
<code>readQual</code>	Integer dictating the minimal mapping quality required for a read to be accepted. Default is 10.

readLimit	Minimum number of reads on a contig to make a strand call. Default is 10
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output
makePlots	Logical determining whether plots should be created. Default is TRUE
verbose	prints messages to the terminal (default is TRUE)

Value

ordered contigs in bed format. Depending on options, intermediate files and plots will also be generated

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleDividedChr")
library(BiocParallel)

example.dir <- file.path(system.file(package='contiBAIT'), 'extdata')

orderedContigs <- contiBAIT(path=example.dir,
cluster=1,
clusterParam=MulticoreParam(),
filter=exampleDividedChr,
pairedEnd=FALSE)
```

ContigOrdering-class *A class for storing contig ordering of a linkage group*

Description

This class is a matrix of two character vectors that represent the calculated ordering of a linkage group. The first element of this matrix is the Linkage Group sub-setted by contigs with equal strand states across all libraries in the calculated order. The second element is the names of names of each contig in the calculated order.

Usage

```
ContigOrdering(ordering = character())
```

Arguments

ordering	a matrix of two character vectors that represent the calculated ordering of a linkage group. The first element of this matrix is the Linkage Group sub-setted by contigs with equal strand states across all libraries in the calculated order. The second element is the names of names of each contig in the calculated order.
----------	--

Value

a ContigOrdering

Examples

```
thisOrdering <- ContigOrdering(matrix(ncol=2, c( "LG1.11", "chr2:1000820-2001640",
"LG1.1", "chr2:3002461-4003281")))
```

exampleChrTable

Example of a ChromosomeTable, containing contigs and their lengths

Description

Example of a ChromosomeTable, containing contigs and their lengths

exampleContigOrder

Example of a ContigOrdering table, containing a list with a matrix of ordered groups element and a StrandStateList element

Description

Example of a ContigOrdering table, containing a list with a matrix of ordered groups element and a StrandStateList element

exampleCrickFreq

An example Crick strand frequencies extracted from BAMS by strandSeqFreqTable where BAITtables=TRUE

Description

An example Crick strand frequencies extracted from BAMS by strandSeqFreqTable where BAITtables=TRUE

exampleDividedChr

Example of a divided chromosome, containing contigs and their lengths

Description

Example of a divided chromosome, containing contigs and their lengths

exampleLGList

Example of a LinkageGroupList output from clusterContigs

Description

Example of a LinkageGroupList output from clusterContigs

exampleLibList

Example of a LibraryGroupList, containing library names

Description

Example of a LibraryGroupList, containing library names

exampleReadCounts

Example of read counts extracted from BAMS by strandSeqFreqTable

Description

Example of read counts extracted from BAMS by strandSeqFreqTable

exampleStrandFreq

Example of strand frequencies extracted from BAMS by strandSeqFreqTable

Description

Example of strand frequencies extracted from BAMS by strandSeqFreqTable

exampleWatsonFreq

An example Watson strand frequencies extracted from BAMS by strandSeqFreqTable where BAITtables=TRUE

Description

An example Watson strand frequencies extracted from BAMS by strandSeqFreqTable where BAITtables=TRUE

exampleWCMatrix	<i>An example StrandStateMatrix containing WW, CC and WC calls for contigs</i>
-----------------	--

Description

An example StrandStateMatrix containing WW, CC and WC calls for contigs

findSexGroups,LinkageGroupList,StrandStateMatrix-method	<i>Bar plot all linkage groups, with the true chromosomes of contigs coloured.</i>
---	--

Description

Bar plot all linkage groups, with the true chromosomes of contigs coloured.

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'  
findSexGroups(linkageGroupList,  
              strandStateMatrix, callThreshold = 0.2)
```

Arguments

linkageGroupList
a LinkageGroupList object as generated by clusterContigs

strandStateMatrix
a StrandStateMatrix object as generated by preprocessStrandTable

callThreshold a value between 0 and 1 to threshold the proportion of libraries in which scaffold folds are heterozygous (ie unlikely to be a monosome sex chromosome). Default value is 0.2

Value

the same LinkageGroupList entered into the function, but with potential sex chromosomes highlighted in the name attribute

findSimilarLibraries,StrandStateMatrix,StrandReadMatrix,ChrTable-method
*findSimilarLibraries – function to identify libraries that have similar
WC patterns on chromosomes*

Description

`findSimilarLibraries` – function to identify libraries that have similar WC patterns on chromosomes

Usage

```
## S4 method for signature 'StrandStateMatrix,StrandReadMatrix,ChrTable'
findSimilarLibraries(strandStateMatrix,
  strandReadMatrix, chrGrange, chrNum, cluster = 1, clusterParam = NULL,
  verbose = TRUE)
```

Arguments

<code>strandStateMatrix</code>	A <code>strandStateMatrix</code> object for all libraries across split fragments, derived from <code>preprocessStrandTable</code>
<code>strandReadMatrix</code>	The number of reads present for each <code>strandStateMatrix</code> element. An object of type <code>strandReadMatrix</code> from <code>strandSeqFreqTable</code>
<code>chrGrange</code>	File of type <code>ChrTable</code> (a <code>GRanges</code> object with a meta column titled 'name' determining contig name) to split chromosomes based on locations. <code>name</code> meta should match the rownames of <code>strandStateMatrix</code> and <code>strandReadMatrix</code>
<code>chrNum</code>	The chromosome number to analyse
<code>cluster</code>	Number of times to recluster and take the consensus of. If <code>NULL</code> , clustering is run only once
<code>clusterParam</code>	optional <code>BiocParallelParam</code> specifying cluster to use for parallel execution. When <code>NULL</code> , execution will be serial.
<code>verbose</code>	prints messages to the terminal (default is <code>TRUE</code>)

Value

a list of type `LinkageGroupList` with two elements; libraries that are mostly Watson, and those that are mostly Crick

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleDividedChr")
data("exampleWCMatrix")
data("exampleReadCounts")
```

```

library(BiocParallel)

example.dir <- file.path(system.file(package='contiBAIT'), 'extdata')

chrGrange <- exampleDividedChr[which(exampleDividedChr$name %in% rownames(exampleWCMatrix))]

exampleLibList <- lapply(seq_len(length(unique(seqnames(chrGrange)))), function(x) findSimilarLibraries(exampleWCMatrices[x]))
exampleLibList <- exampleLibList[!sapply(exampleLibList, is.null)]
exampleLibList <- LibraryGroupList(exampleLibList)

show(exampleLibList)

```

fixLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList-method

*fixLinkageGroups – searches for discrepancies within ordered contigs
to highlight erroneously merged fragments.*

Description

fixLinkageGroups – searches for discrepancies within ordered contigs to highlight erroneously merged fragments.

Usage

```
## S4 method for signature 'ContigOrdering,StrandStateList,LinkageGroupList'
fixLinkageGroups(contigOrdering,
                 orderFrame, linkageGroupList, whichLG = NULL, relatedCutOff = 0.6,
                 verbose = TRUE)
```

Arguments

contigOrdering	a data.frame of ordered contigs with linkage group names of class ContigOrdering
orderFrame	a list of StrandStateMatrix elements of class StrandStateList
linkageGroupList	List of vectors containing names of contigs belonging to each LG of type LinkageGroupList.
whichLG	vector of integers specifying the element(s) of linkageGroupList to be ordered (i.e. which specific linkage groups to try to order). Default is all LGs.
relatedCutOff	The minimal dissimilarity between adjacent contigs to subset a linkage group into multiple smaller groups. Default is 0.6
verbose	Outputs information to the terminal. Default is TRUE.

Value

a LinkageGroupList with erroneously clustered contigs seperated into their own groups

flipOrderedLinkageGroups,ContigOrdering,StrandStateList,LinkageGroupList,StrandStateMatrix-method
flipOrderedLinkageGroups – Simple greedy algorithm to find misorientations within previously ordered LG.

Description

flipOrderedLinkageGroups – Simple greedy algorithm to find misorientations within previously ordered LG.

Usage

```
## S4 method for signature
## 'ContigOrdering,StrandStateList,LinkageGroupList,StrandStateMatrix'
flipOrderedLinkageGroups(contigOrdering,
orderFrame, linkageGroupList, strandStateMatrix, whichLG = NULL,
maxiter = 100, dissimilarityCutoff = 0.3)
```

Arguments

contigOrdering a data.frame of ordered contigs with linkage group names of class ContigOrdering

orderFrame a list of StrandStateMatrix elements of class StrandStateList

linkageGroupList List of vectors containing names of contigs belonging to each LG of type LinkageGroupList. Should be ordered as the output of orderAllLinkageGroups[[3]]

strandStateMatrix a StrandStateMatrix to be reoriented

whichLG vector of integers specifying the element(s) of linkageGroupList to be ordered (i.e. which specific linkage groups to try to order). Default is all LGs.

maxiter The number of iterations used to find the optimal path. Default is 100

dissimilarityCutoff The minimum amount of dissimilarity needed to start reorienting contigs. Default is 0.3.

Value

a StrandStateMatrix with misorientations resolved

highlightAssemblyErrors

*highlightAssemblyErrors – Master function to identify misorientations
and chimeras in the assembly*

Description

highlightAssemblyErrors – Master function to identify misorientations and chimeras in the assembly

Usage

```
highlightAssemblyErrors(path, splitBy = 1e+06, cluster = 1,  
clusterParam = NULL, pairedEnd = TRUE, qual = 10, gapFile = NULL,  
verbose = TRUE)
```

Arguments

path	String denoting location of Strand-seq bam files
splitBy	integer determining the average size contigs should be split by
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note,
qual	Mapping quality threshold. Default is 1
gapFile	A GRanges object consisting of start and end locations of assembly gaps (default is NULL)
verbose	prints messages to the terminal (default is TRUE)

Value

a directional ChrTable object that can be used in downstream functions (strandSeqFreqTable)

ideogramPlot,StrandReadMatrix,StrandReadMatrix,ChrTable-method
ideogramPlot – plots BAIT-like ideograms

Description

`ideogramPlot` – plots BAIT-like ideograms

Usage

```
## S4 method for signature 'StrandReadMatrix,StrandReadMatrix,ChrTable'
ideogramPlot(WatsonFreqList,
             CrickFreqList, chrTable, plotBy = "lib", sizeProportional = NULL,
             showPage = NULL, orderFrame = NULL, orientationData = NULL,
             verbose = TRUE)
```

Arguments

<code>WatsonFreqList</code>	data.frame of Watson calls. Product of <code>strandSeqFreqTable[[3]]</code> when <code>BAITtables=TRUE</code>
<code>CrickFreqList</code>	data.frame of Crick calls. Product of <code>strandSeqFreqTable[[4]]</code> when <code>BAITtables=TRUE</code>
<code>chrTable</code>	A data.frame consisting of chromosomes and lengths. Generated by <code>makeChrTable()</code> . Note rownames equal to chromosome names are required
<code>plotBy</code>	Whether to generate a plot for each library ('lib') or a plot for each chromosome ('chr')
<code>sizeProportional</code>	The plotter will divide each fragment into a discrete number of bins of size <code>sizeProportional</code> and distribute reads across them. For example, when set to 200000, the all contigs in each linkage group will be split into 200kb fragments and each fragment will have an equal proportion of the reads derived from that fragment. This ultimately rescales the ideograms such that LGs with the greatest DNA content are the biggest, as opposed to teh LGs with the most contigs. Default value is <code>NULL</code>
<code>showPage</code>	Integer specifying which LG (if <code>plotBy='chr'</code>) or libraries (if <code>plotBy='lib'</code>) to plot. Useful when not plotting to a file, or when wishing to subset data. Default is <code>NULL</code>
<code>orderFrame</code>	ordered data.frame of contigs (produced by <code>orderAllLinkageGroups</code>). Default is <code>FALSE</code> , where plots will be made from elements in <code>chrTable</code> .
<code>orientationData</code>	<code>ChrTable</code> of contig orientations telling which reads to flip Watson and Crick counts
<code>verbose</code>	prints messages to the terminal (default is <code>TRUE</code>)

Value

ordered contigs in bed format. Depending on options, intermediate files and plots will also be generated

Examples

```
data("exampleWatsonFreq")
data("exampleCrickFreq")
data('exampleDividedChr')

singleWatsonLibrary <- StrandReadMatrix(exampleWatsonFreq[,2, drop=FALSE])
singleCrickLibrary <- StrandReadMatrix(exampleCrickFreq[,2, drop=FALSE])

ideogramPlot(singleWatsonLibrary, singleCrickLibrary, exampleDividedChr)
```

LibraryGroupList-class

A class for storing library group calls for contigs

Description

This class is a list of lists, each primary list element is a chromosome/contig, and contains 2 sub-list elements: a list of 'Mostly Watson' and "Mostly Crick" library names.

Usage

```
LibraryGroupList(libraryGroups = list(), names = character())
```

Arguments

- | | |
|---------------|--|
| libraryGroups | a list of lists, with each primary list element representing a chromosome with two internal list elements; a character vector of mostly watson library names, and a character vector of mostly Crick library names |
| names | a vector of names of linkage groups |

Value

a LibraryGroupList

Examples

```
lg1 <- LinkageGroupList(list(a=c('library1', 'library2'), b=c('library3')), names=c('chr1_Mostly_Crick', 'chr1_Mostly_Watson'))
lg2 <- LinkageGroupList(list(a=c('library1'), b=c('library6', 'library4')), names=c('chr2_Mostly_Crick', 'chr2_Mostly_Watson'))
libList <- LibraryGroupList(list(lg1, lg2))
```

LinkageGroupList-class

A class for storing linkage group calls for contigs

Description

This class is simply a list of character strings containing the names of linkage groups.

Usage

```
LinkageGroupList(linkageGroups = list(), names = character())
```

Arguments

linkageGroups	a list of character vectors of names of contigs in each LG
names	a vector of names of linkage groups

Value

a LinkageGroupList

Examples

```
lgList <- LinkageGroupList(list(lg1=c('contig1', 'contig2'), lg2=c('contig3')),  
                           names=c('lg1', 'lg20'))
```

locateMisorient, GRanges-method

locateMisorient – function to identify libraries that have similar WC patterns on chromosomes

Description

locateMisorient – function to identify libraries that have similar WC patterns on chromosomes

Usage

```
## S4 method for signature 'GRanges'  
locateMisorient(compiledGrange, gapFile = NULL,  
                stateNum = 3, readCutOff = 40, verbose = TRUE)
```

Arguments

compiledGrange	A GRanges object consisting of read locations. Can be an individual file or the product of thoroughBed
gapFile	A GRanges object consisting of start and end locations of assembly gaps (default NULL)
stateNum	The number of expected strand states. Default is 3 (WW, WC and CC). Function may exhibit unusual behaviour if changed
readCutOff	The minimal number of reads required to make an accurate strand state call. Default is 40.
verbose	prints messages to the terminal (default is TRUE)

Value

a list of ChrTable objects. The first is a ChrTable of misorientations detected. The second is a ChrTable of chimera detected. Output can be used in downstream functions (strandSeqFreqTable)

makeBoxPlot,ChrTable,LinkageGroupList-method

makeBoxPlot – creates boxplot of contigs included in the analysis vs those excluded

Description

makeBoxPlot – creates boxplot of contigs included in the analysis vs those excluded

Usage

```
## S4 method for signature 'ChrTable,LinkageGroupList'
makeBoxPlot(chrTable, linkage.contigs)
```

Arguments

chrTable	A GRanges object consisting of contigs and positions. A meta column called 'names' must be present with names in the same format as those from linkage.contigs. Generated by makeChrTable().
linkage.contigs	A list of clustered contigs, generated by clusterContigs()

Value

a box plot of included and excluded contigs

Examples

```
#make an example barplot of data

data("exampleLGList")
data("exampleChrTable")
makeBoxPlot(exampleChrTable, exampleLGList)
```

makeChrTable

makeChrTable – Pulls out chromosome and length data from the header of a bam file

Description

`makeChrTable` – Pulls out chromosome and length data from the header of a bam file

Usage

```
makeChrTable(bamFile, splitFile = NULL, splitBy = NULL, verbose = TRUE)
```

Arguments

- | | |
|------------------------|---|
| <code>bamFile</code> | string of location of a bam file to extract header data from |
| <code>splitFile</code> | GRanges object (of type chr, start and end: no strand or meta columns) of locations in which to split the assembly, such as previously determined locations of contig chimerism |
| <code>splitBy</code> | integer determining the average size contigs should be split by |
| <code>verbose</code> | if FALSE, no messages appear on terminal |

Details

`makeChrTable` creates a table with chromosome name and chromosome length by extracting header data from the supplied bam file.

Value

a GRanges object of class ChrTable, containing information on the organism's chromosomes as extracted from the BAM file header.

Examples

```
#Get an example BAM file and generate a chromosome table featuring fragment names and lengths

example.bam <- list.files(file.path(system.file(package='contiBAIT'), 'extdata'), full.names=TRUE)[1]

chrTable <- makeChrTable(example.bam)
```

```

show(chrTable)

dividedChr <- makeChrTable(example.bam, splitBy=1000000)

show(dividedChr)

```

mapGapFromOverlap

mapGapFromOverlap – function to co-localize strand state changes with assembly gaps

Description

mapGapFromOverlap – function to co-localize strand state changes with assembly gaps

Usage

```
mapGapFromOverlap(sceFile, gapFile, chrTable, verbose = TRUE,
                  overlapNum = 4)
```

Arguments

sceFile	GRanges object of strand state change locations in BED format
gapFile	GRanges object of assembly gaps in BED format (can be downloaded from UCSC table browser)
chrTable	GRanges object of chromosome table (product of makeChrTable)
verbose	prints messages to the terminal (default is TRUE)
overlapNum	Minimal number of strand state changes that overlap with a gap before assembly is cut at that location

Value

a GRanges object of all contigs split by regions where the sceFile and gapFile GRanges objects overlap.

mergeFlankedLGs,LinkageGroupList,StrandStateMatrix-method

mergeFlankedLGs – searches for similarities at the ends of ordered linkage groups to chain groups together

Description

mergeFlankedLGs – searches for similarities at the ends of ordered linkage groups to chain groups together

22orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'  
mergeFlankedLGs(linkageGroupList,  
  strandStateMatrix, buildConsensus = 1, cluster = NULL,  
  clusterParam = NULL, similarityCutoff = 0.7, verbose = TRUE)
```

Arguments

linkageGroupList	List of ordered vectors containing names of contigs belonging to each LG, of type LinkageGroupList
strandStateMatrix	Table of type strandStateMatrix encompassing strand state for all contigs. Product of StrandSeqFreqTable.
buildConsensus	number of contigs to take at the end of the linkage group to build a consensus strand state. Default is 5
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
similarityCutoff	merge contigs that are more similar than this
verbose	Outputs information to the terminal. Default is TRUE.

Value

a list containing a revised LinkageGroupList with merged groups, if appropriate, and a StrandStateMatrix with contigs reoriented, if newly merged groups were in opposite orientations.

orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method
Function to call contig ordering algorithms iteratively across each linkage group element

Description

Function to call contig ordering algorithms iteratively across each linkage group element

Usage

```
## S4 method for signature  
## 'LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix'  
orderAllLinkageGroups(linkageGroupList,  
  strandStateMatrix, strandFreqMatrix, strandReadCount, whichLG = NULL,  
  saveOrdered = NULL, orderCall = "greedy", randomAttempts = 75,  
  nProcesses = 1, verbose = TRUE)
```

orderAllLinkageGroups,LinkageGroupList,StrandStateMatrix,StrandFreqMatrix,StrandReadMatrix-method23

Arguments

linkageGroupList	list of vectors, each specifying which contigs belong in which linkage group (product of clusterContigs)
strandStateMatrix	table of strand calls for all contigs (product of preprocessStrandTable)
strandFreqMatrix	table of W:C read proportions (used for QC) (product of strandSeqFreqTable[[1]])
strandReadCount	table of read counts (product of strandSeqFreqTable[[2]])
whichLG	vector of integers specifying the element(s) of linkageGroupList to be ordered (i.e. which specific linkage groups to try to order). Default is all LGs.
saveOrdered	Will return a pdf of heatmaps for each linkage group; String entered becomes the fileName (default is saveOrderedPDF=FALSE)
orderCall	currently either 'greedy' for greedy algorithm or 'TSP' for travelling salesperson algorithm (default is 'greedy')
randomAttempts	integer specifying number of iterations of either the Monte Carlo or the 2-opt TSP solver to identify the best ordering. Default is 75, but higher values (eg 1000) make more sense for the TSP.
nProcesses	number of processes to attempt ordering in parallel
verbose	Prints messages to the terminal. Default is TRUE

Value

a list containing a ContigOrdering object consisting of ordered contigs with linkage group names, a StrandStateList consisting of StrandStateMatrices for each LG, and a LinkageGroupList consisting of reordered contigs within each list element.

Examples

```
#Get a data.frame of ordered contigs from cells from the same organism, aligned to the same genome

data("exampleLGList")
data("exampleWCMATRIX")
data("exampleStrandFreq")
data("exampleReadCounts")
contigOrder <- orderAllLinkageGroups(exampleLGLIST, exampleWCMATRIX, exampleStrandFreq, exampleReadCounts)

show(contigOrder)

contigOrder <- orderAllLinkageGroups(exampleLGLIST, exampleWCMATRIX, exampleStrandFreq, exampleReadCounts, order
show(contigOrder)
```

<code>orderContigsGreedy</code>	<i>Function to order contigs within a single linkage group using a greedy algorithms Attempt to order contigs within</i>
---------------------------------	--

Description

Function to order contigs within a single linkage group using a greedy algorithms Attempt to order contigs within

Usage

```
orderContigsGreedy(linkageGroupReadTable, randomAttempts = 75,
nProcesses = 1, verbose = TRUE)
```

Arguments

<code>linkageGroupReadTable</code>	dataframe of strand calls (product of <code>combineZeroDists</code> or <code>preprocessStrandTable</code>)
<code>randomAttempts</code>	number of times to repeat the greedy algortihm with a random restart
<code>nProcesses</code>	number of processes to attempt ordering in parallel
<code>verbose</code>	whether to print verbose messages

Value

list of two members: 1) contig names in order, 2) the original data.frame entered into function correctly ordered

<code>orderContigsTSP</code>	<i>Attempt to order contigs within linkage groups using travelling salesperson algorithm</i>
------------------------------	--

Description

Attempt to order contigs within linkage groups using travelling salesperson algorithm

Usage

```
orderContigsTSP(linkageGroupReadTable, reps)
```

Arguments

<code>linkageGroupReadTable</code>	dataframe of strand calls (product of <code>combineZeroDists</code> or <code>preprocessStrandTable</code>)
<code>reps</code>	Number of repetitions for he 2-opt TSP solver algorithm

Value

list of two members: 1) contig names in order, 2) the original data.frame entered into function correctly ordered

plotContigOrder, ContigOrdering-method

Plot ordering of contigs within a single linkage group.

Description

Plot ordering of contigs within a single linkage group.

Usage

```
## S4 method for signature 'ContigOrdering'  
plotContigOrder(contigOrder, lg = "all",  
                 verbose = TRUE)
```

Arguments

contigOrder	matrix from orderAllContigs with the subdivided linkage groups and the names of the contigs to plot
lg	Integer specifying the linkage group by which to plot. Default is all
verbose	prints messages to the terminal (default is TRUE)

Value

A ggplot object (which will be plotted automatically if not assigned).

Examples

```
#Get a data.frame of ordered contigs from cells from the same organism, aligned to the same genome  
data("exampleContigOrder")  
plotContigOrder(exampleContigOrder[[1]], lg=1)
```

plotLGDistances,LinkageGroupList,StrandStateMatrix-method

plotLGDistances – plots a heatmap of the distances between linkage groups

Description

`plotLGDistances` – plots a heatmap of the distances between linkage groups

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'
plotLGDistances(object,
  allStrands, lg = "all", labels = TRUE, state = "all",
  alreadyOrdered = FALSE)
```

Arguments

<code>object</code>	<code>LinkageGroupList</code>
<code>allStrands</code>	<code>StrandStateMatrix</code> for all linkageGroups (usually reoriented by <code>reorientStrandTable</code>)
<code>lg</code>	='all' vector of integers to determine which linkage group(s) to plot. 'all' will calculate consensus strand calls for all linkage groups and plot them side by side (default it 'all')
<code>labels</code>	= <code>TRUE</code> if <code>TRUE</code> , contig names will be plotted on the axes
<code>state</code>	string denoting whether only homozygous states should be used ('homo'; just WW vs CC), if a comparison should be made between homozygous and heterozygous states only ('hetero'; just homo vs hetero), or if all three states ('all'; WW vs WC vs CC). Default is 'all'
<code>alreadyOrdered</code>	if <code>TRUE</code> , the function will assume that the <code>linkageGroupList</code> is already ordered and not create a dendrogram. Default is <code>FALSE</code>
...	additional parameters to pass to <code>heatmap.2</code>

Value

a heatmap of linkage group calls

Examples

```
data("exampleLGList")
data("exampleWCMatrix")

plotLGDistances(exampleLGList, exampleWCMatrix)
plotLGDistances(exampleLGList, exampleWCMatrix, lg=1)
```

plotWCdistribution,StrandFreqMatrix-method*Creates median distribution boxplots across all libraries and contigs*

Description

Creates median distribution boxplots across all libraries and contigs

Usage

```
## S4 method for signature 'StrandFreqMatrix'
plotWCdistribution(object, filterThreshold = 0.8)
```

Arguments

object	object of class StrandFreqMatrix (product of strandSeqFreqTable)
filterThreshold	numeric value used in assessing the threshold for homozygous strand calls. Default is 0.8.

Value

nothing, just plots.

Examples

```
data("exampleStrandFreq")
plotWCdistribution(exampleStrandFreq, filterThreshold=0.8)
```

preprocessStrandTable,StrandFreqMatrix-method*preprocessStrandTable – remove low quality libraries and contigs before attempting to build a genome*

Description

preprocessStrandTable – remove low quality libraries and contigs before attempting to build a genome

Usage

```
## S4 method for signature 'StrandFreqMatrix'
preprocessStrandTable(strandTable,
  strandTableThreshold = 0.8, filterThreshold = 0.8,
  orderMethod = "libsAndConc", lowQualThreshold = 0.9, verbose = TRUE,
  minLib = 10)
```

Arguments

<code>strandTable</code>	data.frame containing the strand table to use as input
<code>strandTableThreshold</code>	threshold at which to call a contig WW or CC rather than WC
<code>filterThreshold</code>	maximum number of libraries a contig can be NA or WC in
<code>orderMethod</code>	the method to order contigs. currently libsAndConc only option. Set to FALSE to not order contigs based on library quality
<code>lowQualThreshold</code>	background threshold at which to toss an entire library. If NULL, function will not make an overall assessment of library quality. Very chimeric assemblies can appear low quality across all libraries.
<code>verbose</code>	messages written to terminal
<code>minLib</code>	minimum number of libraries a contig must be present in to be included in the output

Value

A list of one matrix and three quality data.frames – 1: a matrix of WW/WC/WW calls for all contigs; 2: the quality of libraries used (based on frequencies outside expected ranges); 3: A data.frame of libraries that are of low quality and therefore excluded from analysis; 5: A ChrTable object containing contigs that are present as WC in more libraries than expected. These are excluded from the strandStateMatrix, but are potentially worth investigating for chimerism.

Examples

```
data("exampleStrandFreq")
strandStates <- preprocessStrandTable(exampleStrandFreq, lowQualThreshold=0.8)
show(strandStates[[1]]) # WW-WC-CC matrix
```

reorientAndMergeLGs,LinkageGroupList,StrandStateMatrix-method

reorientAndMergeLGs uses a simple dissimilarity to find misoriented fragments within linkage groups.

Description

`reorientAndMergeLGs` uses a simple dissimilarity to find misoriented fragments within linkage groups.

Usage

```
## S4 method for signature 'LinkageGroupList,StrandStateMatrix'
reorientAndMergeLGs(object,
  allStrands, cluster = NULL, clusterParam = NULL, similarityCutoff = 0.9,
  verbose = TRUE)
```

Arguments

object	List of vectors containing names of contigs belonging to each LG.
allStrands	Table of type strandStateMatrix encompassing strand state for all contigs. Product of StrandSeqFreqTable.
cluster	Number of times to recluster and take the consensus of. If NULL, clustering is run only once.
clusterParam	optional BiocParallelParam specifying cluster to use for parallel execution. When NULL, execution will be serial.
similarityCutoff	merge contigs that are more similar than this
verbose	Outputs information to the terminal. Default is TRUE.

Value

a list consisting of a strandStateMatrix (a reoriented version of allStrands), a ChrTable containing contig names and orientations, as '+' or '-' and a merged LinkageGroupList.

Examples

```
data(exampleLGList)
data(exampleWCMATRIX)

reorientedMatrix <- reorientAndMergeLGs(exampleLGLIST,
exampleWCMATRIX)

# Note that in this example data, everything is correctly oriented to
# to begin with, so all contigs come out as + orientation
```

show,ContigOrdering-method
show-methods

Description

Shows a ContigOrdering

Usage

```
## S4 method for signature 'ContigOrdering'
show(object)
```

Arguments

object	a ContigOrdering
--------	------------------

Value

nothing

show,LibraryGroupList-method
show-methods

Description

Shows a LibraryGroupList

Usage

```
## S4 method for signature 'LibraryGroupList'  
show(object)
```

Arguments

object a LibraryGroupList

Value

nothing

show,LinkageGroupList-method
show-methods

Description

Shows a LinkageGroupList

Usage

```
## S4 method for signature 'LinkageGroupList'  
show(object)
```

Arguments

object a LinkageGroupList

Value

nothing

show,OrientationFrame-method
show-methods

Description

Shows a OrientationFrame

Usage

```
## S4 method for signature 'OrientationFrame'  
show(object)
```

Arguments

object a OrientationFrame

Value

nothing

show,StrandFreqMatrix-method
show-methods

Description

Shows a StrandFreqMatrix

Usage

```
## S4 method for signature 'StrandFreqMatrix'  
show(object)
```

Arguments

object a StrandFreqMatrix

Value

nothing

show,StrandReadMatrix-method
show-methods

Description

Shows a StrandReadMatrix

Usage

```
## S4 method for signature 'StrandReadMatrix'  
show(object)
```

Arguments

object a StrandReadMatrix

Value

nothing

show,StrandStateList-method
show-methods

Description

Shows a StrandStateList

Usage

```
## S4 method for signature 'StrandStateList'  
show(object)
```

Arguments

object a StrandStateList

Value

nothing

```
show,StrandStateMatrix-method  
      show-methods
```

Description

Shows a StrandStateMatrix

Usage

```
## S4 method for signature 'StrandStateMatrix'  
show(object)
```

Arguments

object a StrandStateMatrix

Value

nothing

StrandFreqMatrix-class

A class for storing a matrix of frequencies of Watson to Crick reads for a set of contigs over several libraries

Description

The strand information stored in this object is the ratio of Watson to Crick reads mapping to each contig in each library (cell). This should fall within the range (-1,1). This class simply extends matrix, but with additional validity checking.

Usage

```
StrandFreqMatrix(counts = matrix(double()))
```

Arguments

counts a double matrix of read count ratios

Value

a StrandFreqMatrix

Examples

```
data("exampleWatsonFreq")
data("exampleCrickFreq")
frequencyMatrix <- sapply(1:ncol(exampleCrickFreq),
function(colNum){exampleCrickFreq[,colNum] / exampleWatsonFreq[,colNum]})

StrandFreqMatrix(frequencyMatrix)
```

StrandReadMatrix-class

A class for storing read counts for a set of contigs over several libraries

Description

The information stored in this class is simple read counts, so should be integers ≥ 0 .

Usage

```
StrandReadMatrix(counts = matrix(integer()))
```

Arguments

counts	an integer matrix of read counts
--------	----------------------------------

Value

a StrandReadMatrix

Examples

```
data("exampleWatsonFreq")
StrandReadMatrix(exampleWatsonFreq[, 2, drop=FALSE])
```

strandSeqFreqTable

strandSeqFreqTable – function to process bam files for contiBAIT

Description

strandSeqFreqTable – function to process bam files for contiBAIT

Usage

```
strandSeqFreqTable(bamFileList, fieldSep = ".", field = 1, qual = 0,
rmdup = TRUE, verbose = TRUE, filter = NULL, misorientations = NULL,
chimeras = NULL, tileChunk = 1e+05, pairedEnd = TRUE,
BAITtables = FALSE)
```

Arguments

bamFileList	vector containing the location of the bams file to be read
fieldSep	The field separator of the bam file to use to define the field. Default is ''
field	The field of the bam file name to use as an index (default is 1)
qual	Mapping quality threshold. Default is 0
rmdup	remove duplicates in output file. Default is TRUE
verbose	prints messages to the terminal (default is TRUE)
filter	additional file of type ChrTable (GRanges with a meta column titled 'name' determining contig name) to split chromosomes based on locations. If this parameter is NULL (default), a filter table will be automatically generated from the header of the first file in bamFileList.
misorientations	additional file of type ChrTable (GRanges with a meta column titled 'name' determining contig name) with putative misorientation locations. These location's reads are reversed in the regions of filter that they lie within. Product of locateMisorients[[1]]. Default is NULL
chimeras	additional file of type ChrTable (GRanges with a meta column titled 'name' determining contig name) with putative chimeric locations. These location's reads are masked in the regions of filter that they lie within, and are appended to the end of the output file. Product of locateMisorients[[2]]. Default is NULL
tileChunk	Number of reads to split bam files into (smaller number requires less RAM). Default is 100000.
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output
BAITtables	creates additional matrices in the returned list with just Watson and Crick read counts to be used in downstream BAIT plotting. Default is FALSE

Value

a list containing two matrices: a StrandFreqMatrix of W:C read frequencies, and a StrandReadMatrix of read counts

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);

example.dir <- file.path(system.file(package='contibAIT'), 'extdata')
bam.files <- dir(example.dir, full.names=TRUE)

strand.freq <- strandSeqFreqTable(bam.files, pairedEnd = FALSE)

show(strand.freq[[1]])
show(strand.freq[[2]])
```

StrandStateList-class *A class for storing StrandStateList lists for contigs*

Description

This class is a list of StrandStateMatrices, each a subset of the StrandStateMatrix split by linkagegroups

Usage

```
StrandStateList(strandGroupList = list(), names = character())
```

Arguments

strandGroupList	a list of StrandStateMatrix elements, with each primary element representing a StrandStateMatrix containing ordered contigs from a LinkageGroupList element
names	a vector of names of StrandStateMatrix elements

Value

a StrandStateList

StrandStateMatrix-class

A class for storing a data frame of discrete strand states of a set of contigs over several libraries

Description

The strand information stored in this object is a call of the strand state of each contig in each library. mapping to each contig in each library (cell). This should fall within the range (-1,1). This class simply extends matrix, but with additional validity checking.

Usage

```
StrandStateMatrix(states = matrix(integer()))
```

Arguments

states	an integer matrix of strand states by library
--------	---

Value

a StrandStateMatrix

Examples

```
StrandStateMatrix(matrix(ncol=2, c(1,3,1,2)))
```

thoroughBed, ANY, LibraryGroupList-method

thoroughBed – function to merge chromosomes from libraries that have the same strand states

Description

thoroughBed – function to merge chromosomes from libraries that have the same strand states

Usage

```
## S4 method for signature 'ANY,LibraryGroupList'
thoroughBed(bamFileList, relatedLibList,
            qual = 10, pairedEnd = TRUE, rmdup = TRUE, verbose = TRUE)
```

Arguments

bamFileList	vector containing the location of the bams file to be read
relatedLibList	list where each element contains all library names that show similar strand pattern. The product of findSimilarLibraries
qual	Mapping quality threshold. Default is 10
pairedEnd	Whether the bam files being read are in paired end format. Default is TRUE. Note, since paired reads will be the same direction, only first mate read of pair is used in output to reduce file size
rmdup	Logical as to whether to remove duplicate reads within each library. Default is TRUE.
verbose	prints messages to the terminal (default is TRUE)

Value

a GRanges object comprising merged directional reads from all libraries in relatedLibList.

Examples

```
#Get a list of BAM files containing libraries for cells from the same organism, aligned to the same genome
#In this case these are the example BAM files provided with the package (hence the call to system.file);
data("exampleLibList")
```

```
library(BiocParallel)

example.dir <- file.path(system.file(package='contiBAIT'), 'extdata')
```

```
exampleRange <- thoroughBed(example.dir, exampleLibList)
show(exampleRange)
```

writeBed,ANY,ChrTable,ContigOrdering-method
function to write contig order to BED file

Description

function to write contig order to BED file

Usage

```
## S4 method for signature 'ANY,ChrTable,ContigOrdering'
writeBed(chrTable, orientationData,
         contigOrder, libWeight = NULL, file = "contiBAIT_assembly.bed")
```

Arguments

chrTable	a GRanges object with a 'name' meta column matching contig names. Product of makeChrTable
orientationData	ChrTable of contig and strand (with rownames matching contig names). Product of reorientAndMergeLGs[[2]]
contigOrder	an object of type ContigOrdering with ordered Linkage Groups and contigs. Product of orderAllLinkageGroups
libWeight	average quality across all libraries for a contig
file	character string for bed file name to write

Value

NULL; BED file written to file

Examples

```
## Not run:

data("exampleDividedChr")

writeBed(exampleDividedChr,
        reorientedMatrix[[2]],
        contigOrder)

## End(Not run)
```

Index

```
* data
  exampleChrTable, 9
  exampleContigOrder, 9
  exampleCrickFreq, 9
  exampleDividedChr, 9
  exampleLGLList, 10
  exampleLibList, 10
  exampleReadCounts, 10
  exampleStrandFreq, 10
  exampleWatsonFreq, 10
  exampleWCMATRIX, 11

  BAIT, 3
  barplotLinkageGroupCalls
    (barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method),
    4
  barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method
    4
  barplotLinkageGroupCalls, LinkageGroupList, LinkageGroupList-method,
    (barplotLinkageGroupCalls, LinkageGroupList, ChrTable-method),
    4
  ChrTable (ChrTable-class), 5
  ChrTable-class, 5
  clusterContigs
    (clusterContigs, StrandStateMatrix-method)
    6
  clusterContigs, StrandStateMatrix, StrandStateMatrix-method
    (clusterContigs, StrandStateMatrix-method)
    6
  clusterContigs, StrandStateMatrix-method,
    6
  contIBAIT, 7
  ContigOrdering (ContigOrdering-class), 8
  ContigOrdering-class, 8
  exampleChrTable, 9
  exampleContigOrder, 9
  exampleCrickFreq, 9
  exampleDividedChr, 9

  exampleLGLList, 10
  exampleLibList, 10
  exampleReadCounts, 10
  exampleStrandFreq, 10
  exampleWatsonFreq, 10
  exampleWCMATRIX, 11

  findSexGroups
    (findSexGroups, LinkageGroupList, StrandStateMatrix-method),
    11
  findSexGroups, LinkageGroupList, StrandStateMatrix-method,
    11
  findSimilarLibraries
    (findSimilarLibraries, StrandStateMatrix, StrandReadMatrix),
    12
  findSimilarLibraries, StrandStateMatrix, StrandReadMatrix
    12
  fixLinkageGroups
    (fixLinkageGroups, ContigOrdering, StrandStateList, List),
    13
  fixLinkageGroups, ContigOrdering, StrandStateList, LinkageGroupList
    13
  flipOrderedLinkageGroups
    (flipOrderedLinkageGroups, ContigOrdering, StrandStateList, List),
    14
  flipOrderedLinkageGroups, ContigOrdering, StrandStateList, List
    14
  flipOrderedLinkageGroups-ContigOrdering-StrandStateList-method
    (flipOrderedLinkageGroups, ContigOrdering, StrandStateList),
    14
  highlightAssemblyErrors, 15
  highlightAssemblyErrors, highlightAssemblyErrors-GRanges-method
    (highlightAssemblyErrors), 15
```


StrandFreqMatrix-class, 33
StrandReadMatrix
 (StrandReadMatrix-class), 34
StrandReadMatrix-class, 34
strandSeqFreqTable, 34
StrandStateList
 (StrandStateList-class), 36
StrandStateList-class, 36
StrandStateMatrix
 (StrandStateMatrix-class), 36
StrandStateMatrix-class, 36

thoroughBed
 (thoroughBed, ANY, LibraryGroupList-method),
 37
thoroughBed, ANY, LibraryGroupList-method,
 37
thoroughBed, thoroughBed-LibraryGroupList-method
 (thoroughBed, ANY, LibraryGroupList-method),
 37

writeBed
 (writeBed, ANY, ChrTable, ContigOrdering-method),
 38
writeBed, ANY, ChrTable, ContigOrdering-method,
 38
writeBed-ChrTable-ContigOrdering-method
 (writeBed, ANY, ChrTable, ContigOrdering-method),
 38