

Package ‘maftools’

April 12, 2022

Type Package

Title Summarize, Analyze and Visualize MAF Files

Version 2.10.05

Date 2021-04-30

Maintainer Anand Mayakonda <anand_mt@hotmail.com>

Description Analyze and visualize Mutation Annotation Format (MAF) files from large scale sequencing studies. This package provides various functions to perform most commonly used analyses in cancer genomics and to create feature rich customizable visualizations with minimal effort.

License MIT + file LICENSE

URL <https://github.com/PoisonAlien/maftools>

BugReports <https://github.com/PoisonAlien/maftools/issues>

Depends R (>= 3.3)

Imports data.table, grDevices, methods, RColorBrewer, Rhtslib,
survival

Suggests berryFunctions, Biostrings, BSgenome,
BSgenome.Hsapiens.UCSC.hg19, GenomicRanges, IRanges, knitr,
mclust, MultiAssayExperiment, NMF, R.utils, RaggedExperiment,
rmarkdown, S4Vectors, pheatmap, curl

LinkingTo Rhtslib, zlibbioc

VignetteBuilder knitr

biocViews DataRepresentation, DNaseq, Visualization, DriverMutation,
VariantAnnotation, FeatureExtraction, Classification,
SomaticMutation, Sequencing, FunctionalGenomics, Survival

Encoding UTF-8

LazyData TRUE

NeedsCompilation no

RoxygenNote 7.1.1

SystemRequirements GNU make

git_url <https://git.bioconductor.org/packages/maftools>
git_branch RELEASE_3_14
git_last_commit 3e3625a
git_last_commit_date 2022-02-23
Date/Publication 2022-04-12
Author Anand Mayakonda [aut, cre] (<<https://orcid.org/0000-0003-1162-687X>>)

R topics documented:

annoVarToMaf	4
bamreadcounts	5
cancerhotspots	6
clinicalEnrichment	7
coBarplot	8
compareSignatures	10
coOncoplot	11
drugInteractions	14
estimateSignatures	15
extractSignatures	16
filterMaf	17
forestPlot	18
genesToBarcodes	19
genotypeMatrix	20
getClinicalData	21
getCytobandSummary	21
getFields	22
getGeneSummary	23
getSampleSummary	23
GISTIC-class	24
gisticBubblePlot	25
gisticChromPlot	26
gisticOncoPlot	27
icgcSimpleMutationToMAF	29
inferHeterogeneity	30
lollipopPlot	32
lollipopPlot2	34
MAF	36
MAF-class	37
maf2mae	37
mafbarplot	38
mafCompare	39
mafSummary	40
mafSurvGroup	41
mafSurvival	42
math.score	43
merge_mafs	44

mutCountMatrix	44
oncodrive	45
OncogenicPathways	47
oncoplot	48
oncostrip	52
pfamDomains	53
plotApobecDiff	54
plotCBSsegments	55
plotClusters	57
plotCophenetic	58
plotEnrichmentResults	58
plotmafSummary	59
plotOncodrive	61
PlotOncogenicPathways	62
plotProtein	63
plotSignatures	64
plotTiTv	65
plotVaf	66
prepareMutSig	68
rainfallPlot	69
read.maf	70
readGistic	72
sampleSwaps	73
setdiffMAF	74
signatureEnrichment	75
somaticInteractions	76
subsetMaf	78
survGroup	79
tcgaAvailable	80
tcgaCompare	81
tcgaDriverBP	82
tcgaLoad	83
titv	84
tmb	85
trinucleotideMatrix	85
vafCompare	87
write.GisticSummary	88
write.mafSummary	89
Index	90

annovarToMaf	<i>Converts annovar annotations into MAF.</i>
--------------	---

Description

Converts variant annotations from Annovar into a basic MAF.

Usage

```
annovarToMaf(
  annovar,
  Center = NULL,
  refBuild = "hg19",
  tsbCol = NULL,
  table = "refGene",
  ens2hugo = TRUE,
  basename = NULL,
  sep = "\t",
  MAFobj = FALSE,
  sampleAnno = NULL
)
```

Arguments

annovar	input annovar annotation file. Can be vector of multiple files.
Center	Center field in MAF file will be filled with this value. Default NA.
refBuild	NCBI_Build field in MAF file will be filled with this value. Default hg19.
tsbCol	column name containing Tumor_Sample_Barcode or sample names in input file.
table	reference table used for gene-based annotations. Can be 'ensGene' or 'refGene'. Default 'refGene'
ens2hugo	If 'table' is 'ensGene', setting this argument to 'TRUE' converts all ensemble IDs to hugo symbols.
basename	If provided writes resulting MAF file to an output file.
sep	field separator for input file. Default tab seperated.
MAFobj	If TRUE, returns results as an MAF object.
sampleAnno	annotations associated with each sample/Tumor_Sample_Barcode in input annovar file. If provided it will be included in MAF object. Could be a text file or a data.frame. Ideally annotation would contain clinical data, survival information and other necessary features associated with samples. Default NULL.

Details

Annovar is one of the most widely used Variant Annotation tools in Genomics. Annovar output is generally in a tabular format with various annotation columns. This function converts such annovar output files into MAF. This function requires that annovar was run with gene based annotation as a first operation, before including any filter or region based annotations. Please be aware that this function performs no transcript prioritization.

e.g, table_annoVar.pl example/ex1.avinput humandb/ -buildver hg19 -out myanno -remove -protocol (refGene),cytoBand,dbnsfp30a -operation (g),r,f -nastring NA

This function mainly uses gene based annotations for processing, rest of the annotation columns from input file will be attached to the end of the resulting MAF.

Value

MAF table.

References

Wang, K., Li, M. & Hakonarson, H. ANNOVAR: functional annotation of genetic variants from high-throughput sequencing data. Nucleic Acids Res 38, e164 (2010).

Examples

```
var.annoVar <- system.file("extdata", "variants.hg19_multianno.txt", package = "maftools")
var.annoVar.maf <- annoVarToMaf(annoVar = var.annoVar, Center = 'CSI-NUS', refBuild = 'hg19',
tsbCol = 'Tumor_Sample_Barcode', table = 'ensGene')
```

bamreadcounts

extract nucleotide counts for targeted variants from the BAM file.

Description

Given a BAM file and target loci, ‘bamreadcounts’ fetches readcounts for A, T, G, C, Ins, and Del. Function name is an homage to <https://github.com/genome/bam-readcount>

Usage

```
bamreadcounts(
  bam = NULL,
  loci = NULL,
  zerobased = FALSE,
  mapq = 10,
  sam_flag = 1024,
  op = NULL,
  fa = NULL,
  nthreads = 4
)
```

Arguments

<code>bam</code>	Input bam file(s). Required.
<code>loci</code>	Loci file. Can be a tsv file or a data.frame. First two columns should contain chromosome and position (by default assumes coordinates are 1-based)
<code>zerobased</code>	are coordinates zero-based. Default FALSE.
<code>mapq</code>	Map quality. Default 10
<code>sam_flag</code>	SAM FLAG to filter reads. Default 1024
<code>op</code>	Output file basename. Default parses from BAM file
<code>fa</code>	Indexed fasta file. If provided, extracts and adds reference base to the output tsv.
<code>nthreads</code>	Number of threads to use. Each BAM file will be launched on a separate thread. Works only on Unix and macOS.

cancerhotspots

Genotype known cancer hotspots from the tumor BAM file

Description

‘cancerhotspots’ allows rapid genotyping of known somatic variants from the tumor BAM files. This facilitates to get a quick overlook of known somatic hot-spots in a matter of minutes, without spending hours on variant calling and annotation. In simple words, it fetches nucleotide frequencies of known somatic hotspots and prioritizes them based on allele frequency. Output includes a browsable/sharable HTML report of candidate variants. Known cancerhotspots for both GRCh37 and GRCh38 assemblies (3180 variants) are included. This should be sufficient and cover most of the known driver genes/events. See Reference for details.

Usage

```
cancerhotspots(
  bam = NULL,
  refbuild = "GRCh37",
  mapq = 10,
  sam_flag = 1024,
  vaf = 0.05,
  t_depth = 30,
  t_alt_count = 8,
  op = NULL,
  fa = NULL,
  browse = FALSE
)
```

Arguments

bam	Input bam file. Required.
refbuild	Default "GRCh37". Can be "GRCh37", "GRCh38", "hg19", "hg38"
mapq	Map quality. Default 10
sam_flag	SAM FLAG to filter reads. Default 1024
vaf	VAF threshold. Default 0.05 [Variant filter]
t_depth	Depth of coverage threshold. Default 30 [Variant filter]
t_alt_count	Min. number of reads supporting tumor allele . Default 8 [Variant filter]
op	Output file basename. Default parses from BAM file
fa	Indexed fasta file. If provided, extracts and adds reference base to the output tsv.
browse	If TRUE opens the html file in browser

References

Chang MT, Asthana S, Gao SP, et al. Identifying recurrent mutations in cancer reveals widespread lineage diversity and mutational specificity. Nat Biotechnol. 2016;34(2):155-163. doi:10.1038/nbt.3391

clinicalEnrichment *Performs mutational enrichment analysis for a given clinical feature.*

Description

Performs pairwise and groupwise fisher exact tests to find differentially enriched genes for every factor within a clinical feature.

Usage

```
clinicalEnrichment(
  maf,
  clinicalFeature = NULL,
  annotationDat = NULL,
  minMut = 5,
  useCNV = TRUE,
  pathways = FALSE
)
```

Arguments

maf	MAF object
clinicalFeature	columns names from 'clinical.data' slot of MAF to be analysed for.
annotationDat	If MAF file was read without clinical data, provide a custom data.frame or a tsv file with a column containing Tumor_Sample_Barcodes along with clinical features. Default NULL.

<code>minMut</code>	Consider only genes with minimum this number of samples mutated. Default 5.
<code>useCNV</code>	whether to include copy number events if available. Default TRUE. Not applicable when ‘pathways = TRUE’
<code>pathways</code>	Summarize genes by pathways before comparing. Default ‘FALSE’

Details

Performs fishers test on 2x2 contingency table for WT/Mutants in group of interest vs rest of the sample. Odds Ratio indicate the odds of observing mutant in the group of interest compared to wild-type

Value

result list containing p-values

See Also

[plotEnrichmentResults](#)

Examples

```
## Not run:
laml.maf = system.file('extdata', 'tcga_laml.maf.gz', package = 'maftools')
laml.clin = system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools')
laml = read.maf(maf = laml.maf, clinicalData = laml.clin)
clinicalEnrichment(laml, 'FAB_classification')

## End(Not run)
```

coBarplot

Draw two barplots side by side for cohort comparision.

Description

Draw two barplots side by side for cohort comparision.

Usage

```
coBarplot(
  m1,
  m2,
  genes = NULL,
  orderBy = NULL,
  m1Name = NULL,
  m2Name = NULL,
  colors = NULL,
  normalize = TRUE,
  yLims = NULL,
```

```

borderCol = "gray",
titleSize = 1,
geneSize = 0.8,
showPct = TRUE,
pctSize = 0.7,
axisSize = 0.8,
showLegend = TRUE,
legendTxtSize = 1,
geneMar = 4
)

```

Arguments

m1	first MAF object
m2	second MAF object
genes	genes to be drawn. Default takes top 5 mutated genes.
orderBy	Order genes by mutation rate in ‘m1‘ or ‘m2‘. Default ‘NULL‘, keeps the same order of ‘genes‘
m1Name	optional name for first cohort
m2Name	optional name for second cohort
colors	named vector of colors for each Variant_Classification.
normalize	Default TRUE.
yLims	Default NULL. Auto estimates. Maximum values for ‘m1‘ and ‘m2‘ respectively
borderCol	Default gray
titleSize	Default 1
geneSize	Default 0.8
showPct	Default TRUE
pctSize	Default 0.7
axisSize	Default 0.8
showLegend	Default TRUE.
legendTxtSize	Default 0.8
geneMar	Default 4

Details

Draws two barplots side by side to display difference between two cohorts.

Value

Returns nothing. Just draws plot.

Examples

```
' ##Primary and Relapse APL
primary.apl <- system.file("extdata", "APL_primary.maf.gz", package = "maftools")
relapse.apl <- system.file("extdata", "APL_relapse.maf.gz", package = "maftools")
##Read mafs
primary.apl <- read.maf(maf = primary.apl)
relapse.apl <- read.maf(maf = relapse.apl)
##Plot
coBarplot(m1 = primary.apl, m2 = relapse.apl, m1Name = 'Primary APL', m2Name = 'Relapse APL')
dev.off()
```

compareSignatures

Compares identified denovo mutational signatures to known COSMIC signatures

Description

Takes results from [extractSignatures](#) and compares them known COSMIC signatures. Two COSMIC databases are used for comparisons - "legacy" which includes 30 signaures, and "SBS" - which includes updated/refined 65 signatures

Usage

```
compareSignatures(nmfRes, sig_db = "legacy", verbose = TRUE)
```

Arguments

nmfRes	results from extractSignatures
sig_db	can be legacy or SBS. Default legacy
verbose	Default TRUE

Details

SBS signature database was obtained from <https://www.synapse.org/#!Synapse:syn11738319.7>

Value

list containing cosine smilarities, aetiologies if available, and best match.

See Also

[trinucleotideMatrix](#) [extractSignatures](#) [plotSignatures](#)

coOncoplot

Draw two oncoplots side by side for cohort comparision.

Description

Draw two oncoplots side by side for cohort comparision.

Usage

```
coOncoplot(  
  m1,  
  m2,  
  genes = NULL,  
  m1Name = NULL,  
  m2Name = NULL,  
  clinicalFeatures1 = NULL,  
  clinicalFeatures2 = NULL,  
  annotationColor1 = NULL,  
  annotationColor2 = NULL,  
  annotationFontSize = 1.2,  
  sortByAnnotation1 = FALSE,  
  annotationOrder1 = NULL,  
  sortByAnnotation2 = FALSE,  
  annotationOrder2 = NULL,  
  sampleOrder1 = NULL,  
  sampleOrder2 = NULL,  
  additionalFeature1 = NULL,  
  additionalFeaturePch1 = 20,  
  additionalFeatureCol1 = "white",  
  additionalFeatureCex1 = 0.9,  
  additionalFeature2 = NULL,  
  additionalFeaturePch2 = 20,  
  additionalFeatureCol2 = "white",  
  additionalFeatureCex2 = 0.9,  
  sepwd_genes1 = 0.5,  
  sepwd_samples1 = 0.5,  
  sepwd_genes2 = 0.5,  
  sepwd_samples2 = 0.5,  
  colors = NULL,  
  removeNonMutated = TRUE,  
  anno_height = 2,  
  legend_height = 4,  
  geneNamefont = 0.8,  
  showSampleNames = FALSE,  
  SampleNamefont = 0.5,  
  barcode_mar = 1,  
  outer_mar = 3,
```

```

    gene_mar = 1,
    legendFontSize = 1.2,
    titleFontSize = 1.5,
    keepGeneOrder = FALSE,
    bgCol = "#CCCCCC",
    borderCol = "white"
)

```

Arguments

m1	first MAF object
m2	second MAF object
genes	draw these genes. Default plots top 5 mutated genes from two cohorts.
m1Name	optional name for first cohort
m2Name	optional name for second cohort
clinicalFeatures1	columns names from ‘clinical.data‘ slot of m1 MAF to be drawn in the plot. Default NULL.
clinicalFeatures2	columns names from ‘clinical.data‘ slot of m2 MAF to be drawn in the plot. Default NULL.
annotationColor1	list of colors to use for ‘clinicalFeatures1‘ Default NULL.
annotationColor2	list of colors to use for ‘clinicalFeatures2‘ Default NULL.
annotationFontSize	font size for annotations Default 1.2
sortByAnnotation1	logical sort oncomatrix (samples) by provided ‘clinicalFeatures1‘. Sorts based on first ‘clinicalFeatures1‘. Defaults to FALSE. column-sort
annotationOrder1	Manually specify order for annotations for ‘clinicalFeatures1‘. Works only for first value. Default NULL.
sortByAnnotation2	same as above but for m2
annotationOrder2	Manually specify order for annotations for ‘clinicalFeatures2‘. Works only for first value. Default NULL.
sampleOrder1	Manually speify sample names in m1 for oncolplot ordering. Default NULL.
sampleOrder2	Manually speify sample names in m2 for oncolplot ordering. Default NULL.
additionalFeature1	a vector of length two indicating column name in the MAF and the factor level to be highlighted.
additionalFeaturePch1	Default 20

```

additionalFeatureCol1
    Default "white"
additionalFeatureCex1
    Default 0.9
additionalFeature2
    a vector of length two indicating column name in the MAF and the factor level
    to be highlighted.
additionalFeaturePch2
    Default 20
additionalFeatureCol2
    Default "white"
additionalFeatureCex2
    Default 0.9
sepwd_genes1  Default 0.5
sepwd_samples1 Default 0.5
sepwd_genes2  Default 0.5
sepwd_samples2 Default 0.5
colors         named vector of colors for each Variant_Classification.
removeNonMutated
    Logical. If TRUE removes samples with no mutations in the oncoplot for better
    visualization. Default TRUE.
anno_height    Height of clinical margin. Default 2
legend_height  Height of legend margin. Default 4
geneNamefont   font size for gene names. Default 1
showSampleNames
    whether to show sample names. Default FALSE.
SampleNamefont font size for sample names. Default 0.5
barcode_mar    Margin width for sample names. Default 1
outer_mar      Margin width for outer. Default 3
gene_mar       Margin width for gene names. Default 1
legendFontSize font size for legend. Default 1.2
titleFontSize  font size for title. Default 1.5
keepGeneOrder  force the resulting plot to use the order of the genes as specified. Default FALSE
bgCol          Background grid color for wild-type (not-mutated) samples. Default gray -
    "#CCCCCC"
borderCol      border grid color for wild-type (not-mutated) samples. Default 'white'
```

Details

Draws two oncoplots side by side to display difference between two cohorts.

Value

Invisibly returns a list of sample names in their order of occurrences in M1 and M2 respectively.

Examples

```
' ##Primary and Relapse APL
primary.apl <- system.file("extdata", "APL_primary.maf.gz", package = "maftools")
relapse.apl <- system.file("extdata", "APL_relapse.maf.gz", package = "maftools")
##Read mafs
primary.apl <- read.maf(maf = primary.apl)
relapse.apl <- read.maf(maf = relapse.apl)
##Plot
coNcophat(m1 = primary.apl, m2 = relapse.apl, m1Name = 'Primary APL', m2Name = 'Relapse APL')
dev.off()
```

drugInteractions

Drug-Gene Interactions

Description

Checks for drug-gene interactions and druggable categories

Usage

```
drugInteractions(
  maf,
  top = 20,
  genes = NULL,
  plotType = "bar",
  drugs = FALSE,
  font_size = 0.8
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>top</code>	Top number genes to check for. Default 20
<code>genes</code>	Manually specify gene list
<code>plotType</code>	Can be bar, pie Default bar plot.
<code>drugs</code>	Check for known/reported drugs. Default FALSE
<code>font_size</code>	Default 0.8

Details

This function takes a list of genes and checks for known/reported drug-gene interactions or Drug-gable categories. All gene-drug interactions and drug claims are compiled from Drug Gene Interaction Database. See reference for details and cite it if you use this function.

References

Griffith, M., Griffith, O. L., Coffman, A. C., Weible, J. V., McMichael, J. F., Spies, N. C., et. al., 2013. DGIdb - Mining the druggable genome. *Nature Methods*.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
drugInteractions(maf = laml)
```

<code>estimateSignatures</code>	<i>Estimate number of signatures based on cophenetic correlation metric</i>
---------------------------------	---

Description

Estimate number of signatures based on cophenetic correlation metric

Usage

```
estimateSignatures(
  mat,
  nMin = 2,
  nTry = 6,
  nrun = 10,
  parallel = 4,
  pConstant = NULL,
  verbose = TRUE,
  plotBestFitRes = FALSE
)
```

Arguments

<code>mat</code>	Input matrix of dimension nx96 generated by trinucleotideMatrix
<code>nMin</code>	Minimum number of signatures to try. Default 2.
<code>nTry</code>	Maximum number of signatures to try. Default 6.
<code>nrun</code>	numeric giving the number of runs to perform for each value in range. Default 5
<code>parallel</code>	Default 4. Number of cores to use.
<code>pConstant</code>	A small positive value to add to the matrix. Use it ONLY if the functions throws an non-conformable arrays error
<code>verbose</code>	Default TRUE
<code>plotBestFitRes</code>	plots consensus heatmap for range of values tried. Default FALSE

Details

This function decomposes a non-negative matrix into n signatures. Extracted signatures are compared against 30 experimentally validated signatures by calculating cosine similarity. See <http://cancer.sanger.ac.uk/cosmic/signatures/> for details.

Value

a list with `NMF.rank` object and summary stats.

See Also

`plotCophenetic` `extractSignatures` `trinucleotideMatrix`

Examples

```
## Not run:
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.tnm <- trinucleotideMatrix(maf = laml, ref_genome = 'BSgenome.Hsapiens.UCSC.hg19', prefix = 'chr',
add = TRUE, useSyn = TRUE)
library("NMF")
laml.sign <- estimateSignatures(mat = laml.tnm, plotBestFitRes = FALSE, nMin = 2, nTry = 3, nrun = 2, pConstant = 0.01)

## End(Not run)
```

`extractSignatures` *Extract mutational signatures from trinucleotide context.*

Description

Decompose a matrix of 96 substitution classes into n signatures.

Usage

```
extractSignatures(
  mat,
  n = NULL,
  plotBestFitRes = FALSE,
  parallel = 4,
  pConstant = NULL
)
```

Arguments

<code>mat</code>	Input matrix of dimension nx96 generated by <code>trinucleotideMatrix</code>
<code>n</code>	decompose matrix into n signatures. Default NULL. Tries to predict best value for n by running NMF on a range of values and chooses based on cophenetic correlation coefficient.
<code>plotBestFitRes</code>	plots consensus heatmap for range of values tried. Default FALSE
<code>parallel</code>	Default 4. Number of cores to use.
<code>pConstant</code>	A small positive value to add to the matrix. Use it ONLY if the functions throws an non-conformable arrays error

Details

This function decomposes a non-negative matrix into n signatures.

Value

a list with decomposed scaled signatures, signature contributions in each sample and NMF object.

See Also

[trinucleotideMatrix](#) [plotSignatures](#) [compareSignatures](#)

Examples

```
## Not run:
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.tnm <- trinucleotideMatrix(maf = laml, ref_genome = 'BSgenome.Hsapiens.UCSC.hg19', prefix = 'chr',
add = TRUE, useSyn = TRUE)
library("NMF")
laml.sign <- extractSignatures(mat = laml.tnm, plotBestFitRes = FALSE, n = 2, pConstant = 0.01)

## End(Not run)
```

filterMaf

*Filter MAF objects***Description**

Filter MAF by genes or samples

Usage

```
filterMaf(maf, genes = NULL, tsb = NULL, isTCGA = FALSE)
```

Arguments

maf	an MAF object generated by read.maf
genes	remove these genes
tsb	remove these samples (Tumor Sample Barcodes)
isTCGA	FALSE

Value

Filtered object of class [MAF-class](#)

See Also

[subsetMaf](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "mafTools")
laml <- read.maf(maf = laml.maf)
#get rid of samples of interest
filterMaf(maf = laml, tsb = c("TCGA-AB-2830", "TCGA-AB-2804"))
#remove genes of interest
filterMaf(maf = laml, genes =c("TTN", "AHNAK2"))
```

forestPlot

Draw forest plot for differences between cohorts.

Description

Draw forest plot for differences between cohorts.

Usage

```
forestPlot(
  mafCompareRes,
  pVal = 0.05,
  fdr = NULL,
  color = c("maroon", "royalblue"),
  geneFontSize = 0.8,
  titleSize = 1.2,
  lineWidth = 1
)
```

Arguments

mafCompareRes	results from mafCompare
pVal	p-value threshold. Default 0.05.
fdr	fdr threshold. Default NULL. If provided uses adjusted pvalues (fdr).
color	vector of two colors for the lines. Default 'maroon' and 'royalblue'
geneFontSize	Font size for gene symbols. Default 0.8
titleSize	font size for titles. Default 1.2
lineWidth	line width for CI bars. Default 1

Details

Plots results from [link{mafCompare}](#) as a forest plot with x-axis as log10 converted odds ratio and differentially mutated genes on y-axis.

Value

Nothing

See Also[mafCompare](#)**Examples**

```
##Primary and Relapse APL
primary.apl <- system.file("extdata", "APL_primary.maf.gz", package = "maftools")
relapse.apl <- system.file("extdata", "APL_relapse.maf.gz", package = "maftools")
##Read mafs
primary.apl <- read.maf(maf = primary.apl)
relapse.apl <- read.maf(maf = relapse.apl)
##Perform analysis and draw forest plot.
pt.vs.rt <- mafCompare(m1 = primary.apl, m2 = relapse.apl, m1Name = 'Primary',
m2Name = 'Relapse', minMut = 5)
forestPlot(mafCompareRes = pt.vs.rt)
```

genesToBarcodes

*Extracts Tumor Sample Barcodes where the given genes are mutated.***Description**

Extracts Tumor Sample Barcodes where the given genes are mutated.

Usage

```
genesToBarcodes(maf, genes = NULL, justNames = FALSE, verbose = TRUE)
```

Arguments

maf	an MAF object generated by read.maf
genes	Hogo_Symbol for which sample names to be extracted.
justNames	if TRUE, just returns samples names instead of summarized tables.
verbose	Default TRUE

Value

list of data.tables with samples in which given genes are mutated.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
genesToBarcodes(maf = laml, genes = 'DNMT3A')
```

<code>genotypeMatrix</code>	<i>Creates a Genotype Matrix for every variant</i>
-----------------------------	--

Description

Creates a Genotype matrix using allele frequcies or by muatation status.

Usage

```
genotypeMatrix(
  maf,
  genes = NULL,
  tsb = NULL,
  includeSyn = FALSE,
  vafCol = NULL,
  vafCutoff = c(0.1, 0.75)
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>genes</code>	create matrix for only these genes. Define NULL
<code>tsb</code>	create matrix for only these tumor sample barcodes/samples. Define NULL
<code>includeSyn</code>	whether to include silent mutations. Default FALSE
<code>vafCol</code>	specify column name for vaf's. Default NULL. If not provided simply assumes all mutations are heterozygous.
<code>vafCutoff</code>	specify minimum and maximum vaf to define mutations as heterozygous. Default range 0.1 to 0.75. Mutations above maximum vafs are defined as homozygous.

Value

`matrix`

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
genotypeMatrix(maf = laml, genes = "RUNX1")
```

getClinicalData	<i>extract annotations from MAF object</i>
-----------------	--

Description

extract annotations from MAF object

Usage

```
getClinicalData(x)

## S4 method for signature 'MAF'
getClinicalData(x)
```

Arguments

x An object of class MAF

Value

annotations associated with samples in MAF

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
getClinicalData(x = laml)
```

getCytobandSummary	<i>extract cytoband summary from GISTIC object</i>
--------------------	--

Description

extract cytoband summary from GISTIC object

Usage

```
getCytobandSummary(x)

## S4 method for signature 'GISTIC'
getCytobandSummary(x)
```

Arguments

x An object of class GISTIC

Value

summarized gistic results by altered cytobands.

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")
lam1.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =
getCytobandSummary(lam1.gistic)
```

getFields

extract available fields from MAF object

Description

extract available fields from MAF object

Usage

```
getFields(x)

## S4 method for signature 'MAF'
getFields(x)
```

Arguments

x	An object of class MAF
---	------------------------

Value

Field names in MAF file

Examples

```
lam1.maf <- system.file("extdata", "tcga_lam1.maf.gz", package = "maftools")
lam1 <- read.maf(maf = lam1.maf)
getFields(x = lam1)
```

getGeneSummary	<i>extract gene summary from MAF or GISTIC object</i>
----------------	---

Description

extract gene summary from MAF or GISTIC object

Usage

```
getGeneSummary(x)

## S4 method for signature 'MAF'
getGeneSummary(x)

## S4 method for signature 'GISTIC'
getGeneSummary(x)
```

Arguments

x An object of class MAF or GISTIC

Value

gene summary table

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
getGeneSummary(laml)
```

getSampleSummary	<i>extract sample summary from MAF or GISTIC object</i>
------------------	---

Description

extract sample summary from MAF or GISTIC object

Usage

```
getSampleSummary(x)

## S4 method for signature 'MAF'
getSampleSummary(x)

## S4 method for signature 'GISTIC'
getSampleSummary(x)
```

Arguments

- x An object of class MAF or GISTIC

Value

sample summary table

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
getSampleSummary(x = laml)
```

GISTIC-class

Class GISTIC

Description

S4 class for storing summarized MAF.

Slots

data data.table of summarized GISTIC file.
cnv.summary table containing alterations per sample
cytoband.summary table containing alterations per cytoband
gene.summary table containing alterations per gene
cnMatrix character matrix of dimension n*m where n is number of genes and m is number of samples
numericMatrix numeric matrix of dimension n*m where n is number of genes and m is number of samples
gis.scores gistic.scores
summary table with basic GISTIC summary stats
classCode mapping between numeric values in numericMatrix and copy number events.

See Also

[getGeneSummary](#) [getSampleSummary](#) [getCytobandSummary](#)

gisticBubblePlot *Plot gistic results as a bubble plot*

Description

Plots significantly altered cytobands as a function of number samples in which it is altered and number genes it contains. Size of each bubble is according to -log10 transformed q values.

Usage

```
gisticBubblePlot(  
  gistic = NULL,  
  color = NULL,  
  markBands = NULL,  
  fdrCutOff = 0.1,  
  log_y = TRUE,  
  txtSize = 3  
)
```

Arguments

gistic	an object of class GISTIC generated by readGistic
color	colors for Amp and Del events.
markBands	any cytobands to label. Can be cytoband labels, or number of top bands to highlight. Default top 5 lowest q values.
fdrCutOff	fdr cutoff to use. Default 0.1
log_y	log10 scale y-axis (# genes affected). Default TRUE
txtSize	label size for bubbles.

Value

Nothing

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")  
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")  
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")  
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")  
laml.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =  
gisticBubblePlot(gistic = laml.gistic, markBands = "")
```

<i>gisticChromPlot</i>	<i>Plot gistic results along linearized chromosome</i>
------------------------	--

Description

A genomic plot with segments highlighting significant Amplifications and Deletion regions.

Usage

```
gisticChromPlot(
    gistic = NULL,
    fdrCutOff = 0.1,
    markBands = NULL,
    color = NULL,
    ref.build = "hg19",
    cytobandOffset = 0.01,
    txtSize = 0.8,
    cytobandTxtSize = 0.6,
    maf = NULL,
    mutGenes = NULL,
    y_lims = NULL,
    mutGenesTxtSize = 0.6
)
```

Arguments

<i>gistic</i>	an object of class GISTIC generated by <code>readGistic</code>
<i>fdrCutOff</i>	fdr cutoff to use. Default 0.1
<i>markBands</i>	any cytobands to label. Default top 5 lowest q values.
<i>color</i>	colors for Amp and Del events.
<i>ref.build</i>	reference build. Could be hg18, hg19 or hg38.
<i>cytobandOffset</i>	if scores.gistic file is given use this to adjust cytoband size.
<i>txtSize</i>	label size for labels
<i>cytobandTxtSize</i>	label size for cytoband
<i>maf</i>	an optional maf object
<i>mutGenes</i>	mutated genes from maf object to be highlighted
<i>y_lims</i>	Default NULL. A vector upper and lower y-axis limits
<i>mutGenesTxtSize</i>	Default 0.6

Value

nothing

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")
laml.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =
gisticChromPlot(laml.gistic)
```

gisticOncoPlot

Plot gistic results.

Description

takes output generated by `readGistic` and draws a plot similar to oncplot.

Usage

```
gisticOncoPlot(
  gistic = NULL,
  top = NULL,
  bands = NULL,
  showTumorSampleBarcodes = FALSE,
  gene_mar = 5,
  barcode_mar = 6,
  sepwd_genes = 0.5,
  sepwd_samples = 0.25,
  clinicalData = NULL,
  clinicalFeatures = NULL,
  sortByAnnotation = FALSE,
  sampleOrder = NULL,
  annotationColor = NULL,
  bandsToIgnore = NULL,
  removeNonAltered = TRUE,
  colors = NULL,
  SampleNameFontSize = 0.6,
  fontSize = 0.8,
  legendFontSize = 1.2,
  annotationFontSize = 1.2,
  borderCol = "white",
  bgCol = "#CCCCCC"
)
```

Arguments

<code>gistic</code>	an GISTIC object generated by <code>readGistic</code>
<code>top</code>	how many top cytobands to be drawn. defaults to all.
<code>bands</code>	draw oncplot for these bands. Default NULL.

```

showTumorSampleBarcodes
logical to include sample names.

gene_mar      Default 5
barcode_mar    Default 6
sepwd_genes   Default 0.5
sepwd_samples  Default 0.25
clinicalData   data.frame with columns containing Tumor_Sample_Barcodes and rest of columns
                with annotations.
clinicalFeatures
columns names from 'clinicalData' to be drawn in the plot. Default NULL.
sortByAnnotation
logical sort oncomatrix (samples) by provided 'clinicalFeatures'. Defaults to
FALSE. column-sort
sampleOrder     Manually specify sample names for oncolplot ordering. Default NULL.
annotationColor
list of colors to use for clinicalFeatures. Default NULL.
bandsToIgnore   do not show these bands in the plot Default NULL.
removeNonAltered
Logical. If TRUE removes samples with no mutations in the oncoplot for better
visualization. Default FALSE.
colors          named vector of colors Amp and Del events.
SampleNameFontSize
font size for sample names. Default 0.6
fontSize         font size for cytoband names. Default 0.8
legendFontSize  font size for legend. Default 1.2
annotationFontSize
font size for annotations. Default 1.2
borderCol       Default "white"
bgCol           Default "#CCCCCC"

```

Details

Takes gistic file as input and plots it as a matrix. Any desired annotations can be added at the bottom of the oncoplot by providing annotation

Value

None.

See Also

[oncostrip](#)

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")
lam1.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =
gisticOncoPlot(lam1.gistic)
```

icgcSimpleMutationToMAF

Converts ICGC Simple Somatic Mutation format file to MAF

Description

Converts ICGC Simple Somatic Mutation format file to Mutation Annotation Format. Basic fields are converted as per MAF specifications, rest of the fields are retained as in the input file. Ensemble gene IDs are converted to HGNC Symbols. Note that by default Simple Somatic Mutation format contains all affected transcripts of a variant resulting in multiple entries of the same variant in same sample. It is hard to choose a single affected transcript based on annotations alone and by default this program removes repeated variants as duplicated entries. If you wish to keep all of them, set removeDuplicatedVariants to FALSE.

Usage

```
icgcSimpleMutationToMAF(
  icgc,
  basename = NA,
  MAFObj = FALSE,
  clinicalData = NULL,
  removeDuplicatedVariants = TRUE,
  addHugoSymbol = FALSE
)
```

Arguments

icgc	Input data in ICGC Simple Somatic Mutation format. Can be gz compressed.
basename	If given writes to output file with basename.
MAFObj	If TRUE returns results as an MAF object.
clinicalData	Clinical data associated with each sample/Tumor_Sample_Barcode in MAF. Could be a text file or a data.frame. Default NULL.
removeDuplicatedVariants	removes repeated variants in a particular sample, mapped to multiple transcripts of same Gene. See Description. Default TRUE.
addHugoSymbol	If TRUE replaces ensemble gene IDs with Hugo_Symbols. Default FALSE.

Details

ICGC Simple Somatic Mutation format specification can be found here: <http://docs.icgc.org/submission/guide/icgc-simple-somatic-mutation-format/>

Value

tab delimited MAF file.

Examples

```
esca.icgc <- system.file("extdata", "simple_somatic_mutation.open.ESCA-CN.sample.tsv.gz", package = "maftools")
esca.maf <- icgcSimpleMutationToMAF(icgc = esca.icgc)
```

inferHeterogeneity *Clusters variants based on Variant Allele Frequencies (VAF).*

Description

takes output generated by `read.maf` and clusters variants to infer tumor heterogeneity. This function requires VAF for clustering and density estimation. VAF can be on the scale 0-1 or 0-100. Optionally if copy number information is available, it can be provided as a segmented file (e.g, from Circular Binary Segmentation). Those variants in copy number altered regions will be ignored.

Usage

```
inferHeterogeneity(
  maf,
  tsb = NULL,
  top = 5,
  vafCol = NULL,
  segFile = NULL,
  ignChr = NULL,
  minVaf = 0,
  maxVaf = 1,
  useSyn = FALSE,
  dirichlet = FALSE
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>tsb</code>	specify sample names (Tumor_Sample_Barcodes) for which clustering has to be done.
<code>top</code>	if <code>tsb</code> is <code>NULL</code> , uses top n number of most mutated samples. Defaults to 5.
<code>vafCol</code>	manually specify column name for vafs. Default looks for column ' <code>t_vaf</code> '

<code>segFile</code>	path to CBS segmented copy number file. Column names should be Sample, Chromosome, Start, End, Num_Probes and Segment_Mean (log2 scale).
<code>ignChr</code>	ignore these chromosomes from analysis. e.g, sex chromosomes chrX, chrY. Default NULL.
<code>minVaf</code>	filter low frequency variants. Low vaf variants maybe due to sequencing error. Default 0. (on the scale of 0 to 1)
<code>maxVaf</code>	filter high frequency variants. High vaf variants maybe due to copy number alterations or impure tumor. Default 1. (on the scale of 0 to 1)
<code>useSyn</code>	Use synonymous variants. Default FALSE.
<code>dirichlet</code>	Deprecated! No longer supported. uses nonparametric dirichlet process for clustering. Default FALSE - uses finite mixture models.

Details

This function clusters variants based on VAF to estimate univariate density and cluster classification. There are two methods available for clustering. Default using parametric finite mixture models and another method using nonparametric infinite mixture models (Dirichlet process).

Value

list of clustering tables.

References

- Chris Fraley and Adrian E. Raftery (2002) Model-based Clustering, Discriminant Analysis and Density Estimation Journal of the American Statistical Association 97:611-631
- Jara A, Hanson TE, Quintana FA, Muller P, Rosner GL. DPpackage: Bayesian Semi- and Nonparametric Modeling in R. Journal of statistical software. 2011;40(5):1-30.
- Olshen AB, Venkatraman ES, Lucito R, Wigler M. Circular binary segmentation for the analysis of array-based DNA copy number data. Biostatistics. 2004;5(4):557-72.

See Also

[plotClusters](#)

Examples

```
## Not run:
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
TCGA.AB.2972.clust <- inferHeterogeneity(maf = laml, tsb = 'TCGA-AB-2972', vafCol = 'i_TumorVAF_WU')

## End(Not run)
```

lollipopPlot	<i>Draws lollipop plot of amino acid changes on to Protein structure.</i>
--------------	---

Description

Draws lollipop plot of amino acid changes. Protein domains are derived from PFAM database.

Usage

```
lollipopPlot(
  maf,
  gene = NULL,
  AACol = NULL,
  labelPos = NULL,
  labPosSize = 0.9,
  showMutationRate = TRUE,
  showDomainLabel = TRUE,
  cBioPortal = FALSE,
  refSeqID = NULL,
  proteinID = NULL,
  roundedRect = TRUE,
  repel = FALSE,
  collapsePosLabel = TRUE,
  showLegend = TRUE,
  legendTxtSize = 0.8,
  labPosAngle = 0,
  domainLabelSize = 0.8,
  axisTextSize = c(1, 1),
  printCount = FALSE,
  colors = NULL,
  domainAlpha = 1,
  domainBorderCol = "black",
  bgBorderCol = "black",
  labelOnlyUniqueDoamins = TRUE,
  defaultYaxis = FALSE,
  titleSize = c(1.2, 1),
  pointSize = 1.5
)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
gene	HGNC symbol for which protein structure to be drawn.
AACol	manually specify column name for amino acid changes. Default looks for fields 'HGVSp_Short', 'AAChange' or 'Protein_Change'. Changes can be of any format i.e, can be a numeric value or HGVSp annotations (e.g; p.P459L, p.L2195Pfs*30 or p.Leu2195ProfsTer30)

labelPos	Amino acid positions to label. If 'all', labels all variants.
labPosSize	Text size for labels. Default 0.9
showMutationRate	Whether to show the somatic mutation rate on the title. Default TRUE
showDomainLabel	Label domains within the plot. Default TRUE. If 'FALSE' domains are annotated in legend.
cBioPortal	Adds annotations similar to cBioPortals MutationMapper and collapse Variants into Truncating and rest.
refSeqID	RefSeq transcript identifier for gene if known.
proteinID	RefSeq protein identifier for gene if known.
roundedRect	Default TRUE. If 'TRUE' domains are drawn with rounded corners. Requires <code>berryFunctions</code>
repel	If points are too close to each other, use this option to repel them. Default FALSE. Warning: naive method, might make plot ugly in case of too many variants!
collapsePosLabel	Collapses overlapping labels at same position. Default TRUE
showLegend	Default TRUE
legendTxtSize	Text size for legend. Default 0.8
labPosAngle	angle for labels. Defaults to horizontal 0 degree labels. Set to 90 for vertical; 45 for diagonal labels.
domainLabelSize	text size for domain labels. Default 0.8
axisTextSize	text size x and y tick labels. Default c(1,1).
printCount	If TRUE, prints number of summarized variants for the given protein.
colors	named vector of colors for each Variant_Classification. Default NULL.
domainAlpha	Default 1
domainBorderCol	Default "black". Set to NA to remove.
bgBorderCol	Default "black". Set to NA to remove.
labelOnlyUniqueDoamins	Default TRUE only labels unique doamins.
defaultYaxis	If FALSE, just labels min and maximum y values on y axis.
titleSize	font size for title and subtitle. Default c(1.2, 1)
pointSize	size of lollipop heads. Default 1.5

Details

This function by default looks for fields 'HGVSp_Short', 'AAChange' or 'Protein_Change' in maf file. One can also manually specify field name containing amino acid changes.

Value

Nothing

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
lollipopPlot(maf = laml, gene = 'KIT', AACol = 'Protein_Change')
```

lollipopPlot2

Compare two lollipop plots

Description

Compare two lollipop plots

Usage

```
lollipopPlot2(
  m1,
  m2,
  gene = NULL,
  AACol1 = NULL,
  AACol2 = NULL,
  m1_name = NULL,
  m2_name = NULL,
  m1_label = NULL,
  m2_label = NULL,
  refSeqID = NULL,
  proteinID = NULL,
  labPosAngle = 0,
  labPosSize = 0.9,
  colors = NULL,
  alpha = 1,
  axisTextSize = c(1, 1),
  pointSize = 1.2,
  roundedRect = TRUE,
  showDomainLabel = TRUE,
  domainBorderCol = "black",
  domainLabelSize = 1,
  legendTxtSize = 1,
  verbose = TRUE
)
```

Arguments

m1	first MAF object
m2	second MAF object
gene	HGNC symbol for which protein structure to be drawn.
AACol1	manually specify column name for amino acid changes in m1. Default looks for fields 'HGVSp_Short', 'AAChange' or 'Protein_Change'.
AACol2	manually specify column name for amino acid changes in m2. Default looks for fields 'HGVSp_Short', 'AAChange' or 'Protein_Change'.
m1_name	name for m1 cohort. optional.
m2_name	name for m2 cohort. optional.
m1_label	Amino acid positions to label for m1 cohort. If 'all', labels all variants.
m2_label	Amino acid positions to label for m2 cohort. If 'all', labels all variants.
refSeqID	RefSeq transcript identifier for gene if known.
proteinID	RefSeq protein identifier for gene if known.
labPosAngle	angle for labels. Defaults to horizontal 0 degree labels. Set to 90 for vertical; 45 for diagonal labels.
labPosSize	Text size for labels. Default 3
colors	named vector of colors for each Variant_Classification. Default NULL.
alpha	color adjustment. Default 1
axisTxtSize	text size for axis labels. Default 1.
pointSize	size of lollipop heads. Default 1.2
roundedRect	Default FALSE. If 'TRUE' domains are drawn with rounded corners. Requires berryFunctions
showDomainLabel	Label domains within the plot. Default TRUE. If FALSE domains are annotated in legend.
domainBorderCol	Default "black". Set to NA to remove.
domainLabelSize	text size for domain labels. Default 1.
legendTxtSize	Default 1.
verbose	Default TRUE

Details

Draws lollipop plot for a gene from two cohorts

Value

invisible list of domain overlaps

See Also[lollipopPlot](#)[mafCompare](#)**Examples**

```
primary.apl <- system.file("extdata", "APL_primary.maf.gz", package = "maftools")
relapse.apl <- system.file("extdata", "APL_relapse.maf.gz", package = "maftools")
primary.apl <- read.maf(maf = primary.apl)
relapse.apl <- read.maf(maf = relapse.apl)
lollipopPlot2(m1 = primary.apl, m2 = relapse.apl, gene = "FLT3", AACol1 = "amino_acid_change", AACol2 = "amino_acid_
```

MAF

*Construct an MAF object***Description**

Constructor function which takes non-synonymous, and synonymous variants along with an optional clinical information and generates an MAF object

Usage

```
MAF(nonSyn = NULL, syn = NULL, clinicalData = NULL, verbose = TRUE)
```

Arguments

nonSyn	non-synonymous variants as a data.table or any object that can be coerced into a data.table (e.g: data.frame, GRanges)
syn	synonymous variants as a data.table or any object that can be coerced into a data.table (e.g: data.frame, GRanges)
clinicalData	Clinical data associated with each sample/Tumor_Sample_Barcode in MAF. Could be a text file or a data.frame. Requires at least a column with the name 'Tumor_Sample_Barcode' Default NULL.
verbose	Default TRUE

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml_dt = data.table::fread(input = laml.maf)
laml.clin = system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools') #Clinical data
# Just for demonstration
nsyn_vars = laml_dt[Variant_Classification %in% "Missense_Mutation"]
syn_vars = laml_dt[Variant_Classification %in% "Silent"]
maftools::MAF(nonSyn = nsyn_vars, syn = syn_vars, clinicalData = laml.clin)
```

MAF-class	<i>Class MAF</i>
-----------	------------------

Description

S4 class for storing summarized MAF.

Slots

data data.table of MAF file containing all non-synonymous variants.
variants.per.sample table containing variants per sample
variant.type.summary table containing variant types per sample
variant.classification.summary table containing variant classification per sample
gene.summary table containing variant classification per gene
summary table with basic MAF summary stats
maf.silent subset of main MAF containing only silent variants
clinical.data clinical data associated with each sample/Tumor_Sample_Barcode in MAF.

See Also

[getGeneSummary](#) [getSampleSummary](#) [getFields](#)

maf2mae	<i>Convert MAF to MultiAssayExperiment object</i>
---------	---

Description

Generates an object of class `MultiAssayExperiment` from MAF object

Usage

`maf2mae(m = NULL)`

Arguments

`m` an MAF object

Examples

```
laml.maf = system.file('extdata', 'tcga_laml.maf.gz', package = 'maftools')
laml.clin = system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools')
laml = read.maf(maf = laml.maf, clinicalData = laml.clin)
maf2mae(laml)
```

mafbarplot*Creates a bar plot*

Description

Takes an MAF object and generates a barplot of mutated genes color coded for variant classification

Usage

```
mafbarplot(
  maf,
  n = 20,
  genes = NULL,
  color = NULL,
  fontSize = 0.7,
  includeCN = FALSE,
  legendfontSize = 0.7,
  borderCol = "#34495e",
  showPct = TRUE
)
```

Arguments

<code>maf</code>	an MAF object
<code>n</code>	Number of genes to include. Default 20.
<code>genes</code>	Manually provide names of genes. Default NULL.
<code>color</code>	named vector of colors for each Variant_Classification. Default NULL.
<code>fontSize</code>	Default 0.7
<code>includeCN</code>	Include copy number events if available? Default FALSE
<code>legendfontSize</code>	Default 0.7
<code>borderCol</code>	Default "#34495e". Set to 'NA' for no border color.
<code>showPct</code>	Default TRUE. Show percent altered samples.

Examples

```
laml.maf = system.file("extdata", "tcga_laml.maf.gz", package = "maftools") #MAF file
laml = read.maf(maf = laml.maf)
mafbarplot(maf = laml)
```

mafCompare *compare two cohorts (MAF).*

Description

compare two cohorts (MAF).

Usage

```
mafCompare(  
  m1,  
  m2,  
  m1Name = NULL,  
  m2Name = NULL,  
  minMut = 5,  
  useCNV = TRUE,  
  pathways = FALSE,  
  custom_pw = NULL,  
  pseudoCount = FALSE  
)
```

Arguments

m1	first MAF object
m2	second MAF object
m1Name	optional name for first cohort
m2Name	optional name for second cohort
minMut	Consider only genes with minimum this number of samples mutated in atleast one of the cohort for analysis. Helpful to ignore single mutated genes. Default 5.
useCNV	whether to include copy number events. Default TRUE if available.. Not applicable when 'pathways = TRUE'
pathways	Summarize genes by pathways before comparing. Default 'FALSE'
custom_pw	Optional. Can be a two column data.frame/tsv-file with pathway-name and genes involved in them. Default 'NULL', uses a predefined list of pathways. Applicable only when 'pathways = TRUE'
pseudoCount	If TRUE, adds 1 to the contingency table with 0's to avoid 'Inf' values in the estimated odds-ratio.

Details

Performs fisher test on 2x2 contingency table generated from two cohorts to find differentially mutated genes.

Value

result list

See Also

[forestPlot](#)
[lollipopPlot2](#)

Examples

```
primary.apl <- system.file("extdata", "APL_primary.maf.gz", package = "maftools")
relapse.apl <- system.file("extdata", "APL_relapse.maf.gz", package = "maftools")
primary.apl <- read.maf(maf = primary.apl)
relapse.apl <- read.maf(maf = relapse.apl)
pt.vs.rt <- mafCompare(m1 = primary.apl, m2 = relapse.apl, m1Name = 'Primary',
m2Name = 'Relapse', minMut = 5)
```

mafSummary

Summary statistics of MAF

Description

Summarizes genes and samples irrespective of the type of alteration. This is different from [getSampleSummary](#) and [getGeneSummary](#) which returns summaries of only non-synonymous variants.

Usage

```
mafSummary(maf)
```

Arguments

maf	an MAF object generated by read.maf
-----	---

Details

This function takes MAF object as input and returns summary table.

Value

Returns a list of summarized tables

See Also

[getGeneSummary](#) [getSampleSummary](#)

Examples

```
lam1.maf <- system.file("extdata", "tcga_lam1.maf.gz", package = "maftools")
lam1 <- read.maf(maf = lam1.maf)
mafSummary(maf = lam1)
```

mafSurvGroup	<i>Performs survival analysis for a geneset</i>
--------------	---

Description

Similar to [mafSurvival](#) but for a geneset

Usage

```
mafSurvGroup(  
  maf,  
  geneSet = NULL,  
  minMut = NA,  
  clinicalData = NULL,  
  time = "Time",  
  Status = "Status"  
)
```

Arguments

maf	an MAF object generated by read.maf
geneSet	gene names for which survival analysis needs to be performed.
minMut	minimum number of mutated genes in the ‘geneSet’ to consider a sample as a mutant. Default, ‘NA’, samples with all the genes mutated are treated as mutant group.
clinicalData	dataframe containing events and time to events. Default looks for clinical data in annotation slot of MAF .
time	column name containing time in clinicalData
Status	column name containing status of patients in clinicalData . must be logical or numeric. e.g, TRUE or FALSE, 1 or 0.

Value

Survival plot

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")  
laml.clin <- system.file("extdata", "tcga_laml_annot.tsv", package = "maftools")  
laml <- read.maf(maf = laml.maf, clinicalData = laml.clin)  
mafSurvGroup(maf = laml, geneSet = c('DNMT3A', 'FLT3'), time = 'days_to_last_followup', Status = 'Overall_Survival')
```

mafSurvival	<i>Performs survival analysis</i>
-------------	-----------------------------------

Description

Performs survival analysis by grouping samples from maf based on mutation status of given gene(s) or manual grouping of samples.

Usage

```
mafSurvival(
  maf,
  genes = NULL,
  samples = NULL,
  clinicalData = NULL,
  time = "Time",
  Status = "Status",
  groupNames = c("Mutant", "WT"),
  showConfInt = TRUE,
  addInfo = TRUE,
  col = c("maroon", "royalblue"),
  isTCGA = FALSE,
  textSize = 12
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>genes</code>	gene names for which survival analysis needs to be performed. Samples with mutations in any one of the genes provided are used as mutants.
<code>samples</code>	samples to group by. Genes and samples are mutually exclusive.
<code>clinicalData</code>	dataframe containing events and time to events. Default looks for clinical data in annotation slot of MAF .
<code>time</code>	column name containing time in <code>clinicalData</code>
<code>Status</code>	column name containing status of patients in <code>clinicalData</code> . must be logical or numeric. e.g, TRUE or FALSE, 1 or 0.
<code>groupNames</code>	names for groups. Should be of length two. Default c("Mutant", "WT")
<code>showConfInt</code>	TRUE. Whether to show confidence interval in KM plot.
<code>addInfo</code>	TRUE. Whether to show survival info in the plot.
<code>col</code>	colors for plotting.
<code>isTCGA</code>	FALSE. Is data is from TCGA.
<code>textSize</code>	Text size for surv table. Default 7.

Details

This function takes MAF file and groups them based on mutation status associated with given gene(s) and performs survival analysis. Requires dataframe containing survival status and time to event. Make sure sample names match to Tumor Sample Barcodes from MAF file.

Value

Survival plot

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml.clin <- system.file("extdata", "tcga_laml_annot.tsv", package = "maftools")
laml <- read.maf(maf = laml.maf, clinicalData = laml.clin)
mafSurvival(maf = laml, genes = 'DNMT3A', time = 'days_to_last_followup', Status = 'Overall_Survival_Status', isTC
```

math.score

calculates MATH (Mutant-Allele Tumor Heterogeneity) score.

Description

calculates MATH scores from variant allele frequencies. Mutant-Allele Tumor Heterogeneity (MATH) score is a measure of intra-tumor genetic heterogeneity. High MATH scores are related to lower survival rates. This function requires vafs.

Usage

```
math.score(maf, vafCol = NULL, sampleName = NULL, vafCutOff = 0.075)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
vafCol	manually specify column name for vafs. Default looks for column 't_vaf'
sampleName	sample name for which MATH score to be calculated. If NULL, calculates for all samples.
vafCutOff	minimum vaf for a variant to be considered for score calculation. Default 0.075

Value

`data.table` with MATH score for every Tumor_Sample_Barcode

References

Mroz, Edmund A. et al. Intra-Tumor Genetic Heterogeneity and Mortality in Head and Neck Cancer: Analysis of Data from The Cancer Genome Atlas. Ed. Andrew H. Beck. PLoS Medicine 12.2 (2015): e1001786.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.math <- math.score(maf = laml, vafCol = 'i_TumorVAF_WU',
sampleName = c('TCGA-AB-3009', 'TCGA-AB-2849', 'TCGA-AB-3002', 'TCGA-AB-2972'))
```

`merge_mafs`

Merge multiple maf files into single MAF

Description

Merges multiple maf files/objects/data.frames into a single MAF.

Usage

```
merge_mafs(mafs, verbose = TRUE, ...)
```

Arguments

<code>mafs</code>	a list of MAF objects or data.frames or paths to MAF files.
<code>verbose</code>	Default TRUE
<code>...</code>	additional arguments passed read.maf

Value

[MAF](#) object

`mutCountMatrix`

Generates count matrix of mutations.

Description

Generates a count matrix of mutations. i.e, number of mutations per gene per sample.

Usage

```
mutCountMatrix(
  maf,
  includeSyn = FALSE,
  countOnly = NULL,
  removeNonMutated = TRUE
)
```

Arguments

<code>maf</code>	an MAF object generated by read.maf
<code>includeSyn</code>	whether to include synonymous variants in ouput matrix. Default FALSE
<code>countOnly</code>	Default NULL - counts all variants. You can specify type of 'Variant_Classification' to count. For e.g, <code>countOnly = 'Splice_Site'</code> will generates matrix for only Splice_Site variants.
<code>removeNonMutated</code>	Logical Default TRUE, removes samples with no mutations from the matrix.

Value

Integer Matrix

See Also

[getFields](#) [getGeneSummary](#) [getSampleSummary](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
##Generate matrix
mutCountMatrix(maf = laml)
##Generate count matrix of Splice_Site mutations
mutCountMatrix(maf = laml, countOnly = 'Splice_Site')
```

Description

Clusters variants based on their position to detect disease causing genes.

Usage

```
oncodrive(
  maf,
  AACol = NULL,
  minMut = 5,
  pvalMethod = "zscore",
  nBgGenes = 100,
  bgEstimate = TRUE,
  ignoreGenes = NULL
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>AACol</code>	manually specify column name for amino acid changes. Default looks for field 'AAChange'
<code>minMut</code>	minimum number of mutations required for a gene to be included in analysis. Default 5.
<code>pvalMethod</code>	either zscore (default method for oncodriveCLUST), poisson or combined (uses lowest of the two pvalues).
<code>nBgGenes</code>	minimum number of genes required to estimate background score. Default 100. Do not change this unless its necessary.
<code>bgEstimate</code>	If FALSE skips background estimation from synonymous variants and uses predefined values estimated from COSMIC synonymous variants.
<code>ignoreGenes</code>	Ignore these genes from analysis. Default NULL. Helpful in case data contains large number of variants belonging to polymorphic genes such as mucins and TTN.

Details

This is the re-implmentation of algorithm defined in OncodriveCLUST article. Concept is based on the fact that most of the variants in cancer causing genes are enriched at few specific loci (aka hotspots). This method takes advantage of such positions to identify cancer genes. Cluster score of 1 means, a single hotspot hosts all observed variants. If you use this function, please cite OncodriveCLUST article.

Value

data table of genes ordered according to p-values.

References

Tamborero D, Gonzalez-Perez A and Lopez-Bigas N. OncodriveCLUST: exploiting the positional clustering of somatic mutations to identify cancer genes. Bioinformatics. 2013; doi: 10.1093/bioinformatics/btt395s

See Also

[plotOncodrive](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.sig <- oncodrive(maf = laml, AACol = 'Protein_Change', minMut = 5)
```

OncogenicPathways	<i>Enrichment of known oncogenic pathways</i>
-------------------	---

Description

Checks for enrichment of known oncogenic pathways

Usage

```
OncogenicPathways(maf, pathways = NULL, fontSize = 1, panelWidths = c(2, 4, 4))
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>pathways</code>	Can be a two column data.frame/tsv-file with pathway-name and genes involved in them. Default ‘NULL’, uses a predefined list of pathways. See reference for details.
<code>fontSize</code>	Default 1
<code>panelWidths</code>	Default <code>c(2, 4, 4)</code>

Details

Oncogenic signalling pathways are derived from TCGA cohorts. See reference for details.

Value

Prints fraction of altered pathway

References

Sanchez-Vega F, Mina M, Armenia J, Chatila WK, Luna A, La KC, Dimitriadoy S, Liu DL, Kantheti HS, Saghafinia S et al. 2018. Oncogenic Signaling Pathways in The Cancer Genome Atlas. *Cell* 173: 321-337 e310

See Also

[PlotOncogenicPathways](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
OncogenicPathways(maf = laml)
```

oncoplot *draw an oncoplot*

Description

takes output generated by read.maf and draws an oncoplot

Usage

```
oncoplot(  
  maf,  
  top = 20,  
  minMut = NULL,  
  genes = NULL,  
  altered = FALSE,  
  drawRowBar = TRUE,  
  drawColBar = TRUE,  
  leftBarData = NULL,  
  leftBarLims = NULL,  
  rightBarData = NULL,  
  rightBarLims = NULL,  
  topBarData = NULL,  
  logColBar = FALSE,  
  includeColBarCN = TRUE,  
  clinicalFeatures = NULL,  
  annotationColor = NULL,  
  annotationDat = NULL,  
  pathways = NULL,  
  path_order = NULL,  
  selectedPathways = NULL,  
  pwLineCol = "#535c68",  
  pwLineWd = 1,  
  draw_titv = FALSE,  
  titv_col = NULL,  
  showTumorSampleBarcodes = FALSE,  
  barcode_mar = 4,  
  barcodeSrt = 90,  
  gene_mar = 5,  
  anno_height = 1,  
  legend_height = 4,  
  sortByAnnotation = FALSE,  
  groupAnnotationBySize = TRUE,  
  annotationOrder = NULL,  
  sortByMutation = FALSE,  
  keepGeneOrder = FALSE,  
  GeneOrderSort = TRUE,  
  sampleOrder = NULL,
```

```

additionalFeature = NULL,
additionalFeaturePch = 20,
additionalFeatureCol = "gray70",
additionalFeatureCex = 0.9,
genesToIgnore = NULL,
removeNonMutated = TRUE,
fill = TRUE,
cohortSize = NULL,
colors = NULL,
cBioPortal = FALSE,
bgCol = "#CCCCCC",
borderCol = "white",
annoBorderCol = NA,
numericAnnoCol = NULL,
drawBox = FALSE,
fontSize = 0.8,
SampleNameFontSize = 1,
titleFontSize = 1.5,
legendFontSize = 1.2,
annotationFontSize = 1.2,
sepwd_genes = 0.5,
sepwd_samples = 0.25,
writeMatrix = FALSE,
colbar_pathway = FALSE,
showTitle = TRUE,
titleText = NULL,
showPct = TRUE
)

```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>top</code>	how many top genes to be drawn. defaults to 20.
<code>minMut</code>	draw all genes with ‘min’ number of mutations. Can be an integer or fraction (of samples mutated), Default NULL
<code>genes</code>	Just draw oncplot for these genes. Default NULL.
<code>altered</code>	Default FALSE. Chooses top genes based on mutation status. If TRUE chooses top genes based alterations (CNV or mutation).
<code>drawRowBar</code>	logical. Plots right barplot for each gene. Default TRUE.
<code>drawColBar</code>	logical plots top barplot for each sample. Default TRUE.
<code>leftBarData</code>	Data for leftside barplot. Must be a data.frame with two columns containing gene names and values. Default ‘NULL’
<code>leftBarLims</code>	limits for ‘leftBarData’. Default ‘NULL’.
<code>rightBarData</code>	Data for rightside barplot. Must be a data.frame with two columns containing gene names and values. Default ‘NULL’ which draws distribution by variant classification. This option is applicable when only ‘drawRowBar’ is TRUE.

<code>rightBarLims</code>	limits for ‘rightBarData’. Default ‘NULL’.
<code>topBarData</code>	Default ‘NULL’ which draws absolute number of mutation load for each sample. Can be overridden by choosing one clinical indicator(Numeric) or by providing a two column data.frame containing sample names and values for each sample. This option is applicable when only ‘drawColBar’ is TRUE.
<code>logColBar</code>	Plot top bar plot on log10 scale. Default FALSE.
<code>includeColBarCN</code>	Whether to include CN in column bar plot. Default TRUE
<code>clinicalFeatures</code>	columns names from ‘clinical.data’ slot of MAF to be drawn in the plot. Default NULL.
<code>annotationColor</code>	Custom colors to use for ‘clinicalFeatures’. Must be a named list containing a named vector of colors. Default NULL. See example for more info.
<code>annotationDat</code>	If MAF file was read without clinical data, provide a custom data.frame with a column Tumor_Sample_Barcode containing sample names along with rest of columns with annotations. You can specify which columns to be drawn using ‘clinicalFeatures’ argument.
<code>pathways</code>	Default ‘NULL’. Can be ‘auto’, or a two column data.frame/tsv-file with genes and corresponding pathway mappings.‘
<code>path_order</code>	Default ‘NULL’ Manually specify the order of pathways
<code>selectedPathways</code>	Manually provide the subset of pathway names to be selected from ‘pathways’. Default NULL. In case ‘pathways’ is ‘auto’ draws top 3 altered pathways.
<code>pwLineCol</code>	Color for the box around the pathways Default #535c68
<code>pwLineWd</code>	Line width for the box around the pathways Default 1
<code>draw_titv</code>	logical Includes TiTv plot. FALSE
<code>titv_col</code>	named vector of colors for each transition and transversion classes. Should be of length six with the names "C>T" "C>G" "C>A" "T>A" "T>C" "T>G". Default NULL.
<code>showTumorSampleBarcodes</code>	logical to include sample names.
<code>barcode_mar</code>	Margin width for sample names. Default 4
<code>barcodeSrt</code>	Rotate sample labels. Default 90.
<code>gene_mar</code>	Margin width for gene names. Default 5
<code>anno_height</code>	Height of plotting area for sample annotations. Default 1
<code>legend_height</code>	Height of plotting area for legend. Default 4
<code>sortByAnnotation</code>	logical sort oncomatrix (samples) by provided ‘clinicalFeatures’. Sorts based on first ‘clinicalFeatures’. Defaults to FALSE. column-sort
<code>groupAnnotationBySize</code>	Further group ‘sortByAnnotation’ orders by their size. Defaults to TRUE. Largest groups comes first.

annotationOrder
Manually specify order for annotations. Works only for first ‘clinicalFeatures’. Default NULL.

sortByMutation Force sort matrix according mutations. Helpful in case of MAF was read along with copy number data. Default FALSE.

keepGeneOrder logical whether to keep order of given genes. Default FALSE, order according to mutation frequency

GeneOrderSort logical this is applicable when ‘keepGeneOrder’ is TRUE. Default TRUE

sampleOrder Manually speify sample names for oncoplot ordering. Default NULL.

additionalFeature
a vector of length two indicating column name in the MAF and the factor level to be highlighted. Provide a list of values for highlighting more than one features

additionalFeaturePch
Default 20

additionalFeatureCol
Default "gray70"

additionalFeatureCex
Default 0.9

genesToIgnore do not show these genes in Oncoplot. Default NULL.

removeNonMutated
Logical. If TRUE removes samples with no mutations in the oncoplot for better visualization. Default TRUE.

fill
Logical. If TRUE draws genes and samples as blank grids even when they are not altered.

cohortSize Number of sequenced samples in the cohort. Default all samples from Cohort. You can manually specify the cohort size. Default NULL

colors named vector of colors for each Variant_Classification.

cBioPortal Adds annotations similar to cBioPortals MutationMapper and collapse Variants into Truncating and rest.

bgCol Background grid color for wild-type (not-mutated) samples. Default gray - "#CCCCCC"

borderCol border grid color (not-mutated) samples. Default 'white'.

annoBorderCol border grid color for annotations. Default NA.

numericAnnoCol color palette used for numeric annotations. Default 'YlOrBr' from RColorBrewer

drawBox logical whether to draw a box around main matrix. Default FALSE

fontSize font size for gene names. Default 0.8.

SampleNameFontSize
font size for sample names. Default 1

titleFontSize font size for title. Default 1.5

legendFontSize font size for legend. Default 1.2

annotationFontSize
font size for annotations. Default 1.2

sepwd_genes size of lines seperating genes. Default 0.5
 sepwd_samples size of lines seperating samples. Default 0.25
 writeMatrix writes character coded matrix used to generate the plot to an output file.
 colbar_pathway Draw top column bar with respect to displayed pathway. Default FALSE.
 showTitle Default TRUE
 titleText Custom title. Default 'NULL'
 showPct Default TRUE. Shows percent altered to the right side of the plot.

Details

Takes maf file as input and plots it as a matrix. Any desired clinical features can be added at the bottom of the oncoplot by providing `clinicalFeatures`. Oncoplot can be sorted either by mutations or by `clinicalFeatures` using arguments `sortByMutation` and `sortByAnnotation` respectively.

Value

None.

See Also

[oncostrip](#)

Examples

```

laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml.clin = system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools')
laml <- read.maf(maf = laml.maf, clinicalData = laml.clin)
#Basic oncoplot
oncoplot(maf = laml, top = 3)
#Changing colors for variant classifications (You can use any colors, here in this example we will use a color palette
col = RColorBrewer::brewer.pal(n = 8, name = 'Paired')
names(col) = c('Frame_Shift_Del', 'Missense_Mutation', 'Nonsense_Mutation', 'Multi_Hit', 'Frame_Shift_Ins',
              'In_Frame_Ins', 'Splice_Site', 'In_Frame_Del')
#Color coding for FAB classification; try getAnnotations(x = laml) to see available annotations.
fabcolors = RColorBrewer::brewer.pal(n = 8, name = 'Spectral')
names(fabcolors) = c("M0", "M1", "M2", "M3", "M4", "M5", "M6", "M7")
fabcolors = list(FAB_classification = fabcolors)
oncoplot(maf = laml, colors = col, clinicalFeatures = 'FAB_classification', sortByAnnotation = TRUE, annotationCol = 1)
  
```

oncostrip

draw an oncostrip similar to cBioportal oncoprinter output.

Description

draw an oncostrip similar to cBioportal oncoprinter output.

Usage

```
oncostrip(maf = NULL, ...)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
...	arguments passed oncoplot

Details

This is just a wrapper around [oncoplot](#) with drawRowBar and drawColBar set to FALSE

Value

None.

See Also

[oncoplot](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
dev.new()
oncostrip(maf = laml, genes = c('NPM1', 'RUNX1'))
```

pfamDomains

pfam domain annotation and summarization.

Description

Summarizes amino acid positions and annotates them with pfam domain information.

Usage

```
pfamDomains(
  maf = NULL,
  AACol = NULL,
  summarizeBy = "AAPos",
  top = 5,
  domainsToLabel = NULL,
  baseName = NULL,
  varClass = "nonSyn",
  width = 5,
  height = 5,
  labelSize = 1
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>AACol</code>	manually specify column name for amino acid changes. Default looks for field 'AACode'
<code>summarizeBy</code>	Summarize domains by amino acid position or conversions. Can be "AAPos" or "AACode"
<code>top</code>	How many top mutated domains to label in the scatter plot. Defaults to 5.
<code>domainsToLabel</code>	Default NULL. Exclusive with top argument.
<code>baseName</code>	If given writes the results to output file. Default NULL.
<code>varClass</code>	which variants to consider for summarization. Can be nonSyn, Syn or all. Default nonSyn.
<code>width</code>	width of the file to be saved.
<code>height</code>	height of the file to be saved.
<code>labelSize</code>	font size for labels. Default 1.

Value

returns a list two tables summarized by amino acid positions and domains respectively. Also plots top 5 most mutated domains as scatter plot.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
pfamDomains(maf = laml, AACol = 'Protein_Change')
```

plotApobecDiff

Plot differences between APOBEC enriched and non-APOBEC enriched samples.

Description

Plots differences between APOBEC enriched and non-APOBEC enriched samples

Usage

```
plotApobecDiff(
  tnm,
  maf,
  pVal = 0.05,
  title_size = 1,
  axis_lwd = 1,
  font_size = 1.2
)
```

Arguments

tnm	output generated by trinucleotideMatrix
maf	an MAF object used to generate the matrix
pVal	p-value threshold for fisher's test. Default 0.05.
title_size	size of title. Default 1.3
axis_lwd	axis width. Default 1
font_size	font size. Default 1.2

Details

Plots differences between APOBEC enriched and non-APOBEC enriched samples (TCW). Plot includes differences in mutations load, tCw motif distribution and top genes altered.

Value

list of table containing differentially altered genes. This can be passed to [forestPlot](#) to plot results.

See Also

[trinucleotideMatrix](#) [plotSignatures](#)

Examples

```
## Not run:  
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")  
laml <- read.maf(maf = laml.maf)  
laml.tnm <- trinucleotideMatrix(maf = laml, ref_genome = 'BSgenome.Hsapiens.UCSC.hg19', prefix = 'chr',  
add = TRUE, useSyn = TRUE)  
plotApobecDiff(laml.tnm)  
  
## End(Not run)
```

plotCBSsegments

Plots segmented copy number data.

Description

Plots segmented copy number data.

Usage

```
plotCBSsegments(
  cbsFile = NULL,
  maf = NULL,
  tsb = NULL,
  savePlot = FALSE,
  ylims = NULL,
  seg_size = 0.1,
  width = 6,
  height = 3,
  genes = NULL,
  ref.build = "hg19",
  writeTable = FALSE,
  removeXY = FALSE,
  color = NULL
)
```

Arguments

<code>cbsFile</code>	CBS segmented copy number file. Column names should be Sample, Chromosome, Start, End, Num_Probes and Segment_Mean (log2 scale).
<code>maf</code>	optional MAF
<code>tsb</code>	If segmentation file contains many samples (as in gistic input), specify sample name here. Default plots head 1 sample. Set 'ALL' for plotting all samples. If you are mapping maf, make sure sample names in Sample column of segmentation file matches to those Tumor_Sample_Barcodes in MAF.
<code>savePlot</code>	If true plot is saved as pdf.
<code>ylims</code>	Default NULL
<code>seg_size</code>	Default 0.1
<code>width</code>	width of plot
<code>height</code>	height of plot
<code>genes</code>	If given and maf object is specified, maps all mutations from maf onto segments. Default NULL
<code>ref.build</code>	Reference build for chromosome sizes. Can be hg18, hg19 or hg38. Default hg19.
<code>writeTable</code>	If true and if maf object is specified, writes plot data with each variant and its corresponding copynumber to an output file.
<code>removeXY</code>	don not plot sex chromosomes.
<code>color</code>	Manually specify color scheme for chromosomes. Default NULL. i.e, alternating Gray70 and midnightblue

Details

this function takes segmented copy number data and plots it. If MAF object is specified, all mutations are highlighted on the plot.

Value

Draws plot

Examples

```
tcga.ab.009(seg <- system.file("extdata", "TCGA.AB.3009.hg19.seg.txt", package = "maftools")
plotCBSsegments(cbsFile = tcga.ab.009(seg))
```

plotClusters

Plot density plots from clustering results.

Description

Plots results from [inferHeterogeneity](#).

Usage

```
plotClusters(
  clusters,
  tsb = NULL,
  genes = NULL,
  showCNvars = FALSE,
  colors = NULL
)
```

Arguments

clusters	clustering results from inferHeterogeneity
tsb	sample to plot from clustering results. Default plots all samples from results.
genes	genes to highlight on the plot. Can be a vector of gene names, CN_altered to label copy number altered variants. or all to label all genes. Default NULL.
showCNvars	show copy numbered altered variants on the plot. Default FALSE.
colors	manual colors for clusters. Default NULL.

Value

returns nothing.

See Also

[inferHeterogeneity](#)

Examples

```
## Not run:
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
seg = system.file('extdata', 'TCGA.AB.3009.hg19.seg.txt', package = 'maftools')
TCGA.AB.3009.clust <- inferHeterogeneity(maf = laml, tsb = 'TCGA-AB-3009',
segFile = seg, vafCol = 'i_TumorVAF_WU')
plotClusters(TCGA.AB.3009.clust, genes = c('NF1', 'SUZ12'), showCNvars = TRUE)

## End(Not run)
```

plotCophenetic

Draw an elbow plot of cophenetic correlation metric.

Description

Draw an elbow plot of cophenetic correlation metric.

Usage

```
plotCophenetic(res = NULL, bestFit = NULL)
```

Arguments

res	output from estimateSignatures
bestFit	rank to highlight. Default NULL

Details

This function draws an elbow plot of cophenetic correlation metric.

See Also

[estimateSignatures](#) [plotCophenetic](#)

plotEnrichmentResults *Plots results from clinicalEnrichment analysis*

Description

Plots results from clinicalEnrichment analysis

Usage

```
plotEnrichmentResults(  
  enrich_res,  
  pVal = 0.05,  
  ORthr = 1,  
  featureLvls = NULL,  
  cols = NULL,  
  annoFontSize = 0.8,  
  geneFontSize = 0.8,  
  legendFontSize = 0.8,  
  showTitle = TRUE  
)
```

Arguments

enrich_res	results from clinicalEnrichment or signatureEnrichment
pVal	Default 0.05
ORthr	Default 1. Odds ratio threshold. >1 indicates positive enrichment in the group of interest.
featureLvls	Plot results from the selected levels. Default NULL, plots all.
cols	named vector of colors for factor in a clinical feature. Default NULL
annoFontSize	cex for annotation font size. Default 0.8
geneFontSize	cex for gene font size. Default 0.8
legendFontSize	cex for legend font size. Default 0.8
showTitle	Default TRUE

Value

returns nothing.

See Also

[clinicalEnrichment](#) [signatureEnrichment](#)

plotmafSummary

Plots maf summary.

Description

Plots maf summary.

Usage

```
plotmafSummary(
  maf,
  rmOutlier = TRUE,
  dashboard = TRUE,
  titvRaw = TRUE,
  log_scale = FALSE,
  addStat = NULL,
  showBarcodes = FALSE,
  fs = 1,
  textSize = 0.8,
  color = NULL,
  titleSize = c(1, 0.8),
  titvColor = NULL,
  top = 10
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>rmOutlier</code>	If TRUE removes outlier from boxplot.
<code>dashboard</code>	If FALSE plots simple summary instead of dashboard style.
<code>titvRaw</code>	TRUE. If false instead of raw counts, plots fraction.
<code>log_scale</code>	FALSE. If TRUE log10 transforms Variant Classification, Variant Type and Variants per sample sub-plots.
<code>addStat</code>	Can be either mean or median. Default NULL.
<code>showBarcodes</code>	include sample names in the top bar plot.
<code>fs</code>	base size for text. Default 1
<code>textSize</code>	font size if showBarcodes is TRUE. Default 0.8
<code>color</code>	named vector of colors for each Variant_Classification.
<code>titleSize</code>	font size for title and subtitle. Default c(10, 8)
<code>titvColor</code>	colors for SNV classifications.
<code>top</code>	include top n genes dashboard plot. Default 10.

Value

Prints plot.

See Also

[read.maf MAF](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf, useAll = FALSE)
plotmafSummary(maf = laml, addStat = 'median')
```

plotOncodrive	<i>Plots results from oncodrive</i>
---------------	-------------------------------------

Description

Takes results from oncodrive and plots them as a scatter plot. Size of the gene shows number of clusters (hotspots), x-axis can either be an absolute number of variants accumulated in these clusters or a fraction of total variants found in these clusters. y-axis is fdr values transformed into -log10 for better representation. Labels indicate Gene name with number clusters observed.

Usage

```
plotOncodrive(  
  res = NULL,  
  fdrCutOff = 0.05,  
  useFraction = FALSE,  
  colCode = NULL,  
  bubbleSize = 1,  
  labelSize = 1  
)
```

Arguments

res	results from oncodrive
fdrCutOff	fdr cutoff to call a gene as a driver.
useFraction	if TRUE uses a fraction of total variants as X-axis scale instead of absolute counts.
colCode	Colors to use for indicating significant and non-significant genes. Default NULL
bubbleSize	Size for bubbles. Default 2.
labelSize	font size for labelling genes. Default 1.

Value

Nothing

See Also

[oncodrive](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")  
laml <- read.maf(maf = laml.maf)  
laml.sig <- oncodrive(maf = laml, AACol = 'Protein_Change', minMut = 5)  
plotOncodrive(res = laml.sig, fdrCutOff = 0.1)
```

PlotOncogenicPathways *Plot oncogenic pathways*

Description

Plot oncogenic pathways

Usage

```
PlotOncogenicPathways(
  maf,
  pathways = NULL,
  fullPathway = FALSE,
  removeNonMutated = TRUE,
  tsgCol = "red",
  ogCol = "royalblue",
  fontSize = 0.6,
  showTumorSampleBarcodes = FALSE,
  sampleOrder = NULL,
  SampleNameFontSize = 0.6
)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
pathways	Name of pathways to be drawn
fullPathway	Include all genes from the pathway. Default FALSE only plots mutated genes
removeNonMutated	Default TRUE
tsgCol	Color for tumor suppressor genes. Default red
ogCol	Color for onco genes. Default royalblue
fontSize	Default 0.6
showTumorSampleBarcodes	logical to include sample names.
sampleOrder	Manually specify sample names for oncolplot ordering. Default NULL.
SampleNameFontSize	font size for sample names. Default 10

Details

Draws oncoplot of oncogenic pathway.

References

Sanchez-Vega F, Mina M, Armenia J, Chatila WK, Luna A, La KC, Dimitriadoy S, Liu DL, Kantheti HS, Saghafinia S et al. 2018. Oncogenic Signaling Pathways in The Cancer Genome Atlas. *Cell* 173: 321-337 e310

See Also[OncogenicPathways](#)**Examples**

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
PlotOncogenicPathways(maf = laml, pathways = "RTK-RAS")
```

plotProtein	<i>Display protein domains</i>
-------------	--------------------------------

Description

Display protein domains

Usage

```
plotProtein(
  gene,
  refSeqID = NULL,
  proteinID = NULL,
  domainAlpha = 0.9,
  showLegend = FALSE,
  bgBorderCol = "black",
  axisTextSize = c(1, 1),
  roundedRect = TRUE,
  domainBorderCol = "black",
  showDomainLabel = TRUE,
  domainLabelSize = 0.8,
  titleSize = c(1.2, 1),
  legendTxtSize = 1,
  legendNcol = 1
)
```

Arguments

gene	HGNC symbol for which protein structure to be drawn.
refSeqID	RefSeq transcript identifier for gene if known.
proteinID	RefSeq protein identifier for gene if known.
domainAlpha	Default 1
showLegend	Default TRUE
bgBorderCol	Default "black". Set to NA to remove.
axisTextSize	text size x and y tick labels. Default c(1,1).

```

roundedRect      Default TRUE. If ‘TRUE‘ domains are drawn with rounded corners. Requires
                 berryFunctions

domainBorderCol
                 Default "black". Set to NA to remove.

showDomainLabel
                 Default TRUE

domainLabelSize
                 text size for domain labels. Default 0.8

titleSize        font size for title and subtitle. Default c(1.2, 1)

legendTxtSize   Text size for legend. Default 0.8

legendNcol      Default 1

```

Examples

```

par(mfrow = c(2, 1))
plotProtein(gene = "KIT")
plotProtein(gene = "DNMT3A")

```

<i>plotSignatures</i>	<i>Plots decomposed mutational signatures</i>
-----------------------	---

Description

Takes results from [extractSignatures](#) and plots decomposed mutational signatures as a barplot.

Usage

```

plotSignatures(
  nmfRes = NULL,
  contributions = FALSE,
  color = NULL,
  patient_order = NULL,
  font_size = 1.2,
  show_title = TRUE,
  sig_db = "legacy",
  axis_lwd = 2,
  title_size = 0.9,
  show_barcodes = FALSE,
  yaxisLim = 0.3,
  ...
)

```

Arguments

nmfRes	results from extractSignatures
contributions	If TRUE plots contribution of signatures in each sample.
color	colors for each Ti/Tv conversion class. Default NULL
patient_order	User defined ordering of samples. Default NULL.
font_size	font size. Default 1.2
show_title	If TRUE compares signatures to COSMIC signatures and prints them as title
sig_db	Only applicable if show_title is TRUE. Can be legacy or SBS. Default legacy
axis_lwd	axis width. Default 2.
title_size	size of title. Default 1.3
show_barcodes	Default FALSE
yaxisLim	Default 0.3. If NA autoscales.
...	further plot options passed to barplot

Value

Nothing

See Also

[trinucleotideMatrix](#) [plotSignatures](#)

[plotTiTv](#)

Plot Transition and Trasnversion ratios.

Description

Takes results generated from `titv` and plots the Ti/Tv ratios and contributions of 6 mutational conversion classes in each sample.

Usage

```
plotTiTv(
  res = NULL,
  plotType = "both",
  sampleOrder = NULL,
  color = NULL,
  showBarcodes = FALSE,
  textSize = 0.8,
  baseFontSize = 1,
  axisTextSize = c(1, 1),
  plotNotch = FALSE
)
```

Arguments

<code>res</code>	results generated by titv
<code>plotType</code>	Can be 'bar', 'box' or 'both'. Defaults to 'both'
<code>sampleOrder</code>	Sample names in which the barplot should be ordered. Default NULL
<code>color</code>	named vector of colors for each conversion class.
<code>showBarcodes</code>	Whether to include sample names for barplot
<code>textSize</code>	fontsize if showBarcodes is TRUE. Default 2.
<code>baseFontSize</code>	font size. Default 1.
<code>axisTextSize</code>	text size x and y tick labels. Default c(1,1).
<code>plotNotch</code>	logical. Include notch in boxplot.

Value

None.

See Also

[titv](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.titv = titv(maf = laml, useSyn = TRUE)
plotTiTv(laml.titv)
```

plotVaf

Plots vaf distribution of genes

Description

Plots vaf distribution of genes as a boxplot. Each dot in the jitter is a variant.

Usage

```
plotVaf(
  maf,
  vafCol = NULL,
  genes = NULL,
  top = 10,
  orderByMedian = TRUE,
  keepGeneOrder = FALSE,
  flip = FALSE,
  fn = NULL,
```

```
    gene_fs = 0.8,  
    axis_fs = 0.8,  
    height = 5,  
    width = 5,  
    showN = TRUE,  
    color = NULL  
)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
vafCol	manually specify column name for vafs. Default looks for column 't_vaf'
genes	specify genes for which plots has to be generated
top	if genes is NULL plots top n number of genes. Defaults to 5.
orderByMedian	Orders genes by decreasing median VAF. Default TRUE
keepGeneOrder	keep gene order. Default FALSE
flip	if TRUE, flips axes. Default FALSE
fn	Filename. If given saves plot as a output pdf. Default NULL.
gene_fs	font size for gene names. Default 0.8
axis_fs	font size for axis. Default 0.8
height	Height of plot to be saved. Default 5
width	Width of plot to be saved. Default 4
showN	if TRUE, includes number of observations
color	manual colors. Default NULL.

Value

Nothing.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")  
laml <- read.maf(maf = laml.maf)  
plotVaf(maf = laml, vafCol = 'i_TumorVAF_WU')
```

prepareMutSig	<i>Prepares MAF file for MutSig analysis.</i>
---------------	---

Description

Corrects gene names for MutSig compatibility.

Usage

```
prepareMutSig(maf, fn = NULL)
```

Arguments

maf	an MAF object generated by read.maf
fn	basename for output file. If provided writes MAF to an output file with the given basename.

Details

MutSig/MutSigCV is most widely used program for detecting driver genes. However, we have observed that covariates files (gene.covariates.txt and exome_full192.coverage.txt) which are bundled with MutSig have non-standard gene names (non Hugo_Symbols). This discrepancy between Hugo_Symbols in MAF and non-Hugo_symbols in covariates file causes MutSig program to ignore such genes. For example, KMT2D - a well known driver gene in Esophageal Carcinoma is represented as MLL2 in MutSig covariates. This causes KMT2D to be ignored from analysis and is represented as an insignificant gene in MutSig results. This function attempts to correct such gene symbols with a manually curated list of gene names compatible with MutSig covariates list.

Value

returns a MAF with gene symbols corrected.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
prepareMutSig(maf = laml)
```

rainfallPlot*Rainfall plot to display hyper mutated genomic regions.*

Description

Plots inter variant distance as a function of genomic locus.

Usage

```
rainfallPlot(  
  maf,  
  tsb = NULL,  
  detectChangePoints = FALSE,  
  ref.build = "hg19",  
  color = NULL,  
  savePlot = FALSE,  
  width = 6,  
  height = 3,  
  fontSize = 1.2,  
  pointSize = 0.4  
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code> . Required.
<code>tsb</code>	specify sample names (Tumor_Sample_Barcodes) for which plotting has to be done. If NULL, draws plot for most mutated sample.
<code>detectChangePoints</code>	If TRUE, detects genomic change points where potential kataegis are formed. Results are written to an output tab delimited file.
<code>ref.build</code>	Reference build for chromosome sizes. Can be hg18, hg19 or hg38. Default hg19.
<code>color</code>	named vector of colors for each coversion class.
<code>savePlot</code>	If TRUE plot is saved to output pdf. Default FALSE.
<code>width</code>	width of plot to be saved.
<code>height</code>	height of plot to be saved.
<code>fontSize</code>	Default 12.
<code>pointSize</code>	Default 0.8.

Details

If ‘detectChangePoints“ is set to TRUE, this function will identify Kataegis loci. Kataegis detection algorithm by Moritz Goretzky at WWU Munster, which exploits the definition of Kataegis (six consecutive mutations with an avg. distance of 1000bp) to idetify hyper mutated genomic loci.

Algorithm starts with a double-ended queue to which six consecutive mutations are added and their average intermutation distance is calculated. If the average intermutation distance is larger than 1000, one element is added at the back of the queue and one is removed from the front. If the average intermutation distance is less or equal to 1000, further mutations are added until the average intermutation distance is larger than 1000. After that all mutations in the double-ended queue are written into output as one kataegis and the double-ended queue is reinitialized with six mutations.

Value

Results are written to an output file with suffix changePoints.tsv

read.maf

Read MAF files.

Description

Takes tab delimited MAF (can be plain text or gz compressed) file as an input and summarizes it in various ways. Also creates oncomatrix - helpful for visualization.

Usage

```
read.maf(
  maf,
  clinicalData = NULL,
  rmFlags = FALSE,
  removeDuplicatedVariants = TRUE,
  useAll = TRUE,
  gisticAllLesionsFile = NULL,
  gisticAmpGenesFile = NULL,
  gisticDelGenesFile = NULL,
  gisticScoresFile = NULL,
  cnLevel = "all",
  cnTable = NULL,
  isTCGA = FALSE,
  vc_nonSyn = NULL,
  verbose = TRUE
)
```

Arguments

- | | |
|---------------------|---|
| maf | tab delimited MAF file. File can also be gz compressed. Required. Alternatively, you can also provide already read MAF file as a dataframe. |
| clinicalData | Clinical data associated with each sample/Tumor_Sample_Barcodes in MAF. Could be a text file or a data.frame. Default NULL. |
| rmFlags | Default FALSE. Can be TRUE or an integer. If TRUE removes all the top 20 FLAG genes. If integer, remove top n FLAG genes. |

removeDuplicatedVariants	removes repeated variants in a particular sample, mapped to multiple transcripts of same Gene. See Description. Default TRUE.
useAll	logical. Whether to use all variants irrespective of values in Mutation_Status. Defaults to TRUE. If FALSE, only uses with values Somatic.
gisticAllLesionsFile	All Lesions file generated by gistic. e.g; all_lesions.conf_XX.txt, where XX is the confidence level. Default NULL.
gisticAmpGenesFile	Amplification Genes file generated by gistic. e.g; amp_genes.conf_XX.txt, where XX is the confidence level. Default NULL.
gisticDelGenesFile	Deletion Genes file generated by gistic. e.g; del_genes.conf_XX.txt, where XX is the confidence level. Default NULL.
gisticScoresFile	scores.gistic file generated by gistic. Default NULL
cnLevel	level of CN changes to use. Can be 'all', 'deep' or 'shallow'. Default uses all i.e, genes with both 'shallow' or 'deep' CN changes
cnTable	Custom copynumber data if gistic results are not available. Input file or a data.frame should contain three columns in aforementioned order with gene name, Sample name and copy number status (either 'Amp' or 'Del'). Default NULL.
isTCGA	Is input MAF file from TCGA source. If TRUE uses only first 12 characters from Tumor_Sample_Barcode.
vc_nonSyn	NULL. Provide manual list of variant classifications to be considered as non-synonymous. Rest will be considered as silent variants. Default uses Variant Classifications with High/Moderate variant consequences. https://www.ensembl.org/info/genome/variation/patterns/Frame_Shift_Del , "Frame_Shift_Ins", "Splice_Site", "Translation_Start_Site", "Nonsense_Mutation", "Nonstop_Mutation", "In_Frame_Del", "In_Frame_Ins", "Missense_Mutation"
verbose	TRUE logical. Default to be talkative and prints summary.

Details

This function takes MAF file as input and summarizes them. If copy number data is available, e.g from GISTIC, it can be provided too via arguments gisticAllLesionsFile, gisticAmpGenesFile, and gisticDelGenesFile. Copy number data can also be provided as a custom table containing Gene name, Sample name and Copy Number status.

Note that if input MAF file contains multiple affected transcripts of a variant, this function by default removes them as duplicates, while keeping single unique entry per variant per sample. If you wish to keep all of them, set removeDuplicatedVariants to FALSE.

FLAGS - If you get a note on possible FLAGS while reading MAF, it means some of the top mutated genes are fishy. These genes are often non-pathogenic and passengers, but are frequently mutated in most of the public exome studies. Examples of such genes include TTN, MUC16, etc. This note can be ignored without any harm, it's only generated as to make user aware of such genes. See references for details on FLAGS.

Value

An object of class MAF.

References

Shyr C, Tarailo-Graovac M, Gottlieb M, Lee JJ, van Karnebeek C, Wasserman WW. FLAGS, frequently mutated genes in public exomes. BMC Med Genomics 2014; 7: 64.

See Also

[plotmafSummary](#) [write.mafSummary](#)

Examples

```
laml.maf = system.file("extdata", "tcga_laml.maf.gz", package = "maftools") #MAF file
laml.clin = system.file('extdata', 'tcga_laml_annot.tsv', package = 'maftools') #clinical data
laml = read.maf(maf = laml.maf, clinicalData = laml.clin)
```

readGistic

Read and summarize gistic output.

Description

A little function to summarize gistic output files. Summarized output is returned as a list of tables.

Usage

```
readGistic(
  gisticAllLesionsFile = NULL,
  gisticAmpGenesFile = NULL,
  gisticDelGenesFile = NULL,
  gisticScoresFile = NULL,
  cnLevel = "all",
  isTCGA = FALSE,
  verbose = TRUE
)
```

Arguments

gisticAllLesionsFile

All Lesions file generated by gistic. e.g; all_lesions.conf_XX.txt, where XX is the confidence level. Required. Default NULL.

gisticAmpGenesFile

Amplification Genes file generated by gistic. e.g; amp_genes.conf_XX.txt, where XX is the confidence level. Default NULL.

gisticDelGenesFile

Deletion Genes file generated by gistic. e.g; del_genes.conf_XX.txt, where XX is the confidence level. Default NULL.

<code>gisticScoresFile</code>	scores.gistic file generated by gistic.
<code>cnLevel</code>	level of CN changes to use. Can be 'all', 'deep' or 'shallow'. Default uses all i.e, genes with both 'shallow' or 'deep' CN changes
<code>isTCGA</code>	Is the data from TCGA. Default FALSE.
<code>verbose</code>	Default TRUE

Details

Requires output files generated from GISTIC. Gistic documentation can be found here <ftp://ftp.broadinstitute.org/pub/GISTIC>

Value

A list of summarized data.

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")
laml.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =
```

sampleSwaps

Identify sample swaps and similarities

Description

Given a list BAM files, the function genotypes known SNPs and identifies potentially related samples. For the source of SNPs, see reference

Usage

```
sampleSwaps(
  bams = NULL,
  build = "hg19",
  prefix = NULL,
  add = TRUE,
  min_depth = 30,
  ncores = 4,
  ...
)
```

Arguments

bams	Input bam files. Required.
build	reference genome build. Default "hg19". Can be hg19 or hg38
prefix	Prefix to add or remove from contig names in SNP file. If BAM files are aligned GRCh37/38 genome, use prefix 'chr' to 'add'
add	If prefix is used, default is to add prefix to contig names in SNP file. If FALSE prefix will be removed from contig names.
min_depth	Minimum read depth for a SNP to be considered. Default 30.
ncores	Default 4. Each BAM file will be launched on a separate thread. Works only on Unix and macOS.
...	Additional arguments passed to bamreadcounts

Value

a list with results summarized

References

Westphal, M., Frankhouser, D., Sonzone, C. et al. SMaSH: Sample matching using SNPs in humans. *BMC Genomics* 20, 1001 (2019). <https://doi.org/10.1186/s12864-019-6332-7>

setdiffMAF*Set Operations for MAF objects***Description**

Set Operations for MAF objects

Usage

```
setdiffMAF(x, y, mafObj = TRUE, refAltMatch = TRUE, ...)
intersectMAF(x, y, refAltMatch = TRUE, mafObj = TRUE, ...)
```

Arguments

x	the first 'MAF' object.
y	the second 'MAF' object.
mafObj	Return output as an 'MAF' object. Default 'TRUE'
refAltMatch	Set operations are done by matching ref and alt alleles in addition to loci (Default). If FALSE only loci (chr, start, end positions) are matched.
...	other parameters passing to 'subsetMaf' for subsetting operations.

Value

subset table or an object of class [MAF-class](#). If no overlaps found returns ‘NULL’

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
x <- subsetMaf(maf = laml, tsb = c('TCGA-AB-3009'))
y <- subsetMaf(maf = laml, tsb = c('TCGA-AB-2933'))
setdiffMAF(x, y)
intersectMAF(x, y) #Should return NULL due to no common variants
```

signatureEnrichment	<i>Performs sample stratification based on signature contribution and enrichment analysis.</i>
---------------------	--

Description

Performs k-means clustering to assign signature to samples and performs enrichment analysis. Note
- Do not use this function. This will be removed in future updates.

Usage

```
signatureEnrichment(maf, sig_res, minMut = 5, useCNV = FALSE, fn = NULL)
```

Arguments

maf	an MAF object used for signature analysis.
sig_res	Signature results from extractSignatures
minMut	Consider only genes with minimum this number of samples mutated. Default 5.
useCNV	whether to include copy number events. Only applicable when MAF is read along with copy number data. Default TRUE if available.
fn	basename for output file. Default NULL.

Value

result list containing p-values

See Also

[plotEnrichmentResults](#)

somaticInteractions	<i>Exact tests to detect mutually exclusive, co-occurring and altered gene-sets.</i>
---------------------	--

Description

Performs Pair-wise Fisher's Exact test to detect mutually exclusive or co-occurring events.

Usage

```
somaticInteractions(
  maf,
  top = 25,
  genes = NULL,
  pvalue = c(0.05, 0.01),
  returnAll = TRUE,
  geneOrder = NULL,
  font_size = 0.8,
  showSigSymbols = TRUE,
  showCounts = FALSE,
  countStats = "all",
  countType = "all",
  countsFontSize = 0.8,
  countsFontColor = "black",
  colPal = "BrBG",
  showSum = TRUE,
  colNC = 9,
  nShiftSymbols = 5,
  sigSymbolsSize = 2,
  sigSymbolsFontSize = 0.9,
  pvSymbols = c(46, 42),
  limitColorBreaks = TRUE
)
```

Arguments

maf	an MAF object generated by <code>read.maf</code>
top	check for interactions among top 'n' number of genes. Defaults to top 25. genes
genes	List of genes among which interactions should be tested. If not provided, test will be performed between top 25 genes.
pvalue	Default c(0.05, 0.01) p-value threshold. You can provide two values for upper and lower threshold.
returnAll	If TRUE returns test statistics for all pair of tested genes. Default FALSE, returns for only genes below pvalue threshold.
geneOrder	Plot the results in given order. Default NULL.

fontSize cex for gene names. Default 0.8
 showSigSymbols Default TRUE. Hightlight significant pairs
 showCounts Default TRUE. Include number of events in the plot
 countStats Default ‘all’. Can be ‘all’ or ‘sig’
 countType Default ‘cooccur’. Can be ‘all’, ‘cooccur’, ‘mutexcl’
 countsFontSize Default 0.8
 countsFontColor Default ‘black’
 colPal colPalBrewer palettes. See RColorBrewer::display.brewer.all() for details
 showSum show [sum] with gene names in plot, Default TRUE
 colNC Number of different colors in the palette, minimum 3, default 9
 nShiftSymbols shift if positive shift SigSymbols by n to the left, default = 5
 sigSymbolsSize size of symbols in the matrix and in legend
 sigSymbolsFontSize size of font in legends
 pvSymbols vector of pch numbers for symbols of p-value for upper and lower thresholds
 c(upper, lower)
 limitColorBreaks limit color to extreme values. Default TRUE

Details

This function and plotting is inspired from genetic interaction analysis performed in the published study combining gene expression and mutation data in MDS. See reference for details.

Value

list of data.tables

References

Gerstung M, Pellagatti A, Malcovati L, et al. Combining gene mutation with gene expression data improves outcome prediction in myelodysplastic syndromes. Nature Communications. 2015;6:5901. doi:10.1038/ncomms6901.

Examples

```

laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
somaticInteractions(maf = laml, top = 5)

```

subsetMaf*Subset MAF objects*

Description

Subsets MAF based on given conditions.

Usage

```
subsetMaf(
  maf,
  tsb = NULL,
  genes = NULL,
  query = NULL,
  clinQuery = NULL,
  ranges = NULL,
  mult = "first",
  fields = NULL,
  mafObj = TRUE,
  includeSyn = TRUE,
  isTCGA = FALSE,
  dropLevels = TRUE,
  restrictTo = "all"
)
```

Arguments

<code>maf</code>	an MAF object generated by read.maf
<code>tsb</code>	subset by these samples (Tumor Sample Barcodes)
<code>genes</code>	subset by these genes
<code>query</code>	query string. e.g, "Variant_Classification == 'Missense_Mutation'" returns only Missense variants.
<code>clinQuery</code>	query by clinical variable.
<code>ranges</code>	subset by ranges. data.frame with 3 column (chr, start, end). Overlaps are identified by foverlaps function with arguments 'type = within', 'mult = all', 'no-match = NULL'
<code>mult</code>	When multiple loci in 'ranges' match to the variants maf, mult=. controls which values are returned - "all", "first" (default) or "last". This value is passed to 'mult' argument of foverlaps
<code>fields</code>	include only these fields along with necessary fields in the output
<code>mafObj</code>	returns output as MAF class MAF-class . Default TRUE
<code>includeSyn</code>	Default TRUE, only applicable when mafObj = FALSE. If mafObj = TRUE, synonymous variants will be stored in a seperate slot of MAF object.
<code>isTCGA</code>	Is input MAF file from TCGA source.

dropLevels	Default TRUE.
restrictTo	restrict subset operations to these. Can be 'all', 'cnv', or 'mutations'. Default 'all'. If 'cnv' or 'mutations', subset operations will only be applied on copy-number or mutation data respectively, while retaining other parts as is.

Value

subset table or an object of class [MAF-class](#)

See Also

[getFields](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
##Select all Splice_Site mutations from DNMT3A and NPM1
subsetMaf(maf = laml, genes = c('DNMT3A', 'NPM1'),
query = "Variant_Classification == 'Splice_Site'")
##Select all variants with VAF above 30%
subsetMaf(maf = laml, query = "i_TumorVAF_WU > 30")
##Extract data for samples 'TCGA.AB.3009' and 'TCGA.AB.2933' but only include vaf filed.
subsetMaf(maf = laml, tsb = c('TCGA-AB-3009', 'TCGA-AB-2933'), fields = 'i_TumorVAF_WU')
##Subset by ranges
ranges = data.frame(chr = c("2", "17"), start = c(25457000, 7571720), end = c(25458000, 7590868))
subsetMaf(laml, ranges = ranges)
```

survGroup

Predict genesets associated with survival

Description

Predict genesets associated with survival

Usage

```
survGroup(
  maf,
  top = 20,
  genes = NULL,
  geneSetSize = 2,
  minSamples = 5,
  clinicalData = NULL,
  time = "Time",
  Status = "Status",
  verbose = TRUE,
  plot = FALSE
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>top</code>	If genes is NULL by default used top 20 genes
<code>genes</code>	Manual set of genes
<code>geneSetSize</code>	Default 2
<code>minSamples</code>	minimum number of samples to be mutated to be considered for analysis. Default 5
<code>clinicalData</code>	dataframe containing events and time to events. Default looks for clinical data in annotation slot of MAF .
<code>time</code>	column name containing time in <code>clinicalData</code>
<code>Status</code>	column name containing status of patients in <code>clinicalData</code> . must be logical or numeric. e.g, TRUE or FALSE, 1 or 0.
<code>verbose</code>	Default TRUE
<code>plot</code>	Default FALSE If TRUE, generate KM plots of the genesets combinations.

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml.clin <- system.file("extdata", "tcga_laml_annot.tsv", package = "maftools")
laml <- read.maf(maf = laml.maf, clinicalData = laml.clin)
survGroup(maf = laml, top = 20, geneSetSize = 1, time = "days_to_last_followup", Status = "Overall_Survival_Status")
```

<code>tcgaAvailable</code>	<i>Prints available TCGA datasets</i>
----------------------------	---------------------------------------

Description

Prints available TCGA cohorts

Usage

```
tcgaAvailable(repo = c("github", "gitee"))
```

Arguments

`repo` can be "github" (default) or "gitee". If 'github' fails to fetch, switch to 'gitee'

See Also

[tcgaLoad](#)

Examples

```
tcgaAvailable()
```

`tcgaCompare`*Compare mutation load against TCGA cohorts*

Description

Compares mutation load in input MAF against all of 33 TCGA cohorts derived from MC3 project.

Usage

```
tcgaCompare(  
  maf,  
  capture_size = NULL,  
  tcga_capture_size = 35.8,  
  cohortName = NULL,  
  tcga_cohorts = NULL,  
  primarySite = FALSE,  
  col = c("gray70", "black"),  
  bg_col = c("#EDF8B1", "#2C7FB8"),  
  medianCol = "red",  
  decreasing = FALSE,  
  logscale = TRUE,  
  rm_hyper = FALSE,  
  rm_zero = TRUE,  
  cohortFontSize = 0.8,  
  axisFontSize = 0.8  
)
```

Arguments

<code>maf</code>	MAF object(s) generated by <code>read.maf</code>
<code>capture_size</code>	capture size for input MAF in MBs. Default NULL. If provided plot will be scaled to mutations per mb. TCGA capture size is assumed to be 35.8 mb.
<code>tcga_capture_size</code>	capture size for TCGA cohort in MB. Default 35.8. Do NOT change. See details for more information.
<code>cohortName</code>	name for the input MAF cohort. Default "Input"
<code>tcga_cohorts</code>	restrict tcga data to these cohorts.
<code>primarySite</code>	If TRUE uses primary site of cancer as labels instead of TCGA project IDs. Default FALSE.
<code>col</code>	color vector for length 2 TCGA cohorts and input MAF cohort. Default gray70 and black.
<code>bg_col</code>	background color. Default '#EDF8B1', '#2C7FB8'
<code>medianCol</code>	color for median line. Default red.
<code>decreasing</code>	Default FALSE. Cohorts are arranged in increasing mutation burden.

<code>logscale</code>	Default TRUE
<code>rm_hyper</code>	Remove hyper mutated samples (outliers)? Default FALSE
<code>rm_zero</code>	Remove samples with zero mutations? Default TRUE
<code>cohortFontSize</code>	Default 0.8
<code>axisFontSize</code>	Default 0.8

Details

Tumor mutation burden for TCGA cohorts is obtained from TCGA MC3 study. For consistency TMB is estimated by restricting variants within Agilent Sureselect capture kit of size 35.8 MB.

Value

`data.table` with median mutations per cohort

Source

TCGA MC3 file was obtained from <https://api.gdc.cancer.gov/data/1c8cfef5f-e52d-41ba-94da-f15ea1337efc>. See TCGAmutations R package for more details. Further downstream script to estimate TMB for each sample can be found in ‘inst/scripts/estimate_tcga_tmb.R’

References

Scalable Open Science Approach for Mutation Calling of Tumor Exomes Using Multiple Genomic Pipelines Kyle Ellrott, Matthew H. Bailey, Gordon Saksena, et. al. Cell Syst. 2018 Mar 28; 6(3): 271–281.e7. <https://doi.org/10.1016/j.cels.2018.03.002>

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
tcgaCompare(maf = laml, cohortName = "AML")
```

`tcgaDriverBP`

Compare genes to known TCGA drivers and their biological pathways

Description

A small function which uses known cancer driver genes and their associated pathways from TCGA cohorts. See reference for details

Usage

```
tcgaDriverBP(m, genes = NULL, top = 20, fontSize = 0.7)
```

Arguments

<code>m</code>	an MAF object
<code>genes</code>	genes to compare. Default ‘NULL’.
<code>top</code>	Top number of genes to use. Mutually exclusive with ‘genes’ argument. Default 20
<code>fontSize</code>	Default 0.7

References

Bailey MH, Tokheim C, Porta-Pardo E, et al. Comprehensive Characterization of Cancer Driver Genes and Mutations . Cell. 2018;173(2):371–385.e18. doi:10.1016/j.cell.2018.02.060

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
tcgaDriverBP(m = laml)
```

`tcgaLoad`

Loads a TCGA cohort

Description

Loads the user mentioned TCGA cohorts

Usage

```
tcgaLoad(
  study = NULL,
  source = c("MC3", "Firehose"),
  repo = c("github", "gitee")
)
```

Arguments

<code>study</code>	Study names to load. Use tcgaAvailable to see available options.
<code>source</code>	Source for MAF files. Can be MC3 or Firehose. Default MC3. Argument may be abbreviated (M or F)
<code>repo</code>	one of "github" (default) and "gitee".

Details

The function loads curated and pre-compiled MAF objects from TCGA cohorts. TCGA data are obtained from two sources namely, Broad Firehose repository, and MC3 project.

Value

An object of class MAF.

References

Scalable Open Science Approach for Mutation Calling of Tumor Exomes Using Multiple Genomic Pipelines Kyle Ellrott, Matthew H. Bailey, Gordon Saksena, et. al. Cell Syst. 2018 Mar 28; 6(3): 271–281.e7.

See Also

[tcgaAvailable](#)

Examples

```
# Loads TCGA LAML cohort (default from MC3 project)
tcgaLoad(study = "LAML")
# Loads TCGA LAML cohort (from Broad Firehose)
tcgaLoad(study = "LAML", source = "Firehose")
```

titv

Classifies SNPs into transitions and transversions

Description

takes output generated by `read.maf` and classifies Single Nucleotide Variants into Transitions and Transversions.

Usage

```
titv(maf, useSyn = FALSE, plot = TRUE, file = NULL)
```

Arguments

<code>maf</code>	an MAF object generated by read.maf
<code>useSyn</code>	Logical. Whether to include synonymous variants in analysis. Defaults to FALSE.
<code>plot</code>	plots a titv fractions. default TRUE.
<code>file</code>	basename for output file name. If given writes summaries to output file. Default NULL.

Value

list of data.frames with Transitions and Transversions summary.

See Also

[plotTiTv](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
laml.titv = titv(maf = laml, useSyn = TRUE)
```

tmb

Estimate Tumor Mutation Burden

Description

Estimates Tumor Mutation Burden in terms of per megabases

Usage

```
tmb(maf, captureSize = 50, logScale = TRUE)
```

Arguments

maf	maf MAF object
captureSize	capture size for input MAF in MBs. Default 50MB.
logScale	Default TRUE. For plotting purpose only.

Value

data.table with TMB for every sample

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
tmb(maf = laml)
```

trinucleotideMatrix *Extract single 5' and 3' bases flanking the mutated site for de-novo signature analysis. Also estimates APOBEC enrichment scores.*

Description

Extract single 5' and 3' bases flanking the mutated site for de-novo signature analysis. Also estimates APOBEC enrichment scores.

Usage

```
trinucleotideMatrix(
  maf,
  ref_genome = NULL,
  prefix = NULL,
  add = TRUE,
  ignoreChr = NULL,
  useSyn = TRUE,
  fn = NULL
)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>ref_genome</code>	BSgenome object or name of the installed BSgenome package. Example: <code>BSgenome.Hsapiens.UCSC.hg19</code> . Default <code>NULL</code> , tries to auto-detect from installed genomes.
<code>prefix</code>	Prefix to add or remove from contig names in MAF file.
<code>add</code>	If <code>prefix</code> is used, default is to add prefix to contig names in MAF file. If false <code>prefix</code> will be removed from contig names.
<code>ignoreChr</code>	Chromosomes to ignore from analysis. e.g. <code>chrM</code>
<code>useSyn</code>	Logical. Whether to include synonymous variants in analysis. Defaults to <code>TRUE</code>
<code>fn</code>	If given writes APOBEC results to an output file with basename <code>fn</code> . Default <code>NULL</code> .

Details

Extracts immediate 5' and 3' bases flanking the mutated site and classifies them into 96 substitution classes. Requires BSgenome data packages for sequence extraction.

APOBEC Enrichment: Enrichment score is calculated using the same method described by Roberts et al.

$$E = (n_{tcw} * \text{background}_c) / (n_C * \text{background}_{tcw})$$

where, `n_tcw` = number of mutations within T[C>T]W and T[C>G]W context. (W -> A or T)

`n_C` = number of mutated C and G

`background_C` and `background_tcw` motifs are number of C and TCW motifs occurring around +/- 20bp of each mutation.

One-sided Fisher's Exact test is performed to determine the enrichment of APOBEC tcw mutations over background.

Value

list of 2. A matrix of dimension `nx96`, where `n` is the number of samples in the MAF and a table describing APOBEC enrichment per sample.

References

Roberts SA, Lawrence MS, Klimczak LJ, et al. An APOBEC Cytidine Deaminase Mutagenesis Pattern is Widespread in Human Cancers. *Nature genetics*. 2013;45(9):970-976. doi:10.1038/ng.2702.

See Also

[extractSignatures](#) [plotApobecDiff](#)

Examples

```
## Not run:  
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")  
laml <- read.maf(maf = laml.maf)  
laml.tnm <- trinucleotideMatrix(maf = laml, ref_genome = 'BSgenome.Hsapiens.UCSC.hg19',  
prefix = 'chr', add = TRUE, useSyn = TRUE)  
  
## End(Not run)
```

vafCompare

compare VAF across two cohorts

Description

Draw boxplot distibution of VAFs across two cohorts

Usage

```
vafCompare(  
  m1,  
  m2,  
  genes = NULL,  
  top = 5,  
  vafCol1 = NULL,  
  vafCol2 = NULL,  
  m1Name = "M1",  
  m2Name = "M2",  
  cols = c("#2196F3", "#4CAF50"),  
  sigvals = TRUE,  
  nrows = NULL,  
  ncols = NULL  
)
```

Arguments

m1	first MAF object. Required.
m2	second MAF object. Required.
genes	specify genes for which plot has to be generated. Default NULL.

<code>top</code>	if genes is NULL plots top n number of genes. Defaults to 5.
<code>vafCol1</code>	manually specify column name for vafs in <code>m1</code> . Default looks for column ' <code>t_vaf</code> '
<code>vafCol2</code>	manually specify column name for vafs in <code>m2</code> . Default looks for column ' <code>t_vaf</code> '
<code>m1Name</code>	optional name for first cohort
<code>m2Name</code>	optional name for second cohort
<code>cols</code>	vector of colors corresponding to <code>m1</code> and <code>m2</code> respectively.
<code>sigvals</code>	Estimate and add significance stars. Default TRUE.
<code>nrows</code>	Number of rows in the layout. Default NULL - estimated automatically
<code>ncols</code>	Number of genes drawn per row. Default 4

`write.GisticSummary` *Writes GISTIC summaries to output tab-delimited text files.*

Description

Writes GISTIC summaries to output tab-delimited text files.

Usage

```
write.GisticSummary(gistic, basename = NULL)
```

Arguments

<code>gistic</code>	an object of class GISTIC generated by <code>readGistic</code>
<code>basename</code>	basename for output file to be written.

Value

None. Writes output as tab delimited text files.

See Also

[readGistic](#)

Examples

```
all.lesions <- system.file("extdata", "all_lesions.conf_99.txt", package = "maftools")
amp.genes <- system.file("extdata", "amp_genes.conf_99.txt", package = "maftools")
del.genes <- system.file("extdata", "del_genes.conf_99.txt", package = "maftools")
scores.gistic <- system.file("extdata", "scores.gistic", package = "maftools")
laml.gistic = readGistic(gisticAllLesionsFile = all.lesions, gisticAmpGenesFile = amp.genes, gisticDelGenesFile =
write.GisticSummary(gistic = laml.gistic, basename = 'laml')
```

`write.mafSummary` *Writes maf summaries to output tab-delimited text files.*

Description

Writes maf summaries to output tab-delimited text files.

Usage

```
write.mafSummary(maf, basename = NULL, compress = FALSE)
```

Arguments

<code>maf</code>	an MAF object generated by <code>read.maf</code>
<code>basename</code>	basename for output file to be written.
<code>compress</code>	If ‘TRUE‘ files will be gz compressed. Default ‘FALSE‘

Details

Writes MAF and related summaries to output files.

Value

None. Writes output as text files.

See Also

[read.maf](#)

Examples

```
laml.maf <- system.file("extdata", "tcga_laml.maf.gz", package = "maftools")
laml <- read.maf(maf = laml.maf)
write.mafSummary(maf = laml, basename = 'laml')
```

Index

annovarToMaf, 4
bamreadcounts, 5, 74
barplot, 65

cancerhotspots, 6
clinicalEnrichment, 7, 59
coBarplot, 8
compareSignatures, 10, 17
coOncoplot, 11

drugInteractions, 14

estimateSignatures, 15, 58
extractSignatures, 10, 16, 16, 64, 65, 75, 87

filterMaf, 17
forestPlot, 18, 40, 55
foverlaps, 78

genesToBarcodes, 19
genotypeMatrix, 20
getClinicalData, 21
getClinicalData, MAF-method
 (getClinicalData), 21
getCytobandSummary, 21, 24
getCytobandSummary, GISTIC-method
 (getCytobandSummary), 21
getFields, 22, 37, 45, 79
getFields, MAF-method (getFields), 22
getGeneSummary, 23, 24, 37, 40, 45
getGeneSummary, GISTIC-method
 (getGeneSummary), 23
getGeneSummary, MAF-method
 (getGeneSummary), 23
getSampleSummary, 23, 24, 37, 40, 45
getSampleSummary, GISTIC-method
 (getSampleSummary), 23
getSampleSummary, MAF-method
 (getSampleSummary), 23
GISTIC, 27

GISTIC (GISTIC-class), 24
GISTIC-class, 24
gisticBubblePlot, 25
gisticChromPlot, 26
gisticOncoPlot, 27

icgcSimpleMutationToMAF, 29
inferHeterogeneity, 30, 57
intersectMAF (setdiffMAF), 74

lollipopPlot, 32, 36
lollipopPlot2, 34, 40

MAF, 4, 7, 9, 12, 14, 19, 20, 29, 30, 32, 35, 36,
 38, 39, 41–44, 46, 47, 49, 53–56, 60,
 62, 67–69, 75, 76, 80, 81, 83–87, 89
MAF-class, 37
maf2mae, 37
mafbarplot, 38
mafCompare, 18, 19, 36, 39
mafSummary, 40
mafSurvGroup, 41
mafSurvival, 41, 42
math.score, 43
merge_mafs, 44
mutCountMatrix, 44

oncodrive, 45, 61
OncogenicPathways, 47, 63
oncoplot, 48, 53
oncostrip, 28, 52, 52

pfamDomains, 53
plotApobecDiff, 54, 87
plotCBSsegments, 55
plotClusters, 31, 57
plotCophenetic, 16, 58, 58
plotEnrichmentResults, 8, 58, 75
plotmafSummary, 59, 72
plotOncodrive, 46, 61
PlotOncogenicPathways, 47, 62

plotProtein, 63
plotSignatures, 10, 17, 55, 64, 65
plotTiTv, 65, 84
plotVaf, 66
prepareMutSig, 68

rainfallPlot, 69
read.maf, 14, 17, 19, 20, 30, 32, 40–47, 49,
54, 60, 62, 67–69, 70, 76, 78, 80, 81,
84, 86, 89
readGistic, 27, 72, 88

sampleSwaps, 73
setdiffMAF, 74
signatureEnrichment, 59, 75
somaticInteractions, 76
subsetMaf, 17, 78
survGroup, 79

tcgaAvailable, 80, 83, 84
tcgaCompare, 81
tcgaDriverBP, 82
tcgaLoad, 80, 83
titv, 66, 84
tmb, 85
trinucleotideMatrix, 10, 15–17, 55, 65, 85

vafCompare, 87

write.GisticSummary, 88
write.mafSummary, 72, 89