

Package ‘scHOT’

April 12, 2022

Type Package

Title single-cell higher order testing

Version 1.6.0

Description Single cell Higher Order Testing (scHOT) is an R package that facilitates testing changes in higher order structure of gene expression along either a developmental trajectory or across space. scHOT is general and modular in nature, can be run in multiple data contexts such as along a continuous trajectory, between discrete groups, and over spatial orientations; as well as accommodate any higher order measurement such as variability or correlation. scHOT meaningfully adds to first order effect testing, such as differential expression, and provides a framework for interrogating higher order interactions from single cell data.

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 4.0)

Imports S4Vectors (>= 0.24.3), SingleCellExperiment, Matrix, SummarizedExperiment, IRanges, methods, stats, BiocParallel, reshape, ggplot2, igraph, grDevices, ggforce, graphics

RoxygenNote 7.1.0

Suggests knitr, markdown, rmarkdown, scater, scattermore, scales, matrixStats, deldir

VignetteBuilder knitr

biocViews GeneExpression, RNASeq, Sequencing, SingleCell, Software, Transcriptomics

git_url <https://git.bioconductor.org/packages/scHOT>

git_branch RELEASE_3_14

git_last_commit daee27c

git_last_commit_date 2021-10-26

Date/Publication 2022-04-12

Author Shila Ghazanfar [aut, cre],
Yingxin Lin [aut]

Maintainer Shila Ghazanfar <shazanfar@gmail.com>

R topics documented:

liver	2
MOB_subset	3
params<-	3
plotColouredExpression	4
plotEgoNetwork	5
plotHigherOrderSequence	6
plotOrderedExpression	7
positionColData<-	8
positionType<-	9
scHOT	10
scHOT-class	12
scHOT_addTestingScaffold	13
scHOT_buildFromMatrix	13
scHOT_buildFromSCE	14
scHOT_calculateGlobalHigherOrderFunction	15
scHOT_calculateHigherOrderTestStatistics	16
scHOT_estimatePvalues	18
scHOT_output<-	19
scHOT_performPermutationTest	20
scHOT_plotPermutationDistributions	21
scHOT_setPermutationScaffold	22
scHOT_setWeightMatrix	23
scHOT_stripOutput	24
spatialWeightMatrix	25
testingScaffold<-	26
thin	26
trajectoryWeightMatrix	27
weightedPearson	28
weightedSpearman	28
weightedVariance	29
weightedZIKendall	30
weightedZISpearman	30
weightMatrix<-	31

Index

33

liver	<i>Liver trajectory example data</i>
-------	--------------------------------------

Description

A liver data set contains two branches (hepatocyte and cholangiocyte).

Usage

```
data(liver, package = 'scHOT')
```

Format

A ‘list’ object.

MOB_subset

MOB_subset spatial example data

Description

A MOB spatial data set.

Usage

```
data(MOB_subset, package = 'scHOT')
```

Format

An object of class `list` of length 1.

params<-

Setter functions for scHOT objects

Description

Setter functions for scHOT objects

Usage

```
params(x) <- value
```

Arguments

x A scHOT object

value The value the slot should take

Value

A scHOT object

Examples

```

data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
schOT_spatial <- schOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))

params = list(higherOrderFunction = weightedSpearman,
higherOrderFunctionType = "weighted")

params(schOT_spatial) <- params

```

plotColouredExpression

plotColouredExpression

Description

the `plotColouredExpression` function plots an n-panel scatterplot of the gene pairs split by early, mid, and late in the sample ordering.

Usage

```

plotColouredExpression(
  schOT,
  genes,
  genes_delimiter = "_",
  branches = NULL,
  ranked_by = NULL,
  subsetBranch = NULL,
  n = 3,
  fittedline = TRUE,
  assayName = NULL
)

```

Arguments

<code>schOT</code>	A <code>schOT</code> object.
<code>genes</code>	is either a single character string with a delimiter, or a length two character vector
<code>genes_delimiter</code>	is the delimiter to split into two gene names if <code>genes</code> is provided as a single character
<code>branches</code>	A character indicates that the colnames stored the branch information in <code>colData</code>

ranked_by	A character indicates that the colnames stored the ranking information of the cells in colData, such as trajectory time, if it is NULL, it will be ranked based on the branch information.
subsetBranch	subsetBranch is a character vector containing the names of the branches to be plotted. If NULL it will plot all branches
n	number of panels to split ranked samples into, default 3.
fittedline	logical default TRUE, add a lm straight line to the plot
assayName	the name of the assay that are used to plot.

Value

ggplot a ggplot object of scatterplots of expression split by sample ordering

Examples

```
data(liver)

scHOT_traj <- scHOT_buildFromMatrix(
  mat = liver$liver_branch_hep,
  cellData = list(pseudotime = liver$liver_pseudotime_hep),
  positionType = "trajectory",
  positionColData = "pseudotime")

scHOT_traj

plotColouredExpression(scHOT_traj, c("Cdt1", "Top2a"), n = 5)
```

plotEgoNetwork

plotEgoNetwork

Description

the *plotEgoNetwork* function plots network graphs with edges coloured by weights in the network

Usage

```
plotEgoNetwork(
  scHOT,
  hubnode,
  network,
  weight = "higherOrderStatistic",
  subset = FALSE,
  thresh = NULL
)
```

Arguments

<code>scHOT</code>	a scHOT object
<code>hubnode</code>	is a character vector of node(s) to include as hub nodes
<code>network</code>	is an igraph network
<code>weight</code>	A string indicates the column name stored in scHOT_output slot that are used as the weights of the network
<code>subset</code>	is a logical asking if you should subset based on the weight (default FALSE)
<code>thresh</code>	is the subset weight threshold

Value

`igraph` object containing the network graphed. Produces an igraph plot

`plotHigherOrderSequence`

plotHigherOrderSequence

Description

the `plotHigherOrderSequence` function plots weighted higher order statistic vectors (stored in `higherOrderSequence`) as line plots

Usage

```
plotHigherOrderSequence(
  scHOT,
  gene,
  positionType = NULL,
  branches = NULL,
  positionColData = NULL
)
```

Arguments

<code>scHOT</code>	A scHOT object with higherOrderSequence in scHOT_output slot
<code>gene</code>	is either a logical vector matching rows of entries in wcorsList, or a character of a gene
<code>positionType</code>	A string indicates the position type, either trajectory or spatial
<code>branches</code>	A character indicates that the colnames stored the branch information in colData (for trajectory type of data)
<code>positionColData</code>	A vector indicates column names of colData that stored the postion informaton (for spatial type of data)

Value

ggplot object with line plots

Examples

```
data(liver)

scHOT_traj <- scHOT_buildFromMatrix(
  mat = liver$liver_branch_hep,
  cellData = list(pseudotime = liver$liver_pseudotime_hep),
  positionType = "trajectory",
  positionColData = "pseudotime")
scHOT_traj
plotColouredExpression(scHOT_traj, c("Cdt1", "Top2a"), n = 5)

scHOT_traj <- scHOT_addTestingScaffold(scHOT_traj,
  t(as.matrix(c("Cdt1", "Top2a"))))
scHOT_traj <- scHOT_setWeightMatrix(scHOT_traj,
  positionColData = c("pseudotime"),
  positionType = "trajectory",
  nrow.out = NULL,
  span = 0.25)
scHOT_traj <- scHOT_calculateGlobalHigherOrderFunction(scHOT_traj,
  higherOrderFunction =
    weightedSpearman,
  higherOrderFunctionType =
    "weighted")

scHOT_traj <- scHOT_calculateHigherOrderTestStatistics(scHOT_traj,
  higherOrderSummaryFunction =
    sd)

slot(scHOT_traj, "scHOT_output")
plotHigherOrderSequence(scHOT_traj, c("Cdt1_Top2a"))
```

```
plotOrderedExpression plotOrderedExpression
```

Description

the `plotOrderedExpression` function plots expression vectors along branches and genes as ribbon plots

Usage

```
plotOrderedExpression(
  scHOT,
  genes,
```

```

positionType = NULL,
branches = NULL,
ranked_by = NULL,
xvals = NULL,
subsetBranch = NULL,
facet = FALSE,
positionColData = NULL,
assayName = NULL
)

```

Arguments

<code>scHOT</code>	A scHOT object, where the expression data is stored in the assay slot, with assay name "expression".
<code>genes</code>	is a character vector for gene names
<code>positionType</code>	A string indicates the position type, either trajectory or spatial
<code>branches</code>	A character indicates that the colnames stored the branch information in colData
<code>ranked_by</code>	A character indicates that the colnames stored the ranking information of the cells in colData, such as trajectory time
<code>xvals</code>	A character indicates that the colnames stored in colData of the x-values associated with the samples in branchData
<code>subsetBranch</code>	subsetBranch is a character vector containing the names of the branches to be plotted. If NULL it will plot all branches
<code>facet</code>	can either be FALSE, "branch", "gene", or "both"
<code>positionColData</code>	A vector indicates column names of colData that stored the postion informaton (for spatial type of data)
<code>assayName</code>	the name of the assay that are used to plot.

Value

ggplot a ggplot object for ribbon plot with points

`positionColData<-` *Setter functions for scHOT objects*

Description

Setter functions for scHOT objects

Usage

```
positionColData(x) <- value
```

positionType<-

9

Arguments

- | | |
|-------|--------------------------------|
| x | A scHOT object |
| value | The value the slot should take |

Value

A scHOT object

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))

positionColData(scHOT_spatial) <- c("x", "y")
```

positionType<- *Setter functions for scHOT objects*

Description

Setter functions for scHOT objects

Usage

`positionType(x) <- value`

Arguments

- | | |
|-------|--------------------------------|
| x | A scHOT object |
| value | The value the slot should take |

Value

A scHOT object

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))
```

```
positionType(scHOT_spatial) <- "spatial"
```

scHOT*scHOT*

Description

A wrapper function to perform scHOT

Usage

```
scHOT(
  scHOT,
  testingScaffold = NULL,
  weightMatrix = NULL,
  positionType = NULL,
  positionColData = NULL,
  nrow.out = NULL,
  averageAcrossTrajectoryTies = FALSE,
  higherOrderFunction = NULL,
  higherOrderFunctionType = NULL,
  numberPermutations = 1000,
  numberScaffold = 100,
  storePermutations = TRUE,
  higherOrderSummaryFunction = sd,
  parallel = FALSE,
  BPPARAM = BiocParallel::SerialParam(),
  usenperm_estimate = FALSE,
  nperm_estimate = 10000,
  maxDist = 0.1,
  plot = FALSE,
  verbose = TRUE,
  ...
)
```

Arguments

scHOT	A scHOT object
testingScaffold	A matrix with rows for each testing combination
weightMatrix	A matrix indicates the weight matrix for scHOT analysis
positionType	A string indicating the position type, either "trajectory" or "spatial"

positionColData	Either trajectory or spatial information for each sample. If positionType is "trajectory" then positionColData should be a character or numeric indicating the subset of colData of the scHOT object. If positionType is "spatial" then positionColData should be a character or numeric vector indicating the subset of colData that give the full spatial coordinates.
nrow.out	The number of weightings to include for testing, a smaller value is faster for computation
averageAcrossTrajectoryTies	Logical indicating whether ties in the trajectory should be given the same local weights
higherOrderFunction	A function object indicates the higher order function
higherOrderFunctionType	is "weighted" or "unweighted", determines if there is a weighting argument in the higher order function
numberPermutations	The number of permutations, set as 1000 by default
numberScaffold	The number of testing scaffolds to perform permutations, set as 100 by default
storePermutations	a logical flag on whether permutation values should be saved
higherOrderSummaryFunction	A function indicating the higher order summary function (default is standard deviation 'sd')
parallel	A logical input indicating whether to run the permutation test using multiple cores in parallel.
BPPARAM	A BiocParallelParam class object from the BiocParallel package is used. Default is SerialParam().
usenperm_estimate	Logical (default FALSE) if number of neighbouring permutations should be used to estimate P-values, or if difference of global higher order statistic should be used
nperm_estimate	Number of neighbouring permutations to use for p-value estimation
maxDist	max difference of global higher order statistic to use for p-value estimation (default 0.1)
plot	A logical input indicating whether the results are plotted
verbose	A logical input indicating whether the intermediate steps will be printed
...	parameters for function trajectoryWeightMatrix or spatialWeightMatrix

Value

A scHOT object

Examples

```

data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                       assayName = "logcounts",
                                       positionType = "spatial",
                                       positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")

scHOT_spatial <- scHOT(scHOT_spatial,
                        testingScaffold = pairs,
                        positionType = "spatial",
                        positionColData = c("x", "y"),
                        nrow.out = NULL,
                        higherOrderFunction = weightedSpearman,
                        higherOrderFunctionType = "weighted",
                        numberPermutations = 100,
                        higherOrderSummaryFunction = sd,
                        parallel = FALSE,
                        verbose = TRUE,
                        span = 0.05)

```

scHOT-class

scHOT class

Description

scHOT class

Slots

testingScaffold A matrix with rows for each testing combination
weightMatrix A matrix or dgCMatrix indicates the weight matrix
scHOT_output A data.frame or DtatFrame to store output from scHOT
params A list of parameters
positionType A character indicates the type of the position, either trajectory or spatial
positionColData A vector indicates column names of colData that stored the postion informaton

scHOT_addTestingScaffold
scHOT_addTestingScaffold

Description

Add a testing scaffold to a scHOT object

Usage

```
scHOT_addTestingScaffold(scHOT, testingScaffold)
```

Arguments

scHOT	A scHOT object
testingScaffold	A matrix with rows for each testing combination, and columns for level of dimensionality (1 for single gene etc.)

Value

A scHOT object with slot testingScaffold saved

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
```

scHOT_buildFromMatrix *scHOT_buildFromMatrix*

Description

Create scHOT object from a matrix

Usage

```
scHOT_buildFromMatrix(
  mat,
  cellData = NULL,
  positionType = NULL,
  positionColData = NULL
)
```

Arguments

<code>mat</code>	A matrix with rows for genes and columns for cells
<code>cellData</code>	A datafram or DataFrame object with rows for cells
<code>positionType</code>	A string indicating the position type, either "trajectory" or "spatial"
<code>positionColData</code>	Strings indicate the position information stored in colData. If positionType is "trajectory" then positionColData should be a sortable vector if positionType is "spatial" then positionColData should be a matrix type object.

Value

A scHOT object

Examples

```
dat <- rbind(rnorm(50), rnorm(50), rnorm(50))
colnames(dat) <- paste0("cell_", 1:ncol(dat))
rownames(dat) <- c("gene_1", "gene_2", "gene_2")

scHOT <- scHOT_buildFromMatrix(dat, cellData = data.frame(1:ncol(dat)))
```

`scHOT_buildFromSCE` *scHOT_buildFromSCE*

Description

Create scHOT object from a SingleCellExperiment object

Usage

```
scHOT_buildFromSCE(
  sce,
  assayName = "counts",
  positionType = NULL,
  positionColData = NULL
)
```

Arguments

sce	A SingleCellExperiment object
assayName	is a single assay to pull out from sce as the expression matrix input of scHOT
positionType	A string indicates the position type, either trajectory or spatial
positionColData	Strings indicate the position information stored in colData. If positionType is "trajectory" then positionColData should be a sortable vector if positionType is "spatial" then positionColData should be a matrix type object.

Value

A scHOT object

Examples

```
library(SingleCellExperiment)
dat <- rbind(rnorm(50), rnorm(50), rnorm(50))
colnames(dat) <- paste0("cell_", 1:ncol(dat))
rownames(dat) <- c("gene_1", "gene_2", "gene_2")

sce <- SingleCellExperiment::SingleCellExperiment(assays =
S4Vectors::SimpleList(counts = dat))
scHOT <- scHOT_buildFromSCE(sce)
```

scHOT_calculateGlobalHigherOrderFunction
scHOT_calculateGlobalHigherOrderFunction

Description

this calculates the global higher order function and stores it in the output if these aren't found in the params slot then they need to be specified here

Usage

```
scHOT_calculateGlobalHigherOrderFunction(
  scHOT,
  higherOrderFunction = NULL,
  higherOrderFunctionType = NULL
)
```

Arguments

scHOT A scHOT object
higherOrderFunction A function object indicating the higher order function
higherOrderFunctionType is "weighted" or "unweighted", determines if there is a weighting argument in the higher order function

Details

Calculates the global higher order function

Value

A scHOT object with scHOT_output\$globalHigherOrderFunction in slot scHOT_output saved

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                         assayName = "logcounts",
                                         positionType = "spatial",
                                         positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
                                         positionColData = c("x", "y"),
                                         positionType = "spatial",
                                         nrow.out = NULL,
                                         span = 0.05)
scHOT_spatial <- scHOT_calculateGlobalHigherOrderFunction(
  scHOT_spatial,
  higherOrderFunction = weightedSpearman,
  higherOrderFunctionType = "weighted")
```

scHOT_calculateHigherOrderTestStatistics
scHOT_calculateHigherOrderTestStatistics

Description

Calculate and store the higherOrderSequence and higherOrderTestStatistic

Usage

```
scHOT_calculateHigherOrderTestStatistics(
  scHOT,
  higherOrderSummaryFunction = stats::sd,
  ...
)
```

Arguments

scHOT	A scHOT object
higherOrderSummaryFunction	A function which indicates how the higher order sequence is summarised, default is sd
...	parameters for higherOrderSummaryFunction

Value

scHOT A scHOT object with results stored in scHOT_output slot

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                       assayName = "logcounts",
                                       positionType = "spatial",
                                       positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)

rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)

scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
                                         positionColData = c("x", "y"),
                                         positionType = "spatial",
                                         nrow.out = NULL,
                                         span = 0.05)
scHOT_spatial <- scHOT_calculateGlobalHigherOrderFunction(
  scHOT_spatial,
  higherOrderFunction = weightedSpearman,
  higherOrderFunctionType = "weighted")
scHOT_spatial <- scHOT_setPermutationScaffold(scHOT_spatial,
                                                numberPermutations = 100)
scHOT_spatial <- scHOT_calculateHigherOrderTestStatistics(
  scHOT_spatial,
  higherOrderSummaryFunction = sd)
```

scHOT_estimatePvalues scHOT_estimatePvalues

Description

Estimate p-values based on already run permutation tests

Usage

```
scHOT_estimatePvalues(
  scHOT,
  usenperm_estimate = FALSE,
  nperm_estimate = 10000,
  maxDist = 0.1,
  plot = FALSE,
  verbose = FALSE
)
```

Arguments

scHOT	A scHOT object
usenperm_estimate	Logical (default FALSE) if number of neighbouring permutations should be used, or if difference of global higher order statistic should be used
nperm_estimate	Number of neighbouring permutations to use for p-value estimation
maxDist	max difference of global higher order statistic to use for p-value estimation (default 0.1)
plot	A logical input indicating whether the results are plotted
verbose	A logical input indicating whether the intermediate steps will be printed

Value

scHOT A scHOT object with results stored in scHOT_output slot

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                       assayName = "logcounts",
                                       positionType = "spatial",
                                       positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
```

```

scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
                                         positionColData = c("x", "y"),
                                         positionType = "spatial",
                                         nrow.out = NULL,
                                         span = 0.05)
scHOT_spatial <- scHOT_calculateGlobalHigherOrderFunction(
  scHOT_spatial,
  higherOrderFunction = weightedSpearman,
  higherOrderFunctionType = "weighted")
scHOT_spatial <- scHOT_setPermutationScaffold(scHOT_spatial,
                                                numberPermutations = 100)
scHOT_spatial <- scHOT_calculateHigherOrderTestStatistics(
  scHOT_spatial,
  higherOrderSummaryFunction = sd)

scHOT_spatial <- scHOT_performPermutationTest(
  scHOT_spatial,
  verbose = TRUE,
  parallel = FALSE)

scHOT_spatial <- scHOT_estimatePvalues(scHOT_spatial)

```

scHOT_output<- *Setter functions for scHOT objects*

Description

Setter functions for scHOT objects

Usage

```
scHOT_output(x) <- value
```

Arguments

x	A scHOT object
value	The value the slot should take

Value

A scHOT object

Examples

```

data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",

```

```
positionType = "spatial",
positionColData = c("x", "y"))

scHOT_output(scHOT_spatial) <- data.frame()
```

scHOT_performPermutationTest
scHOT_performPermutationTest

Description

Perform permutation test

Usage

```
scHOT_performPermutationTest(
  scHOT,
  verbose = FALSE,
  parallel = FALSE,
  BPPARAM = BiocParallel::SerialParam()
)
```

Arguments

scHOT	A scHOT object
verbose	A logical input indicates whether the intermediate steps will be printed
parallel	A logical input indicates whether run the permutation test using multiple cores in parallel.
BPPARAM	A BiocParallelParam class object from the BiocParallel package is used. Default is SerialParam().

Value

scHOT A scHOT object with results stored in scHOT_output slot

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                      assayName = "logcounts",
                                      positionType = "spatial",
                                      positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
```

```

positionColData = c("x", "y"),
positionType = "spatial",
nrow.out = NULL,
span = 0.05)
scHOT_spatial <- scHOT_calculateGlobalHigherOrderFunction(
  scHOT_spatial,
  higherOrderFunction = weightedSpearman,
  higherOrderFunctionType = "weighted")
scHOT_spatial <- scHOT_setPermutationScaffold(scHOT_spatial,
                                               numberPermutations = 100)
scHOT_spatial <- scHOT_calculateHigherOrderTestStatistics(
  scHOT_spatial,
  higherOrderSummaryFunction = sd)

scHOT_spatial <- scHOT_performPermutationTest(
  scHOT_spatial,
  verbose = TRUE,
  parallel = FALSE)

```

scHOT_plotPermutationDistributions
scHOT_plotPermutationDistributions

Description

the scHOT_plotPermutationDistributions function plots the permutation test statistics as a diagnostic plot for estimating p-values

Usage

```
scHOT_plotPermutationDistributions(scHOT)
```

Arguments

scHOT	a scHOT object
-------	----------------

Value

ggplot graph of global higher order function and the permutation scHOT test statistics. This should have a continuous pattern to be reliably used for p-value estimation

scHOT_setPermutationScaffold
scHOT_setPermutationScaffold

Description

Set permutation scaffold

Usage

```
scHOT_setPermutationScaffold(
  scHOT,
  numberPermutations = 1000,
  numberScaffold = 100,
  storePermutations = TRUE
)
```

Arguments

scHOT	A scHOT object
numberPermutations	The number of permutations, set as 1000 by default
numberScaffold	The number of scaffold, set as 100 by default, minimum 6. if you want all combinations to do permutations then set, numberScaffold much higher than the testingScaffold
storePermutations	a logical flag on whether Permutations should be stored, or discarded once used

Value

A scHOT object with storePermutations in slot scHOT_output saved

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                       assayName = "logcounts",
                                       positionType = "spatial",
                                       positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
                                         positionColData = c("x", "y"),
                                         positionType = "spatial",
                                         nrow.out = NULL,
                                         span = 0.05)
```

```

scHOT_spatial <- scHOT_calculateGlobalHigherOrderFunction(
  scHOT_spatial,
  higherOrderFunction = weightedSpearman,
  higherOrderFunctionType = "weighted")
scHOT_spatial <- scHOT_setPermutationScaffold(scHOT_spatial,
                                               numberPermutations = 100)

```

scHOT_setWeightMatrix scHOT_setWeightMatrix**Description**

Create scHOT object from a SingleCellExperiment object

Usage

```

scHOT_setWeightMatrix(
  scHOT,
  weightMatrix = NULL,
  positionType = NULL,
  positionColData = NULL,
  nrow.out = NULL,
  averageAcrossTrajectoryTies = FALSE,
  ...
)

```

Arguments

<code>scHOT</code>	A scHOT object
<code>weightMatrix</code>	A matrix indicating the weight matrix for scHOT analysis, such as the output from ‘trajectoryWeightMatrix’ or ‘spatialWeightMatrix’. If this is not NULL then other parameters are ignored.
<code>positionType</code>	A string indicating the position type, either "trajectory" or "spatial"
<code>positionColData</code>	Either trajectory or spatial information for each sample. If positionType is "trajectory" then positionColData should be a character or numeric indicating the subset of colData of the scHOT object. If positionType is "spatial" then positionColData should be a character or numeric vector indicating the subset of colData that give the full spatial coordinates.
<code>nrow.out</code>	The number of weightings to include for testing, a smaller value is faster for computation
<code>averageAcrossTrajectoryTies</code>	Logical indicating whether ties in the trajectory should be given the same local weights
<code>...</code>	parameters for function trajectoryWeightMatrix or spatialWeightMatrix

Value

A scHOT object with slot weightMatrix saved

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                      assayName = "logcounts",
                                      positionType = "spatial",
                                      positionColData = c("x", "y"))
pairs <- matrix(c("Arrb1", "Mtor", "Dnm1l", "Gucy1b3"), ncol = 2, byrow = TRUE)
rownames(pairs) <- apply(pairs, 1, paste0, collapse = "_")
scHOT_spatial <- scHOT_addTestingScaffold(scHOT_spatial, pairs)
scHOT_spatial <- scHOT_setWeightMatrix(scHOT_spatial,
                                         positionColData = c("x", "y"),
                                         positionType = "spatial",
                                         nrow.out = NULL,
                                         span = 0.05)
```

scHOT_stripOutput *scHOT_stripOutput*

Description

Strip the scHOT output

Usage

```
scHOT_stripOutput(scHOT, force = TRUE, store = FALSE, file_name = NULL)
```

Arguments

scHOT	A scHOT object
force	A logical indicates whether forcing stripping the scHOT output
store	A logical flag on whether the scHOT should be stored as .rds file
file_name	A string indicates the file name of the scHOT will be stored

Value

A scHOT object with scHOT_output striped

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
                                      assayName = "logcounts",
                                      positionType = "spatial",
                                      positionColData = c("x", "y"))

scHOT_spatial <- scHOT_stripOutput(scHOT_spatial)
```

spatialWeightMatrix *spatialWeightMatrix*

Description

Create weight matrix for spatial data

Usage

```
spatialWeightMatrix(x, span = NULL)
```

Arguments

- x a matrix with rows corresponding to cells and columns corresponding to dimensions to calculate Euclidean distance
- span proportion of samples to include on either side, default is 13/(number of rows in 'x'), corresponding roughly to points within a diamond shape distance away

Value

A weighted matrix

Examples

```
spat_x <- rnorm(50)
spat_y <- rnorm(50)
spat_coord <- cbind(spat_x, spat_y)
W <- spatialWeightMatrix(spat_coord)
```

`testingScaffold<-` *Setter functions for scHOT objects*

Description

Setter functions for scHOT objects

Usage

```
testingScaffold(x) <- value
```

Arguments

<code>x</code>	A scHOT object
<code>value</code>	The value the slot should take

Value

A scHOT object

Examples

```
data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))

pairs <- t(combn(rownames(sce_MOB_subset),2))
rownames(pairs) <- apply(pairs,1,paste0,collapse = "_")

testingScaffold(scHOT_spatial) <- pairs
```

Description

The thin function extracts the rows of a matrix evenly so that roughly n number of rows remain.
Used for thinning down the weight matrix to speed up overall computation.

Usage

```
thin(W, n = 100)
```

Arguments

W	matrix
n	rough number of rows to keep

Value

matrix of thinned matrix keeping only roughly n rows.

Examples

```
W = trajectoryWeightMatrix(500)
W_small = thin(W, n = 100)
```

trajectoryWeightMatrix	<i>trajectoryWeightMatrix</i>
------------------------	-------------------------------

Description

Create weight matrix for trajectory data

Usage

```
trajectoryWeightMatrix(n, type = NULL, span = NULL)
```

Arguments

n	indicates the number of cells
type	Type of weight matrix, one of "triangular" (default), "block", and "harmonic"
span	proportion of samples to include on either side, default is 0.25

Value

A weighted matrix

Examples

```
W <- trajectoryWeightMatrix(100)
W <- trajectoryWeightMatrix(100, type = "triangular")
W <- trajectoryWeightMatrix(100, type = "block")
W <- trajectoryWeightMatrix(100, type = "harmonic")
```

weightedPearson *weightedPearson*

Description

the weightedPearson function

Usage

```
weightedPearson(x, y, w = 1)
```

Arguments

- | | |
|---|---|
| x | x and y are data vectors |
| y | x and y are data vectors |
| w | weight vector, values should be between 0 and 1 |

Value

numeric weighted correlation value between x and y

Examples

```
x = rnorm(100)
y = rnorm(100)
w = runif(100)
weightedPearson(x,y,w)
```

weightedSpearman *weightedSpearman*

Description

the weightedSpearman function

Usage

```
weightedSpearman(x, y, w = 1)
```

Arguments

- | | |
|---|---|
| x | x and y are data vectors |
| y | x and y are data vectors |
| w | weight vector, values should be between 0 and 1 |

Value

numeric weighted correlation value between x and y

Examples

```
x = rnorm(100)
y = rnorm(100)
w = runif(100)
weightedSpearman(x,y,w)
```

weightedVariance

weightedVariance

Description

the weightedVariance function

Usage

```
weightedVariance(x, y = NULL, w)
```

Arguments

x	x is a data vector
y	default to NULL, if given it is ignored
w	weight vector, values should be between 0 and 1

Value

numeric weighted variance value for x

Examples

```
x = rnorm(100)
w = runif(100)
weightedVariance(x,w = w)
```

`weightedZIKendall` *weightedZIKendall*

Description

the `weightedZIKendall` function calculates weighted Tau*, where Tau* is described in Pimentel et al (2015) doi:10.1016/j.spl.2014.09.002. This association measure is defined for zero-inflated, non-negative random variables.

Usage

```
weightedZIKendall(x, y, w = 1)
```

Arguments

x	x and y are non-negative data vectors
y	x and y are non-negative data vectors
w	weight vector, values should be between 0 and 1

Value

numeric weighted Tau* association value between x and y

Examples

```
x = pmax(0,rnorm(100))
y = pmax(0,rnorm(100))
w = runif(100)
weightedZIKendall(x,y,w)
```

`weightedZISpearman` *weightedZISpearman*

Description

the `weightedZISpearman` function calculates weighted rho*, where rho* is described in Pimentel et al (2009). This association measure is defined for zero-inflated, non-negative random variables.

Usage

```
weightedZISpearman(x, y, w = 1)
```

Arguments

- x x and y are non-negative data vectors
- y x and y are non-negative data vectors
- w weight vector, values should be between 0 and 1

Value

numeric weighted rho* association value between x and y

Pimentel, Ronald Silva, "Kendall's Tau and Spearman's Rho for Zero-Inflated Data" (2009). Dissertations. 721. <https://scholarworks.wmich.edu/dissertations/721>

Examples

```
x = pmax(0,rnorm(100))
y = pmax(0,rnorm(100))
w = runif(100)
weightedZISpearman(x,y,w)
```

`weightMatrix<-` *Setter functions for scHOT objects*

Description

Setter functions for scHOT objects

Usage

```
weightMatrix(x) <- value
```

Arguments

- x A scHOT object
- value The value the slot should take

Value

A scHOT object

Examples

```
library(SingleCellExperiment)

data(MOB_subset)
sce_MOB_subset <- MOB_subset$sce_MOB_subset
scHOT_spatial <- scHOT_buildFromSCE(sce_MOB_subset,
assayName = "logcounts",
positionType = "spatial",
positionColData = c("x", "y"))

W <- spatialWeightMatrix(colData(scHOT_spatial)[,slot(scHOT_spatial, "positionColData")])

weightMatrix(scHOT_spatial) <- W
```

Index

```
* datasets
  liver, 2
  MOB_subset, 3
  .scHOT (scHOT-class), 12
  liver, 2
  MOB_subset, 3
  params<-, 3
  plotColouredExpression, 4
  plotEgoNetwork, 5
  plotHigherOrderSequence, 6
  plotOrderedExpression, 7
  positionColData<-, 8
  positionType<-, 9
  scHOT, 10
  scHOT-class, 12
  scHOT_addTestingScaffold, 13
  scHOT_buildFromMatrix, 13
  scHOT_buildFromSCE, 14
  scHOT_calculateGlobalHigherOrderFunction,
    15
  scHOT_calculateHigherOrderTestStatistics,
    16
  scHOT_estimatePvalues, 18
  scHOT_output<-, 19
  scHOT_performPermutationTest, 20
  scHOT_plotPermutationDistributions, 21
  scHOT_setPermutationScaffold, 22
  scHOT_setWeightMatrix, 23
  scHOT_stripOutput, 24
  spatialWeightMatrix, 25
  testingScaffold<-, 26
  thin, 26
  trajectoryWeightMatrix, 27
  weightedPearson, 28
  weightedSpearman, 28
  weightedVariance, 29
  weightedZIKendall, 30
  weightedZISpearman, 30
  weightMatrix<-, 31
```