

Package ‘systemPipeRdata’

April 13, 2022

Title systemPipeRdata: Workflow templates and sample data

Version 1.22.3

Date 2022-04-10

Author Thomas Girke

Maintainer Thomas Girke <thomas.girke@ucr.edu>

biocViews Genetics, Infrastructure, DataImport, Sequencing, RNASeq, ChIPSeq, MethylSeq, SNP, GeneExpression, Coverage, GeneSetEnrichment, Alignment, QualityControl, ImmunoOncology, RiboSeq, WorkflowStep

Description systemPipeRdata is a helper package to generate with a single command NGS workflow templates that are intended to be used by its parent package systemPipeR. The latter is an environment for building end-to-end analysis pipelines with automated report generation for next generation sequence (NGS) applications such as RNA-Seq, RIBO-Seq, ChIP-Seq, VAR-Seq and many others. Detailed examples for using systemPipeRdata are given in systemPipeR's overview vignette.

Depends methods

Imports BiocGenerics, jsonlite, remotes, GenomicFeatures, GenomicRanges, IRanges, Rsamtools, ShortRead, rtracklayer

Suggests RUnit, BiocStyle, knitr, rmarkdown, systemPipeR

VignetteBuilder knitr

License Artistic-2.0

NeedsCompilation no

URL <https://github.com/tgirke/systemPipeRdata>

git_url <https://git.bioconductor.org/packages/systemPipeRdata>

git_branch RELEASE_3_14

git_last_commit bd012f5

git_last_commit_date 2022-04-11

Date/Publication 2022-04-13

R topics documented:

| | |
|--------------------------|---|
| availableWF | 2 |
| genWorkenvir | 3 |
| getSubsetReads | 5 |
| pathList | 6 |

Index

7

availableWF

List Available Workflows Templates at systemPipeRdata package

Description

This function checks the workflow templates availability from `systemPipeRdata` package and also from [systemPipeR Organization](#) on GitHub.

Usage

```
availableWF(github = FALSE)
```

Arguments

| | |
|---------------------|-----------------------------------------------------------------------------------------------------------------|
| <code>github</code> | logical. If TRUE, it will return current workflow templates available on <code>systemPipeR</code> Organization. |
|---------------------|-----------------------------------------------------------------------------------------------------------------|

Details

Internally, this function uses the GitHub API, and there is an access limit per hour. For more details, please check: `system("curl -i https://api.github.com/users/<username>")`.

Value

Return a list with the names of the workflows templates available at `systemPipeRdata` package. If `github = TRUE`, it will return an additional `data.frame` with current workflow templates available on `systemPipeR` Organization.

Note

We are assuming that workflow templates repositories under [systemPipeR Organization](#) content the keyword "Workflow Template" on the Description section and "Topics" section, we expected "systempiper" and "release" or "development" words.

Author(s)

Daniela Cassol

See Also

[genWorkenvir](#).

Examples

```
availableWF()  
## Not run:  
## List Workflow Templates from \code{systemPipeR} Organization  
availableWF(github = TRUE)  
  
## End(Not run)
```

genWorkenvir

Generate workflow templates

Description

Generates workflow templates for `systemPipeR` package. The template environments contain a predefined directory structure along with run parameter files and sample data. The structure of the workflow templates and the sample data are described in all details in the Overview Vignette of the [systemPipeR package](#).

Usage

```
genWorkenvir(workflow, mydirname=NULL, bam=FALSE, ref="master", subdir=NULL, url=NULL, urlname=NULL)
```

Arguments

| | |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| workflow | character string of workflow templates to be generated. Supported values can be checked with the <code>\link{availableWF}()</code> function. Workflow name containing a '/' are treated as GitHub repositories and installed using <code>BiocManager::\link{install_github}()</code> . For Github workflow templates, the format <code>systemPipeR/repo</code> is required. See Details. |
| mydirname | Specifies the name of the workflow directory. The default <code>NULL</code> uses the name of the chosen workflow. An error is issued if a directory of the same name and path exists already. |
| bam | If <code>bam=TRUE</code> pregenerated short read alignment (BAM) files will be included in the results directory of the workflow environment. Note, these BAM files have been generated with the HISAT2 aligner using the FASTQ files provided in the data directory. The default <code>bam=FALSE</code> omits this step meaning no BAM files will be copied into the results directory. |
| ref | Desired GitHub reference for the branch name. Default to <code>master</code> branch. |
| subdir | subdirectory within GitHub repo that contains the R package, if it is required. |
| url | character string of a specifies the URL of a different version of the R Markdown workflow template or other file to download. The default <code>NULL</code> copies the current version available in the ' <code>systemPipeRdata</code> ' or the workflow template on GitHub being selected. |
| urlname | character string with the name where the downloaded file is saved. This is argument is required when the <code>url</code> is provided. |

Details

When installing GitHub Workflow Packages under **systemPipeR Organization**, it is requested to the remotes package function `BiocManager::link{install_github}()` to build vignettes and also install all the dependencies, via `dependencies=TRUE, build_vignettes=TRUE`.

Check the output of `\link{availableWF}()` to the current workflow templates available on **systemPipeR Organization**. The argument

For an `interactive()` session, the `readline()` function provides the option choose between proceeding or not, through options: yes or no. For non-interactive use, if there is no package install, the option yes will be selected.

Value

Workflow directory containing sample data and parameter files along with the following subdirectories:

| | |
|-----------------------|------------------------|
| <code>param/</code> | stores parameter files |
| <code>data/</code> | stores input data |
| <code>results/</code> | stores output results |

For more details, please consult the Overview Vignette (HTML) of the **systemPipeR** package (<http://bioconductor.org/packages/systemPipeR>).

Author(s)

Thomas Girke and Daniela Cassol

Examples

```
## Return location of sample data
samplepaths <- pathList()
## Not run:
## Generate varseq workflow environment
genWorkenvir(workflow="varseq", mydirname=NULL, url=NULL, urlname=NULL)
setwd("varseq")

## List Workflow Templates from \code{systemPipeRdata} package and \code{systemPipeR} Organization
availableWF(github = TRUE)
## Generate 'systemPipeR/systemPipeChIPseq' workflow environment
genWorkenvir(workflow="systemPipeR/systemPipeChIPseq", mydirname=NULL, ref="master", subdir=NULL)
setwd("systemPipeChIPseq")

## Download a specific R Markdown file
genWorkenvir(workflow="systemPipeR/systemPipeRNaseq", mydirname="rnaseq", url = "https://raw.githubusercontent.com/bioconductor/systemPipeR/main/systemPipeRNaseq.Rmd")
## End(Not run)
```

| | |
|----------------|------------------------------|
| getSubsetReads | <i>Subsetting fastq data</i> |
|----------------|------------------------------|

Description

Returns subsets of fastq files data based on specific mapping regions or list of genes or GRanges object.

Usage

```
getSubsetReads(args,
  geneList = NULL,
  gr = NULL,
  MappingRegion = 1:1e+05,
  sample_range = 90000:1e+05,
  truncate_refs = TRUE,
  id_read_number = TRUE,
  annotation = "data/tair10.gff",
  reference = "data/tair10.fasta",
  annot_outname = "tair10_sub.gff",
  ref_outname = "tair10_sub.fasta",
  outdir = "data/subset/",
  silent = FALSE
)
```

Arguments

| | |
|----------------|----------------------------------------------------------------------------------------------------------------|
| args | object of class <code>SYSargs2</code> . |
| geneList | selected genes list to retrieve the reads from the fastq file. |
| gr | an object containing genomic ranges to retrieve the reads from the fastq file. |
| MappingRegion | integers ranges of start and end of chromosome position to retrieve the reads from the fastq file. |
| sample_range | random range to subsetted the fastq file. |
| truncate_refs | logical. If TRUE it will generate reference genome and annotation subset file. |
| id_read_number | if fastq file contains sequence name with read number (<code>\$ri --defline-seq '@\$sn[_\$rn]/\$ri'</code>). |
| annotation | path to annotation file. |
| reference | path to reference genome. |
| annot_outname | character name of the annotation output file. |
| ref_outname | character name of the reference genome output file. |
| outdir | path to output directory. |
| silent | if set to TRUE, all messages returned by the function will be suppressed. |

Value

Workflow directory containing sample data and parameter files along with the following subdirectories:

| | |
|-----------------------|------------------------|
| <code>param/</code> | stores parameter files |
| <code>data/</code> | stores input data |
| <code>results/</code> | stores output results |

For more details, please consult the Overview Vignette (HTML) of the `systemPipeR` package (<http://bioconductor.org/packages/systemPipeR>).

Author(s)

Thomas Girke, Shiyuan Guo and Daniela Cassol

Examples

```
## Not run:
getSubsetReads(args, MappingRegion = 1:900, sample_range = 800:900, outdir = "data/subset/", silent = FALSE)
getSubsetReads(args, MappingRegion = 1:900, sample_range = NULL, outdir = "data/subset/", silent = FALSE)

## End(Not run)
```

pathList

Return location of sample data

Description

Function to return paths to sample data provided by `systemPipeRdata` package.

Usage

```
pathList()
```

Value

`list`

Author(s)

Thomas Girke

Examples

```
samplepaths <- pathList()
```

Index

* utilities

availableWF, [2](#)
genWorkenvir, [3](#)
getSubsetReads, [5](#)
pathList, [6](#)

availableWF, [2](#)

genWorkenvir, [2](#), [3](#)
getSubsetReads, [5](#)

pathList, [6](#)