

Package ‘scTreeViz’

April 11, 2023

Type Package

Title R/Bioconductor package to interactively explore and visualize
single cell RNA-seq datasets with hierarchical annotations

Version 1.4.0

Description scTreeViz provides classes to support interactive data aggregation and visualization of single cell RNA-seq datasets with hierarchies for e.g. cell clusters at different resolutions. The `TreeIndex` class provides methods to manage hierarchy and split the tree at a given resolution or across resolutions. The `TreeViz` class extends `SummarizedExperiment` and can perform quick aggregations on the count matrix defined by clusters.

License Artistic-2.0

Depends R (>= 4.0), methods, epivizr, SummarizedExperiment

Imports data.table, S4Vectors, digest, Matrix, Rtsne, httr, igraph,
clustree, scran, sys, epivizrData, epivizrServer, ggraph,
scater, Seurat, SingleCellExperiment, ggplot2, stats, utils

Suggests knitr, BiocStyle, testthat, SC3, scRNASeq, rmarkdown, msd16s,
metagenomeSeq, epivizrStandalone, GenomeInfoDb

VignetteBuilder knitr

biocViews Visualization, Infrastructure, GUI, SingleCell

Encoding UTF-8

LazyData true

Collate 'TreeIndex-class.R' 'TreeIndex-methods.R' 'TreeViz-class.R'
'TreeViz-methods.R' 'startTreeViz.R' 'TreeVizApp-class.R'
'EpivizTreeData-class.R' 'helper-functions.R'
'ClusterHierarchy-class.R'

RoxygenNote 7.1.1

git_url <https://git.bioconductor.org/packages/scTreeViz>

git_branch RELEASE_3_16

git_last_commit b21f115

git_last_commit_date 2022-11-01

Date/Publication 2023-04-10

Author Jayaram Kancherla [aut, cre],
 Hector Corrada Bravo [aut],
 Kazi Tasnim Zinat [aut],
 Stephanie Hicks [aut]

Maintainer Jayaram Kancherla <jayaram.kancherla@gmail.com>

R topics documented:

<code>.generate_hierarchy_tree</code>	2
<code>.generate_leaf_of_table</code>	3
<code>.generate_nodes_table</code>	4
<code>.generate_node_ids</code>	4
<code>.replaceNAFeatures</code>	5
<code>ClusterHierarchy</code>	5
<code>ClusterHierarchy-class</code>	6
<code>createFromSCE</code>	6
<code>createFromSeurat</code>	7
<code>createTreeViz</code>	8
<code>EpivizTreeData-class</code>	9
<code>set_gene_list</code>	10
<code>show,TreeViz-method</code>	10
<code>startTreeviz</code>	12
<code>TreeIndex</code>	13
<code>TreeIndex-class</code>	14
<code>TreeViz</code>	14
<code>TreeViz-class</code>	15
<code>TreeVizApp-class</code>	15
<code>[,TreeIndex,ANY,ANY,ANY-method</code>	15
Index	18

`.generate_hierarchy_tree`
generate hierarchy tree

Description

generate hierarchy tree

Usage

`.generate_hierarchy_tree(hierarchy, feature_order)`

Arguments

hierarchy hierarchy as a data.table
feature_order order of the tree if different from colnames

Value

a data frame object

.generate_leaf_of_table
generate leaf of table

Description

generate leaf of table

Usage

```
.generate_leaf_of_table(  
  hierarchy_tree,  
  node_ids_table,  
  nodes_table,  
  feature_order  
)
```

Arguments

hierarchy_tree hierarchy as a data.table
node_ids_table node ids
nodes_table nodes table
feature_order order of the tree if different from colnames

Value

a data frame object

`.generate_nodes_table` *generate nodes table tree*

Description

`generate nodes table tree`

Usage

`.generate_nodes_table(hierarchy_tree, node_ids_table, feature_order)`

Arguments

`hierarchy_tree` hierarchy as a data.table

`node_ids_table` node ids

`feature_order` order of the tree if different from colnames

Value

a data frame object

`.generate_node_ids` *generate node ids in the tree*

Description

`generate node ids in the tree`

Usage

`.generate_node_ids(hierarchy_tree, feature_order)`

Arguments

`hierarchy_tree` hierarchy as a data.table

`feature_order` order of the tree if different from colnames

Value

a data frame object

.replaceNAFeatures *replace if there are NA's in the hierarchy*

Description

replace if there are NA's in the hierarchy

Usage

```
.replaceNAFeatures(replacing_na_obj_fData, feature_order)
```

Arguments

replacing_na_obj_fData

hierarchy data table

feature_order order of the tree if different from colnames

Value

a data frame object

ClusterHierarchy *Creates a new ClusterHierarchy object.*

Description

Works as a validation check for multiple issues user passed dataframe might have. For example, multiple root nodes, incompatible naming, multiple parents of a single node, etc This function performs all this checks and tries to resolve the issues by making changes in cluster assignment User can give either col_regex or columns option to filter the columns or specify the column order

Usage

```
ClusterHierarchy(hierarchy, col_regex = NULL, columns = NULL)
```

Arguments

hierarchy hierarchy as a DataFrame

col_regex Regular Expression for choosing columns

columns Vector containing list of columns to choose from with ordering

Value

'ClusterHierarchy' return an object of class ClusterHierarchy containing cluster information that ensures a valid dataframe for treeviz input

Examples

```
n=64
# create a hierarchy
df<- data.frame(cluster0=rep(1,n))
for(i in seq(1,5)){
  df[[paste0("cluster",i)]]<- rep(seq(1:(2**i)),each=ceiling(n/(2**i)),len=n)
}
clus_hier<-ClusterHierarchy(df, col_regex = "clus")
```

ClusterHierarchy-class

ClusterHierarchy class to manage treeviz cluster data

Description

ClusterHierarchy class to manage treeviz cluster data

createFromSCE

Creates a ‘TreeViz‘ object from ‘SingleCellExperiment‘. Generates clusters based on Walktrap algorithm if no default is provided

Description

Creates a ‘TreeViz‘ object from ‘SingleCellExperiment‘. Generates clusters based on Walktrap algorithm if no default is provided

Usage

```
createFromSCE(
  object,
  check_coldata = FALSE,
  col_regex = NULL,
  columns = NULL,
  reduced_dim = c("TSNE")
)
```

Arguments

- | | |
|---------------|---|
| object | ‘SingleCellExperiment‘ object to be visualized |
| check_coldata | whether to colData of ‘SingleCellExperiment‘ object for cluster information or not |
| col_regex | common regular expression shared across all columns with cluster information |
| columns | vector containing columns with cluster information |
| reduced_dim | Vector of Dimensionality reduction information provided in ‘SingleCellExperiment‘ object to be added in ‘TreeViz‘ (if exists) |

Value

‘TreeViz’ Object

Examples

```
library(SingleCellExperiment)
library(scater)
sce <- mockSCE()
sce <- logNormCounts(sce)
sce <- runTSNE(sce)
sce <- runUMAP(sce)
set.seed(1000)
for (i in seq_len(5)) {
  clust.kmeans <- kmeans(reducedDim(sce, "TSNE"), centers = i)
  sce[[paste0("clust", i)]] <- factor(clust.kmeans$cluster)
}
treeviz <- createFromSCE(sce, check_coldata = TRUE, col_regex = "clust", reduced_dim = c("TSNE", "UMAP"))
```

createFromSeurat

Creates a ‘TreeViz’ object from ‘Seurat’

Description

Creates a ‘TreeViz’ object from ‘Seurat’

Usage

```
createFromSeurat(
  object,
  check_metadata = FALSE,
  col_regex = "*snn*",
  columns = NULL,
  reduced_dim = c("TSNE")
)
```

Arguments

object	‘Seurat’ class containing cluster information at different resolutions
check_metadata	whether to metaData of ‘Seurat’ object for cluster information or not
col_regex	common regular expression shared across all columns with cluster information
columns	vector containing columns with cluster information
reduced_dim	Vector of Dimensionality reduction information provided in ‘Seurat’ object to be added in ‘TreeViz’ (if exists)

Value

‘TreeViz’ Object

Examples

```
library(Seurat)
data(pbmc_small)
pbmc <- pbmc_small
treeviz<- createFromSeurat(pbmc, check_metadata = TRUE, reduced_dim = c("pca","tsne"))
```

createTreeViz

Creates ‘TreeViz’ object from hierarchy and count matrix

Description

Provided with a count matrix and a dataframe or ‘ClusterHierarchy‘ object, this module runs the necessary checks on the dataframe and tries to convert it to a tree by making necessary changes. Returns the ‘TreeViz‘ object if a tree is successfully generated from dataframe, throws error otherwise

Usage

```
createTreeViz(clusters, counts)
```

Arguments

clusters	‘ClusterHierarchy‘ object or a dataframe containing cluster information at different resolutions
counts	matrix Dense or sparse matrix containing the count matrix

Value

‘TreeViz“ Object

Examples

```
n=64
# create a hierarchy
df<- data.frame(cluster0=rep(1,n))
for(i in seq_len(5)){
  df[[paste0("cluster",i)]]<- rep(seq(1:(2**i)),each=ceiling(n/(2**i)),len=n)
}
# generate a count matrix
counts <- matrix(rpois(6400, lambda = 10), ncol=n, nrow=100)
colnames(counts)<- seq_len(64)
# create a `TreeViz` object
treeViz <- createTreeViz(df, counts)
```

EpivizTreeData-class *Data container for MExperiment objects*

Description

Used to serve hierarchical data (used in e.g., icicle plots and heatmaps).

Methods

df_to_tree(root, df) Helper function to recursively build nested response for getHierarchy
root Root of subtree
df data.frame containing children to process

get_default_chart_type() Get name of default chart type for this data type

get_measurements() Get description of measurements served by this object

getCombined(measurements = NULL, seqName, start = 1, end = 1000, order = NULL, nodeSelection = NULL, selectedLevels = 1)
Return the counts aggregated to selected nodes for the given samples

measurements Samples to get counts for
seqName name of datasource
start Start of feature range to query
end End of feature range to query
order Ordering of nodes
nodeSelection Node-id and selectionType pairs
selectedLevels Current aggregation level

getHierarchy(nodeId = NULL) Retrieve feature hierarchy information for subtree with specified root
nodeId Feature identifier with level info

getReducedDim(method = NULL, gene = NULL) Compute PCA over all features for given samples
method which dimension to access
gene send expression of a gene back with the dimensions

getRows(measurements = NULL, start = 1, end = 1000, selectedLevels = 3, selections = NULL)
Return the sample annotation and features within the specified range and level for a given sample and features

measurements Samples to retrieve for
start Start of feature range to query
end End of feature range to query
selections Node-id and selectionType pairs
selectedLevels Current aggregation level

propagateHierarchyChanges(selection = NULL, order = NULL, selectedLevels = NULL, request_with_labels = FALSE)
Update internal state for hierarchy
selection Node-id and selectionType pairs
order Ordering of features

selectedLevels Current aggregation level
request_with_labels For handling requests using fData entries from MRExperiment
row_to_dict(row) Helper function to format each node entry for getHierarchy response
row Information for current node.
searchTaxonomy(query = NULL, max_results = 15) Return list of features matching a text-based query
query String of feature for which to search
max_results Maximum results to return

set_gene_list *Sets gene list for visualization*

Description

Sets gene list for visualization

Usage

```
set_gene_list(treeviz, genes)
```

Arguments

treeviz	TreeViz object
genes	list of genes to use

Value

TreeViz object set with gene list

show,TreeViz-method *show object*

Description

show object
Method to aggregate a TreeViz object
Method to aggregate a TreeViz object
Generic method to register data to the epiviz data server
plot tree from TreeViz

Usage

```

## S4 method for signature 'TreeViz'
show(object)

aggregateTree(x, ...)

## S4 method for signature 'TreeViz'
aggregateTree(
  x,
  selectedLevel = 3,
  selectedNodes = NULL,
  aggFun = colSums,
  start = 1,
  end = NULL,
  by = "row",
  format = "TreeViz"
)

## S4 method for signature 'TreeViz'
register(object, tree = "row", columns = NULL, ...)

## S4 method for signature 'TreeViz,ANY'
plot(x, y)

```

Arguments

object	The object to register to data server
x	treeviz object
...	Additional arguments passed to object constructors
selectedLevel	level to select nodes from
selectedNodes	used to set states on individual nodes to define a cut on the tree
aggFun	aggregate function to use, by default colSums if by="row", rowSums if by="col"
start, end	indices to filter nodes
by	"row" to aggregate the TreeIndex on rowData, "col" to aggregate TreeIndex on colData
format	return format can be one of "counts" or "TreeViz"
tree	Is tree over rows or columns of the object (default: "row")
columns	Name of columns containing data to register
y	none

Value

describe a TreeIndex object
a generic

- a Treeviz object or type specified by format
- An [EpivizTreeData-class](#) object
- Dataframe containing cluster information at different resolutions

Functions

- `show`, TreeViz-method:
- `aggregateTree`:
- `aggregateTree`, TreeViz-method:
- `register`, TreeViz-method:
- `plot`, TreeViz, ANY-method:

Examples

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
mbiome <- TreeViz(SimpleList(counts=counts), rowData=tree)
aggregateTree(mbiome)
```

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
mbiome <- TreeViz(SimpleList(counts=counts), rowData=tree)
aggregateTree(mbiome)
```

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
mbiome <- TreeViz(SimpleList(counts=counts), rowData=tree)
plot(mbiome)
```

`startTreeviz`

Start treeviz app and create [TreeVizApp](#) object to manage connection.

Description

Start treeviz app and create [TreeVizApp](#) object to manage connection.

Usage

```
startTreeviz(
  data = NULL,
  genes = NULL,
  top_genes = 100,
  host = "http://epiviz.cbcn.umd.edu/treeviz",
  register_function = .register_all_treeviz_things,
  delay = 2L,
  ...
)
```

Arguments

data	TreeViz object to explore
genes	(character vector) genes (rownames) to include in heatmap
top_genes	(integer) number of top variable genes to include in the heatmap
host	(character) host address to launch.
register_function	(function) function used to register actions and charts on the treeviz app.
delay	(integer) number of seconds to wait for application to load in browser
...	additional parameters passed to startEpiviz .

Value

An object of class [TreeVizApp](#)

See Also

[TreeVizApp](#)

Examples

```
# see package vignette for example usage
app <- startTreeviz(non_interactive=TRUE, open_browser=FALSE)
app$stop_app()
```

TreeIndex

create a new TreeIndex object

Description

create a new TreeIndex object

Usage

```
TreeIndex(hierarchy = NULL, feature_order = NULL)
```

Arguments

hierarchy	hierarchy as a data.table
feature_order	order of the tree if different from colnames

Value

a ‘TreeIndex‘ object

Examples

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
```

TreeIndex-class

TreeIndex class to manage and query hierarchical data

Description

TreeIndex class to manage and query hierarchical data

TreeViz

The TreeViz class.

Description

SummarizedExperiment-like class for datasets that have hierarchies on either rowData or colData. For microbiome data, rowData is a tree hierarchy For single cell data, colData is a tree hierarchy

Usage

```
TreeViz(assays = SimpleList(), rowData = NULL, colData = NULL, ...)
```

Arguments

assays	simple list of counts
rowData	rowData
colData	colData
...	other parameters for SummarizedExperiment

Value

a ‘TreeViz‘ object

Examples

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
mbiome <- TreeViz(SimpleList(counts=counts), rowData=tree)
```

TreeViz-class

TreeViz class wrapper for SummarizedExperiment objects

Description

TreeViz class wrapper for SummarizedExperiment objects

TreeVizApp-class

Class managing connection to metaviz application.

Description

Class managing connection to metaviz application.

Methods

plotGene(gene = NULL, datasource_name = "SCRNA_1") Plot a bar plot for a gene across cell types
gene gene to extract expression values
datasource_name object to extract from (automatically selected)

[,TreeIndex,ANY,ANY,ANY-method

Subset TreeIndex

Description

Subset TreeIndex

Generic method to get nodes at a tree level

Method to get nodes at a tree level

Generic method for possible node states

Method to get possible node states a node state is 0 if removed, 1 if expanded to show children & 2 if counts are aggregated to the node

Generic method to split the tree

splitAt divides the TreeIndex into groups defined by the level, node selections and filters(start, end)

Show the TreeIndex object

Usage

```

## S4 method for signature 'TreeIndex,ANY,ANY,ANY'
x[i, j, ... , drop = FALSE]

getNodes(x, ...)

## S4 method for signature 'TreeIndex'
getNodes(x, selectedLevel = NULL)

getNodeStates(x)

## S4 method for signature 'TreeIndex'
getNodeStates(x)

splitAt(x, ...)

## S4 method for signature 'TreeIndex'
splitAt(
  x,
  selectedLevel = 3,
  selectedNodes = NULL,
  start = 1,
  end = NULL,
  format = "list"
)

## S4 method for signature 'TreeIndex'
show(object)

```

Arguments

x	TreeIndex object
i, j	indices to subset or keep
...	other parameters
drop	drop the dimensions of the object. defaults to FALSE
selectedLevel	tree level to select nodes from
selectedNodes	used to set states on individual nodes to define a cut on the tree
start, end	indices to filter nodes by
format	return format can be one of "list" or "TreeIndex"
object	TreeIndex object

Value

a 'TreeIndex' subset object
a generic

levels at node cut
node state
node states
a generic
a ‘TreeIndex‘ object or type set in format
object description of the ‘TreeIndex‘ object

Examples

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
getNodes(tree)
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
getNodes(tree)
```

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
splitAt(tree)
```

```
library(metagenomeSeq)
data(mouseData)
counts <- MRcounts(mouseData)
hierarchy <- fData(mouseData)
tree <- TreeIndex(hierarchy)
splitAt(tree)
```

Index

```
.generate_hierarchy_tree, 2
.generate_leaf_of_table, 3
.generate_node_ids, 4
.generate_nodes_table, 4
.replaceNAFeatures, 5
[,TreeIndex,ANY,ANY,ANY-method], 15

aggregateTree (show,TreeViz-method), 10
aggregateTree,TreeViz-method
    (show,TreeViz-method), 10

ClusterHierarchy, 5
ClusterHierarchy-class, 6
createFromSCE, 6
createFromSeurat, 7
createTreeViz, 8

EpivizTreeData (EpivizTreeData-class), 9
EpivizTreeData-class, 9

getNodes
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
getNodes,TreeIndex-method
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
getNodeStates
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
getNodeStates,TreeIndex-method
    ([,TreeIndex,ANY,ANY,ANY-method),
     15

plot,TreeViz,ANY-method
    (show,TreeViz-method), 10

register,TreeViz-method
    (show,TreeViz-method), 10

set_gene_list, 10

show,TreeIndex-method
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
show,TreeViz-method, 10
splitAt
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
splitAt,TreeIndex-method
    ([,TreeIndex,ANY,ANY,ANY-method),
     15
startEpiviz, 13
startTreeviz, 12

TreeIndex, 13
TreeIndex-class, 14
TreeViz, 14
TreeViz-class, 15
TreeVizApp, 12, 13
TreeVizApp (TreeVizApp-class), 15
TreeVizApp-class, 15
```