

Package ‘MsCoreUtils’

October 15, 2023

Title Core Utils for Mass Spectrometry Data

Version 1.12.0

Description MsCoreUtils defines low-level functions for mass spectrometry data and is independent of any high-level data structures. These functions include mass spectra processing functions (noise estimation, smoothing, binning), quantitative aggregation functions (median polish, robust summarisation, ...), missing data imputation, data normalisation (quantiles, vsn, ...) as well as misc helper functions, that are used across high-level data structure within the R for Mass Spectrometry packages.

Depends R (>= 3.6.0)

Imports methods, S4Vectors, MASS, stats, clue

Suggests testthat, knitr, BiocStyle, rmarkdown, roxygen2, imputeLCMD, impute, norm, norm2, pcaMethods, vsn, Matrix, preprocessCore, missForest

Enhances HDF5Array

License Artistic-2.0

Encoding UTF-8

VignetteBuilder knitr

LinkingTo Rcpp

BugReports <https://github.com/RforMassSpectrometry/MsCoreUtils/issues>

URL <https://github.com/RforMassSpectrometry/MsCoreUtils>

biocViews Infrastructure, Proteomics, MassSpectrometry, Metabolomics

Roxygen list(markdown=TRUE)

RoxygenNote 7.2.3

git_url <https://git.bioconductor.org/packages/MsCoreUtils>

git_branch RELEASE_3_17

git_last_commit 14a3fdb

git_last_commit_date 2023-04-25

Date/Publication 2023-10-15

Author RforMassSpectrometry Package Maintainer [cre],

Laurent Gatto [aut] (<<https://orcid.org/0000-0002-1520-2268>>),

Johannes Rainer [aut] (<<https://orcid.org/0000-0002-6977-7147>>),

Sebastian Gibb [aut] (<<https://orcid.org/0000-0001-7406-4443>>),

Adriaan Sticker [ctb],

Sigurdur Smarason [ctb],

Thomas Naake [ctb],

Josep Maria Badia Aparicio [ctb]

(<<https://orcid.org/0000-0002-5704-1124>>),

Michael Witting [ctb] (<<https://orcid.org/0000-0002-1462-4426>>),

Samuel Wiczorek [ctb],

Roger Gine Bertomeu [ctb] (<<https://orcid.org/0000-0003-0288-9619>>)

Maintainer

RforMassSpectrometry Package Maintainer <maintainer@rformassspectrometry.org>

R topics documented:

.peakRegionMask	3
aggregate	4
between	6
bin	7
closest	9
coerce	13
colCounts	13
distance	14
gnps	16
group	19
i2index	20
impute_matrix	21
isPeaksMatrix	26
localMaxima	27
maxi	27
medianPolish	28
noise	29
normalizeMethods	30
ppm	31
rbindFill	32
refineCentroids	33
rla	34
robustSummary	36
rt2numeric	37
smooth	38
sumi	40
validPeaksMatrix	41
valleys	42
vapply1c	43

<code>.peakRegionMask</code>	3
<code>which.first</code>	44
Index	45

<code>.peakRegionMask</code>	<i>Peak Region Mask</i>
------------------------------	-------------------------

Description

This function finds the mz region spanning by a peak. It creates an 0/1 matrix used for multiplications in other functions.

Usage

```
.peakRegionMask(x, p, k = 30L)
```

Arguments

<code>x</code>	numeric, e.g. intensity values.
<code>p</code>	integer, indices of identified peaks/local maxima.
<code>k</code>	integer(1): maximum number of values left and right of the peak that should be looked for valleys.

Value

A matrix with a column for each peak in `p` and $2 * k + 1$ rows where the middle row `k + 1` is the peak centroid. If the values is 1 the index belongs to the peak region.

Author(s)

Sebastian Gibb

See Also

Other extreme value functions: [localMaxima\(\)](#), [refineCentroids\(\)](#), [valleys\(\)](#)

Examples

```
ints <- c(5, 8, 12, 7, 4, 9, 15, 16, 11, 8, 3, 2, 3, 2, 9, 12, 14, 13, 8, 3)
mzs <- seq_along(ints)
peaks <- which(localMaxima(ints, hws = 3L))

m <- MsCoreUtils:::.peakRegionMask(ints, peaks, k = 5L)
```

 aggregate

Aggregate quantitative features

Description

These functions take a matrix of quantitative features `x` and aggregate the features (rows) according to either a vector (or factor) `INDEX` or an adjacency matrix `MAT`. The aggregation method is defined by function `FUN`.

Adjacency matrices are an elegant way to explicitly encode for shared peptides (see example below) during aggregation.

Usage

```
colMeansMat(x, MAT, na.rm = FALSE)
colSumsMat(x, MAT, na.rm = FALSE)
aggregate_by_matrix(x, MAT, FUN, ...)
aggregate_by_vector(x, INDEX, FUN, ...)
```

Arguments

<code>x</code>	A matrix of mode numeric or an <code>HDF5Matrix</code> object of type numeric.
<code>MAT</code>	An adjacency matrix that defines peptide-protein relations with <code>nrow(MAT) == nrow(x)</code> : a non-missing/non-null value at position (i,j) indicates that peptide i belong to protein j. This matrix is typically binary but can also contain weighted relations.
<code>na.rm</code>	A <code>logical(1)</code> indicating whether the missing values (including <code>NaN</code>) should be omitted from the calculations or not. Defaults to <code>FALSE</code> .
<code>FUN</code>	A function to be applied to the subsets of <code>x</code> .
<code>...</code>	Additional arguments passed to <code>FUN</code> .
<code>INDEX</code>	A vector or factor of length <code>nrow(x)</code> .

Value

`aggregate_by_matrix()` returns a matrix (or `Matrix`) of dimensions `ncol(MAT)` and `ncol(x)`, with `dimnames` equal to `colnames(x)` and `rownames(MAT)`.

`aggregate_by_vector()` returns a new matrix (if `x` is a matrix) or `HDF5Matrix` (if `x` is an `HDF5Matrix`) of dimensions `length(INDEX)` and `ncol(x)`, with `dimnames` equal to `colnames(x)` and `INDEX`.

Vector-based aggregation functions

When aggregating with a vector/factor, user-defined functions must return a vector of length equal to `ncol(x)` for each level in `INDEX`. Examples thereof are:

- `medianPolish()` to fits an additive model (two way decomposition) using Tukey's median polish procedure using `stats::medpolish()`;
- `robustSummary()` to calculate a robust aggregation using `MASS::rlm()`;
- `base::colMeans()` to use the mean of each column;
- `base::colSums()` to use the sum of each column;
- `matrixStats::colMedians()` to use the median of each column.

Matrix-based aggregation functions

When aggregating with an adjacency matrix, user-defined functions must return a new matrix. Examples thereof are:

- `colSumsMat(x, MAT)` aggregates by the summing the peptide intensities for each protein. Shared peptides are re-used multiple times.
- `colMeansMat(x, MAT)` aggregation by the calculating the mean of peptide intensities. Shared peptides are re-used multiple times.

Handling missing values

By default, missing values in the quantitative data will propagate to the aggregated data. You can provide `na.rm = TRUE` to most functions listed above to ignore missing values, except for `robustSummary()` where you should supply `na.action = na.omit` (see `?MASS::rlm`).

Author(s)

Laurent Gatto and Samuel Wiczorek (aggregation from an adjacency matrix).

See Also

Other Quantitative feature aggregation: `colCounts()`, `medianPolish()`, `robustSummary()`

Examples

```
x <- matrix(c(10.39, 17.16, 14.10, 12.85, 10.63, 7.52, 3.91,
             11.13, 16.53, 14.17, 11.94, 11.51, 7.69, 3.97,
             11.93, 15.37, 14.24, 11.21, 12.29, 9.00, 3.83,
             12.90, 14.37, 14.16, 10.12, 13.33, 9.75, 3.81),
           nrow = 7,
           dimnames = list(paste0("Pep", 1:7), paste0("Sample", 1:4)))

x

## -----
## Aggregation by vector
## -----
```

```

(k <- paste0("Prot", c("B", "E", "X", "E", "B", "B", "E")))

aggregate_by_vector(x, k, colMeans)
aggregate_by_vector(x, k, robustSummary)
aggregate_by_vector(x, k, medianPolish)

## -----
## Aggregation by matrix
## -----

adj <- matrix(c(1, 0, 0, 1, 1, 1, 0, 0,
               1, 0, 1, 0, 0, 1, 0, 0,
               1, 0, 0, 0, 0, 1),
              nrow = 7,
              dimnames = list(paste0("Pep", 1:7),
                              paste0("Prot", c("B", "E", "X"))))

adj

## Peptide 4 is shared by 2 proteins (has a rowSums of 2),
## namely proteins B and E
rowSums(adj)

aggregate_by_matrix(x, adj, colSumsMat)
aggregate_by_matrix(x, adj, colMeansMat)

## -----
## Missing values
## -----

x <- matrix(c(NA, 2:6), ncol = 2,
            dimnames = list(paste0("Pep", 1:3),
                            c("S1", "S2")))

x

## simply use na.rm = TRUE to ignore missing values
## during the aggregation

(k <- LETTERS[c(1, 1, 2)])
aggregate_by_vector(x, k, colSums)
aggregate_by_vector(x, k, colSums, na.rm = TRUE)

(adj <- matrix(c(1, 1, 0, 0, 0, 1), ncol = 2,
               dimnames = list(paste0("Pep", 1:3),
                               c("A", "B"))))

aggregate_by_matrix(x, adj, colSumsMat, na.rm = FALSE)
aggregate_by_matrix(x, adj, colSumsMat, na.rm = TRUE)

```

Description

These functions help to work with numeric ranges.

Usage

```
between(x, range)
```

```
x %between% range
```

Arguments

x	numeric, input values.
range	numeric(2), range to compare against.

Value

logical vector of length length(x).

Author(s)

Sebastian Gibb

See Also

Other helper functions for developers: [isPeaksMatrix\(\)](#), [rbindFill\(\)](#), [validPeaksMatrix\(\)](#), [vapply1c\(\)](#), [which.first\(\)](#)

Examples

```
between(1:4, 2:3)
1:4 %between% 2:3
```

bin

Binning

Description

Aggregate values in x for bins defined on y: all values in x for values in y falling into a bin (defined on y) are aggregated with the provided function FUN.

Usage

```
bin(  
  x,  
  y,  
  size = 1,  
  breaks = seq(floor(min(y)), ceiling(max(y)), by = size),  
  FUN = max,  
  returnMids = TRUE,  
  .check = TRUE  
)
```

Arguments

x	numeric with the values that should be aggregated/binned.
y	numeric with same length than x with values to be used for the binning. y must be increasingly sorted, or else an error will be thrown.
size	numeric(1) with the size of a bin.
breaks	numeric defining the breaks (bins).
FUN	function to be used to aggregate values of x falling into the bins defined by breaks. FUN is expected to return a numeric(1).
returnMids	logical(1) whether the midpoints for the breaks should be returned in addition to the binned (aggregated) values of x. Setting returnMids = FALSE might be useful if the breaks are defined before hand and binning needs to be performed on a large set of values (i.e. within a loop for multiple pairs of x and y values).
.check	logical(1) whether to check that y is an ordered vector. Setting .check = FALSE will improve performance, provided you are sure that y is always ordered.

Value

Depending on the value of returnMids:

- returnMids = TRUE (the default): returns a list with elements x (aggregated values of x) and mids (the bin mid points).
- returnMids = FALSE: returns a numeric with just the binned values for x.

Author(s)

Johannes Rainer, Sebastian Gibb

See Also

Other grouping/matching functions: [closest\(\)](#), [gnps\(\)](#)

Examples

```
## Define example intensities and m/z values
ints <- abs(rnorm(20, mean = 40))
mz <- seq(1:length(ints)) + rnorm(length(ints), sd = 0.001)

## Bin intensities by m/z bins with a bin size of 2
bin(ints, mz, size = 2)

## Repeat but summing up intensities instead of taking the max
bin(ints, mz, size = 2, FUN = sum)

## Get only the binned values without the bin mid points.
bin(ints, mz, size = 2, returnMids = FALSE)
```

closest

Relaxed Value Matching

Description

These functions offer relaxed matching of one vector in another. In contrast to the similar [match\(\)](#) and [%in%](#) functions they just accept numeric arguments but have an additional tolerance argument that allows relaxed matching.

Usage

```
closest(
  x,
  table,
  tolerance = Inf,
  ppm = 0,
  duplicates = c("keep", "closest", "remove"),
  nomatch = NA_integer_,
  .check = TRUE
)

common(
  x,
  table,
  tolerance = Inf,
  ppm = 0,
  duplicates = c("keep", "closest", "remove"),
  .check = TRUE
)

join(
  x,
  y,
```

```

    tolerance = 0,
    ppm = 0,
    type = c("outer", "left", "right", "inner"),
    .check = TRUE,
    ...
)

```

Arguments

x	numeric, the values to be matched. In contrast to <code>match()</code> x has to be sorted in increasing order and must not contain any NA.
table	numeric, the values to be matched against. In contrast to <code>match()</code> table has to be sorted in increasing order and must not contain any NA.
tolerance	numeric, accepted tolerance. Could be of length one or the same length as x.
ppm	numeric(1) representing a relative, value-specific parts-per-million (PPM) tolerance that is added to tolerance.
duplicates	character(1), how to handle duplicated matches. Has to be one of <code>c("keep", "closest", "remove")</code> . No abbreviations allowed.
nomatch	integer(1), if the difference between the value in x and table is larger than tolerance nomatch is returned.
.check	logical(1) turn off checks for increasingly sorted x and y. This should just be done if it is ensured by other methods that x and y are sorted, see also <code>closest()</code> .
y	numeric, the values to be joined. Should be sorted.
type	character(1), defines how x and y should be joined. See details for join.
...	ignored.

Details

For `closest/common` the tolerance argument could be set to 0 to get the same results as for `match()/%in%`. If it is set to Inf (default) the index of the closest values is returned without any restriction.

It is not guaranteed that there is a one-to-one matching for neither the x to table nor the table to x matching.

If multiple elements in x match a single element in table all their corresponding indices are returned if `duplicates="keep"` is set (default). This behaviour is identical to `match()`. For `duplicates="closest"` just the closest element in x gets the corresponding index in table and for `duplicates="remove"` all elements in x that match to the same element in table are set to `nomatch`.

If a single element in x matches multiple elements in table the *closest* is returned for `duplicates="keep"` or `duplicates="closest"` (*keeping* multiple matches isn't possible in this case because the return value should be of the same length as x). If the differences between x and the corresponding matches in table are identical the lower index (the smaller element in table) is returned. There is one exception: if the lower index is already returned for another x with a smaller difference to this index the higher one is returned for `duplicates = "closer"` (but only if there is no other x that is closer

to the higher one). For `duplicates="remove"` all multiple matches are returned as `nomatch` as above.

`.checks = TRUE` tests among other input validation checks for increasingly sorted `x` and `table` arguments that are mandatory assumptions for the `closest` algorithm. These checks require to loop through both vectors and compare each element against its precursor. Depending on the length and distribution of `x` and `table` these checks take equal/more time than the whole `closest` algorithm. If it is ensured by other methods that both arguments `x` and `table` are sorted the tests could be skipped by `.check = FALSE`. In the case that `.check = FALSE` is used and one of `x` and `table` is not sorted (or decreasingly sorted) the output would be incorrect in the best case and result in infinity loop in the average and worst case.

`join`: joins two numeric vectors by mapping values in `x` with values in `y` and *vice versa* if they are similar enough (provided the `tolerance` and `ppm` specified). The function returns a `matrix` with the indices of mapped values in `x` and `y`. Parameter `type` allows to define how the vectors will be joined: `type = "left"`: values in `x` will be mapped to values in `y`, elements in `y` not matching any value in `x` will be discarded. `type = "right"`: same as `type = "left"` but for `y`. `type = "outer"`: return matches for all values in `x` and in `y`. `type = "inner"`: report only indices of values that could be mapped.

Value

`closest` returns an integer vector of the same length as `x` giving the closest position in `table` of the first match or `nomatch` if there is no match.

`common` returns a logical vector of length `x` that is `TRUE` if the element in `x` was found in `table`. It is similar to `%in%`.

`join` returns a `matrix` with two columns, namely `x` and `y`, representing the index of the values in `x` matching the corresponding value in `y` (or `NA` if the value does not match).

Note

`join` is based on `closest(x, y, tolerance, duplicates = "closest")`. That means for multiple matches just the closest one is reported.

Author(s)

Sebastian Gibb, Johannes Rainer

See Also

`match()`

`%in%`

Other grouping/matching functions: `bin()`, `gnps()`

Examples

```
## Define two vectors to match
x <- c(1, 3, 5)
y <- 1:10
```

```
## Compare match and closest
match(x, y)
closest(x, y)

## If there is no exact match
x <- x + 0.1
match(x, y) # no match
closest(x, y)

## Some new values
x <- c(1.11, 45.02, 556.45)
y <- c(3.01, 34.12, 45.021, 46.1, 556.449)

## Using a single tolerance value
closest(x, y, tolerance = 0.01)

## Using a value-specific tolerance accepting differences of 20 ppm
closest(x, y, ppm = 20)

## Same using 50 ppm
closest(x, y, ppm = 50)

## Sometimes multiple elements in `x` match to `table`
x <- c(1.6, 1.75, 1.8)
y <- 1:2
closest(x, y, tolerance = 0.5)
closest(x, y, tolerance = 0.5, duplicates = "closest")
closest(x, y, tolerance = 0.5, duplicates = "remove")

## Are there any common values?
x <- c(1.6, 1.75, 1.8)
y <- 1:2
common(x, y, tolerance = 0.5)
common(x, y, tolerance = 0.5, duplicates = "closest")
common(x, y, tolerance = 0.5, duplicates = "remove")

## Join two vectors
x <- c(1, 2, 3, 6)
y <- c(3, 4, 5, 6, 7)

jo <- join(x, y, type = "outer")
jo
x[jo$x]
y[jo$y]

jl <- join(x, y, type = "left")
jl
x[jl$x]
y[jl$y]

jr <- join(x, y, type = "right")
jr
x[jr$x]
```

```
y[jr$y]
ji <- join(x, y, type = "inner")
ji
x[ji$x]
y[ji$y]
```

coerce

Coerce functions

Description

- `asInteger`: convert `x` to an integer and throw an error if `x` is not a numeric.

Usage

```
asInteger(x)
```

Arguments

`x` input argument.

Author(s)

Johannes Rainer

Examples

```
## Convert numeric to integer
asInteger(3.4)

asInteger(3)
```

colCounts

Counts the number of features

Description

Returns the number of non-NA features in a features by sample matrix.

Usage

```
colCounts(x, ...)
```

Arguments

`x` A matrix of mode numeric.
`...` Currently ignored.

Value

A numeric vector of length identical to `ncol(x)`.

Author(s)

Laurent Gatto

See Also

Other Quantitative feature aggregation: [aggregate\(\)](#), [medianPolish\(\)](#), [robustSummary\(\)](#)

Examples

```
m <- matrix(c(1, NA, 2, 3, NA, NA, 4, 5, 6),
            nrow = 3)
colCounts(m)
m <- matrix(rnorm(30), nrow = 3)
colCounts(m)
```

distance

Spectra Distance/Similarity Measurements

Description

These functions provide different normalized similarity/distance measurements.

Usage

```
ndotproduct(x, y, m = 0L, n = 0.5, na.rm = TRUE, ...)
```

```
dotproduct(x, y, m = 0L, n = 0.5, na.rm = TRUE, ...)
```

```
neuclidean(x, y, m = 0L, n = 0.5, na.rm = TRUE, ...)
```

```
navdist(x, y, m = 0L, n = 0.5, na.rm = TRUE, ...)
```

```
nspectraangle(x, y, m = 0L, n = 0.5, na.rm = TRUE, ...)
```

Arguments

x	matrix, two-columns e.g. m/z, intensity
y	matrix, two-columns e.g. m/z, intensity
m	numeric, weighting for the first column of x and y (e.g. "mz"), default: 0 means don't weight by the first column. For more details see the <code>ndotproduct</code> details section.

n	numeric, weighting for the second column of x and y (e.g. "intensity"), default: 0.5 means effectly using $\sqrt{x[, 2]}$ and $\sqrt{y[, 2]}$. For more details see the <code>ndotproduct</code> details section.
na.rm	logical(1), should NA be removed prior to calculation (default TRUE).
...	ignored.

Details

All functions that calculate normalized similarity/distance measurements are prefixed with a *n*.

`ndotproduct`: the normalized dot product is described in Stein and Scott 1994 as: $NDP = \frac{\sum(W_1 W_2)^2}{\sum(W_1)^2 \sum(W_2)^2}$; where $W_i = x^m * y^n$, where x and y are the m/z and intensity values, respectively. Please note also that $NDP = N\text{Cos}^2$; where $N\text{Cos}$ is the cosine value (i.e. the orthodox normalized dot product) of the intensity vectors as described in Yilmaz et al. 2017. Stein and Scott 1994 empirically determined the optimal exponents as $m = 3$ and $n = 0.6$ by analyzing ca. 12000 EI-MS data of 8000 organic compounds in the NIST Mass Spectral Library. MassBank (Horai et al. 2010) uses $m = 2$ and $n = 0.5$ for small compounds. In general with increasing values for m , high m/z values will be taken more into account for similarity calculation. Especially when working with small molecules, a value $n > 0$ can be set to give a weight on the m/z values to accommodate that shared fragments with higher m/z are less likely and will mean that molecules might be more similar. Increasing n will result in a higher importance of the intensity values. Most commonly $m = 0$ and $n = 0.5$ are used.

`neuclidean`: the normalized euclidean distance is described in Stein and Scott 1994 as: $NED = (1 + \frac{\sum((W_1 - W_2)^2)}{\text{sum}((W_2)^2)})^{-1}$; where $W_i = x^m * y^n$, where x and y are the m/z and intensity values, respectively. See the details section about `ndotproduct` for an explanation how to set m and n .

`navdist`: the normalized absolute values distance is described in Stein and Scott 1994 as: $NED = (1 + \frac{\sum(|W_1 - W_2|)}{\text{sum}((W_2))})^{-1}$; where $W_i = x^m * y^n$, where x and y are the m/z and intensity values, respectively. See the details section about `ndotproduct` for an explanation how to set m and n .

`nspectraangle`: the normalized spectra angle is described in Toprak et al 2014 as: $NSA = 1 - \frac{2 * \cos^{-1}(W_1 \cdot W_2)}{\pi}$; where $W_i = x^m * y^n$, where x and y are the m/z and intensity values, respectively. The weighting was not originally proposed by Toprak et al. 2014. See the details section about `ndotproduct` for an explanation how to set m and n .

Value

double(1) value between 0:1, where 0 is completely different and 1 identically.

Note

These methods are implemented as described in Stein and Scott 1994 (`navdist`, `ndotproduct`, `neuclidean`) and Toprak et al. 2014 (`nspectraangle`) but because there is no reference implementation available we are unable to guarantee that the results are identical. Note that the Stein and Scott 1994 normalized dot product method (and by extension `ndotproduct`) corresponds to the square of the orthodox normalized dot product (or cosine distance) used also commonly as spectrum similarity measure (Yilmaz et al. 2017). Please see also the corresponding discussion at the github pull request linked below. If you find any problems or reference implementation please open an issue at <https://github.com/rformassspectrometry/MsCoreUtils/issues>.

Author(s)

navdist, neuclidean, nspectraangle: Sebastian Gibb

ndotproduct: Sebastian Gibb and Thomas Naake, <thomasnaake@googlemail.com>

References

Stein, S. E., and Scott, D. R. (1994). Optimization and testing of mass spectral library search algorithms for compound identification. *Journal of the American Society for Mass Spectrometry*, 5(9), 859–866. doi:10.1016/10440305(94)870098.

Yilmaz, S., Vandermarliere, E., and Lennart Martens (2017). Methods to Calculate Spectrum Similarity. In S. Keerthikumar and S. Mathivanan (eds.), *Proteome Bioinformatics: Methods in Molecular Biology*, vol. 1549 (pp. 81). doi:10.1007/9781493967407_7.

Horai et al. (2010). MassBank: a public repository for sharing mass spectral data for life sciences. *Journal of mass spectrometry*, 45(7), 703–714. doi:10.1002/jms.1777.

Toprak et al. (2014). Conserved peptide fragmentation as a benchmarking tool for mass spectrometers and a discriminating feature for targeted proteomics. *Molecular & Cellular Proteomics : MCP*, 13(8), 2056–2071. doi:10.1074/mcp.O113.036475.

Pull Request for these distance/similarity measurements: <https://github.com/rformassspectrometry/MsCoreUtils/pull/33>

See Also

Other distance/similarity functions: [gnps\(\)](#)

Examples

```
x <- matrix(c(1:5, 1:5), ncol = 2, dimnames = list(c(), c("mz", "intensity")))
y <- matrix(c(1:5, 5:1), ncol = 2, dimnames = list(c(), c("mz", "intensity")))
```

```
ndotproduct(x, y)
ndotproduct(x, y, m = 2, n = 0.5)
ndotproduct(x, y, m = 3, n = 0.6)
```

```
neuclidean(x, y)
```

```
navdist(x, y)
```

```
nspectraangle(x, y)
```

Description

The `join_gnps` and `gnps` functions allow to calculate spectra similarity scores as used in **GNPS**. The approach matches first peaks between the two spectra directly using a user-defined ppm and/or tolerance as well as using a fixed delta m/z (considering the same ppm and tolerance) that is defined by the difference of the two spectras' precursor m/z values. For peaks that match multiple peaks in the other spectrum only the matching peak pair with the higher value/similarity is considered in the final similarity score calculation. Note that GNPS similarity scores are calculated only if the two functions are used together.

- `join_gnps`: matches/maps peaks between spectra with the same approach as in GNPS: peaks are considered matching if a) the difference in their m/z values is smaller than defined by tolerance and ppm (this is the same as `joinPeaks`) **and** b) the difference of their m/z *adjusted* for the difference of the spectras' precursor is smaller than defined by tolerance and ppm. Based on this definition, peaks in x can match up to two peaks in y hence returned peak indices might be duplicated. Note that if one of `xPrecursorMz` or `yPrecursorMz` are NA or if both are the same, the results are the same as with `join()`. The function returns a list of two integer vectors with the indices of the peaks matching peaks in the other spectrum or NA otherwise.
- `gnps`: calculates the GNPS similarity score on peak matrices' previously *aligned* (matched) with `join_gnps`. For multi-mapping peaks the pair with the higher similarity are considered in the final score calculation.

Usage

```
gnps(x, y, ...)
```

```
join_gnps(
  x,
  y,
  xPrecursorMz = NA_real_,
  yPrecursorMz = NA_real_,
  tolerance = 0,
  ppm = 0,
  type = "outer",
  ...
)
```

Arguments

x	for <code>join_gnps</code> : numeric with m/z values from a spectrum. For <code>gnps</code> : matrix with two columns "mz" and "intensity" containing the peaks aligned with peaks in y (with <code>join_gnps</code>).
y	for <code>join_gnps</code> : numeric with m/z values from a spectrum. For <code>gnps</code> : matrix with two columns "mz" and "intensity" containing the peaks aligned with peaks in x (with <code>join_gnps</code>).
...	for <code>join_gnps</code> : optional parameters passed to the <code>join()</code> function. For <code>gnps</code> : ignored.
xPrecursorMz	for <code>join_gnps</code> : numeric(1) with the precursor m/z of the spectrum x.

yPrecursorMz	for join_gnps: numeric(1) with the precursor m/z of the spectrum y.
tolerance	for join_gnps: numeric(1) defining a constant maximal accepted difference between m/z values of peaks from the two spectra to be matched/mapped.
ppm	for join_gnps: numeric(1) defining a relative, m/z-dependent, maximal accepted difference between m/z values of peaks from the two spectra to be matched/mapped.
type	for join_gnps: character(1) specifying the type of join that should be performed. See join() for details and options. Defaults to type = "outer".

Details

The implementation of gnps bases on the R code from the publication listed in the references.

Value

See function definition in the description section.

Author(s)

Johannes Rainer, Michael Witting, based on the code from Xing *et al.* (2020).

References

Xing S, Hu Y, Yin Z, Liu M, Tang X, Fang M, Huan T. Retrieving and Utilizing Hypothetical Neutral Losses from Tandem Mass Spectra for Spectral Similarity Analysis and Unknown Metabolite Annotation. *Anal Chem.* 2020 Nov 3;92(21):14476-14483. doi:10.1021/acs.analchem.0c02521.

See Also

Other grouping/matching functions: [bin\(\)](#), [closest\(\)](#)

Other distance/similarity functions: [distance](#)

Examples

```
## Define spectra
x <- cbind(mz = c(10, 36, 63, 91, 93), intensity = c(14, 15, 999, 650, 1))
y <- cbind(mz = c(10, 12, 50, 63, 105), intensity = c(35, 5, 16, 999, 450))
## The precursor m/z
pmz_x <- 91
pmz_y <- 105

## Plain join identifies only 2 matching peaks
join(x[, 1], y[, 1])

## join_gnps finds 4 matches
join_gnps(x[, 1], y[, 1], pmz_x, pmz_y)

## with one of the two precursor m/z being NA, the result are the same as
## with join.
join_gnps(x[, 1], y[, 1], pmz_x, yPrecursorMz = NA)
```



```
group(x, tolerance = 0.05)

## Also values 56, 56.05 and 56.1 were grouped into a single group,
## although the difference between the smallest 56 and largest value in
## this group (56.1) is 0.1. The (pairwise) difference between the ordered
## values is however 0.05.

## With ppm
group(x, ppm = 10)

## Same on an unsorted vector
x <- c(65, 34, 65.1, 35, 66, 65.2)
group(x, tolerance = 0.1)

## Values 65, 65.1 and 65.2 have been grouped into the same group.
```

i2index

Input parameter check for subsetting operations

Description

i2index is a simple helper function to be used in subsetting functions. It checks and converts the parameter *i*, which can be of type integer, logical or character to integer vector that can be used as index for subsetting.

Usage

```
i2index(i, length = length(i), names = NULL)
```

Arguments

<i>i</i>	character logical or integer used in [<i>i</i>] for subsetting.
<i>length</i>	integer representing the length of the object to be subsetted.
<i>names</i>	character with the names (rownames or similar) of the object. This is only required if <i>i</i> is of type character.

Value

integer with the indices

Author(s)

Johannes Rainer

Examples

```
## With `i` being an `integer`  
i2index(c(4, 1, 3), length = 10)  
  
## With `i` being a `logical`  
i2index(c(TRUE, FALSE, FALSE, TRUE, FALSE), length = 5)  
  
## With `i` being a `character`  
i2index(c("b", "a", "d"), length = 5, names = c("a", "b", "c", "d", "e"))
```

impute_matrix

Quantitative mass spectrometry data imputation

Description

The `impute_matrix` function performs data imputation on `matrix` objects instance using a variety of methods (see below).

Users should proceed with care when imputing data and take precautions to assure that the imputation produces valid results, in particular with naive imputations such as replacing missing values with 0.

Usage

```
impute_matrix(x, method, FUN, ...)  
  
imputeMethods()  
  
impute_neighbour_average(x, k = min(x, na.rm = TRUE), MARGIN = 1L)  
  
impute_knn(x, MARGIN = 1L, ...)  
  
impute_mle(x, MARGIN = 2L, ...)  
  
impute_mle2(x, MARGIN = 2L, ...)  
  
impute_bpca(x, MARGIN = 1L, ...)  
  
impute_RF(x, MARGIN = 2L, ...)  
  
impute_mixed(x, randna, mar, mnar, MARGIN = 1L, ...)  
  
impute_min(x)  
  
impute_MinDet(x, q = 0.01, MARGIN = 2L)  
  
impute_MinProb(x, q = 0.01, sigma = 1, MARGIN = 2L)
```

```
impute_QRILC(x, sigma = 1, MARGIN = 2L)
```

```
impute_zero(x)
```

```
impute_with(x, val)
```

```
impute_fun(x, FUN, MARGIN = 1L, ...)
```

```
getImputeMargin(fun)
```

Arguments

x	A matrix or an <code>HDF5Matrix</code> object to be imputed.
method	character(1) defining the imputation method. See <code>imputeMethods()</code> for available ones.
FUN	A user-provided function that takes a matrix as input and returns an imputed matrix of identical dimensions.
...	Additional parameters passed to the inner imputation function.
k	numeric(1) providing the imputation value used for the first and last samples if they contain an NA. The default is to use the smallest value in the data.
MARGIN	integer(1) defining the margin along which to apply imputation, with 1L for rows and 2L for columns. The default value will depend on the imputation method. Use <code>getImputeMargin(fun)</code> to get the default margin of imputation function <code>fun</code> . If the function doesn't take a margin argument, NA is returned.
randna	logical of length equal to <code>nrow(object)</code> defining which rows are missing at random. The other ones are considered missing not at random. Only relevant when <code>methods</code> is mixed.
mar	Imputation method for values missing at random. See <code>method</code> above.
mnar	Imputation method for values missing not at random. See <code>method</code> above.
q	numeric(1) indicating the quantile to be used to estimate the minimum in <code>MinDet</code> and <code>MinProb</code> . Default is 0.01.
sigma	numeric(1) controlling the standard deviation of the MNAR distribution in <code>MinProb</code> and <code>QRILC</code> . Default is 1.
val	numeric(1) used to replace all missing values.
fun	The imputation function to get the default margin from.

Value

A matrix of same class as `x` with dimensions `dim(x)`.

Types of missing values

There are two types of mechanisms resulting in missing values in LC/MSMS experiments.

- Missing values resulting from absence of detection of a feature, despite ions being present at detectable concentrations. For example in the case of ion suppression or as a result from the stochastic, data-dependent nature of the DDA MS acquisition method. These missing values are expected to be randomly distributed in the data and are defined, in statistical terms, as missing at random (MAR) or missing completely at random (MCAR).
- Biologically relevant missing values resulting from the absence or the low abundance of ions (i.e. below the limit of detection of the instrument). These missing values are not expected to be randomly distributed in the data and are defined as missing not at random (MNAR).

MNAR features should ideally be imputed with a left-censor method, such as QRILC below. Conversely, it is recommended to use hot deck methods such nearest neighbours, Bayesian missing value imputation or maximum likelihood methods when values are missing at random.

Imputing by rows or columns

We assume that the input matrix x contains features along the rows and samples along the columns, as is generally the case in omics data analysis. When performing imputation, the missing values are taken as a feature-specific property: feature x is missing because it is absent (in a sample or group), or because it was missed during acquisition (not selected during data dependent acquisition) or data processing (not identified or with an identification score below a chosen false discovery threshold). As such, imputation is by default performed at the *feature level*. In some cases, such as imputation by zero or a global minimum value, it doesn't matter. In other cases, it does matter very much, such as for example when using the minimum value computed for each margin (i.e. row or column) as in the *MinDet* method (see below) - do we want to use the minimum of the sample or of that feature? KNN is another such example: do we consider the most similar features to impute a feature with missing values, or the most similar samples to impute all missing in a sample.

The MARGIN argument can be used to change the imputation margin from features/rows (MARGIN = 1) to samples/columns (MARGIN = 2). Different imputations will have different default values, and changing this parameter can have a major impact on imputation results and downstream results.

Imputation methods

Currently, the following imputation methods are available.

- *MLE*: Maximum likelihood-based imputation method using the EM algorithm. The `impute_mle()` function relies on `norm::imp.norm()` function. See `norm::imp.norm()` for details and additional parameters. Note that here, `...` are passed to the `norm::em.norm()` function, rather than to the actual imputation function `imp.norm`. The `impute_mle2()` function uses the more recent `norm2::emNorm()` function that is more reliable when the number of variables exceed 30.
- *bPCA*: Bayesian missing value imputation are available, as implemented in the `pcaMethods::pca()` function. See `pcaMethods::pca()` for details and additional parameters.
- *RF*: Random Forest imputation, as implemented in the `missForest::missForest` function. See `missForest::missForest()` for details and additional parameters.
- *knn*: Nearest neighbour averaging, as implemented in the `impute::impute.knn` function. See `impute::impute.knn()` for details and additional parameters.
- *QRILC*: A missing data imputation method that performs the imputation of left-censored missing data using random draws from a truncated distribution with parameters estimated using quantile regression. The `impute_QRILC()` function calls `imputeLCMD::impute.QRILC()` from the `imputeLCMD` package.

- *MinDet*: Performs the imputation of left-censored missing data using a deterministic minimal value approach. Considering an expression data with n samples and p features, for each sample, the missing entries are replaced with a minimal value observed in that sample. The minimal value observed is estimated as being the q -th quantile (default $q = 0.01$) of the observed values in that sample. The implementation is based on the `imputeLCMD::impute.MinDet()` function.
- *MinProb*: Performs the imputation of left-censored missing data by random draws from a Gaussian distribution centred to a minimal value. Considering an expression data matrix with n samples and p features, for each sample, the mean value of the Gaussian distribution is set to a minimal observed value in that sample. The minimal value observed is estimated as being the q -th quantile (default $q = 0.01$) of the observed values in that sample. The standard deviation is estimated as the median of the feature (or sample) standard deviations. Note that when estimating the standard deviation of the Gaussian distribution, only the peptides/proteins which present more than 50 values are considered. The `impute_MinProb()` function calls `imputeLCMD::impute.MinProb()` from the `imputeLCMD` package.
- *min*: Replaces the missing values with the smallest non-missing value in the data.
- *zero*: Replaces the missing values with 0.
- *mixed*: A mixed imputation applying two methods (to be defined by the user as `mar` for values missing at random and `mnr` for values missing not at random, see example) on two MCAR/MNAR subsets of the data (as defined by the user by a `randna` logical, of length equal to `nrow(object)`).
- *nbavg*: Average neighbour imputation for fractions collected along a fractionation/separation gradient, such as sub-cellular fractions. The method assumes that the fraction are ordered along the gradient and is invalid otherwise.
Continuous sets NA value at the beginning and the end of the quantitation vectors are set to the lowest observed value in the data or to a user defined value passed as argument `k`. Then, when a missing value is flanked by two non-missing neighbouring values, it is imputed by the mean of its direct neighbours.
- *with*: Replaces all missing values with a user-provided value.
- *none*: No imputation is performed and the missing values are left untouched. Implemented in case one wants to only impute value missing at random or not at random with the *mixed* method.

The `imputeMethods()` function returns a vector with valid imputation method names. Use `getImputeMargin()` to get the default margin for each imputation function.

Author(s)

Laurent Gatto

References

- Olga Troyanskaya, Michael Cantor, Gavin Sherlock, Pat Brown, Trevor Hastie, Robert Tibshirani, David Botstein and Russ B. Altman, Missing value estimation methods for DNA microarrays *Bioinformatics* (2001) 17 (6): 520-525.
- Oba et al., A Bayesian missing value estimation method for gene expression profile data, *Bioinformatics* (2003) 19 (16): 2088-2096.

Cosmin Lazar (2015). imputeLCMD: A collection of methods for left-censored missing data imputation. R package version 2.0. <http://CRAN.R-project.org/package=imputeLCMD>.

Lazar C, Gatto L, Ferro M, Bruley C, Burger T. Accounting for the Multiple Natures of Missing Values in Label-Free Quantitative Proteomics Data Sets to Compare Imputation Strategies. J Proteome Res. 2016 Apr 1;15(4):1116-25. doi: 10.1021/acs.jproteome.5b00981. PubMed PMID:26906401.

Examples

```
## test data
set.seed(42)
m <- matrix(rlnorm(60), 10)
dimnames(m) <- list(letters[1:10], LETTERS[1:6])
m[sample(60, 10)] <- NA

## available methods
imputeMethods()

impute_matrix(m, method = "zero")

impute_matrix(m, method = "min")

impute_matrix(m, method = "knn")

## same as impute_zero
impute_matrix(m, method = "with", val = 0)

## impute with half of the smallest value
impute_matrix(m, method = "with",
              val = min(m, na.rm = TRUE) * 0.5)

## all but third and fourth features' missing values
## are the result of random missing values
randna <- rep(TRUE, 10)
randna[c(3, 9)] <- FALSE

impute_matrix(m, method = "mixed",
              randna = randna,
              mar = "knn",
              mmar = "min")

## user provided (random) imputation function
random_imp <- function(x) {
  m <- mean(x, na.rm = TRUE)
  sdev <- sd(x, na.rm = TRUE)
  n <- sum(is.na(x))
  x[is.na(x)] <- rnorm(n, mean = m, sd = sdev)
  x
}

impute_matrix(m, FUN = random_imp)
```

```
## get the default margin
getImputeMargin(impute_knn) ## default imputes along features

getImputeMargin(impute_mle) ## default imputes along samples

getImputeMargin(impute_zero) ## NA: no margin here

## default margin for all MsCoreUtils::impute_* functions
sapply(ls("package:MsCoreUtils", pattern = "impute_"), getImputeMargin)
```

isPeaksMatrix

Check functions

Description

These functions are used to check input arguments.

Usage

```
isPeaksMatrix(x)
```

Arguments

x object to test.

Details

isPeaksMatrix: test for a numeric matrix with two columns named "mz" and "intensity". The "mz" column has to be sorted increasingly.

Value

logical(1), TRUE if checks are successful otherwise FALSE.

Author(s)

Sebastian Gibb

See Also

Other helper functions for developers: [between\(\)](#), [rbindFill\(\)](#), [validPeaksMatrix\(\)](#), [vapply1c\(\)](#), [which.first\(\)](#)

Examples

```
isPeaksMatrix(1:2)
isPeaksMatrix(cbind(mz = 2:1, intensity = 1:2))
isPeaksMatrix(cbind(mz = 1:2, intensity = 1:2))
```

localMaxima	<i>Local Maxima</i>
-------------	---------------------

Description

This function finds local maxima in a numeric vector. A local maximum is defined as maximum in a window of the current index +/- hws.

Usage

```
localMaxima(x, hws = 1L)
```

Arguments

x	numeric, vector that should be searched for local maxima.
hws	integer(1), half window size, the resulting window reaches from (i - hws):(i + hws).

Value

A logical of the same length as x that is TRUE for each local maxima.

Author(s)

Sebastian Gibb

See Also

Other extreme value functions: [.peakRegionMask\(\)](#), [refineCentroids\(\)](#), [valleys\(\)](#)

Examples

```
x <- c(1:5, 4:1, 1:10, 9:1, 1:5, 4:1)
localMaxima(x)
localMaxima(x, hws = 10)
```

maxi	<i>Maximum MS Intensity Value</i>
------	-----------------------------------

Description

maxi determines the maximum or mass spectrometry intensity values, e.g. from a spectrum or chromatogram. In contrast to the base R [max\(\)](#) function this function returns NA_real_ if all intensity values are NA or if length(x) is 0 (the base R max function returns -Inf in these cases).

Usage

```
maxi(x)
```

Arguments

`x` numeric with intensity values from which the maximum should be reported. Will be coerced to numeric.

Value

numeric(1) representing the maximum of values in `x`. Returns always a numeric (double) even if `x` is an integer.

Author(s)

Johannes Rainer, Sebastian Gibb

See Also

[sumi\(\)](#)

Examples

```
x <- c(3.2, 34.4, 1.3, NA)
maxi(x)

## Compared to base R max:
max(x)
max(x, na.rm = TRUE)

max(numeric(), na.rm = TRUE)
maxi(numeric())

max(c(NA, NA), na.rm = TRUE)
maxi(c(NA, NA))
```

medianPolish

Return the Median Polish (Robust Twoway Decomposition) of a matrix

Description

Fits an additive model (two way decomposition) using Tukey's median polish procedure using [stats::medpolish\(\)](#).

Usage

```
medianPolish(x, verbose = FALSE, ...)
```

Arguments

`x` A matrix of mode numeric.
`verbose` Default is FALSE.
`...` Additional arguments passed to `stats::medpolish()`.

Value

A numeric vector of length identical to `ncol(x)`.

Author(s)

Laurent Gatto

See Also

Other Quantitative feature aggregation: `aggregate()`, `colCounts()`, `robustSummary()`

Examples

```
x <- matrix(rnorm(30), nrow = 3)
medianPolish(x)
```

noise	<i>Noise Estimation</i>
-------	-------------------------

Description

This functions estimate the noise in the data.

Usage

```
noise(x, y, method = c("MAD", "SuperSmoother"), ...)
```

Arguments

`x` numeric, x values for noise estimation (e.g. *mz*)
`y` numeric, y values for noise estimation (e.g. intensity)
`method` character(1) used method. Currently MAD (median absolute deviation) and Friedman's SuperSmoother are supported.
`...` further arguments passed to method.

Value

A numeric of the same length as `x` with the estimated noise.

Author(s)

Sebastian Gibb

See Also`stats::mad()`, `stats::supsmu()`Other noise estimation and smoothing functions: `smooth()`**Examples**

```
x <- 1:20
y <- c(1:10, 10:1)
noise(x, y)
noise(x, y, method = "SuperSmoother", span = 1 / 3)
```

normalizeMethods

Quantitative data normalisation

Description

Function to normalise a matrix of quantitative omics data. The nature of the normalisation is controlled by the method argument, described below.

Usage

```
normalizeMethods()
```

```
normalize_matrix(x, method, ...)
```

Arguments

x	A matrix or an HDF5Matrix object to be normalised.
method	character(1) defining the normalisation method. See <code>normalizeMethods()</code> for available ones.
...	Additional parameters passed to the inner normalisation function.

Details

The method parameter can be one of "sum", "max", "center.mean", "center.median", "div.mean", "div.median", "diff.meda", "quantiles", "quantiles.robust" or "vsn". The `normalizeMethods()` function returns a vector of available normalisation methods.

- For "sum" and "max", each feature's intensity is divided by the maximum or the sum of the feature respectively. These two methods are applied along the features (rows).
- "center.mean" and "center.median" center the respective sample (column) intensities by subtracting the respective column means or medians. "div.mean" and "div.median" divide by the column means or medians.

- "diff.median" centers all samples (columns) so that they all match the grand median by subtracting the respective columns medians differences to the grand median.
- Using "quantiles" or "quantiles.robust" applies (robust) quantile normalisation, as implemented in `preprocessCore::normalize.quantiles()` and `preprocessCore::normalize.quantiles.robust()`. "vsr" uses the `vsr::vsr2()` function. Note that the latter also glog-transforms the intensities. See respective manuals for more details and function arguments.

Value

A matrix of same class as `x` with dimensions `dim(x)`.

Author(s)

Laurent Gatto

See Also

The `scale()` function that centers (like `center.mean` above) and scales.

Examples

```
normalizeMethods()

## test data
set.seed(42)
m <- matrix(rlnorm(60), 10)

normalize_matrix(m, method = "sum")

normalize_matrix(m, method = "max")

normalize_matrix(m, method = "quantiles")

normalize_matrix(m, method = "center.mean")
```

ppm

PPM - Parts per Million

Description

`ppm` is a small helper function to determine the parts-per-million for a user-provided value and `ppm`.

Usage

```
ppm(x, ppm)
```

Arguments

`x` numeric, value(s) used for ppm calculation, e.g. m/z value(s).
`ppm` numeric, parts-per-million (ppm) value(s).

Value

numeric: parts-per-million of x (always a positive value).

Author(s)

Sebastian Gibb

Examples

```
ppm(c(1000, 2000), 5)
```

```
ppm(c(-300, 200), 5)
```

rbindFill

Combine R Objects by Row

Description

This function combines instances of `matrix`, `data.frame` or `DataFrame` objects into a single instance adding eventually missing columns (filling them with NAs).

Usage

```
rbindFill(...)
```

Arguments

... 2 or more: `matrix`, `data.frame` or `DataFrame`.

Value

Depending on the input a single `matrix`, `data.frame` or `DataFrame`.

Note

`rbindFill` might not work if one of the columns contains S4 classes.

Author(s)

Johannes Rainer, Sebastian Gibb

See Also

Other helper functions for developers: [between\(\)](#), [isPeaksMatrix\(\)](#), [validPeaksMatrix\(\)](#), [vapply1c\(\)](#), [which.first\(\)](#)

Examples

```
## Combine matrices
a <- matrix(1:9, nrow = 3, ncol = 3)
colnames(a) <- c("a", "b", "c")
b <- matrix(1:12, nrow = 3, ncol = 4)
colnames(b) <- c("b", "a", "d", "e")
rbindFill(a, b)
rbindFill(b, a, b)
```

refineCentroids	<i>Refine Peak Centroids</i>
-----------------	------------------------------

Description

This function refines the centroided values of a peak by weighting the y values in the neighbourhood that belong most likely to the same peak.

Usage

```
refineCentroids(x, y, p, k = 2L, threshold = 0.33, descending = FALSE)
```

Arguments

x	numeric, i.e. m/z values.
y	numeric, i.e. intensity values.
p	integer, indices of identified peaks/local maxima.
k	integer(1), number of values left and right of the peak that should be considered in the weighted mean calculation.
threshold	double(1), proportion of the maximal peak intensity. Just values above are used for the weighted mean calculation.
descending	logical, if TRUE just values between the nearest valleys around the peak centroids are used.

Details

For `descending = FALSE` the function looks for the `k` nearest neighbouring data points and use their `x` for weighted mean with their corresponding `y` values as weights for calculation of the new peak centroid. If `k` are chosen too large it could result in skewed peak centroids, see example below. If `descending = TRUE` is used the `k` should be general larger because it is trimmed automatically to the nearest valleys on both sides of the peak so the problem with skewed centroids is rare.

Author(s)

Sebastian Gibb, Johannes Rainer

See Also

Other extreme value functions: `.peakRegionMask()`, `localMaxima()`, `valleys()`

Examples

```
ints <- c(5, 8, 12, 7, 4, 9, 15, 16, 11, 8, 3, 2, 3, 9, 12, 14, 13, 8, 3)
mzs <- seq_along(ints)

plot(mzs, ints, type = "h")

pidx <- as.integer(c(3, 8, 16))
points(mzs[pidx], ints[pidx], pch = 16)

## Use the weighted average considering the adjacent mz
mzs1 <- refineCentroids(mzs, ints, pidx,
                        k = 2L, descending = FALSE, threshold = 0)
mzs2 <- refineCentroids(mzs, ints, pidx,
                        k = 5L, descending = FALSE, threshold = 0)
mzs3 <- refineCentroids(mzs, ints, pidx,
                        k = 5L, descending = TRUE, threshold = 0)
points(mzs1, ints[pidx], col = "red", type = "h")
## please recognize the artificial moved centroids of the first peak caused
## by a too large k, here
points(mzs2, ints[pidx], col = "blue", type = "h")
points(mzs3, ints[pidx], col = "green", type = "h")
legend("topright",
       legend = paste0("k = ", c(2, 5, 5),
                       ", descending =", c("FALSE", "FALSE", "TRUE")),
       col = c("red", "blue", "green"), lwd = 1)
```

rla

Calculate relative log abundances

Description

`rla` calculates the relative log abundances (RLA, see reference) on a numeric vector. `rowRla` performs row-wise RLA calculations on a numeric matrix.

Usage

```
rla(
  x,
  f = rep_len(1, length(x)),
  transform = c("log2", "log10", "identity"),
  na.rm = TRUE
)

rowRla(x, f = rep_len(1, ncol(x)), transform = c("log2", "log10", "identity"))
```

Arguments

x	numeric (for rla) or matrix (for rowRla) with the abundances (in natural scale) on which the RLA should be calculated.
f	factor, numeric or character with the same length than x (or, for rowRla equal to the number of columns of x) allowing to define the grouping of values in x. If omitted all values are considered to be from the same group.
transform	character(1) defining the function to transform x. Defaults to transform = "log2" which log2 transforms x prior to calculation. If x is already in log scale use transform = "identity" to avoid transformation of the values.
na.rm	logical(1) whether NA values should be removed prior to calculation of the group-wise medians.

Details

The RLA is defined as the (log₂) abundance of an analyte relative to the median across all abundances of that analyte in samples of the same group. The grouping of values can be defined with parameter f.

Value

numeric with the relative log abundances (in log₂ scale) with the same length than x (for rla) or matrix with the same dimensions than x (for rowRla).

Author(s)

Johannes Rainer

References

De Livera AM, Dias DA, De Souza D, Rupasinghe T, Pyke J, Tull D, Roessner U, McConville M, Speed TP. Normalizing and integrating metabolomics data. *Anal Chem* 2012 Dec 18;84(24):10768-76.

Examples

```
x <- c(3, 4, 5, 1, 2, 3, 7, 8, 9)
grp <- c(1, 1, 1, 2, 2, 2, 3, 3, 3)
rla(x, grp)

x <- rbind(c(324, 4542, 3422, 3232, 5432, 6535, 3321, 1121),
           c(12, 3341, 3034, 6540, 34, 4532, 56, 1221))
grp <- c("a", "b", "b", "b", "a", "b", "a", "b")

## row-wise RLA values
rowRla(x, grp)
```

robustSummary	<i>Return the Robust Expression Summary of a matrix</i>
---------------	---

Description

This function calculates the robust summarisation for each feature (protein). Note that the function assumes that the intensities in input `e` are already log-transformed.

Usage

```
robustSummary(x, ...)
```

Arguments

<code>x</code>	A feature by sample matrix containing quantitative data with mandatory <code>colnames</code> and <code>rownames</code> .
<code>...</code>	Additional arguments passed to <code>MASS::rlm()</code> .

Value

`numeric()` vector of length `ncol(x)` with robust summarised values.

Author(s)

Adriaan Sticker, Sebastian Gibb and Laurent Gatto

See Also

Other Quantitative feature aggregation: [aggregate\(\)](#), [colCounts\(\)](#), [medianPolish\(\)](#)

Examples

```
x <- matrix(rnorm(30), nrow = 3)
colnames(x) <- letters[1:10]
rownames(x) <- LETTERS[1:3]
robustSummary(x)
```

`rt2numeric`*Format Retention Time*

Description

These vectorised functions convert retention times from a numeric in seconds to/from a character as "mm:ss". `rt2character()` performs the numeric to character conversion while `rt2numeric()` performs the character to numeric conversion. `formatRt()` does one of the other depending on the input type.

Usage

```
rt2numeric(rt)
```

```
rt2character(rt)
```

```
formatRt(rt)
```

Arguments

`rt` A vector of retention times of length > 1. Either a `numeric()` in seconds or a `character()` as "mm:ss" depending on the function.

Value

A reformatted retention time.

Author(s)

Laurent Gatto

Examples

```
## rt2numeric

rt2numeric("25:24")
rt2numeric(c("25:24", "25:25", "25:26"))

## rt2character

rt2character(1524)
rt2character(1)
rt2character(1:10)

## formatRt

formatRt(1524)
formatRt(1)
formatRt(1:10)
```

```
formatRt("25:24")  
formatRt(c("25:24", "25:25", "25:26"))
```

smooth

Smoothing

Description

This function smoothes a numeric vector.

Usage

```
smooth(x, cf)  
  
coefMA(hws)  
  
coefWMA(hws)  
  
coefSG(hws, k = 3L)
```

Arguments

x	numeric, i.e. m/z values.
cf	matrix, a coefficient matrix generated by coefMA, coefWMA or coefSG.
hws	integer(1), half window size, the resulting window reaches from (i - hws) : (i + hws).
k	integer(1), set the order of the polynomial used to calculate the coefficients.

Details

For the Savitzky-Golay-Filter the hws should be smaller than *FWHM* of the peaks (full width at half maximum; please find details in Bromba and Ziegler 1981).

In general the hws for the (weighted) moving average (coefMA/coefWMA) has to be much smaller than for the Savitzky-Golay-Filter to conserve the peak shape.

Value

smooth: A numeric of the same length as x.
coefMA: A matrix with coefficients for a simple moving average.
coefWMA: A matrix with coefficients for a weighted moving average.
coefSG: A matrix with *Savitzky-Golay-Filter* coefficients.

Functions

- `coefMA()`: Simple Moving Average
This function calculates the coefficients for a simple moving average.
- `coefWMA()`: Weighted Moving Average
This function calculates the coefficients for a weighted moving average with weights depending on the distance from the center calculated as $1/2^{\text{abs}(-\text{hws}:\text{hws})}$ with the sum of all weights normalized to 1.
- `coefSG()`: Savitzky-Golay-Filter
This function calculates the Savitzky-Golay-Coefficients. The additional argument `k` controls the order of the used polynomial. If `k` is set to zero it yield a simple moving average.

Note

The `hws` depends on the used method ((weighted) moving average/Savitzky-Golay).

Author(s)

Sebastian Gibb, Sigurdur Smarason (weighted moving average)

References

A. Savitzky and M. J. Golay. 1964. Smoothing and differentiation of data by simplified least squares procedures. *Analytical chemistry*, 36(8), 1627-1639.

M. U. Bromba and H. Ziegler. 1981. Application hints for Savitzky-Golay digital smoothing filters. *Analytical Chemistry*, 53(11), 1583-1586.

Implementation based on: Steinier, J., Termonia, Y., & Deltour, J. (1972). Comments on Smoothing and differentiation of data by simplified least square procedure. *Analytical Chemistry*, 44(11), 1906-1909.

See Also

Other noise estimation and smoothing functions: [noise\(\)](#)

Examples

```
x <- c(1:10, 9:1)
plot(x, type = "b", pch = 20)
cf <- list(MovingAverage = coefMA(2),
          WeightedMovingAverage = coefWMA(2),
          SavitzkyGolay = coefSG(2))
for (i in seq_along(cf)) {
  lines(smooth(x, cf[[i]]), col = i + 1, pch = 20, type = "b")
}
legend("bottom", legend = c("x", names(cf)), pch = 20,
      col = seq_len(length(cf) + 1))
```

`sumi`*Summing MS Intensity Values*

Description

`sumi` sums mass spectrometry intensity values, e.g. from a spectrum or chromatogram. In contrast to the base R `sum()` function this function returns `NA_real_` if all intensity values are NA or if `length(x)` is 0.

Usage

```
sumi(x)
```

Arguments

`x` numeric with intensity values to be summed up. Will be coerced to numeric using `as.double`.

Value

`numeric(1)` representing the sum of values in `x`. Always returns a numeric (double) even if `x` is an integer.

Author(s)

Johannes Rainer

See Also

[maxi\(\)](#)

Examples

```
x <- c(3.2, 34.4, 1.3, NA)
sumi(x)
```

```
## Compared to base R sum:
sum(x)
sum(x, na.rm = TRUE)
```

```
sum(numeric(), na.rm = TRUE)
sumi(numeric())
```

```
sum(c(NA, NA), na.rm = TRUE)
sumi(c(NA, NA))
```

validPeaksMatrix	<i>Validation functions</i>
------------------	-----------------------------

Description

These functions are used to validate input arguments. In general they are just wrapper around their corresponding `is*` function with an error message.

Usage

```
validPeaksMatrix(x)
```

Arguments

`x` object to test.

Details

`validPeaksMatrix`: see [isPeaksMatrix](#).

Value

logical(1), TRUE if validation are successful otherwise an error is thrown.

Author(s)

Sebastian Gibb

See Also

Other helper functions for developers: [between\(\)](#), [isPeaksMatrix\(\)](#), [rbindFill\(\)](#), [vapply1c\(\)](#), [which.first\(\)](#)

Examples

```
try(validPeaksMatrix(1:2))
validPeaksMatrix(cbind(mz = 1:2, intensity = 1:2))
```

valleys

Find Peak Valleys

Description

This function finds the valleys around peaks.

Usage

```
valleys(x, p)
```

Arguments

`x` numeric, e.g. intensity values.
`p` integer, indices of identified peaks/local maxima.

Value

A matrix with three columns representing the index of the left valley, the peak centroid, and the right valley.

Note

The detection of the valleys is based on [localMaxima](#). It returns the *first* occurrence of a local maximum (in this specific case the minimum). For plateaus, e.g. `c(0, 0, 0, 1:3, 2:1, 0)` this results in a wrongly reported left valley index of 1 (instead of 3, see the example section as well). In real data this should not be a real problem. `x[x == min(x)] <- Inf` could be used before running `valleys` to circumvent this specific problem but it is not really tested and could cause different problems.

Author(s)

Sebastian Gibb

See Also

Other extreme value functions: [.peakRegionMask\(\)](#), [localMaxima\(\)](#), [refineCentroids\(\)](#)

Examples

```
ints <- c(5, 8, 12, 7, 4, 9, 15, 16, 11, 8, 3, 2, 3, 2, 9, 12, 14, 13, 8, 3)
mzs <- seq_along(ints)
peaks <- which(localMaxima(ints, hws = 3))
cols <- seq_along(peaks) + 1

plot(mzs, ints, type = "h", ylim = c(0, 16))
points(mzs[peaks], ints[peaks], col = cols, pch = 20)
```

```
v <- valleys(ints, peaks)
segments(mzs[v[, "left"]], 0, mzs[v[, "right"]], col = cols, lwd = 2)

## Known limitations for plateaus
y <- c(0, 0, 0, 0, 0, 1:5, 4:1, 0)
valleys(y, 10L) # left should be 5 here but is 1

## a possible workaround that may cause other problems
y[ $\min(y) == y$ ] <- Inf
valleys(y, 10L)
```

vapply1c

vapply wrappers

Description

These functions are short wrappers around typical vapply calls for easier development.

Usage

```
vapply1c(X, FUN, ..., USE.NAMES = FALSE)
```

```
vapply1d(X, FUN, ..., USE.NAMES = FALSE)
```

```
vapply1l(X, FUN, ..., USE.NAMES = FALSE)
```

Arguments

X	a vector (atomic or list).
FUN	the function to be applied to each element of X.
...	optional arguments to FUN.
USE.NAMES	logical, should the return value be named.

Value

vapply1c returns a vector of characters of length X.

vapply1d returns a vector of doubles of length X.

vapply1l returns a vector of logicals of length X.

Author(s)

Sebastian Gibb

See Also

Other helper functions for developers: [between\(\)](#), [isPeaksMatrix\(\)](#), [rbindFill\(\)](#), [validPeaksMatrix\(\)](#), [which.first\(\)](#)

Examples

```
l <- list(a=1:3, b=4:6)
vapply1d(l, sum)
```

`which.first`*Which is the first/last TRUE value.*

Description

Determines the location, i.e., index of the first or last TRUE value in a logical vector.

Usage

```
which.first(x)
```

```
which.last(x)
```

Arguments

`x` logical, vector.

Value

integer, index of the first/last TRUE value. `integer(0)` if no TRUE (everything FALSE or NA) was found.

Author(s)

Sebastian Gibb

See Also

[which.min\(\)](#)

Other helper functions for developers: [between\(\)](#), [isPeaksMatrix\(\)](#), [rbindFill\(\)](#), [validPeaksMatrix\(\)](#), [vapply1c\(\)](#)

Examples

```
l <- 2 <= 1:3
which.first(l)
which.last(l)
```

Index

* Quantitative feature aggregation

aggregate, 4
colCounts, 13
medianPolish, 28
robustSummary, 36

* coerce functions

coerce, 13

* distance/similarity functions

distance, 14
gnps, 16

* extreme value functions

.peakRegionMask, 3
localMaxima, 27
refineCentroids, 33
valleys, 42

* grouping/matching functions

bin, 7
closest, 9
gnps, 16

* helper functions for developers

between, 6
isPeaksMatrix, 26
rbindFill, 32
validPeaksMatrix, 41
vapply1c, 43
which.first, 44

* helper functions for users

ppm, 31

* internal

.peakRegionMask, 3

* noise estimation and smoothing functions

noise, 29
smooth, 38

.peakRegionMask, 3, 27, 34, 42

%between% (between), 6

%in%, 9–11

aggregate, 4, 14, 29, 36

aggregate_by_matrix (aggregate), 4

aggregate_by_matrix(), 4

aggregate_by_vector (aggregate), 4

aggregate_by_vector(), 4

asInteger (coerce), 13

base::colMeans(), 5

base::colSums(), 5

between, 6, 26, 32, 41, 43, 44

bin, 7, 11, 18

C, 24

closest, 8, 9, 18

closest(), 10

coefMA (smooth), 38

coefSG (smooth), 38

coefWMA (smooth), 38

coerce, 13

colCounts, 5, 13, 29, 36

colMeansMat (aggregate), 4

colSumsMat (aggregate), 4

common (closest), 9

distance, 14, 18

dotproduct (distance), 14

formatRt (rt2numeric), 37

getImputeMargin (impute_matrix), 21

gnps, 8, 11, 16, 16

group, 19

i2index, 20

impute::impute.knn(), 23

impute_bpca (impute_matrix), 21

impute_fun (impute_matrix), 21

impute_knn (impute_matrix), 21

impute_matrix, 21

impute_min (impute_matrix), 21

impute_MinDet (impute_matrix), 21

impute_MinProb (impute_matrix), 21

impute_mixed (impute_matrix), 21

impute_mle (impute_matrix), 21

impute_mle2 (impute_matrix), 21
 impute_neighbour_average
 (impute_matrix), 21
 impute_QRILC (impute_matrix), 21
 impute_RF (impute_matrix), 21
 impute_with (impute_matrix), 21
 impute_zero (impute_matrix), 21
 imputeLCMD::impute.MinProb(), 24
 imputeLCMD::impute.QRILC(), 23
 imputeMethods (impute_matrix), 21
 isPeaksMatrix, 7, 26, 32, 41, 43, 44

 join (closest), 9
 join(), 17, 18
 join_gnps (gnps), 16

 localMaxima, 3, 27, 34, 42

 MASS::rlm(), 5, 36
 match(), 9–11
 matrixStats::colMedians(), 5
 max(), 27
 maxi, 27
 maxi(), 40
 medianPolish, 5, 14, 28, 36
 medianPolish(), 5
 missForest::missForest(), 23

 navdist (distance), 14
 ndotproduct (distance), 14
 neulclidean (distance), 14
 noise, 29, 39
 norm::em.norm(), 23
 norm::imp.norm(), 23
 normalize_matrix (normalizeMethods), 30
 normalizeMethods, 30
 nspectraangle (distance), 14

 pcaMethods::pca(), 23
 ppm, 31
 preprocessCore::normalize.quantiles(),
 31
 preprocessCore::normalize.quantiles.robust(),
 31

 rbindFill, 7, 26, 32, 41, 43, 44
 refineCentroids, 3, 27, 33, 42
 rla, 34
 robustSummary, 5, 14, 29, 36
 robustSummary(), 5

 rowRla (rla), 34
 rt2character (rt2numeric), 37
 rt2numeric, 37

 scale(), 31
 smooth, 30, 38
 stats::mad(), 30
 stats::medpolish(), 5, 28, 29
 stats::supsmu(), 30
 sum(), 40
 sumi, 40
 sumi(), 28

 validPeaksMatrix, 7, 26, 32, 41, 43, 44
 valleys, 3, 27, 34, 42
 vapply1c, 7, 26, 32, 41, 43, 44
 vapply1d (vapply1c), 43
 vapply1l (vapply1c), 43
 vsn::vsn2(), 31

 which.first, 7, 26, 32, 41, 43, 44
 which.last (which.first), 44
 which.min(), 44