

# Package ‘PhenStat’

October 15, 2023

**Type** Package

**Title** Statistical analysis of phenotypic data

**Version** 2.36.0

**Date** 2019-07-09

**Author** Natalja Kurbatova, Natasha Karp, Jeremy Mason, Hamed Haselimashhadi

**Maintainer** Hamed Haselimashhadi <hamedhm@ebi.ac.uk>

**Depends** R (>= 3.5.0)

**Imports** SmoothWin, methods, car, nlme, nortest, MASS, msgps, logistf,  
knitr, tools, pingr, ggplot2, reshape, corrplot, graph, lme4,  
graphics, grDevices, utils, stats

**Suggests** RUnit, BiocGenerics

**Description** Package contains methods for statistical analysis of phenotypic data.

**License** file LICENSE

**NeedsCompilation** no

**biocViews** StatisticalMethod

**git\_url** <https://git.bioconductor.org/packages/PhenStat>

**git\_branch** RELEASE\_3\_17

**git\_last\_commit** b04074b

**git\_last\_commit\_date** 2023-04-25

**Date/Publication** 2023-10-15

## R topics documented:

analysedDataset . . . . .	4
analysedDatasetPhenList . . . . .	4
analysedSubset . . . . .	5
analysisResults . . . . .	5
batchIn . . . . .	6
boxplotResidualBatch . . . . .	6
boxplotSexGenotype . . . . .	7

boxplotSexGenotypeBatch . . . . .	8
boxplotSexGenotypeBatchAdjusted . . . . .	10
boxplotSexGenotypeResult . . . . .	11
boxplotSexGenotypeWeightBatchAdjusted . . . . .	12
categoricalBarplot . . . . .	13
checkDataset . . . . .	14
classificationTag . . . . .	16
columnChecks . . . . .	17
columnLevels . . . . .	18
comparison . . . . .	19
dataset . . . . .	19
determiningLambda . . . . .	19
dim . . . . .	20
finalLRModel . . . . .	21
finalModel . . . . .	22
finalTFModel . . . . .	24
FisherExactTest . . . . .	25
formulaDeterminingLambda . . . . .	27
generateGraphs . . . . .	27
getColumn . . . . .	28
getColumnBatchAdjusted . . . . .	29
getColumnView . . . . .	29
getColumnWeightBatchAdjusted . . . . .	29
getCountMatrices . . . . .	30
getDataset . . . . .	30
getGenotypeEffect . . . . .	30
getMatrix . . . . .	31
getPercentageMatrix . . . . .	31
getStat . . . . .	31
getVariable . . . . .	32
getVariables . . . . .	32
hemiGenotype . . . . .	32
htest-class . . . . .	33
htestPhenStat-class . . . . .	34
JSONOutput . . . . .	35
LargeDataObject-class . . . . .	36
LRDataset . . . . .	37
matrixCount . . . . .	38
method . . . . .	38
methodText . . . . .	39
modelFormula . . . . .	39
modelFormulaLR . . . . .	40
multipleBatches . . . . .	41
noSexes . . . . .	42
parameters . . . . .	42
parserOutputSummary . . . . .	42
parserOutputSummaryLR . . . . .	43
parserOutputTFSummary . . . . .	44

performReverseTransformation . . . . .	45
performTransformation . . . . .	46
PhenList . . . . .	47
PhenList-class . . . . .	49
PhenStatReport . . . . .	51
PhenTestResult . . . . .	53
PhenTestResult-class . . . . .	55
plot.PhenList . . . . .	58
plot.PhenTestResult . . . . .	59
plotResidualPredicted . . . . .	61
printLROutput . . . . .	62
printTabStyle . . . . .	63
pvalue . . . . .	64
qqplotGenotype . . . . .	64
qqplotRandomEffects . . . . .	65
qqplotRotatedResiduals . . . . .	66
recommendMethod . . . . .	67
refGenotype . . . . .	68
RRTTest . . . . .	69
scatterplotGenotypeWeight . . . . .	70
scatterplotGenotypeWeightResult . . . . .	71
scatterplotSexGenotypeBatch . . . . .	73
scatterplotSexGenotypeBatchResult . . . . .	74
setBatch . . . . .	75
setGenotype . . . . .	76
setMissingValue . . . . .	76
setSex . . . . .	76
setWeight . . . . .	77
startLRModel . . . . .	77
startModel . . . . .	79
startTFModel . . . . .	81
subsetText . . . . .	83
summary.PhenTestResult . . . . .	83
summaryOutput . . . . .	84
testDataset . . . . .	85
testFinalLRModel . . . . .	88
testFinalModel . . . . .	90
testGenotype . . . . .	91
TFDataset . . . . .	91
transformation . . . . .	92
transformationJSON . . . . .	93
transformationText . . . . .	93
vectorOutput . . . . .	93
vectorOutputMatrices . . . . .	95
weightIn . . . . .	96

**analysedDataset**      *Method "analysedDataset"*

### Description

Method `analysedDataset` returns subset of the original dataset that was analysed

### Value

This function returns the analysed dataset.

### Methods

`signature(obj = "PhenTestResult")`

### Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")

result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
head(PhenStat:::analysedDataset(obj = result))
```

**analysedDatasetPhenList**      *Method "analysedDatasetPhenList"*

### Description

Method `analysedDatasetPhenList` returns subset of the original dataset that will be analysed

### Value

The function returns the analysed dataset.

### Methods

`signature(obj = "PhenList")`

---

analysedSubset	<i>Method "analysedSubset"</i>
----------------	--------------------------------

---

### Description

Method `analysedSubset` returns name of the subset that was analysed by RR or FE frameworks

### Value

The function returns name of the subset that was analysed by RR or FE frameworks.

### Methods

```
signature(obj = "htestPhenStat")
```

---

---

analysisResults	<i>Method "analysisResults"</i>
-----------------	---------------------------------

---

### Description

Method `analysisResults` returns analysis results

### Value

The function returns the analysis result.

### Methods

```
signature(obj = "PhenTestResult")
```

### Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")

result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
r = PhenStat:::analysisResults(obj = result)
```

**batchIn***Method "batchIn"***Description**

Method batchIn returns TRUE/FALSE values depending on the batch column presence/absence in the dataset

**Value**

TRUE/FALSE

**Methods**

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

**boxplotResidualBatch    Method "boxplotResidualBatch"****Description**

Graph function for the Mixed Model framework's results. Creates a box plot with residue versus batch split by genotype.

**Usage**

```
boxplotResidualBatch(phenTestResult, outputMessages=TRUE)
```

**Arguments**

<code>phenTestResult</code>	instance of the <code>PhenTestResult</code> class that comes from the function <code>testDataset</code> ; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenList](#) and [PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                  depVariable="Lean.Mass")
PhenStat:::boxplotResidualBatch(result)
```

boxplotSexGenotype     *Method "boxplotSexGenotype"*

## Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype.

## Usage

```
boxplotSexGenotype(phenList,
                   depVariable=NULL,
                   graphingName=NULL,
                   outputMessages=TRUE)
```

## Arguments

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
graphingName	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410  
 West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
PhenStat:::boxplotSexGenotype(test,
                             depVariable="Bone.Mineral.Content",
                             graphingName="BMC")

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                                 testGenotype="Mysm1/+")
# box plot for females only dataset
PhenStat:::boxplotSexGenotype(test_1sex,
                             depVariable="Lean.Mass",
                             graphingName="Lean Mass (g)")
```

*boxplotSexGenotypeBatch*

*Method "boxplotSexGenotypeBatch"*

**Description**

NB! Function is deprecated, please use scatterplotSexGenotypeBatch function instead. Graph function for the phenotypic dataset. Creates a box plot split by sex, genotype and batch.

Note: the batches are not ordered with time but allow assessment of how the treatment groups lie relative to the normal control variation.

**Usage**

```
boxplotSexGenotypeBatch(phenList,
                       depVariable=NULL,
                       graphingName=NULL,
                       outputMessages=TRUE)
```

## Arguments

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
graphingName	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

#### **See Also**

## PhenList

## Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
    testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
PhenStat:::boxplotSexGenotypeBatch(test,
    depVariable="Bone.Mineral.Content",
    graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
    testGenotype="Mysm1/+")
# box plot for females only dataset
PhenStat:::boxplotSexGenotypeBatch(test_1sex,depVariable="Lean.Mass",
    graphingName="Lean Mass")

```

**boxplotSexGenotypeBatchAdjusted**  
*Method "boxplotSexGenotypeBatchAdjusted"*

## Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype after accounting for batch.

## Usage

```
boxplotSexGenotypeBatchAdjusted(
  phenList,
  depVariable=NULL,
  graphingName=NULL,
  outputMessages=TRUE)
```

## Arguments

<code>phenList</code>	instance of the <a href="#">PhenList</a> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>graphingName</code>	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenList](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
PhenStat:::boxplotSexGenotypeBatchAdjusted(test,
                                            depVariable="Bone.Mineral.Content",
                                            graphingName="BMC" )
```

### boxplotSexGenotypeResult

*Method "boxplotSexGenotypeResult"*

## Description

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype. Is based on `PhenTestResult` object.

## Usage

```
boxplotSexGenotypeResult(phenTestResult,
                        graphingName=NULL,
                        outputMessages=TRUE)
```

## Arguments

<code>phenTestResult</code>	instance of the <code>PhenTestResult</code> class; mandatory argument
<code>graphingName</code>	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**[PhenList](#)**Examples**

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
# box plot for dataset with two sexes: males and females
PhenStat:::boxplotSexGenotypeResult(result,
                                     graphingName="BMC")

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                                   testGenotype="Mysm1/+")
result_1sex <- PhenStat:::testDataset(test_1sex,
                                       depVariable="Lean.Mass")
# box plot for females only dataset
PhenStat:::boxplotSexGenotypeResult(result_1sex,
                                     graphingName="Lean Mass (g)")

```

**boxplotSexGenotypeWeightBatchAdjusted**  
*Method "boxplotSexGenotypeWeightBatchAdjusted"*

**Description**

Graph function for the phenotypic dataset. Creates a box plot split by sex and genotype after accounting for batch and weight.

**Usage**

```
boxplotSexGenotypeWeightBatchAdjusted(
  phenList,
  depVariable=NULL,
  graphingName=NULL,
  outputMessages=TRUE)
```

**Arguments**

<b>phenList</b>	instance of the <a href="#">PhenList</a> class; mandatory argument
<b>depVariable</b>	a character string defining the dependent variable of interest; mandatory argument
<b>graphingName</b>	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
<b>outputMessages</b>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
PhenStat:::boxplotSexGenotypeWeightBatchAdjusted(test,
                                                 depVariable="Bone.Mineral.Content",
                                                 graphingName="BMC" )
```

---

categoricalBarplot      *Method "categoricalBarplot"*

---

**Description**

Graph function for the Fisher Exact Test framework's results. Creates stacked bar plot(s) to compare proportions seen in a categorical variable between different genotypes. Graphs are created for all data and also for each sex individually.

**Usage**

```
categoricalBarplot(phenTestResult,
                   outputMessages=TRUE)
```

**Arguments**

- phenTestResult instance of the [PhenTestResult](#) class that comes from the function `testDataset`; mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result <- PhenStat:::testDataset(test,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
PhenStat:::categoricalBarplot(result)
```

*checkDataset*

*Method "checkDataset"*

**Description**

Checks dataset for the minimum required info:

1. Column names should present
2. Genotype column should present
3. Sex column should present
4. Two data points for each Genotype/Sex combination
5. Number of Genotype levels should be 2
6. Number of Sex levels should be 1 or 2
7. Sex levels have to be "Female" and/or "Male"
8. Records with reference genotype should be in the dataset
9. Records with test genotype should be in the dataset

Perform the following additional checks:

- presence of Weight column,
- presence of Batch column (Assay.Date).

Warning given in case of missed data indicating that you can only fit a glm or to use MM equation "withoutWeight".

Function [checkDataset](#) is called from [PhenList](#) function.

## Usage

```
checkDataset(dataset,  
testGenotype,  
refGenotype="+/+",  
outputMessages=TRUE,  
dataset.clean=TRUE)
```

## Arguments

dataset	data frame created from file or from another source; mandatory argument
testGenotype	defines the test genotype to be compared to the reference genotype; mandatory argument
refGenotype	defines the reference genotype; assigned default value is "+/+"
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; assigned default value is TRUE
dataset.clean	flag: "FALSE" value for no modification of the dataset; "TRUE" value to clean dataset if needed; assigned default value is TRUE

## Value

Returns an instance of the [PhenList](#) class.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
# "checkDataset" is called internally from "PhenList" function
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
```

**classificationTag**      *Method "classificationTag"*

## Description

Returns a classification tag to assign a sexual dimorphism assessment of the phenotypic change.

## Usage

```
classificationTag(phenTestResult,
userMode = "summaryOutput",
phenotypeThreshold = 0.01,
outputMessages=TRUE)
```

## Arguments

<b>phenTestResult</b>	instance of the <a href="#">PhenTestResult</a> class that comes from the function <a href="#">testDataset</a> ; mandatory argument
<b>userMode</b>	flag: "vectorOuput" a sexual dimorphic classification is assigned with a proviso of later assessing the overall statistical significance; "summaryOutput" the phenotypeThreshold is used to assess the overall statistical significance and then if significant the sexual dimorphic classification determined; defaults to summaryOutput
<b>phenotypeThreshold</b>	a numerical value defining the threshold to use in classificationTag in determining whether the genotype effect is classed as significant or not; default value 0.01
<b>outputMessages</b>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE

## Value

Returns a classification tag to assign a sexual dimorphism assessment of the phenotypic change.

If you are working interactively with the data, the argument "userMode" set to the value "summaryOutput" will use the "phenotypeThreshold" argument's value to assess statistical significance of the genotype effect and if significant then assign a sexual dimorphic classification. Alternatively, if the "userMode" set to the value "vectorMode", a sexual dimorphic classification will be returned with the MM framework where later you can globally assess whether the variable had a significant genotype effect. With the FE framework and the vectorMode, a NA is returned as the type of the effect cannot be assessed without assessing the statistical significance of the genotype effect.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410  
 West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                  depVariable="Lean.Mass")
PhenStat:::classificationTag(result,
                               userMode="summaryOutput",
                               phenotypeThreshold=0.001)
PhenStat:::classificationTag(result,
                               userMode="vectorOutput")
```

columnChecks

*Method "columnChecks"*

**Description**

Checks the particular column of the dataset for eligibility. Returns: presence of column, all data are numeric, number of levels that passed check (number of data points for each genotype/sex combination is at least equals to threshold).

**Usage**

```
columnChecks(dataset,
             columnName,
             dataPointsThreshold=4)
```

**Arguments**

- |                     |  |
|---------------------|--|
| dataset             | data frame created from file or from another source; mandatory argument            |
| columnName          | name of the column to check; mandatory argument                                    |
| dataPointsThreshold | number of data points for each genotype/sex combination; default value is set to 4 |

**Value**

Boolean vector of length 3: presence of column, all data are numeric, number of levels that passed check (number of data points for each genotype/sex combination is at least equals to threshold).

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410  
 West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

*columnLevels*

*Method "columnLevels"*

**Description**

Method removes null values from the column and calculates column basic stat. Returns: No of data points, No of levels, No of Genotype/Sex combinations, No of data points for each one combination.

**Usage**

```
columnLevels(dataset, columnName)
```

**Arguments**

- |            |   |
|------------|---|
| dataset    | data frame created from file or from another source; mandatory argument |
| columnName | name of the column to check; mandatory argument                         |

**Value**

Numeric vector of length 6 or 7: No of data points, No of levels, No of Genotype/Sex combinations, No of data points for each one combination.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410  
 West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

---

comparison	<i>Method "comparison"</i>
------------	----------------------------

---

**Description**

Method comparison returns name of the comparison that was performed by RR framework: "High vs Normal/Low" or "Low vs Normal/High"

**Value**

returns name of the comparison that was performed by RR framework.

**Methods**

`signature(obj = "htestPhenStat")`

---

dataset	<i>Method "dataset"</i>
---------	-------------------------

---

**Description**

Method dataset returns data frame stored in the object

**Value**

returns data frame stored in the object

**Methods**

`signature(obj = "PhenList")`

---

determiningLambda	<i>Method "determiningLambda"</i>
-------------------	-----------------------------------

---

**Description**

Function role 1. Rescale data if needed (Box-Cox transformation can only be applied on data >0) 2. Calculate lambda value for a Box-Cox transformation 3. Assess whether transformation is required (if confidence interval includes 1 then no transformation required) 4. Return output to allow application of the transformation if necessary using the returned lambda value and any associated rescaling that was needed. 5. Requires a function that will be fitted determined from formulaAssessingBoxCox

**Usage**

```
determiningLambda(phenList,
depVariable,
equation="withWeight")
```

**Arguments**

<code>phenList</code>	instance of the <code>PhenList</code> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>equation</code>	a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight"

**Value**

Returns a vector with five elements: 1. 95 2. Midepoint of the 95 3. Calculated lambda value 4. TransformationRequired: TRUE/FALSE 5. Calculated scale shift value

**Author(s)**

Natasha Karp

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
PhenStat:::determiningLambda(test,"Lean.Mass",equation="withoutWeight")
```

---

**dim**

*Method "dim"*

---

**Description**

Retrieve the number of rows (measures) and columns (parameters) for a `PhenList` object.

**Usage**

```
## S3 method for class 'PhenList'
dim(x)
```

**Arguments**

<code>x</code>	an object of class <code>PhenList</code>
----------------	--

## Details

These methods allow one to extract the size of phenotypic data objects in the same way that one would do for ordinary matrices.

A consequence is that row and column commands `nrow(x)`, `ncol(x)` and so on also work.

## Value

Numeric vector of length 2. The first element is the number of rows (measures) and the second is the number of columns (parameters).

## Author(s)

Natalja Kurbatova

## See Also

`dim` in the base package.

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
PhenStat:::dim.PhenList(test)
```

`finalLRModel`

*Method "finalLRModel"*

## Description

This is an internal function run within LR framework. It completes the final stage of the LR framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with `PhenTestResult` object created by `startLRModel` function. The creation of LR final model is based on the significance of different fixed effects, `depVariable` and equation values stored in `PhenTestResult` object.

## Usage

```
finalLRModel(phenTestResult,
             outputMessages = TRUE)
```

## Arguments

`phenTestResult` instance of the `PhenTestResult` class that comes from the function `testDataset`; mandatory argument  
`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Returns results stored in instance of the [PhenTestResult](#) class

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenTestResult](#) and [testDataset](#)

**Examples**

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                             testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startLRModel" function is called - the first step of LR framework
resultLR <- PhenStat:::testDataset(testLR2,
                                    depVariable="V2",
                                    callAll=FALSE,
                                    method="LR")
# print out formula that has been created
PhenStat:::analysisResults(resultLR)$model.formula.genotype
# print out batch effect's significance
PhenStat:::analysisResults(resultLR)$model.effect.batch
resultLR <- PhenStat:::finalLRModel(resultLR)
```

**finalModel**

*Method "finalModel"*

**Description**

This is an internal function run within MM framework. It completes the final stage of the MM framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenTestResult](#) object created by [startModel](#) function. The creation of MM final model is based on the significance of different fixed effects, depVariable and equation values stored in [PhenTestResult](#) object.

**Usage**

```
finalModel(phenoTestResult,  
          outputMessages = TRUE,  
          modelWeight = NULL)
```

**Arguments**

- phenoTestResult instance of the [PhenoTestResult](#) class that comes from the function [testDataset](#); mandatory argument
- outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE
- modelWeight A vector of positive values for weights mainly used for applying windowing to the data

**Value**

Returns results stored in instance of the [PhenoTestResult](#) class

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenoTestResult](#) and [testDataset](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")  
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),  
                           testGenotype="Sparc/Sparc")  
# when "testDataset" function's argument "callAll" is set to FALSE  
# only "startModel" function is called - the first step of MM framework  
result <- PhenStat:::testDataset(test,  
                                 depVariable="Lean.Mass",  
                                 equation="withoutWeight",  
                                 callAll=FALSE)  
# print out formula that has been created  
# result$model.formula.genotype  
# print out batch effect's significance  
# result$model.effect.batch  
# change the model  
# result <- PhenStat:::testDataset(test,
```

```

#      depVariable="Lean.Mass",
#      equation="withWeight",
#      callAll=FALSE)
# print out new formula
#result$model.formula.genotype
# run the final model fitting when statisfied with the model
result <- PhenStat:::finalModel(result)

```

finalTFModel                  *Method "finalTFModel"*

## Description

This is an internal function run within TF framework. It completes the final stage of the TF framework, which builds the final model and estimates effects. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenTestResult](#) object created by [startTFModel](#) function. The creation of TF final model is based on the significance of different fixed effects, depVariable and equation values stored in [PhenTestResult](#) object.

## Usage

```
finalTFModel(phenTestResult,
outputMessages = TRUE)
```

## Arguments

**phenTestResult** instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument  
**outputMessages** flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Returns results stored in instance of the [PhenTestResult](#) class

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#) and [testDataset](#)

**Examples**

```
file <- system.file("extdata", "test7_TFE.csv", package="PhenStat")
test <- PhenList(dataset=read.csv(file,na.strings = '-'),
                 testGenotype="het",
                 refGenotype = "WT",
                 dataset.colname.sex="sex",
                 dataset.colname.genotype="Genotype",
                 dataset.values.female="f",
                 dataset.values.male= "m",
                 dataset.colname.weight="body.weight",
                 dataset.colname.batch="Date_of_procedure_start")

test_TF <- PhenStat:::TFDataset(test,depVariable="Cholesterol")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startTFModel" function is called - the first step of TFE framework
result <- PhenStat:::testDataset(test_TF,
                                  depVariable="Cholesterol",
                                  callAll=FALSE,
                                  method="TF")
# print out formula that has been created
PhenStat:::analysisResults(result)$model.formula.genotype
# print out batch effect's significance
PhenStat:::analysisResults(result)$model.effect.batch
result <- PhenStat:::finalTFModel(result)
```

FisherExactTest

*Method "FisherExactTest"*

**Description**

The main function of the Fisher Exact Test framework. Creates n times 2 matrices with record counts, where n rows represent dependent variable levels and two columns represent genotype levels. Performs Fisher Exact Tests on calculated count matrices.

Three matrices can be created and three tests can be potentially perform depending on the dataset:

- all records together regardless the sex values - combined dataset,
- records where sex value is "Male" (if such exists) - males only dataset,
- records where sex value is "Female" (if such exists) - females only dataset.

Together with count matrices creates percentage matrices, calculates effect sizes and statistics for count matrices. Performs Fisher Exact Tests.

The results (matrices, statistics and Fisher Exact Test outputs) are stored in [PhenTestResult](#) object.

The funciton is called from "testDataset" function when "method" argument is set to "FE" meaning "Fisher Exact Test".

**Usage**

```
FisherExactTest(phenList,
  depVariable,
  outputMessages=TRUE)
```

**Arguments**

<code>phenList</code>	instance of the <a href="#">PhenList</a> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Returns results stored in instance of the [PhenTestResult](#) class

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Aff3/Aff3")
# "FisherExactTest" function is called from "testDataset" function.
result <- PhenStat:::testDataset(test,depVariable="Thoracic.Processes",method="FE")
# Fisher Exact Test results can be printed out using function "summaryOutput"
summary(result)
```

---

**formulaDeterminingLambda**

*Method "formulaDeterminingLambda"*

---

### Description

Returns the starting formula that we wish to interrogate the data with in estimating the lambda for a Box-Cox transformation

### Usage

```
formulaDeterminingLambda(noSexes,
depVariable,
multipleBatches,
equation)
```

### Arguments

noSexes	number of sexes in the data; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
multipleBatches	TRUE if there are multiple batch values in the data, FALSE otherwise
equation	a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight"

### Value

Returns a formula

### Author(s)

Natasha Karp

---

**generateGraphs**

*Method "generateGraphs"*

---

### Description

Function generates graphs for the Mixed Model and Time as Fixed Effect frameworks' results and stores generated graphs in the defined directory.

### Usage

```
generateGraphs(phenTestResult, dir,
graphingName=NULL, type="Xlib")
```

**Arguments**

<code>phenTestResult</code>	instance of the <a href="#">PhenTestResult</a> class that comes from the function <a href="#">testDataset</a> ; mandatory argument
<code>dir</code>	directory where to store generated graphs; mandatory argument
<code>graphingName</code>	a character string defining the name to be used on the graph for the dependent variable; defaults to NULL then the <code>depVariable</code> name will be plotted
<code>type</code>	character string, one of "Xlib" or "quartz" (some OS X builds) or "cairo", or "window", or "cairo-png"; mandatory argument

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

`getColumn`

*Method "getColumn"*

**Description**

Method `getColumn` returns column of interest

**Value**

This function returns column of interest

**Methods**

`signature(obj = "PhenList")`

---

```
getColumnBatchAdjusted
```

*Method "getColumnBatchAdjusted"*

---

### Description

Method getColumnBatchAdjusted returns column of interest adjusted for batch

### Value

This function returns column of interest

### Methods

```
signature(obj = "PhenList")
```

---

```
getColumnView
```

*Method "getColumnView"*

---

### Description

Method getColumnView returns RR or FE frameworks results in a column format

### Value

This function returns RR or FE frameworks results in a column format

### Methods

```
signature(obj = "htestPhenStat")
```

---

```
getColumnWeightBatchAdjusted
```

*Method "getColumnWeightBatchAdjusted"*

---

### Description

Method getColumnWeightBatchAdjusted returns column of interest adjusted for weight and batch

### Value

This function returns column of interest

### Methods

```
signature(obj = "PhenList")
```

`getCountMatrices`      *Method "getCountMatrices"*

### Description

Method `getCountMatrices` returns count matrices for FE and RR frameworks

### Value

This function returns count matrices for FE and RR frameworks

### Methods

`signature(obj = "PhenTestResult")`

`getDataset`      *Method "getDataset"*

### Description

Method `getDataset` returns data frame stored in the object

### Value

This function returns data frame stored in the object.

### Methods

`signature(obj = "PhenList")`

`getGenotypeEffect`      *Method "getGenotypeEffect"*

### Description

Method `getGenotypeEffect` returns genotype effect and standard error for the linear regression frameworks

### Value

This function returns genotype effect and standard error for the linear regression frameworks

### Methods

`signature(obj = "PhenTestResult")`

---

getMatrix

*Method "getMatrix"*

---

### Description

Method getMatrix returns RR or FE frameworks results in a matrix format

### Value

This function returns RR or FE frameworks results in a matrix format

### Methods

`signature(obj = "htestPhenStat")`

---

getPercentageMatrix

*Method "getPercentageMatrix"*

---

### Description

Method getPercentageMatrix returns percentage matrix calculated out of counts

### Value

This function returns percentage matrix calculated out of counts.

### Methods

`signature(obj = "htestPhenStat")`

---

getStat

*Method "getStat"*

---

### Description

Method getStat returns simple statistics about variables in the dataset

### Value

This function returns simple statistics about variables in the dataset

### Methods

`signature(obj = "PhenList")`

---

getVariable	<i>Method "getVariable"</i>
-------------	-----------------------------

---

**Description**

Method getVariable returns dependent variable name

**Value**

This function returns dependent variable name

**Methods**

`signature(obj = "PhenTestResult")`

---

getVariables	<i>Method "getVariables"</i>
--------------	------------------------------

---

**Description**

Method getVariables returns names of variables in the dataset

**Value**

This function returns names of variables in the dataset

**Methods**

`signature(obj = "PhenList")`

---

hemiGenotype	<i>Method "hemiGenotype"</i>
--------------	------------------------------

---

**Description**

Method hemiGenotype returns hemi genotype if defined

**Value**

This function returns hemi genotype if defined

**Methods**

`signature(obj = "PhenList")`  
`signature(obj = "PhenTestResult")`

---

htest-class	<i>Class "htest"</i>
-------------	----------------------

---

## Description

An old S3 class from package stats rewritten into S4 style in order to add functionality needed for PhenStat.

## Value

S3 class

## Explore htest object

A list with class "htest" containing the following components:

1. p.value: the p-value of the test.
2. conf.int: a confidence interval for the odds ratio. Only present in the 2 by 2 case and if argument conf.int = TRUE.
3. estimate: an estimate of the odds ratio. Note that the conditional Maximum Likelihood Estimate (MLE) rather than the unconditional MLE (the sample odds ratio) is used. Only present in the 2 by 2 case.
4. null.value: the odds ratio under the null, or. Only present in the 2 by 2 case.
5. alternative: a character string describing the alternative hypothesis.
6. method: the character string "Fisher's Exact Test for Count Data".
7. data.name: a character string giving the names of the data.

## Author(s)

Natalja Kurbatova

## See Also

[htestPhenStat-class](#)

**htestPhenStat-class**    *Class "htestPhenStat"*

## Description

Extension of htest class for the PhenStat needs

## Value

Empty.

## Explore htestPhenStat object

A list with "htest" components in modelOutput slot and the additional PhenStat specific slots:

1. modelOutput: htest object with Fisher Exact test (fisher.test) output
2. analysedSubset: the subset analysed with possible values "all", "males", "females"
3. comparison: for the RR method with possible values "High vs Normal/Low", "Low vs Normal/High"
4. ES: effect size value
5. matrixCount: matrix of counts used for the test

## Slots

```
modelOutput: Object of class "htest" ~~
analysedSubset: Object of class "character" ~~
comparison: Object of class "character" ~~
ES: Object of class "numeric" ~~
matrixCount: Object of class "matrix" ~~
```

## Methods

```
getColumnView signature(obj = "htestPhenStat"): ...
getMatrix signature(obj = "htestPhenStat"): ...
getPercentageMatrix signature(obj = "htestPhenStat"): ...
subsetText signature(object = "htestPhenStat"): ...
comparison signature(object = "htestPhenStat"): ...
show signature(object = "htestPhenStat"): ...
```

## Author(s)

Natalja Kurbatova

**See Also**[htest-class](#)**Examples**

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
# "FisherExactTest" function is called from "testDataset" function.
result <- PhenStat:::testDataset(test,depVariable="Thoracic.Processes",method="FE")
# Fisher Exact Test results can be printed out using function "summaryOutput"
val <- PhenStat:::analysisResults(result)[[1]]
print(val)
class(val)
```

---

**JSONOutput***Method "JSONOutput"*

---

**Description**

Wrapper for the model fitting results. Returns model fitting and testing results in a JSON format. Assumes that modelling results are stored in the [PhenTestResult](#) object (output from function [testDataset](#)).

**Usage**

```
JSONOutput(phenoTestResult,
phenotypeThreshold = 0.01)
```

**Arguments**

phenoTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument  
phenotypeThreshold a numerical value defining the threshold to use in classificationTag; default value 0.01

**Value**

Returns a vector with model fitting results in JSON format: model output summary and other values

**Author(s)**

Natalja Kurbatova

**See Also**[PhenTestResult](#)

## Examples

```

## Not run:
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
PhenStat:::JSONOutput(result)

# Fishe Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result2 <- PhenStat:::testDataset(test2,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
PhenStat:::JSONOutput(result2)
## End(Not run)

```

**LargeDataObject-class Class "*LargeDataObject*"**

## Description

Internal class. A list-based S4 class for storing large data objects.

## Value

Empty.

## Methods

```

show signature(object = "LargeDataObject"): Prints out the object head using common method
show

printHead signature(object = "LargeDataObject"): Print leading 5 elements or rows of atomic
object

```

## Author(s)

Gordon Smyth

## References

limma package of Bioconductor <http://bioconductor.org/packages/release/bioc/html/limma.html>.

---

**LRDataset***Method "LRDataset"*

---

**Description**

Prepares dataset for the LR framework - maps values of dependent variable to 0/1, where 1 is modeled.

**Usage**

```
LRDataset(  
  phenList = NULL,  
  depVariable = NULL,  
  abnormalValues =  
    c("abnormal", "Abnormal", "TRUE", "deviant"),  
  outputMessages = TRUE  
)
```

**Arguments**

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
abnormalValues	a list of abnormal values that will be mapped to 0; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Returns dataset suitable for LR framework, where provided abnormal values are mapped to 1 and all other values of dependent variable are assumed to be normal and are mapped to 0.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")
```

---

**matrixCount**

*Method "matrixCount"*

---

## Description

Method **matrixCount** returns matrix of counts that was created by RR or FE framework.

## Value

This function returns matrix of counts that was created by RR or FE framework.

## Methods

```
signature(obj = "htestPhenStat")
```

---

**method**

*Method "method"*

---

## Description

Method **method** returns method abbreviation, for example: "RR", "MM".

## Value

This function returns returns method abbreviation.

## Methods

```
signature(obj = "PhenTestResult")
```

---

**methodText***Method "methodText"*

---

**Description**

Method `methodText` returns method's name, for example: "Reference Range Plus", "Linear Mixed Model".

**Value**

This function returns method's name.

**Methods**

```
signature(obj = "PhenTestResult")
```

---

**modelFormula***Method "modelFormula"*

---

**Description**

Creates formula for the start Mixed Model based on equation and number of sexes in the data.

**Usage**

```
modelFormula(equation, numberofsexes, depVariable)
```

**Arguments**

- |                            |   |
|----------------------------|---|
| <code>equation</code>      | a character string defining the equation to use (withWeight or withoutWeight); mandatory argument |
| <code>numberofsexes</code> | a numerical value for levels of sex in the dataset (1 or 2); mandatory argument                   |
| <code>depVariable</code>   | a character string defining the dependent variable of interest; mandatory argument                |

**Value**

Returns formula to use.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
formula <- PhenStat:::modelFormula(equation="withWeight",
                                     numberofsexes=2,
                                     depVariable="Lean.Mass")
```

**modelFormulaLR**

*Method "modelFormulaLR"*

## Description

Creates formula for the start Mixed Model based on equation and number of sexes in the data.

## Usage

```
modelFormulaLR(numberofsexes,
               depVariable,
               sexIncluded,
               dimorphismIncluded,
               IncludeBatch)
```

## Arguments

numberofsexes	a numerical value for levels of sex in the dataset (1 or 2); mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
sexIncluded	include sex effect into formula or not; mandatory argument
dimorphismIncluded	include interaction effect of Genotype/Sex into formula or not; mandatory argument
IncludeBatch	include batch effect into formula or not; mandatory argument

## Value

Returns formula to use.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
formula <- PhenStat:::modelFormulaLR(numberofsexes=2,  
                                     depVariable="Lean.Mass",TRUE,TRUE,"No")
```

---

**multipleBatches**

*Method "multipleBatches"*

---

**Description**

Method `multipleBatches` returns TRUE if there are multiple batches in the dataset, FALSE otherwise

**Value**

This function returns TRUE if there are multiple batches in the dataset.

**Methods**

```
signature(obj = "PhenList")
```

noSexes

*Method "noSexes"***Description**

Method noSexes returns number of sex levels: 1/2

**Value**

This function returns number of sex levels.

**Methods**

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

parameters

*Method "parameters"***Description**

Method parameters returns parameters specific for applied method/dataset combination

**Value**

This function returns parameters specific for applied method/dataset combination.

**Methods**

```
signature(obj = "PhenTestResult")
```

parserOutputSummary

*Method "parserOutputSummary"***Description**

Parsers model output summary and returns it in readable named vector format

**Usage**

```
parserOutputSummary(linearRegressionOutput)
```

**Arguments**

`linearRegressionOutput`  
 linear regression output that comes from the MM methods; mandatory argument

**Value**

Returns a named vector with linear regression model output summary results

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
  depVariable="Lean.Mass")
linearRegressionOutput <- PhenStat:::analysisResults(result)
PhenStat:::parserOutputSummary(linearRegressionOutput)
```

`parserOutputSummaryLR` *Method "parserOutputSummaryLR"*

**Description**

Parsers model output summary and returns it in readable named vector format

**Usage**

```
parserOutputSummaryLR(linearRegressionOutput)
```

**Arguments**

`linearRegressionOutput`  
 linear regression output that comes from the MM methods; mandatory argument

**Value**

Returns a named vector with logistic regression model output summary results

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")
resultLR <- PhenStat:::testDataset(testLR2,
                                    depVariable="V2",
                                    method="LR")
linearRegressionOutput <- PhenStat:::analysisResults(resultLR)
PhenStat:::parserOutputSummaryLR(linearRegressionOutput)
```

*parserOutputTFSummary Method "parserOutputTFSummary"*

**Description**

Parsers model output summary from TF framework and returns it in readable named vector format

**Usage**

```
parserOutputTFSummary(linearRegressionOutput)
```

**Arguments**

`linearRegressionOutput`

linear regression output that comes from the TF method; mandatory argument

**Value**

Returns a named vector with model output summary results

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "test6_RR.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="0xr1/0xr1")
result <- PhenStat:::testDataset(test,
                                 depVariable="Ca",
                                 method="TF",
                                 dataPointsThreshold=2)
linearRegressionOutput <- PhenStat:::analysisResults(result)
PhenStat:::parserOutputTFSummary(linearRegressionOutput)
```

**performReverseTransformation**

*Method "performReverseTransformation"*

**Description**

Reverse back the transformed values according to the lambda value: exponential transformation if the lambda is 0, fractional power transformation otherwise

**Usage**

```
performReverseTransformation(values, lambda, scaleShift)
```

**Arguments**

- |            |   |
|------------|---|
| values     | vector of values to reverse                 |
| lambda     | lambda value of Box-Cox transformation      |
| scaleShift | sclae shift value of Box-Cox transformation |

**Value**

Returns values transformed back to original scale.

**Author(s)**

Natalja Kurbatova

**Examples**

```
PhenStat:::performReverseTransformation(c(-5.7312462,1.3166139,-0.8921497),-0.7,0)
```

`performTransformation` *Method "performTransformation"*

**Description**

Transforms the given vector of values according to the lambda value: log transformation if the lambda is 0, power transformation otherwise

**Usage**

```
performTransformation(values, lambda, scaleShift)
```

**Arguments**

values	vector of values to reverse
lambda	lambda value of Box-Cox transformation
scaleShift	sclae shift value of Box-Cox transformation

**Value**

Returns values transformed according to Box-Cox rules.

**Author(s)**

Natalja Kurbatova

**Examples**

```
PhenStat:::performTransformation(c(0.1,38,0.5),-0.7,0)
```

---

PhenList*Method "PhenList"*

---

**Description**

Function to create data object from the data frame.

In addition to dependent variable column (the variable of interest) mandatory columns that should present in the data frame are "Genotype" and "Sex". The "Assay.Date" column is used to model "Batch" effect if not specified differently. "Weight" column is used to model body weight effect.

Function creates [PhenList](#) object, checks data integrity, renames columns when requested, provides simple statistics about dataset.

Returns an instance of the [PhenList](#) object created from the data file.

Dataset is cleaned to ensure there is a maximum two sex levels and there are exactly two levels for genotype. Data cleaning can be switched off by defining the argument "dataset.clean" as FALSE.

**Usage**

```
PhenList(dataset, testGenotype, refGenotype="+/+", hemiGenotype=NULL,
         outputMessages=TRUE, dataset.clean=TRUE,
         dataset.colname.batch=NULL, dataset.colname.genotype=NULL,
         dataset.colname.sex=NULL, dataset.colname.weight=NULL,
         dataset.values.missingValue=" ", dataset.values.male=NULL,
         dataset.values.female=NULL)
```

**Arguments**

dataset	data frame created from file or from another source; mandatory argument
testGenotype	defines the test genotype to be compared to the reference genotype; mandatory argument
refGenotype	defines the reference genotype; assigned default value is "+/+"
hemiGenotype	defines the genotype value for hemizygous that will be changed to test genotype value
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; assigned default value is TRUE
dataset.clean	flag: "FALSE" value for no modification of the dataset; "TRUE" value to clean dataset if needed; assigned default value is TRUE
dataset.colname.batch	column name within dataset for the batch effect
dataset.colname.genotype	column name within dataset for the genotype info
dataset.colname.sex	column name within dataset for the sex info

```

dataset.colname.weight
    column name within dataset for the weight info
dataset.values.missingValue
    value used as missing value in the dataset
dataset.values.male
    value used to label "males" in the dataset
dataset.values.female
    value used to label "females" in the dataset

```

**Value**

Returns an instance of the [PhenList](#) class.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenList](#)

**Examples**

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file, na.strings = '-'),
                           testGenotype="Sparc/Sparc")

file <- system.file("extdata", "test2.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file, na.strings = '-'),
                            testGenotype="Arid4a/Arid4a",
                            refGenotype="+/+",
                            hemiGenotype="Arid4a/+", 
                            dataset.colname.weight="Weight.Value")

file <- system.file("extdata", "test3.csv", package="PhenStat")
test3 <- PhenStat:::PhenList(dataset=read.csv(file, na.strings = '-'),
                             dataset.clean=TRUE,
                             dataset.values.female=1,
                             dataset.values.male=2,
                             testGenotype="Mysm1/+")

```

---

<b>PhenList-class</b>	<i>Class "PhenList"</i>
-----------------------	-------------------------

---

## Description

A list-based S4 class for storing phenotypic data. Helps to support data integrity checks and statistics calculation. The PhenList object can be created by using function [PhenList](#).

## Explore PhenList object

PhenList object instance contains the following slots:

1. "datasetPL" where cleaned and checked dataset is stored: `getDataset(phenList)`
2. "testGenotype" where the genotype level to test is stored: `testGenotype(phenList)`
3. "refGenotype" where reference genotype value is stored with default value set to "++":  
`refGenotype(phenList)`
4. "hemiGenotype" if defined contains the genotype value for hemizygous: `hemiGenotype(phenList)`
6. "dataset.clean" flag value is stored, see [PhenList](#) for more details:  
`phenList@dataset.clean`
7. "dataset.colname" if defined contains dataset column names that have been renamed:
  - `phenList@dataset.colname.batch` column name for batch values
  - `phenList@dataset.colname.genotype` column name for genotype values
  - `phenList@dataset.colname.sex` column name for sex values
  - `phenList@dataset.colname.weight` column name for weight values
8. "dataset.values" if defined contains dataset values that have been changed during dataset cleaning process:
  - `phenList@dataset.values.missingValue` value used as missing value in the orginal dataset
  - `phenList@dataset.values.male` value used to label "males" in the original dataset
  - `phenList@dataset.values.female` value used to label "females" in the original dataset

## Slots

- datasetPL:** Object of class "data.frame" ~~ dataset to work with
- refGenotype:** Object of class "character" ~~ reference genotype
- testGenotype:** Object of class "character" ~~ test genotype
- hemiGenotype:** Object of class "character" ~~ hemi genotype
- dataset.colname.batch:** Object of class "character" ~~ column name for batch values
- dataset.colname.genotype:** Object of class "character" ~~ column name for genotype values
- dataset.colname.sex:** Object of class "character" ~~ column name for sex values
- dataset.colname.weight:** Object of class "character" ~~ column name for weight values

**dataset.values.missingValue:** Object of class "character" ~~ value used as missing value in the orginal dataset

**dataset.values.male:** Object of class "character" ~~ value used to label "males" in the original dataset

**dataset.values.female:** Object of class "character" ~~ value used to label "females" in the original dataset

**dataset.clean:** Object of class "logical" ~~ flag value is stored

**datasetUNF:** Object of class "data.frame" ~~ unfiltered dataset

## Methods

**getDataset** (accessor): Returns dataset

**refGenotype** (accessor): Returns reference genotype

**testGenotype** (accessor): Returns test genotype

**hemiGenotype** (accessor): Returns hemi genotype if specified

**getColumn** Returns specified column if exists

**getColumnBatchAdjusted** Returns specified column adjusted for batch effect

**getColumnWeightBatchAdjusted** Returns specified column adjusted for batch and weight effects

**getStat** Returns simple dataset statistics

**getVariables** Returns dataset column names

**batchIn** Returns TRUE if the batch is in the dataset, FALSE otherwise

**weightIn** Returns TRUE if the weight is in the dataset, FALSE otherwise

**multipleBatches** Returns TRUE if the batches are variable in the dataset, FALSE otherwise

**noSexes** Returns number of sexes in the dataset

**setBatch** Sets the batch column - change the column names

**setGenotype** Sets the genotype column - change the column names

**setMissingValue** Sets the missing value

**setSex** Sets the sex column - change the column names

**setWeight** Sets the weight column - change the column names

## Author(s)

Natalja Kurbatova

## See Also

[PhenList](#)

## Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
class(test)

file <- system.file("extdata", "test2.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Arid4a/Arid4a",
                           refGenotype="/+",
                           hemiGenotype="Arid4a/+",
                           dataset.colname.weight="Weight.Value")
PhenStat:::getStat(test2)
PhenStat:::testGenotype(test2)
PhenStat:::refGenotype(test2)
PhenStat:::hemiGenotype(test2)

```

PhenStatReport

*Generating a pdf report from a PhenList object*

## Description

This function takes a Phenlist object and generates a pdf report containing several statistical methods.

## Usage

```

PhenStatReport(
  PhenlistObject      ,
  depVariable = NULL ,
  other.response = NULL ,
  update = TRUE      ,
  Gene.Symbol = NULL ,
  Response.name = NULL ,
  destination = NULL ,
  reportTitle = "Extended Statistical Report",
  DataRelease = NULL ,
  Showsource = FALSE ,
  open = FALSE       ,
  clean = TRUE       ,
  verbos = FALSE     ,
  ...
)

```

## Arguments

**PhenlistObject** A phenlist object that is already created by PhenList() function in PhenStat.  
**depVariable** String. Name of the dependent variable.

<code>other.response</code>	The vector of strings. A vector of names containing the other dependent variables in the data set. Default NULL
<code>update</code>	Logical flag. Set to TRUE to get the latest version of the report on the fly. Default is TRUE
<code>Gene.Symbol</code>	Optional string. Gene symbol. Default NULL
<code>Response.name</code>	Optional string. Name of the dependent variable. Default NULL
<code>destination</code>	Location of the final report file. The default is the working directory of R.
<code>reportTitle</code>	The title of the report that is printed on the top of the first page of the report.
<code>DataRelease</code>	Optional flag. Data release version. Default NULL
<code>Showsource</code>	Logical flag. Set to TRUE to see the actual R codes that generate each section of the report. Default FALSE
<code>open</code>	Logical flag. Set to TRUE to open the report after it is generated. Default FALSE
<code>clean</code>	Logical flag. Set to TRUE to remove the auxiliary files after successfully generating the report. Default TRUE
<code>verbos</code>	Logical flag. Setting to TRUE shows the details and progress of the report generating function on screen. Default FALSE
<code>...</code>	List of other parameters that can be passed to the functions.

## Details

See [PhenStatReport page on the IMPC website](#)

## Value

<code>PhenlistObject</code>	The input object
<code>depVariable</code>	Dependent variable
<code>texfile</code>	The location of the .tex file, given Clean=FALSE
<code>pdffile</code>	The location of the final pdf file
<code>...</code>	The same as the input parameters

## Author(s)

Hamed Haselimashhadi <hamedhm@ebi.ac.uk>

## See Also

[PhenList](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package = "PhenStat")
test = PhenStat:::PhenList(dataset = read.csv(file,na.strings = '-'),
                           testGenotype = "Sparc/Sparc")
## Not run:
PhenStatReport(test,
               depVariable = 'Bone.Area',
               open = TRUE)

## End(Not run)
```

PhenTestResult      *Method "PhenTestResult"*

## Description

Creates [PhenTestResult](#) object based on test results or model building results. Internal function for the package. Not build for users to directly call.

## Usage

```
PhenTestResult(model.output=NULL, model.dataset=NULL,
               depVariable=NULL,
               refGenotype=NULL,
               equation="withWeight",
               method="MM", model.effect.batch=NULL,
               model.effect.variance=NULL, model.effect.sex=NULL,
               model.effect.interaction=NULL, model.output.interaction=NULL,
               model.effect.weight=NULL, numberSexes=NULL, pThreshold=0.05,
               model.formula.null=NULL, model.formula.genotype=NULL,
               model.output.genotype.nulltest.pVal=NULL,
               model.output.quality=NULL, model.output.summary=NULL,
               model.output.averageRefGenotype = NULL,
               model.output.percentageChanges = NULL)
```

## Arguments

<code>model.output</code>	representing the model fit gls object or lme object
<code>model.dataset</code>	dataset used for modeling
<code>depVariable</code>	depending variable in the model
<code>refGenotype</code>	reference genotype in the model
<code>equation</code>	possible values: "withWeight" to include weight effect into model, "withoutWeight" to exclude weight effect from the model
<code>method</code>	possible values: "MM" to work with Mixed Model framework, "FE" to work with Fisher Exact Test framework

```

model.effect.batch
    Result of the test for batch effect significance
model.effect.variance
    Result of the test for residual variance effect
model.effect.sex
    Result of the test for sex effect significance
model.effect.weight
    Result of the test for weight effect significance
model.effect.interaction
    Result of the test for genotype by sex interaction significance
model.output.interaction
    Interaction test result: p-value
numberSexes      number of possible sex values in the dataset
pThreshold       p-value threshold used to evaluate the effect significance, default value 0.05
model.formula.null
    formula for the model without genotype effect
model.formula.genotype
    formula for the model with genotype effect
model.output.genotype.nulltest.pVal
    Genotype test results: p-value
model.output.quality
    vector that contains diagnostic test output for mixed model quality of fit
model.output.summary
    named vector that contains summary of the model output
model.output.averageRefGenotype
    named vector that contains mean values calculated for reference genotype records
model.output.percentageChanges
    named vector that contains percentage changes values per sex

```

### **Value**

Returns an instance of the [PhenTestResult](#) class.

### **Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

### **References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

### **See Also**

[PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# "testDataset" function calls "PhenTestResult" function internally
result <- PhenStat:::testDataset(test,
                                  equation="withoutWeight",
                                  depVariable="Lean.Mass")
class(result)
```

PhenTestResult-class Class "PhenTestResult"

## Description

A list-based S4 class for storing of model fitting results and other information like dependent variable, method used to build a model, etc. Helps to support operations needed for model fitting process and modelling/testing results storage. In the package PhenTestResult object is created by function [testDataset](#).

## Explore PhenTestResult object

PhenTestResults object instance contains the following slots:

1. "analysedDataset" contains subdataset that was used for the modelling/testing:

```
analysedDataset(phenTestResult)
```

2. "depVariable" contains dependent variable that was tested: [getVariable\(phenTestResult\)](#)

3. "refGenotype" contains reference genotype which is usually is wildtype: [refGenotype\(phenTestResult\)](#)

4. "testGenotype" contains test genotype: [testGenotype\(phenTestResult\)](#)

5. "method" contains method name that was used for modelling/testing: [method\(phenTestResult\)](#)

6. "transformationRequired" contains TRUE/FALSE value indicating transofrmation of dependent variable:

```
transformationText(phenTestResult) or phenTestResult@transformationRequired
```

7. "lambdaValue" contains lambda value for the Box-Cox transformation:

```
transformationText(phenTestResult) or phenTestResult$lambdaValue
```

8. "scaleShift" contains the value of scale shift for Box-Cox transformation:

```
transformationText(phenTestResult) or phenTestResult@scaleShift
```

9. "transformationCode" contains the code of transformation. Possible values:

0 - transformation is not applicable (methods "FE", "RR", "LR") or switched off by user 1 - transformation is not needed (1 is within the 95 2 - log transformation 3 - power transformation 4 - transformation is not performed since optimal lambda value is not found (-5 > lambda > 5)

```
transformationText(phenTestResult) or phenTestResult@transformationCode
```

10. "parameters" contains the parameters used during method application, e.g. pThreshold for MM and TF:

```
parameters(phenTestResult)
```

11. Modelling/testing results are stored in the sections "analysisResults": analysisResults(phenTestResult)

The contents of the analysisResults slot depend on framework that was used.

The results of MM and TF frameworks: 1. Equation used during linear modeling: analysisResults(phenTestResult)\$equation

2. Batch effect significance: analysisResults(phenTestResult)\$model.effect.batch

3. Variance equality: analysisResults(phenTestResult)\$model.effect.variance

4. Weight effect significance: analysisResults(phenTestResult)\$model.effect.weight

5. Sex effect significance: analysisResults(phenTestResult)\$model.effect.interaction

6. Evidence of sex effect (p-value): analysisResults(phenTestResult)\$model.output.interaction

7. Evidence of genotype effect (p-value): analysisResults(phenTestResult)\$model.output.genotype.nulltest.pValue

8. Formula for the final genotype model: analysisResults(phenTestResult)\$model.formula.genotype

9. Formula for the final null model: analysisResults(phenTestResult)\$model.formula.null

10. Model fitting output: analysisResults(phenTestResult)\$model.output

11. Model fitting summary: summary(analysisResults(phenTestResult)\$model.output)\$tTable

The results of FE and RR frameworks are stored as a list of htestPhenStat S4 objects: analysisResults(phenTestResult)[[1]]

Each one htestPhenStat object contains:

1. Output of Fisher Exact Test: pvalue(analysisResults(phenTestResult)[[1]]).

2. Effect size: ES(analysisResults(phenTestResult)[[1]]).

3. Name of the table analysed (all, males, females): analysedSubset(analysisResults(phenTestResult)[[1]]).

4. Comparison, used for RR only (High vs Normal/Low, Low vs High/Normal): comparison(analysisResults(phenTestResult)[[1]]).

5. Matrix of counts: matrixCount(analysisResults(phenTestResult)[[1]]).

## Slots

**analysedDataset:** Object of class "data.frame" ~~ analysed dataset

**transformationRequired:** Object of class "logical" ~~ flag indicating was or not transformation performed

**lambdaValue:** Object of class "numeric" ~~ Box-Cox transform lambda value

**scaleShift:** Object of class "numeric" ~~ Box-Cox transform scale shift

**transformationCode:** Object of class "numeric" ~~ code explaining the transformation output

**depVariable:** Object of class "character" ~~ dependent variable

**refGenotype:** Object of class "character" ~~ reference genotype

**testGenotype:** Object of class "character" ~~ test genotype

**method:** Object of class "character" ~~ analysis method

**parameters:** Object of class "matrix" ~~ parameters of method

**analysisResults:** Object of class "list" ~~ results of the analysis

## Methods

**getVariable** (accessor): Returns dependent variable  
**refGenotype** (accessor): Returns reference genotype  
**testGenotype** (accessor): Returns test genotype  
**method** (accessor): Returns method used  
**methodText** (accessor): Returns full name of the method used  
**parameters** (accessor): Returns parameteres used during the method application  
**analysisResults** (accessor): Returns analysis results depending on method  
**analysedDataset** (accessor): Returns analysed dataset  
**transformationText** (accessor): Returns the info about transformation  
**batchIn** Returns TRUE if the batch is in the dataset, FALSE otherwise  
**weightIn** Returns TRUE if the weight is in the dataset, FALSE otherwise  
**noSexes** Returns number of sexes in the dataset  
**show** Prints out the PhenTestResult object  
**getCountMatrices** Returns count matrices if they are present (for methods "FE" and "RR"), NULL otherwise.

## Author(s)

Natalja Kurbatova

## Examples

```

# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="SpArc/SpArc")
result <- PhenStat:::testDataset(test,
                                 equation="withoutWeight",
                                 depVariable="Bone.Area")
PhenStat:::getVariable(result)
PhenStat:::method(result)
# Batch effect is significant
PhenStat:::analysisResults(result)$model.effect.batch
# Variance homogeneity
PhenStat:::analysisResults(result)$model.effect.variance
# Weight effect is significant
PhenStat:::analysisResults(result)$model.effect.weight
# Sex effect is significant
PhenStat:::analysisResults(result)$model.effect.interaction
# Sex effect p-value - the result of the test
PhenStat:::analysisResults(result)$model.output.interaction
# Genotype effect p-value
PhenStat:::analysisResults(result)$model.output.genotype.nulltest.pVal
# Final model formula with genotype
PhenStat:::analysisResults(result)$model.formula.genotype
  
```

```

# Final model formula without genotype
PhenStat:::analysisResults(result)$model.formula.null
# Final model fitting output
# result$model.output
# Final model fitting summary
# summary(result$model.output)$tTable

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result <- PhenStat:::testDataset(test,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
PhenStat:::getVariable(result)
PhenStat:::method(result)
for (i in seq_along(analysisResults(result))) {
  val <- PhenStat:::analysisResults(result)[[i]]
  val
}

```

**plot.PhenList***Plot Phenlist object***Description**

Plot method for objects of class "PhenList".

**Usage**

```

## S3 method for class 'PhenList'
plot(
  x,
  depVariable = 'Value',
  graphingName = NULL ,
  outputMessages = TRUE,
  type = NULL,
  ...
)

```

**Arguments**

- x** instance of the PhenList class mandatory argument
- depVariable** a character string defining the dependent variable of interest mandatory argument
- graphingName** character string defining the name to be used on the graph for the dependent variable

outputMessages	flag:"FALSE" value to suppress output messages "TRUE" value to show output messages default value TRUE
type	a vector of names. Select one or more from the list below to only get those plots.
	<ul style="list-style-type: none"><li>• boxplotSexGenotype. See documentations for boxplotSexGenotype</li><li>• boxplotSexGenotypeBatchAdjusted. See documentations for boxplotSexGenotypeBatchAdjusted</li><li>• boxplotSexGenotypeWeightBatchAdjusted. See documentations for boxplotSexGenotypeWeightBatchAdjusted</li><li>• scatterplotSexGenotypeBatch. See documentations for scatterplotSexGenotypeBatch</li><li>• scatterplotGenotypeWeight. See documentations for scatterplotGenotypeWeight</li><li>• boxplotSexGenotypeBatch. See documentations for boxplotSexGenotypeBatch</li></ul>
	...

**Value**

Empty.

**Author(s)**

Hamed Haselimashhadi < hamedhm@eb.ac.uk >

**See Also**

[PhenList](#),

**Examples**

```
example(testDataset)
```

---

plot.PhenTestResult     *Plot phenTestResult object*

---

**Description**

Plot method for objects of class "phenTestResult".

**Usage**

```
## S3 method for class 'PhenTestResult'
plot(
  x
  ,
  graphingName = NULL
  ,
  outputMessages = TRUE
  ,
  type = NULL
  ...
)
```

**Arguments**

- x** instance of the PhenTestResult class mandatory argument
- graphingName** character string defining the name to be used on the graph for the dependent variable
- outputMessages** flag:"FALSE" value to suppress output messages "TRUE" value to show output messages default value TRUE
- type** a vector of names. Select one or more from the list below to only get those plots.
- boxplotSexGenotypeResult. See documentations for boxplotSexGenotypeResult
  - scatterplotSexGenotypeBatchResult. See documentations for scatterplotSexGenotypeBatchResult
  - scatterplotGenotypeWeightResult. See documentations for scatterplotGenotypeWeightResult
  - plotResidualPredicted. See documentations for plotResidualPredicted
  - qqplotRandomEffects. See documentations for qqplotRandomEffects
  - boxplotResidualBatch. See documentations for boxplotResidualBatch
  - qqplotRotatedResiduals. See documentations for qqplotRotatedResiduals
  - qqplotGenotype. See documentations for qqplotGenotype
  - categoricalBarplot. See documentations for categoricalBarplot
- ...

**Value**

Empty.

**Author(s)**

Hamed Haselimashhadi <hamedhm@eb.ac.uk>

**See Also**[testDataset](#)**Examples**

```
example(testDataset)
```

---

plotResidualPredicted *Method "plotResidualPredicted"*

---

**Description**

Graph function for the Mixed Model framework's results. Creates predicted versus residual values plots split by genotype.

**Usage**

```
plotResidualPredicted(phenTestResult, outputMessages=TRUE)
```

**Arguments**

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument  
outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#) and [PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
PhenStat:::plotResidualPredicted(result)
```

**printLROutput**      *Method "printLROutput"*

## Description

Prints out for linear regression output

## Usage

```
printLROutput(phenTestResult,phenotypeThreshold=0.01)
```

## Arguments

phenTestResult	instance of the <a href="#">PhenTestResult</a> class that comes from the function <code>testDataset</code> ; mandatory argument
effectValues	a vector with genotype effect and standard error for the linear regression; mandatory argument
phenotypeThreshold	a numerical value defining the threshold to use in <code>classificationTag</code> ; default value 0.01

## Value

Prints out the common part of linear regression output.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410  
 West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")
resultLR <- PhenStat:::testDataset(testLR2,
  depVariable="V2",
  method="LR")
PhenStat:::printLROutput(resultLR)
```

**printTabStyle**      *Method "printTabStyle"*

## Description

Makes ready list of strings to be printed in tabular form, creates a table row from it. Adds empty positions if needed in order to make all strings the same by length and adds "tabSep" character between strings. Returns text that is ready to be printed (one row of a table).

## Usage

```
printTabStyle(textList,positions,tabSep="|")
```

## Arguments

textList	list of strings to prepare
positions	desired length of one cell in the table
tabSep	character used to separate columns in the table; default value is " "

## Value

Returns text that is ready to be printed (one row of a table).

## Author(s)

Natalja Kurbatova

## Examples

```
row_sep <- rep("-----",3)
print(PhenStat:::printTabStyle(row_sep,11))
list1 <- c("Owner","Model","Cc")
print(PhenStat:::printTabStyle(list1,11))
print(PhenStat:::printTabStyle(row_sep,11))
list2 <- c("Natalja","Honda","125")
print(PhenStat:::printTabStyle(list2,11))
print(PhenStat:::printTabStyle(row_sep,11))
```

---

pvalue	<i>Method "pvalue"</i>
--------	------------------------

---

### Description

Method pvalue returns p-value that was calculate by RR or FE framework.

### Value

This function returns p-value that was calculate by RR or FE framework.

### Methods

```
signature(obj = "htestPhenStat")
```

---

qqplotGenotype	<i>Method "qqplotGenotype"</i>
----------------	--------------------------------

---

### Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of residuals for each genotype.

### Usage

```
qqplotGenotype(phenTestResult, outputMessages=TRUE)
```

### Arguments

`phenTestResult` instance of the `PhenTestResult` class that comes from the function `testDataset`; mandatory argument  
`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

### Value

Empty.

### Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenList](#) and [PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                  depVariable="Lean.Mass")
PhenStat:::qqplotGenotype(result)
```

qqplotRandomEffects     *Method "qqplotRandomEffects"*

## Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of blups (best linear unbiased predictions).

## Usage

```
qqplotRandomEffects(phenTestResult, outputMessages=TRUE)
```

## Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument  
 outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenList](#) and [PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
PhenStat:::qqplotRandomEffects(result)
```

**qqplotRotatedResiduals**

*Method "qqplotRotatedResiduals"*

## Description

Graph function for the Mixed Model framework's results. Creates a Q-Q plot of rotated residuals.

## Usage

```
qqplotRotatedResiduals(phenTestResult,outputMessages=TRUE)
```

## Arguments

**phenTestResult** instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

**outputMessages** flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- Houseman, E. A., Ryan, L. M., Coull, B. A. (2004): Cholesky residuals for assessing normal errors in a linear model with correlated outcomes. *Journal of the American Statistical Association* 99:466: pg 383-394. Doi 10.1198
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenList](#) and [PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test2.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           dataset.colname.weight="Weight.Value",
                           testGenotype="Arid4a/Arid4a",
                           hemiGenotype="Arid4a/+")
result <- PhenStat:::testDataset(test,
                                 depVariable="C1")
PhenStat:::qqplotRotatedResiduals(result)
```

recommendMethod	<i>Method "recommendMethod"</i>
-----------------	---------------------------------

## Description

Checks the dependent variable and dataset to make choose the appropriate statistical method. Returns the method or the list of methods that are appropriate for statistical analysis.

## Usage

```
recommendMethod(phenList    = NULL,
                depVariable = NULL,
                outputMessages = TRUE,
                upper        = 5)
```

## Arguments

- |                |   |
|----------------|---|
| phenList       | instance of the <a href="#">PhenList</a> class; mandatory argument  |
| depVariable    | a character string defining the dependent variable of interest; mandatory argument                        |
| outputMessages | flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE |
| upper          | Single integer: maximum allowed number of levels for the Batch in the TF framework                        |

**Value**

Returns the method or the list of methods that are appropriate for statistical analysis.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
PhenStat:::recommendMethod(test,"Lean.Mass")
```

*refGenotype*

*Method "refGenotype"*

**Description**

Method `refGenotype` returns reference genotype

**Value**

This function returns reference genotype.

**Methods**

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

---

RRTest	<i>Method "RRTest"</i>
--------	------------------------

---

## Description

This is an internal function run within RR framework. It performs Reference Ranges Plus test and after that Fisher Exact test on calculated count matrices. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

Works with [PhenList](#) object created by [PhenList](#) function.

## Usage

```
    RRTest(  
      phenList,  
      depVariable,  
      outputMessages = TRUE,  
      naturalVariation = 95,  
      controlPointsThreshold = 60  
    )
```

## Arguments

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE
naturalVariation	number defining the natural variation range in percents for normal values; default value 95
controlPointsThreshold	number defining how many control points is needed to perform RR plus method; default value 60

## Value

Returns results stored in instance of the [PhenTestResult](#) class

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#) and [testDataset](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# "RRTTest" function is called from "testDataset" function
result <- PhenStat:::testDataset(test,
                                  depVariable="Lean.Mass",
                                  method="RR")
# RR test results can be printed out using function "summaryOutput"
summary(result)
```

**scatterplotGenotypeWeight**

*Method "scatterplotGenotypeWeight"*

**Description**

Graph function for the phenotypic dataset. Creates a scatter plot body weight versus dependent variable.

Both a regression line and a loess line (locally weighted line) is fitted for each genotype.

**Usage**

```
scatterplotGenotypeWeight(
  phenList,
  depVariable = NULL,
  graphingName = NULL,
  outputMessages = TRUE
)
```

**Arguments**

<code>phenList</code>	instance of the <a href="#">PhenList</a> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>graphingName</code>	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Sparc/Sparc")
PhenStat:::scatterplotGenotypeWeight(test,
  depVariable="Bone.Mineral.Content",
  graphingName="BMC" )
file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Mysm1/+")
PhenStat:::scatterplotGenotypeWeight(test_1sex,
  depVariable="Lean.Mass",
  graphingName="Lean Mass")
```

scatterplotGenotypeWeightResult  
*Method "scatterplotGenotypeWeightResult"*

**Description**

Graph function for the phenotypic dataset. Creates a scatter plot body weight versus dependent variable. It is based on PhenTestResult object. Both a regression line and a loess line (locally weighted line) is fitted for each genotype.

**Usage**

```
scatterplotGenotypeWeightResult(phenTestResult,
  graphingName = NULL,
  outputMessages = TRUE)
```

## Arguments

`phenTestResult` instance of the `PhenTestResult` class; mandatory argument  
`graphingName` a character string defining the name to be used on the graph for the dependent variable; mandatory argument  
`outputMessages` flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Empty.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

#### **See Also**

## PhenList

## Examples

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
    testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
    depVariable="Lean.Mass")
PhenStat:::scatterplotGenotypeWeightResult(result,
    graphingName="BMC" )
file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
    testGenotype="Mysm1/+")
result_1sex <- PhenStat:::testDataset(test_1sex,
    depVariable="Lean.Mass")
PhenStat:::scatterplotGenotypeWeightResult(result_1sex,
    graphingName="Lean Mass")

```

---

**scatterplotSexGenotypeBatch**

*Method "scatterplotSexGenotypeBatch"*

---

**Description**

Graph function for the phenotypic dataset. Creates a scatterplot split by sex, genotype and batch. refGenotype data points are shown in black and the testGenotype data points are shown in red.

Note: the batches are not ordered with time but allow assessment of how the testGenotype data lie relative to the variation within the refGenotype data.

**Usage**

```
scatterplotSexGenotypeBatch(  
  phenList,  
  depVariable = NULL,  
  graphingName = NULL,  
  outputMessages = TRUE  
)
```

**Arguments**

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
graphingName	a character string defining the name to be used on the graph for the dependent variable; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**[PhenList](#)**Examples**

```

file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# box plot for dataset with two sexes: males and females
PhenStat:::scatterplotSexGenotypeBatch(test,
                                       depVariable="Bone.Mineral.Content",
                                       graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                                  testGenotype="Mysm1/+")
# box plot for females only dataset
PhenStat:::scatterplotSexGenotypeBatch(test_1sex,depVariable="Lean.Mass",
                                       graphingName="Lean Mass")

```

**scatterplotSexGenotypeBatchResult***Method "scatterplotSexGenotypeBatchResult"***Description**

Graph function for the phenotypic dataset. Creates a scatterplot split by sex, genotype and batch. refGenotype data points are shown in black and the testGenotype data points are shown in red. It is based on **PhenTestResult** object.

Note: the batches are not ordered with time but allow assessment of how the testGenotype data lie relative to the variation within the refGenotype data.

**Usage**

```
scatterplotSexGenotypeBatchResult(phenTestResult,
                                 graphingName = NULL,
                                 outputMessages = TRUE)
```

**Arguments**

- phenTestResult** instance of the [PhenTestResult](#) class; mandatory argument
- graphingName** a character string defining the name to be used on the graph for the dependent variable; mandatory argument
- outputMessages** flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

**Value**

Empty.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
# box plot for dataset with two sexes: males and females
PhenStat:::scatterplotSexGenotypeBatchResult(result,
                                              graphingName="BMC" )

file <- system.file("extdata", "test4.csv", package="PhenStat")
test_1sex <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                                   testGenotype="Mysm1/+")
result_1sex <- PhenStat:::testDataset(test_1sex,
                                       depVariable="Lean.Mass")
# box plot for females only dataset
PhenStat:::scatterplotSexGenotypeBatchResult(result_1sex,
                                              graphingName="Lean Mass")
```

---

setBatch

*Method "setBatch"*

---

**Description**

Method setBatch sets batch column in the dataset

**Value**

This function sets batch column in the dataset.

**Methods**`signature(obj = "PhenList")`

---

`setGenotype`      *Method "setGenotype"*

---

**Description**

Method `setGenotype` sets genotype column in the dataset

**Value**

This function sets genotype column in the dataset.

**Methods**`signature(obj = "PhenList")`

---

`setMissingValue`      *Method "setMissingValue"*

---

**Description**

Method `setMissingValue` sets missing value in the dataset

**Value**

This function sets missing value in the dataset.

**Methods**`signature(obj = "PhenList")`

---

`setSex`      *Method "setSex"*

---

**Description**

Method `setSex` sets sex column in the dataset

**Value**

This function sets sex column in the dataset.

**Methods**`signature(obj = "PhenList")`

---

setWeight

*Method "setWeight"*

---

## Description

Method setWeight sets weight column in the dataset

## Value

This function sets weight column in the dataset.

## Methods

`signature(obj = "PhenList")`

---

---

startLRModel

*Method "startLRModel"*

---

## Description

This is an internal function run within LR framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis.

The tested effects are:

- batch effect (TRUE if batch variation is significant, FALSE if not), though it is never used in final LR model;
- interaction effect (TRUE if genotype by sex interaction is significant),
- sex effect (TRUE if sex is significant),
- weight effect and variance effect are not tested and used in LR model.

## Usage

```
startLRModel(phenList,  
depVariable,  
outputMessages = TRUE,  
pThreshold = 0.05)
```

### Arguments

<code>phenList</code>	instance of the <a href="#">PhenList</a> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE
<code>pThreshold</code>	a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05

### Value

Returns results stored in instance of the [PhenTestResult](#) class

### Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

### References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

### See Also

[PhenList](#)

### Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startLRModel" function is called - the first step of LR framework
resultLR <- PhenStat:::testDataset(testLR2,
                                    depVariable="V2",
                                    callAll=FALSE,
                                    method="LR")
# print out formula that has been created
PhenStat:::analysisResults(resultLR)$model.formula.genotype
# print out batch effect's significance
PhenStat:::analysisResults(resultLR)$model.effect.batch
```

---

startModel*Method "startModel"*

---

**Description**

This is an internal function run within MM framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis (the model fixed effects).

The model random effects are:

- batch effect (TRUE if batch variation is significant, FALSE if not)

The model fixed effects are:

- variance effect (TRUE if residual variances for genotype groups are homogeneous and FALSE if they are heterogeneous),

- interaction effect (TRUE if genotype by sex interaction is significant),

- sex effect (TRUE if sex is significant),

- weight effect (TRUE if weight is significant).

If user would like to assign other TRUE/FALSE values to the fixed effects of the model then he or she has to define keepList argument which is vector of TRUE/FALSE values.

If user has defined model fixed effects (keepList argument) then function prints out calculated and user defined effects (only when outputMessages argument is set to TRUE), checks user defined effects for consistency (for instance, if there are no "Weight" column in the dataset then weight effect can't be assigned to TRUE, etc.) and modifies start model according to user defined effects.

As the result PhenTestResult object that contains calculated or user defined model fixed effects and MM start model is created.

**Usage**

```
startModel(phenList, depVariable,
           equation="withWeight", outputMessages=TRUE,
           pThreshold=0.05, keepList=NULL, modelWeight = NULL,
           threshold = 10^-18,
           check = 1)
```

**Arguments**

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
equation	a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight"
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE

<code>pThreshold</code>	a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05
<code>keepList</code>	a logical vector defining the significance of different model effects: <code>keep_batch</code> , <code>keep_equalvar</code> , <code>keep_weight</code> , <code>keep_sex</code> , <code>keep_interaction</code> ; default value <code>NULL</code>
<code>modelWeight</code>	a vector of positive values for weights in the mixed model. The sum of the values must be one.
<code>threshold</code>	a single positive value. The threshold for the <code>ModelWeights</code> to consider as zero (see <code>modelWeight</code> )
<code>check</code>	Only useful when <code>modelWeight</code> is included. Select between 0, 1, 2 to impose different weighting strategies on the Linear Mixed model. <code>check=1</code> (default) selects the weights that are greater than the threshold (above) and keeps the batches that include more than one single sample. <code>check=2</code> keeps only the weights that are greater than the threshold but ignores the single sample batches. <code>check=0</code> to disable the function.

**Value**

Returns results stored in instance of the [PhenTestResult](#) class

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
# when "testDataset" function's argument "callAll" is set to FALSE
# only "startModel" function is called - the first step of MM framework
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass",
                                 callAll=FALSE)
# print out formula that has been created
PhenStat:::analysisResults(result)$model.formula.genotype
# print out batch effect's significance
PhenStat:::analysisResults(result)$model.effect.batch
# change the model
```

```

result <- PhenStat:::testDataset(test,
                                depVariable="Lean.Mass",
                                equation="withWeight",
                                callAll=FALSE)
# print out new formula
PhenStat:::analysisResults(result)$model.formula.genotype

```

**startTFModel***Method "startTFModel"***Description**

This is an internal function run within TF framework. It completes the testing stage of which effects are significant. As an internal function, it doesn't include extensive error testing of inputs. Please use cautiously if calling directly.

It creates start model and modify it after testing of different hypothesis.

The tested fixed effects are:

- batch effect (TRUE if batch variation is significant, FALSE if not),
- variance effect (TRUE if residual variances for genotype groups are homogeneous and FALSE if they are heterogeneous),
- interaction effect (TRUE if genotype by sex interaction is significant),
- sex effect (TRUE if sex is significant),
- weight effect (TRUE if weight is significant).

**Usage**

```
startTFModel(phenList, depVariable,
             equation="withWeight", outputMessages=TRUE,
             pThreshold=0.05, keepList=NULL)
```

**Arguments**

<b>phenList</b>	instance of the <b>PhenList</b> class; mandatory argument
<b>depVariable</b>	a character string defining the dependent variable of interest; mandatory argument
<b>equation</b>	a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight"
<b>outputMessages</b>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages ; default value TRUE
<b>pThreshold</b>	a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05
<b>keepList</b>	a logical vector defining the significance of different model effects: keep_batch, keep_equalvar, keep_weight, keep_sex, keep_interaction; default value NULL

**Value**

Returns results stored in instance of the [PhenTestResult](#) class

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test7_TFE.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="het",
                           refGenotype = "WT",
                           dataset.colname.sex="sex",
                           dataset.colname.genotype="Genotype",
                           dataset.values.female="f",
                           dataset.values.male= "m",
                           dataset.colname.weight="body.weight",
                           dataset.colname.batch="Date_of_procedure_start")

test_TF <- PhenStat:::TFDataset(test,depVariable="Cholesterol")

# when "testDataset" function's argument "callAll" is set to FALSE
# only "startTFModel" function is called - the first step of TFE framework
result <- PhenStat:::testDataset(test_TF,
                                 depVariable="Cholesterol",
                                 callAll=FALSE,
                                 method="TF")
# print out formula that has been created
PhenStat:::analysisResults(result)$model.formula.genotype
# print out batch effect's significance
PhenStat:::analysisResults(result)$model.effect.batch
```

---

`subsetText`

*Method "subsetText"*

---

### Description

Method `subsetText` returns full name of subset that was analysed by RR or FE framework: Males only, Females only, All.

### Value

This function returns full name of subset that was analysed by RR or FE framework.

### Methods

```
signature(obj = "htestPhenStat")
```

---

`summary.PhenTestResult`

*summary*

---

### Description

Wrapper for the model fitting results. Returns model fitting and testing results in a user friendly format.

### Usage

```
## S3 method for class 'PhenTestResult'  
summary(object, phenotypeThreshold = 0.01,...)
```

### Arguments

<code>object</code>	instance of the <code>PhenTestResult</code> class that comes from the function <code>testDataset</code> ; mandatory argument
<code>phenotypeThreshold</code>	a numerical value defining the threshold to use in <code>classificationTag</code> ; default value 0.01
<code>...</code>	Not applicable

### Value

Returns model fitting results in a text format for the screen

### Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="SpArc/SpArc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
summary(result)

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result2 <- PhenStat:::testDataset(test2,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
summary(result2)
```

*summaryOutput*      *Method "summaryOutput"*

## Description

Wrapper for the model fitting results. Returns model fitting and testing results in a user friendly format.

## Usage

```
summaryOutput(phenTestResult, phenotypeThreshold = 0.01)
```

## Arguments

**phenTestResult** instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument  
**phenotypeThreshold** a numerical value defining the threshold to use in classificationTag; default value 0.01

**Value**

Returns model fitting results in a text format for the screen

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
PhenStat:::summaryOutput(result)

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result2 <- PhenStat:::testDataset(test2,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
PhenStat:::summaryOutput(result2)
```

---

testDataset

*Method "testDataset"*

---

**Description**

Statistical analysis manager function in PhenStat package.

Firstly, it performs the checks for dependent variable in the dataset. Some checks are generic, some depends on selected statistical framework/method.

Secondly, if checks are passed it runs the stages of selected framework to analyse dependent variable.

For instance, runs startModel and finalModel for the MM framework if the argument "callAll" is set to TRUE. If framework contains only one stage like in Fisher Exact Test case then runs that one stage regardless "callAll" value.

## Usage

```
testDataset(
  phenList = NULL,
  depVariable = NULL,
  equation = "withWeight",
  outputMessages = TRUE,
  pThreshold = 0.05,
  method = "MM",
  modelWeight = NULL,
  callAll = TRUE,
  keepList = NULL,
  dataPointsThreshold = 4,
  RR_naturalVariation = 95,
  RR_controlPointsThreshold = 60,
  transformValues = FALSE,
  useUnfiltered = FALSE,
  threshold = 10 ^ -18,
  check = 1,
  upper = 5
)
```

## Arguments

<code>phenList</code>	instance of the <a href="#">PhenList</a> class; mandatory argument
<code>depVariable</code>	a character string defining the dependent variable of interest; mandatory argument
<code>equation</code>	a character string defining the equation to use. Possible values "withWeight" (default), "withoutWeight"
<code>outputMessages</code>	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE
<code>pThreshold</code>	a numerical value for the p-value threshold used to determine which fixed effects to keep in the model, default value 0.05
<code>method</code>	a character string ("MM", "FE", "TF" or "RR") defining the method to use for model building; default value "MM" for mixed model
<code>modelWeight</code>	a vector of possible weights (the same length as the response) that are imposed on the weighted MM. Only works when method="MM". The default is NULL that leads to normal (non-weighted) MM.
<code>callAll</code>	flag: "FALSE" value to run only the first stage of the selected framework; "TRUE" value (default) to run all stages of framework one after another
<code>keepList</code>	a logical vector defining the significance of different model effects: <code>keep_batch</code> , <code>keep_equalvar</code> , <code>keep_weight</code> , <code>keep_sex</code> , <code>keep_interaction</code> ; default value NULL

	<b>dataPointsThreshold</b>
	threshold for the number of data points in the MM framework; default value is 4 ; minimal value is 2
	<b>RR_naturalVariation</b>
	threshold for the variation ranges in the RR framework; default value is 95 ; minimal value is 60
	<b>RR_controlPointsThreshold</b>
	threshold for the number of control data points in the RR framework ; default value is 60; minimal value is 40
	<b>transformValues</b>
	flag: "FALSE" value to suppress transformation; "TRUE" value to perform transformation if needed; default value FALSE
<b>useUnfiltered</b>	flag: "FALSE" value to use filtered dataset; "TRUE" value to use unfiltered dataset; default value FALSE
<b>threshold</b>	The threshold for the model weights to be considered as zero. It only works when method="MM" and modelWeight is not null. Default is 10^-18.
<b>check</b>	Only useful when modelWeight is included. Select between 0, 1, 2 to impose different weighting strategies on the Linear Mixed model. check=1 (default) selects the weights that are greater than the threshold (above) and keeps the batches that include more than one single sample. check=2 keeps only the weights that are greater than the threshold but ignores the single sample batches. check=0 to disable the function.
<b>upper</b>	Single integer: maximum allowed number of levels for the Batch in the TF framework. Default 5

## Value

Returns results stored in instance of the [PhenTestResult](#) class

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

## See Also

[PhenList](#), [plot.PhenTestResult](#), [plot.PhenList](#)

## Examples

```

# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
plot(test,depVariable="Lean.Mass")

result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
# print out formula that has been created
PhenStat:::analysisResults(result)$model.formula.genotype
summary(result)
plot(result)

# Mixed Model framework with user defined effects
user_defined_effects <- c(keep_batch=TRUE,
                           keep_equalvar=TRUE,
                           keep_weight=TRUE,
                           keep_sex=TRUE,
                           keep_interaction=TRUE)
result3 <- PhenStat:::testDataset(test,
                                   depVariable="Lean.Mass",
                                   keepList=user_defined_effects)
# print out formula that has been created
PhenStat:::analysisResults(result3)$model.formula.genotype
summary(result3)
plot(result3)

# Fisher Exact Test framework
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
plot(test2,depVariable="Thoracic.Processes")
result2 <- PhenStat:::testDataset(test2,
                                   depVariable="Thoracic.Processes",
                                   method="FE")
summary(result2)
plot(result2)

```

## Description

Performs diagnostic tests for Logistic Regression model quality of fit. There are no arguments checks assuming that function is called internally from the "finalLRModel" function. Otherwise should be used with precaution.

## Usage

```
testFinalLRModel(phenTestResult)
```

## Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function `testDataset`  
; mandatory argument

## Value

Returns a vector with model fitting results

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "testLR.csv", package="PhenStat")
testLR <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
    testGenotype="Mock")
testLR2 <- PhenStat:::LRDataset(testLR,"V2")
resultLR <- PhenStat:::testDataset(testLR2,
    depVariable="V2",
    method="LR")
PhenStat:::testFinalLRModel(resultLR)
```

**testFinalModel**      *Method "testFinalModel"*

## Description

Performs diagnostic tests for Mixed Model quality of fit. There are no arguments checks assuming that function is called internally from the "finalModel" function. Otherwise should be used with precaution.

## Usage

```
testFinalModel(phenTestResult)
```

## Arguments

**phenTestResult** instance of the [PhenTestResult](#) class that comes from the function `testDataset`  
; mandatory argument

## Value

Returns a vector with model fitting results

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

## See Also

[PhenTestResult](#)

## Examples

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
                                 depVariable="Lean.Mass")
PhenStat:::testFinalModel(result)
```

---

testGenotype	<i>Method "testGenotype"</i>
--------------	------------------------------

---

**Description**

Method testGenotype returns test genotype

**Value**

This function returns test genotype.

**Methods**

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

---

---

TFDataset	<i>Method "TFDataset"</i>
-----------	---------------------------

---

**Description**

Removes of all non-concurrent batches from the dataset. Returns dataset suitable for TF framework or original dataset if data removal was not successful.

**Usage**

```
TFDataset(phenList,
          depVariable,
          outputMessages = TRUE,
          forDecisionTree = FALSE,
          upper           = 5)
```

**Arguments**

phenList	instance of the <a href="#">PhenList</a> class; mandatory argument
depVariable	a character string defining the dependent variable of interest; mandatory argument
outputMessages	flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE
forDecisionTree	flag: "FALSE" value for normal procedure; "TRUE" value to indicate that is called form decisionTree function; default value FALSE
upper	Single integer: maximum allowed number of levels for the Batch in the TF framework. Default 5.

**Value**

Returns dataset suitable for TF framework or original dataset if data removal was not successful.

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software *New York: Chapman & Hall/CRC* 353 p.

**See Also**

[PhenList](#)

**Examples**

```
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Sparc/Sparc")
test2 <- PhenStat:::TFDataset(test,"Lean.Mass")
```

transformation

*Method "transformation"*

**Description**

Method *transformation* returns transformation values: lamda=value, scaleShift=value

**Value**

This function returns transformation values.

**Methods**

```
signature(obj = "PhenTestResult")
```

---

transformationJSON      *Method "transformationJSON"*

---

**Description**

Method `transformationJSON` returns transformation values as JSON string

**Value**

This function returns transformation values as JSON string.

**Methods**

`signature(obj = "PhenTestResult")`

---

transformationText      *Method "transformationText"*

---

**Description**

Method `transformationText` returns transformation values as one string

**Value**

This function returns transformation values as one string.

**Methods**

`signature(obj = "PhenTestResult")`

---

vectorOutput      *Method "vectorOutput"*

---

**Description**

Wrapper for the model fitting results. Returns model fitting and testing results in a vector format. Assumes that modelling results are stored in the `PhenTestResult` object (output from function `testDataset`).

**Usage**

```
vectorOutput(
  phenTestResult,
  phenotypeThreshold = 0.01,
  othercolumns = NULL,
  quote  = '"'
)
```

**Arguments**

phenTestResult	instance of the <a href="#">PhenTestResult</a> class that comes from the function <a href="#">testDataset</a> ; mandatory argument
phenotypeThreshold	a numerical value defining the threshold to use in classificationTag; default value 0.01
othercolumns	a vector of column names that needs to be included in the function output
quote	The character that is used to encompass the JSON keys in summary statistics. The default is quotation

**Value**

Returns a vector with model fitting results: model output summary and other values

**Author(s)**

Natalja Kurbatova, Natasha Karp, Jeremy Mason

**References**

- Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410
- West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

**See Also**

[PhenTestResult](#)

**Examples**

```
# Mixed Model framework
file <- system.file("extdata", "test1.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
  testGenotype="Sparc/Sparc")
result <- PhenStat:::testDataset(test,
  depVariable="Lean.Mass")
PhenStat:::vectorOutput(result)

# Fishe Exact Test framework
```

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test2 <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result2 <- PhenStat:::testDataset(test2,
                                   depVariable="Thoracic.Processes",
                                   method="FE")
PhenStat:::vectorOutput(result2)
```

---

vectorOutputMatrices *Method "vectorOutputMatrices"*

---

## Description

Returns count matrices from Fisher Exact Test framework in a vector form.

Note: Maximal supported number of dependent variable levels is 10.

## Usage

```
vectorOutputMatrices(phenTestResult, outputMessages=TRUE)
```

## Arguments

phenTestResult instance of the [PhenTestResult](#) class that comes from the function [testDataset](#); mandatory argument

outputMessages flag: "FALSE" value to suppress output messages; "TRUE" value to show output messages; default value TRUE

## Value

Returns a vector with count values.

## Author(s)

Natalja Kurbatova, Natasha Karp, Jeremy Mason

## References

Karp N, Melvin D, Sanger Mouse Genetics Project, Mott R (2012): Robust and Sensitive Analysis of Mouse Knockout Phenotypes. *PLoS ONE* 7(12): e52410. doi:10.1371/journal.pone.0052410

West B, Welch K, Galecki A (2007): Linear Mixed Models: A practical guide using statistical software New York: Chapman & Hall/CRC 353 p.

## See Also

[PhenTestResult](#)

**Examples**

```
file <- system.file("extdata", "test_categorical.csv", package="PhenStat")
test <- PhenStat:::PhenList(dataset=read.csv(file,na.strings = '-'),
                           testGenotype="Aff3/Aff3")
result <- PhenStat:::testDataset(test,
                                 depVariable="Thoracic.Processes",
                                 method="FE")
PhenStat:::vectorOutputMatrices(result)
```

---

**weightIn**

*Method "weightIn"*

---

**Description**

Returns TRUE if the weight is in the dataset, FALSE otherwise

**Value**

TRUE/FALSE

**Methods**

```
signature(obj = "PhenList")
signature(obj = "PhenTestResult")
```

# Index

- \* **classes**
  - htest-class, 33
  - htestPhenStat-class, 34
  - LargeDataObject-class, 36
  - PhenList-class, 49
  - PhenTestResult-class, 55
- \* **internal**
  - columnChecks, 17
  - columnLevels, 18
  - determiningLambda, 19
  - dim, 20
  - formulaDeterminingLambda, 27
  - htest-class, 33
  - htestPhenStat-class, 34
  - LargeDataObject-class, 36
  - modelFormula, 39
  - modelFormulaLR, 40
  - performReverseTransformation, 45
  - performTransformation, 46
  - printLROutput, 62
  - printTabStyle, 63
- \* **methods**
  - analysedDataset, 4
  - analysedDatasetPhenList, 4
  - analysedSubset, 5
  - analysisResults, 5
  - batchIn, 6
  - comparison, 19
  - dataset, 19
  - getColumn, 28
  - getColumnBatchAdjusted, 29
  - getColumnView, 29
  - getColumnWeightBatchAdjusted, 29
  - getCountMatrices, 30
  - getDataset, 30
  - getGenotypeEffect, 30
  - getMatrix, 31
  - getPercentageMatrix, 31
  - getStat, 31
  - getVariable, 32
  - getVariables, 32
  - hemiGenotype, 32
  - htestPhenStat-class, 34
  - matrixCount, 38
  - method, 38
  - methodText, 39
  - multipleBatches, 41
  - noSexes, 42
  - parameters, 42
  - PhenList-class, 49
  - PhenTestResult-class, 55
  - pvalue, 64
  - refGenotype, 68
  - setBatch, 75
  - setGenotype, 76
  - setMissingValue, 76
  - setSex, 76
  - setWeight, 77
  - subsetText, 83
  - testGenotype, 91
  - transformation, 92
  - transformationJSON, 93
  - transformationText, 93
  - weightIn, 96
- analysedDataset, 4
- analysedDataset, PhenTestResult-method
  - (PhenTestResult-class), 55
- analysedDatasetPhenList, 4
- analysedSubset, 5
- analysedSubset, htestPhenStat-method
  - (htestPhenStat-class), 34
- analysisResults, 5
- analysisResults, PhenTestResult-method
  - (PhenTestResult-class), 55
- batchIn, 6
- batchIn, PhenList-method (batchIn), 6

batchIn, PhenTestResult-method  
     (batchIn), 6  
 batchIn-methods (batchIn), 6  
 boxplotResidualBatch, 6  
 boxplotSexGenotype, 7  
 boxplotSexGenotypeBatch, 8  
 boxplotSexGenotypeBatchAdjusted, 10  
 boxplotSexGenotypeResult, 11  
 boxplotSexGenotypeWeightBatchAdjusted,  
     12  
  
 categoricalBarplot, 13  
 checkDataset, 14, 15  
 classificationTag, 16  
 columnChecks, 17  
 columnLevels, 18  
 comparison, 19  
 comparison, htestPhenStat-method  
     (htestPhenStat-class), 34  
  
 dataset, 19  
 dataset, PhenList-method  
     (PhenList-class), 49  
 determiningLambda, 19  
 dim, 20, 21  
  
 finalLRModel, 21  
 finalModel, 22  
 finalTFModel, 24  
 FisherExactTest, 25  
 formulaDeterminingLambda, 27  
  
 generateGraphs, 27  
 getColumn, 28  
 getColumn, PhenList, character-method  
     (PhenList-class), 49  
 getColumnBatchAdjusted, 29  
 getColumnBatchAdjusted, PhenList, character-method  
     (PhenList-class), 49  
 getColumnView, 29  
 getColumnView, htestPhenStat-method  
     (htestPhenStat-class), 34  
 getColumnWeightBatchAdjusted, 29  
 getColumnWeightBatchAdjusted, PhenList, character-method  
     (PhenList-class), 49  
 getCountMatrices, 30  
 getCountMatrices, PhenTestResult-method  
     (PhenTestResult-class), 55  
 getDataset, 30

getGenotypeEffect, 30  
 getGenotypeEffect, PhenTestResult-method  
     (PhenTestResult-class), 55  
 getMatrix, 31  
 getMatrix, htestPhenStat-method  
     (htestPhenStat-class), 34  
 getPercentageMatrix, 31  
 getPercentageMatrix, htestPhenStat-method  
     (htestPhenStat-class), 34  
 getStat, 31  
 getStat, PhenList-method  
     (PhenList-class), 49  
 getVariable, 32  
 getVariable, PhenTestResult-method  
     (PhenTestResult-class), 55  
 getVariables, 32  
 getVariables, PhenList-method  
     (PhenList-class), 49  
  
 hemiGenotype, 32  
 hemiGenotype, PhenList-method  
     (PhenList-class), 49  
 htest-class, 33  
 htestPhenStat-class, 34  
  
 JSONOutput, 35  
  
 LargeDataObject-class, 36  
 LRDataset, 37  
  
 matrixCount, 38  
 matrixCount, htestPhenStat-method  
     (htestPhenStat-class), 34  
 method, 38  
 method, PhenTestResult-method  
     (PhenTestResult-class), 55  
 methodText, 39  
 methodText, PhenTestResult-method  
     (PhenTestResult-class), 55  
 modelFormula, 39  
 modelFormulaLR, 40  
 multipleBatches, 41  
 multipleBatches, PhenList-method  
     (PhenList-class), 49  
  
 noSexes, 42  
 noSexes, PhenList-method (noSexes), 42  
 noSexes, PhenTestResult-method  
     (noSexes), 42

parameters, 42  
parameters, PhenTestResult-method  
    (PhenTestResult-class), 55  
parserOutputSummary, 42  
parserOutputSummaryLR, 43  
parserOutputTFSummary, 44  
performReverseTransformation, 45  
performTransformation, 46  
PhenList, 7–10, 12–15, 20, 26, 37, 47, 47,  
    48–50, 52, 59, 61, 65–75, 78–82, 86,  
    87, 91, 92  
PhenList-class, 49  
PhenStatReport, 51  
PhenTestResult, 6, 7, 11, 13, 15–17, 21–26,  
    28, 35, 40, 41, 43–45, 53, 53, 54, 61,  
    62, 64–67, 69, 72, 74, 78, 80, 82–85,  
    87, 89, 90, 93–95  
PhenTestResult-class, 55  
plot.PhenList, 58, 87  
plot.PhenTestResult, 59, 87  
plotResidualPredicted, 61  
printHead, LargeDataObject-method  
    (LargeDataObject-class), 36  
printLROutput, 62  
printTabStyle, 63  
pvalue, 64  
pvalue, htestPhenStat-method  
    (htestPhenStat-class), 34  
  
qqplotGenotype, 64  
qqplotRandomEffects, 65  
qqplotRotatedResiduals, 66  
  
recommendMethod, 67  
refGenotype, 68  
refGenotype, PhenList-method  
    (PhenList-class), 49  
refGenotype, PhenTestResult-method  
    (PhenTestResult-class), 55  
RRTest, 69  
  
scatterplotGenotypeWeight, 70  
scatterplotGenotypeWeightResult, 71  
scatterplotSexGenotypeBatch, 73  
scatterplotSexGenotypeBatchResult, 74  
setBatch, 75  
setBatch, PhenList, character-method  
    (PhenList-class), 49  
setGenotype, 76  
  
setGenotype, PhenList, character-method  
    (PhenList-class), 49  
setMissingValue, 76  
setMissingValue, PhenList, character-method  
    (PhenList-class), 49  
setSex, 76  
setSex, PhenList, character-method  
    (PhenList-class), 49  
setWeight, 77  
setWeight, PhenList, character-method  
    (PhenList-class), 49  
show, htestPhenStat-method  
    (htestPhenStat-class), 34  
show, LargeDataObject-method  
    (LargeDataObject-class), 36  
show, PhenTestResult-method  
    (PhenTestResult-class), 55  
startLRModel, 21, 77  
startModel, 22, 79  
startTFModel, 24, 81  
subsetText, 83  
subsetText, htestPhenStat-method  
    (htestPhenStat-class), 34  
summary.PhenTestResult, 83  
summaryOutput, 84  
  
testDataset, 6, 16, 21–25, 28, 35, 55, 61,  
    64–66, 70, 83, 84, 85, 93–95  
testFinalLRModel, 88  
testFinalModel, 90  
testGenotype, 91  
testGenotype, PhenList-method  
    (PhenList-class), 49  
testGenotype, PhenTestResult-method  
    (PhenTestResult-class), 55  
TFDataset, 91  
transformation, 92  
transformationJSON, 93  
transformationText, 93  
transformationText, PhenTestResult-method  
    (PhenTestResult-class), 55  
  
vectorOutput, 93  
vectorOutputMatrices, 95  
  
weightIn, 96  
weightIn, PhenList-method (weightIn), 96  
weightIn, PhenTestResult-method  
    (weightIn), 96  
weightIn-methods (weightIn), 96