

Package ‘alabaster.bumpy’

October 15, 2023

Title Save and Load BumpyMatrices to/from file

Version 1.0.0

Date 2023-02-28

Description Save BumpyMatrix objects into file artifacts, and load them back into memory.
This is a more portable alternative to serialization of such objects into RDS files.
Each artifact is associated with metadata for further interpretation;
downstream applications can enrich this metadata with context-specific properties.

License MIT + file LICENSE

Depends BumpyMatrix, alabaster.base

Imports methods, Matrix, BiocGenerics, S4Vectors, IRanges

Suggests BiocStyle, rmarkdown, knitr, testthat, jsonlite

VignetteBuilder knitr

RoxygenNote 7.2.3

biocViews DataImport, DataRepresentation

git_url <https://git.bioconductor.org/packages/alabaster.bumpy>

git_branch RELEASE_3_17

git_last_commit da9aa0c

git_last_commit_date 2023-04-25

Date/Publication 2023-10-15

Author Aaron Lun [cre, aut]

Maintainer Aaron Lun <infinite.monkeys.with.keyboards@gmail.com>

R topics documented:

loadBumpyDataFrameMatrix	2
stageObject,BumpyDataFrameMatrix-method	3
useBumpyHDF5	3

Index	5
--------------	----------

`loadBumpyDataFrameMatrix`*Load a BumpyDataFrameMatrix object*

Description

Load a [BumpyDataFrameMatrix](#) object based on its metadata.

Usage

```
loadBumpyDataFrameMatrix(assay.info, project)
```

Arguments

<code>assay.info</code>	Named list of metadata for the BumpyDataFrameMatrix , generated by the corresponding stageObject method.
<code>project</code>	Any argument accepted by the acquisition functions, see ?acquireFile . By default, this should be a string containing the path to a staging directory.

Value

A [BumpyDataFrameMatrix](#) object.

Author(s)

Aaron Lun

Examples

```
# Mocking up a BumpyMatrix.
library(BumpyMatrix)
library(S4Vectors)
df <- DataFrame(x=runif(100), y=runif(100))
f <- factor(sample(letters[1:20], nrow(df), replace=TRUE), letters[1:20])
out <- S4Vectors::split(df, f)
mat <- BumpyMatrix(out, c(5, 4))

# Staging it:
tmp <- tempfile()
dir.create(tmp)
meta <- stageObject(mat, tmp, "BUMPY")

# Loading it:
loadBumpyDataFrameMatrix(meta, tmp)
```

stageObject,BumpyDataFrameMatrix-method
Stage BumpyDataFrameMatrix objects

Description

Staging method for [BumpyDataFrameMatrix](#) objects. See [?stageObject](#) for more details.

Usage

```
## S4 method for signature 'BumpyDataFrameMatrix'
stageObject(x, dir, path, child = FALSE)
```

Arguments

x	A BumpyDataFrameMatrix object.
dir	String containing the path to the staging directory.
path	String containing a prefix of the relative path inside dir where x is to be saved. The actual path used to save x may include additional components, see Details .
child	Logical scalar indicating whether x is a child of a larger object.

Value

A named list of metadata, to be used by [.writeMetadata](#).

Author(s)

Aaron Lun

See Also

[useBumpyHDF5](#), to control whether the concatenated data frame is saved as a CSV or HDF5 file.

useBumpyHDF5	<i>Save BumpyMatrix data to HDF5</i>
--------------	--------------------------------------

Description

Use HDF5 for the underlying data frame, i.e., obtained after [unlisting](#) the [BumpyMatrix](#). This is less intuitive than a CSV but preserves the precision of floating-point numbers.

Usage

```
useBumpyHDF5(use)
```

Arguments

`use` Logical scalar indicating whether to save in HDF5.

Value

If `use` is missing, a logical scalar is returned indicating whether data should be saved in HDF5.

If `use` is provided, it is used to set the corresponding flag globally. The previous value of the flag is returned invisibly.

Examples

```
useBumpyHDF5()  
  
old <- useBumpyHDF5(FALSE)  
useBumpyHDF5()  
  
# Setting it back.  
useBumpyHDF5(old)
```

Index

`.writeMetadata`, 3
`acquireFile`, 2
`BumpyDataFrameMatrix`, 2, 3
`BumpyMatrix`, 3
`loadBumpyDataFrameMatrix`, 2
`stageObject`, 2, 3
`stageObject`, `BumpyDataFrameMatrix`-method,
3
`unlist`, 3
`useBumpyHDF5`, 3, 3