

Package ‘omicsViewer’

October 15, 2023

Title Interactive and explorative visualization of
SummarizedExpressionSet or ExpressionSet using omicsViewer

Version 1.4.0

Description omicsViewer visualizes ExpressionSet (or SummarizedExperiment) in an interactive way. The omicsViewer has a separate back- and front-end. In the back-end, users need to prepare an ExpressionSet that contains all the necessary information for the downstream data interpretation. Some extra requirements on the headers of phenotype data or feature data are imposed so that the provided information can be clearly recognized by the front-end, at the same time, keep a minimum modification on the existing ExpressionSet object. The pure dependency on R/Bioconductor guarantees maximum flexibility in the statistical analysis in the back-end. Once the ExpressionSet is prepared, it can be visualized using the front-end, implemented by shiny and plotly. Both features and samples could be selected from (data) tables or graphs (scatter plot/heatmap). Different types of analyses, such as enrichment analysis (using Bioconductor package fgsea or fisher's exact test) and STRING network analysis, will be performed on the fly and the results are visualized simultaneously. When a subset of samples and a phenotype variable is selected, a significance test on means (t-test or ranked based test; when phenotype variable is quantitative) or test of independence (chi-square or fisher's exact test; when phenotype data is categorical) will be performed to test the association between the phenotype of interest with the selected samples. Additionally, other analyses can be easily added as extra shiny modules. Therefore, omicsViewer will greatly facilitate data exploration, many different hypotheses can be explored in a short time without the need for knowledge of R. In addition, the resulting data could be easily shared using a shiny server. Otherwise, a standalone version of omicsViewer together with designated omics data could be easily created by integrating it with portable R, which can be shared with collaborators or submitted as supplementary data together with a manuscript.

Depends R (>= 4.2)

License GPL-2

Imports survminer, survival, fastmatch, reshape2, stringr, beeswarm,
grDevices, DT, shiny, shinythemes, shinyWidgets, plotly,
networkD3, httr, matrixStats, RColorBrewer, Biobase, fgsea,
openxlsx, psych, shinybusy, ggseqlogo, htmlwidgets, graphics,
grid, stats, utils, methods, shinyjs, curl, flatxml, ggplot2,
S4Vectors, SummarizedExperiment, RSQLite, Matrix,
shinycssloaders, ROCR

Suggests BiocStyle, knitr, rmarkdown, unittest

VignetteBuilder knitr

LazyData false

Encoding UTF-8

biocViews Software, Visualization, GeneSetEnrichment,
DifferentialExpression, MotifDiscovery, Network,
NetworkEnrichment

BugReports <https://github.com/mengchen18/omicsViewer>

URL <https://github.com/mengchen18/omicsViewer>

Video <https://www.youtube.com/watch?v=0nirB-exquY&list=PLo2m88IJf-RRoLKY8UEGqCpraKYrX5lk>

RoxygenNote 7.1.2

git_url <https://git.bioconductor.org/packages/omicsViewer>

git_branch RELEASE_3_17

git_last_commit 34e4d9d

git_last_commit_date 2023-04-25

Date/Publication 2023-10-15

Author Chen Meng [aut, cre]

Maintainer Chen Meng <mengchen18@gmail.com>

R topics documented:

app_module	3
app_ui	5
asEsetWithAttr	5
correlationAnalysis	6
csc2list	7
draw_roc_pr	7
exprspca	8
extendMetaData	9
fgsea1	10
fillNA	11
filterRow	12
getAutoRIF	12
getMQParams	13
getUPRefProteomeID	14
gsAnnotIdList	14
hasAttr	16
hclust2str	16
list2csc	17
multi.t.test	17
nColors	19

normalize.nQuantiles	19
normalize.totsum	20
normalizeColWise	21
normalizeData	22
omicsViewer	23
parseDatTerm	24
plotly_boxplot_module	24
plotly_boxplot_ui	25
plotly_scatter_module	26
plotly_scatter_ui	28
plot_roc_pr_module	30
prepOmicsViewer	31
read.proteinGroups	33
read.proteinGroups.If	34
readESVObj	34
read_gmt	35
removeVarQC	36
rowshift	36
saveOmicsViewerDb	37
triselector_module	38
triselector_ui	39
trisetter	40
validMQFolder	41
varSelector	42

Index**43**

app_module	<i>Application level 0 module</i>
------------	-----------------------------------

Description

Function should only be used for the developers

Usage

```
app_module(  
  input,  
  output,  
  session,  
  .dir,  
  filePattern = ".(RDS|db|sqlite|sqlite3)$",  
  additionalTabs = NULL,  
  ESVObj = reactive(NULL),  
  esetLoader = readESVObj,  
  exprsGetter = getExprs,  
  pDataGetter = getPData,  
  fDataGetter = getFData,
```

```

imputeGetter = getExprsImpute,
defaultAxisGetter = getAx,
appName = "omicsViewer",
appVersion = packageVersion("omicsViewer")
)

```

Arguments

input	input
output	output
session	session
.dir	reactive; directory containing the .RDS file of ExpressionSet or SummarizedExperiment
filePattern	file pattern to be displayed.
additionalTabs	additional tabs added to "Analyst" panel
ESVObj	the ESV object given, the drop down list should be disable in the "ui" component.
esetLoader	function to load the eset object, if an RDS file, should be "readRDS"
exprsGetter	function to get the expression matrix from eset
pDataGetter	function to get the phenotype data from eset
fDataGetter	function to get the feature data from eset
imputeGetter	function to get the imputed expression matrix from eset, only used when exporting imputed data to excel
defaultAxisGetter	function to get the default axes to be visualized. It should be a function with two arguments: x - the object loaded to the viewer; what - one of "sx", "sy", "fx" and "fy", representing the sample space x-axis, sample space y-axis, feature space x-axis and feature space y-axis respectively.
appName	name of the application
appVersion	version of the application

Value

do not return any values

Examples

```

if (interactive()) {
  dir <- system.file("extdata", package = "omicsViewer")
  server <- function(input, output, session) {
    callModule(app_module, id = "app", dir = reactive(dir))
  }
  ui <- fluidPage(
    app_ui("app")
  )
  shinyApp(ui = ui, server = server)
}

```

app_ui*Application level 0 UI*

Description

Function should only be used for the developers

Usage

```
app_ui(id, showDropList = TRUE, activeTab = "Feature")
```

Arguments

id	id
showDropList	logical; whether to show the dropdown list to select RDS file, if the ESVObj is given, this should be set to "FALSE"
activeTab	one of "Feature", "Feature table", "Sample", "Sample table", "Heatmap"

Value

a list of UI components

Examples

```
if (interactive()) {  
  dir <- system.file("extdata", package = "omicsViewer")  
  server <- function(input, output, session) {  
    callModule(app_module, id = "app", dir = reactive(dir))  
  }  
  ui <- fluidPage(  
    app_ui("app")  
  )  
  shinyApp(ui = ui, server = server)  
}
```

asEsetWithAttr*Convert SummarizedExperiment to ExpressionSet retaining all attributes*

Description

Convert SummarizedExperiment to ExpressionSet retaining all attributes

Usage

```
asEsetWithAttr(x)
```

Arguments

- x an object of class SummarizedExperiment

Value

an object of class ExpressionSet

correlationAnalysis *Correlating a expression matrix with phenotypical variables*

Description

This is a convenience function to perform correlation analysis, the output is in a format ready to be incorporated into object to be visualized by omicsViewer.

Usage

```
correlationAnalysis(x, pheno, min.value = 12, prefix = "Cor")
```

Arguments

- x an expression matrix, rows are the features (e.g. proteins), columns are the samples
- pheno a data.frame storing the numerical phenotypical variable to be correlated with the rows (features) in expression matrix.
- min.value the minimum number of samples required in the correlation analysis, if lower than this number, NA will be returned.
- prefix prefix of the names. Usually don't need to be changed by the user. When changes are needed, the prefix should be in a format like [analysis name][subset] so the "analysis name" and "subset" can be selected in the omicsViewer.

Value

Every correlation analysis returns a data.frame with five columns: R - pearson correlation coefficient N - number of values used in the analysis P - p-values returned by pearson correlation analysis logP - log transformed p-values range - the range of values in expression matrix used in the analysis

Examples

```
e1 <- matrix(rnorm(500), 50, 10)
rownames(e1) <- paste0("FT", 1:50)
p1 <- matrix(rnorm(50), 10, 5)
colnames(p1) <- paste0("PH", 1:5)
colnames(e1) <- rownames(p1) <- paste0("S", 1:10)
correlationAnalysis(x = e1, pheno = p1, min.value = 8)
```

csc2list*convert a column compressed sparse matrix to a list*

Description

convert a column compressed sparse matrix to a list

Usage

```
csc2list(x)
```

Arguments

x	a matrix or CsparseMatrix object
---	----------------------------------

Value

a sparse frame in data.frame

draw_roc_pr*Drawing ROC and PR curve*

Description

Drawing ROC and PR curve

Usage

```
draw_roc_pr(value, label)
```

Arguments

value	a numerical vector indicates the predictions
label	true class labels, could be two or more unique values

Examples

```
v <- sort(rnorm(100))
l <- sample(1:2, size = 100, replace = TRUE)
draw_roc_pr(v, l)
l <- rep(c("b", "c", "a", "d"), each = 25)
draw_roc_pr(v, l)
draw_roc_pr(v, sample(l))
```

exprspca*Perform PCA and prepare results for omicsViewer*

Description

This is a convenience function to perform PCA on expression matrix, the output of PCA will be in a format ready to be incorporated into object to be visualized by `omicsViewer`.

Usage

```
exprspca(x, n = min(8, ncol(x) - 1), prefix = "PCA|All", fillNA = FALSE, ...)
```

Arguments

<code>x</code>	an expression matrix, where rows are features and samples are on columns.
<code>n</code>	number of components to keep
<code>prefix</code>	prefix of the names. Usually don't need to be changed by the user. When changes are needed, the prefix should be in a format like [analysis name][subset] so the "analysis name" and "subset" can be selected in the <code>omicsViewer</code> .
<code>fillNA</code>	logical; whether NA should be filled? If FALSE (default), <code>na.omit</code> will be called before PCA. If TRUE, the missing value will be replaced using <code>fillNA</code> .
<code>...</code>	other parameters passed to <code>prcomp</code>

Value

a `data.frame` storing the PCA results

Examples

```
# reading expression
packdir <- system.file("extdata", package = "omicsViewer")
expr <- read.delim(file.path(packdir, "expressionMatrix.tsv"), stringsAsFactors = FALSE)
# call PCA
pc <- exprspca(expr)
head(pc$samples)
head(pc$features)
```

extendMetaData	<i>Add extra columns to the phenoData/colData or featureData/rowData in ExpressionSet/SummarizedExperiment</i>
----------------	--

Description

Add extra columns to the phenoData/colData or featureData/rowData in ExpressionSet/SummarizedExperiment
Add extra columns to the phenoData/colData or featureData/rowData in ExpressionSet/SummarizedExperiment
Add extra columns to the phenoData/colData or featureData/rowData in ExpressionSet/SummarizedExperiment

Usage

```
extendMetaData(object, newData, where)

## S4 method for signature 'ExpressionSet,data.frame'
extendMetaData(
  object,
  newData,
  where = c("pData", "fData", "colData", "rowData")[1]
)

## S4 method for signature 'SummarizedExperiment,data.frame'
extendMetaData(
  object,
  newData,
  where = c("pData", "fData", "colData", "rowData")[1]
)

## S4 method for signature 'SummarizedExperiment,DFrame'
extendMetaData(
  object,
  newData,
  where = c("pData", "fData", "colData", "rowData")[1]
)
```

Arguments

object	an object of ExpressionSet-class
newData	a data.frame containing the data to be added
where	where to add the extra columns, should be one of "pData", "fData", "rowData" and "colData".

Value

an object of ExpressionSet-class

Note

The attributes in the pheno data and feature data will be preserved

Examples

```
est <- Biobase::ExpressionSet(assayData=matrix(runif(1000), nrow=100, ncol=10))
Biobase::pData(est)
est <- extendMetaData(est, data.frame(letter = letters[1:10]), where = "pData")
Biobase::pData(est)
```

fgsea1

Wrapper of fgseaMultilevel function to take binary gene set matrix as input

Description

Wrapper of fgseaMultilevel function to take binary gene set matrix as input

Usage

```
fgsea1(gs, stats, gs_desc = NULL, ...)
```

Arguments

gs	either a data.frame or a (sparse) matrix input. If a data.frame object is given, it should have at least three columns named as "featureId", "gsId" and "weight". If a matrix is given, the matrix is binary matrix where rows are features and columns are gene sets. The values in the matrix should be either 1 or 0 representing the presence and absence of a feature in the genesets, repectively.
stats	ranking stats
gs_desc	description of gene sets, it should be a named vector and the names should be the same as colnames(gs)
...	other parameters passed to fgseaMultilevel

Value

a data.frame of fgsea results

Examples

```
## not for users
# library(fgsea)
# library(Biobase)
# dat <- readRDS(system.file(package = "omicsViewer", "extdata/demo.RDS"))
# fd <- fData(dat)
# fdgs <- fd[, grep("^GS\\|", colnames(fd))]
# res <- fgsea1(fdgs, stats = fd$t-test|OV_BR|md`, minSize = 5, maxSize = 500)
```

```
# res <- fgsea1(
#   fdgs, stats = fd$t-test|OV_BR|md`,
#   minSize = 5, maxSize = 500, gs_desc = colnames(fdgs))
```

fillNA

Filling NAs in a matrix using constants calculated from user the defined function

Description

This function is usually use to impute missing values in expression matrix, where the rows are feature and columns are samples. This function impute the missing values on the row-wise, that is, every row will be imputed using different constant.

Usage

```
fillNA(
  x,
  maxfill = quantile(x, probs = 0.15, na.rm = TRUE),
  fillingFun = function(x) min(x, na.rm = TRUE) - log10(2)
)
```

Arguments

<code>x</code>	a matrix with NA values
<code>maxfill</code>	the maximum filled value, if the value calculated by <code>fillingFun</code> is greater than <code>maxfill</code> , then <code>maxfill</code> will be used to replace NAs.
<code>fillingFun</code>	function to calculate the filling values. It should be a function accept at least one argument "x", which is a row of input expression matrix. The default is <code>function(x) min(x, na.rm = TRUE) - log10(2)</code> corresponds to the "half of lowest detected values" if the expression matrix is <code>log10</code> transformed. More examples: #` function(x) min(x, na.rm = TRUE) - 1 # half of lowest detected value when expression matrix is in <code>log2</code> scale #` function(x) 0 # replace NA by 0

Value

a matrix without NAs

Note

The returned matrix may have -Inf, which may need to be filtered/replaced additionally

Examples

```
m <- matrix(rnorm(200), 20, 10)
m[sample(1:200, size = 20)] <- NA
mf <- fillNA(m)
```

filterRow*Filter out rows of expression matrix***Description**

The function is used to filter rows with values of low intensities or do not reproducible presented in replicates.

Usage

```
filterRow(x, max.quantile = NULL, max.value = NULL, var = NULL, min.rep = 2)
```

Arguments

<code>x</code>	an expression matrix
<code>max.quantile</code>	a single numerical value between (0, 1), if the row maximum is smaller than this quantile (calculated from the whole matrix), the row will be removed.
<code>max.value</code>	a single numerical value, if the the maximum value of a rwo is smaller than this value, the row will be removed. Only used if <code>max.quantile</code> is set to "NULL".
<code>var</code>	variables has the same length as the column number in <code>x</code> to indicate which sample is from which group
<code>min.rep</code>	the minimum number of replicate in at least one of the groups, if less than this value, the row will be removed.

Value

a logical vector where the TRUE means row to keep

Examples

```
e1 <- matrix(rnorm(5000, sd = 0.3), 500, 10) + rnorm(500)
f <- filterRow(x = e1, max.quantile = 0.25)
table(f)
```

getAutoRIF*Get genes associated with search terms and AutoRIF annotations***Description**

Get genes associated with search terms and AutoRIF annotations

Usage

```
getAutoRIF(term, rif = c("generif", "autorif")[1], filter = TRUE)
```

Arguments

<code>term</code>	a character vector of terms want to search
<code>rif</code>	either autorif or generif, see " https://maayanlab.cloud/geneshot/ "
<code>filter</code>	whether the result should be filtered. The least frequently mentioned genes (most like 1 or 2 times) will be removed.

Value

a `data.frame` of 4 columns: gene, n, perc, rank.

Note

<https://amp.pharm.mssm.edu/geneshot/>

References

Alexander Lachmann, Brian M Schilder, Megan L Wojciechowicz, Denis Torre, Maxim V Kuleshov, Alexandra B Keenan, Avi Ma'ayan, Geneshot: search engine for ranking genes from arbitrary text queries, Nucleic Acids Research, Volume 47, Issue W1, 02 July 2019, Pages W571–W577, <https://doi.org/10.1093/nar/gkz393>

Alexander Lachmann, Brian M Schilder, Megan L Wojciechowicz, Denis Torre, Maxim V Kuleshov, Alexandra B Keenan, Avi Ma'ayan, Geneshot: search engine for ranking genes from arbitrary text queries, Nucleic Acids Research, Volume 47, Issue W1, 02 July 2019, Pages W571–W577, <https://doi.org/10.1093/nar/gkz393>

Examples

```
a <- getAutoRIF("mtor signaling")
```

`getMQParams`

Parse mqpar.xml file

Description

Getting the experimental informatione (TMT or label free) from mqpar.xml file.

Usage

```
getMQParams(x)
```

Arguments

<code>x</code>	the path to mqpar.xml file
----------------	----------------------------

Value

a list of MQ paramters

`getUPRefProteomeID` *get uniprot reference proteome IDs*

Description

get uniprot reference proteome IDs
get uniprot reference proteome IDs

Usage

```
getUPRefProteomeID(
  domain = c("Eukaryota", "Archaea", "Bacteria", "Viruses")[1]
)

downloadUPRefProteome(
  id,
  domain = c("Eukaryota", "Archaea", "Bacteria", "Viruses")[1],
  destdir = "./"
)
```

Arguments

<code>domain</code>	the domain, one of "Eukaryota", "Archaea", "Bacteria" or "Viruses"
<code>id</code>	the UP id to download
<code>destdir</code>	destination directory

Value

a character vector of UP ids
a character vector of UP ids

Functions

- `getUPRefProteomeID`: get uniprot reference protein IDs

`gsAnnotIdList` *Annotation of gene/protein function using multiple IDs.*

Description

Annotation of gene/protein function using multiple IDs.

Usage

```
gsAnnotIdList(
  idList,
  gsIdMap,
  minSize = 5,
  maxSize = 500,
  data.frame = FALSE,
  sparse = TRUE
)
```

Arguments

<code>idList</code>	list of protein IDs, e.g. <code>list(c("ID1", "ID2"), c("ID13"), c("ID4", "ID8", "ID10"))</code>
<code>gsIdMap</code>	a data frame for geneset to id map, it has two columns - id: the ID column - term: annotation terms e.g. <code>gsIdMap <- data.frame(id = c("ID1", "ID2", "ID1", "ID2", "ID8", "ID10"), term = c("T1", "T1", "T2", "T2", "T2", "T2"), stringsAsFactors = FALSE)</code>
<code>minSize</code>	minimum size of gene sets
<code>maxSize</code>	maximum size of gene sets
<code>data.frame</code>	logical; whether to organize the result into <code>data.frame</code> format, see "Value" section.
<code>sparse</code>	logical; whether to return a sparse matrix, only used when <code>data.frame=FALSE</code>

Value

A binary matrix (if `data.frame = FALSE`), the number of rows is the same with length of `idList`, the columns are the annotated gene set; or a `data.frame` (if `data.frame = TRUE`) with three columns: `featureId`, `gsId`, `weight`.

Examples

```
terms <- data.frame(
  id = c("ID1", "ID2", "ID1", "ID2", "ID8", "ID10"),
  term = c("T1", "T1", "T2", "T2", "T2", "T2"),
  stringsAsFactors = FALSE
)
features <- list(c("ID1", "ID2"), c("ID13"), c("ID4", "ID8", "ID10"))
gsAnnotIdList(idList = features, gsIdMap = terms, minSize = 1, maxSize = 500)

terms <- data.frame(
  id = c("ID1", "ID2", "ID1", "ID2", "ID8", "ID10", "ID4", "ID4"),
  term = c("T1", "T1", "T2", "T2", "T2", "T2", "T1", "T2"),
  stringsAsFactors = FALSE
)
features <- list(F1 = c("ID1", "ID2", "ID4"), F2 = c("ID13"), F3 = c("ID4", "ID8", "ID10"))
gsAnnotIdList(features, gsIdMap = terms, data.frame = TRUE, minSize = 1)
gsAnnotIdList(features, gsIdMap = terms, data.frame = FALSE, minSize = 1)
```

<code>hasAttr</code>	<i>Check whether an object has an attribute</i>
----------------------	---

Description

Check whether an object has an attribute

Usage

```
hasAttr(x, attr.name)
```

Arguments

<code>x</code>	the object
<code>attr.name</code>	a character vector containing the name of attributes to be checked

Value

a logical value/vector has the same length as attr.name

<code>hclust2str</code>	<i>Convert hclust object to/from single character</i>
-------------------------	---

Description

Convert hclust object to/from single character

Usage

```
hclust2str(x)
str2hclust(x)
```

Arguments

<code>x</code>	a character of length one or an hclust object
----------------	---

Value

a character stores the hclust object
a hclust object

Note

The \$call element in hclust will not retained in the conversion. The conversion decrease the precision in \$height element.

Examples

```
# not for end users
# m <- matrix(rnorm(50), 25)
# hc <- hclust(dist(m))
# plot(hc)
# te <- hclust2str(hc)
# hc2 <- str2hclust(te)
# plot(hc2)
```

list2csc

convert a list to column compressed sparse matrix

Description

convert a list to column compressed sparse matrix

Usage

```
list2csc(l, dimnames)
```

Arguments

- | | |
|----------|---|
| l | a data.frame with at least two columns - featureId, gsId; optionally a "weight" column. |
| dimnames | a list of dimnames, should contain at least one element for the row names. |

Value

a sparse matrix, CsparseMatrix, column compressed

multi.t.test

Function to perform multiple t-tests on an expression matrix

Description

This is a convenience function to perform multiple student's t-test. The output is in a format ready to be incorporated into object to be visualized by `omicsViewer`. This function use `t.test`.

Usage

```
multi.t.test(x, pheno, compare = NULL, fillNA = FALSE, ...)
```

Arguments

x	an expression matrix, usually log10 transformed.
pheno	phenotype data of x, the number of rows in pheno must equal the number of columns of x. Please refer to examples for more details.
compare	NULL or a matrix with three columns to define the comparisons to do. When a matrix is given, the first column should be one of the column headers in pheno; then the second and third columns should be two values presented (more than once) in the columns of pheno selected by the values in the first column. The samples mapped to the two values are compared. If paired comparisons to be done, the orders of samples should be mapped
fillNA	logical; whether NA should be filled? If FALSE (default), t test will be performed whenever possible. If not possible, then NA will be returned. If TRUE, the missing value will be replaced using fillNA .
...	other parameters passed to t.test

Value

a data.frame stores the t-test results with the follow columns:

- mean|[selected header in pheno]|[[group 1 in test]] - The mean value of group 1
- n value|[selected header in pheno]|[[group 1 in test]] - The number of value used in the test for group 1
- quantile|[selected header in pheno]|[[group 1 in test]] - The quantile of means values in group 1
- mean|[selected header in pheno]|[[group 2 in test]] - The mean value of group 2
- n value|[selected header in pheno]|[[group 2 in test]] - The number of value used in the test for group 2
- quantile|[selected header in pheno]|[[group 2 in test]] - The quantile of means values in group 2
- ttest|[group 1 in test]_vs_[group 2 in test]|pvalue - The p-value return by [t.test](#)
- ttest|[group 1 in test]_vs_[group 2 in test]|log.pvalue - The -log10 transformed p-value
- ttest|[group 1 in test]_vs_[group 2 in test]|fdr - The BH method corrected p-values, e.g. FDR
- ttest|[group 1 in test]_vs_[group 2 in test]|log.fdr - The -log10 transformed FDR
- mean.diff - The difference between the means of the two groups, e.g. fold change

Examples

```
# reading expression
packdir <- system.file("extdata", package = "omicsViewer")
expr <- read.delim(file.path(packdir, "expressionMatrix.tsv"), stringsAsFactors = FALSE)
# reading phenotype data
pd <- read.delim(file.path(packdir, "sampleGeneral.tsv"), stringsAsFactors = FALSE)

## Single t-test
head(pd)
# define comparisons
tests <- c("Origin", "RE", "ME")
tres <- multi.t.test(x = expr, pheno = pd, compare = tests)

## multiple t-test
head(pd)
# define comparisons
tests <- rbind(
  c("Origin", "RE", "ME"),
  c("RE", "ME", "Origin"),
  c("RE", "Origin", "ME"))
```

```
c("Origin", "RE", "LE"),
c('TP53.Status', "MT", "WT")
)
tres <- multi.t.test(x = expr, pheno = pd, compare = tests)
```

nColors*Generating k distinct colors***Description**

Mainly used in the shiny app to generate reproducible k distinct colors.

Usage

```
nColors(k, stop = FALSE)
```

Arguments

- | | |
|------|---|
| k | a number between 1 to 60 tells how many distinct colors to use |
| stop | logical; whether the function should return an error message if k is not in the range of 2 to 60. Default FALSE, the function will return NULL. |

Value

a vector of hex code for k colors or NULL

Examples

```
nColors(5)
nColors(1, stop = FALSE)
```

normalize.nQuantiles *Normalization using n quantiles***Description**

Normalization using n quantiles

Usage

```
normalize.nQuantiles(x, probs = 0.5, shareFeature = FALSE, ref = 1)
```

Arguments

x	an expression matrix, usually log transformed
probs	the quantiles to be aligned across samples. If probs is a length 1 numerical vector, the quantiles will be aligned. As a special case, probs = 0.5 equals the median centering. If probs' length is > 1, a shift and scaling factor of samples will be calculating by fitting linear models using quantiles of samples, the median and variance of samples will be corrected using the intercept and slope of the fitted model.
shareFeature	logical; if TRUE, the normalization will be based on the shared features between samples
ref	the column name or index to specify the reference sample, only used when shareFeature = TRUE

Value

a normalized matrix

Examples

```
e1 <- matrix(rnorm(5000), 500, 10)
e1[, 6:10] <- 0.3 * e1[, 6:10] + 3
boxplot(e1)
# median centering, no variance correction
e2 <- normalize.nQuantiles(x = e1, probs = 0.5)
boxplot(e2)
# median centering + variance stabilization
e3 <- normalize.nQuantiles(x = e1, probs = seq(0.25, 0.75, by = 0.1))
boxplot(e3)
```

normalize.totsum *Normalize total sum*

Description

Normalize total sum

Usage

```
normalize.totsum(x)
```

Arguments

x	a log10 transformed expression matrix
---	---------------------------------------

Value

a normalized matrix

Examples

```
e1 <- matrix(rnorm(5000), 500, 10)
e1[, 6:10] <- e1[, 6:10]+3
boxplot(e1)
e2 <- normalize.totsum(x = e1)
boxplot(e2)
```

normalizeColWise *Column-wise normalization of expression matrix*

Description

A wrapper function of all column-wise normalization methods

Usage

```
normalizeColWise(
  x,
  method = c("Median centering", "Median centering (shared ID)", "Total sum",
            "median centering + variance stablization")[1]
)
```

Arguments

- | | |
|---------------|--|
| x | an expression matrix where rows are features and columns are samples, usually log transformed. |
| method | normalization method to use "Median centering" - median centering, see normalize.nQuantiles
"Median centering (shared ID)" - median centering using shared features, see normalize.nQuantiles "Total sum" - total sum normalization "median centering + variance stablization" - 10 quantile normalization using 0.25, 0.3, ..., 0.75, see normalize.nQuantiles |

Value

a normalized matrix

Examples

```
e1 <- matrix(rnorm(5000), 100, 50)+10
boxplot(e1)
e2 <- normalizeColWise(x = e1, method = "Median centering")
boxplot(e2)
```

normalizeData	<i>Normalized expression matrix</i>
---------------	-------------------------------------

Description

A wrapper function of all normalization methods, including row-wise or column-wise normalization.

Usage

```
normalizeData(
  x,
  colWise = c("None", "Median centering", "Median centering (shared ID)", "Total sum",
             "median centering + variance stabilization")[1],
  rowWise = c("None", "Reference", "Batch mean", "Batch reference")[1],
  ref = NULL,
  batch = NULL
)
```

Arguments

<code>x</code>	an expression matrix where rows are features and columns are samples, usually log transformed.
<code>colWise</code>	column-wise normalization method to use, see normalizeColWise
<code>rowWise</code>	row-wise normalization method to used Reference - using removeVarQC method Batch mean - using rowshift method without reference samples Batch reference - using rowshift method with reference samples
<code>ref</code>	index of reference samples
<code>batch</code>	batch factor

Value

a normalized matrix

Examples

```
e1 <- matrix(rnorm(5000), 100, 50)+10
boxplot(e1)
e2 <- normalizeData(x = e1, ref = seq(5, 45, by = 10), rowWise = "Reference")
boxplot(e2)
```

omicsViewer	<i>Start omicsViewer</i>
-------------	--------------------------

Description

Start omicsViewer

Usage

```
omicsViewer(  
  dir,  
  additionalTabs = NULL,  
  filePattern = ".(RDS|DB|SQLITE|SQLITE3)$",  
  ESVObj = NULL,  
  esetLoader = readESVObj,  
  exprsGetter = getExprs,  
  pDataGetter = getPData,  
  fDataGetter = getFData,  
  defaultAxisGetter = getAx,  
  appName = "omicsViewer",  
  appVersion = packageVersion("omicsViewer")  
)
```

Arguments

dir	directory to the ExpressionSet or SummarizedExperiment object. Only give the directory in this argument, not the .rds file.
additionalTabs	additional tabs added to "Analyst" panel
filePattern	file pattern to be displayed.
ESVObj	the ESV object
esetLoader	function to load the eset object, if an RDS file, should be "readRDS"
exprsGetter	function to get the expression matrix from eset
pDataGetter	function to get the phenotype data from eset
fDataGetter	function to get the feature data from eset
defaultAxisGetter	function to get the default axes to be visualized. It should be a function with two arguments: x - the object loaded to the viewer; what - one of "sx", "sy", "fx" and "fy", representing the sample space x-axis, sample space y-axis, feature space x-axis and feature space y-axis respectively.
appName	name of the application
appVersion	version of the application

Value

do not return values

Examples

```

1
## To start the shiny app:
# omicsViewer(
#   system.file("extdata", package = "omicsViewer")
# )

```

`parseDatTerm`

Extract function annotation from uniprot .dat file

Description

Extract function annotation from uniprot .dat file

Usage

```
parseDatTerm(file, outputDir = NULL, ...)
```

Arguments

<code>file</code>	the .dat or .dat.gz file
<code>outputDir</code>	dir of output file
<code>...</code>	other parameters passed to readLines

Value

a data.frame parse from .dat file

`plotly_boxplot_module` *Shiny module for boxplot using plotly - Module*

Description

Shiny module for boxplot using plotly - Module

Usage

```
plotly_boxplot_module(
  input,
  output,
  session,
  reactive_param_plotly_boxplot,
  reactive_checkpoint = reactive(TRUE)
)
```

Arguments

input	input
output	output
session	session
reactive_param_plotly_boxplot	reactive value; argument passed to plotly_boxplot
reactive_checkpoint	reactive_value; check this value before render any plot/executing any calculation

Value

do not return any values

Examples

```
if (interactive()) {

  library(shiny)

  ui <- fluidPage(
    plotly_boxplot_ui("testplotly")
  )

  server <- function(input, output, session) {

    x <- cbind(matrix(rnorm(10000, mean = 3), 1000, 10), matrix(rnorm(20000), 1000, 20))
    x[sample(1:length(x), size = 0.3*length(x))] <- NA
    rownames(x) <- paste("R", 1:nrow(x), sep = "")
    colnames(x) <- paste("C", 1:ncol(x), sep = "")
    callModule(plotly_boxplot_module, id = "testplotly",
              reactive_param_plotly_boxplot = reactive(list(
                x = x# , i = c(4, 20, 80)# , highlight = c(1, 4, 5, 20), extvar = 1:30
              )))
  }
}

shinyApp(ui, server)
}
```

plotly_boxplot_ui *Shiny module for boxplot using plotly - UI*

Description

Function should only be used for the developers

Usage

`plotly_boxplot_ui(id)`

Arguments

id	id
----	----

Value

a tagList of UI components	a tagList of UI components
----------------------------	----------------------------

Examples

```
if (interactive()) {

  library(shiny)

  ui <- fluidPage(
    plotly_boxplot_ui("testplotly")
  )

  server <- function(input, output, session) {

    x <- cbind(matrix(rnorm(10000, mean = 3), 1000, 10), matrix(rnorm(20000), 1000, 20))
    x[sample(1:length(x), size = 0.3*length(x))] <- NA
    rownames(x) <- paste("R", 1:nrow(x), sep = "")
    colnames(x) <- paste("C", 1:ncol(x), sep = "")
    callModule(plotly_boxplot_module, id = "testplotly",
              reactive_param_plotly_boxplot = reactive(list(
                x = x# , i = c(4, 20, 80)# , highlight = c(1, 4, 5, 20), extvar = 1:30
              )))
  }
}

shinyApp(ui, server)
}
```

plotly_scatter_module *Shiny module for scatter plot using plotly - Module*

Description

Function should only be used for the developers

Usage

```
plotly_scatter_module(
  input,
  output,
  session,
  reactive_param_plotly_scatter,
```

```

reactive_regLine = reactive(FALSE),
reactive_checkpoint = reactive(TRUE),
htest_var1 = reactive(NULL),
htest_var2 = reactive(NULL)
)

```

Arguments

input	input
output	output
session	sesion
reactive_param_plotly_scatter	reactive parammeters for plotly_scatter
reactive_regLine	logical show or hide the regression line
reactive_checkpoint	checkpoint
htest_var1	when the plot is a beeswarmplot, two groups could be selected for two group comparison, this argument gives the default value. Mainly used for restoring the saved session.
htest_var2	see above

Value

a list containing the information about the selected data points
 an reactive object containing the information of selected, brushed points.

Examples

```

if (interactive()) {
  library(shiny)

  # two random variables
  x <- rnorm(30)
  y <- x + rnorm(30, sd = 0.5)

  # variables mapped to color, shape and size
  cc <- sample(letters[1:4], replace = TRUE, size = 30)
  shape <- sample(c("S1", "S2", "S3"), replace = TRUE, size = 30)
  sz <- sample(c(10, 20, 30, replace = TRUE, size = 30))

  ui <- fluidPage(
    plotly_scatter_ui("test_scatter")
  )

  server <- function(input, output, session) {
    v <- callModule(plotly_scatter_module, id = "test_scatter",
      # reactive_checkpoint = reactive(FALSE),
      reactive_param_plotly_scatter = reactive(list(

```

```

        x = x, y = y,
        color = cc,
        shape = shape,
        size = sz,
        tooltips = paste("A", 1:30)
    )))
    observe(print(v())))
}
shinyApp(ui, server)

# example beeswarm horizontal
x <- rnorm(30)
y <- sample(c("x", "y", "z"), size = 30, replace = TRUE)
shinyApp(ui, server)

# example beeswarm vertical
x <- sample(c("x", "y", "z"), size = 30, replace = TRUE)
y <- rnorm(30)
shinyApp(ui, server)

# return values
x <- c(5, 6, 3, 4, 1, 2)
y <- c(5, 6, 3, 4, 1, 2)
ui <- fluidPage(
    plotly_scatter_ui("test_scatter")
)
server <- function(input, output, session) {
    v <- callModule(plotly_scatter_module, id = "test_scatter",
                    reactive_param_plotly_scatter = reactive(list(
                        x = x, y = y, tooltips = paste("A", 1:6), highlight = 2:4
                    )))
    observe(print(v()))
}
shinyApp(ui, server)
}

```

plotly_scatter_ui *Shiny module for scatter plot using plotly - UI*

Description

Function should only be used for the developers

Usage

```
plotly_scatter_ui(id, height = "400px")
```

Arguments

<code>id</code>	<code>id</code>
<code>height</code>	figure height

Value

a tagList of UI components

Examples

```
if (interactive()) {
  library(shiny)

  # two random variables
  x <- rnorm(30)
  y <- x + rnorm(30, sd = 0.5)

  # variables mapped to color, shape and size
  cc <- sample(letters[1:4], replace = TRUE, size = 30)
  shape <- sample(c("S1", "S2", "S3"), replace = TRUE, size = 30)
  sz <- sample(c(10, 20, 30, replace = TRUE, size = 30))

  ui <- fluidPage(
    plotly_scatter_ui("test_scatter")
  )

  server <- function(input, output, session) {
    v <- callModule(plotly_scatter_module, id = "test_scatter",
      # reactive_checkpoint = reactive(FALSE),
      reactive_param_plotly_scatter = reactive(list(
        x = x, y = y,
        color = cc,
        shape = shape,
        size = sz,
        tooltips = paste("A", 1:30)
      )))
    observe(print(v()))
  }
  shinyApp(ui, server)

  # example beeswarm horizontal
  x <- rnorm(30)
  y <- sample(c("x", "y", "z"), size = 30, replace = TRUE)
  shinyApp(ui, server)

  # example beeswarm vertical
  x <- sample(c("x", "y", "z"), size = 30, replace = TRUE)
  y <- rnorm(30)
  shinyApp(ui, server)
```

```

# return values
x <- c(5, 6, 3, 4, 1, 2)
y <- c(5, 6, 3, 4, 1, 2)
ui <- fluidPage(
  plotly_scatter_ui("test_scatter")
)
server <- function(input, output, session) {
  v <- callModule(plotly_scatter_module, id = "test_scatter",
                  reactive_param_plotly_scatter = reactive(list(
                    x = x, y = y, tooltips = paste("A", 1:6), highlight = 2:4
                  )))
  observe(print(v()))
}
shinyApp(ui, server)
}

```

plot_roc_pr_module *Shiny module for boxplot using plotly - Module*

Description

Shiny module for boxplot using plotly - Module

Usage

```

plot_roc_pr_module(
  input,
  output,
  session,
  reactive_param,
  reactive_checkpoint = reactive(TRUE)
)

```

Arguments

input	input
output	output
session	session
reactive_param	reactive value; argument pass to draw_roc_pr
reactive_checkpoint	reactive_value; check this value before render any plot/executing any calculation

Value

do not return any values

Examples

```
if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    sliderInput("ngrp", label = "Number of groups", min = 2, max = 5, value = 2),
    plot_roc_pr_ui("testplot")
  )

  server <- function(input, output, session) {
    ng <- reactive(
      sample(letters[1:input$ngrp], size = 100, replace = TRUE)
    )
    callModule(
      plot_roc_pr_module, id = "testplot",
      reactive_param = reactive(list(
        x = ng(),
        y = rnorm(100)
      )))
  }
  shinyApp(ui, server)
}
```

`prepOmicsViewer` *Prepare object to be viewed by omicsViewer*

Description

This is a convenience function to prepare the data to be visualized using `omicsViewer`. The result of PCA and t-test could be included directly.

Usage

```
prepOmicsViewer(
  expr,
  pData,
  fData,
  PCA = TRUE,
  ncomp = min(8, ncol(expr)),
  pca.fillNA = TRUE,
  t.test = NULL,
  ttest.fillNA = FALSE,
  ...,
  gs = NULL,
  stringDB = NULL,
  surv = NULL,
  SummarizedExperiment = TRUE
)
```

Arguments

expr	expression matrix where the rows are feature and columns are samples, matrix should be log10 transformed and have unique row and column names
pData	phenotype data
fData	feature data
PCA	pca
ncomp	number of components to keep
pca.fillNA	logical, whether the NA should be filled with a constant in PCA.
t.test	will be passed to the compare argument in multi.t.test
ttest.fillNA	logical, whether the NA should be filled with a constant in t-test.
...	arguments passed to t.test , such as paired.
gs	gene-set data, please refer to examples for more details about the format
stringDB	the IDs that can be used in the STRING database (https://string-db.org/) query.
surv	survival data, please refer to examples for more details about the format
SummarizedExperiment	logical; whether to return an object of class SummarizedExperiment. If set to FALSE, the function will return an ExpressionSet object.

Value

an object of ExpressionSet or SummarizedExperiment that can be visualized using `omicsViewer`

Examples

```
packdir <- system.file("extdata", package = "omicsViewer")
# reading expression
expr <- read.delim(file.path(packdir, "expressionMatrix.tsv"), stringsAsFactors = FALSE)
colnames(expr) <- make.names(colnames(expr))
rownames(expr) <- make.names(rownames(expr))
# reading feature data
fd <- read.delim(file.path(packdir, "featureGeneral.tsv"), stringsAsFactors = FALSE)
# reading phenotype data
pd <- read.delim(file.path(packdir, "sampleGeneral.tsv"), stringsAsFactors = FALSE)

# reading other datasets
drugData <- read.delim(file.path(packdir, "sampleDrug.tsv"))
# survival data
# this data is from cell line, the survival data are fake data to
# show how to use the survival data in #' omicsViewer
surv <- read.delim(file.path(packdir, "sampleSurv.tsv"))
# gene set information
genesets <- read_gmt(file.path(packdir, "geneset.gmt"), data.frame = TRUE)
gsannot <- gsAnnotIdList(idList = rownames(fd), gsIdMap = genesets, data.frame = TRUE)

# Define t-test to be done, a matrix nx3
# every row define a t-test, the format
# [column header] [group 1 in the test] [group 2 in the test]
```

```

tests <- rbind(
  c("Origin", "RE", "ME"),
  c("Origin", "RE", "LE"),
  c('TP53.Status', "MT", "WT")
)
# prepare column for stringDB query
strid <- sapply(strsplit(fd$Protein.ID, ";|-"), "[", 1)
##-
d <- prepOmicsViewer(
  expr = expr, pData = pd, fData = fd,
  PCA = TRUE, pca.fillNA = TRUE,
  t.test = tests, ttest.fillNA = FALSE,
  gs = gsannot, stringDB = strid, surv = surv)
# feature space - default x axis
attr(d, "fx") <- "ttest|RE_vs_ME|mean.diff"
# feature space - default y axis
attr(d, "fy") <- "ttest|RE_vs_ME|log.fdr"
# sample space - default x axis
attr(d, "sx") <- "PCA|All|PC1"
# sample space - default y axis
attr(d, "sy") <- "PCA|All|PC2"
# Save object and view
# saveRDS(d, file = "dtest.RDS")
## to open the viewer
# omicsViewer("./")

```

`read.proteinGroups` *Reading proteinGroup table of MaxQuant output*

Description

A convenience function to read the proteinGroups table of MaxQuant output. The function organize the result into different tables, e.g. iBAQ.

Usage

```
read.proteinGroups(x, quant = c("LF", "TMT")[1])
```

Arguments

- | | |
|-------|---|
| x | the proteinGroup.txt file returned by MaxQuant search |
| quant | the quantification method, LF or TMT |

Value

a list of tables extracted from proteinGroups.txt file

`read.proteinGroups.lf` *Read protein groups output of maxquant output and split it to columns*

Description

Read protein groups output of maxquant output and split it to columns

Usage

```
read.proteinGroups.lf(file)
```

Arguments

file	Maxquant proteinGroup.txt file path
------	-------------------------------------

Value

a list of tables extracted from proteinGroups.txt file

`readESVObj`

Read the object of SummarizedExperiment or ExpressionSet to be visualized using omicsViewer

Description

This function accept a path to a sqlite database or RDS object. If an RDS file to be read, The function is similar to `readRDS`. It reads the object to R working environment and perform extra two things.
 1. If the loaded data an class of `SummarizedExperiment`, it will be converted to `ExpressionSet`;
 2. If the gene set annotation is in matrix format, the gene set annotation is converted to `data.frame` format.

Usage

```
readESVObj(x)
```

Arguments

x	the path of an object of <code>SummarizedExperiment</code> or <code>ExpressionSet</code> , passed to <code>readRDS</code>
---	---

Value

an object of class `ExpressionSet` or `SummarizedExperiment` to be visualized.

Examples

```
file <- system.file("extdata/demo.RDS", package = "omicsViewer")
obj <- readESVObj(file)
```

read_gmt

Reading gene set .gmt file

Description

Frequently the .gmt files are downloaded from MSigDB database

Usage

```
read_gmt(x, id = NA, data.frame = FALSE)
```

Arguments

- | | |
|------------|--|
| x | the name/path of the gmt file to be read |
| id | the id used in gene sets, if is not NA, it should be either "SYMBOL" or "ENTREZ". Usually only used when reading the .gmt file downloaded from MSigDB. |
| data.frame | logical; whether to organize the data in data.frame format. Default is FALSE, a list will be returned. |

Value

a list or data frame of gene set. When data.frame = TRUE, the returned object is a data.frame with two columns: id and term.

Examples

```
file <- system.file("extdata", package = "omicsViewer")
file <- file.path(file, "geneset.gmt")
gs <- read_gmt(file)
```

`removeVarQC`*Removing variance of reference samples***Description**

This normalization removes the variance in reference samples. The method do not need to specific the batch assignment but cannot work with data contains less than five common reference samples. A typical use of this normalization is to correct some drifting effect in mass spec based label free proteomics or untargeted metabolomics experiment. Usually, this is a very strong normalization should only be used with good reasons.

Usage

```
removeVarQC(x, ref, positive = TRUE, ...)
```

Arguments

<code>x</code>	an expression matrix
<code>ref</code>	the index of reference samples
<code>positive</code>	logical; force only positive values in the resulted matrix
<code>...</code>	if given, <code>normalize.nQuantiles</code> will be called first, the arguments here will be passed to <code>normalize.nQuantiles</code>

Value

a normalized matrix

Examples

```
e1 <- matrix(rnorm(5000), 100, 50)+10
e2 <- removeVarQC(x = e1, ref = seq(5, 45, by = 10))
boxplot(e2)
```

`rowshift`*Row-wise normalization of expression matrix with or without reference sample***Description**

Row-wise normalization of expression matrix with or without reference sample

Usage

```
rowshift(x, batch, ref = NULL, useMean = FALSE)
```

Arguments

x	an expression matrix where rows are features, e.g. genes, proteins and columns are samples. The values in the matrix are usually log transformed.
batch	a factor or vector has the same length as ncol(x) to indicate the batch assignment of samples.
ref	a logical vector has the same length as ncol(x) to indicated which columns are the common references among batches. If it is NULL (by default), the mean of all channels will be used as batch reference. When NA present in the reference channels, the mean values will be used in correction.
useMean	logical; whether to use means of batches, usually set to TRUE when no reference available

Value

a matrix (hopefully without/with less batch effect)

Examples

```
e1 <- matrix(rnorm(5000), 500, 10)
e1[, 6:10] <- e1[, 6:10] + 3
boxplot(e1)
f <- rep(c("a", "b"), each = 5)
e2 <- rowshift(x = e1, batch = f)
boxplot(e2)
```

saveOmicsViewerDb

Save the xcmsViewer result object as sqlite database

Description

Save the xcmsViewer result object as sqlite database

Usage

```
saveOmicsViewerDb(obj, db.file, overwrite = TRUE)

## S4 method for signature 'SummarizedExperiment,character'
saveOmicsViewerDb(obj, db.file, overwrite = TRUE)

## S4 method for signature 'ExpressionSet,character'
saveOmicsViewerDb(obj, db.file, overwrite = TRUE)
```

Arguments

obj	an object of class ExpressionSet or SummarizedExperiment
db.file	a character indicate file name of the database file
overwrite	logical. whether the database should be overwritten if exist already.

Value

the directory where the database saved

Examples

```
f <- system.file("extdata", "demo.RDS", package = "omicsViewer")
es <- readRDS(f)
# The following line will write a database file on your disk
# saveOmicsViewerDb(es, db.file = "./omicsViewerData.db")
```

triselector_module *The three-step selector - the module function*

Description

The selector is used to select columns of phenotype and feature data. Function should only be used for the developers.

Usage

```
triselector_module(
  input,
  output,
  session,
  reactive_x,
  reactive_selector1 = reactive(NULL),
  reactive_selector2 = reactive(NULL),
  reactive_selector3 = reactive(NULL),
  label = "Group Label:"
)
```

Arguments

input	input
output	output
session	session
reactive_x	an nx3 matrix
reactive_selector1	default value for selector 1
reactive_selector2	default value for selector 2
reactive_selector3	default value for selector 3
label	of the triselector

Value

an reactive object containing the selected values

Examples

```
if (interactive()) {
  library(shiny)
  library(BioBase)

  file <- system.file("extdata/demo.RDS", package = "omicsViewer")
  dat <- readRDS(file)
  fData <- fData(dat)
  triiset <- stringr::str_split_fixed(colnames(fData), '\\|', n= 3)

  ui <- fluidPage(
    triselector_ui("tres"),
    triselector_ui("tres2")
  )
  server <- function(input, output, session) {
    v1 <- callModule(triselector_module, id = "tres", reactive_x = reactive(triset),
                     reactive_selector1 = reactive("ttest"),
                     reactive_selector2 = reactive("RE_vs_ME"),
                     reactive_selector3 = reactive("mean.diff"))
    v2 <- callModule(triselector_module, id = "tres2", reactive_x = reactive(triset),
                     reactive_selector1 = reactive("ttest"),
                     reactive_selector2 = reactive("RE_vs_ME"),
                     reactive_selector3 = reactive("log.fdr"))
    observe({
      print("/////////////////////////////")
      print(v1())
    })
  }
}

shinyApp(ui, server)
}
```

Description

Function should only be used for the developers

Usage

```
triselector_ui(id, right_margin = "20")
```

Arguments

id	id
right_margin	margin on the right side, in px. For example, "20" translates to "20px".

Value

a tagList of UI components

Examples

```
if (interactive()) {
  library(shiny)
  library(Biobase)

  file <- system.file("extdata/demo.RDS", package = "omicsViewer")
  dat <- readRDS(file)
  fData <- fData(dat)
  triset <- stringr::str_split_fixed(colnames(fData), '\\|', n= 3)

  ui <- fluidPage(
    trisector_ui("tres"),
    trisector_ui("tres2")
  )
  server <- function(input, output, session) {
    v1 <- callModule(trisector_module, id = "tres", reactive_x = reactive(triset),
                     reactive_selector1 = reactive("ttest"),
                     reactive_selector2 = reactive("RE_vs_ME"),
                     reactive_selector3 = reactive("mean.diff"))
    v2 <- callModule(trisector_module, id = "tres2", reactive_x = reactive(triset),
                     reactive_selector1 = reactive("ttest"),
                     reactive_selector2 = reactive("RE_vs_ME"),
                     reactive_selector3 = reactive("log.fdr"))
    observe({
      print("||||||||||||||||||||")
      print(v1())
    })
  }
}

shinyApp(ui, server)
}
```

trisetter

Create a nx3 matrix that can be used for trisector given a meta and expression table

Description

only used inside reactive

Usage

```
trisetter(meta, expr = NULL, combine)
```

Arguments

meta	a meta data, usually either phenotype data or feature data
expr	expression matrix, optional.
combine	how the meta and expression to be combined. Should be either "pheno" or "feature" or "none".

Value

a nx3 matrix
a `data.frame` with 3 columns

validMQFolder	<i>MQ folder validator Validate whether a folder is a MQ output folder</i>
---------------	--

Description

MQ folder validator Validate whether a folder is a MQ output folder

Usage

```
validMQFolder(dir)
```

Arguments

dir	the directory to check
-----	------------------------

Details

from the root level, these files exist: mqpar.xml [[combined/]txt/]proteinGroups.txt

Value

a list containing the info about MQ folder check

varSelector	<i>variable selector</i>
-------------	--------------------------

Description

variable selector

Usage

```
varSelector(x, expr, meta, alternative = NULL)
```

Arguments

x	variable return by triselector, a list of length three named as "analysis", "subset" and "variable"
expr	the expression matrix
meta	a meta matrix
alternative	alternative value to be returned when nothing to select

Value

the selected values in input argument x

Index

app_module, 3
app_ui, 5
asEsetWithAttr, 5

correlationAnalysis, 6
csc2list, 7

downloadUPRefProteome
 (getUPRefProteomeID), 14
draw_roc_pr, 7

exprspca, 8
extendMetaData, 9
extendMetaData, ExpressionSet, data.frame-method, 35
 (extendMetaData), 9
extendMetaData, SummarizedExperiment, data.frame-method, 34
 (extendMetaData), 9
extendMetaData, SummarizedExperiment, DFrame-method, 36
 (extendMetaData), 9

fgseal, 10
fillNA, 8, 11, 18
filterRow, 12

getAutoRIF, 12
getMQParams, 13
getUPRefProteomeID, 14
gsAnnotIdList, 14

hasAttr, 16
hclust2str, 16

list2csc, 17

multi.t.test, 17, 32

nColors, 19
normalize.nQuantiles, 19, 21, 36
normalize.totsum, 20
normalizeColWise, 21, 22
normalizeData, 22

omicsViewer, 23, 31

parseDatTerm, 24
plot_roc_pr_module, 30
plotly_boxplot_module, 24
plotly_boxplot_ui, 25
plotly_scatter_module, 26
plotly_scatter_ui, 28
prcomp, 8
prepOmicsViewer, 31

read.proteinGroups, 33
read.proteinGroups.lf, 34

readESVObj, 34

removeVarQC, 22, 36

removeVarQC, 22, 36

saveOmicsViewerDb, 37
saveOmicsViewerDb, ExpressionSet, character-method
 (saveOmicsViewerDb), 37
saveOmicsViewerDb, SummarizedExperiment, character-method
 (saveOmicsViewerDb), 37
str2hclust (hclust2str), 16

t.test, 17, 18, 32
triselector_module, 38
triselector_ui, 39
trisetter, 40

validMQFolder, 41
varSelector, 42