

Package ‘DOSE’

October 16, 2024

Type Package

Title Disease Ontology Semantic and Enrichment analysis

Version 3.30.5

Maintainer Guangchuang Yu <guangchuangyu@gmail.com>

Description This package implements five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively for measuring semantic similarities among DO terms and gene products. Enrichment analyses including hypergeometric model and gene set enrichment analysis are also implemented for discovering disease associations of high-throughput biological data.

Depends R (>= 3.5.0)

Imports AnnotationDbi, BiocParallel, fgsea, ggplot2, GOSemSim (>= 2.30.2), methods, qvalue, reshape2, stats, utils

Suggests prettydoc, clusterProfiler, gson (>= 0.0.5), knitr, rmarkdown, org.Hs.eg.db, testthat, yulab.utils

VignetteBuilder knitr

ByteCompile true

License Artistic-2.0

Encoding UTF-8

URL <https://yulab-smu.top/biomedical-knowledge-mining-book/>

BugReports <https://github.com/GuangchuangYu/DOSE/issues>

biocViews Annotation, Visualization, MultipleComparison, GeneSetEnrichment, Pathways, Software

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/DOSE>

git_branch RELEASE_3_19

git_last_commit f2882c1

git_last_commit_date 2024-08-26

Repository Bioconductor 3.19

Date/Publication 2024-10-16

Author Guangchuang Yu [aut, cre],
 Li-Gen Wang [ctb],
 Vladislav Petyuk [ctb],
 Giovanni Dall'Olio [ctb]

Contents

DOSE-package	3
clusterSim	3
compareClusterResult-class	4
computeIC	5
DataSet	6
doseSim	6
doSim	7
enrichDGN	7
enrichDGNv	8
enrichDO	10
enricher_internal	11
enrichNCG	12
enrichResult-class	13
EXTID2NAME	14
gene2DO	14
geneID	15
geneInCategory	15
geneSim	16
gseaResult-class	17
GSEA_internal	18
gseDGN	19
gseDO	20
gseNCG	21
gsfilter	22
hpoSim	22
mclusterSim	23
mpoSim	24
parse_ratio	25
reexports	25
setReadable	26
show	26
simplot	27
summary	28
theme_dose	28

DOSE-package

DOSE: Disease Ontology Semantic and Enrichment analysis

Description

This package implements five methods proposed by Resnik, Schlicker, Jiang, Lin and Wang respectively for measuring semantic similarities among DO terms and gene products. Enrichment analyses including hypergeometric model and gene set enrichment analysis are also implemented for discovering disease associations of high-throughput biological data.

Author(s)

Maintainer: Guangchuang Yu <guangchuangyu@gmail.com>

Other contributors:

- Li-Gen Wang <reeganwang020@gmail.com> [contributor]
- Vladislav Petyuk <petyuk@gmail.com> [contributor]
- Giovanni Dall’Olio <giovanni.dallolio@upf.edu> [contributor]

See Also

Useful links:

- <https://yulab-smu.top/biomedical-knowledge-mining-book/>
- Report bugs at <https://github.com/GuangchuangYu/DOSE/issues>

clusterSim

clusterSim

Description

semantic similarity between two gene clusters

Usage

```
clusterSim(  
  cluster1,  
  cluster2,  
  ont = "HDO",  
  organism = "hsa",  
  measure = "Wang",  
  combine = "BMA"  
)
```

Arguments

cluster1	a vector of gene IDs
cluster2	another vector of gene IDs
ont	one of "HDO", "HPO" and "MPO"
organism	organism
measure	One of "Resnik", "Lin", "Rel", "Jiang" and "Wang" methods.
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining

Details

given two gene clusters, this function calculates semantic similarity between them.

Value

similarity

Author(s)

Yu Guangchuang

Examples

```
## Not run:
cluster1 <- c("835", "5261", "241", "994")
cluster2 <- c("307", "308", "317", "321", "506", "540", "378", "388", "396")
clusterSim(cluster1, cluster2)

## End(Not run)
```

compareClusterResult-class

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Description

Class "compareClusterResult" This class represents the comparison result of gene clusters by GO categories at specific level or GO enrichment analysis.

Slots

compareClusterResult cluster comparing result
geneClusters a list of genes
fun one of groupGO, enrichGO and enrichKEGG
gene2Symbol gene ID to Symbol
keytype Gene ID type
readable logical flag of gene ID in symbol or not.
.call function call
termsim Similarity between term
method method of calculating the similarity between nodes
dr dimension reduction result

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[enrichResult](#)

computeIC

compute information content

Description

compute information content

Usage

computeIC(ont = "HDO")

Arguments

ont one of "DO", "HPO" and "MPO"

Author(s)

Guangchuang Yu <https://yulab-smu.top>

DataSet	<i>Datasets</i>
---------	-----------------

Description

Information content and DO term to entrez gene IDs mapping

doseSim	<i>doSim</i>
---------	--------------

Description

measuring similarities between two DO term vectors.

Usage

```
doseSim(DOID1, DOID2, measure = "Wang", ont = "HDO")
```

Arguments

DOID1	DO term, MPO term or HPO term vector
DOID2	DO term, MPO term or HPO term vector
measure	one of "Wang", "Resnik", "Rel", "Jiang", "Lin", and "TCSS".
ont	one of "HDO", "HPO" and "MPO"

Details

provide two term vectors, this function will calculate their similarities.

Value

score matrix

`doSim`*doSim*

Description

measuring similarities between two MPO term vectors.

Usage

```
doSim(DOID1, DOID2, measure = "Wang")
```

Arguments

DOID1	DO term vector
DOID2	DO term vector
measure	one of "Wang", "Resnik", "Rel", "Jiang", "Lin", and "TCSS".

Details

provide two DO term vectors, this function will calculate their similarities.

Value

score matrix

Author(s)

Guangchuang Yu <https://yulab-smu.top>

`enrichDGN`

*Enrichment analysis based on the DisGeNET ([http://www.
disgenet.org/](http://www.disgenet.org/))*

Description

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Usage

```
enrichDGN(
  gene,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  readable = FALSE
)
```

Arguments

gene	a vector of entrez gene id
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

References

Janet et al. (2015) DisGeNET: a discovery platform for the dynamical exploration of human diseases and their genes. *Database* bav028 <http://database.oxfordjournals.org/content/2015/bav028.long>

Description

Enrichment analysis based on the DisGeNET (<http://www.disgenet.org/>)

Usage

```
enrichDGNv(
  snp,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  readable = FALSE
)
```

Arguments

snp	a vector of SNP
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Details

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

References

Janet et al. (2015) DisGeNET: a discovery platform for the dynamical exploration of human diseases and their genes. *Database* bav028 <http://database.oxfordjournals.org/content/2015/bav028.long>

enrichDO*DO Enrichment Analysis*

Description

Given a vector of genes, this function will return the enrichment DO categories with FDR control.

Usage

```
enrichDO(
  gene,
  ont = "HDO",
  organism = "hsa",
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  readable = FALSE
)
```

Arguments

gene	a vector of entrez gene id
ont	one of "HDO", "HPO" or "MPO".
organism	one of "hsa" and "mm"
pvalueCutoff	pvalue cutoff
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes
minGSSize	minimal size of genes annotated by NCG category for testing
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	qvalue cutoff
readable	whether mapping gene ID to gene Name

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[enrichResult-class](#)

Examples

```
data(geneList)
gene = names(geneList)[geneList > 1]
yy = enrichDO(gene, pvalueCutoff=0.05)
summary(yy)
```

enricher_internal *enrich.internal*

Description

internal method for enrichment analysis

Usage

```
enricher_internal(
  gene,
  pvalueCutoff,
  pAdjustMethod = "BH",
  universe = NULL,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  USER_DATA
)
```

Arguments

gene	a vector of entrez gene id.
pvalueCutoff	Cutoff value of pvalue.
pAdjustMethod	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
universe	background genes, default is the intersection of the 'universe' with genes that have annotations. Users can set 'options(enrichment_force_universe = TRUE)' to force the 'universe' untouched.
minGSSize	minimal size of genes annotated by Ontology term for testing.
maxGSSize	maximal size of each geneSet for analyzing
qvalueCutoff	cutoff of qvalue
USER_DATA	ontology information

Details

using the hypergeometric model

Value

A `enrichResult` instance.

Author(s)

Guangchuang Yu <https://yulab-smu.top>

`enrichNCG`

enrichNCG

Description

Enrichment analysis based on the Network of Cancer Genes database (<http://ncg.kcl.ac.uk/>)

Usage

```
enrichNCG(
  gene,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  universe,
  minGSSize = 10,
  maxGSSize = 500,
  qvalueCutoff = 0.2,
  readable = FALSE
)
```

Arguments

<code>gene</code>	a vector of entrez gene id
<code>pvalueCutoff</code>	pvalue cutoff
<code>pAdjustMethod</code>	one of "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
<code>universe</code>	background genes
<code>minGSSize</code>	minimal size of genes annotated by NCG category for testing
<code>maxGSSize</code>	maximal size of each geneSet for analyzing
<code>qvalueCutoff</code>	qvalue cutoff
<code>readable</code>	whether mapping gene ID to gene Name

Details

given a vector of genes, this function will return the enrichment NCG categories with FDR control

Value

A `enrichResult` instance

Author(s)

Guangchuang Yu

enrichResult-class	<i>Class "enrichResult" This class represents the result of enrichment analysis.</i>
--------------------	--

Description

Class "enrichResult" This class represents the result of enrichment analysis.

Slots

result enrichment analysis
pvalueCutoff pvalueCutoff
pAdjustMethod pvalue adjust method
qvalueCutoff qvalueCutoff
organism only "human" supported
ontology biological ontology
gene Gene IDs
keytype Gene ID type
universe background gene
gene2Symbol mapping gene to Symbol
geneSets gene sets
readable logical flag of gene ID in symbol or not.
termsim Similarity between term
method method of calculating the similarity between nodes
dr dimension reduction result

Author(s)

Guangchuang Yu <https://yulab-smu.top>

See Also

[enrichDO](#)

EXTID2NAME

*EXTID2NAME***Description**

mapping gene ID to gene Symbol

Usage

EXTID2NAME(OrgDb, geneID, keytype)

Arguments

OrgDb	OrgDb
geneID	entrez gene ID
keytype	keytype

Value

gene symbol

Author(s)Guangchuang Yu <https://yulab-smu.top>

gene2DO

*convert Gene ID to DO Terms***Description**

provide gene ID, this function will convert to the corresponding DO Terms

Usage

gene2DO(gene, organism = "hsa", ont = "HDO")

Arguments

gene	entrez gene ID
organism	organism
ont	ont

Value

DO Terms

Author(s)

Guangchuang Yu <https://yulab-smu.top>

geneID

geneID generic

Description

geneID generic

Usage

geneID(x)

Arguments

x enrichResult object

Value

'geneID' return the 'geneID' column of the enriched result which can be converted to data.frame via 'as.data.frame'

Examples

```
data(geneList, package="DOSE")
de <- names(geneList)[1:100]
x <- enrichDO(de)
geneID(x)
```

geneInCategory

geneInCategory generic

Description

geneInCategory generic

Usage

geneInCategory(x)

Arguments

x enrichResult

Value

'geneInCategory' return a list of genes, by splitting the input gene vector to enriched functional categories

Examples

```
data(geneList, package="DOSE")
de <- names(geneList)[1:100]
x <- enrichDO(de)
geneInCategory(x)
```

geneSim

*geneSim***Description**

measuring similarities bewteen two gene vectors.

Usage

```
geneSim(
  geneID1,
  geneID2 = NULL,
  ont = "HDO",
  organism = "hsa",
  measure = "Wang",
  combine = "BMA"
)
```

Arguments

geneID1	entrez gene vector
geneID2	entrez gene vector
ont	one of "HDO" and "MPO"
organism	organism
measure	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple DO terms associated with gene/protein.

Details

provide two entrez gene vectors, this function will calculate their similarity.

Value

score matrix

Author(s)

Guangchuang Yu <https://yulab-smu.top>

Examples

```
g <- c("835", "5261", "241", "994")
geneSim(g)
```

gseaResult-class

Class "gseaResult" This class represents the result of GSEA analysis

Description

Class "gseaResult" This class represents the result of GSEA analysis

Slots

```
result GSEA analysis
organism organism
setType setType
geneSets geneSets
geneList order rank geneList
keytype ID type of gene
permScores permutation scores
params parameters
gene2Symbol gene ID to Symbol
readable whether convert gene ID to symbol
dr dimension reduction result
```

Author(s)

Guangchuang Yu <https://yulab-smu.top>

GSEA_internal	<i>GSEA_internal</i>
---------------	----------------------

Description

generic function for gene set enrichment analysis

Usage

```
GSEA_internal(
  geneList,
  exponent,
  minGSSize,
  maxGSSize,
  eps,
  pvalueCutoff,
  pAdjustMethod,
  verbose,
  seed = FALSE,
  USER_DATA,
  by = "fgsea",
  ...
)
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
eps	This parameter sets the boundary for calculating the p value.
pvalueCutoff	p value Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	set seed inside the function to make result reproducible. FALSE by default.
USER_DATA	annotation data
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

Description

perform gsea analysis

Usage

```
gseDGN(  
    geneList,  
    exponent = 1,  
    minGSSize = 10,  
    maxGSSize = 500,  
    pvalueCutoff = 0.05,  
    pAdjustMethod = "BH",  
    verbose = TRUE,  
    seed = FALSE,  
    by = "fgsea",  
    ...  
)
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gseDODO Gene Set Enrichment Analysis

Description

perform gsea analysis

Usage

```
gseDO(
  geneList,
  ont = "HDO",
  organism = "hsa",
  exponent = 1,
  minGSSize = 10,
  maxGSSize = 500,
  pvalueCutoff = 0.05,
  pAdjustMethod = "BH",
  verbose = TRUE,
  seed = FALSE,
  by = "fgsea",
  ...
)
```

Arguments

geneList	order ranked geneList
ont	one of "HDO", "HPO" or "MPO"
organism	one of "hsa" and "mm"
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

Description

perform gsea analysis

Usage

```
gseNCG(  
  geneList,  
  exponent = 1,  
  minGSSize = 10,  
  maxGSSize = 500,  
  pvalueCutoff = 0.05,  
  pAdjustMethod = "BH",  
  verbose = TRUE,  
  seed = FALSE,  
  by = "fgsea",  
  ...  
)
```

Arguments

geneList	order ranked geneList
exponent	weight of each step
minGSSize	minimal size of each geneSet for analyzing
maxGSSize	maximal size of each geneSet for analyzing
pvalueCutoff	pvalue Cutoff
pAdjustMethod	p value adjustment method
verbose	print message or not
seed	logical
by	one of 'fgsea' or 'DOSE'
...	other parameter

Value

gseaResult object

Author(s)

Yu Guangchuang

gsfilter*gsfilter***Description**

filter enriched result by gene set size or gene count

Usage

```
gsfilter(x, by = "GSSize", min = NA, max = NA)
```

Arguments

<code>x</code>	instance of enrichResult or compareClusterResult
<code>by</code>	one of 'GSSize' or 'Count'
<code>min</code>	minimal size
<code>max</code>	maximal size

Value

update object

Author(s)

Guangchuang Yu

hpoSim*doSim***Description**

measuring similarities between two MPO term vectors.

Usage

```
hpoSim(DOID1, DOID2, measure = "Wang")
```

Arguments

<code>DOID1</code>	HPO term vector
<code>DOID2</code>	HPO term vector
<code>measure</code>	one of "Wang", "Resnik", "Rel", "Jiang", "Lin", and "TCSS".

Details

provide two HPO term vectors, this function will calculate their similarities.

Value

score matrix

mclusterSim***mclusterSim***

Description

Pairwise semantic similarity for a list of gene clusters

Usage

```
mclusterSim(  
  clusters,  
  ont = "HDO",  
  organism = "hsa",  
  measure = "Wang",  
  combine = "BMA"  
)
```

Arguments

clusters	A list of gene clusters
ont	one of "HDO", "HPO" and "MPO"
organism	organism
measure	one of "Wang", "Resnik", "Rel", "Jiang", and "Lin".
combine	One of "max", "avg", "rcmax", "BMA" methods, for combining semantic similarity scores of multiple DO terms associated with gene/protein.

Value

similarity matrix

Author(s)

Guangchuang Yu

Examples

```
## Not run:
cluster1 <- c("835", "5261", "241")
cluster2 <- c("578", "582")
cluster3 <- c("307", "308", "317")
clusters <- list(a=cluster1, b=cluster2, c=cluster3)
mclusterSim(clusters, measure="Wang")

## End(Not run)
```

mpoSim

doSim

Description

measuring similarities between two MPO term vectors.

Usage

```
mpoSim(DOID1, DOID2, measure = "Wang")
```

Arguments

DOID1	MPO term vector
DOID2	MPO term vector
measure	one of "Wang", "Resnik", "Rel", "Jiang", "Lin", and "TCSS".

Details

provide two MPO term vectors, this function will calculate their similarities.

Value

score matrix

<code>parse_ratio</code>	<i>parse_ratio</i>
--------------------------	--------------------

Description

parse character ratio to double value, such as 1/5 to 0.2

Usage

```
parse_ratio(ratio)
```

Arguments

<code>ratio</code>	character vector of ratio to parse
--------------------	------------------------------------

Value

A numeric vector (double) of parsed ratio

Author(s)

Guangchuang Yu

<code>reexports</code>	<i>Objects exported from other packages</i>
------------------------	---

Description

These objects are imported from other packages. Follow the links below to see their documentation.

[ggplot2](#) [facet_grid](#)

<code>setReadable</code>	<i>setReadable</i>
--------------------------	--------------------

Description

mapping geneID to gene Symbol

Usage

```
setReadable(x, OrgDb, keyType = "auto")
```

Arguments

<code>x</code>	enrichResult Object
<code>OrgDb</code>	OrgDb
<code>keyType</code>	keyType of gene

Value

enrichResult Object

Author(s)

Yu Guangchuang

<code>show</code>	<i>show method</i>
-------------------	--------------------

Description

show method for gseaResult instance
show method for enrichResult instance

Usage

```
show(object)
```

```
show(object)
```

Arguments

<code>object</code>	A enrichResult instance.
---------------------	--------------------------

Value

```
message  
message
```

Author(s)

Guangchuang Yu <https://yulab-smu.top>

```
simplot          simplot
```

Description

plotting similarity matrix

Usage

```
simplot(  
  sim,  
  xlab = "",  
  ylab = "",  
  color.low = "white",  
  color.high = "red",  
  labs = TRUE,  
  digits = 2,  
  labs.size = 3,  
  font.size = 14  
)
```

Arguments

sim	similarity matrix
xlab	xlab
ylab	ylab
color.low	color of low value
color.high	color of high value
labs	logical, add text label or not
digits	round digit numbers
labs.size	label size
font.size	font size

Value

ggplot object

Author(s)

Yu Guangchuang

summary

summary method

Description

summary method for gseaResult instance

summary method for enrichResult instance

Usage

summary(object, ...)

summary(object, ...)

Arguments

object A enrichResult instance.

... additional parameter

Value

A data frame

A data frame

Author(s)

Guangchuang Yu <https://guangchuangyu.github.io>

Guangchuang Yu <http://guangchuangyu.github.io>

theme_dose

theme_dose

Description

ggplot theme of DOSE

Usage

theme_dose(font.size = 14)

Arguments

font.size font size

Value

ggplot theme

Examples

```
library(ggplot2)
qplot(1:10) + theme_dose()
```

Index

* **classes**
 compareClusterResult-class, 4
 enrichResult-class, 13
 gseaResult-class, 17

* **datasets**
 DataSet, 6

* **internal**
 DOSE-package, 3
 reexports, 25

* **manip**
 enrichD0, 10
 enricher_internal, 11
 gseDGN, 19
 gseD0, 20
 gseNCG, 21

clusterSim, 3
compareClusterResult-class, 4
computeIC, 5

DataSet, 6
DGN_EXTID2PATHID (DataSet), 6
DGN_PATHID2EXTID (DataSet), 6
DGN_PATHID2NAME (DataSet), 6
DO2ALLEG (DataSet), 6
DO2EG (DataSet), 6
DOIC (DataSet), 6
DOLite2EG (DataSet), 6
DOLiteTerm (DataSet), 6
DOSE (DOSE-package), 3
DOSE-package, 3
doseSim, 6
doSim, 7
dotbl (DataSet), 6

EG2ALLD0 (DataSet), 6
EG2D0 (DataSet), 6
EG2DOLite (DataSet), 6
enrichDGN, 7
enrichDGNv, 8

enrichD0, 10, 13
enricher_internal, 11
enrichNCG, 12
enrichResult, 5
enrichResult-class, 13
EXTID2NAME, 14

facet_grid, 25
facet_grid(reexports), 25

gene2D0, 14
geneID, 15
geneInCategory, 15
geneList (DataSet), 6
geneSim, 16
GSEA_internal, 18
gseahResult-class (gseaResult-class), 17
gseaResult-class, 17
gseDGN, 19
gseD0, 20
gseNCG, 21
gsfilter, 22

hpoSim, 22
hpotbl (DataSet), 6

mclusterSim, 23
mpoSim, 24
mpotbl (DataSet), 6

NCG_EXTID2PATHID (DataSet), 6
NCG_PATHID2EXTID (DataSet), 6
NCG_PATHID2NAME (DataSet), 6

parse_ratio, 25
plot, compareClusterResult-method
 (compareClusterResult-class), 4

reexports, 25

setReadable, 26

show, [26](#)
show, compareClusterResult-method
 ([compareClusterResult-class](#)), [4](#)
show, enrichResult-method
 ([enrichResult-class](#)), [13](#)
show, gseaResult-method
 ([gseaResult-class](#)), [17](#)
simplot, [27](#)
summary, [28](#)
summary, compareClusterResult-method
 ([compareClusterResult-class](#)), [4](#)
summary, enrichResult-method
 ([enrichResult-class](#)), [13](#)
summary, gseaResult-method
 ([gseaResult-class](#)), [17](#)

theme_dose, [28](#)

VDGN_EXTID2PATHID (DataSet), [6](#)
VDGN_PATHID2EXTID (DataSet), [6](#)
VDGN_PATHID2NAME (DataSet), [6](#)