

# Package ‘Rhdf5lib’

October 17, 2024

**Type** Package

**Title** hdf5 library as an R package

**Version** 1.26.0

**Description** Provides C and C++ hdf5 libraries.

**License** Artistic-2.0

**Copyright** src/hdf5/COPYING

**LazyLoad** true

**VignetteBuilder** knitr

**Depends** R (>= 4.2.0)

**Suggests** BiocStyle, knitr, rmarkdown, tinytest, mockery

**URL** <https://github.com/grimbough/Rhdf5lib>

**BugReports** <https://github.com/grimbough/Rhdf5lib>

**SystemRequirements** GNU make

**Encoding** UTF-8

**biocViews** Infrastructure

**RoxygenNote** 7.1.2

**git\_url** <https://git.bioconductor.org/packages/Rhdf5lib>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 9755392

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-10-16

**Author** Mike Smith [ctb, cre] (<<https://orcid.org/0000-0002-7800-3848>>),  
The HDF Group [cph]

**Maintainer** Mike Smith <grimbough@gmail.com>

## Contents

<code>.getDynamicLinks</code> . . . . .	2
<code>.getSzipLoc</code> . . . . .	2
<code>getHdf5Version</code> . . . . .	3
<code>pkgconfig</code> . . . . .	3
<code>Rhdf5lib</code> . . . . .	4

## Index

5

<code>.getDynamicLinks</code>	<i>Return the link flags determined when HDF5 was configured</i>
-------------------------------	--

### Description

Return the link flags determined when HDF5 was configured

### Usage

```
.getDynamicLinks()
```

<code>.getSzipLoc</code>	
--------------------------	--

*If we compiled our own version of SZIP this returns the link path Otherwise it returns an empty string.*

### Description

If we compiled our own version of SZIP this returns the link path Otherwise it returns an empty string.

### Usage

```
.getSzipLoc(path)
```

---

`getHdf5Version`

*Report the version of HDF5 distributed with this package*

---

## Description

This function returns the version number of the HDF5 library that is distributed with this package.

## Usage

```
getHdf5Version()
```

## Value

Returns a character vector of length 1 containing the version number.

## Examples

```
getHdf5Version()
```

---

`pkgconfig`

*Compiler arguments for using Rhdf5lib*

---

## Description

This function returns values for PKG\_LIBS variables for use in Makevars files.

## Usage

```
pkgconfig(  
  opt = c("PKG_CXX_LIBS", "PKG_C_LIBS", "PKG_CXX_HL_LIBS", "PKG_C_HL_LIBS")  
)
```

## Arguments

`opt` A scalar character from the list of available options; default is PKG\_CXX\_LIBS.  
Valid options are PKG\_C\_LIBS, PKG\_CXX\_LIBS, PKG\_C\_HL\_LIBS and PKG\_CXX\_HL\_LIBS,  
where HL indicates that you want to include the HDF5 'high-level' API and CXX  
denotes including the C++ interface.

## Value

NULL; prints the corresponding value to stdout.

## Examples

```
pkgconfig("PKG_C_LIBS")
pkgconfig("PKG_CXX_LIBS")
pkgconfig("PKG_C_HL_LIBS")
pkgconfig("PKG_CXX_HL_LIBS")
```

---

Rhdf5lib

*Rhdf5lib: A version of the HDF5 library built into an R package.*

---

## Description

This package provides a compiled version of the HDF5 library bundled within the R package structure. It is primarily useful to developers of other R packages who want to make use of the capabilities of the HDF5 library directly in the C or C++ code of their own packages, rather than using a higher level interface.

# Index

\* **internal**  
  · [getDynamicLinks, 2](#)  
  · [getSzipLoc, 2](#)  
· [getDynamicLinks, 2](#)  
· [getSzipLoc, 2](#)  
  
[getHdf5Version, 3](#)  
  
[pkgconfig, 3](#)  
  
[Rhdf5lib, 4](#)