

Package ‘VCFArray’

October 17, 2024

Title Representing on-disk / remote VCF files as array-like objects

Version 1.20.0

Description VCFArray extends the DelayedArray to represent VCF data entries as array-like objects with on-disk / remote VCF file as backend. Data entries from VCF files, including info fields, FORMAT fields, and the fixed columns (REF, ALT, QUAL, FILTER) could be converted into VCFArray instances with different dimensions.

biocViews Infrastructure, DataRepresentation, Sequencing,
VariantAnnotation

Depends R (>= 3.6), methods, BiocGenerics, DelayedArray (>= 0.7.28)

License GPL-3

Encoding UTF-8

URL <https://github.com/Liubuntu/VCFArray>

BugReports <https://github.com/Liubuntu/VCFArray/issues>

Imports tools, GenomicRanges, VariantAnnotation (>= 1.29.3),
GenomicFiles (>= 1.17.3), S4Vectors (>= 0.19.19), Rsamtools

RoxygenNote 6.1.1

VignetteBuilder knitr

Suggests SeqArray, BiocStyle, BiocManager, testthat, knitr, rmarkdown

git_url <https://git.bioconductor.org/packages/VCFArray>

git_branch RELEASE_3_19

git_last_commit a0e0abb

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-10-16

Author Qian Liu [aut, cre],
Martin Morgan [aut]

Maintainer Qian Liu <qliu7@buffalo.edu>

Contents

<i>dim, VCFArraySeed-method</i>	2
<i>extract_array</i>	3
Index	5

dim, VCFArraySeed-method

VCFArraySeed or VCFArray related methods, slot getters and setters.

Description

- dim, dimnames: dimension and dimnames of object contained in the VCF file.
- vcffile: extract the VcfFile object corresponding to the backend VCF file.
- rowRanges: extract the rowRanges information from the backend VCF file.

Usage

```
## S4 method for signature 'VCFArraySeed'
dim(x)

## S4 method for signature 'VCFArraySeed'
dimnames(x)

vcffile(x)

## S4 method for signature 'VCFArraySeed'
vcffile(x)

## S4 method for signature 'VCFArraySeed'
rowRanges(x)

## S4 method for signature 'VCFArraySeed'
show(object)

## S4 method for signature 'VCFArray'
vcffile(x)

## S4 method for signature 'VCFArray'
rowRanges(x)
```

Arguments

- x the VCFArray or VCFArraySeed objects.
- object the VCFArraySeed object.

Value

dim: the integer vector of dimensions for VCFArray or VCFArraySeed objects.
 dimnames: the unnamed list of dimension names for VCFArray and VCFArraySeed objects.
 vcffile: the VcfFile object corresponding to the backend VCF file.

Examples

```
f1 <- system.file("extdata", "chr22.vcf.gz",
                  package="VariantAnnotation")
va <- VCFArray(f1, name = "GT")
dim(va)
dimnames(va)
vcffile(va)
seed(va)
dim(seed(va))
DelayedArray::type(va)
```

extract_array

*VCFArray constructor and coercion methods.***Description**

`extract_array`: the function to extract data from a VCF file, by taking VCFArraySeed as input. This function is required by the DelayedArray for the seed contract.
`VCFArray`: The function to convert data entries inside VCF file into the VCFArray instance.

Usage

```
## S4 method for signature 'VCFArraySeed'
extract_array(x, index)

VCFArray(file, vindex = character(), name = NA, pfix = NULL)
```

Arguments

<code>x</code>	the VCFArraySeed object
<code>index</code>	in <code>extract_array()</code> , an unnamed list of subscripts as positive integer vectors, one vector per dimension in <code>x</code> . Empty and missing subscripts (represented by <code>integer(0)</code> and <code>NULL</code> list elements, respectively) are allowed. The subscripts can contain duplicated indices. They cannot contain NAs or non-positive values.
<code>file</code>	takes values for character string (specifying the VCF file path), VcfFile object, and RangedVcfStack object.
<code>vindex</code>	in <code>VCFArray()</code> , the character string specifying the index file path. This argument is required if a remote VCF file is used for the <code>file</code> argument.
<code>name</code>	the data entry from VCF file to be read into VCFArraySeed / VCFArray. For VCFArray. This argument should always be specified.

pfix the category that the name belongs to. Available values are `fixed`, `info`, and `info`. Can also Check `vcfFields(file)` for matching name and pfix.

Value

`VCFArray` class object.

Examples

```
f1 <- system.file("extdata", "chr22.vcf.gz",
                  package="VariantAnnotation")
va <- VCFArray(f1, name = "GT")
va
vcf <- VariantAnnotation::VcfFile(f1)
va1 <- VCFArray(vcf, name = "GT")
va1
all.equal(va, va1)
## Not run:
## RangedVcfStack class
extdata <- system.file(package = "GenomicFiles", "extdata")
files <- dir(extdata, pattern="^CEUtrio.*bgz$", full=TRUE)[1:2]
names(files) <- sub(".*_([0-9XY]+).*", "\\\\"1", basename(files))
seqinfo <- as(readRDS(file.path(extdata, "seqinfo.rds")), "Seqinfo")
stack <- GenomicFiles::VcfStack(files, seqinfo)
gr <- as(GenomicFiles::seqinfo(stack)[rownames(stack)], "GRanges")
## RangedVcfStack
rgstack <- GenomicFiles::RangedVcfStack(stack, rowRanges = gr)
rgstack
va2 <- VCFArray(rgstack, name = "SB")
va2

## End(Not run)
## coercion
as(va[1:10, ], "array")
```

Index

coerce(extract_array), 3
coerce, ANY, VCFMatrix-method
 (extract_array), 3
coerce, VCFArray, VCFMatrix-method
 (extract_array), 3
coerce, VCFMatrix, VCFArray-method
 (extract_array), 3

dim, VCFArraySeed-method, 2
dimnames, VCFArraySeed-method
 (dim, VCFArraySeed-method), 2

extract_array, 3
extract_array, VCFArraySeed-method
 (extract_array), 3

matrixClass, VCFArray-method
 (extract_array), 3

rowRanges, VCFArray-method
 (dim, VCFArraySeed-method), 2
rowRanges, VCFArraySeed-method
 (dim, VCFArraySeed-method), 2

show, VCFArraySeed-method
 (dim, VCFArraySeed-method), 2

VCFArray(extract_array), 3
VCFArray-class(extract_array), 3
VCFArray-method(extract_array), 3
vcffile(dim, VCFArraySeed-method), 2
vcffile, VCFArray
 (dim, VCFArraySeed-method), 2
vcffile, VCFArray-method
 (dim, VCFArraySeed-method), 2
vcffile, VCFArraySeed
 (dim, VCFArraySeed-method), 2
vcffile, VCFArraySeed-method
 (dim, VCFArraySeed-method), 2
VCFMatrix(extract_array), 3
VCFMatrix-class(extract_array), 3