

immunoClust - Automated Pipeline for Population Detection in Flow Cytometry

*Till Sørensen*¹

¹till-
antonи.soerensen@charite.de

May 1, 2024

Contents

1	Licensing	2
2	Overview	2
3	Getting started	2
4	Example Illustrating the immunoClust Pipeline	2
4.1	Cell Event Clustering	3
4.2	Meta Clustering	6
4.3	Meta Annotation	7
5	Session Info	10

1 Licensing

Under the Artistic License, you are free to use and redistribute this software. However, we ask you to cite the following paper if you use this software for publication.

Sørensen, T., Baumgart, S., Durek, P., Grützkau, A. and Häupl, T.
immunoClust - an automated analysis pipeline for the identification of
immunophenotypic signatures in high-dimensional cytometric datasets.
Cytometry A (accepted).

2 Overview

immunoClust presents an automated analysis pipeline for uncompensated fluorescence and mass cytometry data and consists of two parts. First, cell events of each sample are grouped into individual clusters (cell-clustering). Subsequently, a classification algorithm assorts these cell event clusters into populations comparable between different samples (meta-clustering). The clustering of cell events is designed for datasets with large event counts in high dimensions as a global unsupervised method, sensitive to identify rare cell types even when next to large populations. Both parts use model-based clustering with an iterative Expectation Maximization (EM) algorithm and the Integrated Classification Likelihood (ICL) to obtain the clusters.

The cell-clustering process fits a mixture model with t -distributions. Within the clustering process a optimisation of the *asinh*-transformation for the fluorescence parameters is included.

The meta-clustering fits a Gaussian mixture model for the meta-clusters, where adjusted Bhattacharyya-Coefficients give the probability measures between cell- and meta-clusters.

Several plotting routines are available visualising the results of the cell- and meta-clustering process. Additional helper-routines to extract population features are provided.

3 Getting started

The installation on *immunoClust* is normally done within the Bioconductor.

The core functions of *immunoClust* are implemented in C/C++ for optimal utilization of system resources and depend on the GNU Scientific Library (GSL) and Basic Linear Subprogram (BLAS). When installing *immunoClust* form source using Rtools be aware to adjust the GSL library and include pathes in src/Makevars.in or src/Makevars.win (on Windows systems) repectively to the correct installation directory of the GSL-library on the system.

immunoClust relies on the *flowFrame* structure imported from the *flowCore*-package for accessing the measured cell events from a flow cytometer device.

4 Example Illustrating the immunoClust Pipeline

The functionality of the immunoClust pipeline is demonstrated on a dataset of blood cell samples of defined composition that were depleted of particular cell subsets by magnetic cell sorting. Whole blood leukocytes taken from three healthy individuals, which were experimen-

immunoClust

tally modified by the depletion of one particular cell type per sample, including granulocytes (using CD15-MACS-beads), monocytes (using CD14-MACS-beads), T lymphocytes (CD3-MACS-beads), T helper lymphocytes (using CD4-MACS-beads) and B lymphocytes (using CD19-MACS-beads).

The example datasets contain reduced (10.000 cell-events) of the first Flow Cytometry (FC) sample in `dat.fcs` and the *immunoClust* cell-clustering results of all 5 reduced FC samples for the first donor in `dat.exp`. The full sized dataset is published and available under <http://flowrepository.org/id/FR-FCM-ZZWB>.

4.1 Cell Event Clustering

```
> library(immunoClust)
```

The cell-clustering is performed by the `cell.process` function for each FC sample separately. Its major input are the measured cell-events in a `flowFrame`-object imported from the `flowCore`-package.

```
> data(dat.fcs)
> dat.fcs

flowFrame object '2d36b4cf-da0f-4b8d-9a4c-fc7e4f5fccc8'
with 10000 cells and 7 observables:
      name   desc    range minRange maxRange
$P2     FSC-A    NA  262144    0.00  262143
$P5     SSC-A    NA  262144 -111.00  262143
$P8     FITC-A   CD14 262144 -111.00  262143
$P9     PE-A     CD19 262144 -111.00  262143
$P12    APC-A    CD15 262144 -111.00  262143
$P13    APC-Cy7-A CD4  262144 -111.00  262143
$P14 Pacific Blue-A CD3  262144  -98.94  262143
171 keywords are stored in the 'description' slot
```

In the parameters argument the parameters (named as observables in the `flowFrame`) used for cell-clustering are specified. When omitted all determined parameters are used.

```
> pars=c("FSC-A", "SSC-A", "FITC-A", "PE-A", "APC-A", "APC-Cy7-A", "Pacific Blue-A")
> res.fcs <- cell.process(dat.fcs, parameters=pars)
```

The `summary` method for an *immunoClust*-object gives an overview of the clustering results.

```
> summary(res.fcs)

** Experiment Information **
Experiment name: 12443.fcs
Data Filename: fcs/12443.fcs
Parameters: FSC-A SSC-A FITC-A PE-A APC-A APC-Cy7-A Pacific Blue-A
Description: NA NA CD14 CD19 CD15 CD4 CD3

** Data Information **
Number of observations: 10000
Number of parameters: 7
Removed from above: 318 (3.18%)
```

immunoClust

```
Removed from below: 0 (0%)  
  
** Transformation Information **  
htrans-A: 0.000000 0.000000 0.010000 0.010000 0.010000 0.010000 0.010000  
htrans-B: 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000  
htrans-decade: -1  
  
** Clustering Summary **  
ICL bias: 0.30  
Number of clusters: 11  
Cluster Proportion Observations  
1 0.091950 890  
2 0.005908 57  
3 0.637708 6166  
4 0.007323 70  
5 0.015544 149  
6 0.028608 281  
7 0.040364 391  
8 0.033895 330  
9 0.016019 156  
10 0.007975 80  
11 0.114706 1112  
  
Min. 0.005908 57  
Max. 0.637708 6166  
  
** Information Criteria **  
Log likelihood: -254133.4 -254239 -173243.4  
BIC: -254133.4  
ICL: -254239
```

With the `bias` argument of the `cell.process` function the number of clusters in the final model is controlled.

```
> res2 <- cell.process(dat.fcs, bias=0.25)  
> summary(res2)  
  
** Experiment Information **  
Experiment name: 12443.fcs  
Data Filename: fcs/12443.fcs  
Parameters: FSC-A SSC-A FITC-A PE-A APC-A APC-Cy7-A Pacific Blue-A  
Description: NA NA CD14 CD19 CD15 CD4 CD3  
  
** Data Information **  
Number of observations: 10000  
Number of parameters: 7  
Removed from above: 318 (3.18%)  
Removed from below: 0 (0%)  
  
** Transformation Information **  
htrans-A: 0.000000 0.000000 0.010000 0.010000 0.010000 0.010000 0.010000  
htrans-B: 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000 0.000000
```

immunoClust

```
htrans-decade: -1

** Clustering Summary **
ICL bias: 0.25
Number of clusters: 16
Cluster      Proportion   Observations
  1      0.092245        908
  2      0.005145         50
  3      0.036555        362
  4      0.054762        525
  5      0.004097         37
  6      0.031778        312
  7      0.008611         79
  8      0.033977        331
  9      0.015605        151
 10     0.025254        230
 11     0.005754         57
 12     0.027963        274
 13     0.007172         69
 14     0.002167         21
 15     0.011172        108
 16     0.637744       6168

Min.    0.002167        21
Max.    0.637744       6168

** Information Criteria **
Log likelihood: -254154.5 -254393.8 -172573.9
BIC: -254154.5
ICL: -254393.8
```

An ICL-bias of 0.3 is reasonable for fluorescence cytometry data based on our experiences, whereas the number of clusters increase dramatically when a bias below 0.2 is applied. A principal strategy for the ICL-bias in the whole pipeline is the use of a moderately small bias (0.2 - 0.3) for cell-clustering and to optimise the bias on meta-clustering level to retrieve the common populations across all samples.

For plotting the clustering results on cell event level, the optimised *asinh*-transformation has to be applied to the raw FC data first.

```
> dat.transformed <- trans.ApplyToData(res.fcs, dat.fcs)
```


A scatter plot matrix of all used parameters for clustering is obtained by the `spolm` method.

```
> spolm(res.fcs, dat.transformed, N=1000)
```

For a scatter plot of 2 particular parameters the `plot` method can be used, where parameters of interest are specified in the `subset` argument.

immunoClust

```
> plot(res.fcs, data=dat.transformed, subset=c(1,2))
```



4.2 Meta Clustering


For meta-clustering the cell-clustering results of all FC samples obtained by the `cell.process` function are collected in a vector of *immunoClust*-objects and processed by the `meta.process` function.

```
> data(dat.exp)
> meta<-meta.process(dat.exp, meta.bias=0.3)
```

The obtained *immunoMeta*-object contains the meta-clustering result in `$res.clusters`, and the used cell-clusters information in `$dat.clusters`. Additionally, the clusters can be structures manually in a hierarchical manner using methods of the *immunoMeta*-object.

A scatter plot matrix of the meta-clustering is obtained by the `plot` method.

```
> plot(meta, c(), plot.subset=c(1,2))
```



In these scatter plots each cell-cluster is marked by a point of its centre. With the default `plot.ellipse=TRUE` argument the meta-clusters are outlined by ellipses of the 90% quantile.

4.3 Meta Annotation

We take a look and first sort the meta-clusters according to the scatter parameter into five major areas

```
> cls <- clusters(meta,c())
> inc <- mu(meta,cls,1) > 20000 & mu(meta,cls,1) < 150000
> addLevel(meta,c(1),"leucocytes") <- cls[inc]
> cls <- clusters(meta,c(1))
> sort(mu(meta,cls,2))

    cls-10    cls-7    cls-2    cls-6    cls-9    cls-4    cls-11   cls-13
 12653.96 14379.67 14987.31 24119.51 28807.31 38562.50 39089.67 53084.06
    cls-12    cls-1    cls-5    cls-8    cls-18   cls-14    cls-16   cls-3
```


immunoClust

```
59202.13 62146.93 69861.55 123717.22 130008.05 138973.89 160894.71 168585.76
cls-20    cls-15
206575.52 209360.68

> inc <- (mu(meta,cls,2)) < 40000
> addLevel(meta,c(1,1), "ly") <- cls[inc]
> addLevel(meta,c(1,2), "mo") <- c()
> inc <- (mu(meta,cls,2)) > 100000
> addLevel(meta,c(1,3), "gr") <- cls[inc]
> move(meta,c(1,2)) <- unclassified(meta,c(1))
```

In the plot of this level the three major scatter population are seen easily

```
> plot(meta, c(1))
```



and we identify the clusters for the particular populations successivley by their expression levels.

```
> cls <- clusters(meta,c(1,1))
> sort(mu(meta,cls,7)) ## CD3 expression
```

immunoClust

```
cls-6    cls-7    cls-9    cls-4    cls-11   cls-2    cls-10  
1.017751 1.023148 1.501441 2.043337 2.686877 5.339878 5.503499  
  
> sort(mu(meta,cls,6))  ## CD4 expression  
  
cls-2    cls-7    cls-6    cls-9    cls-4    cls-10   cls-11  
0.3526607 0.4631971 0.5680941 3.0448631 3.3933842 4.1704618 5.3378243  
  
> inc <- mu(meta,cls,7) > 5 & mu(meta,cls,6) > 4  
> addLevel(meta,c(1,1,1), "CD3+CD4+") <- cls[inc]  
> inc <- mu(meta,cls,7) > 5 & mu(meta,cls,6) < 4  
> addLevel(meta,c(1,1,2), "CD3+CD4-") <- cls[inc]  
> cls <- unclassified(meta,c(1,1))  
> inc <- (mu(meta,cls,4)) > 3  
> addLevel(meta,c(1,1,3), "CD19+") <- cls[inc]  
> cls <- clusters(meta,c(1,2))  
> inc <- mu(meta,cls,3) > 5 & mu(meta,cls,7) < 5  
> addLevel(meta,c(1,2,1), "CD14+") <- cls[inc]  
> cls <- clusters(meta,c(1,3))  
> inc <- mu(meta,cls,5) > 3 & mu(meta,cls,7) < 5  
> addLevel(meta,c(1,3,1), "CD15+") <- cls[inc]
```

The whole analysis is performed on uncompensated FC data, thus the high CD19 values on the CD14-population is explained by spillover of FITC into PE.

The event numbers of each meta-cluster and each sample are extracted in a numeric matrix by the `meta.numEvents` function.


```
> tbl <- meta.numEvents(meta, out.unclassified=FALSE)  
> tbl[,1:5]  
  
               12543 12546 12549 12552 12555  
measured      10000 10000 10000 10000 10000  
.all          9682  9842  9736  9736  9510  
1.all_leucocytes 9531  9244  9479  9489  9232  
1.1.all_leucocytes_ly 1911  6663  3391  1291  771  
1.1.1.all_leucocytes_ly_CD3+CD4+ 1107  3425  1585  0     0  
1.1.2.all_leucocytes_ly_CD3+CD4- 389   1079  574   433   46  
1.1.3.all_leucocytes_ly_CD19+    0     926   452   331   325  
1.2.all_leucocytes_mo        898   2472   0     761   950  
1.2.1.all_leucocytes_mo_CD14+ 898   2370   0     761   950  
1.3.all_leucocytes_gr        6722  109   6088  7437  7511  
1.3.1.all_leucocytes_gr_CD15+ 6459  101   5849  7280  7417
```

Each row denotes an annotated hierarchical level or/and meta-cluster and each column a data sample used in meta-clustering. The row names give the annotated population name. In the last columns additionally the meta-cluster centre values in each parameter are given, which helps to identify the meta-clusters. Further export functions retrieve relative cell event frequencies and sample meta-cluster centre values in a particular parameter.

We see here, that for sample 12546 where the CD15-cells are depleted, the CD14-population is missing. Anyway, this missing cluster could be in the so far unclassified clusters.

```
> plot(meta, c(1,2,1), plot.subset=c(1,2,3,4))
```

1.2.1.all_leucocytes_mo_CD14+



We see the CD14 population of sample 12546 shifted in FSC and CD3 expression levels, probably due to technical variation in the measurement of the CD15-depleted sample, where the granulocytes are missing which constitute about 60% - 70% of the events in the other samples.

5 Session Info

The documentation and example output was compiled and obtained on the system:

```
> toLatex(sessionInfo())
```

- R version 4.4.0 beta (2024-04-15 r86425), x86_64-pc-linux-gnu

- Locale: LC_CTYPE=en_US.UTF-8, LC_NUMERIC=C, LC_TIME=en_US.UTF-8, LC_COLLATE=en_US.UTF-8, LC_MONETARY=en_US.UTF-8, LC_MESSAGES=en_US.UTF-8, LC_PAPER=en_US.UTF-8, LC_NAME=C, LC_ADDRESS=C, LC_TELEPHONE=C, LC_MEASUREMENT=en_US.UTF-8, LC_IDENTIFICATION=C
- Time zone: America/New_York
- TZcode source: system (glibc)
- Running under: Ubuntu 22.04.4 LTS
- Matrix products: default
- BLAS: /home/biocbuild/bbs-3.19-bioc/R/lib/libRblas.so
- LAPACK: /usr/lib/x86_64-linux-gnu/lapack/liblapack.so.3.10.0
- Base packages: base, datasets, graphics, grDevices, methods, stats, utils
- Other packages: flowCore 2.16.0, immunoClust 1.36.0
- Loaded via a namespace (and not attached): Biobase 2.64.0, BiocGenerics 0.50.0, BiocManager 1.30.22, BiocStyle 2.32.0, cli 3.6.2, compiler 4.4.0, cytolib 2.16.0, digest 0.6.35, evaluate 0.23, fastmap 1.1.1, grid 4.4.0, htmltools 0.5.8.1, knitr 1.46, lattice 0.22-6, matrixStats 1.3.0, rlang 1.1.3, rmarkdown 2.26, RProtoBufLib 2.16.0, S4Vectors 0.42.0, stats4 4.4.0, tools 4.4.0, xfun 0.43, yaml 2.3.8