

Package ‘CEMiTool’

March 31, 2025

Title Co-expression Modules identification Tool

Version 1.30.0

Description The CEMiTool package unifies the discovery and the analysis of coexpression gene modules in a fully automatic manner, while providing a user-friendly html report with high quality graphs. Our tool evaluates if modules contain genes that are over-represented by specific pathways or that are altered in a specific sample group. Additionally, CEMiTool is able to integrate transcriptomic data with interactome information, identifying the potential hubs on each network.

Depends R (>= 4.0)

Imports methods, scales, dplyr, data.table (>= 1.9.4), WGCNA, grid, ggplot2, ggpmisc, ggthemes, ggrepel, sna, clusterProfiler, fgsea, stringr, rmarkdown, igraph, DT, htmltools, pracma, intergraph, grDevices, utils, network, matrixStats, ggdendro, gridExtra, gtable, fastcluster

Suggests testthat, BiocManager

License GPL-3

Encoding UTF-8

biocViews GeneExpression, Transcriptomics, GraphAndNetwork, mRNAMicroarray, RNASeq, Network, NetworkEnrichment, Pathways, ImmunoOncology

LazyData true

RoxygenNote 7.1.2

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/CEMiTool>

git_branch RELEASE_3_20

git_last_commit b1ca198

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-03-31

Author Pedro Russo [aut],
Gustavo Ferreira [aut],
Matheus Bürger [aut],
Lucas Cardozo [aut],

Diogenes Lima [aut],
 Thiago Hirata [aut],
 Melissa Lever [aut],
 Helder Nakaya [aut, cre]

Maintainer Helder Nakaya <hnakaya@usp.br>

Contents

adj_data	3
cem	4
cemitool	4
CEMiTool-class	7
diagnostic_report	8
expr0	8
expr_data	9
expr_pct_filter	10
filter_genes	10
find_modules	11
fit_data	13
generate_report	13
get_adj	14
get_beta_data	15
get_cemitool_r2_beta	16
get_connectivity	17
get_hubs	17
get_merged_mods	18
get_mods	19
get_phi	20
gsea_data	21
interactions_data	21
module_genes	22
module_to_gmt	23
mod_colors	23
mod_gene_num	24
mod_gsea	25
mod_names	26
mod_ora	26
mod_summary	27
new_cem	28
nmodules	29
ora_data	29
plot_beta_r2	30
plot_gsea	31
plot_hist	32
plot_interactions	32
plot_mean_k	33
plot_mean_var	34
plot_ora	35
plot_ora_single	35
plot_profile	36
plot_qq	37

plot_sample_tree	38
read_gmt	39
sample_annot	39
sample_annotation	40
save_plots	41
select_genes	42
show,CEMiTool-method	43
show_plot	43
vst	44
write_files	44

Index**46**

adj_data	<i>Get or set adjacency matrix value</i>
----------	--

Description

This function takes a CEMiTool object containing expression values and returns a CEMiTool object with an adjacency matrix in the adjacency slot.

Usage

```
adj_data(cem, ...)

## S4 method for signature 'CEMiTool'
adj_data(cem)

adj_data(cem) <- value

## S4 replacement method for signature 'CEMiTool'
adj_data(cem) <- value
```

Arguments

cem	Object of class CEMiTool
...	Optional parameters.
value	Object of class <code>matrix</code> containing adjacency data. Only used for setting adjacency values to CEMiTool object.

Value

Object of class `matrix` with adjacency values or object of class CEMiTool.

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Calculate adjacency matrix with example beta value 8
cem <- get_adj(cem, beta=8)
```

```
# Return adjacency matrix
adj <- adj_data(cem)
# Check result
adj[1:5, 1:5]
# Set adjacency matrix to CEMiTool object
adj_data(cem) <- adj
```

cem*CEMiTool Object***Description**

This object can be used as input for CEMiTool functions. Data used are from `expr` and `sample_annot`.

Usage

```
data(cem)
```

Format

An object of class `CEMiTool`

Examples

```
# Get example CEMiTool object
data(cem)
cem
```

cemitool*Full gene co-expression analysis***Description**

Defines co-expression modules and runs several different analyses.

Usage

```
cemitool(
  expr,
  annot,
  gmt,
  interactions,
  filter = TRUE,
  filter_pval = 0.1,
  apply_vst = FALSE,
  n_genes,
  eps = 0.1,
  cor_method = c("pearson", "spearman"),
  cor_function = "cor",
  network_type = "unsigned",
```

```

    tom_type = "signed",
    set_beta = NULL,
    force_beta = FALSE,
    sample_name_column = "SampleName",
    class_column = "Class",
    merge_similar = TRUE,
    rank_method = "mean",
    ora_pval = 0.05,
    gsea_scale = TRUE,
    gsea_min_size = 15,
    gsea_max_size = 1000,
    min_nngen = 30,
    diss_thresh = 0.8,
    plot = TRUE,
    plot_diagnostics = TRUE,
    order_by_class = TRUE,
    center_func = "mean",
    directed = FALSE,
    verbose = FALSE
)

```

Arguments

expr	Gene expression data.frame.
annot	Sample annotation data.frame.
gmt	A data.frame containing two columns, one with pathways and one with genes
interactions	A data.frame containing two columns with gene names.
filter	Logical. If TRUE, will filter expression data.
filter_pval	P-value threshold for filtering. Default 0.1.
apply_vst	Logical. If TRUE, will apply Variance Stabilizing Transform before filtering genes. Currently ignored if parameter filter is FALSE.
n_genes	Number of genes left after filtering.
eps	A value for accepted R-squared interval between subsequent beta values. Default is 0.1.
cor_method	A character string indicating which correlation coefficient is to be computed. One of "pearson" or "spearman". Default is "pearson".
cor_function	A character string indicating the correlation function to be used. Supported functions are currently 'cor' and 'bicor'. Default is "cor"
network_type	A character string indicating if network type should be computed as "signed" or "unsigned". Default is "unsigned"
tom_type	A character string indicating if the TOM type should be computed as "signed" or "unsigned". Default is "signed"
set_beta	A value to override the automatically selected beta value. Default is NULL.
force_beta	Whether or not to automatically force a beta value based on number of samples. Default is FALSE.
sample_name_column	A character string indicating the sample column name of the annotation table.
class_column	A character string indicating the class column name of the annotation table.

merge_similar	Logical. If TRUE, merge similar modules.
rank_method	Character string indicating how to rank genes. Either "mean" (the default) or "median".
ora_pval	P-value for overrepresentation analysis. Default 0.05.
gsea_scale	If TRUE, apply z-score transformation for GSEA analysis. Default is TRUE
gsea_min_size	Minimum size of gene sets for GSEA analysis. Default is 15
gsea_max_size	Maximum size of gene sets for GSEA analysis. Default is 1000
min_nngen	Minimal number of genes per submodule. Default 30.
diss_thresh	Module merging correlation threshold for eigengene similarity. Default 0.8.
plot	Logical. If TRUE, plots all figures.
plot_diagnostics	Logical. If TRUE, creates diagnostic plots. Overwritten if plot=FALSE.
order_by_class	Logical. If TRUE, samples in profile plot are ordered by the groups defined by the class_column slot in the sample annotation file. Ignored if there is no sample_annotation file. Default TRUE.
center_func	Character string indicating the centrality measure to show in the plot. Either 'mean' (the default) or 'median'.
directed	Logical. If TRUE, the igraph objects in interactions slot will be directed.
verbose	Logical. If TRUE, reports analysis steps.

Value

Object of class CEMiTool

Examples

```
# Get example expression data
data(expr0)
# Run CEMiTool analyses
cem <- cemitool(expr=expr0)
# Run CEMiTool applying Variance Stabilizing Transformation to data
cem <- cemitool(expr=expr0, apply_vst=TRUE)
# Run CEMiTool with additional processing messages
cem <- cemitool(expr=expr0, verbose=TRUE)

## Not run:
# Run full CEMiTool analysis
## Get example sample annotation data
data(sample_annot)
## Read example pathways file
gmt_fname <- system.file("extdata", "pathways.gmt", package = "CEMiTool")
gmt_in <- read_gmt(gmt_fname)
## Get example interactions file
int_df <- read.delim(system.file("extdata", "interactions.tsv", package = "CEMiTool"))
## Run CEMiTool
cem <- cemitool(expr=expr0, annot=sample_annot, gmt=gmt_in,
                 interactions=int_df, verbose=TRUE, plot=TRUE)

# Create report as html file
generate_report(cem, directory = "./Report", output_format="html_document")
```

```
# Write analysis results into files
write_files(cem, directory=".Tables", force=TRUE)

# Save all plots
save_plots(cem, "all", directory=".Plots")

## End(Not run)
```

CEMiTool-class

An S4 class to represent the CEMiTool analysis.

Description

An S4 class to represent the CEMiTool analysis.

Slots

```
expression Gene expression data.frame.
sample_annotation Sample annotation data.frame.
fit_indices data.frame containing scale-free model fit, soft-threshold and network parameters.
selected_genes Character vector containing the names of genes selected for analysis
module Genes in modules information data.frame.
enrichment list with modules enrichment results for sample classes.
ora Over-representation analysis results data.frame.
interactions list containing gene interactions present in modules.
interaction_plot list of ggplot graphs with module gene interactions.
profile_plot list of ggplot graphs with gene expression profile per module.
enrichment_plot ggplot graph for enrichment analysis results.
beta_r2_plot ggplot graph with scale-free topology fit results for each soft-threshold.
mean_k_plot ggplot graph with mean network connectivity.
barplot_ora list of ggplot graphs with over-representation analysis results per module.
sample_tree_plot gtable containing sample dendrogram with class labels and clinical data (if
available in sample_annotation(cem)).
mean_var_plot Mean x variance scatterplot.
hist_plot Expression histogram.
qq_plot Quantile-quantile plot.
sample_name_column character string containing the name of the column with sample names in
the annotation file.
class_column character string containing the name of the column with class names in the annota-
tion file.
mod_colors character vector containing colors associated with each network module.
parameters list containing analysis parameters.
adjacency matrix containing gene adjacency values based on correlation
```

Examples

```
# Get example expression data
data(expr0)
# Initialize CEMiTool object with expression
cem <- new("CEMiTool", expression=expr0)
```

diagnostic_report *Diagnostic report*

Description

Creates report for identifying potential problems with data.

Usage

```
diagnostic_report(cem, ...)

## S4 method for signature 'CEMiTool'
diagnostic_report(
  cem,
  title = "Diagnostics",
  directory = "./Reports/Diagnostics",
  force = FALSE,
  ...
)
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	parameters to rmarkdown::render
<code>title</code>	Character string with the title of the report.
<code>directory</code>	Directory name for results.
<code>force</code>	If the directory exists, execution will not stop.

Value

An HTML file with an interactive diagnostic report.

expr0 *Yellow Fever gene expression data from GEO study GSE13485*

Description

Modified data from a yellow fever vaccination study by Querec et al, 2009. In order to reduce package size, only the 4000 genes with the highest variance were selected for this dataset.

Usage

```
data(expr0)
```

Format

An object of class `data.frame`

Source

GEO

References

Querec TD, Akondy RS, Lee EK, Cao W et al. Systems biology approach predicts immunogenicity of the yellow fever vaccine in humans. *Nat Immunol* 2009 Jan;10(1):116-25. PMID: 19029902
[PubMed](#)

Examples

```
data(expr0)
# Run CEMiTool analysis
## Not run: cemitoole(expr0)
```

expr_data

Retrieve and set expression attribute

Description

Retrieve and set expression attribute

Usage

```
expr_data(cem, ...)

## S4 method for signature 'CEMiTool'
expr_data(cem, filter = TRUE, apply_vst = FALSE, filter_pval = 0.1, ...)

expr_data(cem) <- value

## S4 replacement method for signature 'CEMiTool'
expr_data(cem) <- value
```

Arguments

<code>cem</code>	Object of class <code>CEMiTool</code>
<code>...</code>	Additional parameters to <code>filter_genes</code> or <code>select_genes</code> functions.
<code>filter</code>	logical. If TRUE, retrieves filtered expression data (Default: TRUE)
<code>apply_vst</code>	logical. If TRUE, applies variance stabilizing transformation to expression data (Default: FALSE)
<code>filter_pval</code>	logical. Threshold for filter p-value. Ignored if filter = FALSE (Default: 0.1)
<code>value</code>	Object of class <code>data.frame</code> with gene expression data

Value

Object of class `data.frame` with gene expression data

Examples

```
# Initialize an empty CEMiTool object
cem <- new_cem()
# Get example expression data
data(expr0)
# Add expression file to CEMiTool object
expr_data(cem) <- expr0
# Check expression file
head(expr_data(cem))
```

expr_pct_filter

Filter genes based on expression.

Description

Filter genes based on expression.

Usage

```
expr_pct_filter(expr, pct = 0.75)
```

Arguments

expr	expression file containing genes in the rows and samples in the columns
pct	percentage of most expressed genes to maintain

Value

A data.frame containing the results

filter_genes

Filter a gene expression data.frame

Description

Filter a gene expression data.frame

Usage

```
filter_genes(expr, pct = 0.75, apply_vst = FALSE)
```

Arguments

expr	A data.frame containing expression data
pct	Percentage of most expressed genes to keep.
apply_vst	Logical. If TRUE, will apply variance stabilizing transform before filtering data.

Details

This function takes a gene expression data.frame and applies a percentage filter (keeps the pct) most expressed genes). If apply_vst is TRUE, a variance stabilizing transformation is applied on gene expression values as long as mean and variance values have a Spearman's rho of over 0.5. This transformation is intended to remove this dependence between the parameters. One should then apply the select_genes function to get significant genes.

Value

A data.frame containing filtered expression data

Examples

```
# Get example expression data
data(expr0)
# Filter genes
expr_f <- filter_genes(expr0)
# Check selected genes
expr_f[1:5, 1:5]
# Filter genes and apply variance stabilizing transformation
expr_f2 <- filter_genes(expr0, apply_vst=TRUE)
# Check results
expr_f2[1:5, 1:5]
# Selected genes
selected <- select_genes(expr_f2)
# Get data.frame with only selected genes
expr_s <- expr_f2[selected, ]
# Check results
expr_s[1:5, 1:5]
```

Description

Defines co-expression modules

Usage

```
find_modules(cem, ...)

## S4 method for signature 'CEMiTool'
find_modules(
  cem,
  cor_method = c("pearson", "spearman"),
  cor_function = "cor",
  eps = 0.1,
  set_beta = NULL,
  force_beta = FALSE,
  min_nngen = 20,
  merge_similar = TRUE,
  network_type = "unsigned",
```

```

    tom_type = "signed",
    diss_thresh = 0.8,
    verbose = FALSE
)

```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	Optional parameters.
<code>cor_method</code>	A character string indicating which correlation coefficient is to be computed. Default "pearson"
<code>cor_function</code>	A character string indicating the correlation function to be used. Default 'cor'.
<code>eps</code>	A value for accepted R-squared interval between subsequent beta values. Default is 0.1.
<code>set_beta</code>	A value to override the automatically selected beta value. Default is NULL.
<code>force_beta</code>	Whether or not to automatically force a beta value based on number of samples. Default is FALSE.
<code>min_nngen</code>	Minimal number of genes per submodule. Default 20.
<code>merge_similar</code>	Logical. If TRUE, (the default) merge similar modules.
<code>network_type</code>	A character string indicating to use either "unsigned" (default) or "signed" networks. Default "unsigned"
<code>tom_type</code>	A character string indicating to use either "unsigned" or "signed" (default) TOM similarity measure.
<code>diss_thresh</code>	Module merging correlation threshold for eigengene similarity. Default 0.8.
<code>verbose</code>	Logical. If TRUE, reports analysis steps. Default FALSE

Value

Object of class CEMiTool

Examples

```

# Get example expression data
data(expr0)
# Initialize CEMiTool object with expression
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Define network modules
cem <- find_modules(cem)
# Check results
head(module_genes(cem))

```

fit_data	<i>Retrieve scale-free model fit data</i>
----------	---

Description

Retrieve scale-free model fit data

Usage

```
fit_data(cem)

## S4 method for signature 'CEMiTool'
fit_data(cem)
```

Arguments

cem Object of class CEMiTool

Value

Object of class data.frame

Examples

```
# Get example CEMiTool object
data(cem)
# Get modules and beta data
cem <- find_modules(cem)
# Get fit data
fit_data(cem)
```

generate_report	<i>CEMiTool report</i>
-----------------	------------------------

Description

Creates report for CEMiTool results

Usage

```
generate_report(cem, ...)

## S4 method for signature 'CEMiTool'
generate_report(
  cem,
  max_rows_ora = 50,
  title = "Report",
  directory = "./Reports/Report",
  force = FALSE,
  ...
)
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	parameters to rmarkdown::render
<code>max_rows_ora</code>	maximum number of rows in Over Representation Analysis table results
<code>title</code>	Character string with the title of the report.
<code>directory</code>	Directory name for results.
<code>force</code>	If the directory exists, execution will not stop.

Value

An HTML file with an interactive report of CEMiTool analyses.

Examples

```
## Not run:
# Get example CEMiTool object
data(cem)
generate_report(cem, output_format=c("pdf_document", "html_document"))

## End(Not run)
```

<code>get_adj</code>	<i>Calculate adjacency matrix</i>
----------------------	-----------------------------------

Description

This function takes a CEMiTool object and returns an adjacency matrix.

Usage

```
get_adj(cem, ...)

## S4 method for signature 'CEMiTool'
get_adj(
  cem,
  beta,
  network_type = "unsigned",
  cor_function = "cor",
  cor_method = "pearson"
)
```

Arguments

<code>cem</code>	Object of class CEMiTool
<code>...</code>	Optional parameters.
<code>beta</code>	Selected soft-threshold value
<code>network_type</code>	A character string indicating to use either "unsigned" (default) or "signed" networks. Default "unsigned".

cor_function	A character string indicating the correlation function to be used. Default 'cor'.
cor_method	A character string indicating which correlation coefficient is to be computed. Default "pearson".

Value

Object of class CEMiTool with adjacency data

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Calculate adjacency matrix with example beta value 8
cem <- get_adj(cem, beta=8)
# Check results
adj <- adj_data(cem)
adj[1:5, 1:5]
```

get_beta_data	<i>Soft-threshold beta data</i>
---------------	---------------------------------

Description

This function takes the input parameters from find_modules and calculates the WGCNA soft-threshold parameters and returns them.

Usage

```
get_beta_data(cem, ...)

## S4 method for signature 'CEMiTool'
get_beta_data(
  cem,
  network_type = "unsigned",
  cor_function = "cor",
  cor_method = "pearson",
  verbose = FALSE
)
```

Arguments

cem	A CEMiTool object containing expression data
...	Optional parameters.
network_type	A character string indicating to use either "unsigned" (default) or "signed" networks. Default "unsigned".
cor_function	A character string indicating the correlation function to be used. Default 'cor'.
cor_method	A character string indicating which correlation coefficient is to be computed. Default "pearson"
verbose	Logical. If TRUE, reports analysis steps. Default FALSE

Value

A list containing the soft-threshold selected by WGCNA and scale-free model parameters

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Get beta data
beta_data <- get_beta_data(cem)
```

`get_cemitoor_r2_beta` *Calculate CEMiTool beta and R2 values*

Description

This function takes a CEMiTool object with beta data and returns a vector containing the chosen beta and corresponding R squared value.

Usage

```
get_cemitoor_r2_beta(cem, ...)
## S4 method for signature 'CEMiTool'
get_cemitoor_r2_beta(cem, eps = 0.1)
```

Arguments

<code>cem</code>	A CEMiTool object containing the <code>fit_indices</code> slot
<code>...</code>	Optional parameters.
<code>eps</code>	A value indicating the accepted interval between successive values of R squared to use to calculate the selected beta. Default: 0.1.

Value

A vector containing R squared value and the chosen beta parameter.

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Get modules and beta data
cem <- find_modules(cem)
# Get CEMiTool R2 and beta values
get_cemitoor_r2_beta(cem)
```

<code>get_connectivity</code>	<i>Calculate network connectivity</i>
-------------------------------	---------------------------------------

Description

This function takes a CEMiTool object and returns the network connectivity.

Usage

```
get_connectivity(cem, ...)

## S4 method for signature 'CEMiTool'
get_connectivity(cem, beta)
```

Arguments

cem	Object of class CEMiTool containing the fit_indices slot
...	Optional parameters.
beta	A soft-thresholding value to be used for the network.

Value

The value of the network's connectivity.

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Get modules and beta data
cem <- find_modules(cem)
# Get network connectivity with example beta value 8
get_connectivity(cem, beta=8)
```

<code>get_hubs</code>	<i>Get hubs</i>
-----------------------	-----------------

Description

Returns n genes in each module with high connectivity.

Usage

```
get_hubs(cem, ...)

## S4 method for signature 'CEMiTool'
get_hubs(cem, n = 5, method = "adjacency")
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	Optional parameters.
<code>n</code>	Number of hubs to return from each module. If "all", returns all genes in decreasing order of connectivity. Default: 5.
<code>method</code>	Method for hub calculation. Either "adjacency" or "kME". Default: "adjacency"

Value

A list containing hub genes for each module and the value of the calculated method.

Examples

```
# Get example CEMiTool object
data(cem)
# Get module hubs
hubs <- get_hubs(cem, n=10, "adjacency")
```

get_merged_mods *Merge similar modules*

Description

This function takes a CEMiTool object with expression and a vector of numeric labels to merge similar modules.

Usage

```
get_merged_mods(cem, ...)
## S4 method for signature 'CEMiTool'
get_merged_mods(cem, mods, diss_thresh = 0.8, verbose = FALSE)
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	Optional parameters.
<code>mods</code>	A vector containing numeric labels for each module gene
<code>diss_thresh</code>	A threshold of dissimilarity for modules. Default is 0.8.
<code>verbose</code>	Logical. If TRUE, reports analysis steps. Default FALSE

Value

Numeric labels assigning genes to modules.

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Calculate adjacency matrix with example beta value 8
cem <- get_adj(cem, beta=8)
# Get modules
mods <- get_mods(cem)
# Merge similar modules
merged_mods <- get_merged_mods(cem, mods)
```

get_mods

Calculate co-expression modules

Description

This function takes a CEMiTool object containing an adjacency matrix together with the given network parameters, and returns the given co-expression modules.

Usage

```
get_mods(cem, ...)

## S4 method for signature 'CEMiTool'
get_mods(
  cem,
  cor_function = "cor",
  cor_method = "pearson",
  tom_type = "signed",
  min_nngen = 20
)
```

Arguments

cem	Object of class CEMiTool.
...	Optional parameters.
cor_function	A character string indicating the correlation function to be used. Default 'cor'.
cor_method	A character string indicating which correlation coefficient is to be computed. Default "pearson".
tom_type	A character string indicating to use either "unsigned" or "signed" (default) TOM similarity measure.
min_nngen	Minimal number of genes per module (Default: 20).

Value

Numeric labels assigning genes to modules.

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Calculate adjacency matrix with example beta value 8
cem <- get_adj(cem, beta=8)
# Get module labels
mods <- get_mods(cem)
```

get_phi

Calculate phi

Description

This function takes a CEMiTool object and returns the phi parameter.

Usage

```
get_phi(cem, ...)
## S4 method for signature 'CEMiTool'
get_phi(cem)
```

Arguments

cem	A CEMiTool object containing the fit_indices slot
...	Optional parameters.

Value

The phi parameter

Examples

```
# Get example expression data
data(expr0)
# Initialize new CEMiTool object with expression data
cem <- new_cem(expr0, filter=TRUE, apply_vst=FALSE)
# Get modules and beta data
cem <- find_modules(cem)
# Get phi
get_phi(cem)
```

gsea_data*Retrieve Gene Set Enrichment Analysis (GSEA) results*

Description

Retrieve Gene Set Enrichment Analysis (GSEA) results

Usage

```
gsea_data(cem)

## S4 method for signature 'CEMiTool'
gsea_data(cem)
```

Arguments

cem Object of class CEMiTool

Value

Object of class list with GSEA data

Examples

```
# Get example CEMiTool object
data(cem)
# Look at example annotation file
sample_annotation(cem)
# Run GSEA on network modules
cem <- mod_gsea(cem)
# Check results
gsea_data(cem)
```

interactions_data*Retrieve and set interaction data to CEMiTool object*

Description

Retrieve and set interaction data to CEMiTool object

Usage

```
interactions_data(cem, ...)

## S4 method for signature 'CEMiTool'
interactions_data(cem)

interactions_data(cem) <- value

## S4 replacement method for signature 'CEMiTool'
interactions_data(cem) <- value
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	parameters for <code>igraph::graph_from_data_frame</code>
<code>value</code>	a <code>data.frame</code> or matrix containing two columns

Value

Object of class CEMiTool

Examples

```
# Get example CEMiTool object
data(cem)
# Read example interactions data
int_df <- read.delim(system.file("extdata", "interactions.tsv",
  package = "CEMiTool"))
# Insert interactions data
interactions_data(cem) <- int_df
# Check interactions data
interactions_data(cem)
```

`module_genes`

Get the module genes in a CEMiTool object

Description

Get the module genes in a CEMiTool object

Usage

```
module_genes(cem, module = NULL)

## S4 method for signature 'CEMiTool'
module_genes(cem, module = NULL)
```

Arguments

<code>cem</code>	Object of class CEMiTool
<code>module</code>	A character string with the name of the module of which genes are to be returned. Defaults to <code>NULL</code> , which returns the full list of genes and modules.

Value

Object of class `data.frame` containing genes and their respective module

Examples

```
# Get example CEMiTool object
data(cem)
# Get the module genes
module_genes(cem)
# Get genes for module M1
module_genes(cem, module="M1")
```

module_to_gmt *Transform module genes list to a gmt file*

Description

Transform module genes list to a gmt file

Usage

```
module_to_gmt(cem, directory = "./Tables")
```

Arguments

cem

Value

A .gmt file containing module genes in each row

mod_colors *Retrieve and set mod_colors attribute*

Description

Retrieve and set mod_colors attribute

Usage

```
mod_colors(cem)

## S4 method for signature 'CEMiTool'
mod_colors(cem)

mod_colors(cem) <- value

## S4 replacement method for signature 'CEMiTool,character'
mod_colors(cem) <- value
```

Arguments

cem	Object of class CEMiTool
value	a character vector containing colors for each module. Names should match with module names

Value

A vector with color names.

Examples

```
# Get example CEMiTool object
data(cem)
# See module colors
mod_colors(cem)
```

mod_gene_num

Get the number of genes in modules in a CEMiTool object

Description

Get the number of genes in modules in a CEMiTool object

Usage

```
mod_gene_num(cem, module = NULL)

## S4 method for signature 'CEMiTool'
mod_gene_num(cem, module = NULL)
```

Arguments

cem	Object of class CEMiTool
module	Default is NULL. If a character string designating a module is given, the number of genes in that module is returned instead.

Value

The number of genes in module(s)

Examples

```
# Get example CEMiTool object
data(cem)
# Get the number of genes in modules
mod_gene_num(cem)
# Get the number of genes in module M1
mod_gene_num(cem, "M1")
```

mod_gsea

Module Gene Set Enrichment Analysis

Description

Perfoms Gene Set Enrichment Analysis (GSEA) for each co-expression module found.

Usage

```
mod_gsea(cem, ...)

## S4 method for signature 'CEMiTool'
mod_gsea(
  cem,
  gsea_scale = TRUE,
  rank_method = "mean",
  gsea_min_size = 15,
  gsea_max_size = 1000,
  verbose = FALSE
)
```

Arguments

cem	Object of class CEMiTool.
...	Optional parameters.
gsea_scale	If TRUE, transform data using z-score transformation. Default: TRUE
rank_method	Character string indicating how to rank genes. Either "mean" (the default) or "median".
gsea_min_size	Minimum gene set size (Default: 15).
gsea_max_size	Maximum gene set size (Default: 1000).
verbose	logical. Report analysis steps.

Value

GSEA results.

See Also

[plot_gsea](#)

Examples

```
# Get example CEMiTool object
data(cem)
# Look at example annotation file
sample_annotation(cem)
# Run GSEA on network modules
cem <- mod_gsea(cem)
# Check results
gsea_data(cem)
```

mod_names	<i>Get module names in a CEMiTool object</i>
-----------	--

Description

Get module names in a CEMiTool object

Usage

```
mod_names(cem, include_NC = TRUE)

## S4 method for signature 'CEMiTool'
mod_names(cem, include_NC = TRUE)
```

Arguments

cem	Object of class CEMiTool
include_NC	Logical. Whether or not to include "Not.Correlated" module. Defaults to TRUE.

Value

Module names

Examples

```
# Get example CEMiTool object
data(cem)
# Get module names
mod_names(cem)
```

mod_ora	<i>Module Overrepresentation Analysis</i>
---------	---

Description

Performs overrepresentation analysis for each co-expression module found.

Usage

```
mod_ora(cem, ...)

## S4 method for signature 'CEMiTool'
mod_ora(cem, gmt, verbose = FALSE)
```

Arguments

cem	Object of class CEMiTool.
...	Optional parameters.
gmt	Object of class <code>data.frame</code> with 2 columns, one with pathways and one with genes
verbose	logical. Report analysis steps.

Value

Object of class CEMiTool

See Also

[ora_data](#)

Examples

```
# Get example CEMiTool object
data(cem)
# Read gmt file
gmt <- read_gmt(system.file('extdata', 'pathways.gmt',
                             package='CEMiTool'))
# Run module overrepresentation analysis
cem <- mod_ora(cem, gmt)
# Check results
head(ora_data(cem))
```

mod_summary

Co-expression module summarization

Description

Summarizes modules using mean or eigengene expression.

Usage

```
mod_summary(cem, ...)
## S4 method for signature 'CEMiTool'
mod_summary(cem, method = c("mean", "median", "eigengene"), verbose = FALSE)
```

Arguments

cem	Object of class CEMiTool.
...	Optional parameters.
method	A character string indicating which summarization method is to be used. Can be 'eigengene', 'mean' or 'median'. Default is 'mean'.
verbose	Logical. If TRUE, reports analysis steps.

Value

A `data.frame` with summarized values.

Examples

```
# Get example CEMiTool object
data(cem)
# Summarize results
mod_summary <- mod_summary(cem)
```

<code>new_cem</code>	<i>Create a CEMiTool object</i>
----------------------	---------------------------------

Description

Create a CEMiTool object

Usage

```
new_cem(
  expr = data.frame(),
  sample_annot = data.frame(),
  sample_name_column = "SampleName",
  class_column = "Class",
  filter = TRUE,
  apply_vst = FALSE,
  filter_pval = 0.1
)
```

Arguments

<code>expr</code>	Object of class <code>data.frame</code> with gene expression data
<code>sample_annot</code>	Object of <code>data.frame</code> containing the sample annotation. It should have at least two columns containing group Class and the Sample Name that should match with samples in expression file
<code>sample_name_column</code>	A string specifying the column to be used as sample identification. Default: "SampleName".
<code>class_column</code>	A string specifying the column to be used as a grouping factor for samples. Default: "Class"
<code>filter</code>	Logical. Used to define if posterior functions should use filtered expression data or not (Default: TRUE)
<code>apply_vst</code>	Logical. Used to define if posterior functions should use a variance stabilizing transformation on expression data before analyses. Only valid if argument <code>filter</code> is TRUE. (Default: FALSE)
<code>filter_pval</code>	logical. Threshold for filter p-value. Ignored if <code>filter</code> = FALSE (Default: 0.1)

Value

Object of class CEMiTool

Examples

```
# Create new CEMiTool object
cem <- new_cem()
# Create new CEMiTool object with expression and sample_annotation data
data(expr0)
data(sample_annot)
cem <- new_cem(expr0, sample_annot, "SampleName", "Class")
# Equivalent to a call to new()
cem2 <- new("CEMiTool", expression=expr0, sample_annotation=sample_annot)
identical(cem, cem2)
```

nmodules	<i>Get the number of modules in a CEMiTool object</i>
----------	---

Description

Get the number of modules in a CEMiTool object

Usage

```
nmodules(cem)  
## S4 method for signature 'CEMiTool'  
nmodules(cem)
```

Arguments

cem Object of class CEMiTool

Value

number of modules

Examples

```
# Get example CEMiTool object  
data(cem)  
# Get the number of modules  
nmodules(cem)
```

ora_data	<i>Retrieve over representation analysis (ORA) results</i>
----------	--

Description

Retrieve over representation analysis (ORA) results

Usage

```
ora_data(cem)  
## S4 method for signature 'CEMiTool'  
ora_data(cem)
```

Arguments

cem Object of class CEMiTool

Details

This function returns the results of the `mod_ora` function on the `CEMiTool` object. The ID column corresponds to pathways in the gmt file for which genes in the modules were enriched. The Count column shows the number of genes in the module that are enriched for each pathway. The GeneRatio column shows the proportion of genes in the module enriched for a given pathway out of all the genes in the module enriched for any given pathway. The BgRatio column shows the proportion of genes in a given pathway out of all the genes in the gmt file. For more details, please refer to the `clusterProfiler` package documentation.

Value

Object of class `data.frame` with ORA data

References

Guangchuang Yu, Li-Gen Wang, Yanyan Han, Qing-Yu He. `clusterProfiler`: an R package for comparing biological themes among gene clusters. *OMICS: A Journal of Integrative Biology*. 2012, 16(5):284-287.

Examples

```
# Get example CEMiTool object
data(cem)
# Read gmt file
gmt <- read_gmt(system.file('extdata', 'pathways.gmt',
                             package='CEMiTool'))
# Run module overrepresentation analysis
cem <- mod_ora(cem, gmt)
# Check results
head(ora_data(cem))
```

plot_beta_r2

Soft-threshold beta selection graph

Description

Creates a graph showing each possible soft-threshold value and its corresponding R squared value

Usage

```
plot_beta_r2(cem, ...)
## S4 method for signature 'CEMiTool'
plot_beta_r2(cem, plot_title = "Scale independence (beta selection)")
```

Arguments

<code>cem</code>	Object of class <code>CEMiTool</code> .
<code>...</code>	Optional parameters.
<code>plot_title</code>	title of the graph

Value

Object of class CEMiTool with beta x R squared plot

Examples

```
# Get example CEMiTool object
data(cem)
# Plot scale-free model fit as a function of the soft-thresholding beta parameter choice
cem <- plot_beta_r2(cem)
# Check resulting plot
show_plot(cem, "beta_r2")
```

plot_gsea

GSEA visualization

Description

Creates a heatmap with the results of gene set enrichment analysis (GSEA) of co-expression modules

Usage

```
plot_gsea(cem, ...)
## S4 method for signature 'CEMiTool'
plot_gsea(cem, pv_cut = 0.05)
```

Arguments

cem	Object of class CEMiTool.
...	Optional parameters.
pv_cut	P-value cut-off. Default 0.05

Value

Object of class CEMiTool with GSEA plots

Examples

```
# Get example CEMiTool object
data(cem)
# Get example sample annotation file
# Run GSEA on network modules
cem <- mod_gsea(cem)
# Plot GSEA results
cem <- plot_gsea(cem)
# Check resulting plot
show_plot(cem, "gsea")
```

<code>plot_hist</code>	<i>Plot histogram</i>
------------------------	-----------------------

Description

This function plots a histogram of the distribution of gene expression, to help assess the normality of the data.

Usage

```
plot_hist(cem, ...)

## S4 method for signature 'CEMiTool'
plot_hist(cem, filter = FALSE)
```

Arguments

<code>cem</code>	Object of class CEMiTool
<code>...</code>	Optional parameters
<code>filter</code>	Logical. Whether or not to use filtered data for CEMiTool objects (Default: FALSE).

Value

Object of class CEMiTool containing expression histogram

Examples

```
# Get example CEMiTool object
data(cem)
# Plot histogram
cem <- plot_hist(cem)
# Check results
show_plot(cem, "hist")
```

<code>plot_interactions</code>	<i>Network visualization</i>
--------------------------------	------------------------------

Description

Creates a graph based on interactions provided

Usage

```
plot_interactions(cem, ...)

## S4 method for signature 'CEMiTool'
plot_interactions(cem, n = 10, ...)
```

Arguments

- cem Object of class CEMiTool.
- ... Optional parameters.
- n number of nodes to label

Value

Object of class CEMiTool with profile plots

Examples

```
# Get example CEMiTool object
data(cem)
# Get example gene interactions data
int <- system.file("extdata", "interactions.tsv", package = "CEMiTool")
int_df <- read.delim(int)
# Include interaction data into CEMiTool object
interactions_data(cem) <- int_df
# Plot resulting networks
cem <- plot_interactions(cem)
# Check resulting plot
show_plot(cem, "interaction")
```

plot_mean_k

Network mean connectivity

Description

Creates a graph showing the mean connectivity of genes in the network

Usage

```
plot_mean_k(cem, ...)
## S4 method for signature 'CEMiTool'
plot_mean_k(cem, title = "Mean connectivity")
```

Arguments

- cem Object of class CEMiTool.
- ... Optional parameters.
- title title of the graph

Value

Object of class CEMiTool with connectivity plot

Examples

```
# Get example CEMiTool object
data(cem)
# Plot scale-free model fit as a function of the soft-thresholding beta parameter choice
cem <- plot_mean_k(cem)
# Check resulting plot
show_plot(cem, "mean_k")
```

plot_mean_var

Plot mean and variance

Description

This plot returns a scatterplot of the mean by the variance of gene expression. A linear relationship between these values for RNAseq data suggest that an appropriate transformation such as the Variance Stabilizing Transformation should be applied.

Usage

```
plot_mean_var(cem, ...)
## S4 method for signature 'CEMiTool'
plot_mean_var(cem, filter = FALSE)
```

Arguments

cem	Object of class CEMiTool
...	Optional parameters
filter	Logical. Whether or not to use filtered data for CEMiTool objects (Default: FALSE).

Value

Object of class CEMiTool containing a mean and variance plot

Examples

```
# Get example CEMiTool object
data(cem)
# Plot mean and variance plot
cem <- plot_mean_var(cem)
# Check results
show_plot(cem, 'mean_var')
```

plot_ora*ORA visualization*

Description

Creates a bar plot with the results of module overrepresentation analysis

Usage

```
plot_ora(cem, ...)
## S4 method for signature 'CEMiTool'
plot_ora(cem, n = 10, pv_cut = 0.05, ...)
```

Arguments

cem	Object of class CEMiTool.
...	parameters to plot_ora_single
n	number of modules to show
pv_cut	p-value significance cutoff. Default is 0.05.

Value

Object of class CEMiTool with ORA plots

Examples

```
# Get example CEMiTool object
data(cem)
# Read example gmt file
gmt <- read_gmt(system.file('extdata', 'pathways.gmt',
                             package='CEMiTool'))
# Run overrepresentation analysis
cem <- mod_ora(cem, gmt)
# Plot module gene expression profiles
cem <- plot_ora(cem)
# Check resulting plot
show_plot(cem, "ora")
```

plot_ora_single*ORA visualization for one module*

Description

ORA visualization for one module

Usage

```
plot_ora_single(
  es,
  ordr_by = "p.adjust",
  max_length = 50,
  pv_cut = 0.05,
  graph_color = "#4169E1",
  title = "Over Representation Analysis"
)
```

Arguments

<code>es</code>	a data.frame from ora function containing only one module
<code>ordr_by</code>	column to order the data.frame
<code>max_length</code>	max length of a gene set name
<code>pv_cut</code>	p-value cutoff
<code>graph_color</code>	color of bars
<code>title</code>	title of the graph

Value

a list with ggplot2 object and the number of significant gene sets

<code>plot_profile</code>	<i>Expression profile visualization</i>
---------------------------	---

Description

Creates a plot with module gene expression profiles along samples

Usage

```
plot_profile(cem, ...)

## S4 method for signature 'CEMiTool'
plot_profile(cem, order_by_class = TRUE, center_func = "mean")
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	Optional parameters.
<code>order_by_class</code>	Logical. Only used if a sample annotation file is present. Whether or not to order by the class column in the sample annotation file (as defined by the <code>class_column</code> slot in <code>cem</code>).
<code>center_func</code>	Character string indicating the centrality measure to show in the plot. Either ' <code>mean</code> ' (the default) or ' <code>median</code> '.

Value

Object of class CEMiTool with profile plots

Examples

```
# Get example CEMiTool object
data(cem)
# Plot module gene expression profiles
cem <- plot_profile(cem)
# Check resulting plot
show_plot(cem, "profile")
```

plot_qq

Plot quantile-quantile plot

Description

This function creates a normal QQ plot of the expression values.

Usage

```
plot_qq(cem, ...)
## S4 method for signature 'CEMiTool'
plot_qq(cem, filter = FALSE)
```

Arguments

cem	Object of class CEMiTool
...	Optional parameters
filter	Logical. Whether or not to use filtered data for CEMiTool objects (Default: FALSE).

Value

Object of class CEMiTool containing qqplot

Examples

```
# Get example CEMiTool object
data(cem)
# Plot quantile-quantile plot
cem <- plot_qq(cem)
# Check results
show_plot(cem, 'qq')
```

plot_sample_tree *Sample clustering*

Description

Creates a dendrogram showing the similarities between samples in the expression data.

Usage

```
plot_sample_tree(cem, ...)

## S4 method for signature 'CEMiTool'
plot_sample_tree(
  cem,
  col_vector = NULL,
  sample_name_column = NULL,
  class_column = NULL,
  filter = FALSE
)
```

Arguments

<code>cem</code>	Object of class CEMiTool or <code>data.frame</code> .
<code>...</code>	Optional parameters.
<code>col_vector</code>	A vector of columns to use for visualizing the clustering. See Details.
<code>sample_name_column</code>	A string specifying the column to be used as sample identification. For CEMiTool objects, this will be the string specified in the <code>sample_name_column</code> slot.
<code>class_column</code>	A string specifying the column to be used as sample group identification. For CEMiTool objects, this will be the string specified in the <code>class_column</code> slot.
<code>filter</code>	Logical. Whether or not to use filtered data for CEMiTool objects (Default: <code>FALSE</code>).

Value

Object of class CEMiTool with dendrogram or a plot object.

Examples

```
# Get example CEMiTool object
data(cem)
# Plot sample dendrogram
cem <- plot_sample_tree(cem)
# Check resulting plot
show_plot(cem, "sample_tree")
```

read_gmt*Read a GMT file*

Description

Read a GMT file

Usage

```
read_gmt(fname)
```

Arguments

fname GMT file name.

Value

A list containing genes and description of each pathway

Examples

```
# Read example gmt file
gmt_fname <- system.file("extdata", "pathways.gmt", package = "CEMiTool")
gmt_in <- read_gmt(gmt_fname)
```

sample_annot*Yellow Fever Sample Annotation data*

Description

Modified data from a yellow fever vaccination study by Querec et al, 2009. This dataset, together with expr can be used as input for CEMiTool functions

Usage

```
data(sample_annot)
```

Format

An object of class `data.frame`

Source

GEO

References

Querec TD, Akondy RS, Lee EK, Cao W et al. Systems biology approach predicts immunogenicity of the yellow fever vaccine in humans. *Nat Immunol* 2009 Jan;10(1):116-25. PMID: 19029902
[PubMed](#)

Examples

```
data(expr)
data(sample_annot)
# Run CEMiTool analysis
## Not run: cemitool(expr, sample_annot)
```

sample_annotation	<i>Retrieve or set the sample_annotation attribute</i>
-------------------	--

Description

Retrieve or set the sample_annotation attribute

Usage

```
sample_annotation(cem)

## S4 method for signature 'CEMiTool'
sample_annotation(cem)

sample_annotation(
  cem,
  sample_name_column = "SampleName",
  class_column = "Class"
) <- value

## S4 replacement method for signature 'CEMiTool'
sample_annotation(
  cem,
  sample_name_column = "SampleName",
  class_column = "Class"
) <- value
```

Arguments

<code>cem</code>	Object of class CEMiTool
<code>sample_name_column</code>	A string containing the name of a column which should be used as a unique identifier for samples in the file. Only used when assigning a sample annotation data.frame. Default: "SampleName".
<code>class_column</code>	A string containing the name of a column which should be used to identify different sample groups. Only used when assigning a sample annotation data.frame. Default: "Class"
<code>value</code>	A data.frame containing the sample annotation, should have at least two columns containing the Class and the Sample Name that should match with samples in expression

Value

A data.frame containing characteristics of each sample.

Examples

```
# Get example expression data
data(expr0)
# Get example sample_annotation data
data(sample_annot)
# Initialize CEMiTool object with expression
cem <- new_cem(expr0)
# Add sample annotation file to CEMiTool object
sample_annotation(cem,
  sample_name_column="SampleName",
  class_column="Class") <- sample_annot
# Check annotation
head(sample_annotation(cem))
```

save_plots

Save CEMiTool object plots

Description

Save plots into the directory specified by the `directory` argument.

Usage

```
save_plots(cem, ...)

## S4 method for signature 'CEMiTool'
save_plots(
  cem,
  value = c("all", "profile", "gsea", "ora", "interaction", "beta_r2", "mean_k",
    "sample_tree", "mean_var", "hist", "qq"),
  force = FALSE,
  directory = "./Plots"
)
```

Arguments

<code>cem</code>	Object of class CEMiTool.
<code>...</code>	Optional parameters One of "all", "profile", "gsea", "ora", "interaction", "beta_r2", "mean_k", "sample_tree", "mean_var", "hist", "qq".
<code>value</code>	A character string containing the name of the plot to be saved.
<code>force</code>	If the directory exists, execution will not stop.
<code>directory</code>	Directory into which the files will be saved.

Value

A pdf file or files with the desired plot(s)

Examples

```
# Get example CEMiTool object
data(cem)
# Plot beta x R squared graph
cem <- plot_beta_r2(cem)
# Save plot
## Not run: save_plots(cem, value="beta_r2", directory="./Plots")
```

select_genes

Select genes based on variance

Description

Select genes based on variance

Usage

```
select_genes(expr, n_genes, filter_pval = 0.1)
```

Arguments

expr	A data.frame containing expression values
n_genes	(Optional) Number of genes to be selected
filter_pval	P-value cutoff for gene selection

Value

A vector containing the names of selected genes

Examples

```
# Get example expression data
data(expr0)
# Filter genes
expr_f <- filter_genes(expr0)
# Check selected genes
expr_f[1:5, 1:5]
# Filter genes and apply variance stabilizing transformation
expr_f2 <- filter_genes(expr0, apply_vst=TRUE)
# Check results
expr_f2[1:5, 1:5]
# Selected genes
selected <- select_genes(expr_f2)
# Get data.frame with only selected genes
expr_s <- expr_f2[selected, ]
# Check results
expr_s[1:5, 1:5]
```

show,CEMiTool-method *Print a cemitool object*

Description

Print a cemitool object

Usage

```
## S4 method for signature 'CEMiTool'  
show(object)
```

Arguments

object Object of class CEMiTool

Value

A CEMiTool object.

show_plot *Retrieve CEMiTool object plots*

Description

Retrieve CEMiTool object plots

Usage

```
show_plot(cem, value)  
  
## S4 method for signature 'CEMiTool'  
show_plot(  
  cem,  
  value = c("profile", "gsea", "ora", "interaction", "beta_r2", "mean_k",  
          "sample_tree", "mean_var", "hist", "qq"))  
)
```

Arguments

cem Object of class CEMiTool.
value A character string containing the name of the plot to be shown. One of "profile", "gsea", "ora", "interaction", "beta_r2", "mean_k", "sample_tree", "mean_var", "hist", "qq".

Value

A plot corresponding to a CEMiTool analysis

Examples

```
# Get example CEMiTool object
data(cem)
# Plot beta x R squared graph
cem <- plot_beta_r2(cem)
# Check plot
show_plot(cem, "beta_r2")
```

vst

Perform variance stabilizing transformation on expression file.

Description

Perform variance stabilizing transformation on expression file.

Usage

```
vst(expr)
```

Arguments

expr	expression file containing genes in the rows and samples in the columns
------	---

Value

A data.frame containing the results.

write_files

Save the CEMiTool object in files

Description

Save the CEMiTool object in files

Usage

```
write_files(cem, ...)
## S4 method for signature 'CEMiTool'
write_files(cem, directory = "./Tables", force = FALSE)
```

Arguments

cem	Object of class CEMiTool
...	Optional parameters
directory	a directory
force	if the directory exists the execution will not stop

Value

A directory containing CEMiTool results in files.

Examples

```
# Get example CEMiTool object
data(cem)
# Save CEMiTool results in files
write_files(cem, directory=".", force=TRUE)
```

Index

- * datasets
 - expr0, 8
 - sample_annot, 39
- * data
 - cem, 4
- * internal
 - expr_pct_filter, 10
 - module_to_gmt, 23
 - plot_ora_single, 35
 - vst, 44
- adj_data, 3
- adj_data, CEMiTool-method (adj_data), 3
- adj_data<- (adj_data), 3
- adj_data<-, CEMiTool-method (adj_data), 3
- cem, 4
- cemitool, 4
- CEMiTool-class, 7
- diagnostic_report, 8
- diagnostic_report, CEMiTool-method (diagnostic_report), 8
- expr0, 8
- expr_data, 9
- expr_data, CEMiTool-method (expr_data), 9
- expr_data<- (expr_data), 9
- expr_data<-, CEMiTool-method (expr_data), 9
- expr_pct_filter, 10
- filter_genes, 10
- find_modules, 11
- find_modules, CEMiTool-method (find_modules), 11
- fit_data, 13
- fit_data, CEMiTool-method (fit_data), 13
- generate_report, 13
- generate_report, CEMiTool-method (generate_report), 13
- get_adj, 14
- get_adj, CEMiTool-method (get_adj), 14
- get_beta_data, 15
- get_beta_data, CEMiTool-method (get_beta_data), 15
- get_cemitool_r2_beta, 16
- get_cemitool_r2_beta, CEMiTool-method (get_cemitool_r2_beta), 16
- get_connectivity, 17
- get_connectivity, CEMiTool-method (get_connectivity), 17
- get_hubs, 17
- get_hubs, CEMiTool-method (get_hubs), 17
- get_merged_mods, 18
- get_merged_mods, CEMiTool-method (get_merged_mods), 18
- get_mods, 19
- get_mods, CEMiTool-method (get_mods), 19
- get_phi, 20
- get_phi, CEMiTool-method (get_phi), 20
- gsea_data, 21
- gsea_data, CEMiTool-method (gsea_data), 21
- interactions_data, 21
- interactions_data, CEMiTool-method (interactions_data), 21
- interactions_data<- (interactions_data), 21
- interactions_data<-, CEMiTool-method (interactions_data), 21
- mod_colors, 23
- mod_colors, CEMiTool-method (mod_colors), 23
- mod_colors<- (mod_colors), 23
- mod_colors<-, CEMiTool, character-method (mod_colors), 23
- mod_gene_num, 24
- mod_gene_num, CEMiTool-method (mod_gene_num), 24
- mod_gsea, 25
- mod_gsea, CEMiTool-method (mod_gsea), 25
- mod_names, 26
- mod_names, CEMiTool-method (mod_names), 26
- mod_ora, 26

mod_ora, CEMiTool-method (mod_ora), 26
mod_summary, 27
mod_summary, CEMiTool-method
(mod_summary), 27
module_genes, 22
module_genes, CEMiTool-method
(module_genes), 22
module_to_gmt, 23
new_cem, 28
nmodules, 29
nmodules, CEMiTool-method (nmodules), 29
ora_data, 27, 29
ora_data, CEMiTool-method (ora_data), 29
plot_beta_r2, 30
plot_beta_r2, CEMiTool-method
(plot_beta_r2), 30
plot_gsea, 25, 31
plot_gsea, CEMiTool-method (plot_gsea),
31
plot_hist, 32
plot_hist, CEMiTool-method (plot_hist),
32
plot_interactions, 32
plot_interactions, CEMiTool-method
(plot_interactions), 32
plot_mean_k, 33
plot_mean_k, CEMiTool-method
(plot_mean_k), 33
plot_mean_var, 34
plot_mean_var, CEMiTool-method
(plot_mean_var), 34
plot_ora, 35
plot_ora, CEMiTool-method (plot_ora), 35
plot_ora_single, 35
plot_profile, 36
plot_profile, CEMiTool-method
(plot_profile), 36
plot_qq, 37
plot_qq, CEMiTool-method (plot_qq), 37
plot_sample_tree, 38
plot_sample_tree, CEMiTool-method
(plot_sample_tree), 38
read_gmt, 39
sample_annotation, 39
sample_annotation, 40
sample_annotation, CEMiTool-method
(sample_annotation), 40
sample_annotation<–
(sample_annotation), 40
sample_annotation<–, CEMiTool-method
(sample_annotation), 40
save_plots, 41
save_plots, CEMiTool-method
(save_plots), 41
select_genes, 42
show, CEMiTool-method, 43
show_plot, 43
show_plot, CEMiTool-method (show_plot),
43
vst, 44
write_files, 44
write_files, CEMiTool-method
(write_files), 44