

Package ‘MACSQuantifyR’

March 31, 2025

Type Package

Title Fast treatment of MACSQuantify FACS data

Date 08/10/2019

Version 1.20.0

Author Raphaël Bonnet [aut, cre], Marielle Nebout [dtc], Giulia Biondani [dtc], Jean-François Peyron[aut,ths], Inserm [fnd]

Maintainer Raphaël Bonnet <raphael.bonnet@univ-cotedazur.fr>

Description Automatically process the metadata of MACSQuantify FACS sorter.

It runs multiple modules: i) imports of raw file and graphical selection of duplicates in well plate, ii) computes statistics on data and iii) can compute combination index.

Imports readxl, graphics, tools, utils, grDevices, ggplot2, ggrepel, methods, stats, latticeExtra, lattice, rmarkdown, png, grid, gridExtra, prettydoc, rvest, xml2

biocViews DataImport, Preprocessing, Normalization, FlowCytometry, DataRepresentation, GUI

License Artistic-2.0

Encoding UTF-8

LazyData true

RoxygenNote 7.1.0

Suggests knitr, testthat, R.utils, spelling

VignetteBuilder knitr

Language en-US

git_url <https://git.bioconductor.org/packages/MACSQuantifyR>

git_branch RELEASE_3_20

git_last_commit 80761e4

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-03-31

Contents

barplot_data	2
combination_index	3
generate_report	4
load_MACSQuant	4
MACSQuant	5
new_class_MQ	5
on_plate_selection	7
pipeline	7
rData	8
setPath	9
sorted	9

Index

11

barplot_data	<i>Generate barplots</i>
--------------	--------------------------

Description

Uses the informations stored in the statistic tables of the MACSQuant object to generate barplots for the specified conditions. Plots can also be saved in the form of a png file in the output_MQ directory.

Usage

```
barplot_data(MACSQuant,plt.col=NULL,plt.conditions=NULL, plt.flavour=NULL,
plt.labels = NULL, plt.combo=FALSE,plt.3D.only = NULL,...)
```

Arguments

MACSQuant	object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
plt.col	In case of manual run is used to define the bar colors. (must be the same for all conditions)
plt.conditions	user defined vector of conditions to plot (example: plt.conditions=c(1:9))
plt.flavour	Which barplot to produce, cell count or percentage of fluorochrome (i.e: "counts","percent")
plt.labels	xlabels of the plot
plt.combo	Does the experiment involves multiple variables (i.e some condition are a drug combination screening)
plt.3D.only	Whether to plot 3D barplot alone
...	params for lattice cloud namely z and x for parameter screen default for z and x are c(-110,-70) and argument xlab and ylab

Value

returns a barplot of the data

Examples

```

drugs_R_image <- system.file("extdata",
  "drugs.RDS",
  package = "MACSQuantifyR")
MACSQuant <- readRDS(drugs_R_image)
flavour <- "counts"
number_of_conditions <-
  slot(MACSQuant, "param.experiment")$number_of_conditions
plt.col <- c(rep(2, number_of_conditions), 1)
barplot_data(MACSQuant,
  plt.col = plt.col,
  plt.conditions = NULL,
  plt.flavour = flavour,
  plt.labels = NULL,
  plt.combo = FALSE)

```

combination_index *compute combination index*

Description

This function allows the user to compute combination index on the drug combinations. This function also generates intermediary plots and tables.

Usage

```
combination_index(MACSQuant, ...)
```

Arguments

MACSQuant	object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
...	params for lattice cloud namely z and x for parameter screen default for z and x are c(-110,-70) and argument xlab and ylab

Value

Several plots and combination index

References

Chou, T. C. (2006). Theoretical basis, experimental design, and computerized simulation of synergism and antagonism in drug combination studies. *Pharmacological reviews*, 58(3), 621-681.

Examples

```

filepath <- system.file("extdata", "drugs.Rdata",
  package = "MACSQuantifyR")
load(filepath)
combination_index(MACSQuant)

```

generate_report	<i>Word report generation</i>
-----------------	-------------------------------

Description

Allows the user to generate a report at every steps of the analysis
Also generates a complete report with the graphics

Usage

```
generate_report(MACSQuant)
```

Arguments

MACSQuant	object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
-----------	---

Value

A formatted report

Examples

```
drugs_R_image <- system.file("extdata",
  "drugs.RDS",
  package = "MACSQuantifyR")
MACSQuant <- readRDS(drugs_R_image)
generate_report(MACSQuant)
```

load_MACSQuant	<i>Load xls file from maxQuant 96-well-plate device</i>
----------------	---

Description

Load xls file from maxQuant 96-well-plate device

Usage

```
load_MACSQuant(filepath,sheet_name= NULL,MACSQuant.obj= NULL)
```

Arguments

filepath	path of the excel file
sheet_name	Name of the sheet to load (optional, first sheet is default)
MACSQuant.obj	object of class MACSQuant

Value

An object called MACSQuant of class MACSQuant containing variable my_data that corresponds to the data of the excel file in R

Examples

```
filepath <- system.file("extdata", "SingleDrugs.xlsx",
  package = "MACSQuantifyR")
# load_MACSQuant(filepath)
```

MACSQuant

The MACSQuant Class

Description

MACSQuant object contains all the data and the user parameters

Slots

- `my_data` Contains the raw data
- `my_data_sorted` Contains the sorted data (according to replicates order)
- `my_replicates_sorted` Contains the sorted matrix containing replicates names
- `experiment_name` Contains the experiment name given by the user
- `statistics` Contains the statistics for each condition
- `combination.index.df` data.frame that contains the outputs of the combination_index function
- `param.experiment` list that contains the parameters relative to the experiment (i.e, number of replicates, number of conditions...)
- `param.output` List that contains the parameters relative to the report generation and outputs (i.e, save intermediary results, generate full report..)

new_class_MQ

Create a new MACSQuant object

Description

The user can create a new custom MACSQuant object This function is also used in internal code for MACSQuant initialization

Usage

```
#initialize empty MACSQuant object
new_class_MQ(my_data=NULL,my_data_sorted=NULL,my_replicates_sorted=NULL,
experiment_name=NULL,statistics=NULL,combination.index.df=NULL,
number_of_replicates=NULL,number_of_conditions=NULL,doses=NULL,
doses.alt=NULL,c_names=NULL, control=NULL,plt.title=NULL,
plt.labels=NULL,plt.col=NULL,save.files=NULL,path=tempdir())
#initialize custom MACSQuant object
new_class_MQ(my_data,my_data_sorted=NULL,my_replicates_sorted=NULL,
experiment_name=NULL,statistics=NULL,combination.index.df=NULL,
number_of_replicates=NULL,number_of_conditions=NULL,
doses=NULL,doses.alt=NULL, c_names=NULL,control=NULL,plt.title=NULL,
plt.labels=NULL,plt.col=NULL, save.files=NULL,path=tempdir())
```

Arguments

my_data Contains the raw data
 my_data_sorted Contains the sorted data (according to replicates order)
 my_replicates_sorted
 Contains the sorted matrix containing replicates names
 experiment_name
 User defined experiment named. Used for the report generation
 statistics Contains the statistics for each condition
 combination.index.df
 data.frame that contains the outputs of the combination_index function
 number_of_replicates
 For each condition, the number of duplicates (must be the same for all conditions)
 number_of_conditions
 The number of conditions tested (eg: Drug 1 alone, Drug 2 alone)
 doses Numeric vector representing doses for each conditions
 doses.alt In case of interaction test second dose vector
 c_names Vector containing experiment names
 control logical: is there a control in this experiment (eg: Staurosporin)
 plt.title Title of the experiment to add to the barplot
 plt.labels legend labels for the bar plot
 plt.col color vector for the graphical representations
 save.files Used to save the image in the output folder
 path path of the experiment output folder (default ':')

Value

A formatted report file along with intermediates results

Examples

```

# initialize empty MACSQuant object
new_class_MQ()
# initialize custom MACSQuant object
my_data <- data.frame(character(length = 10), character(length = 10),
                      numeric(length = 10), numeric(length = 10))
names(my_data) <- c("Full path", "WID", "%-#", "Count/mL")
new_class_MQ(my_data)
  
```

on_plate_selection *Sort experimental design on graphical 96-well-plate*

Description

Loads user's data, prompt a graphical representation of a 96 well plate and let the user select where the duplicates of each condition were placed. Use for reordering excel file. Plate image with selection can also be saved in the form of a png file in the "specified_path/output_MQ" directory.

Usage

```
on_plate_selection(MACSQuant, number_of_replicates, number_of_conditions,  
control=FALSE, save.files=FALSE)
```

Arguments

MACSQuant object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
number_of_replicates For each condition, the number of duplicates (must be the same for all conditions)
number_of_conditions The number of conditions tested (eg: Drug 1 alone, Drug 2 alone)
control Is there a control in this experiment (eg: Staurosporin)
save.files Used to save the image in the output folder

Value

A formatted report file along with intermediates results

Examples

```
print("run manually, requires user input")  
# on_plate_selection(MACSQuant,3,5)  
# let you select 5 conditions of 3 replicates each
```

pipeline *pipeline with report generation*

Description

Loads user's data, prompt a graphical representation of a 96 well plate and let the user select where the duplicates of each condition were placed. Use for reordering excel file. Plate image with selection can also be saved in the form of a png file in the output_MQ directory.

Also generates a complete report with the graphics

Usage

```
pipeline(filepath, sheet_name=NULL, number_of_replicates, number_of_conditions,  
control=FALSE, save.files=TRUE, MACSQuant.obj=NULL)
```

Arguments

filepath path of the excel file
 sheet_name Name of the sheet to load (optional, first sheet is default)
 number_of_replicates
 For each condition, the number of duplicates (must be the same for all conditions)
 number_of_conditions
 The number of conditions tested (eg: Drug 1 alone, Drug 2 alone)
 control Is there a control in this experiment (eg: Staurosporin)
 save.files Used to save the image in the output folder
 MACSQuant.obj object of class MACSQuant

Value

A formatted report file along with intermediates results

Examples

```

print("run manually, requires user input")
filepath <- system.file("extdata", "SingleDrugs.xlsx",
  package = "MACSQuantifyR")
# pipeline(filepath,3,5)
# let you select 5 conditions of 3 replicates each
  
```

rData

accessor function to access raw data

Description

This function allows the user to access raw data table

Usage

```
rData(MACSQuant)
```

Arguments

MACSQuant object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table

Value

the raw data table

Examples

```

filepath <- system.file("extdata", "SingleDrugs.xlsx",
  package = "MACSQuantifyR")
#MACSQuant = load_MACSQuant(filepath)

#rData(MACSQuant)
  
```

setPath	<i>sets custom output path</i>
---------	--------------------------------

Description

This function allows the user to set the output directory path

Usage

```
setPath(MACSQuant, path=NULL)
```

Arguments

MACSQuant	object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
path	user defined path, default is tempd

Value

object of class MACSQuant with updated path

Examples

```
filepath <- system.file("extdata", "SingleDrugs.xlsx",
                        package = "MACSQuantifyR")
#MACSQuant = load_MACSQuant(filepath)
user_path = "."
#MACSQuant = setPath(MACSQuant, path=user_path)
```

sorted	<i>accessor function to access sorted data</i>
--------	--

Description

This function allows the user to access sorted data table

Usage

```
sorted(MACSQuant)
```

Arguments

MACSQuant	object of class MACSQuant resulting of the function load_maxQuant(). Contains the original data table
-----------	---

Value

the raw data table

Examples

```
filepath <- system.file("extdata", "SingleDrugs.xlsx",
  package = "MACSQuantifyR")
#MACSQuant = load_MACSQuant(filepath)

#sorted(MACSQuant)
```

Index

barplot_data, 2
combination_index, 3
generate_report, 4
load_MACSQuant, 4
MACSQuant, 5
MACSQuant-class (MACSQuant), 5
new_class_MQ, 5
on_plate_selection, 7
pipeline, 7
rData, 8
setPath, 9
sorted, 9