

Package ‘multiWGCNA’

April 1, 2025

Type Package

Title multiWGCNA

Version 1.4.0

Description An R package for deeping mining gene co-expression networks in multi-trait expression data. Provides functions for analyzing, comparing, and visualizing WGCNA networks across conditions. multiWGCNA was designed to handle the common case where there are multiple biologically meaningful sample traits, such as disease vs wildtype across development or anatomical region.

License GPL-3

Encoding UTF-8

LazyData true

Suggests BiocStyle, doParallel, ExperimentHub, knitr, markdown, rmarkdown, testthat (>= 3.0.0), vegan

VignetteBuilder knitr

RoxxygenNote 7.2.3

biocViews Sequencing, RNASeq, GeneExpression, DifferentialExpression, Regression, Clustering

Imports stringr, readr, WGCNA, dplyr, reshape2, data.table, patchwork, scales, igraph, flashClust, ggplot2, dcanr, cowplot, ggrepel, methods, SummarizedExperiment

Depends R (>= 4.3.0), ggalluvial

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/multiWGCNA>

git_branch RELEASE_3_20

git_last_commit 870ea52

git_last_commit_date 2024-10-29

Repository Bioconductor 3.20

Date/Publication 2025-03-31

Author Dario Tommasini [aut, cre] (<<https://orcid.org/0000-0002-1214-6547>>), Brent Fogel [aut, ctb]

Maintainer Dario Tommasini <dtommasini0@gmail.com>

Contents

multiWGCNA-package	2
bidirectionalBestMatches	3
cleanDatExpr	3
coexpressionLineGraph	4
computeOverlapsFromWGCNA	5
constructNetworks	6
diffCoexpression	7
diffModuleExpression	8
drawMultiWGCNAnetwork	9
GetDatExpr	11
getPreservation	11
iterate	12
makeTraitTable	13
moduleComparisonPlot	13
moduleExpressionPlot	14
moduleToModuleHeatmap	15
name	16
overlapComparisons	16
performANOVA	17
permutationTestResults	18
preservationComparisonPlot	18
preservationComparisons	19
PreservationPermutationTest	20
PreservationScoreDistribution	22
runDME	23
summarizeResults	24
TOMFlowPlot	25
topNGenes	25
WGCNA-class	26

Index

27

multiWGCNA-package *multiWGCNA: multiWGCNA*

Description

An R package for deeping mining gene co-expression networks in multi-trait expression data. Provides functions for analyzing, comparing, and visualizing WGCNA networks across conditions. multiWGCNA was designed to handle the common case where there are multiple biologically meaningful sample traits, such as disease vs wildtype across development or anatomical region.

Author(s)

Maintainer: Dario Tommasini <dtommasini0@gmail.com> ([ORCID](#))

Authors:

- Brent Fogel [contributor]

bidirectionalBestMatches
Best matching modules

Description

Find all the modules from dataset1 that have a best match to a module in dataset2 if that module in dataset2 is also a best match to the module in dataset1

Usage

```
bidirectionalBestMatches(comparisonList, plot = TRUE)
```

Arguments

comparisonList a list with an elemnt "overlap", which is a data.frame resulting from a call to computeOverlapsFromWGCNA
plot whether to generate a heatmap; default is TRUE

Value

A ggplot object

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdat"))
astrocyte_networks = eh_query[["EH8222"]]
comparisonList = list()
comparisonList$overlaps = computeOverlapsFromWGCNA(astrocyte_networks$EAE, astrocyte_networks$WT)
bidirectionalBestMatches(comparisonList)
```

cleanDatExpr *cleanDatExpr*

Description

A function that converts a data.frame where row 1 is gene symbols to a numeric matrix where columns are genes and rows are samples for compatibility with most WGCNA functions.

Usage

```
cleanDatExpr(datExpr, checkGenesSamples = FALSE)
```

Arguments

- `datExpr` a data.frame were columns are samples and rows are samples and the gene symbols are in the first row
`checkGenesSamples` call the WGCNA function checkGenesSamples?

Value

Returns a datExpr with rows as samples and columns as genes

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdat"))
astrocyte_se = eh_query[["EH8223"]]
datExpr = data.frame(X = rownames(assays(astrocyte_se)[[1]]), assays(astrocyte_se)[[1]])
cleanDatExpr(datExpr)
```

*coexpressionLineGraph Coexpression Line Graph***Description**

Plots a line graph showing the co-expression of selected genes across samples

Usage

```
coexpressionLineGraph(datExpr, splitBy = 1, fontSize = 2.15, colors = NULL)
```

Arguments

- `datExpr` a data.frame with genes as rows and samples as columns
`splitBy` how much to split genes by on line graph
`fontSize` the font size of the gene labels
`colors` a vector of colors; default is random colors generated by colors function

Value

a ggplot object

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
datExpr = GetDatExpr(astrocyte_networks[[1]],
genes = topNGenes(astrocyte_networks$EAE, "EAE_015", 20))
coexpressionLineGraph(datExpr) +
geom_vline(xintercept = 20.5, linetype='dashed')
```

computeOverlapsFromWGCNA

computeOverlapsFromWGCNA

Description

Computes overlap between the modules of two objects of class WGCNA

Usage

```
computeOverlapsFromWGCNA(dataset1, dataset2)
```

Arguments

dataset1	an object of class WGCNA to compare with dataset2
dataset2	an object of class WGCNA to compare with dataset1

Value

Returns a data.frame showing the overlap results for modules from dataset1 with dataset2

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
computeOverlapsFromWGCNA(astrocyte_networks$EAE, astrocyte_networks$WT)
```

constructNetworks	<i>constructNetworks: Construct all the weighted gene correlation networks</i>
-------------------	--

Description

A high level function that returns all networks possible for a given experimental design

Usage

```
constructNetworks(
  datExpr,
  sampleTable,
  conditions1,
  conditions2,
  write = FALSE,
  alphaLevel = 0.05,
  plot = FALSE,
  ...
)
```

Arguments

datExpr	either a SummarizedExperiment object or data.frame with genes are rows and samples as columns
sampleTable	data.frame with sample names in first column and sample traits in the second and third column. First column should be called "Sample"
conditions1	first design conditions, ie healthy/disease
conditions2	second design conditions, ie frontal lobe/temporal lobe
write	write results out to files?
alphaLevel	significance value passed to findBestTrait function, default is 0.05
plot	plot modules? Default is false
...	Arguments to pass to blockwiseModules function

Value

A list of WGCNA objects, ie level one, two, and three networks.

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdat"))
autism_se = eh_query[["EH8219"]]
set.seed(1)
autism_se = autism_se[sample(rownames(autism_se), 500),]
```

```

sampleTable = colData(autism_se)
conditions1 = unique(sampleTable[,2])
conditions2 = unique(sampleTable[,3])
autism_networks = constructNetworks(autism_se, sampleTable, conditions1[[1]], conditions2[[1]],
    networkType = "signed", TOMType = "unsigned",
    power = 10, minModuleSize = 100, maxBlockSize = 25000,
    reassessThreshold = 0, minKMEtoStay = 0, mergeCutHeight = 0,
    numericLabels = TRUE, pamRespectsDendro = FALSE,
    deepSplit = 4, verbose = 3)
autism_networks[["combined"]]

```

diffCoexpression*Differential co-expression analysis***Description**

Performs a differential co-expression analysis given an expression data.frame and a conditions vector

Usage

```

diffCoexpression(
  datExpr,
  conditions,
  geneList = NULL,
  plot = FALSE,
  method = c("pearson", "spearman"),
  removeFreeNodes = TRUE,
  labelSize = 0.5,
  labelDist = 0,
  shape = "circle",
  degreeForSize = FALSE,
  label = FALSE,
  onlyPositive = FALSE,
  z.threshold = NULL,
  FDR.threshold = 0.05,
  nodeSize = 3
)

```

Arguments

<code>datExpr</code>	a data.frame containing expression values
<code>conditions</code>	a vector containing conditions for the samples
<code>geneList</code>	vector of genes, will use all genes if NULL (default)
<code>plot</code>	plot a network?
<code>method</code>	either "pearson" or "spearman"
<code>removeFreeNodes</code>	remove free nodes from network?
<code>labelSize</code>	label size

```

labelDist      distance from labels to nodes
shape          shape of nodes
degreeForSize should node size correspond to degree?
label          label nodes?
onlyPositive   only draw positive correlations?
z.threshold    z-score threshold
FDR.threshold FDR threshold
nodeSize       size of node

```

Value

A list including a matrix of z-scores, a matrix of raw p-values, a matrix of adjusted p-values, and a summary data.frame

Author(s)

Dario Tommasini

Examples

```

library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_se = eh_query[["EH8223"]]
datExpr = assays(astrocyte_se)[[1]]
diffCoexpression(datExpr, c(rep(1,20), rep(2,16)),
  geneList = c("Gfap", "Vim", "Aspg", "Serpina3n", "Cp", "Osmr", "Cd44",
  "Cxcl10", "Hspb1", "Timp1", "S1pr3", "Stear4", "Lcn2"))

```

diffModuleExpression Differential module expression

Description

Runs (and plots) the differential module expression analysis

Usage

```

diffModuleExpression(
  WGCNAobject,
  geneList,
  design,
  plotTitle = NULL,
  mode = c("PC1", "Zscore"),
  testColumn = 2,
  refColumn = 3,
  test = c("ANOVA", "PERMANOVA"),
  plot = TRUE
)

```

Arguments

WGCNAobject	WGCNA object
geneList	vector of genes in WGCNAobject
design	the sampleTable
plotTitle	title for the plot
mode	either PC1 or Zscore, default is PC1
testColumn	the column of the sampleTable to be resolved
refColumn	the column of the sampleTable to be used as biological variation
test	statistical test to perform, either "ANOVA" or "PERMANOVA"
plot	generate a plot?

Value

a data.frame with the resulting p-values

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_se = eh_query[["EH8223"]]
sampleTable = colData(astrocyte_se)
astrocyte_networks = eh_query[["EH8222"]]
diffModuleExpression(astrocyte_networks[["combined"]],
  topNGenes(astrocyte_networks$combined, "combined_013"),
  sampleTable,
  test = "ANOVA",
  plotTitle = "combined_013",
  plot = TRUE)
```

drawMultiWGCNAnetwork *Draw multiWGCNA network*

Description

Draw a network where nodes are modules and edges represent significant gene overlap. Modules are sorted by levels 1, 2, and 3.

Usage

```
drawMultiWGCNAnetwork(
  WGCNAlist,
  comparisonList,
  moduleOfInterest,
  design,
  overlapCutoff = 0,
  padjCutoff = 1,
  removeOutliers = TRUE,
  alpha = 1e-50,
```

```

  layout = NULL,
  hjust = 0.4,
  vjust = 0.3,
  width = 0.5,
  colors = NULL
)

```

Arguments

<code>WGCNAList</code>	list of WGCNA objects
<code>comparisonList</code>	the list of overlap comparisons ie from iterate(myNetworks, overlapComparisons, ...)
<code>moduleOfInterest</code>	module of interest, ie "combined_001"
<code>design</code>	the sampleTable design matrix
<code>overlapCutoff</code>	cutoff to remove module correspondences with less than this number of genes
<code>padjCutoff</code>	cutoff to remove module correspondences above this significance value
<code>removeOutliers</code>	remove outlier modules?
<code>alpha</code>	alpha level of significance
<code>layout</code>	layout of network to be passed to plot function of igraph object, defaults to multiWGCNA custom layout
<code>hjust</code>	horizontal justification of labels
<code>vjust</code>	vertical justification of labels
<code>width</code>	width of labels
<code>colors</code>	colors to use for modules, should be the same length as the number of WGCNA objects in the WGCNAList. Defaults to random colors for each condition.

Value

an igraph plot

Author(s)

Dario Tommasini

Examples

```

library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_se = eh_query[["EH8223"]]
sampleTable = colData(astrocyte_se)
astrocyte_networks = eh_query[["EH8222"]]
results = list()
results$overlaps = iterate(astrocyte_networks, overlapComparisons, plot=FALSE)
drawMultiWGCNAnetwork(astrocyte_networks,
  results$overlaps,
  "combined_013",
  sampleTable)

```

GetDatExpr	<i>Get expression data</i>
------------	----------------------------

Description

Returns the expression data frame a WGCNA object as a data.frame

Usage

```
GetDatExpr(object, genes = NULL)
```

Arguments

object	An object of class WGCNA
genes	a list of genes to subset to; default is NULL

Value

a data.frame

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
datExpr = GetDatExpr(astrocyte_networks[[1]],
  genes = topNGenes(astrocyte_networks$EAE, "EAE_015", 20))
coexpressionLineGraph(datExpr) +
  geom_vline(xintercept = 20.5, linetype='dashed')
```

getPreservation	<i>getPreservation</i>
-----------------	------------------------

Description

Performs a network preservation analysis

Usage

```
getPreservation(reference, test, nPermutations = 100, write = FALSE)
```

Arguments

<code>reference</code>	reference network of class WGCNA
<code>test</code>	test network of class WGCNA
<code>nPermutations</code>	number of permutations to perform; at least 50 permutations
<code>write</code>	write to file?

Value

a data.frame summarizing results of preservation analysis

Author(s)

Dario Tommasini

<code>iterate</code>	<i>iterate: Iterate function across networks</i>
----------------------	--

Description

A high level function that iterates functions across a list of WGCNA objects

Usage

```
iterate(WGCNAlist, FUN, ...)
```

Arguments

<code>WGCNAlist</code>	a vector of objects of type WGCNAobject
<code>FUN</code>	function to iterate, either overlapComparisons or preservationComparisons
<code>...</code>	argmuents to be passed on to overlapComparisons or preservationComparisons

Value

a comparison list from overlapComparisons or preservationComparisons

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
results = list()
iterate(astrocyte_networks, overlapComparisons, plot=FALSE)
```

makeTraitTable *Generate a trait table from a sample table*

Description

Generates a WGCNA-compatible trait table from a sampleTable dataframe

Usage

```
makeTraitTable(inputTable, column, detectNumbers = FALSE)
```

Arguments

- | | |
|---------------|--|
| inputTable | the sampleTable data.frame |
| column | the column from the sampleTable to use as traits |
| detectNumbers | whether to consider traits with numbers as numerical rather than categorical variables |

Value

a data.frame with integer values denoting the categorical sample traits

Examples

```
sampleTable = data.frame(Sample = c(paste0("EAE", 1:10), paste0("WT", 1:10)),
                         Disease = c(rep("EAE", 10), rep("WT", 10)),
                         Region = c(rep(c("Cbl", "Sc"), 5)))
makeTraitTable(sampleTable, 2)
```

moduleComparisonPlot *Module comparison plot*

Description

A plotting function that returns a heatmap and barplot for a module

Usage

```
moduleComparisonPlot(overlapDf, dataset1, dataset2)
```

Arguments

- | | |
|-----------|--|
| overlapDf | a data.frame resulting from a call to computeOverlapsFromWGCNA |
| dataset1 | an object of class WGCNA to compare with dataset2 |
| dataset2 | an object of class WGCNA to compare with dataset1 |

Value

Returns a ggplot object (flowplot and heatmap) showing the module correspondence between two objects of class WGCNA

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
overlapDf = computeOverlapsFromWGCNA(astrocyte_networks$EAE, astrocyte_networks$WT)
moduleComparisonPlot(overlapDf, astrocyte_networks$EAE, astrocyte_networks$WT)
```

moduleExpressionPlot *Plots an expression profile for a module*

Description

A plotting function that returns a heatmap and barplot for a module

Usage

```
moduleExpressionPlot(
  WGCNAobject,
  geneList,
  mode = c("PC1", "averageZscore"),
  legend = FALSE,
  title = NULL,
  clusterGenes = FALSE
)
```

Arguments

WGCNAobject	an object of class WGCNAobject
geneList	a vector of gene names to be extracted from WGCNAobject
mode	use first principal component or averageZscore?
legend	plot legend?
title	title of the plot
clusterGenes	cluster heatmap genes by hierarchical clustering?

Value

a patchworked ggplot object

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
moduleExpressionPlot(astrocyte_networks[["combined"]],
                      geneList = topNGenes(astrocyte_networks$combined, "combined_013"))
```

`moduleToModuleHeatmap` *Module to module heatmap*

Description

Returns a heatmap where color corresponds to FDR-adjusted overlap (hypergeometric test) and the label corresponds to the number of overlapping genes

Usage

```
moduleToModuleHeatmap(
  comparisonDf,
  dataset1 = NULL,
  dataset2 = NULL,
  trait1 = NULL,
  trait2 = NULL,
  list1 = NULL,
  list2 = NULL,
  filterByTrait = FALSE,
  alphaLevel = 0.05
)
```

Arguments

comparisonDf	the data.frame output of computeOverlapFromWGCNA
dataset1	optional; WGCNA object for dataset 1
dataset2	optional; WGCNA object for dataset 2
trait1	optional; subset to modules correlated to this trait for dataset 1
trait2	optional; subset to modules correlated to this trait for dataset 2
list1	subset to this list of modules for dataset 1
list2	subset to this list of modules for dataset 2
filterByTrait	only plot for modules that correlate with some trait?
alphaLevel	the alpha level of significance for module-trait correlation, defaults to 0.05

Value

A ggplot object

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
overlapDf = computeOverlapsFromWGCNA(astrocyte_networks$EAE, astrocyte_networks$WT)
moduleToModuleHeatmap(overlapDf)
```

name	<i>name: Name of WGCNAobject</i>
------	----------------------------------

Description

Returns the name of a WGCNAobject.

Usage

```
name(WGCNAobject)
```

Arguments

WGCNAobject an object of class WGCNA

Value

Returns the name of the WGCNA object, ie "EAE" for astrocyte_networks\$EAE.

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
name(astrocyte_networks$EAE)
```

overlapComparisons	<i>Overlap comparisons</i>
--------------------	----------------------------

Description

Compares modules between two objects of type WGCNAobjects within a WGCNAobject list given the indices. Recommended to be used in conjunction with the iterate function.

Usage

```
overlapComparisons(
  comparisonList,
  WGCNAlist,
  first,
  second,
  element,
  plot = TRUE,
  write = FALSE
)
```

Arguments

<code>comparisonList</code>	a list passed by the iterate function
<code>WGCNAlist</code>	list of objects of class WGCNA
<code>first</code>	index of first WGCNA object
<code>second</code>	index of second WGCNA object
<code>element</code>	element position in the comparison list (passed by iterate function)
<code>plot</code>	generate plots?
<code>write</code>	write results to file?

Value

A list, in which the first element is a data.frame showing the overlap results and the second element is a data.frame showing the best matching modules between the two WGCNA objects.

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
results = list()
results$overlaps = iterate(astrocyte_networks, overlapComparisons, plot=FALSE)
```

performANOVA

Perform ANOVA

Description

Test association between module expression to traits using ANOVA

Usage

```
performANOVA(datExpr, design, testCondition, refCondition, alphaLevel = 0.05)
```

Arguments

<code>datExpr</code>	expression data.frame
<code>design</code>	the sampleTable
<code>testCondition</code>	test column in sampleTable
<code>refCondition</code>	reference column in sampleTable
<code>alphaLevel</code>	the significance level

Value

a data.frame with p-values for each association

`permutationTestResults`

Permutation test results

Description

The results of running the `PreservationPermutationTest` in the astrocyte vignette. This is provided since this function is quite slow. Please see the astrocyte vignette for more details.

Usage

```
data(permutationTestResults)
```

Format

A list of data.frames containing preservation results for each permutation

`preservationComparisonPlot`

Preservation Comparison Scatterplot

Description

A plotting function that draws a scatterplot of preservation scores between two WGCNA objects

Usage

```
preservationComparisonPlot(
  preservationList,
  dataset1,
  dataset2,
  alphaLevel = 0.05,
  outliers = FALSE
)
```

Arguments

preservationList	a list resulting from a call to preservationComparisons
dataset1	an object of class WGCNAobject to compare with dataset2
dataset2	an object of class WGCNAobject to compare with dataset1
alphaLevel	alpha level of significance, default is 0.05
outliers	leave outlier modules? By default these are removed

Value

a ggplot object

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
results = list()
results$preservation=iterate(astrocyte_networks[c("EAE", "WT")],
  preservationComparisons,
  write=FALSE,
  plot=FALSE,
  nPermutations=2)
preservationComparisonPlot(results$preservation$EAE_vs_WT,
  astrocyte_networks$EAE,
  astrocyte_networks$WT)
```

preservationComparisons

Preservation comparisons

Description

A high level function that performs a perservation comparison between two WGCNAobjects in a WGCNAlist, usually supplied by iterate function

Usage

```
preservationComparisons(
  comparisonList,
  WGCNAlist,
  first,
  second,
  element,
  plot = FALSE,
```

```

    write = FALSE,
    alphaLevel = 0.05,
    nPermutations = 100
)

```

Arguments

comparisonList	a list passed by the iterate function
WGCAlist	list of objects of type WGCAobject
first	index of first WGCAobject
second	index of second WGCAobject
element	element position in the comparison list (passed by iterate function)
plot	generate plots?
write	write results to file?
alphaLevel	alpha level of significance for module-trait correlation
nPermutations	number of permutations, defaults to 100

Value

a list of preservation comparisons results across levels 1, 2, 3

Author(s)

Dario Tommasini

Examples

```

library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCAdata"))
astrocyte_networks = eh_query[["EH8222"]]
results = list()
iterate(astrocyte_networks[c("EAE", "WT")],
       preservationComparisons,
       write=FALSE,
       plot=FALSE,
       nPermutations=2)

```

Description

Performs a permutation test to determine if a null distribution of expected preservation scores for modules in this dataset if the labels were randomly assigned. Please look at the astrocyte vignette for more info.

Usage

```
PreservationPermutationTest(
  referenceDatExpr,
  design,
  constructNetworksIn,
  testPreservationIn,
  nPermutations = 100,
  nPresPermutations = 100,
  ...
)
```

Arguments

referenceDatExpr	the combined datExpr
design	the sampleTable
constructNetworksIn	the condition to use for network construction, e.g. for the astrocyte data, this is "EAE"
testPreservationIn	the condition to use for testing preservation, e.g. for the astrocyte data, this was "WT"
nPermutations	the number of permutations to perform for permutation test
nPresPermutations	the number of permutations to perform in modulePreservation function
...	arguments to pass to blockwiseModules function for network construction (should be the same as used for constructing the original network)

Value

A list of data.frames with preservation results for each permutation

Author(s)

Dario Tommasini

Examples

```
## Not run:
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdat"))
astrocyte_networks = eh_query[["EH8222"]]
astrocyte_se = eh_query[["EH8223"]]
sampleTable = colData(astrocyte_se)
results = list()
results$permutation.test = PreservationPermutationTest(astrocyte_networks$combined@datExpr[sample(17000, 300),
  sampleTable,
  constructNetworksIn = "EAE", # Construct networks using EAE samples
  testPreservationIn = "WT", # Test preservation of disease samples in WT samples
  nPermutations = 10, # Number of permutations for permutation test
  nPresPermutations = 10, # Number of permutations for modulePreservation function
  networkType = "signed", TOMType = "unsigned",
```

```

power = 12, minModuleSize = 100, maxBlockSize = 25000,
reassignThreshold = 0, minKMEtoStay = 0, mergeCutHeight = 0,
numericLabels = TRUE, pamRespectsDendro = FALSE,
deepSplit = 4, verbose = 3
)

## End(Not run)

```

PreservationScoreDistribution

PreservationScoreDistribution

Description

Extracts the preservation score distribution from the results of PreservationPermutationTest.

Usage

```
PreservationScoreDistribution(preservationData, moduleOfInterestSize)
```

Arguments

`preservationData` the results from `PreservationPermutationTest`
`moduleOfInterestSize` the number of genes in your module of interest

Value

A data.frame with Z-summary preservation scores of the module from each permutation and the corresponding module size

Author(s)

Dario Tommasini

Examples

runDME	<i>Run differential module expression</i>
--------	---

Description

A wrapper to run diffModuleExpression on all the modules in a network

Usage

```
runDME(  
  WGCNAobject,  
  design,  
  alphaLevel = 0.05,  
  testCondition = NULL,  
  refCondition = NULL,  
  p.adjust = "fdr",  
  plot = FALSE,  
  test = c("ANOVA", "PERMANOVA"),  
  write = FALSE,  
  out = NULL  
)
```

Arguments

WGCNAobject	object of class WGCNA with the modules to run DME on
design	the sampleTable
alphaLevel	level of significance
testCondition	the column of the sampleTable to be resolved
refCondition	the column of the sampleTable to be used as biological variation
p.adjust	adjust for multiple comparisons, argument to pass to p.adjust function
plot	generate a plot?
test	statistical test to perform, either "ANOVA" or "PERMANOVA"
write	write results to a file?
out	file name for DME plots, only used if write is TRUE

Value

a data.frame summarizing the results of the analysis

Author(s)

Dario Tommasini

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_se = eh_query[["EH8223"]]
sampleTable = colData(astrocyte_se)
astrocyte_networks = eh_query[["EH8222"]]
runDME(astrocyte_networks[["combined"]], 
       design = sampleTable,
       p.adjust = "fdr",
       refCondition = "Region",
       testCondition = "Disease")
```

summarizeResults

summarizeResults: Summarize results from a results list object

Description

Prints (or writes) a summary of the results from a results list object

Usage

```
summarizeResults(
  myNetworks,
  results,
  alphaLevel = 0.05,
  write = FALSE,
  outputFile = "results.txt"
)
```

Arguments

myNetworks	a list of WGCNAobjects
results	results list
alphaLevel	alpha level of significance
write	write to file?
outputFile	name of output file, defaults to results.txt

Value

prints a summary of results from the multiWGCNA analysis

`TOMFlowPlot`*TOMflowPlot*

Description

Plots a sankey flow diagram showing the movement of genes from one WGCNA to another WGCNA.
Uses the ggalluvial framework.

Usage

```
TOMFlowPlot(
  WGCNAlist,
  networks,
  toms,
  genes_to_label,
  alpha = 0.1,
  color = "black",
  width = 0.05
)
```

Arguments

WGCNAlist	list of WGCNA objects
networks	list of network names of length 2
toms	a list of TOM distance objects of length 2
genes_to_label	genes to label across two networks
alpha	alpha of flows
color	color of flows
width	width of the strata

Value

a ggplot object

Author(s)

Dario Tommasini

`topNGenes`*topNGenes: Top N genes of a module*

Description

Returns the top N number of genes of a module. All genes returned if no number is specified. Genes are in order of intramodular connectivity.

Usage

```
topNGenes(WGCNAobject, module, nGenes = NULL)
```

Arguments

- `WGCNAobject` an object of class WGCNA
`module` the name of the module in WGCNAobject
`nGenes` an integer from 1 to module size; returns all genes if left NULL

Value

a character vector of the genes/probes in the module

Examples

```
library(ExperimentHub)
eh = ExperimentHub()
eh_query = query(eh, c("multiWGCNAdata"))
astrocyte_networks = eh_query[["EH8222"]]
topNGenes(astrocyte_networks$EAE, "EAE_015", nGenes = 10)
```

Description

The WGCNA class is the main class used in multiWGCNA to store results from a weighted gene co-expression network analysis. These include the original unaltered expression data used as input, connectivity metrics, module assignment, input sample conditions, trait

Value

NA

Slots

- `datExpr` The expression data, connectivity data, and module assignment
- `conditions` A data.frame with integer conditions for WGCNA
- `trait` A data.frame showing pearson correlation values to traits
- `moduleEigengenes` A data.frame of module eigengenes for each module across samples
- `outlierModules` A vector of modules classified by our algorithm as being driven by sample outliers

Index

- * **datasets**
 - permutationTestResults, 18
- * **internal**
 - multiWGCNA-package, 2
- bidirectionalBestMatches, 3
- cleanDatExpr, 3
- coexpressionLineGraph, 4
- computeOverlapsFromWGCNA, 5
- constructNetworks, 6
- diffCoexpression, 7
- diffModuleExpression, 8
- drawMultiWGCNAnetwork, 9
- GetDatExpr, 11
- getPreservation, 11
- iterate, 12
- makeTraitTable, 13
- moduleComparisonPlot, 13
- moduleExpressionPlot, 14
- moduleToModuleHeatmap, 15
- multiWGCNA (multiWGCNA-package), 2
- multiWGCNA-package, 2
- name, 16
- overlapComparisons, 16
- performANOVA, 17
- permutationTestResults, 18
- preservationComparisonPlot, 18
- preservationComparisons, 19
- PreservationPermutationTest, 20
- PreservationScoreDistribution, 22
- runDME, 23
- summarizeResults, 24
- TOMFlowPlot, 25
- topNGenes, 25
- WGCNA-class, 26