

# Package ‘spatialSimGP’

July 10, 2025

**Title** Simulate Spatial Transcriptomics Data with the Mean-variance Relationship

**Version** 1.2.0

**Description** This packages simulates spatial transcriptomics data with the mean-variance relationship using a Gaussian Process model per gene.

**URL** <https://github.com/kinnaryshah/spatialSimGP>

**BugReports** <https://github.com/kinnaryshah/spatialSimGP/issues>

**Imports** SpatialExperiment, MASS, SummarizedExperiment

**License** MIT + file LICENSE

**Encoding** UTF-8

**Suggests** testthat (>= 3.0.0), STexampleData, ggplot2, knitr

**biocViews** Spatial, Transcriptomics, GeneExpression

**Depends** R (>= 4.4)

**Roxygen** list(markdown = TRUE)

**RoxygenNote** 7.3.2

**Config/testthat/edition** 3

**VignetteBuilder** knitr

**git\_url** https://git.bioconductor.org/packages/spatialSimGP

**git\_branch** RELEASE\_3\_21

**git\_last\_commit** 505d949

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.21

**Date/Publication** 2025-07-09

**Author** Kinnary Shah [aut, cre] (ORCID:

[<https://orcid.org/0000-0001-7098-2116>](https://orcid.org/0000-0001-7098-2116)),

Boyi Guo [aut] (ORCID: <<https://orcid.org/0000-0003-2950-2349>>),

Stephanie C. Hicks [aut] (ORCID:

[<https://orcid.org/0000-0002-7858-0231>](https://orcid.org/0000-0002-7858-0231))

**Maintainer** Kinnary Shah <kinnaryshahh@gmail.com>

## Contents

<code>spatial_simulate</code> . . . . .	2
<b>Index</b>	<b>4</b>

---

<code>spatial_simulate</code>	<i>Simulate SpatialExperiment object</i>
-------------------------------	--

---

### Description

Simulate a SpatialExperiment object with spatially varying genes

### Usage

```
spatial_simulate(
  n_genes,
  proportion,
  coords,
  range_sigma_sq,
  range_beta,
  length_scale,
  length_scale_option = "fixed"
)
```

### Arguments

<code>n_genes</code>	an integer specifying the number of genes to simulate.
<code>proportion</code>	a numeric value specifying the proportion of genes that will have no spatially varying patterns.
<code>coords</code>	a matrix of coordinates.
<code>range_sigma_sq</code>	a numeric vector of length 2 specifying the range of the spatial variance parameter.
<code>range_beta</code>	a numeric vector of length 2 specifying the range of the mean expression value.
<code>length_scale</code>	if <code>length_scale_option</code> is "fixed", a numeric value specifying the length scale parameter. If <code>length_scale_option</code> is "unique", a numeric vector of length <code>n_genes</code> specifying the length scale parameter for each gene.
<code>length_scale_option</code>	a character string specifying the length scale option. Options are "fixed" for a single length scale for all genes or "unique" for a unique length scale for each gene.

### Details

This function simulates a SpatialExperiment object with spatially varying genes. The function takes in the number of genes to simulate, the proportion of genes that will have no spatially varying patterns, a matrix of coordinates, the range of the spatial variance parameter, the range of the mean expression value, the length scale parameter, and the length scale option.

**Value**

A SpatialExperiment object with the simulated data.

**Examples**

```
library(STexampleData)

set.seed(1)
n_genes <- 1
proportion <- 0.5
range_sigma_sq <- c(0.2, 3)
range_beta <- c(0.5, 9)
length_scale <- 60

spe_demo <- Visium_mouseCoronal()
colData(spe_demo)$subset <- ifelse(
  colData(spe_demo)$array_row > 20 &
  colData(spe_demo)$array_row < 65 &
  colData(spe_demo)$array_col > 30 &
  colData(spe_demo)$array_col < 65,
  TRUE, FALSE
)
spe_demo <- spe_demo[, colData(spe_demo)$subset]
coords <- spatialCoords(spe_demo)

spe <- spatial_simulate(n_genes, proportion, coords, range_sigma_sq, range_beta,
  length_scale, length_scale_option = "fixed")
```

# Index

`spatial_simulate`, 2