

Package ‘ginmappeR’

August 3, 2025

Type Package

Title Gene Identifier Mapper

Version 1.5.0

Description Provides functionalities to translate gene or protein identifiers between state-of-art biological databases: CARD (<<https://card.mcmaster.ca/>>), NCBI Protein, Nucleotide and Gene (<<https://www.ncbi.nlm.nih.gov/>>), UniProt (<<https://www.uniprot.org/>>) and KEGG (<<https://www.kegg.jp/>>). Also offers complementary functionality like NCBI identical proteins or UniProt similar genes clusters retrieval.

License GPL-3 + file LICENSE

Encoding UTF-8

VignetteBuilder knitr

biocViews Annotation, KEGG, Genetics, ThirdPartyClient, Software

Imports KEGGREST, UniProt.ws, XML, rentrez, httr, utils, memoise, cachem, jsonlite, rvest

Suggests RUnit, BiocGenerics, markdown, knitr

git_url <https://git.bioconductor.org/packages/ginmappeR>

git_branch devel

git_last_commit 1e1ef8

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-08-03

Author Fernando Sola [aut, cre] (ORCID: <<https://orcid.org/0000-0003-1685-3270>>), Daniel Ayala [aut] (ORCID: <<https://orcid.org/0000-0003-2095-1009>>), Marina Pulido [aut] (ORCID: <<https://orcid.org/0000-0003-1633-4294>>), Rafael Ayala [aut] (ORCID: <<https://orcid.org/0000-0002-9332-4623>>), Lorena López-Cerero [aut] (ORCID: <<https://orcid.org/0000-0001-8950-4384>>), Inma Hernández [aut] (ORCID: <<https://orcid.org/0000-0001-8920-6635>>), David Ruiz [aut] (ORCID: <<https://orcid.org/0000-0003-4460-5493>>)

Maintainer Fernando Sola <fsola@us.es>

Contents

changeCARDPath	2
getCARD2KEGG	3
getCARD2NCBIGene	4
getCARD2NCBINucleotide	5
getCARD2NCBIProtein	5
getCARD2UniProt	6
getCARDVersion	7
getKEGG2CARD	7
getKEGG2NCBIGene	8
getKEGG2NCBINucleotide	9
getKEGG2NCBIProtein	10
getKEGG2UniProt	11
getKEGGVersion	12
getNCBIGene2CARD	12
getNCBIGene2KEGG	13
getNCBIGene2NCBINucleotide	14
getNCBIGene2NCBIProtein	14
getNCBIGene2UniProt	15
getNCBIIdenticalProteins	16
getNCBINucleotide2CARD	17
getNCBINucleotide2KEGG	17
getNCBINucleotide2NCBIGene	18
getNCBINucleotide2NCBIProtein	19
getNCBINucleotide2UniProt	20
getNCBIProtein2CARD	21
getNCBIProtein2KEGG	22
getNCBIProtein2NCBIGene	23
getNCBIProtein2NCBINucleotide	23
getNCBIProtein2UniProt	24
getNCBIVersion	25
getUniProt2CARD	25
getUniProt2KEGG	26
getUniProt2NCBIGene	27
getUniProt2NCBINucleotide	28
getUniProt2NCBIProtein	29
getUniProtSimilarGenes	30
getUniProtVersion	31
updateCARDDataBase	31

Index	32
--------------	-----------

changeCARDPath	<i>Change path to download CARD database</i>
----------------	--

Description

Defines a new path to the folder where to download CARD database. By default, this path is the temporary folder tempdir().

Usage

```
changeCARDPath(path=tempdir())
```

Arguments

path valid route to desired folder. Default value: tempdir()

Value

Updated path for CARD database to be downloaded.

getCARD2KEGG	<i>Translates a CARD database ID to KEGG database</i>
--------------	---

Description

Retrieves the ID translation of an specific instance of CARD database ID to the KEGG Genes database.

Usage

```
getCARD2KEGG(cardId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
byIdenticalProteins = TRUE, bySimilarGenes = TRUE)
```

Arguments

cardId valid CARD database ARO ID or a vector of them

exhaustiveMapping logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

detailedMapping logical value (TRUE or FALSE) indicating to return a vector of KEGG IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.

byIdenticalProteins logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID

bySimilarGenes logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as cardId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate CARD ID '3000938' to KEGG
getCARD2KEGG('3000938', byIdenticalProteins = FALSE, bySimilarGenes = FALSE)

# Translate CARD IDs '3000938' and '3002557' to KEGG
getCARD2KEGG(c('3000938', '3002557'))

# Get all possible translations of IDs '3000938', '3002511' with detailed origin
getCARD2KEGG(c('3000938', '3002511'), exhaustiveMapping = TRUE,
detailedMapping = TRUE)
```

getCARD2NCBIGene	<i>Translates a CARD database ID to NCBI Gene database</i>
------------------	--

Description

Retrieves the ID translation of an specific instance of CARD database ID to the NCBI Gene database.

Usage

```
getCARD2NCBIGene(cardId, exhaustiveMapping = FALSE)
```

Arguments

cardId	valid CARD database ARO ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as cardId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate CARD ID '3002525' to NCBI Gene
getCARD2NCBIGene('3002525')

# Translate CARD IDs '3002524' and '3002525' to NCBI Gene
getCARD2NCBIGene(c('3002524', '3002525'))

# Get all possible translations of IDs '3005061' and '3002524'
getCARD2NCBIGene(c('3005061', '3002524'), exhaustiveMapping = TRUE)
```

`getCARD2NCBINucleotide`*Translates a CARD database ID to NCBI Nucleotide database*

Description

Retrieves the ID translation of an specific instance of CARD database ID to the NCBI Nucleotide database. Note that, due to the nature of NCBI Nucleotide database, a complete genome is often retrieved.

Usage

```
getCARD2NCBINucleotide(cardId)
```

Arguments

`cardId` valid CARD database ARO ID or a vector of them

Value

A character vector of the same length as `cardId`.

Examples

```
# Translate CARD ID '3002535' to NCBI Nucleotide
getCARD2NCBINucleotide('3002535')

# Translate CARD ID 'ARO:3002535' to NCBI Nucleotide
getCARD2NCBINucleotide('ARO:3002535')

# Translate CARD IDs '3002535' and '3003988' to NCBI Nucleotide
getCARD2NCBINucleotide(c('3002535', '3003988'))
```

`getCARD2NCBIProtein`*Translates a CARD database ID to NCBI Protein database*

Description

Retrieves the ID translation of an specific instance of CARD database ID to the NCBI Protein database.

Usage

```
getCARD2NCBIProtein(cardId)
```

Arguments

`cardId` valid CARD database ARO ID or a vector of them

Value

A character vector of the same length as `cardId`.

Examples

```
# Translate CARD ID '3002535' to NCBI Protein
getCARD2NCBIProtein('3002535')

# Translate CARD ID 'ARO:3002535' to NCBI Protein
getCARD2NCBIProtein('ARO:3002535')

# Translate CARD IDs '3002535' and '3003988' to NCBI Protein
getCARD2NCBIProtein(c('3002535', '3003988'))
```

getCARD2UniProt	<i>Translates a CARD database ID to UniProt database</i>
-----------------	--

Description

Retrieves the ID translation of an specific instance of CARD database ID to the UniProt database.

Usage

```
getCARD2UniProt(cardId, exhaustiveMapping = FALSE, detailedMapping = FALSE)
```

Arguments

cardId	valid CARD database ARO ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of UniProt IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.

Value

A character vector of the same length as cardId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate CARD ID '3002867' to UniProt
getCARD2UniProt('3002867')

# Translate CARD IDs '3002867' and '3002535' to UniProt
getCARD2UniProt(c('3002867', '3002535'))

# Get all possible translations of IDs '3002867', '3002535' with detailed origin
getCARD2UniProt(c('3002867', '3002535'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getCARDVersion	<i>Prints CARD database version being used</i>
----------------	--

Description

Prints the downloaded CARD version and release date.

Usage

```
getCARDVersion()
```

Value

Downloaded CARD database version.

getKEGG2CARD	<i>Translates a KEGG database ID to CARD database</i>
--------------	---

Description

Retrieves the ID translation of an specific instance of KEGG Genes database ID to the CARD database.

Usage

```
getKEGG2CARD(keggId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

keggId	valid KEGG Genes database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of CARD IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as keggId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate KEGG ID 'ag:ACC85616' to CARD
getKEGG2CARD('ag:ACC85616')

# Translate KEGG IDs 'ag:ACC85616' and 'ag:CAJ47134' to CARD
getKEGG2CARD(c('ag:ACC85616', 'ag:CAJ47134'))

# Get all possible translations of IDs 'ag:ACC85616', 'ag:CAJ47134'
# with detailed origin
getKEGG2CARD(c('ag:ACC85616', 'ag:CAJ47134'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getKEGG2NCBIGene	<i>Translates a KEGG database ID to NCBI Gene database</i>
------------------	--

Description

Retrieves the ID translation of an specific instance of KEGG Genes database ID to the NCBI Gene database.

Usage

```
getKEGG2NCBIGene(keggId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

keggId	valid KEGG Genes database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of NCBI Gene IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as keggId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate KEGG ID 'aag:5579347' to NCBI Gene
getKEGG2NCBIGene('aag:5579347', detailedMapping = TRUE)

# Translate KEGG IDs 'aag:5579347' and 'abh:M3Q_2831' to NCBI Gene
getKEGG2NCBIGene(c('aag:5579347', 'abh:M3Q_2831'))

# Get all possible translations of IDs 'aag:5579347', 'abh:M3Q_2831' with
# detailed origin
getKEGG2NCBIGene(c('aag:5579347', 'abh:M3Q_2831'), exhaustiveMapping = TRUE,
detailedMapping = TRUE)
```

```
getKEGG2NCBINucleotide
```

Translates a KEGG database ID to NCBI Nucleotide database

Description

Retrieves the ID translation of an specific instance of KEGG Genes database ID to the NCBI Nucleotide database. Note that, due to the nature of NCBI Nucleotide database, a complete genome is often retrieved.

Usage

```
getKEGG2NCBINucleotide(keggId, exhaustiveMapping = FALSE,
detailedMapping = FALSE, bySimilarGenes = TRUE)
```

Arguments

keggId	valid KEGG Genes database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of NCBI Nucleotide IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as keggId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate KEGG ID 'llo:LLO_2673' to NCBI Nucleotide
getKEGG2NCBINucleotide('llo:LLO_2673', bySimilarGenes = FALSE)

# Translate KEGG IDs 'llo:LLO_2673' and 'abh:M3Q_2831' to NCBI Nucleotide
getKEGG2NCBINucleotide(c('llo:LLO_2673', 'abh:M3Q_2831'))

# Get all possible translations of IDs 'aag:5579347', 'abh:M3Q_2831' with
# detailed origin
getKEGG2NCBINucleotide(c('aag:5579347', 'abh:M3Q_2831'),
exhaustiveMapping = TRUE, detailedMapping = TRUE)
```

getKEGG2NCBIProtein	<i>Translates a KEGG database ID to NCBI Protein database</i>
---------------------	---

Description

Retrieves the ID translation of an specific instance of KEGG Genes database ID to the NCBI Protein database.

Usage

```
getKEGG2NCBIProtein(keggId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

keggId	valid KEGG Genes database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of NCBI Protein IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as keggId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate KEGG ID 'llo:LLO_2673' to NCBI Protein
getKEGG2NCBIProtein('llo:LLO_2673')

# Translate KEGG IDs 'llo:LLO_2673' and 'abh:M3Q_2831' to NCBI Protein
getKEGG2NCBIProtein(c('llo:LLO_2673', 'abh:M3Q_2831'))

# Get all possible translations of IDs 'llo:LLO_2673', 'abh:M3Q_2831' with
# detailed origin
getKEGG2NCBIProtein(c('llo:LLO_2673', 'abh:M3Q_2831'),
  exhaustiveMapping = TRUE, detailedMapping = TRUE)
```

getKEGG2UniProt

Translates a KEGG Genes database ID to UniProt database

Description

Retrieves the ID translation of an specific instance of KEGG Genes database ID to the UniProt database.

Usage

```
getKEGG2UniProt(keggId, exhaustiveMapping = FALSE)
```

Arguments

keggId	valid KEGG Genes database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as keggId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate KEGG Genes ID 'llo:LLO_2673' to UniProt
getKEGG2UniProt('llo:LLO_2673')

# Translate KEGG IDs 'llo:LLO_2673' and 'abh:M3Q_2831' to NCBI UniProt
getKEGG2UniProt(c('llo:LLO_2673', 'abh:M3Q_2831'))

# Get all possible translations of IDs 'llo:LLO_2673', 'abh:M3Q_2831'
getKEGG2UniProt(c('llo:LLO_2673', 'abh:M3Q_2831'), exhaustiveMapping = TRUE)
```

getKEGGVersion	<i>Prints KEGG database version being used</i>
----------------	--

Description

Prints the accessed KEGG version and its corresponding release date. It also prints the API version release date.

Usage

```
getKEGGVersion()
```

Value

KEGG database and API version.

getNCBIGene2CARD	<i>Translates a NCBI Gene database ID to CARD database</i>
------------------	--

Description

Retrieves the ID translation of an specific instance of NCBI Gene database ID to the CARD database.

Usage

```
getNCBIGene2CARD(ncbiId, exhaustiveMapping = FALSE)
```

Arguments

ncbiId	valid NCBI Gene database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Gene ID '3510143' to CARD
getNCBIGene2CARD('3510143')

# Translate NCBI Gene IDs '3510143' and '29426913' to CARD
getNCBIGene2CARD(c('3510143', '29426913'))

# Get all possible translations of IDs '3510143' and '29426913'
getNCBIGene2CARD(c('3510143', '29426913'), exhaustiveMapping = TRUE)
```

getNCBIGene2KEGG	<i>Translates a NCBI Gene database ID to KEGG database</i>
------------------	--

Description

Retrieves the ID translation of an specific instance of NCBI Gene database ID to the KEGG Genes database.

Usage

```
getNCBIGene2KEGG(ncbiId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
  byIdenticalProteins = TRUE, bySimilarGenes = TRUE)
```

Arguments

ncbiId	valid NCBI Gene database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of KEGG IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
byIdenticalProteins	logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Gene ID '76524190' to KEGG
getNCBIGene2KEGG('AFU38919', bySimilarGenes = FALSE, byIdenticalProteins = FALSE)

# Translate NCBI Gene IDs '76524190' and 'AFU38919' to KEGG
getNCBIGene2KEGG(c('76524190', 'AFU38919'))

# Get all possible translations of IDs '76524190' and 'AFU38919' with
# detailed origin
getNCBIGene2KEGG(c('76524190', 'AFU38919'), detailedMapping = TRUE,
  exhaustiveMapping = TRUE)
```

```
getNCBIGene2NCBINucleotide
```

Translates a NCBI Gene database ID to NCBI Nucleotide database

Description

Retrieves the ID translation of an specific instance of NCBI Gene database ID to the NCBI Nucleotide database. Note that, due to the nature of NCBI Nucleotide database, a complete genome is often retrieved.

Usage

```
getNCBIGene2NCBINucleotide(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Gene database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Gene ID '76524190' to NCBI Nucleotide
getNCBIGene2NCBINucleotide('76524190')

# Translate NCBI Gene IDs '76524190' and '1272' to NCBI Nucleotide
getNCBIGene2NCBINucleotide(c('76524190', '1272'))

# Get all possible translations of IDs '76524190' and '1272'
getNCBIGene2NCBINucleotide(c('76524190', '1272'), exhaustiveMapping = TRUE)
```

```
getNCBIGene2NCBIProtein
```

Translates a NCBI Gene database ID to NCBI Protein database

Description

Retrieves the ID translation of an specific instance of NCBI Gene database ID to the NCBI Protein database.

Usage

```
getNCBIGene2NCBIProtein(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Gene database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Gene ID '76524190' to NCBI Protein
getNCBIGene2NCBIProtein('76524190')

# Translate NCBI Gene IDs '76524190' and '1272' to NCBI Protein
getNCBIGene2NCBIProtein(c('76524190', '1272'))

# Get all possible translations of IDs '76524190', '1272'
getNCBIGene2NCBIProtein(c('76524190', '1272'), exhaustiveMapping = TRUE)
```

`getNCBIGene2UniProt` *Translates a NCBI Gene database ID to UniProt database*

Description

Retrieves the ID translation of an specific instance of NCBI Gene database ID to the UniProt database.

Usage

```
getNCBIGene2UniProt(ncbiId, exhaustiveMapping = FALSE,
  detailedMapping = FALSE, byIdenticalProteins = TRUE)
```

Arguments

`ncbiId` valid NCBI Gene database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
`detailedMapping` logical value (TRUE or FALSE) indicating to return a vector of UniProt IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
`byIdenticalProteins` logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID

Value

A character vector of the same length as `ncbiId`. If parameter `exhaustiveMapping` is `TRUE`, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Gene ID '76524190' to UniProt
getNCBIGene2UniProt('76524190')

# Translate NCBI Gene IDs '76524190' and '1272' to UniProt
getNCBIGene2UniProt(c('76524190', '1272'))

# Get all possible translations of IDs '76524190', '1272' with detailed origin
getNCBIGene2UniProt(c('76524190', '1272'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getNCBIIdenticalProteins

Search NCBI Identical Protein database by a given NCBI ID

Description

Retrieves identical NCBI proteins to that of a given ID.

Usage

```
getNCBIIdenticalProteins(ncbiId, format='ids')
```

Arguments

<code>ncbiId</code>	valid NCBI ID or a vector of them
<code>format</code>	return format of the response. Default value <code>ids</code> returns a vector of the identical proteins IDs; <code>dataframe</code> value returns a dataframe with different information about the found identical proteins

Value

Depending on parameter `format`, it will return a list of same length as `ncbiId` with identical NCBI Protein IDs or with dataframes containing different information about the identical proteins found: `Id`, `Source`, `Nucleotide`, `Accession`, `Start`, `Stop`, `Strand`, `Protein`, `Protein.Name`, `Organism`, `Strain` and `Assembly`.

Examples

```
# Get IDs on identical proteins to the one with ID 'AHA80958'
getNCBIIdenticalProteins('AHA80958', format = 'ids')

# Get IDs on identical proteins to the ones with IDs 'AHA80958' and 'CAA76794'
getNCBIIdenticalProteins(c('AHA80958', 'CAA76794'), format = 'ids')
```

`getNCBINucleotide2CARD`*Translates a NCBI Nucleotide database ID to CARD database*

Description

Retrieves the ID translation of an specific instance of NCBI Nucleotide database ID to the CARD database.

Usage

```
getNCBINucleotide2CARD(ncbiId, exhaustiveMapping = FALSE)
```

Arguments

<code>ncbiId</code>	valid NCBI Nucleotide database ID or a vector of them
<code>exhaustiveMapping</code>	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `ncbiId`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Nucleotide ID 'AY034138' to CARD
getNCBINucleotide2CARD('AY034138')

# Translate NCBI Nucleotide IDs 'AY034138' and 'X54723.1' to CARD
getNCBINucleotide2CARD(c('AY034138', 'X54723.1'))

# Get all possible translations of IDs 'AY034138', 'X54723.1'
getNCBINucleotide2CARD(c('AY034138', 'X54723.1'), exhaustiveMapping = TRUE)
```

`getNCBINucleotide2KEGG`*Translates a NCBI Nucleotide database ID to KEGG database*

Description

Retrieves the ID translation of an specific instance of NCBI Nucleotide database ID to the KEGG Genes database.

Usage

```
getNCBINucleotide2KEGG(ncbiId, exhaustiveMapping = FALSE,
  detailedMapping = FALSE, byIdenticalProteins = TRUE, bySimilarGenes = TRUE)
```

Arguments

ncbiId	valid NCBI Nucleotide database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of KEGG IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
byIdenticalProteins	logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Nucleotide ID 'NC_013861.1' to KEGG
getNCBINucleotide2KEGG('NC_013861.1', bySimilarGenes = FALSE, byIdenticalProteins = FALSE)

# Translate NCBI Nucleotide IDs 'AY536519' and 'NC_013861.1' to KEGG
getNCBINucleotide2KEGG(c('AY536519', 'NC_013861.1'))

# Get all possible translations of IDs 'AY536519', 'NC_013861.1'
# with detailed origin
getNCBINucleotide2KEGG(c('AY536519', 'NC_013861.1'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

```
getNCBINucleotide2NCBIGene
```

Translates a NCBI Nucleotide database ID to NCBI Gene database

Description

Retrieves the ID translation of an specific instance of NCBI Nucleotide database ID to the NCBI Gene database.

Usage

```
getNCBINucleotide2NCBIGene(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Nucleotide database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Nucleotide ID 'Z21488' to NCBI Gene
getNCBINucleotide2NCBIGene('Z21488')

# Get all possible translations of ID 'Z21488'
getNCBINucleotide2NCBIGene(c('Z21488'), exhaustiveMapping = TRUE)
```

`getNCBINucleotide2NCBIProtein`*Translates a NCBI Nucleotide database ID to NCBI Protein database*

Description

Retrieves the ID translation of an specific instance of NCBI Nucleotide database ID to the NCBI Protein database.

Usage

```
getNCBINucleotide2NCBIProtein(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Nucleotide database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Nucleotide ID 'AY536519' to NCBI Protein
getNCBINucleotide2NCBIProtein('AY536519')

# Translate NCBI Nucleotide IDs 'AY536519' and 'X54723.1' to NCBI Protein
getNCBINucleotide2NCBIProtein(c('AY536519', 'X54723.1'))

# Get all possible translations of IDs 'AY536519', 'X54723.1'
getNCBINucleotide2NCBIProtein(c('AY536519', 'X54723.1'),
exhaustiveMapping = TRUE)
```

```
getNCBINucleotide2UniProt
```

Translates a NCBI Nucleotide database ID to UniProt database

Description

Retrieves the ID translation of an specific instance of NCBI Nucleotide database ID to the UniProt database.

Usage

```
getNCBINucleotide2UniProt(ncbiId, exhaustiveMapping = FALSE,
detailedMapping = FALSE, byIdenticalProteins = TRUE)
```

Arguments

ncbiId	valid NCBI Nucleotide database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of UniProt IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
byIdenticalProteins	logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Nucleotide ID 'AY536519' to UniProt
getNCBINucleotide2UniProt('AY536519')

# Translate NCBI Nucleotide IDs 'AY536519' and 'X54723.1' to UniProt
getNCBINucleotide2UniProt(c('AY536519', 'X54723.1'))

# Get all possible translations of IDs 'AY536519', 'X54723.1'
# with detailed origin
getNCBINucleotide2UniProt(c('AY536519', 'X54723.1'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getNCBIProtein2CARD	<i>Translates a NCBI Protein database ID to CARD database</i>
---------------------	---

Description

Retrieves the ID translation of an specific instance of NCBI Protein database ID to the CARD database.

Usage

```
getNCBIProtein2CARD(ncbiId, exhaustiveMapping = FALSE)
```

Arguments

ncbiId	valid NCBI Protein database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Protein ID 'AAK64581' to CARD
getNCBIProtein2CARD('AAK64581')

# Translate NCBI Protein IDs 'AAK64581' and 'WP_010896559.1' to CARD
getNCBIProtein2CARD(c('AAK64581', 'WP_010896559.1'))

# Get all possible translations of IDs 'AAK64581', 'WP_010896559.1'
getNCBIProtein2CARD(c('AAK64581', 'WP_010896559.1'), exhaustiveMapping = TRUE)
```

getNCBIProtein2KEGG *Translates a NCBI Protein database ID to KEGG database*

Description

Retrieves the ID translation of an specific instance of NCBI Protein database ID to the KEGG Genes database.

Usage

```
getNCBIProtein2KEGG(ncbiId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
  byIdenticalProteins = TRUE, bySimilarGenes = TRUE)
```

Arguments

ncbiId	valid NCBI Protein database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of KEGG IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
byIdenticalProteins	logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Protein ID 'AFU38919' to KEGG
getNCBIProtein2KEGG('AFU38919', exhaustiveMapping = FALSE,
  detailedMapping = FALSE, byIdenticalProteins = FALSE, bySimilarGenes = FALSE)

# Translate NCBI Protein IDs 'AFU38919' and 'WP_010896559.1' to KEGG
getNCBIProtein2KEGG(c('AFU38919', 'WP_010896559.1'),
  byIdenticalProteins = FALSE)

# Get all possible translations of ID 'AFU38919', 'WP_010896559.1'
# with detailed origin
getNCBIProtein2KEGG(c('AFU38919', 'WP_010896559.1'), exhaustiveMapping = TRUE,
  detailedMapping = TRUE)
```

`getNCBIProtein2NCBIGene`*Translates a NCBI Protein database ID to NCBI Gene database*

Description

Retrieves the ID translation of an specific instance of NCBI Protein database ID to the NCBI Gene database.

Usage

```
getNCBIProtein2NCBIGene(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Protein database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Protein ID 'CAA79696' to NCBI Gene
getNCBIProtein2NCBIGene('CAA79696')

# Translate NCBI Protein IDs 'CAA79696' and 'WP_001082319' to NCBI Gene
getNCBIProtein2NCBIGene(c('CAA79696', 'WP_001082319'))

# Get all possible translations of IDs 'CAA79696', 'WP_001082319'
getNCBIProtein2NCBIGene(c('CAA79696', 'WP_001082319'), exhaustiveMapping=TRUE)
```

`getNCBIProtein2NCBINucleotide`*Translates a NCBI Protein database ID to NCBI Nucleotide database*

Description

Retrieves the ID translation of an specific instance of NCBI Protein database ID to the NCBI Nucleotide database. Note that, due to the nature of NCBI Nucleotide database, a complete genome is often retrieved.

Usage

```
getNCBIProtein2NCBINucleotide(id, exhaustiveMapping=FALSE)
```

Arguments

`id` valid NCBI Protein database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

Value

A character vector of the same length as `id`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Protein ID 'AAS48620' to NCBI Nucleotide
getNCBIProtein2NCBINucleotide('AAS48620')

# Translate NCBI Protein IDs 'AAS48620' and 'CAA38525' to NCBI Nucleotide
getNCBIProtein2NCBINucleotide(c('AAS48620', 'CAA38525'))

# Get all possible translations of IDs 'AAS48620', 'CAA38525'
getNCBIProtein2NCBINucleotide(c('AAS48620', 'CAA38525'), exhaustiveMapping=TRUE)
```

```
getNCBIProtein2UniProt
```

Translates a NCBI Protein database ID to UniProt database

Description

Retrieves the ID translation of an specific instance of NCBI Protein database ID to the UniProt database.

Usage

```
getNCBIProtein2UniProt(ncbiId, exhaustiveMapping = FALSE,
  detailedMapping = FALSE, byIdenticalProteins = TRUE)
```

Arguments

`ncbiId` valid NCBI Protein database ID or a vector of them
`exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
`detailedMapping` logical value (TRUE or FALSE) indicating to return a vector of UniProt IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
`byIdenticalProteins` logical value (TRUE or FALSE) indicating to translate also through NCBI Identical Proteins. TRUE value could mean higher translation time and FALSE, fewer chances to translate the ID

Value

A character vector of the same length as ncbiId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate NCBI Protein ID 'WP_010896559.1' to UniProt
getNCBIProtein2UniProt('WP_010896559.1')

# Translate NCBI Protein IDs 'AAS48620' and 'WP_010896559' to UniProt
getNCBIProtein2UniProt(c('AAS48620', 'WP_010896559'))

# Get all possible translations of IDs 'AAS48620', 'WP_010896559'
# with detailed origin
getNCBIProtein2UniProt(c('AAS48620', 'WP_010896559'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

`getNCBIVersion`*Prints NCBI databases versions being used*

Description

Prints the build version and release date of the Protein, Gene, Nucleotide and Identical Proteins NCBI databases.

Usage

```
getNCBIVersion()
```

Value

NCBI databases versions.

`getUniProt2CARD`*Translates an UniProt database ID to CARD database*

Description

Retrieves the ID translation of an specific instance of UniProt database ID to the CARD database.

Usage

```
getUniProt2CARD(upId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

- `upId` valid UniProt database ID or a vector of them
- `exhaustiveMapping` logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
- `detailedMapping` logical value (TRUE or FALSE) indicating to return a vector of CARD IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
- `bySimilarGenes` logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as `upId`. If parameter `exhaustiveMapping` is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate UniProt ID 'A0A1S7BGS4' to CARD
getUniProt2CARD('A0A1S7BGS4')

# Translate UniProt IDs 'A0A1S7BGS4' and 'A0A6H2TXZ6' to CARD
getUniProt2CARD(c('A0A1S7BGS4', 'A0A6H2TXZ6'))

# Get all possible translations of IDs 'A0A1S7BGS4', 'A0A6H2TXZ6'
# with detailed origin
getUniProt2CARD(c('A0A1S7BGS4', 'A0A6H2TXZ6'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getUniProt2KEGG

Translates an UniProt database ID to KEGG database

Description

Retrieves the ID translation of an specific instance of UniProt database ID to the KEGG Genes database.

Usage

```
getUniProt2KEGG(upId, exhaustiveMapping = FALSE, bySimilarGenes = TRUE,
detailedMapping = FALSE)
```

Arguments

upId	valid UniProt database ID or a vector of them.
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of KEGG IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.

Value

A character vector of the same length as upId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate UniProt ID 'G9JVE6' to KEGG
getUniProt2KEGG('G9JVE6')

# Translate UniProt IDs 'A0A1S7BGS4' and 'G9JVE6' to KEGG
getUniProt2KEGG(c('A0A1S7BGS4', 'G9JVE6'))

# Get all possible translations of ID 'A0A2R4PHC7' with detailed origin
getUniProt2KEGG(c('test_id', 'A0A2R4PHC7'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getUniProt2NCBIGene	<i>Translates an UniProt database ID to NCBI Gene database</i>
---------------------	--

Description

Retrieves the ID translation of an specific instance of UniProt database ID to the NCBI Gene database.

Usage

```
getUniProt2NCBIGene(upId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

upId	valid UniProt database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

detailedMapping

logical value (TRUE or FALSE) indicating to return a vector of NCBI Gene IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.

bySimilarGenes

logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as upId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate UniProt ID 'G9JVE6' to NCBI Gene
getUniProt2NCBIGene('G9JVE6')

# Translate UniProt IDs 'A0SNL9' and 'G9JVE6' to NCBI Gene
getUniProt2NCBIGene(c('A0SNL9', 'G9JVE6'))

# Get all possible translations of IDs 'A0SNL9', 'G9JVE6' with detailed origin
getUniProt2NCBIGene(c('A0SNL9', 'G9JVE6'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getUniProt2NCBINucleotide

Translates an UniProt database ID to NCBI Nucleotide database

Description

Retrieves the ID translation of an specific instance of UniProt database ID to the NCBI Nucleotide database. Note that, due to the nature of NCBI Nucleotide database, a complete genome is often retrieved.

Usage

```
getUniProt2NCBINucleotide(upId, exhaustiveMapping = FALSE,
detailedMapping = FALSE, bySimilarGenes = TRUE)
```

Arguments

upId valid UniProt database ID or a vector of them

exhaustiveMapping

logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.

detailedMapping

logical value (TRUE or FALSE) indicating to return a vector of NCBI Nucleotide IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.

bySimilarGenes logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as upId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate UniProt ID 'G9JVE6' to NCBI Nucleotide
getUniProt2NCBINucleotide('G9JVE6')

# Translate UniProt IDs 'A0SNL9' and 'G9JVE6' to NCBI Nucleotide
getUniProt2NCBINucleotide(c('A0SNL9', 'G9JVE6'))

# Get all possible translations of IDs 'A0SNL9', 'G9JVE6' with detailed origin
getUniProt2NCBINucleotide(c('A0SNL9', 'G9JVE6'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

```
getUniProt2NCBIProtein
```

Translates an UniProt database ID to NCBI Protein database

Description

Retrieves the ID translation of an specific instance of UniProt database ID to the NCBI Protein database.

Usage

```
getUniProt2NCBIProtein(upId, exhaustiveMapping = FALSE, detailedMapping = FALSE,
bySimilarGenes = TRUE)
```

Arguments

upId	valid UniProt database ID or a vector of them
exhaustiveMapping	logical value (TRUE or FALSE) indicating to retrieve all possible translations or only the first and fastest one.
detailedMapping	logical value (TRUE or FALSE) indicating to return a vector of NCBI Protein IDs if FALSE, or a named vector if TRUE. This named vector details the origin of the translated IDs, dividing them in DT, if it is a Direct Translation, or 1.0, 0.9 or 0.5, if it has been retrieved through any of the identical gene clusters.
bySimilarGenes	logical value (TRUE or FALSE) indicating to translate also through similar UniProt genes (100%, 90% or 50% of identity). Using TRUE value may take a long time, only advised if there is not a direct translation possible.

Value

A character vector of the same length as upId. If parameter exhaustiveMapping is TRUE, it will return a list instead of a character vector to avoid mixing the identifiers.

Examples

```
# Translate UniProt ID 'G9JVE6' to NCBI Protein
getUniProt2NCBIProtein('G9JVE6')

# Translate UniProt IDs 'A0SNL9' and 'G9JVE6' to NCBI Protein
getUniProt2NCBIProtein(c('A0SNL9', 'G9JVE6'))

# Get all possible translations of IDs 'A0SNL9', 'G9JVE6' with detailed origin
getUniProt2NCBIProtein(c('A0SNL9', 'G9JVE6'), detailedMapping = TRUE,
exhaustiveMapping = TRUE)
```

getUniProtSimilarGenes

Get similar UniProt genes by a given identity percentage

Description

Retrieves the cluster of genes with a certain percentage of identity where a given UniProt gene belongs.

Usage

```
getUniProtSimilarGenes(upId, clusterIdentity = '1.0', clusterNames = FALSE)
```

Arguments

upId	valid UniProt ID or a vector of them
clusterIdentity	identity of the cluster to be retrieved. Default value 1.0 returns the 100% identical genes cluster, values 0.9 and 0.5, the 90% and 50% identical genes clusters, respectively
clusterNames	logical value (TRUE or FALSE) indicating if cluster names are retrieved

Value

A list of the same length as upId. If parameter clusterNames is TRUE it will return a named list.

Examples

```
# Get UniProt IDs of 50% identical genes of UniProt gene 'G0L217'
getUniProtSimilarGenes('G0L217', clusterIdentity = '0.5')

# Get UniProt IDs of 50% identical genes of UniProt genes 'G0L217' and 'A0SNL9'
getUniProtSimilarGenes(c('G0L217', 'A0SNL9'), clusterIdentity = '0.5')
```

getUniProtVersion	<i>Prints UniProt database version being used</i>
-------------------	---

Description

Prints the accessed UniProt version and its corresponding release date.

Usage

```
getUniProtVersion()
```

Value

UniProt database version.

updateCARDDataBase	<i>Downloads the most up-to-date version of CARD database</i>
--------------------	---

Description

Cleans previous CARD database versions if there were, and downloads its latest version.

Usage

```
updateCARDDataBase()
```

Value

Downloaded CARD database.

Index

[changeCARDPath, 2](#)

[getCARD2KEGG, 3](#)

[getCARD2NCBIGene, 4](#)

[getCARD2NCBINucleotide, 5](#)

[getCARD2NCBIProtein, 5](#)

[getCARD2UniProt, 6](#)

[getCARDVersion, 7](#)

[getKEGG2CARD, 7](#)

[getKEGG2NCBIGene, 8](#)

[getKEGG2NCBINucleotide, 9](#)

[getKEGG2NCBIProtein, 10](#)

[getKEGG2UniProt, 11](#)

[getKEGGVersion, 12](#)

[getNCBIGene2CARD, 12](#)

[getNCBIGene2KEGG, 13](#)

[getNCBIGene2NCBINucleotide, 14](#)

[getNCBIGene2NCBIProtein, 14](#)

[getNCBIGene2UniProt, 15](#)

[getNCBIIdenticalProteins, 16](#)

[getNCBINucleotide2CARD, 17](#)

[getNCBINucleotide2KEGG, 17](#)

[getNCBINucleotide2NCBIGene, 18](#)

[getNCBINucleotide2NCBIProtein, 19](#)

[getNCBINucleotide2UniProt, 20](#)

[getNCBIProtein2CARD, 21](#)

[getNCBIProtein2KEGG, 22](#)

[getNCBIProtein2NCBIGene, 23](#)

[getNCBIProtein2NCBINucleotide, 23](#)

[getNCBIProtein2UniProt, 24](#)

[getNCBIVersion, 25](#)

[getUniProt2CARD, 25](#)

[getUniProt2KEGG, 26](#)

[getUniProt2NCBIGene, 27](#)

[getUniProt2NCBINucleotide, 28](#)

[getUniProt2NCBIProtein, 29](#)

[getUniProtSimilarGenes, 30](#)

[getUniProtVersion, 31](#)

[updateCARDDataBase, 31](#)