

# Package ‘DFP’

October 30, 2025

**Type** Package

**Title** Gene Selection

**Version** 1.69.0

**Date** 2009-07-22

**Author** R. Alvarez-Gonzalez, D. Glez-Pena, F. Diaz, F. Fdez-Riverola

**Maintainer** Rodrigo Alvarez-Glez <rodrigo.djv@uvigo.es>

**Depends** methods, Biobase (>= 2.5.5)

**Collate** AllClasses.R show-methods.R DFP.R

**LazyLoad** Yes

**Description** This package provides a supervised technique able to identify differentially expressed genes, based on the construction of \emph{Fuzzy Patterns} (FPs). The Fuzzy Patterns are built by means of applying 3 Membership Functions to discretized gene expression values.

**License** GPL-2

**biocViews** Microarray, DifferentialExpression

**git\_url** <https://git.bioconductor.org/packages/DFP>

**git\_branch** devel

**git\_last\_commit** 5d2534a

**git\_last\_commit\_date** 2025-10-29

**Repository** Bioconductor 3.23

**Date/Publication** 2025-10-30

## Contents

|                                             |   |
|---------------------------------------------|---|
| DFP-package . . . . .                       | 2 |
| calculateDiscriminantFuzzyPattern . . . . . | 3 |
| calculateFuzzyPatterns . . . . .            | 4 |
| calculateMembershipFunctions . . . . .      | 5 |
| DFP-internal . . . . .                      | 6 |

|                                        |           |
|----------------------------------------|-----------|
| discretizeExpressionValues . . . . .   | 7         |
| discriminantFuzzyPattern . . . . .     | 8         |
| ExpressionLevel-class . . . . .        | 10        |
| HighExpressionLevel-class . . . . .    | 11        |
| LowExpressionLevel-class . . . . .     | 12        |
| MediumExpressionLevel-class . . . . .  | 13        |
| plotDiscriminantFuzzyPattern . . . . . | 14        |
| plotMembershipFunctions . . . . .      | 15        |
| readCSV . . . . .                      | 16        |
| rmdatase . . . . .                     | 17        |
| show-methods . . . . .                 | 18        |
| showDiscreteValues . . . . .           | 18        |
| showFuzzyPatterns . . . . .            | 19        |
| <b>Index</b>                           | <b>20</b> |

---

|             |                      |
|-------------|----------------------|
| DFP-package | DFP Package Overview |
|-------------|----------------------|

---

**Description**

This package provides a supervised technique able to identify differentially expressed genes, based on the construction of *Fuzzy Patterns* (FPs). The *Fuzzy Patterns* are built by means of applying 3 *Membership Functions* to discretized gene expression values.

**Details**

Package: DFP  
Type: Package  
Version: 1.0  
Date: 2008-07-03  
License: GPL-2

The main functionality of the package is provided by the [discriminantFuzzyPattern](#) function, which works in a 4-step process:

1. Calculates the *Membership Functions*. These functions are used in the next step to discretize gene expression data.
2. Discretizes the gene expression data (float values) into ‘Low’, ‘Medium’ or ‘High’ labels.
3. Calculates a *Fuzzy Pattern* for each category. To do this, a given percentage of the samples belonging to a category must have the same label (‘Low’, ‘Medium’ or ‘High’).
4. Calculates the *Discriminant Fuzzy Pattern* (DFP) that includes those genes present in two or more FPs with different assigned labels.

Additional data classes: [ExpressionSet](#), [AnnotatedDataFrame](#).

**Author(s)**

Rodrigo Alvarez-Gonzalez  
 Daniel Glez-Pena  
 Fernando Diaz  
 Florentino Fdez-Riverola  
 Maintainer: Rodrigo Alvarez-Gonzalez <rodrigo.djv@uvigo.es>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

**Examples**

```
#####
##### Get sample data #####
#####
library(DFP)
data(rmadataset)

#####
# Filter the most representative genes #
#####
res <- discriminantFuzzyPattern(rmadataset)

#####
##### Different result displays #####
#####
plotMembershipFunctions(rmadataset, res$membership.functions, featureNames(rmadataset)[1:2])
showDiscreteValues(res$discrete.values, featureNames(rmadataset)[1:10], c("healthy", "AML-inv"))
showFuzzyPatterns(res$fuzzy.patterns, "healthy")[21:50]
plotDiscriminantFuzzyPattern(res$discriminant.fuzzy.pattern)
```

---

calculateDiscriminantFuzzyPattern

*Calculates the Discriminant Fuzzy Pattern to select significant genes*

---

**Description**

Calculates the *Discriminant Fuzzy Pattern* (DFP) that includes those genes present in two or more FPs with different assigned labels.

**Usage**

```
calculateDiscriminantFuzzyPattern(rmadataset, fps)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rmdatataset | <a href="#">ExpressionSet</a> with numeric values containing gene expression values (rows) of samples belonging to different categories (columns).<br>The <a href="#">ExpressionSet</a> also contains an <a href="#">AnnotatedDataFrame</a> with metadata regarding the classes to which each sample belongs. |
| fps         | Genes belonging to each <i>Fuzzy Patterns</i> . There are one FP for each class.<br>Includes an attribute <i>ifs</i> with the <i>Impact Factor</i> for each category.                                                                                                                                         |

**Value**

Genes belonging to the final DFP.  
Includes an attribute *ifs* with the *Impact Factor* for each category.

**Author(s)**

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

calculateFuzzyPatterns

*Calculates a Fuzzy Pattern for each category of the samples*

---

**Description**

Calculates a *Fuzzy Pattern* for each category. To do this, a given percentage of the samples belonging to a category must have the same label ('Low', 'Medium' or 'High').

**Usage**

```
calculateFuzzyPatterns(rmdatataset, dvs, piVal = 0.9, overlapping = 2)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                               |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rmdatataset | <a href="#">ExpressionSet</a> with numeric values containing gene expression values (rows) of samples belonging to different categories (columns).<br>The <a href="#">ExpressionSet</a> also contains an <a href="#">AnnotatedDataFrame</a> with metadata regarding the classes to which each sample belongs. |
|-------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|             |                                                                                                                                                                                                                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dvs         | Matrix containing discrete values according to the overlapping parameter after discretizing the gene expression values.<br>Includes an attribute <i>types</i> which determines the category of each sample.                                                                                                                                                 |
| piVal       | Controls the degree of exigency for selecting a gene as a member of a <i>Fuzzy Pattern</i> .<br>Default value = 0.9. Range[0,1].                                                                                                                                                                                                                            |
| overlapping | Modifies the number of membership functions used in the discretization process.<br>Possible values: <ol style="list-style-type: none"> <li>1. 'Low', 'Medium', 'High'.</li> <li>2. 'Low', 'Low-Medium', 'Medium', 'Medium-High', 'High'.</li> <li>3. 'Low', 'Low-Medium', 'Low-Medium-High', 'Medium', 'Medium-High', 'High'.</li> </ol> Default value = 2. |

**Value**

Genes belonging to each *Fuzzy Patterns*. There are one FP for each class.  
Includes an attribute *ifs* with the *Impact Factor* for each category.

**Author(s)**

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

calculateMembershipFunctions

*Calculates Membership Functions*

---

**Description**

Calculates the *Membership Functions*. These functions are used in the next step ([discretizeExpressionValues](#)) to discretize gene expression data.

**Usage**

```
calculateMembershipFunctions(rmadataset, skipFactor = 3)
```

**Arguments**

- rmdatataset**      [ExpressionSet](#) with numeric values containing gene expression values (rows) of samples belonging to different categories (columns).  
The [ExpressionSet](#) also contains an [AnnotatedDataFrame](#) with metadata regarding the classes to which each sample belongs.
- skipFactor**      Numeric value to omit odd values (a way of normalization).  
Higher values imply that less samples of a gene are considered as odd. If *skipFactor*=0 do **NOT** skip.  
Default value = 3. Range[0, ).

**Value**

*Membership functions* to determine the discret value (linguistic label) corresponding to a given gene expression level.

**Author(s)**

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

 DFP-internal

---

*Internal DFP objects*


---

**Description**

Internal DFP objects.

**Details**

These are not to be called by the user.

---

`discretizeExpressionValues`*Function to discretize gene expression data*

---

## Description

Discretizes the gene expression data (float values) into 'Low', 'Medium' or 'High' labels.

## Usage

```
discretizeExpressionValues(rmadataSet, mfs, zeta = 0.5, overlapping = 2)
```

## Arguments

|                          |                                                                                                                                                                                                                                                                                                                                                               |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>rmadataSet</code>  | <a href="#">ExpressionSet</a> with numeric values containing gene expression values (rows) of samples belonging to different categories (columns).<br>The <a href="#">ExpressionSet</a> also contains an <a href="#">AnnotatedDataFrame</a> with metadata regarding the classes to which each sample belongs.                                                 |
| <code>mfs</code>         | <i>Membership functions</i> to determine the discret value (linguistic label) corresponding to a given gene expression level.                                                                                                                                                                                                                                 |
| <code>zeta</code>        | Threshold value which controls the activation of a linguistic label ('Low', 'Medium' or 'High').<br>The lower, the less possibilities of having genes with more than one assigned linguistic label.<br>Default value = 0.5. Range[0,1].                                                                                                                       |
| <code>overlapping</code> | Modifies the number of membership functions used in the discretization process.<br>Possible values:<br><ol style="list-style-type: none"><li>1. 'Low', 'Medium', 'High'.</li><li>2. 'Low', 'Low-Medium', 'Medium', 'Medium-High', 'High'.</li><li>3. 'Low', 'Low-Medium', 'Low-Medium-High', 'Medium', 'Medium-High', 'High'.</li></ol><br>Default value = 2. |

## Value

Matrix containing discrete values according to the overlapping parameter after discretizing the gene expression values.

Includes an attribute *types* which determines the category of each sample.

## Author(s)

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

discriminantFuzzyPattern

*Discriminant Fuzzy Pattern to filter genes*

---

## Description

*discriminantFuzzyPattern* discovers significant genes based on the construction of *Fuzzy Patterns* (FPs). The *Fuzzy Patterns* are built by means of applying 3 *Membership Functions* to the gene expression values in the matrix *rmadataset*.

## Usage

```
discriminantFuzzyPattern(rmadataset, skipFactor = 3, zeta = 0.5, overlapping = 2, piVal = 0.9)
```

## Arguments

|             |                                                                                                                                                                                                                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| rmadataset  | <a href="#">ExpressionSet</a> with numeric values containing gene expression values (rows) of samples belonging to different categories (columns).<br>The <a href="#">ExpressionSet</a> also contains an <a href="#">AnnotatedDataFrame</a> with metadata regarding the classes to which each sample belongs.                                               |
| skipFactor  | Numeric value to omit odd values (a way of normalization).<br>Higher values imply that less samples of a gene are considered as odd. If <i>skipFactor</i> =0 do <b>NOT</b> skip.<br>Default value = 3. Range[0, ).                                                                                                                                          |
| zeta        | Threshold value which controls the activation of a linguistic label ('Low', 'Medium' or 'High').<br>The lower, the less possibilities of having genes with more than one assigned linguistic label.<br>Default value = 0.5. Range[0, 1].                                                                                                                    |
| overlapping | Modifies the number of membership functions used in the discretization process.<br>Possible values: <ol style="list-style-type: none"> <li>1. 'Low', 'Medium', 'High'.</li> <li>2. 'Low', 'Low-Medium', 'Medium', 'Medium-High', 'High'.</li> <li>3. 'Low', 'Low-Medium', 'Low-Medium-High', 'Medium', 'Medium-High', 'High'.</li> </ol> Default value = 2. |
| piVal       | Controls the degree of exigency for selecting a gene as a member of a <i>Fuzzy Pattern</i> .<br>Default value = 0.9. Range[0, 1].                                                                                                                                                                                                                           |



## Details

The `discriminantFuzzyPattern` function works in a 4-step process:

1. Calculates the *Membership Functions*. These functions are used in the next step to discretize gene expression data.
2. Discretizes the gene expression data (float values) into 'Low', 'Medium' or 'High' labels.
3. Calculates a *Fuzzy Pattern* for each category. To do this, a given percentage of the samples belonging to a category must have the same label ('Low', 'Medium' or 'High').
4. Calculates the *Discriminant Fuzzy Pattern* (DFP) that includes those genes present in two or more FPs with different assigned labels.

## Value

|                                         |                                                                                                                                                                                           |
|-----------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>membership.functions</code>       | <i>Membership functions</i> to determine the discret value corresponding to a given gene expression level.                                                                                |
| <code>discrete.values</code>            | Discrete values according to the overlapping parameter after discretizing the gene expression values.<br>Includes an attribute <i>types</i> which determines the category of each sample. |
| <code>fuzzy.patterns</code>             | Genes belonging to each <i>Fuzzy Patterns</i> . There are one FP for each class.<br>Includes an attribute <i>ifs</i> with the <i>Impact Factor</i> for each category.                     |
| <code>discriminant.fuzzy.pattern</code> | Genes belonging to the final DFP.<br>Includes an attribute <i>ifs</i> with the <i>Impact Factor</i> for each category.                                                                    |
| <code>params</code>                     | The parameters used to tune the algorithm (as arguments in the function).                                                                                                                 |

## Author(s)

Rodrigo Alvarez-Gonzalez  
 Daniel Glez-Pena  
 Fernando Diaz  
 Florentino Fdez-Riverola  
 Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

## Examples

```
#####
##### Get sample data #####
#####
library(DFP)
data(rmadataset)
```

```
#####
# Filters the most representative genes #
#####
res <- discriminantFuzzyPattern(rmadataset)
summary(res)
```

---

ExpressionLevel-class    Class "ExpressionLevel"

---

### Description

A virtual class which represents a generic *Membership Function*.

### Objects from the Class

A virtual Class: No objects may be created from it.

### Slots

**center:** Object of class "numeric". Represents the peak point in the function curve.

**width:** Object of class "numeric". Represents the length of values lower than 1 and greater than 0 in the function curve.

### Methods

**show** signature(object = "ExpressionLevel"): Prints the ExpressionLevel subclass of the object.

**setValues** signature(object = "ExpressionLevel", values = "numeric"): Generic function to be implemented in the subclasses.

**computeMembership** signature(object = "ExpressionLevel", x = "numeric"): Generic function to be implemented in the subclasses.

### Author(s)

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

### References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

**Examples**

```
showClass("ExpressionLevel")
```

---

```
HighExpressionLevel-class  
  Class "HighExpressionLevel"
```

---

**Description**

A class which represents a *Membership Function* to determine the membership of a numeric value to the 'High' discrete label. The result depends on the 'center' and 'width' values.

**Objects from the Class**

Objects can be created by calls of the form `new("HighExpressionLevel")`.

**Slots**

**center:** Object of class "numeric". Represents the peak point in the function curve.

**width:** Object of class "numeric". Represents the length of values lower than 1 and greater than 0 in the function curve.

**Extends**

Class "[ExpressionLevel](#)", directly.

**Methods**

**setValues** signature(object = "HighExpressionLevel", values = "numeric"): Establishes the 'center' and 'width' slots of the object, given a vector of numeric values.

**computeMembership** signature(object = "HighExpressionLevel", x = "numeric"): Returns a value in the [0,1] interval, which represents the membership to the 'High' discrete label.

**Author(s)**

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

**Examples**

```
showClass("HighExpressionLevel")
```

---

```
LowExpressionLevel-class
```

```
Class "LowExpressionLevel"
```

---

**Description**

A class which represents a *Membership Function* to determine the membership of a numeric value to the 'Low' discrete label. The result depends on the 'center' and 'width' values.

**Objects from the Class**

Objects can be created by calls of the form `new("LowExpressionLevel")`.

**Slots**

**center:** Object of class "numeric". Represents the peak point in the function curve.

**width:** Object of class "numeric". Represents the length of values lower than 1 and greater than 0 in the function curve.

**Extends**

Class "[ExpressionLevel](#)", directly.

**Methods**

**setValues** signature(object = "LowExpressionLevel", values = "numeric"): Establishes the 'center' and 'width' slots of the object, given a vector of numeric values.

**computeMembership** signature(object = "LowExpressionLevel", x = "numeric"): Returns a value in the [0,1] interval, which represents the membership to the 'Low' discrete label.

**Author(s)**

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

**Examples**

```
showClass("LowExpressionLevel")
```

---

```
MediumExpressionLevel-class  
  Class "MediumExpressionLevel"
```

---

**Description**

A class which represents a *Membership Function* to determine the membership of a numeric value to the 'Medium' discrete label. The result depends on the 'center' and 'width' values.

**Objects from the Class**

Objects can be created by calls of the form `new("MediumExpressionLevel")`.

**Slots**

**center:** Object of class "numeric". Represents the peak point in the function curve.

**width:** Object of class "numeric". Represents the length of values lower than 1 and greater than 0 in the function curve.

**Extends**

Class "[ExpressionLevel](#)", directly.

**Methods**

**setValues** signature(object = "MediumExpressionLevel", values = "numeric"): Establishes the 'center' and 'width' slots of the object, given a vector of numeric values.

**computeMembership** signature(object = "MediumExpressionLevel", x = "numeric"): Returns a value in the [0,1] interval, which represents the membership to the 'Medium' discrete label.

**Author(s)**

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

**References**

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

**Examples**

```
showClass("MediumExpressionLevel")
```

---

```
plotDiscriminantFuzzyPattern
```

*Plots the Discriminant Fuzzy Pattern of the relevant genes*

---

**Description**

This function plots the *Discriminant Fuzzy Pattern* of the relevant genes (in rows) for the sample classes (in columns), as well as the impact factor which determines if a gene belongs to a *Fuzzy Pattern* in a class (if its value is higher than the *piVal*).

The relevant genes are those which are present in almost two different *Fuzzy Patterns* with different linguistic labels.

The plotting is made in both graphical and text mode.

**Usage**

```
plotDiscriminantFuzzyPattern(dfp, overlapping = 2)
```

**Arguments**

|             |                                                                                                                                                                                                                                                                                                                                                             |
|-------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dfp         | A matrix with the fuzzy patterns and impact factors for the relevant genes.                                                                                                                                                                                                                                                                                 |
| overlapping | Modifies the number of membership functions used in the discretization process.<br>Possible values: <ol style="list-style-type: none"> <li>1. 'Low', 'Medium', 'High'.</li> <li>2. 'Low', 'Low-Medium', 'Medium', 'Medium-High', 'High'.</li> <li>3. 'Low', 'Low-Medium', 'Low-Medium-High', 'Medium', 'Medium-High', 'High'.</li> </ol> Default value = 2. |

**Value**

A matrix with the discriminant genes in rows, along with the *Fuzzy Pattern* for each class (in columns).

This object contains an attribute (*ifs*) which stores the *Impact Factors* used to determine if a gene belongs to a *Fuzzy Pattern* in a class (if the value is higher than the *piVal*).

**Author(s)**

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

plotMembershipFunctions

*Plots the Membership Functions (Low, Medium, High) used to discretize gene expression values*

---

## Description

Each gene has 3 *Membership Functions* ('Low', 'Medium' and 'High') which can be plotted as curves in graphical mode.

In the text mode a membership function is represented with its *center* and *width*.

This function receives one or more gene names and plots the results in both graphical and text mode.

If a set of genes containing more than 36 elements is provided, only the text mode is available.

## Usage

```
plotMembershipFunctions(rmadataset, mfs, genes)
```

## Arguments

|            |                                                                                                                   |
|------------|-------------------------------------------------------------------------------------------------------------------|
| rmadataset | An <a href="#">ExpressionSet</a> object with <a href="#">AnnotatedDataFrame</a> metadata.                         |
| mfs        | A list of 3 <a href="#">ExpressionLevel</a> objects ('Low', 'Medium' and 'High') for each gene (a list of lists). |
| genes      | The set of genes to plot (a vector).                                                                              |

## Value

A dataframe with the values of the membership functions ('Low', 'Medium' and 'High') for each gene (in rows) received as a parameter.

## Author(s)

Rodrigo Alvarez-Gonzalez

Daniel Glez-Pena

Fernando Diaz

Florentino Fdez-Riverola

Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

|         |                                                                           |
|---------|---------------------------------------------------------------------------|
| readCSV | <i>Creates an ExpressionSet with an AnnotatedDataFrame from CSV files</i> |
|---------|---------------------------------------------------------------------------|

---

## Description

This function creates an [ExpressionSet](#) with an [AnnotatedDataFrame](#). To do this, it requires two CSV files in a predefined format:

1. 'exprsData' with the expression values of genes (in rows) of different samples (in columns).
2. 'pData' with the samples (in columns) and the metadata 'class' (the most important for the algorithm [discriminantFuzzyPattern](#)), 'age' and 'sex'.

## Usage

```
readCSV(fileExprs, filePhenodata)
```

## Arguments

fileExprs        The path to the exprsData file.  
filePhenodata   The path to the pData file.

## Value

An [ExpressionSet](#) object with an [AnnotatedDataFrame](#) storing 'class', 'age' and 'sex' information.

## Author(s)

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

## Examples

```
dataDir <- system.file("extdata", package="DFP"); dataDir
fileExprs <- file.path(dataDir, "exprsData.csv"); fileExprs
filePhenodata <- file.path(dataDir, "pData.csv"); filePhenodata
rmdatataset <- readCSV(fileExprs, filePhenodata); rmdatataset
pData(phenoData(rmdatataset))
exprs(rmdatataset)[1:10,1:5]
```



---

|            |                                      |
|------------|--------------------------------------|
| rmadataset | <i>A sample ExpressionSet object</i> |
|------------|--------------------------------------|

---

## Description

This [ExpressionSet](#) object includes an [AnnotatedDataFrame](#) with metadata about ‘Disease type’ (the most important for the algorithm), ‘Patient age’ and ‘Patient gender’.  
This data set gives the expression values of 500 genes in 35 samples.

## Usage

```
data(rmadataset)
```

## Format

```
ExpressionSet      str(pData(phenoData(rmadataset)))  
AnnotatedDataFrame str(exprs(rmadataset))
```

## Author(s)

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

## Examples

```
data(rmadataset)  
featureNames(rmadataset)[1:20]  
sampleNames(rmadataset)  
varLabels(rmadataset)  
pData(phenoData(rmadataset))  
exprs(rmadataset)[1:10, 1:5]
```

---

|              |                                                                   |
|--------------|-------------------------------------------------------------------|
| show-methods | <i>Prints the slots (attributes) of an ExpressionLevel object</i> |
|--------------|-------------------------------------------------------------------|

---

### Description

Prints the slots (center and width) of an "[ExpressionLevel](#)" object.

### Methods

**object** = "[ExpressionLevel](#)" See "[ExpressionLevel](#)".

---

|                    |                                                                                     |
|--------------------|-------------------------------------------------------------------------------------|
| showDiscreteValues | <i>Prints the labels to which the algorithm converts the gene expression values</i> |
|--------------------|-------------------------------------------------------------------------------------|

---

### Description

In an intermediate step, the algorithm [discriminantFuzzyPattern](#) converts the gene expression values into discrete labels (combining 'Low', 'Medium' and 'High', depending on the value of the param 'overlapping').

This function permits printing these labels, specifying a set of genes (a vector) and/or classes of samples.

### Usage

```
showDiscreteValues(dvs, genes, classes)
```

### Arguments

|         |                                                                                                                                                                      |
|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| dvs     | A matrix with discrete labels for a set of genes (in rows) of several samples (in columns).                                                                          |
| genes   | [optional] The set of genes to plot.                                                                                                                                 |
| classes | [optional] A set of classes to which the samples belong. It must be one of the classes stored in the phenoData of the original <a href="#">ExpressionSet</a> object. |

### Value

A subset of the matrix dvs determined by the restrictions (genes and/or classes).

### Author(s)

Rodrigo Alvarez-Gonzalez  
 Daniel Glez-Pena  
 Fernando Diaz  
 Florentino Fdez-Riverola  
 Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

---

|                   |                                                          |
|-------------------|----------------------------------------------------------|
| showFuzzyPatterns | <i>Plots the Fuzzy Patterns corresponding to a class</i> |
|-------------------|----------------------------------------------------------|

---

## Description

This functions prints (in text mode) the *Fuzzy Patterns* (discrete labels) calculated for a single class of samples.

## Usage

```
showFuzzyPatterns(fps, class)
```

## Arguments

|       |                                                                                                                                                                    |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fps   | A matrix with the <i>Fuzzy Patterns</i> (discrete labels) for all the samples and genes.                                                                           |
| class | A class to which the samples belong. It must be one of the classes stored in the phenoData of the original <a href="#">ExpressionSet</a> <i>rmadataset</i> object. |

## Value

A vector of *Fuzzy Patterns* (discrete labels) for a single class of samples, with the genes associated.

## Author(s)

Rodrigo Alvarez-Gonzalez  
Daniel Glez-Pena  
Fernando Diaz  
Florentino Fdez-Riverola  
Maintainer: Rodrigo Alvarez-Gonzalez <<rodrigo.djv@uvigo.es>>

## References

F. Diaz; F. Fdez-Riverola; D. Glez-Pena; J.M. Corchado. Using Fuzzy Patterns for Gene Selection and Data Reduction on Microarray Data. 7th International Conference on Intelligent Data Engineering and Automated Learning: IDEAL 2006, (2006) pp. 1095-1102

# Index

## \* classes

ExpressionLevel-class, [10](#)  
HighExpressionLevel-class, [11](#)  
LowExpressionLevel-class, [12](#)  
MediumExpressionLevel-class, [13](#)

## \* datasets

rmadataset, [17](#)

## \* internal

DFP-internal, [6](#)

## \* manip

calculateDiscriminantFuzzyPattern, [3](#)  
calculateFuzzyPatterns, [4](#)  
calculateMembershipFunctions, [5](#)  
discretizeExpressionValues, [7](#)  
discriminantFuzzyPattern, [8](#)  
plotDiscriminantFuzzyPattern, [14](#)  
plotMembershipFunctions, [15](#)  
readCSV, [16](#)  
showDiscreteValues, [18](#)  
showFuzzyPatterns, [19](#)

## \* methods

show-methods, [18](#)

## \* package

DFP-package, [2](#)

.calculateDiscriminantFuzzyPattern  
(DFP-internal), [6](#)  
.calculateFuzzyPatterns (DFP-internal),  
[6](#)  
.calculateMembershipFunctions  
(DFP-internal), [6](#)  
.computeMembershipHigh (DFP-internal), [6](#)  
.computeMembershipLow (DFP-internal), [6](#)  
.computeMembershipMedium  
(DFP-internal), [6](#)  
.discretizeExpressionValues  
(DFP-internal), [6](#)  
.fuzzyDiscretization (DFP-internal), [6](#)  
.fuzzyPatterns (DFP-internal), [6](#)

.plotGeneMF (DFP-internal), [6](#)  
.setValuesHigh (DFP-internal), [6](#)  
.setValuesLow (DFP-internal), [6](#)  
.setValuesMedium (DFP-internal), [6](#)  
.skipOddValues (DFP-internal), [6](#)

AnnotatedDataFrame, [2, 4, 6–8, 15–17](#)

calculateDiscriminantFuzzyPattern, [3](#)  
calculateFuzzyPatterns, [4](#)  
calculateMembershipFunctions, [5](#)  
computeMembership, HighExpressionLevel-method  
(HighExpressionLevel-class), [11](#)  
computeMembership, LowExpressionLevel-method  
(LowExpressionLevel-class), [12](#)  
computeMembership, MediumExpressionLevel-method  
(MediumExpressionLevel-class),  
[13](#)

DFP (DFP-package), [2](#)

DFP-internal, [6](#)

DFP-package, [2](#)

discretizeExpressionValues, [5, 7](#)

discriminantFuzzyPattern, [2, 8, 9, 16, 18](#)

ExpressionLevel, [11–13, 18](#)

ExpressionLevel-class, [10](#)

ExpressionSet, [2, 4, 6–8, 15–19](#)

HighExpressionLevel-class, [11](#)

LowExpressionLevel-class, [12](#)

MediumExpressionLevel-class, [13](#)

plotDiscriminantFuzzyPattern, [14](#)  
plotMembershipFunctions, [15](#)

readCSV, [16](#)

rmadataset, [17](#)

setValues,HighExpressionLevel-method  
    (HighExpressionLevel-class), [11](#)  
setValues,LowExpressionLevel-method  
    (LowExpressionLevel-class), [12](#)  
setValues,MediumExpressionLevel-method  
    (MediumExpressionLevel-class),  
    [13](#)  
show,ExpressionLevel-method  
    (ExpressionLevel-class), [10](#)  
show-methods, [18](#)  
showDiscreteValues, [18](#)  
showFuzzyPatterns, [19](#)