

Package ‘Sushi’

April 15, 2017

Type Package

Title Tools for visualizing genomics data

Description Flexible, quantitative, and integrative genomic visualizations for publication-quality multi-panel figures

Version 1.12.0

Date 2015-05-06

Author Douglas H Phanstiel <dphansti@stanford.edu>

Maintainer Douglas H Phanstiel <dphansti@stanford.edu>

biocViews DataRepresentation, Visualization, Genetics, Sequencing,
Infrastructure, HiC

License GPL (>= 2)

Depends R (>= 2.10), zoo,biomaRt

Imports graphics, grDevices

NeedsCompilation no

R topics documented:

addlegend	2
chromOffsets	3
convertstrandinfo	3
labelgenome	4
labelplot	5
maptocolors	6
maptolwd	6
opaque	7
plotBed	7
plotBedgraph	9
plotBedpe	10
plotGenes	12
plotHic	13
plotManhattan	14
sortChrom	15
SushiColors	15
Sushi_5C.bedpe	16
Sushi_ChIAPET_pol2.bedpe	16
Sushi_ChIPExo_CTCF.bedgraph	17

Sushi_ChIPSeq_CTCF.bedgraph	17
Sushi_ChIPSeq_pol2.bed	18
Sushi_ChIPSeq_pol2.bedgraph	18
Sushi_ChIPSeq_severalfactors.bed	19
Sushi_DNaseI.bedgraph	19
Sushi_genes.bed	20
Sushi_GWAS.bed	20
Sushi_hg18_genome	21
Sushi_HiC.matrix	21
Sushi_RNASeq_K562.bedgraph	22
Sushi_transcripts.bed	22
zoombox	23
zoomsregion	24

Index**27**

addlegend	<i>adds a legend to a Sushi plot</i>
------------------	--------------------------------------

Description

This function adds a legend to Sushi plots that have a colorby function (e.g. `plotHic`, `plotGenes`, and `plotBedpe`)

Usage

```
addlegend(range, title = "", labels.digits = 1, palette = topo.colors,
          side = "right", labelside = "left", xoffset = 0.1, width = 0.05,
          bottominset = 0.025, topinset = 0.025, tick.num = 5,
          tick.length = 0.01, txt.font = 1, txt.cex = 0.75, title.offset = 0.05,
          title.font = 2, title.cex = 1)
```

Arguments

range	the range of values to be plotted. ie <code>c(min,max)</code>
title	title of values to be mapped
labels.digits	Number of digits after the decimal point to include in labels
palette	color palette to use
side	side of plot to place legend ('right','left')
labelside	side of legend to place legend title
xoffset	fraction of plot to offset the legend
width	width as a fraction of the plot width
bottominset	inset from the bottom of the blot as a fraction of the plot width
topinset	inset from the top of the blot as a fraction of the plot width
tick.num	desired number of tickmarks
tick.length	length of tick marks
txt.font	font type of legend text
txt.cex	font size of legned text

title.offset	offset of title from the key
title.font	font type of legend title
title.cex	font size of legned text

Examples

```
data(Sushi_HiC.matrix)

chrom          = "chr11"
chromstart     = 500000
chromend       = 5050000

phic = plotHiC(Sushi_HiC.matrix,chrom,chromstart,chromend,max_y = 20,zrange=c(0,28),palette = topo.colors,flabel=1)
labelgenome(chrom,chromstart,chromend,side=1,scipen=20,n=4,scale="Mb",edgeblankfraction=0.20,line=.18,chromwidth=1)
addlegend(phic[[1]],palette=phic[[2]],title="score",side="right",bottominset=0.4,topinset=0,xoffset=-.035,yoffset=.05)
```

chromOffsets	<i>defines chromosome offsets for plotting multi chromosomal plot (eg plotManhattan)</i>
--------------	--

Description

defines chromosome offsets for plotting multi chromosomal plot (eg plotManhattan)

Usage

```
chromOffsets(genome, space = 0.01)
```

Arguments

genome	A genome object to be used (2 columns: column 1 = chromosome name, column 2 = length of chromosome)
space	the space in between each chromosome as a fraction of the width of the plot

convertstrandinfo	<i>Converts strand info to 1 / -1</i>
-------------------	---------------------------------------

Description

Converts strand info to 1 / -1

Usage

```
convertstrandinfo(strandvector)
```

Arguments

strandvector	vector of strand information to convert from +/- to 1/-1 if neccesary
--------------	---

labelgenome*Adds genome coordinates to the x-axis of a Sushi plot***Description**

Adds genome coordinates to the x-axis of a Sushi plot

Usage

```
labelgenome(chrom, chromstart, chromend, genome = NULL, space = 0.01,
           scale = "bp", side = 1, scipen = 20, n = 5, chromfont = 2,
           chromadjust = 0.015, chromcex = 1, chromline = 0.5, scalefont = 2,
           scaleadjust = 0.985, scalecex = 1, scaleline = 0.5, line = 0.18,
           edgeblankfraction = 0.1, ...)
```

Arguments

<code>chrom</code>	chromosome to plot
<code>chromstart</code>	start position
<code>chromend</code>	end position
<code>genome</code>	a genome object (2 columns: column 1 = chromosome name, column 2 = length of chromosome). Only for multi chromosomal plots
<code>space</code>	the space in between each chromosome as a fraction of the width of the plot. Only for multi chromosomal plots
<code>scale</code>	Scale of the plot ('bp','Kb','Mb')
<code>side</code>	Side of the scale to add the plot to. Only tested for sides 1 and 3.
<code>scipen</code>	higher values decrease the likelihood of using scientific for the position labels.
<code>n</code>	Desired number of ticks
<code>chromfont</code>	font type of chromosome label
<code>chromadjust</code>	position, as a fraction of the width of the plot, of the chromosome label
<code>chromcex</code>	font size of the chromosome label
<code>chromline</code>	vertical offset of the chromosome label
<code>scalefont</code>	font type of scale label
<code>scaleadjust</code>	position, as a fraction of the width of the plot, of the scale label
<code>scalecex</code>	font size of the scale label
<code>scaleline</code>	vertical offset of the scale label
<code>line</code>	vertical offset of position labels
<code>edgeblankfraction</code>	percent of the edges to leave black for chromosome and scale labels
<code>...</code>	values to be passed to axis

Examples

```
data(Sushi_DNaseI.bedgraph)
# set the genomic regions

plotBedgraph(Sushi_DNaseI.bedgraph,chrom="chr11",chromstart=1650000,chromend=2350000,colorbycol=SushiColors)
labelgenome(chrom="chr11",chromstart=1650000,chromend=2350000,side=1,n=4,scale="Mb")
axis(side=2,las=2,tcl=.2)
mtext("Read Depth",side=2,line=1.75,cex=.75,font=2)
```

labelplot

adds a letter and a title to a plot

Description

This function adds a letter and a title (both are optional) to the top of a plot. Useful for generating paper figures.

Usage

```
labelplot(letter = NULL, title = NULL, letteradj = -0.05, titleadj = 0,
         letterfont = 2, titlefont = 2, lettercex = 1.2, titlecex = 1,
         letterline = 0.5, titleline = 0.5, lettercol = "black",
         titlecol = "black")
```

Arguments

letter	A string, typically a letter or number (eg 'A', 'A)', '1', etc) to label the plot with
title	A string for a plot title
letteradj	adj of letter. See par
titleadj	adj of title. See par
letterfont	font of letter. See par
titlefont	font of title See par
lettercex	cex of letter. See par
titlecex	cex of title See par
letterline	line of letter. See par
titleline	line of title See par
lettercol	color of letter. See par
titlecol	color of title See par

Examples

```
par(mar=c(3,3,3,3))
plot((1:10),col=maptocolors(vec=(1:10),colorRampPalette(c("blue","red")))),pch=19,cex=4)
labelplot("A"," sample plot",lettercex=2,titlecex=2,titlecol="blue")
```

maptocolors*maps numeric vector to color palette***Description**

maps numeric vector to color palette

Usage

```
maptocolors(vec, col, num = 100, range = NULL)
```

Arguments

<code>vec</code>	numeric vector to map to color
<code>col</code>	color palette to which to be mapped
<code>num</code>	number of bins of colors
<code>range</code>	range of values to map

Examples

```
plot((1:10), col=maptocolors(vec=(1:10), colorRampPalette(c("blue", "red"))), pch=19, cex=4)
```

maptolwd*maps numeric vector to line widths***Description**

maps numeric vector to line widths

Usage

```
maptolwd(lwdby, range = c(1, 5))
```

Arguments

<code>lwdby</code>	numeric vector to map to line widths
<code>range</code>	range of values to map

Examples

```
plot((1:10), lwd=maptolwd(lwdby=(1:10)))
```

opaque	<i>makes colors transparent (or opaque)</i>
--------	---

Description

makes colors transparent (or opaque)

Usage

```
opaque(color = SushiColors(7)(7), transparency = 0.5)
```

Arguments

- | | |
|--------------|---|
| color | color or colors to make opaque |
| transparency | value between 0 and 1 indicating desired opaqueness |

Examples

```
plot((1:10), col="red", pch=19)
points((10:1), col=opaque("red", transparency=0.3), pch=19)
```

plotBed	<i>plots data stored in bed file format</i>
---------	---

Description

plots data stored in bed file format

Usage

```
plotBed(beddata, chrom, chromstart, chromend, type = "region",
        colorby = NULL, colorbycol = NULL, colorbyrange = NULL,
        rownumber = NULL, row = "auto", height = 0.4, plotbg = "white",
        wiggle = 0.02, splitstrand = FALSE, numbins = 200, binsmoothing = 10,
        palettes = topo.colors, rowlabels = NULL, rowlabelcol = "dodgerblue2",
        rowlabelfont = 2, rowlabelcex = 1, maxrows = 1e+06,
        color = "dodgerblue4", xaxt = "none", yaxt = "none", xlab = "",
        ylab = "", xaxs = "i", yaxs = "i", bty = "n", border = NA, ...)
```

Arguments

- | | |
|------------|---|
| beddata | genomic data to be plotted (in bed format) |
| chrom | chromosome of region to be plotted |
| chromstart | start position |
| chromend | end position |
| type | type of plot ('region','circles','density') |
| colorby | vector to scale colors by |
| colorbycol | palette to apply color scale to (only valid when colorby is not NULL) |

colorbyrange	the range of values to apply the color scale to. Values outside that range will be set to the limits of the range.
rownumber	vector giving the row numbers of each bed element to be plotted.
row	How row number should be determined. Appropriate values are 'auto' or 'supplied'
height	Value, typically between 0 and 1, that sets the height of each bed element
plotbg	The background color of the plot
wiggle	the fraction of the plot to leave blank on either side of each element to avoid overcrowding.
splitstrand	TRUE/FALSE indicating whether reverse strand bed elements should be plotted below the x axis. (only valid when row is set to 'auto')
numbins	The number of bins to divide the region into when type is set to density (only valid when type is set to 'density')
binsmoothing	umber of bins to sum together when type is set to density (only valid when type is set to 'density')
palettes	list of color palettes used for density plots. Each row can have a unique palette. number of palettes is less than the number of rows then only the first palette is used (only valid when type is set to 'density')
rowlabels	labels for the y-axis
rowlabelcol	color of the y-axis labels
rowlabelfont	font of the y-axis labels
rowlabelcex	font size of the y-axis labels
maxrows	The maximum number of rows to plot on the y-axis
color	single color or vector of colors to use to plot the points or regions (not valid when type is set to 'density')
xaxt	A character which specifies the x axis type. See par
yaxt	A character which specifies the y axis type. See par
xlab	Label for the x-axis
ylab	Label for the y-axis
xaxs	Must be set to 'i' for appropriate integration into Sushi plots. See par
yaxs	Must be set to 'i' for appropriate integration into Sushi plots. See par
bty	A character string which determined the type of box which is drawn about plots. See par
border	border color drawn around each bed element or density bin. Set to 'n' for none.
...	values to be passed to other functions

Examples

```

data(Sushi_ChIPSeq_severalfactors.bed)
chrom      = "chr15"
chromstart = 72800000
chromend   = 73100000
Sushi_ChIPSeq_severalfactors.bed$color = heat.colors(max(Sushi_ChIPSeq_severalfactors.bed$row))[Sushi_ChIPSeq_severalfactors.bed$row]
plotBed(beddata = Sushi_ChIPSeq_severalfactors.bed, chrom = chrom, chromstart = chromstart, chromend = chromend,
        rownumber = Sushi_ChIPSeq_severalfactors.bed$row, type = "circles", color=Sushi_ChIPSeq_severalfactors.bed$color,
        rowlabels=unique(Sushi_ChIPSeq_severalfactors.bed$name), rowlabelcol=unique(Sushi_ChIPSeq_severalfactors.bed$name))

```

```
Sushi_ChIPSeq_severalfactors.bed$color = heat.colors(max(Sushi_ChIPSeq_severalfactors.bed$row))[Sushi_ChIPSeq_severalfactors.bed$chrom]

plotBed(beddata    = Sushi_ChIPSeq_severalfactors.bed, chrom = chrom, chromstart = chromstart, chromend = chromend,
        rownumber = Sushi_ChIPSeq_severalfactors.bed$row, type = "region", color=Sushi_ChIPSeq_severalfactors$color,
        rowlabels=unique(Sushi_ChIPSeq_severalfactors.bed$name), rowlabelcol=unique(Sushi_ChIPSeq_severalfactors$chrom),
        colors = c("dodgerblue1","firebrick2","violet","yellow",
                  "dodgerblue1","firebrick2","violet","yellow",
                  "dodgerblue1","firebrick2","violet"))
plotBed(beddata    = Sushi_ChIPSeq_severalfactors.bed, chrom = chrom, chromstart = chromstart, chromend = chromend,
        rownumber = Sushi_ChIPSeq_severalfactors.bed$row, type = "density", row="supplied",
        rowlabels=unique(Sushi_ChIPSeq_severalfactors.bed$name), rowlabelcol=colors, rowlabelcex=0.75,
        palettes=list(
          colorRampPalette(c("black",colors[1])),
          colorRampPalette(c("black",colors[2])),
          colorRampPalette(c("black",colors[3])),
          colorRampPalette(c("black",colors[4])),
          colorRampPalette(c("black",colors[5])),
          colorRampPalette(c("black",colors[6])),
          colorRampPalette(c("black",colors[7])),
          colorRampPalette(c("black",colors[8])),
          colorRampPalette(c("black",colors[9])),
          colorRampPalette(c("black",colors[10])),
          colorRampPalette(c("black",colors[11]))))
```

plotBedgraph*plots data stored in bed file format***Description**

plots data stored in bed file format

Usage

```
plotBedgraph(signal, chrom, chromstart, chromend, range = NULL,
            color = SushiColors(2)(2)[1], lwd = 1, linecolor = NA,
            addscale = FALSE, overlay = FALSE, rescaleoverlay = FALSE,
            transparency = 1, flip = FALSE, xaxt = "none", yaxt = "none",
            xlab = "", ylab = "", xaxs = "i", yaxs = "i", bty = "n",
            ymax = 1.04, colorbycol = NULL, ...)
```

Arguments

<code>signal</code>	signal track data to be plotted (in bedgraph format)
<code>chrom</code>	chromosome of region to be plotted
<code>chromstart</code>	start position
<code>chromend</code>	end position
<code>range</code>	y-range to plt (c(min,max))
<code>color</code>	color of signal track
<code>lwd</code>	color of line outlining signal track. (only valid if linecol is not NA)

linecolor	color of line outlining signal track. use NA for no outline
addscale	TRUE/FALSE whether to add a y-axis
overlay	TRUE / FALSE whether this data should be plotted on top of an existing plot
rescaleoverlay	TRUE/FALSE whether the new plot shold be rescaled based on the maximum value to match the existing plot (only valid when overlay is set to 'TRUE')
transparency	Value between 0 and 1 indication the degree of transparency of the plot
flip	TRUE/FALSE whether the plot should be flipped over the x-axis
xaxt	A character which specifies the x axis type. See par
yaxt	A character which specifies the y axis type. See par
xlab	Label for the x-axis
ylab	Label for the y-axis
xaxs	Must be set to 'i' for appropriate integration into Sushi plots. See par
yaxs	Must be set to 'i' for appropriate integration into Sushi plots. See par plottype
bty	A character string which determined the type of box which is drawn about plots. See par
ymax	fraction of max y value to set as height of plot.
colorbycol	palette to use to shade the signal track plot. Only applicable when overlay is set to FALSE.
...	values to be passed to plot

Examples

```

data(Sushi_ChIPSeq_CTCF.bedgraph)
data(Sushi_DNaseI.bedgraph)

chrom      = "chr11"
chromstart = 1955000
chromend   = 1965000

plotBedgraph(Sushi_ChIPSeq_CTCF.bedgraph,chrom,chromstart,chromend,transparency=.50,flip=FALSE,color="blue")
plotBedgraph(Sushi_DNaseI.bedgraph,chrom,chromstart,chromend,transparency=.50,flip=FALSE,color="#E5001B",labelgenome(chrom,chromstart,chromend,side=1,scipen=20,n=3,line=.18,chromline=.5,scaleline=0.5,scale="Mb"))

transparency = 0.5
col1 = col2rgb("blue")
finalcolor1 = rgb(col1[1],col1[2],col1[3],alpha=transparency * 255,maxColorValue = 255)
col2 = col2rgb("#E5001B")
finalcolor2 = rgb(col2[1],col2[2],col2[3],alpha=transparency * 255,maxColorValue = 255)

legend("topright",inset=0.025,legend=c("DnaseI","ChIP-seq (CTCF)"),fill=c(finalcolor1,finalcolor2),border=0)

```

plotBedpe

plots data stored in bed file format

Description

plots data stored in bed file format

Usage

```
plotBedpe(bedpedata, chrom, chromstart, chromend, heights, color = "black",
          colorby = NULL, colorbycol = NULL, colorbyrange = NULL, border = NULL,
          lwdby = NULL, lwdrange = c(1, 5), offset = 0, flip = FALSE, lwd = 1,
          xaxt = "n", yaxt = "n", bty = "n", plottype = "loops",
          maxrows = 10000, height = 0.3, ymax = 1.04, ...)
```

Arguments

<code>bedpedata</code>	bed paired end data to be plotted
<code>chrom</code>	chromosome of region to be plotted
<code>chromstart</code>	start position
<code>chromend</code>	end position
<code>heights</code>	single value or vector specifying the height of the arches to be plotted (only valid when <code>plottype</code> is set to "loops")
<code>color</code>	single value or vector specifying colors of bedpe elements
<code>colorby</code>	vector to scale colors by
<code>colorbycol</code>	palette to apply color scale to (only valid when <code>colorby</code> is not <code>NULL</code>)
<code>colorbyrange</code>	the range of values to apply the color scale to. Values outside that range will be set to the limits of the range.
<code>lwdby</code>	vector to scale line widths by
<code>lwdrange</code>	the range of values to apply the line width scale to. Values outside that range will be set to the limits of the range.
<code>offset</code>	offset of bedpe elements from the x-axis
<code>flip</code>	TRUE/FALSE whether the plot should be flipped over the x-axis
<code>lwd</code>	linewidth for bedpe elements (only valid when <code>colorby</code> is not <code>NULL</code>)
<code>xaxt</code>	A character which specifies the x axis type. See par
<code>yaxt</code>	A character which specifies the y axis type. See par
<code>bty</code>	A character string which determined the type of box which is drawn about plots. See par
<code>plottype</code>	type of plot (acceptable values are 'loops', 'ribbons', or 'lines')
<code>maxrows</code>	The maximum number of rows to plot on the y-axis
<code>height</code>	the height of the boxes at either end of a bedpe element if <code>plottype</code> is set to 'lines'. Typical values range from 0 to 1. (only valid when <code>plottype</code> is set to 'lines')
<code>ymax</code>	fraction of max y value to set as height of plot. Only applies when <code>plottype</code> is set to 'loops' or 'ribbons'
<code>...</code>	values to be passed to plot

Examples

```
data(Sushi_5C.bedpe)

chrom      = "chr11"
chromstart = 1650000
chromend   = 2350000
```

```
pbpe = plotBedpe(Sushi_5C.bedpe,chrom,chromstart,chromend,heights = Sushi_5C.bedpe$score,offset=0,flip=FALSE,
lwd=1,plottype="ribbons",colorby=Sushi_5C.bedpe$samplenumber,colorbycol=topo.colors,border="black")
labelgenome(chrom, chromstart,chromend,side=1,scipen=20,n=3,scale="Mb",line=.18,chromline=.5,scaleline=0.5)
legend("topright",inset =0.01,legend=c("K562","HeLa","GM12878"),col=c(topo.colors(3)),pch=19,bty='n',text.f
axis(side=2,las=2,tcl=.2)
mtext("Z-score",side=2,line=1.75,cex=.75,font=2)
```

plotGenes*plots gene structure or transcript structures***Description**

plots gene structure or transcript structures

Usage

```
plotGenes(geneinfo = NULL, chrom = NULL, chromstart = NULL,
chromend = NULL, col = SushiColors(2)(2)[1], bheight = 0.3,
lheight = 0.3, bentline = TRUE, packrow = TRUE, maxrows = 10000,
colorby = NULL, colorbyrange = NULL,
colorbycol = colorRampPalette(c("blue", "red")), types = "exon",
plotgenetype = "box", arrowlength = 0.005, wigglefactor = 0.05,
labeltext = TRUE, labeloffset = 0.4, fontsize = 0.7, fonttype = 2,
labelat = "middle", ...)
```

Arguments

geneinfo	gene info stored in a bed-like format. If NULL it will look up genes in the region using biomart (with biomart="ensembl" and dataset="hsapiens_gene_ensembl"). See also useMart
chrom	chromosome of region to be plotted
chromstart	start position
chromend	end position
col	single value or vector specifying colors of gene structures
bheight	the height of the boxes drawn for exons
lheight	the height of the bent line is set to TRUE
bentline	TRUE/FALSE indicating whether lines between exons should be bent
packrow	TRUE / FALSE indicating whether genes should be packed or whether each gene should be plotted on its own row
maxrows	The maximum number of rows to plot on the y-axis
colorby	vector to scale colors by
colorbyrange	the range of values to apply the color scale to. Values outside that range will be set to the limits of the range.
colorbycol	palette to apply color scale to (only valid when colorby is not NULL)
types	single value or vector specifying types of elements (acceptable values are 'exon','utr')
plotgenetype	String specifying whether the genes should resemble a 'box' or a 'arrow'

arrowlength	value (between 0 and 1) specifying the length of the tail of each arrow as a fraction of the total plot width (only valid when plotgenotype is set to "arrow")
wigglefactor	the fraction of the plot to leave blank on either side of each element to avoid overcrowding.
labeltext	TRUE/FALSE indicating whether genes should be labeled
labeloffset	value (between 0 and 1) specifying the vertical offset of gene labels
fontsize	font size of gene labels
fonttype	font type of gene labels
labelat	position along gene to place labels (acceptable values are "middle","start",and "end")
...	values to be passed to plot

Examples

```

data(Sushi_genes.bed)

chrom      = "chr15"
chromstart = 72998000
chromend   = 73020000
chrom_biomart = 15

plotGenes(Sushi_genes.bed,chrom_biomart,chromstart,chromend ,types=Sushi_genes.bed$type,
          maxrows=1,height=0.5,plotgenotype="arrow",bentline=FALSE,col="blue",
          labeloffset=1,fontsize=1.2)

labelgenome( chrom, chromstart,chromend,side=1,scipen=20,n=3,scale="Mb",line=.18,chromline=.5,scaleline=0.5

```

plotHic *plots HiC interactio matrix*

Description

plots HiC interactio matrix

Usage

```
plotHic(hicdata, chrom, chromstart, chromend, max_y = 30, zrange = NULL,
        palette = SushiColors(7), flip = FALSE)
```

Arguments

hicdata	interaction matrix representing HiC data. Row and column names should be positions along a chromosome
chrom	chromosome of region to be plotted
chromstart	start position
chromend	end position
max_y	The maximum bin distance to plot
zrange	The range of interaction scores to plot (more extreme value will be set to the max or min)
palette	color palette to use for representing interaction scores
flip	TRUE/FALSE whether plot should be flipped over the x-axis

Examples

```
data(Sushi_HiC.matrix)

chrom      = "chr11"
chromstart = 500000
chromend   = 5050000

phic = plotHic(Sushi_HiC.matrix,chrom,chromstart,chromend,max_y = 20,zrange=c(0,28),palette = topo.colors,floor=0,ceiling=28)

labelgenome(chrom,chromstart,chromend,side=1,scipen=20,n=4,scale="Mb",edgeblankfraction=0.20,line=.18,chromwidth=10)

addlegend(phic[[1]],palette=phic[[2]],title="score",side="right",bottominset=0.4,topinset=0,xoffset=-.035,yoffset=.05)
```

plotManhattan *plots a Manhattan plot*

Description

plots a Manhattan plot

Usage

```
plotManhattan(bedfile, chrom = NULL, chromstart = NULL, chromend = NULL,
  pvalues, genome = NULL, col = SushiColors(5), space = 0.01,
  ymax = 1.04, ...)
```

Arguments

bedfile	bedfile for Manhattan plot
chrom	chromosome of region to be plotted
chromstart	start position
chromend	end position
pvalues	pvalues to be used for plotting (will be converted to -log(10) space)
genome	A genome object (2 columns: column 1 = chromosome name, column 2 = length of chromosome). Required if plotting multiple chromosomes at once.
col	single colors, vector of colors, or color palette for coloring points
space	the space in between each chromosome as a fraction of the width of the plot
ymax	fraction of max y value to set as height of plot.
...	Arguments to be passed to methods such as plot

Examples

```
data(Sushi_GWAS.bed)
data(Sushi_hg18_genome)

chrom1      = "chr11"
chromstart1 = 500000
chromend1   = 5050000

plotManhattan(bedfile=Sushi_GWAS.bed,pvalues=Sushi_GWAS.bed[,5],genome=Sushi_hg18_genome,col=topo.colors,ceiling=28)
```

```
labelgenome(genome=Sushi_hg18_genome,side=1,scipen=20,n=4,scale="Mb",edgeblankfraction=0.20,line=.18,chrom)
axis(side=2,las=2,tcl=.2)
mtext("log10(P)",side=2,line=1.75,cex=.75,font=2)
```

sortChrom*sort chromosome files by chom name***Description**

sort chromosome files by chom name

Usage

```
sortChrom(genome)
```

Arguments

genome	A genome object to be used (2 columns: column 1 = chromosome name, column 2 = length of chromosome)
--------	---

SushiColors*Generates a Sushi color palette***Description**

Generates a Sushi color palette

Usage

```
SushiColors(palette = "fire")
```

Arguments

palette	The name of the Sushi palette to return. For list of available palettes try (SushiColors(list))
---------	---

Examples

```
plot(1,xlab='',xaxt='n',ylab='',yaxt='n',xlim=c(0,8),ylim=c(2,8),type='n',bg="grey")
for (i in (2:7))
{
  points(x=(1:i),y=rep(i,i),bg=SushiColors(i)(i),cex=3,pch=21)

}

axis(side=2,at=(2:7),labels=(2:7),las=2)
axis(side=1,at=(1:7),labels=(1:7))
mtext("SushiColors",side=3,font=2, line=1, cex=1.5)
mtext("colors",side=1,font=2, line=2)
mtext("palette",side=2,font=2, line=2)
```

Sushi_5C.bedpe *Sushi_5C.bedpe*

Description

This data set lists the genomic locations of 5C interactions in multiple cell lines with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_5C.bedpe

Format

bedpe format

Source

Sanyal, A., Lajoie, B. R., Jain, G. & Dekker, J. The long-range interaction landscape of gene promoters. *Nature* 489, 109-113 (2012).

Sushi_ChIAPET_pol2.bedpe
Sushi_ChIAPET_pol2.bedpe

Description

This data set lists the genomic locations of Pol2 ChIA PET interactions in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIAPET_pol2.bedpe

Format

bedpe format

Source

Li, G. et al. Extensive Promoter-Centered Chromatin Interactions Provide a Topological Basis for Transcription Regulation. *Cell* 148, 84-98 (2012).

*Sushi_ChIPExo_CTCF.bedgraph**Sushi_ChIPExo_CTCF.bedgraph*

Description

This data set describes read depths across the genome resulting from a CTCF ChIP Exo experiment in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIPExo_CTCF.bedgraph

Format

bedgraph format

Source

Rhee, H. S. & Pugh, B. F. Comprehensive genome-wide protein-DNA interactions detected at single-nucleotide resolution. *Cell* 147, 1408-1419 (2011).

*Sushi_ChIPSeq_CTCF.bedgraph**Sushi_ChIPSeq_CTCF.bedgraph*

Description

This data set describes read depths across the genome resulting from a CTCF ChIP seq experiment in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIPSeq_CTCF.bedgraph

Format

bedgraph format

Source

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

Sushi_ChIPSeq_pol2.bed
Sushi_ChIPSeq_pol2.bed

Description

This data set describes aligned sequencing reads for Pol2 in K562 cells as determined by ChIP-seq with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIPSeq_pol2.bed

Format

bed format

Source

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. Nature 489, 57-74 (2012).

Sushi_ChIPSeq_pol2.bedgraph
Sushi_ChIPSeq_pol2.bedgraph

Description

This data set describes read depths across the genome resulting from a Pol2 ChIP seq experiment in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIPSeq_pol2.bedgraph

Format

bedgraph format

Source

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. Nature 489, 57-74 (2012).

Sushi_ChIPSeq_severalfactors.bed
Sushi_ChIPSeq_severalfactors.bed

Description

This data set describes binding sites for multiple factors in K562 cells as determined by ChIP-seq with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_ChIPSeq_severalfactors.bed

Format

bed format

Source

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

Sushi_DNaseI.bedgraph *Sushi_DNaseI.bedgraph*

Description

This data set describes read depths across the genome resulting from a DNaseI hypersensitivity experiment in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_DNaseI.bedgraph

Format

bedgraph format

Source

Neph, S. et al. An expansive human regulatory lexicon encoded in transcription factor footprints. *Nature* 489, 83-90 (2012).

Sushi_genes.bed *Sushi_genes.bed*

Description

Bed data representing human genes with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_genes.bed

Format

bed format

Source

<http://www.biomart.org/>

Sushi_GWAS.bed *Sushi_GWAS.bed*

Description

Bed data representing results from a GWAS study of blood pressure and cardiovascular disease risk with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_GWAS.bed

Format

bed format

Source

Ehret, G. B. et al. Genetic variants in novel pathways influence blood pressure and cardiovascular disease risk. Nature 478, 103-109 (2011).

Sushi_hg18_genome *Sushi_hg18_genome*

Description

This data set describes the length of human chromosomes according to the NCBI36 / hg18 genome build.

Usage

`Sushi_hg18_genome`

Format

two columns (column 1 = chromosome name, column 2 = length of chromosome)

Source

<http://www.biomart.org/> and Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

Sushi_HiC.matrix *Sushi_HiC.matrix*

Description

Bed data representing results from a GWAS study of blood pressure and cardiovascular disease risk with coordinates based on the NCBI36 / hg18 genome build.

Usage

`Sushi_HiC.matrix`

Format

matrix

Source

Dixon, J. R. et al. Topological domains in mammalian genomes identified by analysis of chromatin interactions. *Nature* (2012). doi:10.1038/nature11082

Sushi_RNASeq_K562.bedgraph

Sushi_RNASeq_K562.bedgraph

Description

Bedgraph data representing RNA-seq dat from K562 with coordinates based on the NCBI36 / hg18 genome build.

Bedgraph data representing RNA-seq dat from K562 with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_RNASeq_K562.bedgraph

Sushi_RNASeq_K562.bedgraph

Format

bedgraph format

Source

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

Sushi_transcripts.bed *Sushi_transcripts.bed*

Description

Bed data representing human transcripts and their expression in K562 cells with coordinates based on the NCBI36 / hg18 genome build.

Usage

Sushi_transcripts.bed

Format

bed format

Source

<http://www.biomart.org/> and Consortium, T. E. P. An integrated encyclopedia of DNA elements in the human genome. *Nature* 489, 57-74 (2012).

zoombox	<i>Adds a zoom box to a plot</i>
---------	----------------------------------

Description

This function is used on the second plot of a zoom in

Usage

```
zoombox(zoomregion = NULL, lty = 2, lwd = 1, col = "black",
        topextend = 2, passthrough = FALSE)
```

Arguments

zoomregion	Region of another zoom on this plot. Only required if this plot has another zoomregion on it.
lty	line type for box. See par
lwd	line width. See See par
col	Color for zoombox line
topextend	How far to exted the lines above the current plot (as a fraction of the plot height)
passthrough	TRUE / FALSE whether or not to pass the zoom though this plot. If set to FALSE no horizontal line is drawn on the botoom of the plot

Examples

```
data(Sushi_DNaseI.bedgraph)
data(Sushi_ChIPSeq_CTCF.bedgraph)

# make a layout for all of the plots
layout(matrix(c(1,1,
               2,2),
               ,2, 2, byrow = TRUE))
par(mgp=c(3, .3, 0))

par(mar=c(3,4,2,1))
chrom      = "chr11"
chromstart = 1650000
chromend   = 2350000
zoomregion1 = c(1955000,1965000)

plotBedgraph(Sushi_DNaseI.bedgraph,chrom,chromstart,chromend,transparency=1.0,color="#5900E5",lwd=1,lineco...
zoomsregion(zoomregion1,col=NA,zoomborder="black",lty=2,lwd=1,extend=c(0.01,0.09),wideextend=0.10,offsets=...
labelgenome(chrom,chromstart,chromend,side=1,scipen=20,n=4,line=.18,chromline=.5,scaleline=0.5,scale="Mb")
axis(side=2,las=2,tcl=.2)
mtext("Read Depth",side=2,line=1.75,cex=.75,font=2)

# plot dnaseI data
plotBedgraph(Sushi_DNaseI.bedgraph,chrom,zoomregion1[1],zoomregion1[2],transparency=.50,flip=FALSE,color="#"...
```

```
# plot chip-seq data
plotBedgraph(Sushi_ChIPSeq_CTCF.bedgraph,chrom,zoomregion1[1],zoomregion1[2],transparency=.30,flip=FALSE,co

# add zoombox
zoombox(zoomregion = NULL,lwd = 1,col="black")

axis(side=2,las=2,tcl=.2)
mtext("Read Depth",side=2,line=1.75,cex=.75,font=2)

# add the genome labels
labelgenome(chrom,zoomregion1[1],zoomregion1[2],side=1,scipen=20,n=3,line=.18,chromline=.5,scaleline=0.5,so

# set the legend colors
transparency = 0.5
col1 = col2rgb("blue")
finalcolor1 = rgb(col1[1],col1[2],col1[3],alpha=transparency * 255,max = 255)
col2 = col2rgb("#E5001B")
finalcolor2 = rgb(col2[1],col2[2],col2[3],alpha=transparency * 255,max = 255)

# add legend
legend("topright",inset=0.025,legend=c("DnaseI","ChIP-seq (CTCF)"),fill=c(finalcolor1,finalcolor2),border=c(1,1,1,1),cex=.75)
```

zoomsregion*Adds a zoom region to a plot***Description**

This function is used on the first plot of a zoom in

Usage

```
zoomsregion(region, chrom = NULL, genome = NULL, space = 0.01,
padding = 0.005, col = NA, zoomborder = "black", lty = 2, lwd = 1,
extend = 0, wideextend = 0.1, offsets = c(0, 0), highlight = FALSE)
```

Arguments

<code>region</code>	chromosome start and stop to zoom in on
<code>chrom</code>	chromosome of region to be plotted
<code>genome</code>	A genome object (2 columns: column 1 = chromosome name, column 2 = length of chromosome). Set to NULL if adding zoom to a plot with only a single chromosome.
<code>space</code>	the space in between each chromosome as a fraction of the width of the plot. Only used when adding a zoomsregion to a plot with multiple chromosomes (e.g. a Manhattan plot)
<code>padding</code>	The minimum size of a zoom region (as a fraction of the plot width). If the specified zoom region is too small it will zoom on a region twice this wide centered on the specified zoom region.
<code>col</code>	Color of the zoom region
<code>zoomborder</code>	Color of the border of the zoom region
<code>lty</code>	line type of zoom region border. See plot

<code>lwd</code>	line type of zoom region border. See plot
<code>extend</code>	single value or vector of 2 values specifying how far the zoom region extend above and below the plot region (as a fraction of the plot height). Note this value only applies to the narrow portion of the zoom region.
<code>wideextend</code>	Value specifying how below the plot region (as a fraction of the plot height) the wide portion of the zoom window starts. Only applicable if <code>highlight</code> is set to <code>FALSE</code> .
<code>offsets</code>	vector of 2 values specifying offsets to the left and right side of the wide portion of the zoom window. It may be necessary to adjust these by trial and error for more complicated layouts. Only applicable if <code>highlight</code> is set to <code>FALSE</code> .
<code>highlight</code>	<code>TRUE/FALSE</code> indicating if you are adding a highlight region as opposed to a zoom in. Highlight regions simply draw a box around the region of interest

Examples

```

data(Sushi_DNaseI.bedgraph)
data(Sushi_ChIPSeq_CTCF.bedgraph)

# make a layout for all of the plots
layout(matrix(c(1,1,
              2,2),
              ,2, 2, byrow = TRUE))
par(mgp=c(3, .3, 0))

par(mar=c(3,4,2,1))
chrom      = "chr11"
chromstart = 1650000
chromend   = 2350000
zoomregion1 = c(1955000,1965000)

plotBedgraph(Sushi_DNaseI.bedgraph,chrom,chromstart,chromend,transparency=1.0,color="#5900E5",lwd=1,lineco

zoomsregion(zoomregion1,col=NA,zoomborder="black",lty=2,lwd=1,extend=c(0.01,0.09),wideextend=0.10,offsets=0.05)

labelgenome(chrom,chromstart,chromend,side=1,scipen=20,n=4,line=.18,chromline=.5,scaleline=0.5,scale="Mb")

axis(side=2,las=2,tcl=.2)
mtext("Read Depth",side=2,line=1.75,cex=.75,font=2)

# plot dnaseI data
plotBedgraph(Sushi_DNaseI.bedgraph,chrom,zoomregion1[1],zoomregion1[2],transparency=.50,flip=FALSE,color="#5900E5",lwd=1)

# plot chip-seq data
plotBedgraph(Sushi_ChIPSeq_CTCF.bedgraph,chrom,zoomregion1[1],zoomregion1[2],transparency=.30,flip=FALSE,color="#5900E5",lwd=1)

# add zoombox
zoombox(zoomregion = NULL,lwd = 1,col="black")

axis(side=2,las=2,tcl=.2)
mtext("Read Depth",side=2,line=1.75,cex=.75,font=2)

# add the genome labels
labelgenome(chrom,zoomregion1[1],zoomregion1[2],side=1,scipen=20,n=3,line=.18,chromline=.5,scaleline=0.5,scale="Mb")

# set the legend colors

```

```
transparency = 0.5
col1 = col2rgb("blue")
finalcolor1 = rgb(col1[1],col1[2],col1[3],alpha=transparency * 255,max = 255)
col2 = col2rgb("#E5001B")
finalcolor2 = rgb(col2[1],col2[2],col2[3],alpha=transparency * 255,max = 255)

# add legend
legend("topright",inset=0.025,legend=c("DnaseI","ChIP-seq (CTCF)"),fill=c(finalcolor1,finalcolor2),border=0)
```

Index

addlegend, 2
axis, 4

chromOffsets, 3
convertstrandinfo, 3

labelgenome, 4
labelplot, 5

maptocolors, 6
maptolwd, 6

opaque, 7

par, 5, 8, 10, 11, 23
plot, 10, 11, 13, 14, 24, 25
plotBed, 7
plotBedgraph, 9
plotBedpe, 10
plotGenes, 12
plotHic, 13
plotManhattan, 14

sortChrom, 15
Sushi_5C.bedpe, 16
Sushi_ChIAPET_pol2.bedpe, 16
Sushi_ChIPExo_CTCF.bedgraph, 17
Sushi_ChIPSeq_CTCF.bedgraph, 17
Sushi_ChIPSeq_pol2.bed, 18
Sushi_ChIPSeq_pol2.bedgraph, 18
Sushi_ChIPSeq_severalfactors.bed, 19
Sushi_DNaseI.bedgraph, 19
Sushi_genes.bed, 20
Sushi_GWAS.bed, 20
Sushi_hg18_genome, 21
Sushi_HiC.matrix, 21
Sushi_RNASeq_K562.bedgraph, 22
Sushi_transcripts.bed, 22
SushiColors, 15

useMart, 12

zoombox, 23
zoomsregion, 24