

Package ‘systemPipeRdata’

October 17, 2019

Title systemPipeRdata: NGS workflow templates and sample data

Version 1.12.0

Date 2019-04-22

Author Thomas Girke

Maintainer Thomas Girke <thomas.girke@ucr.edu>

biocViews Genetics, Infrastructure, DataImport, Sequencing, RNASeq, ChIPSeq, MethylSeq, SNP, GeneExpression, Coverage, GeneSetEnrichment, Alignment, QualityControl, ImmunoOncology

Description systemPipeRdata is a helper package to generate with a single command NGS workflow templates that are intended to be used by its parent package systemPipeR. The latter is an environment for building end-to-end analysis pipelines with automated report generation for next generation sequence (NGS) applications such as RNA-Seq, RIBO-Seq, ChIP-Seq, VAR-Seq and many others. Detailed examples for using systemPipeRdata are given in systemPipeR's overview vignette.

Depends methods

Imports BiocGenerics

Suggests RUnit, BiocStyle, knitr, rmarkdown, systemPipeR

VignetteBuilder knitr

License Artistic-2.0

NeedsCompilation no

URL <https://github.com/tgirke/systemPipeRdata>

git_url <https://git.bioconductor.org/packages/systemPipeRdata>

git_branch RELEASE_3_9

git_last_commit 47e924d

git_last_commit_date 2019-05-02

Date/Publication 2019-10-17

R topics documented:

genWorkenvir	2
pathList	3
Index	4

 genWorkenvir

Generate workflow templates

Description

Generates workflow templates for systemPipeR package. The template environments contain a predefined directory structure along with run parameter files and sample data. The structure of the workflow templates and the sample data are described in all details in the Overview Vignette of the systemPipeR package here: <http://bioconductor.org/packages/systemPipeR>.

Usage

```
genWorkenvir(workflow, mydirname=NULL, bam=FALSE, url=NULL, urlname=NULL)
```

Arguments

workflow	Can be assigned workflow type as character string. Supported values are: rnaseq, riboseq, varseq or chipseq
mydirname	Specifies the name of the workflow directory. The default NULL uses the name of the chosen workflow. An error is issued if a directory of the same name and path exists already.
bam	If bam=TRUE pregenerated short read alignment (BAM) files will be included in the results directory of the workflow environment. Note, these BAM files have been generated with the HISAT2 aligner using the FASTQ files provided in the data directory. The default bam=FALSE omits this step meaning no BAM files will be copied into the results directory.
url	Specifies the location of a different version of the workflow template or other file to download. The default NULL copies the current version available in the 'systemPipeRdata'. Please check the available options [here](https://github.com/tgirke/systemPipeRdata/)
urlname	Specifies the name of the download file. The default NULL uses the name of the chosen workflow. An error is issued when the url is provided and only the default urlname is provided it.

Value

Workflow directory containing sample data and parameter files along with the following subdirectories:

param/	stores parameter files
data/	stores input data
results/	stores output results

For more details, please consult the Overview Vignette (HTML) of the systemPipeR package (<http://bioconductor.org/packages/systemPipeR>).

Author(s)

Thomas Girke

Examples

```
## Return location of sample data
samplepaths <- pathList()
## Not run:
## Generate varseq workflow environment
genWorkenvir(workflow="varseq", mydirname=NULL, url=NULL, urlname=NULL)
setwd("varseq")

## End(Not run)
```

<code>pathList</code>	<i>Return location of sample data</i>
-----------------------	---------------------------------------

Description

Function to return paths to sample data provided by `sytemPipeRdata` package.

Usage

```
pathList()
```

Value

list

Author(s)

Thomas Girke

Examples

```
samplepaths <- pathList()
```

Index

*Topic **utilities**

genWorkenvir, [2](#)

pathList, [3](#)

genWorkenvir, [2](#)

pathList, [3](#)