

# Package ‘AnVILBilling’

July 15, 2025

**Title** Provide functions to retrieve and report on usage expenses in NHGRI AnVIL (anvilproject.org).

**Date** 2020-09-30

**Version** 1.19.0

**Description** AnVILBilling helps monitor AnVIL-related costs in R, using queries to a BigQuery table to which costs are exported daily. Functions are defined to help categorize tasks and associated expenditures, and to visualize and explore expense profiles over time. This package will be expanded to help users estimate costs for specific task sets.

**License** Artistic-2.0

**Encoding** UTF-8

**LazyData** true

**Depends** R (>= 4.1)

**Imports** methods, DT, shiny, bigquery, shinytoastr, DBI, magrittr, dplyr, lubridate, plotly, ggplot2

**Suggests** testthat, knitr, BiocStyle, rmarkdown

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

**biocViews** Infrastructure, Software

**BugReports** <https://github.com/vjcitn/AnVILBilling/issues>

**git\_url** <https://git.bioconductor.org/packages/AnVILBilling>

**git\_branch** devel

**git\_last\_commit** fc7f4b2

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.22

**Date/Publication** 2025-07-15

**Author** BJ Stubbs [aut],  
Vince Carey [aut, cre]

**Maintainer** Vince Carey <stvjc@channing.harvard.edu>

Contents

|                                        |           |
|----------------------------------------|-----------|
| ab_reckoning . . . . .                 | 2         |
| browse_reck . . . . .                  | 3         |
| browse_reck2 . . . . .                 | 3         |
| demo_rec . . . . .                     | 3         |
| getBilling . . . . .                   | 4         |
| getKeys . . . . .                      | 5         |
| getSkus . . . . .                      | 5         |
| getSubmissionCost . . . . .            | 6         |
| getSubmissionRam . . . . .             | 6         |
| getValues . . . . .                    | 7         |
| reckon . . . . .                       | 7         |
| reckoning . . . . .                    | 8         |
| reckoning,avReckoning-method . . . . . | 8         |
| setup_billing_request . . . . .        | 9         |
| subsetByKeyValue . . . . .             | 9         |
| subsetBySku . . . . .                  | 10        |
| <b>Index</b>                           | <b>11</b> |

---

|              |                                       |
|--------------|---------------------------------------|
| ab_reckoning | <i>accessor for reckoning element</i> |
|--------------|---------------------------------------|

---

Description

accessor for reckoning element

Usage

ab\_reckoning(x)

Arguments

x                      an instance of avReckoning

Value

a tibble with one row for each expense type by time slice

Examples

dim(ab\_reckoning(demo\_rec))

---

|             |                                        |
|-------------|----------------------------------------|
| browse_reck | <i>prototypical cost exploring app</i> |
|-------------|----------------------------------------|

---

**Description**

prototypical cost exploring app

**Usage**

```
browse_reck()
```

**Value**

returns "NULL"

**Examples**

```
if (interactive()) browse_reck()
```

---

|              |                                                             |
|--------------|-------------------------------------------------------------|
| browse_reck2 | <i>alternate app for AnVIL where htmlwidgets misbehaves</i> |
|--------------|-------------------------------------------------------------|

---

**Description**

alternate app for AnVIL where htmlwidgets misbehaves

**Usage**

```
browse_reck2()
```

---

|          |                                           |
|----------|-------------------------------------------|
| demo_rec | <i>a demonstration avReckoning object</i> |
|----------|-------------------------------------------|

---

**Description**

a demonstration avReckoning object

**Usage**

```
demo_rec
```

**Format**

avReckoning instance

**Note**

This is a snapshot of cost data collected for a specific project.

**Examples**

```
demo_rec
```

---

|            |                             |
|------------|-----------------------------|
| getBilling | <i>request billing data</i> |
|------------|-----------------------------|

---

## Description

request billing data

## Usage

```
getBilling(
  startDate,
  endDate,
  bqProject,
  bqDataset,
  bqTable,
  bqBilling_code,
  page_size = 50000
)
```

## Arguments

|                |                                                    |
|----------------|----------------------------------------------------|
| startDate      | character(1) date of start of reckoning            |
| endDate        | character(1) date of end of reckoning              |
| bqProject      | character(1) GCP project id                        |
| bqDataset      | character(1) GCP dataset id for billing data in BQ |
| bqTable        | character(1) GCP table for billing data in BQ      |
| bqBilling_code | character(1) GCP billing code                      |
| page_size      | numeric(1) passed to dbConnect                     |

## Value

tbl\_df

## Note

On 21 August 2020 VJC changed condition on endDate to <=

## Examples

```
if (interactive()) {
  getBilling(startDate="2020-08-01",
    endDate="2020-08-15", bqProject="bjbilling",
    bqTable="gcp_billing_export_v1_015E39_38569D_3CC771",
    bqDataset="anvilbilling", bqBilling_code="landmarkanvil2")
}
```

---

|         |                    |
|---------|--------------------|
| getKeys | <i>return keys</i> |
|---------|--------------------|

---

**Description**

return keys

**Usage**

```
getKeys(mybilling)
```

**Arguments**

|           |        |
|-----------|--------|
| mybilling | tbl_df |
|-----------|--------|

**Value**

character()

---

|         |                                            |
|---------|--------------------------------------------|
| getSkus | <i>List the available GCP product skus</i> |
|---------|--------------------------------------------|

---

**Description**

List the available GCP product skus

**Usage**

```
getSkus(mybilling)
```

**Arguments**

|           |        |
|-----------|--------|
| mybilling | tbl_df |
|-----------|--------|

**Value**

character()

---

|                   |                                                        |
|-------------------|--------------------------------------------------------|
| getSubmissionCost | <i>Calculate costs for a workflow submission by ID</i> |
|-------------------|--------------------------------------------------------|

---

**Description**

Calculate costs for a workflow submission by ID

**Usage**

```
getSubmissionCost(mybilling, submissionID)
```

**Arguments**

|              |                                  |
|--------------|----------------------------------|
| mybilling    | tbl_df                           |
| submissionID | character(1) Terra submission ID |

**Value**

numeric()

**Examples**

```
data(demo_rec) # makes rec
v = getValues(demo_rec@reckoning, "terra-submission-id")[1] # for instance
getSubmissionCost(demo_rec@reckoning,v)
```

---

|                  |                                                            |
|------------------|------------------------------------------------------------|
| getSubmissionRam | <i>Calculate ram usage for a workflow submission by ID</i> |
|------------------|------------------------------------------------------------|

---

**Description**

Calculate ram usage for a workflow submission by ID

**Usage**

```
getSubmissionRam(mybilling, submissionID)
```

**Arguments**

|              |                                  |
|--------------|----------------------------------|
| mybilling    | tbl_df                           |
| submissionID | character(1) Terra submission ID |

**Value**

data.frame

**Examples**

```
data(demo_rec) # makes rec
v = getValues(demo_rec@reckoning, "terra-submission-id")[1] # for instance
getSubmissionRam(demo_rec@reckoning,v)
```

---

|           |                                               |
|-----------|-----------------------------------------------|
| getValues | <i>deal with nested tables in a reckoning</i> |
|-----------|-----------------------------------------------|

---

**Description**

deal with nested tables in a reckoning

**Usage**

```
getValues(mybilling, mykey)
```

**Arguments**

|           |                      |
|-----------|----------------------|
| mybilling | tbl_df from reckon() |
| mykey     | character(1) key     |

**Value**

character()

**Examples**

```
if (interactive()) getValues(reckoning(demo_rec), "security")
```

---

|        |                          |
|--------|--------------------------|
| reckon | <i>perform reckoning</i> |
|--------|--------------------------|

---

**Description**

perform reckoning

**Usage**

```
reckon(obj)
```

**Arguments**

|     |                                |
|-----|--------------------------------|
| obj | instance of avReckoningRequest |
|-----|--------------------------------|

**Value**

instance of avReckoning

**Examples**

```
data(demo_rec)
if (interactive()) reckon(demo_rec)
```

---

|           |                                                     |
|-----------|-----------------------------------------------------|
| reckoning | <i>generic for accessor for reckoning component</i> |
|-----------|-----------------------------------------------------|

---

**Description**

generic for accessor for reckoning component

**Usage**

```
reckoning(x)
```

**Arguments**

|   |                                    |
|---|------------------------------------|
| x | object inheriting from avReckoning |
|---|------------------------------------|

**Value**

tbl\_df

**Examples**

```
if (interactive()) reckoning(reckon(demo_rec))
```

---

|                               |                                         |
|-------------------------------|-----------------------------------------|
| reckoning, avReckoning-method | <i>accessor for reckoning component</i> |
|-------------------------------|-----------------------------------------|

---

**Description**

accessor for reckoning component

**Usage**

```
## S4 method for signature 'avReckoning'
reckoning(x)
```

**Arguments**

|   |                         |
|---|-------------------------|
| x | instance of avReckoning |
|---|-------------------------|

**Value**

tbl\_df

**Examples**

```
if (interactive()) reckoning(reckon(demo_rec))
```

---

setup\_billing\_request    *set up request object*

---

### Description

set up request object

### Usage

```
setup_billing_request(start, end, project, dataset, table, billing_code)
```

### Arguments

|              |                                                    |
|--------------|----------------------------------------------------|
| start        | character(1) date of start of reckoning            |
| end          | character(1) date of end of reckoning              |
| project      | character(1) GCP project id                        |
| dataset      | character(1) GCP dataset id for billing data in BQ |
| table        | character(1) GCP table for billing data in BQ      |
| billing_code | character(1) GCP billing code                      |

### Value

instance of avReckoningRequest

### Examples

```
lk1 = setup_billing_request("2020-08-01", "2020-08-15",
  "bq-scoped-project", "bq_dataset", "bq_table", "billcode")
lk1
```

---

|                  |                                                                                                    |
|------------------|----------------------------------------------------------------------------------------------------|
| subsetByKeyValue | <i>filter a reckoning by 'label' retaining records associated with a particular key-value pair</i> |
|------------------|----------------------------------------------------------------------------------------------------|

---

### Description

filter a reckoning by 'label' retaining records associated with a particular key-value pair

### Usage

```
subsetByKeyValue(mybilling, mykey, myvalue)
```

### Arguments

|           |                         |
|-----------|-------------------------|
| mybilling | instance of avReckoning |
| mykey     | character(1)            |
| myvalue   | character(1)            |

**Value**

data.frame

**Examples**

```
example(reckon) # makes rec
v = getValues(ab_reckoning(demo_rec), "terra-submission-id")[1] # for instance
nt = subsetByKeyValue(ab_reckoning(demo_rec), "terra-submission-id", v)
head(nt)
dim(nt)
```

---

|             |                                       |
|-------------|---------------------------------------|
| subsetBySku | <i>subset a billing object by sku</i> |
|-------------|---------------------------------------|

---

**Description**

subset a billing object by sku

**Usage**

```
subsetBySku(mybilling, mysku)
```

**Arguments**

|           |                              |
|-----------|------------------------------|
| mybilling | tbl_df                       |
| mysku     | character(1) GCP product sku |

**Value**

data.frame

# Index

- \* **datasets**
  - demo\_rec, [3](#)
- ab\_reckoning, [2](#)
- browse\_reck, [3](#)
- browse\_reck2, [3](#)
- demo\_rec, [3](#)
- getBilling, [4](#)
- getKeys, [5](#)
- getSkus, [5](#)
- getSubmissionCost, [6](#)
- getSubmissionRam, [6](#)
- getValues, [7](#)
- reckon, [7](#)
- reckoning, [8](#)
- reckoning, avReckoning-method, [8](#)
- setup\_billing\_request, [9](#)
- subsetByKeyValue, [9](#)
- subsetBySku, [10](#)