

Package ‘ReactomeGSA’

July 7, 2025

Type Package

Title Client for the Reactome Analysis Service for comparative multi-omics gene set analysis

Version 1.23.0

Author Johannes Griss [aut, cre]
(<https://orcid.org/0000-0003-2206-9511>)

Maintainer Johannes Griss <johannes.griss@meduniwien.ac.at>

Description The ReactomeGSA packages uses Reactome's online analysis service to perform a multi-omics gene set analysis. The main advantage of this package is, that the retrieved results can be visualized using REACTOME's powerful webapplication. Since Reactome's analysis service also uses R to perform the actual gene set analysis you will get similar results when using the same packages (such as limma and edgeR) locally. Therefore, if you only require a gene set analysis, different packages are more suited.

License MIT + file LICENSE

URL <https://github.com/reactome/ReactomeGSA>

BugReports <https://github.com/reactome/ReactomeGSA/issues>

Imports Biobase, BiocSingular, dplyr, ggplot2, gplots, httr, igraph, jsonlite, methods, progress, RColorBrewer, SummarizedExperiment, tidyr

Suggests devtools, knitr, ReactomeGSA.data, rmarkdown, scatter, scan, scRNAseq, scuttle, Seurat (>= 3.0), SingleCellExperiment, testthat

VignetteBuilder knitr

biocViews GeneSetEnrichment, Proteomics, Transcriptomics, SystemsBiology, GeneExpression, Reactome

Encoding UTF-8

LazyData false

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/ReactomeGSA>

git_branch devel

git_last_commit d9a274e

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-07-06

Contents

add_dataset	3
add_dataset,ReactomeAnalysisRequest,data.frame-method	5
add_dataset,ReactomeAnalysisRequest,DGEList-method	6
add_dataset,ReactomeAnalysisRequest,EList-method	8
add_dataset,ReactomeAnalysisRequest,ExpressionSet-method	10
add_dataset,ReactomeAnalysisRequest,matrix-method	11
analyse_sc_clusters	13
analyse_sc_clusters,Seurat-method	14
analyse_sc_clusters,SingleCellExperiment-method	15
break_names	17
checkRequestValidity	17
check_reactome_url	18
convert_reactome_result	18
data_frame_as_string	19
fetch_public_data	19
find_public_datasets	20
generate_metadata	21
generate_metadata,data.frame-method	21
generate_pseudo_bulk_data	22
generate_pseudo_bulk_data,Seurat-method	23
generate_pseudo_bulk_data,SingleCellExperiment-method	24
get_dataset_loading_status	24
get_fc_for_dataset	25
get_is_sig_dataset	25
get_public_species	26
get_reactome_analysis_result	26
get_reactome_analysis_status	27
get_reactome_data_types	27
get_reactome_methods	28
get_result	30
get_result,ReactomeAnalysisResult-method	31
is_gsva_result	32
load_public_dataset	32
names,ReactomeAnalysisResult-method	33
open_reactome	34
open_reactome,ReactomeAnalysisResult-method	34
pathways	35
pathways,ReactomeAnalysisResult-method	36
perform_reactome_analysis	37
plot_correlations	38
plot_correlations,ReactomeAnalysisResult-method	39
plot_gsva_heatmap	40
plot_gsva_heatmap,ReactomeAnalysisResult-method	41
plot_gsva_pathway	42
plot_gsva_pathway,ReactomeAnalysisResult-method	43
plot_gsva_pca	44

plot_gsva_pca,ReactomeAnalysisResult-method	44
plot_heatmap	45
plot_heatmap,ReactomeAnalysisResult-method	46
plot_volcano	47
plot_volcano,ReactomeAnalysisResult-method	48
print,ReactomeAnalysisRequest-method	49
print,ReactomeAnalysisResult-method	50
ReactomeAnalysisRequest	50
ReactomeAnalysisResult-class	51
reactome_links	52
reactome_links,ReactomeAnalysisResult-method	53
remove_dataset	54
remove_dataset,ReactomeAnalysisRequest-method	54
result_types	55
result_types,ReactomeAnalysisResult-method	55
set_method	56
set_method,ReactomeAnalysisRequest-method	57
set_parameters	58
set_parameters,ReactomeAnalysisRequest-method	58
show,ReactomeAnalysisRequest-method	59
show,ReactomeAnalysisResult-method	60
split_clustering	60
split_random_sce	61
split_subclustering_sce	62
split_variable	62
split_variable_random	63
split_variable_sce	63
start_reactome_analysis	64
wait_for_loading_dataset	65

Index

66

add_dataset	<i>add_dataset</i>
-------------	--------------------

Description

Adds a dataset to the analysis request

Usage

```
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
```

```
    ...  
  )
```

Arguments

request	The request to add the dataset to. Commonly a ReactomeAnalysisRequest object.
expression_values	Object containing the expression values of the dataset to add (multiple types supported).
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using get_reactome_data_types
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other add_dataset methods: [add_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add_dataset, ReactomeAnalysisRequest, matrix-method](#)

Examples

```
# create a request using Camera as an analysis  
library(ReactomeGSA.data)  
data(griss_melanoma_proteomics)  
library(methods)  
  
my_request <- ReactomeAnalysisRequest(method = "Camera")  
  
# since the expression_values object is a limma EList object, the sample_data is
```

```
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

add_dataset, ReactomeAnalysisRequest, data.frame-method
add_dataset - data.frame

Description

Adds a dataset to the analysis request

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,data.frame'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```

Arguments

request	ReactomeAnalysisRequest.
expression_values	data.frame. In this case, the sample_data must be set.
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using get_reactome_data_types
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.

<code>comparison_group_2</code>	character. Name of the second group within <code>comparison_factor</code> to use for the comparison.
<code>sample_data</code>	<code>data.frame</code> (optional) <code>data.frame</code> containing the sample metadata of the <code>expression_values</code> . Depending on the object type of <code>expression_values</code> , this information can also be extracted from there.
<code>additional_factors</code>	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
<code>overwrite</code>	boolean. If set to <code>TRUE</code> , datasets with the same name will be overwritten
<code>...</code>	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other `add_dataset` methods: [add_dataset\(\)](#), [add_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add_dataset, ReactomeAnalysisRequest, EList-method](#), [add_dataset, ReactomeAnalysisRequest, ExpressionS](#), [add_dataset, ReactomeAnalysisRequest, matrix-method](#)

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

`add_dataset, ReactomeAnalysisRequest, DGEList-method`
add_dataset - DGEList

Description

Adds a dataset to the analysis request

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,DGEList'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```

Arguments

request	ReactomeAnalysisRequest.
expression_values	DGEList Here, the sample_data is automaticall extracted from the expression_values object unless sample_data is specified as well.
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using get_reactome_data_types
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other add_dataset methods: [add_dataset\(\)](#), [add_dataset, ReactomeAnalysisRequest, EList-method](#), [add_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add_dataset, ReactomeAnalysisRequest, matrix-method](#)

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

add_dataset, ReactomeAnalysisRequest, EList-method
add_dataset - EList

Description

Adds a dataset to the analysis request

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,EList'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```


Arguments

request	ReactomeAnalysisRequest.
expression_values	EList. Here, the sample_data is automaticall extracted from the expression_values object unless sample_data is specified as well.
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using get_reactome_data_types
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other add_dataset methods: [add_dataset\(\)](#), [add_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add_dataset, ReactomeAnalysisRequest, matrix-method](#)

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
```

```

expression_values = griss_melanoma_proteomics,
name = "Proteomics",
type = "proteomics_int",
comparison_factor = "condition",
comparison_group_1 = "MOCK",
comparison_group_2 = "MCM",
additional_factors = c("cell.type", "patient.id"))

```

`add_dataset,ReactomeAnalysisRequest,ExpressionSet-method`
add_dataset - ExpressionSet

Description

Adds a dataset to the analysis request

Usage

```

## S4 method for signature 'ReactomeAnalysisRequest,ExpressionSet'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)

```

Arguments

<code>request</code>	ReactomeAnalysisRequest.
<code>expression_values</code>	ExpressionSet. Here, the <code>sample_data</code> is automaticall extracted from the <code>expression_values</code> object unless <code>sample_data</code> is specified as well.
<code>name</code>	character. Name of the dataset. This must be unique within one request.
<code>type</code>	character. The type of the dataset. Get available types using get_reactome_data_types
<code>comparison_factor</code>	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from <code>expression_values</code> or from <code>sample_data</code> .
<code>comparison_group_1</code>	character. Name of the first group within <code>comparison_factor</code> to use for the comparison.
<code>comparison_group_2</code>	character. Name of the second group within <code>comparison_factor</code> to use for the comparison.

sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other add_dataset methods: [add_dataset\(\)](#), [add_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add_dataset, ReactomeAnalysisRequest, EList-method](#), [add_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add_dataset, ReactomeAnalysisRequest, matrix-method](#)

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
  expression_values = griss_melanoma_proteomics,
  name = "Proteomics",
  type = "proteomics_int",
  comparison_factor = "condition",
  comparison_group_1 = "MOCK",
  comparison_group_2 = "MCM",
  additional_factors = c("cell.type", "patient.id"))
```

add_dataset, ReactomeAnalysisRequest, matrix-method
add_dataset - matrix

Description

Adds a dataset to the analysis request

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,matrix'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```

Arguments

<code>request</code>	<code>ReactomeAnalysisRequest</code> .
<code>expression_values</code>	<code>matrix</code> . In this case, the <code>sample_data</code> must be set.
<code>name</code>	character. Name of the dataset. This must be unique within one request.
<code>type</code>	character. The type of the dataset. Get available types using get_reactome_data_types
<code>comparison_factor</code>	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from <code>expression_values</code> or from <code>sample_data</code> .
<code>comparison_group_1</code>	character. Name of the first group within <code>comparison_factor</code> to use for the comparison.
<code>comparison_group_2</code>	character. Name of the second group within <code>comparison_factor</code> to use for the comparison.
<code>sample_data</code>	<code>data.frame</code> (optional) <code>data.frame</code> containing the sample metadata of the <code>expression_values</code> . Depending on the object type of <code>expression_values</code> , this information can also be extracted from there.
<code>additional_factors</code>	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
<code>overwrite</code>	boolean. If set to <code>TRUE</code> , datasets with the same name will be overwritten
<code>...</code>	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

Value

The [ReactomeAnalysisRequest](#) object with the added dataset

See Also

Other `add_dataset` methods: [add_dataset\(\)](#), [add_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add_dataset, ReactomeAnalysisRequest, EList-method](#), [add_dataset, ReactomeAnalysisRequest, ExpressionS](#), [add_dataset, ReactomeAnalysisRequest, data.frame-method](#)

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

analyse_sc_clusters *analyse_sc_clusters*

Description

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

Usage

```
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  ...
)
```

Arguments

<code>object</code>	The object containing the single-cell RNA-sequencing data.
<code>use_interactors</code>	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
<code>include_disease_pathways</code>	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.

create_reactome_visualization	If set, the interactive visualization in Reactome's PathwayBrowser is created.
create_reports	If set, PDF and Microsoft Excel reports are created. Links to these report files are send to the supplied e-mail address.
report_email	The e-mail address to which reports should be sent to.
verbose	If set, additional status messages are printed.
...	Parameters passed to the specific implementation. Detailed documentations can be found there.

Details

There are currently two specific implementations of this function, one to support Seurat objects and one to support Bioconductor's SingleCellExperiment class.

Value

A [ReactomeAnalysisResult](#) object.

Examples

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

analyse_sc_clusters, Seurat-method
analyse_sc_clusters - Seurat

Description

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

Usage

```
## S4 method for signature 'Seurat'
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  assay = "RNA",
  slot = "counts",
  ...
)
```

Arguments

<code>object</code>	The Seurat object containing the single cell RNA-sequencing data.
<code>use_interactors</code>	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
<code>include_disease_pathways</code>	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.
<code>create_reactome_visualization</code>	If set, the interactive visualization in Reactome's PathwayBrowser is created.
<code>create_reports</code>	If set, PDF and Microsoft Excel reports are created. Links to these report files are sent to the supplied e-mail address.
<code>report_email</code>	The e-mail address to which reports should be sent to.
<code>verbose</code>	If set, additional status messages are printed.
<code>assay</code>	By default, the "RNA" assay is used, which contains the original read counts.
<code>slot</code>	The slot in the Seurat object to use. Default and recommended approach is to use the raw counts.
<code>...</code>	Parameters passed to the specific implementation. Detailed documentations can be found there.

Details

There are currently two specific implementations of this function, one to support Seurat objects and one to support Bioconductor's SingleCellExperiment class.

Value

A `ReactomeAnalysisResult` object.

Examples

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

analyse_sc_clusters, SingleCellExperiment-method
analyse_sc_clusters - SingleCellExperiment

Description

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

Usage

```
## S4 method for signature 'SingleCellExperiment'
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  cell_ids,
  ...
)
```

Arguments

<code>object</code>	The <code>SingleCellExperiment</code> object containing the single cell RNA-sequencing data.
<code>use_interactors</code>	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
<code>include_disease_pathways</code>	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.
<code>create_reactome_visualization</code>	If set, the interactive visualization in Reactome's PathwayBrowser is created.
<code>create_reports</code>	If set, PDF and Microsoft Excel reports are created. Links to these report files are send to the supplied e-mail address.
<code>report_email</code>	The e-mail address to which reports should be sent to.
<code>verbose</code>	If set, additional status messages are printed.
<code>cell_ids</code>	A factor specifying the group to which each cell belongs. For example, <code>object\$cluster</code> . Alternatively, a string specifying the metada field's name may be passed.
<code>...</code>	Parameters passed to <code>scater</code> 's <code>aggregateAcrossCells</code> function.

Details

There are currently two specific implementations of this function, one to support `Seurat` objects and one to support Bioconductor's `SingleCellExperiment` class.

Value

A `ReactomeAnalysisResult` object.

Examples

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

break_names	<i>break_names</i>
-------------	--------------------

Description

Introduce a line break in the middle of a long name.

Usage

```
break_names(the_names, long_name_limit = 46)
```

Arguments

the_names	A vector of names
long_name_limit	The limit to define a long name (defaultl 46 chars.)

Value

The list of adapted names

checkRequestValidity	<i>Check's if a ReactomeAnalysisRequest object is valid</i>
----------------------	---

Description

Check's if a ReactomeAnalysisRequest object is valid

Usage

```
checkRequestValidity(object)
```

Arguments

object	The request object to check.
--------	------------------------------

Value

TRUE if the object is valid or a string with the reason why it is not

check_reactome_url	<i>check_reactome_url</i>
--------------------	---------------------------

Description

Makes sure the passed URL is valid. If not URL is passed, the one stored in the options is retrieved

Usage

```
check_reactome_url(reactome_url)
```

Arguments

reactome_url character The URL to test. If NULL the URL is retrieved from the options.

Value

character The potentially cleaned / retrieved URL with a trailing "/"

convert_reactome_result	<i>Convert the Reactome JSON result to a ReactomeAnalysisResult object</i>
-------------------------	--

Description

Convert the Reactome JSON result to a ReactomeAnalysisResult object

Usage

```
convert_reactome_result(reactome_result)
```

Arguments

reactome_result
The JSON result already converted to R objects (name list)

Value

A [ReactomeAnalysisResult](#) object

data_frame_as_string	<i>Converts a data.frame to a string representation</i>
----------------------	---

Description

A data.frame is converted into a single string using ‘\t’ (the characters, not tab) as field delimiter and ‘\n’ (the characters, not newline) as line delimiter

Usage

```
data_frame_as_string(data)
```

Arguments

data	The data.frame to convert
------	---------------------------

Value

A string representing the passed data.frame

fetch_public_data	<i>fetch_public_data</i>
-------------------	--------------------------

Description

Loads an already available public dataset from ReactomeGSA and returns it as a Biobase::ExpressionSet object.

Usage

```
fetch_public_data(dataset_entry, reactome_url)
```

Arguments

dataset_entry	The entry of the respective dataset as returned by the find_public_datasets function.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the ‘reactome_gsa.url’ option. Specific ports can be set using the standard URL specification (for example http://your.service:1234)

Value

The loaded data as an ExpressionSet object.

find_public_datasets	<i>find_public_datasets</i>
----------------------	-----------------------------

Description

Search for a public dataset in the resources supported by ReactomeGSA as external data sources.

Usage

```
find_public_datasets(  
  search_term,  
  species = "Homo sapiens",  
  reactome_url = NULL  
)
```

Arguments

search_term	The search terms as a single string. Multiple words (seperated by a space) are combined by an "AND".
species	Limit the search to selected species. The complete list of available species can be retrieved through get_public_species . By default, entries as limited to human datasets.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example http://your.service:1234)

Value

A data.frame containing a list of datasets found through the search.

Examples

```
# search for any public dataset relating to BRAF in melanoma  
melanoma_datasets <- find_public_datasets("melanoma braf")  
  
# it is also possible to limit this to another species than human  
melanoma_mouse <- find_public_datasets("melanoma", species = "Mus musculus")  
  
# the list of available species can be retrieved using get_public_species  
all_species <- get_public_species()  
  
# datasets can then be loaded using the load_public_dataset function
```

generate_metadata	<i>generate_metadata</i>
-------------------	--------------------------

Description

The pseudobulk data is generated using the [generate_pseudo_bulk_data](#) function.

Usage

```
generate_metadata(pseudo_bulk_data)
```

Arguments

`pseudo_bulk_data`
Pseudobulk data generated from the [generate_pseudo_bulk_data](#) function

Value

Metadata table for later use

See Also

[generate_pseudo_bulk_data](#) for generating pseudobulk data.

Examples

```
# Example pseudobulk data
pseudo_bulk_data <- data.frame(
  sample1_groupA = c(10, 20, 30),
  sample2_groupA = c(15, 25, 35),
  sample3_groupB = c(5, 10, 15)
)

# Generate metadata from pseudobulk data
metadata <- generate_metadata(pseudo_bulk_data)
```

generate_metadata, data.frame-method
<i>Generate metadata</i>

Description

Generate metadata

Usage

```
## S4 method for signature 'data.frame'
generate_metadata(pseudo_bulk_data)
```

Arguments

pseudo_bulk_data

Pseudobulk data generated from the `generate_pseudo_bulk_data` function**Value**

Returns metadata table for later use

`generate_pseudo_bulk_data`*generate_pseudo_bulk_data*

Description`generate_pseudo_bulk_data`**Usage**

```
generate_pseudo_bulk_data(
  object,
  group_by = NULL,
  split_by = "random",
  k_variable = 4
)
```

Arguments

<code>object</code>	The Seurat or SingleCellExperiment object to analyse.
<code>group_by</code>	entry in metadata table, based on these cluster annotation pseudo bulk is performed
<code>split_by</code>	variable -> split by a variable within the metadata; k must be a string random -> splits based on a random number; k must be a number Louvain, Louvain_multilevel, SLM, Leiden -> subclusters k must be a list with [resolution, cluster_1, cluster_2]
<code>k_variable</code>	variable dependent on the split_by

Value

returns pseudo bulk generated data

Examples

```
#using SCE object
library("scRNAseq")
SCE_OBJECT <- ZeiselBrainData()
# generating pseudo bulk data using the SCE object above,
# and clustering level level1class from the metadata

# generate pseudo bulk data based on random subsampling
SCE_RESULT_RANDOM <- generate_pseudo_bulk_data(SCE_OBJECT,
  group_by = "level1class",
```

```

split_by = "random",
k_variable = 5)

# generate pseudo bulk data based on variable within the metadata
SCE_RESULT_VARIABLE <- generate_pseudo_bulk_data(SCE_OBJECT, "level1class", "variable", "tissue")

```

```

generate_pseudo_bulk_data, Seurat-method
      generate_pseudo_bulk_data - Seurat

```

Description

Generate Pseudo Bulk Data for Seurat Objects

Usage

```

## S4 method for signature 'Seurat'
generate_pseudo_bulk_data(
  object,
  group_by = NULL,
  split_by = "random",
  k_variable = 4
)

```

Arguments

object	The object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
split_by	variable -> split by a variable within the metadata; k must be a string random -> splits based on a random number; k must be a number Louvain, Louvain_multilevel, SLM, Leiden -> subclusters k must be a list with [resolution, cluster_1, cluster_2]
k_variable	variable dependent on the split_by

Value

returns pseudo bulk generated data

```
generate_pseudo_bulk_data, SingleCellExperiment-method
      generate_pseudo_bulk_data - SingleCellExperiment
```

Description

generate_pseudo_bulk_data - SingleCellExperiment

Usage

```
## S4 method for signature 'SingleCellExperiment'
generate_pseudo_bulk_data(
  object,
  group_by = NULL,
  split_by = "random",
  k_variable = 4
)
```

Arguments

object	The SingleCellExperiment object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
split_by	variable -> split by a variable within the metadata; k must be a string random -> splits based on a random number; k must be a number subclustering [resolution, cluster_1, cluster_2]
k_variable	variable dependent on the split_by

Value

returns pseudo bulk generated data

```
get_dataset_loading_status
      Retrieves the status of the submitted dataset loading request
```

Description

Retrieves the status of the submitted dataset loading request

Usage

```
get_dataset_loading_status(loading_id, reactome_url = NULL)
```

Arguments

loading_id	The dataset loading process' id
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example http://your.service:1234)

Value

A list containing the id, status (can be "running", "complete", "failed"), description, and completed (numeric between 0 - 1)

get_fc_for_dataset	<i>get_fc_for_dataset</i>
--------------------	---------------------------

Description

Retrieve the fold-changes for all pathways of the defined dataset

Usage

```
get_fc_for_dataset(dataset, pathway_result)
```

Arguments

dataset	Name of the dataset to retrieve the fold changes for.
pathway_result	The data.frame created by the pathways function.

Value

A vector of fold-changes

get_is_sig_dataset	<i>get_is_sig_dataset</i>
--------------------	---------------------------

Description

Determines how significant a pathway is across the datasets. Returns the lowest significance.

Usage

```
get_is_sig_dataset(dataset, pathway_result)
```

Arguments

dataset	Name of the dataset
pathway_result	data.frame created by the pathways function

Value

A vector with 3=non-significant, 2= $p \leq 0.05$, 1= $p < 0.01$

get_public_species	<i>get_public_species</i>
--------------------	---------------------------

Description

Return the list of found species labels in the supported public data resources

Usage

```
get_public_species(reactome_url = NULL)
```

Arguments

reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)
--------------	--

Value

A vector of species strings.

Examples

```
# get the available species
available_species <- get_public_species()

# inspect the first 1 - 3 entries
available_species[1:3]
```

get_reactome_analysis_result	<i>Retrieves the result of the submitted analysis using</i> <i>perform_reactome_analysis</i>
------------------------------	---

Description

The result is only available if `get_reactome_analysis_status` indicates that the analysis is complete.

Usage

```
get_reactome_analysis_result(analysis_id, reactome_url = NULL)
```

Arguments

analysis_id	The running analysis' id
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Value

The result object

`get_reactome_analysis_status`

*Retrieves the status of the submitted analysis using
[start_reactome_analysis](#)*

Description

Retrieves the status of the submitted analysis using [start_reactome_analysis](#)

Usage

```
get_reactome_analysis_status(analysis_id, reactome_url = NULL)
```

Arguments

<code>analysis_id</code>	The running analysis' id
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Value

A list containing the id, status (can be "running", "complete", "failed"), description, and completed (numeric between 0 - 1)

`get_reactome_data_types`

ReactomeGSA supported data types

Description

ReactomeGSA supported data types

Usage

```
get_reactome_data_types(  
  print_types = TRUE,  
  return_result = FALSE,  
  reactome_url = NULL  
)
```

Arguments

print_types	If set to TRUE (default) a (relatively) nice formatted version of the result is printed.
return_result	If set to TRUE, the result is returned as a data.frame (see below)
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Value

A `data.frame` containing one row per data type with its id and description.

Author(s)

Johannes Griss

See Also

Other Reactome Service functions: [get_reactome_methods\(\)](#)

Examples

```
# retrieve the available data types
available_types <- get_reactome_data_types(print_types = FALSE, return_result = TRUE)

# print all data type ids
available_types$id

# simply print the available methods
get_reactome_data_types()
```

`get_reactome_methods` *get_reactome_methods*

Description

Returns all available analysis methods from the Reactome analysis service.

Usage

```
get_reactome_methods(
  print_methods = TRUE,
  print_details = FALSE,
  return_result = FALSE,
  method = NULL,
  reactome_url = NULL
)
```

Arguments

<code>print_methods</code>	If set to TRUE (default) a (relatively) nice formatted version of the result is printed.
<code>print_details</code>	If set to TRUE detailed information about every method, including available parameters and description are displayed. This does not affect the data returned if <code>return_result</code> is TRUE.
<code>return_result</code>	If set to TRUE, the result is returned as a data.frame (see below)
<code>method</code>	If set to a method's id, only information for this method will be shown. This is especially useful if detailed information about a single method should be retrieved. This does not affect the data returned if <code>return_result</code> is TRUE.
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Details

Every method has a type, a scope, and sometimes a list of allowed values. The type (string, int = integer, float) define the expected data type. The **scope** defines at what level the parameter can be set. *dataset* level parameters can be set at the dataset level (using the [add_dataset](#) function) or at the analysis request level (using [set_parameters](#)). If these parameters are set at the analysis request level, this overwrites the default value for all datasets. *analysis* and *global* level parameters must only be set at the analysis request level using [set_parameters](#). The difference between these two types of parameters is that while *analysis* parameters influence the results, *global* parameters only influence the behaviour of the analysis system (for example whether a Reactome visualization is created).

Value

If `return_result` is set to TRUE, a data.frame with one row per method. Each method has a name, description, and (optional) a list of parameters. Parameters again have a name, type, and description.

Author(s)

Johannes Griss

See Also

Other Reactome Service functions: [get_reactome_data_types\(\)](#)

Examples

```
# retrieve the available methods only in an object
available_methods <- get_reactome_methods(print_methods = FALSE, return_result = TRUE)

# print all method names
available_methods$name

# list all parameters for the first method
first_method_parameters <- available_methods[1, "parameters"]
first_method_parameters

# simply print the available methods
get_reactome_methods()
```

```
# get the details for PADOG
get_reactome_methods(print_details = TRUE, method = "PADOG")
```

`get_result`*get_result*

Description

Retrieves a result from a [ReactomeAnalysisResult](#) object.

Usage

```
get_result(x, type, name)
```

Arguments

<code>x</code>	<code>ReactomeAnalysisResult</code> .
<code>type</code>	the type of result. Use result_types to retrieve all available types.
<code>name</code>	the name of the result. Use names to retrieve all available results.

Value

A `data.frame` containing the respective result.

See Also

Other `ReactomeAnalysisResult` functions: [names](#), [ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)

# get the dataset names
names(griss_melanoma_result)

# get the fold_changes for the first dataset
prot_fc <- get_result(griss_melanoma_result, type = "fold_changes", name = "proteomics")

head(prot_fc)
```

get_result, ReactomeAnalysisResult-method
ReactomeAnalysisResult - get_result

Description

Retrieves a result from a [ReactomeAnalysisResult](#) object.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'  
get_result(x, type, name)
```

Arguments

x	ReactomeAnalysisResult.
type	the type of result. Use result_types to retrieve all available types.
name	the name of the result. Use names to retrieve all available results.

Value

A data.frame containing the respective result.

See Also

Other ReactomeAnalysisResult functions: [names](#), [ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result object  
library(ReactomeGSA.data)  
data(griss_melanoma_result)  
  
# get the available result types  
result_types(griss_melanoma_result)  
  
# get the dataset names  
names(griss_melanoma_result)  
  
# get the fold_changes for the first dataset  
prot_fc <- get_result(griss_melanoma_result, type = "fold_changes", name = "proteomics")  
  
head(prot_fc)
```

is_gsva_result	<i>is_gsva_result</i>
----------------	-----------------------

Description

is_gsva_result

Usage

```
is_gsva_result(object)
```

Arguments

object A [ReactomeAnalysisResult](#) object

Value

Boolean indicating whether the object is a GSVA result.

load_public_dataset	<i>load_public_dataset</i>
---------------------	----------------------------

Description

Loads a public dataset that was found through the [find_public_datasets](#) function. The dataset is returned as a Biobase ExpressionSet object.

Usage

```
load_public_dataset(dataset_entry, verbose = FALSE, reactome_url = NULL)
```

Arguments

dataset_entry	The entry of the respective dataset as returned by the find_public_datasets function.
verbose	If set to TRUE, status messages and a status bar are displayed.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example http://your.service:1234)

Value

The loaded data as an ExpressionSet object.

Examples

```
# As a first step, you need to find available datasets
available_datasets <- find_public_datasets("psoriasis tnf")

# have a quick look at the found datasets
available_datasets[, c("id", "title")]

# load the first one, use the whole row of the found datasets
# data.frame as the parameter
dataset_1 <- load_public_dataset(available_datasets[1,], verbose = TRUE)
```

names, ReactomeAnalysisResult-method

ReactomeAnalysisResult - names

Description

Retrieves the names of the contained datasets within an [ReactomeAnalysisResult](#) object.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
names(x)
```

Arguments

x ReactomeAnalysisResult.

Value

character vector with the names of the contained datasets

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the names of the available datasets
names(griss_melanoma_result)
```

open_reactome	<i>open_reactome</i>
---------------	----------------------

Description

Opens the specified Reactome visualization in the system's default browser.

Usage

```
open_reactome(x, ...)
```

Arguments

x	ReactomeAnalysisResult.
...	Additional parameters passed to downstream functions.

Value

The opened link

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
# open_reactome(griss_melanoma_result)
```

open_reactome, ReactomeAnalysisResult-method
<i>open_reactome - ReactomeAnalysisResult</i>

Description

Opens the specified Reactome visualization in the system's default browser.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
open_reactome(x, n_visualization = 1, ...)
```

Arguments

`x` ReactomeAnalysisResult.

`n_visualization` numeric The index of the visualization to display (default 1). Use [reactome_links](#) to retrieve all available visualizations and their index. By default, the first visualization is opened.

`...` Additional parameters passed to downstream functions.

Value

The opened link

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
# open_reactome(griss_melanoma_result)
```

pathways

pathways

Description

Combines and returns the pathways of all analysed datasets.

Usage

```
pathways(x, ...)
```

Arguments

`x` ReactomeAnalysisResult.

`...` Additional parameters for specific implementations.

Value

A `data.frame` containing all merged pathways.

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

head(pathway_result)
```

pathways, ReactomeAnalysisResult-method
ReactomeAnalysisResult - pathways

Description

Combines and returns the pathways of all analysed datasets.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
pathways(x, p = 0.01, order_by = NULL, ...)
```

Arguments

x	ReactomeAnalysisResult.
p	Minimum p-value to accept a pathway as significantly regulated. Default is 0.01.
order_by	Name of the dataset to sort the result list by. By default, the results are sorted based on the first dataset.
...	Additional parameters for specific implementations.

Value

A data.frame containing all merged pathways.

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

head(pathway_result)
```

perform_reactome_analysis

Perform a Reactome Analysis

Description

This function wraps all steps required to perform an Analysis using the Reactome Analysis Service. It submits the passed [ReactomeAnalysisRequest](#) object to the Reactome Analysis Service API, checks the submitted analysis' status and returns the result once the analysis is complete.

Usage

```
perform_reactome_analysis(
  request,
  verbose = TRUE,
  compress = TRUE,
  reactome_url = NULL
)
```

Arguments

request	ReactomeAnalysisRequest to submit.
verbose	logical. If FALSE status messages are not printed to the console.
compress	logical. If TRUE (default) the request data is compressed before submitting it to the ReactomeGSA API. This is the generally recommended way and should only be disabled for debugging purposes.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Value

The analysis' result

Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)

my_request <- ReactomeAnalysisRequest(method = "Camera")
```

```
# set maximum missing values to 0.5 and do not create any reactome visualizations
my_request <- set_parameters(request = my_request,
                             max_missing_values = 0.5,
                             create_reactome_visualization = FALSE)

# add the dataset
my_request <- add_dataset(request = my_request,
                           expression_values = griss_melanoma_proteomics,
                           name = "Proteomics",
                           type = "proteomics_int",
                           comparison_factor = "condition",
                           comparison_group_1 = "MOCK",
                           comparison_group_2 = "MCM",
                           additional_factors = c("cell.type", "patient.id"))

# perform the analysis
my_result <- perform_reactome_analysis(request = my_request, verbose = FALSE)
```

plot_correlations	<i>plot_correlations</i>
-------------------	--------------------------

Description

Plots correlations of the average fold-changes of all pathways between the different datasets. This function is only available to GSA based results (not GSVA ones).

Usage

```
plot_correlations(x, hide_non_sig = FALSE)
```

Arguments

x ReactomeAnalysisResult. The result object to use as input

hide_non_sig If set, non-significant pathways are not shown.

Value

A list of ggplot2 plot objects representing one plot per combination

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the correlation plots
```

```
plot_objs <- plot_correlations(griss_melanoma_result)

# only one plot created for this result as it contains two datasets
length(plot_objs)

# show the plot using `print(plot_objs[[1]])`
```

```
plot_correlations, ReactomeAnalysisResult-method
      plot_correlations - ReactomeAnalysisResult
```

Description

Plots correlations of the average fold-changes of all pathways between the different datasets. This function is only available to GSA based results (not GSVA ones).

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_correlations(x, hide_non_sig = FALSE)
```

Arguments

x ReactomeAnalysisResult. The result object to use as input

hide_non_sig If set, non-significant pathways are not shown.

Value

A list of ggplot2 plot objects representing one plot per combination

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the correlation plots
plot_objs <- plot_correlations(griss_melanoma_result)

# only one plot created for this result as it contains two datasets
length(plot_objs)

# show the plot using `print(plot_objs[[1]])`
```

plot_gsva_heatmap	<i>plot_gsva_heatmap</i>
-------------------	--------------------------

Description

Plots pathway expression values / sample as a heatmap. Ranks pathways based on their expression difference.

Usage

```
plot_gsva_heatmap(
  object,
  pathway_ids = NULL,
  max_pathways = 20,
  truncate_names = TRUE,
  ...
)
```

Arguments

object	The ReactomeAnalysisResult object.
pathway_ids	A vector of pathway ids. If set, only these pathways are included in the plot.
max_pathways	The maximum number of pathways to include. Only takes effect if pathway_ids is not set.
truncate_names	If set, long pathway names are truncated.
...	Additional parameters passed to specific implementations.

Value

None

See Also

Other [ReactomeAnalysisResult](#) functions: [get_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# plot the heatmap
relevant_pathways <- c("R-HSA-983170", "R-HSA-388841", "R-HSA-2132295",
  "R-HSA-983705", "R-HSA-5690714")
plot_gsva_heatmap(gsva_result,
  pathway_ids = relevant_pathways, # limit to these pathways
```



```

margins = c(6,30), # adapt the figure margins in heatmap.2
dendrogram = "col", # only plot column dendrogram
scale = "row", # scale for each pathway
key = FALSE, # don't display the color key
lwid=c(0.1,4)) # remove the white space on the left

```

plot_gsva_heatmap, ReactomeAnalysisResult-method

plot_gsva_heatmap - ReactomeAnalysisResult function

Description

Plots pathway expression values / sample as a heatmap. Ranks pathways based on their expression difference.

Usage

```

## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_heatmap(
  object,
  pathway_ids = NULL,
  max_pathways = 20,
  truncate_names = TRUE,
  ...
)

```

Arguments

object	The ReactomeAnalysisResult object.
pathway_ids	A vector of pathway ids. If set, only these pathways are included in the plot.
max_pathways	The maximum number of pathways to include. Only takes effect if pathway_ids is not set.
truncate_names	If set, long pathway names are truncated.
...	Additional parameters passed to the heatmap.2 function.

Value

None

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# plot the heatmap
relevant_pathways <- c("R-HSA-983170", "R-HSA-388841", "R-HSA-2132295",
                      "R-HSA-983705", "R-HSA-5690714")
plot_gsva_heatmap(gsva_result,
                  pathway_ids = relevant_pathways, # limit to these pathways
                  margins = c(6,30), # adapt the figure margins in heatmap.2
                  dendrogram = "col", # only plot column dendrogram
                  scale = "row", # scale for each pathway
                  key = FALSE, # don't display the color key
                  lwid=c(0.1,4)) # remove the white space on the left
```

plot_gsva_pathway	<i>plot_gsva_pathway</i>
-------------------	--------------------------

Description

Plots the expression of a specific pathway from a ssGSEA result.

Usage

```
plot_gsva_pathway(object, pathway_id, ...)
```

Arguments

object	The ReactomeAnalysisResult object.
pathway_id	The pathway's id
...	Additional parameters for specific implementations.

Value

A ggplot2 plot object

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# create the plot
plot_obj <- plot_gsva_pathway(gsva_result, "R-HSA-389542")
```

```
plot_gsva_pathway, ReactomeAnalysisResult-method
      ReactomeAnalysisResult - plot_gsva_pathway
```

Description

Plots the expression of a specific pathway from a ssGSEA result.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_pathway(object, pathway_id, ...)
```

Arguments

object	The ReactomeAnalysisResult object.
pathway_id	The pathway's id
...	Additional parameters for specific implementations.

Value

A ggplot2 plot object

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# create the plot
plot_obj <- plot_gsva_pathway(gsva_result, "R-HSA-389542")
```

plot_gsva_pca	<i>plot_gsva_pca</i>
---------------	----------------------

Description

Runs a Principal Component analysis (using prcomp) on the samples based on the pathway analysis results.

Usage

```
plot_gsva_pca(object, pathway_ids = NULL, ...)
```

Arguments

object	A ReactomeAnalysisResult object containing a ssGSEA result
pathway_ids	A character vector of pathway ids. If set, only these pathways will be used for the PCA analysis.
...	Additional paramters passed to specific implementations.

Value

A ggplot2 object representing the plot.

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

plot_gsva_pca, ReactomeAnalysisResult-method
<i>plot_gsva_pca - ReactomeAnalysisResult</i>

Description

Runs a Principal Component analysis (using prcomp) on the samples based on the pathway analysis results.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_pca(object, pathway_ids = NULL, ...)
```

Arguments

object	A ReactomeAnalysisResult object containing a ssGSEA result
pathway_ids	A character vector of pathway ids. If set, only these pathways will be used for the PCA analysis.
...	Additional parameters are passed to prcomp

Value

A ggplot2 object representing the plot.

Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

plot_heatmap

plot_heatmap

Description

Creates a heatmap to show which pathways are up- and down-regulated in different datasets

Usage

```
plot_heatmap(
  x,
  fdr = 0.01,
  max_pathways = 30,
  break_long_names = TRUE,
  return_data = FALSE
)
```

Arguments

x	ReactomeAnalysisResult . The result object to use as input
fdr	numeric. The minimum FDR to consider a pathways as significantly regulated. (Default 0.01)
max_pathways	numeric. The maximum number of pathways to plot. Pathways are sorted based on in how many datasets they are significantly regulated. This has no effect if return_data is set to TRUE.
break_long_names	logical. If set, long pathway names are broken into two lines.
return_data	logical. If set, only the plotting data, but not the plot object itself is returned. This can be used to create customized plots that use the same data structure.

Value

A ggplot2 plot object representing the heatmap of pathways

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the heatmap plot
plot_obj <- plot_heatmap(griss_melanoma_result)

# show the plot
print(plot_obj)
```

plot_heatmap, ReactomeAnalysisResult-method

plot_heatmap - ReactomeAnalysisResult

Description

Creates a heatmap to show which pathways are up- and down-regulated in different datasets

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_heatmap(
  x,
  fdr = 0.01,
  max_pathways = 30,
  break_long_names = TRUE,
  return_data = FALSE
)
```

Arguments

x	ReactomeAnalysisResult. The result object to use as input
fdr	numeric. The minimum FDR to consider a pathways as significantly regulated. (Default 0.01)
max_pathways	numeric. The maximum number of pathways to plot. Pathways are sorted based on in how many datasets they are significantly regulated. This has no effect if return_data is set to TRUE.
break_long_names	logical. If set, long pathway names are broken into two lines.
return_data	logical. If set, only the plotting data, but not the plot object itself is returned. This can be used to create customized plots that use the same data structure.

Value

A ggplot2 plot object representing the heatmap of pathways

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the heatmap plot
plot_obj <- plot_heatmap(griss_melanoma_result)

# show the plot
print(plot_obj)
```

plot_volcano

plot_volcano

Description

Creates a volcano plot for the pathway analysis result. Every point represents one pathway, the x-axis the log fold-change and the y-axis the adjusted p-value (-log10).

Usage

```
plot_volcano(x, ...)
```

Arguments

x	ReactomeAnalysisResult. The analysis result to plot the volcano plot for.
...	Additional parameters for specific implementations.

Details

This function is only available for GSA-based analysis results.

Value

A ggplot2 plot object representing the volcano plot.

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the volcano plot for the first dataset
plot_obj <- plot_volcano(griss_melanoma_result)

# display the plot using `print(plot_obj)`
```

plot_volcano, ReactomeAnalysisResult-method

ReactomeAnalysisResult - plot_volcano

Description

Creates a volcano plot for the pathway analysis result. Every point represents one pathway, the x-axis the log fold-change and the y-axis the adjusted p-value (-log10).

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_volcano(x, dataset = 1, ...)
```

Arguments

x	ReactomeAnalysisResult. The analysis result to plot the volcano plot for.
dataset	The name or index of the dataset to plot (first one by default).
...	Additional parameters for specific implementations.

Details

This function is only available for GSA-based analysis results.

Value

A ggplot2 plot object representing the volcano plot.

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [reactome_links\(\)](#), [result_types\(\)](#)

Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the volcano plot for the first dataset
plot_obj <- plot_volcano(griss_melanoma_result)

# display the plot using `print(plot_obj)`
```

```
print,ReactomeAnalysisRequest-method
```

```
print - ReactomeAnalysisRequest
```

Description

Shows a [ReactomeAnalysisRequest](#) object summary.

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
print(x, ...)
```

Arguments

x	ReactomeAnalysisRequest
...	Not used

Value

The classname of the object

Examples

```
library(methods)

request <- ReactomeAnalysisRequest(method = "Camera")
print(request)

# add additional parameters
request <- set_parameters(request, "max_missing_values" = 0.5)
show(request)
```

```
print,ReactomeAnalysisResult-method  
print - ReactomeAnalysisResult
```

Description

Displays basic information about the [ReactomeAnalysisResult](#) object.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'  
print(x, ...)
```

Arguments

x	ReactomeAnalysisResult.
...	Not used

Value

character classname of the object

Examples

```
library(ReactomeGSA.data)  
data(griss_melanoma_result)  
  
print(griss_melanoma_result)
```

```
ReactomeAnalysisRequest  
ReactomeAnalysisRequest class
```

Description

This class is used to collect all information required to submit an analysis request to the Reactome Analysis System.

Usage

```
ReactomeAnalysisRequest(method)  
  
ReactomeAnalysisRequest(method)
```

Arguments

method	character. Name of the method to use.
--------	---------------------------------------

Value

A ReactomeAnalysisRequest object.

Slots

method character. Name of the method to use

request_object list. This slot should not be set manually. It stores the internal request representation and should be modified using the classes' functions. To add parameters, use [set_parameters, ReactomeAnalysisRequest-method](#)

Examples

```
library(ReactomeGSA.data)
library(methods)

# create the request method and specify its method
request <- ReactomeAnalysisRequest(method = "Camera")

# add a dataset to the request
data(griss_melanoma_proteomics)

request <- add_dataset(request = request,
  expression_values = griss_melanoma_proteomics,
  name = "Proteomics",
  type = "proteomics_int",
  comparison_factor = "condition",
  comparison_group_1 = "MOCK",
  comparison_group_2 = "MCM",
  additional_factors = c("cell.type", "patient.id"))

# to launch the actual analysis use the perform_reactome_analysis function
```

 ReactomeAnalysisResult-class

ReactomeAnalysisResult class

Description

A ReactomeAnalysisResult object contains the pathway analysis results of all submitted datasets at once.

Details

This class represents a result retrieved from the Reactome Analysis Service. It is returned by [get_reactome_analysis_result](#) and its wrapper [perform_reactome_analysis](#). Generally, object of this class should not be created manually.

Value

A ReactomeAnalysisResult object.

Slots

reactome_release The Reactome version used to create this result.

mappings Stores the mapping results that were generated for this analysis.

results A named list containing the actual analysis results for every dataset and possibly combined results as well.

reactome_links Links pointing to reactome results as a list.

Methods

names: Retrieves the names of all datasets in the result object

result_types: Retrieves the available result types

pathways: Merges the pathway results of all analysed datasets.

get_result: Retrieve a specific result as data.frame

reactome_links: Displays / retrieves the URLs to the available visualizations in Reactome's pathway browser.

open_reactome: Opens the specified Reactome visualization in the system's default browser.

Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# retrieve the names of all datasets in the result
names(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

# check which result types are available
result_types(griss_melanoma_result)

# get the fold changes for the first dataset
first_dataset_name <- names(griss_melanoma_result)[1]

first_fc <- get_result(griss_melanoma_result, "fold_changes", first_dataset_name)
```

reactome_links	<i>reactome_links</i>
----------------	-----------------------

Description

Displays detailed information about the result visualizations in Reactome.

Usage

```
reactome_links(x, ...)
```

Arguments

x	ReactomeAnalysisResult.
...	Additional parameters for specific implementations.

Value

If `return_result` is set to `TRUE`, a vector of the available visualizations.

See Also

Other `ReactomeAnalysisResult` functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [result_types\(\)](#)

Examples

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
reactome_links(griss_melanoma_result)
```

`reactome_links, ReactomeAnalysisResult-method`
ReactomeAnalysisResult - reactome_links

Description

Displays detailed information about the result visualizations in Reactome.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
reactome_links(x, print_result = TRUE, return_result = FALSE)
```

Arguments

<code>x</code>	<code>ReactomeAnalysisResult</code> .
<code>print_result</code>	If set to <code>FALSE</code> the links are not printed to the console.
<code>return_result</code>	If <code>TRUE</code> the available visualizations are returned as a list containing named vectors for every visualization. These vectors' have a <code>url</code> , <code>name</code> , and optionally a <code>description</code> slot.

Value

If `return_result` is set to `TRUE`, a vector of the available visualizations.

See Also

Other `ReactomeAnalysisResult` functions: [get_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [result_types\(\)](#)

Examples

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
reactome_links(griss_melanoma_result)
```

remove_dataset	<i>remove_dataset</i>
----------------	-----------------------

Description

Remove the dataset from the [ReactomeAnalysisRequest](#) object.

Usage

```
remove_dataset(x, dataset_name)
```

Arguments

x	The ReactomeAnalysisRequest to remove the dataset from
dataset_name	character The dataset's name

Value

The updated [ReactomeAnalysisRequest](#)

remove_dataset, ReactomeAnalysisRequest-method
<i>remove_dataset - ReactomeAnalysisRequest</i>

Description

Remove the dataset from the [ReactomeAnalysisRequest](#) object.

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
remove_dataset(x, dataset_name)
```

Arguments

x	The ReactomeAnalysisRequest to remove the dataset from
dataset_name	character The dataset's name

Value

The updated [ReactomeAnalysisRequest](#)

result_types	<i>result_types</i>
--------------	---------------------

Description

Retrieves the available result types for the [ReactomeAnalysisResult](#) object. Currently, the Reactome Analysis System supports pathways and gene level fold_changes as result types. Not all analysis methods return both data types though. Use the names function to find out which datasets are available in the result object.

Usage

```
result_types(x)
```

Arguments

x [ReactomeAnalysisResult](#).

Value

A character vector of result types.

See Also

Other [ReactomeAnalysisResult](#) functions: [get_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#)

Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)
```

result_types, ReactomeAnalysisResult-method
<i>ReactomeAnalysisResult - result_types</i>

Description

Retrieves the available result types for the [ReactomeAnalysisResult](#) object. Currently, the Reactome Analysis System supports pathways and gene level fold_changes as result types. Not all analysis methods return both data types though. Use the names function to find out which datasets are available in the result object.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
result_types(x)
```

Arguments

x ReactomeAnalysisResult.

Value

A cacharacter vector of result types.

See Also

Other ReactomeAnalysisResult functions: [get_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open_reactome\(\)](#), [pathways\(\)](#), [plot_correlations\(\)](#), [plot_gsva_heatmap\(\)](#), [plot_gsva_pathway\(\)](#), [plot_heatmap\(\)](#), [plot_volcano\(\)](#), [reactome_links\(\)](#)

Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)
```

set_method	<i>set_method</i>
------------	-------------------

Description

Set the analysis method used by the [ReactomeAnalysisRequest](#)

Usage

```
set_method(request, method, ...)
```

Arguments

request	The ReactomeAnalysisRequest to adjust
method	The name of the method to use. Use get_reactome_methods to retrieve all available methods
...	Additional parameters passed to specific implementations

Value

The [ReactomeAnalysisRequest](#) with the adapted method

Examples

```
# create a request using Camera as an analysis
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

print(my_request)

# change the method to ssGSEA
my_request <- set_method(my_request, "ssGSEA")

print(my_request)
```

set_method, ReactomeAnalysisRequest-method
set_method - ReactomeAnalysisRequest

Description

Set the analysis method used by the [ReactomeAnalysisRequest](#)

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
set_method(request, method, ...)
```

Arguments

request	The ReactomeAnalysisRequest to adjust
method	The name of the method to use. Use get_reactome_methods to retrieve all available methods
...	Additional parameters passed to specific implementations

Value

The [ReactomeAnalysisRequest](#) with the adapted method

Examples

```
# create a request using Camera as an analysis
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

print(my_request)

# change the method to ssGSEA
my_request <- set_method(my_request, "ssGSEA")

print(my_request)
```

set_parameters	<i>set_parameters</i>
----------------	-----------------------

Description

Sets the analysis parameters for the given [ReactomeAnalysisRequest](#). If the parameter is already set, it is overwritten. Use [get_reactome_methods](#) to get a list of all available parameters for each available method.

Usage

```
set_parameters(request, ...)
```

Arguments

request	The ReactomeAnalysisRequest to set the parameters for.
...	Any name / value pair to set a parameter (see example). For a complete list of available parameters use get_reactome_methods

Details

Both, parameters with the scope "dataset" as well as "analysis" can be set on the analysis level. In this case, these parameters overwrite the system's default values. If a parameter with the scope "dataset" is defined again at the dataset level, this value will overwrite the analysis' scope value for the given dataset.

Value

The modified [ReactomeAnalysisRequest](#) object

Examples

```
library(methods)

# create a request object
request <- ReactomeAnalysisRequest(method = "Camera")

# add a parameter
request <- set_parameters(request, max_missing_values = 0.5, discrete_norm_function = "TMM")
```

set_parameters, ReactomeAnalysisRequest-method
<i>ReactomeAnalysisRequest - set_parameters</i>

Description

Sets the analysis parameters for the given [ReactomeAnalysisRequest](#). If the parameter is already set, it is overwritten. Use [get_reactome_methods](#) to get a list of all available parameters for each available method.

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
set_parameters(request, ...)
```

Arguments

request	The ReactomeAnalysisRequest to set the parameters for.
...	Any name / value pair to set a parameter (see example). For a complete list of available parameters use get_reactome_methods

Details

Both, parameters with the scope "dataset" as well as "analysis" can be set on the analysis level. In this case, these parameters overwrite the system's default values. If a parameter with the scope "dataset" is defined again at the dataset level, this value will overwrite the analysis' scope value for the given dataset.

Value

The modified [ReactomeAnalysisRequest](#) object

Examples

```
library(methods)

# create a request object
request <- ReactomeAnalysisRequest(method = "Camera")

# add a parameter
request <- set_parameters(request, max_missing_values = 0.5, discrete_norm_function = "TMM")
```

```
show,ReactomeAnalysisRequest-method
  print - ReactomeAnalysisRequest
```

Description

Shows a [ReactomeAnalysisRequest](#) object summary.

Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
show(object)
```

Arguments

object	ReactomeAnalysisRequest
--------	---

Value

The classname of the object

Examples

```
library(methods)

request <- ReactomeAnalysisRequest(method = "Camera")
print(request)

# add additional parameters
request <- set_parameters(request, "max_missing_values" = 0.5)
show(request)
```

```
show,ReactomeAnalysisResult-method
      show - ReactomeAnalysisResult
```

Description

Displays basic information about the [ReactomeAnalysisResult](#) object.

Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
show(object)
```

Arguments

object [ReactomeAnalysisResult](#).

Value

character classname of the object

Examples

```
library(ReactomeGSA.data)
data(griss_melanoma_result)

show(griss_melanoma_result)
```

```
split_clustering        method implementation subclustering
```

Description

method implementation subclustering

Usage

```
split_clustering(seurat_object, group_by, res, alg, cluster1, cluster2)
```

Arguments

seurat_object	The Seurat object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
res	The clustering resolution to use.
alg	Seurat subclustering algorithm id
cluster1	cluster to subcluster
cluster2	cluster to subcluster

Value

returns pseudo bulk generated data

split_random_sce	<i>split SCE Object with random pooling</i>
------------------	---

Description

split SCE Object with random pooling

Usage

```
split_random_sce(sce_object, group_by, k_variable)
```

Arguments

sce_object	The SingleCellExperiment object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
k_variable	number of pools that should be created

Value

returns pseudo bulk generated data

split_subclustering_sce

split SCE Object with random pooling

Description

split SCE Object with random pooling

Usage

```
split_subclustering_sce(
  sce_object,
  group_by,
  resolution,
  subcluster_ref,
  subcluster_comp
)
```

Arguments

sce_object	The SingleCellExperiment object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
resolution	resolution
subcluster_ref	cluster to subcluster as areference
subcluster_comp	cluster to subcluster for comparison

Value

returns pseudo bulk generated data

split_variable

split Seurat object by variable

Description

split Seurat object by variable

Usage

```
split_variable(seurat_object, group_by, k_variable)
```

Arguments

seurat_object	The Seurat object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
k_variable	variable dependent on the split_by -> meta data entry

Value

returns pseudo bulk generated data

split_variable_random *split Seurat object by random pooling*

Description

split Seurat object by random pooling

Usage

```
split_variable_random(seurat_object, group_by, k_variable)
```

Arguments

seurat_object	The Seurat object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
k_variable	number of random pools

Value

returns pseudo bulk generated data

split_variable_sce *split SCE Object by variable*

Description

split SCE Object by variable

Usage

```
split_variable_sce(sce_object, group_by, k_variable)
```

Arguments

sce_object	The SingleCellExperiment object to analyse.
group_by	entry in metadata table, based on these cluster annotation pseudo bulk is performed
k_variable	variable for sub setting must be in the metadata

Value

returns pseudo bulk generated data

start_reactome_analysis

Start Reactome Analysis

Description

Submits a [ReactomeAnalysisRequest](#) to the Reactome Analysis Service API and returns the analysis id of the submitted job.

Usage

```
start_reactome_analysis(request, compress = TRUE, reactome_url = NULL)
```

Arguments

request	ReactomeAnalysisRequest object to submit.
compress	If set (default) the JSON request data is compressed using gzip.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code>)

Details

This function should only be used for very large requests that likely take a long time to complete. By default, users should use the [perform_reactome_analysis](#) function to run an analysis.

Value

character The analysis job's id.

```
#' @examples # create a request using Camera as an analysis library(ReactomeGSA.data) data(griss_melanoma_proteomics)
my_request <- ReactomeAnalysisRequest(method = "Camera")

# set maximum missing values to 0.5 and do not create any reactome visualizations my_request <-
set_parameters(request = my_request, max_missing_values = 0.5, create_reactome_visualization =
FALSE)

# add the dataset my_request <- add_dataset(request = my_request, expression_values = griss_melanoma_proteomics,
name = "Proteomics", type = "proteomics_int", comparison_factor = "condition", comparison_group_1
= "MOCK", comparison_group_2 = "MCM", additional_factors = c("cell.type", "patient.id")) #
start the analysis analysis_id <- start_reactome_analysis(my_request)
```

```
wait_for_loading_dataset  
    wait_for_loading_dataset
```

Description

This function loops until the dataset is available. If verbose is set to TRUE, the progress is displayed in a status bar.

Usage

```
wait_for_loading_dataset(request, verbose, reactome_url)
```

Arguments

request	The httr request object of the dataset loading request.
verbose	If set to TRUE, the progress is displayed as a status bar.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example http://your.service:1234)

Index

- * **Reactome Service functions**
 - get_reactome_data_types, [27](#)
 - get_reactome_methods, [28](#)
- * **ReactomeAnalysisResult functions**
 - get_result, [30](#)
 - names, ReactomeAnalysisResult-method, [33](#)
 - open_reactome, [34](#)
 - pathways, [35](#)
 - plot_correlations, [38](#)
 - plot_gsva_heatmap, [40](#)
 - plot_gsva_pathway, [42](#)
 - plot_heatmap, [45](#)
 - plot_volcano, [47](#)
 - reactome_links, [52](#)
 - result_types, [55](#)
- * **add_dataset methods**
 - add_dataset, [3](#)
 - add_dataset, ReactomeAnalysisRequest, data.frame-method, [5](#)
 - add_dataset, ReactomeAnalysisRequest, DGEList-method, [6](#)
 - add_dataset, ReactomeAnalysisRequest, EList-method, [8](#)
 - add_dataset, ReactomeAnalysisRequest, ExpressionSet-method, [10](#)
 - add_dataset, ReactomeAnalysisRequest, matrix-method, [11](#)
- add_dataset, [3](#), [6](#), [8](#), [9](#), [11](#), [12](#), [29](#)
- add_dataset, ReactomeAnalysisRequest, data.frame-method, [5](#)
- add_dataset, ReactomeAnalysisRequest, DGEList-method, [6](#)
- add_dataset, ReactomeAnalysisRequest, EList-method, [8](#)
- add_dataset, ReactomeAnalysisRequest, ExpressionSet-method, [10](#)
- add_dataset, ReactomeAnalysisRequest, matrix-method, [11](#)
- analyse_sc_clusters, [13](#)
- analyse_sc_clusters, Seurat-method, [14](#)
- analyse_sc_clusters, SingleCellExperiment-method, [15](#)
- break_names, [17](#)
- check_reactome_url, [18](#)
- checkRequestValidity, [17](#)
- convert_reactome_result, [18](#)
- data_frame_as_string, [19](#)
- fetch_public_data, [19](#)
- find_public_datasets, [19](#), [20](#), [32](#)
- generate_metadata, [21](#)
- generate_metadata, data.frame-method, [21](#)
- generate_pseudo_bulk_data, [21](#), [22](#), [22](#)
- generate_pseudo_bulk_data, Seurat-method, [23](#)
- generate_pseudo_bulk_data, SingleCellExperiment-method, [24](#)
- get_dataset_loading_status, [24](#)
- get_fc_for_dataset, [25](#)
- get_is_sig_dataset, [25](#)
- get_public_species, [20](#), [26](#)
- get_reactome_analysis_result, [26](#), [51](#)
- get_reactome_analysis_status, [26](#), [27](#)
- get_reactome_data_types, [4](#), [5](#), [7](#), [9](#), [10](#), [12](#), [27](#), [29](#)
- get_reactome_methods, [28](#), [28](#), [56–59](#)
- get_result, [30](#), [33–36](#), [38–43](#), [46–48](#), [52](#), [53](#), [55](#), [56](#)
- get_result, ReactomeAnalysisResult-method, [31](#)
- is_gsva_result, [32](#)
- load_public_dataset, [32](#)
- names, [30](#), [31](#), [52](#)
- names, ReactomeAnalysisResult-method, [33](#)
- open_reactome, [30](#), [31](#), [33](#), [34](#), [36](#), [38–43](#), [46–48](#), [52](#), [53](#), [55](#), [56](#)
- open_reactome, ReactomeAnalysisResult-method, [34](#)

- pathways, [30](#), [31](#), [33–35](#), [35](#), [38–43](#), [46–48](#),
[52](#), [53](#), [55](#), [56](#)
- pathways, ReactomeAnalysisResult-method,
[36](#)
- perform_reactome_analysis, [26](#), [37](#), [51](#), [64](#)
- plot_correlations, [30](#), [31](#), [33–36](#), [38](#),
[40–43](#), [46–48](#), [53](#), [55](#), [56](#)
- plot_correlations, ReactomeAnalysisResult-method,
[39](#)
- plot_gsva_heatmap, [30](#), [31](#), [33–36](#), [38](#), [39](#),
[40](#), [42](#), [43](#), [46–48](#), [53](#), [55](#), [56](#)
- plot_gsva_heatmap, ReactomeAnalysisResult-method,
[41](#)
- plot_gsva_pathway, [30](#), [31](#), [33–36](#), [38–41](#),
[42](#), [46–48](#), [53](#), [55](#), [56](#)
- plot_gsva_pathway, ReactomeAnalysisResult-method,
[43](#)
- plot_gsva_pca, [44](#)
- plot_gsva_pca, ReactomeAnalysisResult-method,
[44](#)
- plot_heatmap, [30](#), [31](#), [33–36](#), [38–43](#), [45](#), [47](#),
[48](#), [53](#), [55](#), [56](#)
- plot_heatmap, ReactomeAnalysisResult-method,
[46](#)
- plot_volcano, [30](#), [31](#), [33–36](#), [38–43](#), [46](#), [47](#),
[47](#), [53](#), [55](#), [56](#)
- plot_volcano, ReactomeAnalysisResult-method,
[48](#)
- print, ReactomeAnalysisRequest-method,
[49](#)
- print, ReactomeAnalysisResult-method,
[50](#)
- reactome_links, [30](#), [31](#), [33–36](#), [38–43](#),
[46–48](#), [52](#), [52](#), [55](#), [56](#)
- reactome_links, ReactomeAnalysisResult-method,
[53](#)
- ReactomeAnalysisRequest, [4](#), [6](#), [7](#), [9](#), [11](#), [12](#),
[37](#), [49](#), [50](#), [54](#), [56–59](#), [64](#)
- ReactomeAnalysisResult, [14–16](#), [18](#), [30–33](#),
[40–45](#), [50](#), [55](#), [60](#)
- ReactomeAnalysisResult
(ReactomeAnalysisResult-class),
[51](#)
- ReactomeAnalysisResult-class, [51](#)
- remove_dataset, [54](#)
- remove_dataset, ReactomeAnalysisRequest-method,
[54](#)
- result_types, [30](#), [31](#), [33–36](#), [38–43](#), [46–48](#),
[52](#), [53](#), [55](#)
- result_types, ReactomeAnalysisResult-method,
[55](#)
- set_method, [56](#)
- set_method, ReactomeAnalysisRequest-method,
[57](#)
- set_parameters, [29](#), [58](#)
- set_parameters, ReactomeAnalysisRequest-method,
[58](#)
- show, ReactomeAnalysisRequest-method,
[59](#)
- show, ReactomeAnalysisResult-method, [60](#)
- split_clustering, [60](#)
- split_random_sce, [61](#)
- split_subclustering_sce, [62](#)
- split_variable, [62](#)
- split_variable_random, [63](#)
- split_variable_sce, [63](#)
- start_reactome_analysis, [27](#), [64](#)
- wait_for_loading_dataset, [65](#)