

# Package ‘SPLINTER’

July 8, 2025

**Type** Package

**Title** Splice Interpreter of Transcripts

**Version** 1.35.0

**Date** 2024-04-24

**URL** <https://github.com/dianalow/SPLINTER/>

**BugReports** <https://github.com/dianalow/SPLINTER/issues>

**Description** Provides tools to analyze alternative splicing sites, interpret outcomes based on sequence information, select and design primers for site validation and give visual representation of the event to guide downstream experiments.

**License** GPL-2

**LazyData** TRUE

**Depends** R (>= 3.6.0), grDevices, stats

**Imports** graphics, ggplot2, seqLogo, Biostrings, pwalgn, biomaRt, GenomicAlignments, GenomicRanges, GenomicFeatures, Gviz, IRanges, S4Vectors, GenomeInfoDb, utils, plyr, stringr, methods, BSgenome.Mmusculus.UCSC.mm9, googleVis

**biocViews** ImmunoOncology, GeneExpression, RNASeq, Visualization, AlternativeSplicing

**Collate** primerpcr.R main\_splinter.R

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**VignetteBuilder** knitr

**Suggests** txdbmaker, BiocStyle, knitr, rmarkdown

**git\_url** <https://git.bioconductor.org/packages/SPLINTER>

**git\_branch** devel

**git\_last\_commit** 82171f3

**git\_last\_commit\_date** 2025-04-15

**Repository** Bioconductor 3.22

**Date/Publication** 2025-07-07

**Author** Diana Low [aut, cre]

**Maintainer** Diana Low <lowdiana@gmail.com>

## Contents

|                                 |    |
|---------------------------------|----|
| acceptor.m . . . . .            | 3  |
| addEnsemblAnnotation . . . . .  | 3  |
| annotateEvents . . . . .        | 4  |
| callPrimer3 . . . . .           | 5  |
| checkPrimer . . . . .           | 6  |
| compatible_cds . . . . .        | 6  |
| compatible_tx . . . . .         | 7  |
| donor.m . . . . .               | 7  |
| eventOutcomeCompare . . . . .   | 8  |
| eventOutcomeTranslate . . . . . | 9  |
| eventPlot . . . . .             | 10 |
| extendROI . . . . .             | 11 |
| extractSpliceEvents . . . . .   | 11 |
| extractSpliceSites . . . . .    | 12 |
| findCompatibleEvents . . . . .  | 13 |
| findCompatibleExon . . . . .    | 14 |
| findExactOverlaps . . . . .     | 15 |
| findTermination . . . . .       | 15 |
| findTX . . . . .                | 16 |
| getPCRSizes . . . . .           | 16 |
| getRegionDNA . . . . .          | 17 |
| insertRegion . . . . .          | 18 |
| makeROI . . . . .               | 19 |
| makeUniqueIDs . . . . .         | 19 |
| matchExons . . . . .            | 20 |
| metaremove . . . . .            | 20 |
| pcr_result1 . . . . .           | 21 |
| plot_seqlogo . . . . .          | 21 |
| primers . . . . .               | 22 |
| psiPlot . . . . .               | 23 |
| region_minus_exon . . . . .     | 23 |
| removeRegion . . . . .          | 24 |
| remvalue . . . . .              | 24 |
| roi . . . . .                   | 25 |
| shapiroAcceptor . . . . .       | 25 |
| shapiroDensity . . . . .        | 26 |
| shapiroDonor . . . . .          | 27 |
| splice_data . . . . .           | 28 |
| splice_fasta . . . . .          | 28 |
| splitPCRhit . . . . .           | 29 |
| thecds . . . . .                | 29 |
| theexons . . . . .              | 30 |
| valid_cds . . . . .             | 30 |
| valid_tx . . . . .              | 30 |

## Index

31

---

acceptor.m

*acceptor.m*


---

### Description

Acceptor site mammalian frequency matrices for GT-AG pairs from SpliceDB

### Usage

```
data("acceptor.m")
```

### Format

The format is: num [1:4, 1:15] 9 31.03 12.5 42.36 8.44 ... - attr(\*, "dimnames")=List of 2 ..\$ : chr [1:4] "A" "C" "G" "T" ..\$ : chr [1:15] "V1" "V2" "V3" "V4" ...

### Source

<http://www.softberry.com/spldb/SpliceDB.html>

### References

Burset M., Seledtsov I., Solovyev V. (Nucl.Acids Res.,2000,28,4364-4375; Nucl. Acids Res.,2001,29,255-259)

### Examples

```
data(acceptor.m)
```

---

addEnsemblAnnotation

*addEnsemblAnnotation*


---

### Description

Adds annotation to [extractSpliceEvents](#) object (if not present)

### Usage

```
addEnsemblAnnotation(data, species = "hsapiens")
```

### Arguments

|         |                                                                                                          |
|---------|----------------------------------------------------------------------------------------------------------|
| data    | <a href="#">extractSpliceEvents</a> object                                                               |
| species | character. biomaRt species passed to retrieve annotation. Common species include: 'hsapiens','mmusculus' |

### Value

[extractSpliceEvents](#) object with annotated genes under \$geneSymbol

**Author(s)**

Diana Low

**See Also**

[http://asia.ensembl.org/info/data/biomart/biomart\\_r\\_package.html#biomartexamples](http://asia.ensembl.org/info/data/biomart/biomart_r_package.html#biomartexamples)

**Examples**

```
data_path<-system.file("extdata",package="SPLINTER")
splice_data<-extractSpliceEvents(data=paste(data_path,"/skipped_exons.txt",sep=""))
#splice_data<-addEnsemblAnnotation(data=splice_data,species="mmusculus")
```

---

 annotateEvents

*annotateEvents*


---

**Description**

Gives detailed description of splicing event in terms of splicing outcome post translation. Currently supports exon skipping and intron retention events.

**Usage**

```
annotateEvents(
  thedata,
  db,
  bsgenome,
  outputdir,
  full_output = FALSE,
  output_prefix = "results"
)
```

**Arguments**

|               |                                                                |
|---------------|----------------------------------------------------------------|
| thedata       | list. output of extractSpliceEvents.                           |
| db            | TxDb object                                                    |
| bsgenome      | BSGenome object                                                |
| outputdir     | character. relative output directory to current location.      |
| full_output   | logical. writes out detailed text report and generate figures. |
| output_prefix | character. text prefix for full_output files.                  |

**Value**

list containing information on (1) data.frame with splicing regions (2) splice event type

**Author(s)**

Diana LOW

---

callPrimer3

*callPrimer3*


---

## Description

call primer3 for a given set of DNAstringSet object

## Usage

```
callPrimer3(
  seq,
  size_range = "150-500",
  Tm = c(57, 59, 62),
  name = "Primer1",
  primer3 = "primer3-2.3.7/bin/primer3_core",
  thermo.param = "primer3-2.3.7/src/primer3_config/",
  sequence_target = NULL,
  settings = "primer3-2.3.7/primer3web_v4_0_0_default_settings.txt"
)
```

## Arguments

|                 |                                                                                               |
|-----------------|-----------------------------------------------------------------------------------------------|
| seq             | DNAstring object, one DNA string for the given amplicon                                       |
| size_range      | default: '151-500'                                                                            |
| Tm              | melting temprature parameters default:c(55,57,58)                                             |
| name            | name of the amplicon in chr_start_end format                                                  |
| primer3         | primer3 path                                                                                  |
| thermo.param    | thermodynamic parameters folder                                                               |
| sequence_target | If one or more targets is specified then a legal primer pair must flank at least one of them. |
| settings        | text file for parameters                                                                      |

## Details

modified to include SEQUENCE\_TARGET as an option

## Value

data.frame of designed primers and parameters

## Author(s)

Altuna Akalin's modified Arnaud Krebs' original function further modified here by Diana Low

## Examples

```
### NOT RUN ###
# primer_results<-callPrimer3(seq='')
```

checkPrimer

*checkPrimer*

---

**Description**

checkPrimer

**Usage**

```
checkPrimer(pp, genome, roi = NULL)
```

**Arguments**

|        |                                                                                                                                      |
|--------|--------------------------------------------------------------------------------------------------------------------------------------|
| pp     | data.frame defining primers, or output of <a href="#">callPrimer3</a> . minimal columns = PRIMER_LEFT_SEQUENCE,PRIMER_RIGHT_SEQUENCE |
| genome | BSgenome object                                                                                                                      |
| roi    | <a href="#">makeROI</a> object                                                                                                       |

**Value**

list of GRanges with primer locations

**Author(s)**

Diana Low

**Examples**

```
# create a primer pair
roi
primer_pair <- data.frame(PRIMER_LEFT_SEQUENCE="agctcttgaaattggagctgac",
                          PRIMER_RIGHT_SEQUENCE="cttagaaagaacaggaaatcc",
                          stringsAsFactors=FALSE)
```

---

compatible\_cds*compatible\_cds*

---

**Description**

compatible\_cds

**Examples**

```
data(compatible_cds)
## maybe str(compatible_cds) ; plot(compatible_cds) ...
```

---

|               |                      |
|---------------|----------------------|
| compatible_tx | <i>compatible_tx</i> |
|---------------|----------------------|

---

### Description

compatible\_tx

### Examples

```
data(compatible_tx)
## maybe str(compatible_tx) ; plot(compatible_tx) ...
```

---

|         |                |
|---------|----------------|
| donor.m | <i>donor.m</i> |
|---------|----------------|

---

### Description

Donor site mammalian frequency matrices for GT-AG pairs from SpliceDB

### Usage

```
data("donor.m")
```

### Format

The format is: num [1:4, 1:9] 34.1 36.2 18.3 11.4 60.4 ... - attr(\*, "dimnames")=List of 2 ..\$ : chr [1:4] "A" "C" "G" "T" ..\$ : chr [1:9] "V1" "V2" "V3" "V4" ...

### Source

<http://www.softberry.com/spldb/SpliceDB.html>

### References

Burset M., Seledtsov I., Solovyev V. (Nucl.Acids Res.,2000,28,4364-4375; Nucl. Acids Res.,2001,29,255-259)

### Examples

```
data(donor.m)
```

---

eventOutcomeCompare     *eventOutcomeCompare*


---

## Description

Compares two sequences and gives differences if there's a switch from 1->2 if seq2 is NULL, assume seq1 is a list of length 2 to compare

## Usage

```
eventOutcomeCompare(
  seq1,
  seq2 = NULL,
  genome,
  direction = TRUE,
  fullseq = TRUE,
  verbose = FALSE
)
```

## Arguments

|           |                                               |
|-----------|-----------------------------------------------|
| seq1      | GRangesList                                   |
| seq2      | GRangesList                                   |
| genome    | BSGenome object                               |
| direction | logical. Report direction of sequence change. |
| fullseq   | logical. Report full sequences.               |
| verbose   | logical. turn messages on/off.                |

## Value

list containing  
 (1) tt : PairwiseAlignmentsSingleSubject pairwise alignment  
 (2) eventtypes : string detailing primary event classification

## Author(s)

Diana LOW

## Examples

```
suppressMessages(library(BSgenome.Mmusculus.UCSC.mm9))
bsgenome<-BSgenome.Mmusculus.UCSC.mm9
eventOutcomeCompare(seq1=compatible_cds$hits[[1]],seq2=region_minus_exon,
  genome=bsgenome,direction=TRUE)
```

---

`eventOutcomeTranslate` *eventOutcomeTranslate*

---

## Description

translates sequences, reports if NMD or NTC

## Usage

```
eventOutcomeTranslate(  
  seq1,  
  genome,  
  direction = FALSE,  
  fullseq = TRUE,  
  verbose = FALSE  
)
```

## Arguments

|                        |                                               |
|------------------------|-----------------------------------------------|
| <code>seq1</code>      | <code>GRangesList</code>                      |
| <code>genome</code>    | <code>BSGenome</code> object                  |
| <code>direction</code> | logical. Report direction of sequence change. |
| <code>fullseq</code>   | logical. Output full AA sequence.             |
| <code>verbose</code>   | logical. turn messages on/off.                |

## Value

list of translated sequences

## Author(s)

Diana LOW

## Examples

```
suppressMessages(library(BSgenome.Mmusculus.UCSC.mm9))  
bsgenome<-BSgenome.Mmusculus.UCSC.mm9  
translation_results<-eventOutcomeTranslate(compatible_cds,genome=bsgenome,  
  direction=TRUE)
```

eventPlot

*eventPlot***Description**

eventPlot

**Usage**

```
eventPlot(
  transcripts,
  roi_plot = NULL,
  bams = c(),
  names = c(),
  annoLabel = c("Gene A"),
  rspan = 1000,
  pfam_dom = NULL,
  showAll = TRUE
)
```

**Arguments**

|             |                                                                                                 |
|-------------|-------------------------------------------------------------------------------------------------|
| transcripts | GRanges object                                                                                  |
| roi_plot    | GRanges object region to plot                                                                   |
| bams        | character vector of bam file locations                                                          |
| names       | character vector of name labels                                                                 |
| annoLabel   | character. annotation label                                                                     |
| rspan       | integer or NULL. number of basepairs to span from roi. if NULL, will consider whole gene of roi |
| pfam_dom    | optional GRanges object of PFAM domains from UCSC Tables.                                       |
| showAll     | logical. TRUE = display splice junctions of entire view or FALSE = just roi.                    |

**Value**

a Gviz plot of genomic region

**Author(s)**

Diana Low

**Examples**

```
# define BAM files
data_path<-system.file("extdata",package="SPLINTER")
mt<-paste(data_path,"/mt_chr14.bam",sep="")
wt<-paste(data_path,"/wt_chr14.bam",sep="")

# plot results
eventPlot(transcripts=valid_tx,roi_plot=roi,bams=c(wt,mt),
  names=c('wt','mt'),rspan=1000)
```

---

|           |                  |
|-----------|------------------|
| extendROI | <i>extendROI</i> |
|-----------|------------------|

---

### Description

extend the span of the current ROI by n number of up/downstream exon(s) by modifying roi\_range within the makeROI object while retaining legacy sites by keeping \$roi and \$flank

### Usage

```
extendROI(roi, tx, up = 0, down = 0, type = 1)
```

### Arguments

|      |                                                  |
|------|--------------------------------------------------|
| roi  | <a href="#">makeROI</a> object                   |
| tx   | GRangesList transcript list to pull regions from |
| up   | integer. number of exons to extend upstream      |
| down | integer. number of exons to extend downstream    |
| type | integer. 1=full cassette, 2=flank only           |

### Value

[makeROI](#) object with modified ranges

### Examples

```
extendROI(roi,valid_tx,up=1)
```

---

|                     |                            |
|---------------------|----------------------------|
| extractSpliceEvents | <i>extractSpliceEvents</i> |
|---------------------|----------------------------|

---

### Description

Extracts the location of target, upstream and downstream splice sites Used for calculations and genome visualizations

### Usage

```
extractSpliceEvents(
  data = NULL,
  filetype = "mats",
  splicetype = "SE",
  fdr = 1,
  inclusion = 1,
  start0 = TRUE
)
```

**Arguments**

|            |                                                                      |
|------------|----------------------------------------------------------------------|
| data       | character. path to file                                              |
| filetype   | character. type of splicing output. c('mats','custom'). see Details. |
| splicetype | character. c('SE', 'RI', 'MXE', 'A5SS', 'A3SS')                      |
| fdr        | numeric. false discovery rate filter range [0,1]                     |
| inclusion  | numeric. splicing inclusion range, takes absolute value              |
| start0     | boolean 0-base start                                                 |

**Details**

filetype 'custom' should provide a 9-column tab-delimited text file with the following columns: ID (Ensembl gene id), Symbol (gene name), chr, strand, exonStart, exonEnd, exon2Start, exon2End, upstreamStart, upstreamEnd, downstreamStart, downstreamEnd eg. ENSG0000012345 chr1 + 3 4 5 6 1 2 7 8

**Value**

list containing information on  
 (1) original file type  
 (2) splice event type  
 (3) data.frame with splicing regions

**Author(s)**

Diana Low

**See Also**

[http://rnaseq-mats.sourceforge.net/user\\_guide.htm](http://rnaseq-mats.sourceforge.net/user_guide.htm) for MATS file definition

**Examples**

```
data_path<-system.file("extdata",package="SPLINTER")
splice_data<-extractSpliceEvents(data=paste(data_path,"/skipped_exons.txt",sep=""))
```

---

|                    |                           |
|--------------------|---------------------------|
| extractSpliceSites | <i>extractSpliceSites</i> |
|--------------------|---------------------------|

---

**Description**

Extracts and formats to bed the location of target, upstream and downstream splice sites

**Usage**

```
extractSpliceSites(
  df,
  target = "SE",
  site = "donor",
  motif_range = c(-3, 6),
  start0 = TRUE
)
```

**Arguments**

|             |                                              |
|-------------|----------------------------------------------|
| df          | extractSpliceEvents object                   |
| target      | the target site to extract. See Details.     |
| site        | character donor or acceptor                  |
| motif_range | numeric vector of splice position to extract |
| start0      | boolean 0-base start                         |

**Details**

target : the site to extract the sequence from. It can be either the event in question (SE, RI, MXE - first exon, MXE2 - second exon, A5SSlong, A5SSshort, A3SSlong, A3SSshort, upstream or downstream). If this function is used in conjunction with [shapiroDonor](#) or [shapiroAcceptor](#) to compute scores, then most likely it will be run twice - once for the event, and the other either up- or downstream as a comparison.

**Value**

GRanges object

**Author(s)**

Diana Low

**See Also**

[http://rnaseq-mats.sourceforge.net/user\\_guide.htm](http://rnaseq-mats.sourceforge.net/user_guide.htm) for MATS file definition

**Examples**

```
data_path<-system.file("extdata",package="SPLINTER")
splice_data<-extractSpliceEvents(data=paste(data_path, "/skipped_exons.txt", sep=""))
splice_sites<-extractSpliceSites(splice_data, target="SE")
```

---

findCompatibleEvents    *findCompatibleEvents*

---

**Description**

Which transcript contains the event? Each event has 2 possibilities, as long as the transcript fulfills one, it passes the test Has to be exact (inner junctions)

**Usage**

```
findCompatibleEvents(tx, tx2 = NULL, roi, sequential = TRUE, verbose = FALSE)
```

**Arguments**

|            |                                                                        |
|------------|------------------------------------------------------------------------|
| tx         | GRangesList object of transcripts                                      |
| tx2        | optional GRangesList object of transcripts if tx is list of cds        |
| roi        | <a href="#">makeROI</a> object containing event information            |
| sequential | logical. Exons have to appear sequentially to be considered compatible |
| verbose    | logical. printouts and messages.                                       |

**Details**

Seperates into event/region1 and 2 for the alternative case

**Value**

list of length 4  
 (1) GRangesList  
 (2) Hits status [c]=coding; [nc]=non-coding  
 (3) ct - compatible transcripts  
 (4) tt - total transcripts

**Author(s)**

Diana Low

**Examples**

```
compatible_cds <- findCompatibleEvents(valid_cds,roi=roi,verbose=TRUE)
```

---

|                    |                           |
|--------------------|---------------------------|
| findCompatibleExon | <i>findCompatibleExon</i> |
|--------------------|---------------------------|

---

**Description**

Finds compatible exon in annotation with the one present in roi object

**Usage**

```
findCompatibleExon(tx, roi, verbose = FALSE)
```

**Arguments**

|         |                                                            |
|---------|------------------------------------------------------------|
| tx      | GRangesList object of transcripts                          |
| roi     | <a href="#">makeROI</a> object containng event information |
| verbose | logical. printouts and messages.                           |

**Value**

list of length 3  
 (1) GRangesList hits  
 (2) Number of transcripts  
 (3) Original number of input transcripts

**Author(s)**

Diana Low

**Examples**

```
compatible_exons <- findCompatibleExon(valid_cds,roi)
```

---

|                   |                          |
|-------------------|--------------------------|
| findExactOverlaps | <i>findExactOverlaps</i> |
|-------------------|--------------------------|

---

**Description**

Internal function similar to findSpliceOverlaps but only preserves internal flanks

**Usage**

```
findExactOverlaps(query, subject, sequential = FALSE, verbose = FALSE)
```

**Arguments**

|            |                                        |
|------------|----------------------------------------|
| query      | GRanges object                         |
| subject    | GRanges object                         |
| sequential | logical. TRUE if exons are sequential. |
| verbose    | logical. report intermediate output    |

**Value**

Hits object

**Author(s)**

Diana Low

---

|                 |                        |
|-----------------|------------------------|
| findTermination | <i>findTermination</i> |
|-----------------|------------------------|

---

**Description**

Internal function to find the first stop codon that occurs in the AA sequence, returns their position and the resulting truncated protein

**Usage**

```
findTermination(s1)
```

**Arguments**

|    |                             |
|----|-----------------------------|
| s1 | character. protein sequence |
|----|-----------------------------|

**Value**

list containing  
(1) stop1 : stop position  
(2) s1 : sequence truncated to first stop

**Author(s)**

Diana LOW

---

|        |               |
|--------|---------------|
| findTX | <i>findTX</i> |
|--------|---------------|

---

**Description**

Given an ENSEMBL id, find all transcripts that matches id

**Usage**

```
findTX(id, db, tx, valid = FALSE, verbose = FALSE)
```

**Arguments**

|         |                                                                     |
|---------|---------------------------------------------------------------------|
| id      | character. transcript identification (currently ENSEMBL gene names) |
| db      | TxDb object                                                         |
| tx      | GRangesList                                                         |
| valid   | logical. check if in multiples of 3 [TRUE] for CDS translation.     |
| verbose | logical. turn messages on/off.                                      |

**Value**

GRangesList

**Author(s)**

Diana Low

**Examples**

```
valid_cds <-findTX(id=splice_data$data[2,]$ID,tx=thecds,db=txdb,valid=FALSE)
```

---

|             |                    |
|-------------|--------------------|
| getPCRsizes | <i>getPCRsizes</i> |
|-------------|--------------------|

---

**Description**

returns length of product given a GRanges span and GRangesList of transcripts

**Usage**

```
getPCRsizes(pcr_span, txlist, verbose = FALSE)
```

**Arguments**

|          |                                      |
|----------|--------------------------------------|
| pcr_span | GRanges object                       |
| txlist   | GRangesList object                   |
| verbose  | logical. report intermediate output. |

**Value**

data.frame of transcript names with detected sizes in basepairs

**Author(s)**

Diana Low

**Examples**

```
suppressMessages(library(BSgenome.Mmusculus.UCSC.mm9))
bsgenome<-BSgenome.Mmusculus.UCSC.mm9
## create a primer pair
## for actual use, obtain primer pair from primer design (callPrimer3)
primer_pair <- data.frame(PRIMER_LEFT_SEQUENCE="agctcttgaaattggagctgac",
                          PRIMER_RIGHT_SEQUENCE="cttagaaagaacaggaaatcc",
                          stringsAsFactors=FALSE)

## confirm location
cp<-checkPrimer(primer_pair,bsgenome,roi)
cp

## get the PCR sizes
pcr_result1 <- getPCRsizes(cp,theexons)
```

---

getRegionDNA

*getRegionDNA*


---

**Description**

get DNA sequence give a region of interest

**Usage**

```
getRegionDNA(roi, genome, introns = FALSE)
```

**Arguments**

|         |                                                                                                          |
|---------|----------------------------------------------------------------------------------------------------------|
| roi     | <a href="#">makeROI</a> object                                                                           |
| genome  | BSgenome object                                                                                          |
| introns | TRUE/FALSE. whether to include intronic (lowercase) DNA. By default returns only exonic (uppercase) DNA. |

**Value**

list of  
(1) DNA sequence (2) Junction start (for primer design)

**Author(s)**

Diana Low

**Examples**

```
suppressMessages(library(BSgenome.Mmusculus.UCSC.mm9))
bsgenome<-BSgenome.Mmusculus.UCSC.mm9
getRegionDNA(roi,bsgenome)
```

---

insertRegion

*insertRegion*


---

**Description**

inserts a region (exon or intron) into roi object

**Usage**

```
insertRegion(subject, roi)
```

**Arguments**

subject            GrangesList

roi                [makeROI](#) object containg region of interest (to insert). refer to makeROI().

**Details**

in the case of intron retention, replaces exon with intron retention range `reduce()` the GRanges in question

**Value**

GRanges object

**Author(s)**

Diana Low

**Examples**

```
#Inserts the exon defined in roi GRanges object from a GRanges/GRangesList
region_minus_exon
region_with_exon<-insertRegion(region_minus_exon,roi)
```

---

|         |                |
|---------|----------------|
| makeROI | <i>makeROI</i> |
|---------|----------------|

---

**Description**

Creates an object to store information about the splice site (region of interest) including flanking regions and alternative splice outcome

**Usage**

```
makeROI(df, type = "SE")
```

**Arguments**

|      |                                                             |
|------|-------------------------------------------------------------|
| df   | data.frame object from <a href="#">extractSpliceEvents</a>  |
| type | type of splicing event c("SE", "RI", "MXE", "A5SS", "A3SS") |

**Value**

a list containing

- (1) type : splice type
- (2) name : ID of transcript
- (3) roi : GRanges object of splice site
- (4) flank : GRanges object of flanking exons of splice site
- (5) roi\_range : GRangesList of splice site and it's alternative outcome based on type

**Author(s)**

Diana Low

**Examples**

```
single_record<-splice_data$data[which(grepl("Prmt5", splice_data$data$Symbol)),]  
roi <- makeROI(single_record, type="SE")
```

---

|               |                      |
|---------------|----------------------|
| makeUniqueIDs | <i>makeUniqueIDs</i> |
|---------------|----------------------|

---

**Description**

Makes unique ID names from event location

**Usage**

```
makeUniqueIDs(ddata)
```

**Arguments**

|       |                            |
|-------|----------------------------|
| ddata | extractSpliceEvents object |
|-------|----------------------------|

**Value**

original extractSpliceEvents list object with unique ID appended to data accessor

**Author(s)**

Diana Low

**Examples**

```
data_with_id<-makeUniqueIDs(splice_data)
```

---

|            |                   |
|------------|-------------------|
| matchExons | <i>matchExons</i> |
|------------|-------------------|

---

**Description**

Internal function to help match the inner coordinates of a 2/3 cassette checks if reference and subject matches

**Usage**

```
matchExons(ref, subject)
```

**Arguments**

|         |                |
|---------|----------------|
| ref     | GRanges object |
| subject | GRanges object |

**Value**

logical. check if exons match (TRUE) or not (FALSE)

**Author(s)**

Diana Low

---

|            |                   |
|------------|-------------------|
| metaremove | <i>metaremove</i> |
|------------|-------------------|

---

**Description**

helper function to remove metadata from GRanges object

**Usage**

```
metaremove(x)
```

**Arguments**

|   |                        |
|---|------------------------|
| x | GRanges or GRangesList |
|---|------------------------|

## Value

GRanges or GRangesList

---

|             |                    |
|-------------|--------------------|
| pcr_result1 | <i>pcr_result1</i> |
|-------------|--------------------|

---

## Description

pcr\_result1

## Examples

```
data(pcr_result1)
```

---

|              |                               |
|--------------|-------------------------------|
| plot_seqlogo | <i>plotting sequence logo</i> |
|--------------|-------------------------------|

---

## Description

Plots the sequence logo of a given set of FASTA sequences

## Usage

```
plot_seqlogo(fasta_seq)
```

## Arguments

fasta\_seq      DNASTringSet or path to fasta-formatted file

## Value

sequence logo image

## Author(s)

Diana Low

## Examples

```
head(splice_fasta)
plot_seqlogo(Biostrings::DNASTringSet(splice_fasta$V2))
```

---

primers

*primers*


---

### Description

primers designed using Primer3 for sample data

### Usage

```
data("primers")
```

### Format

A data frame with 5 observations on the following 28 variables.

`i` a numeric vector

`PRIMER_LEFT_SEQUENCE` a character vector

`PRIMER_RIGHT_SEQUENCE` a character vector

`PRIMER_LEFT_TM` a numeric vector

`PRIMER_RIGHT_TM` a numeric vector

`PRIMER_LEFT_pos` a numeric vector

`PRIMER_LEFT_len` a numeric vector

`PRIMER_RIGHT_pos` a numeric vector

`PRIMER_RIGHT_len` a numeric vector

`PRIMER_PAIR_PENALTY` a numeric vector

`PRIMER_LEFT_PENALTY` a numeric vector

`PRIMER_RIGHT_PENALTY` a numeric vector

`PRIMER_LEFT_GC_PERCENT` a numeric vector

`PRIMER_RIGHT_GC_PERCENT` a numeric vector

`PRIMER_LEFT_SELF_ANY_TH` a numeric vector

`PRIMER_RIGHT_SELF_ANY_TH` a numeric vector

`PRIMER_LEFT_SELF_END_TH` a numeric vector

`PRIMER_RIGHT_SELF_END_TH` a numeric vector

`PRIMER_LEFT_HAIRPIN_TH` a numeric vector

`PRIMER_RIGHT_HAIRPIN_TH` a numeric vector

`PRIMER_LEFT_END_STABILITY` a numeric vector

`PRIMER_RIGHT_END_STABILITY` a numeric vector

`PRIMER_LEFT_TEMPLATE_MISPRIMING` a numeric vector

`PRIMER_RIGHT_TEMPLATE_MISPRIMING` a numeric vector

`PRIMER_PAIR_COMPL_ANY_TH` a numeric vector

`PRIMER_PAIR_COMPL_END_TH` a numeric vector

`PRIMER_PAIR_PRODUCT_SIZE` a numeric vector

`PRIMER_PAIR_TEMPLATE_MISPRIMING` a numeric vector

**Value**

Dataframe of primer design results

**Examples**

```
data(primers)
```

---

|         |                |
|---------|----------------|
| psiPlot | <i>psiPlot</i> |
|---------|----------------|

---

**Description**

Plots percentage spliced in (PSI) values in terms of inclusion levels

**Usage**

```
psiPlot(df = NULL, type = "MATS", sample_labels = c("Sample 1", "Sample 2"))
```

**Arguments**

|               |                                                                                                             |
|---------------|-------------------------------------------------------------------------------------------------------------|
| df            | data.frame containing PSI values                                                                            |
| type          | character. either 'MATS' output (will read in MATS headers) or 'generic' (provide 4 or 6 column data.frame) |
| sample_labels | x-axis labels for the plot                                                                                  |

**Value**

bar plot of PSI values

**Author(s)**

Diana Low

**Examples**

```
#we give inclusion and skipped numbers as reads
#this will be converted into percentages
df<-data.frame(inclusion1=c("6,4,6"),skipped1=c("10,12,12"),inclusion2=c("15,15,15"),
               skipped2=c("3,3,4"),stringsAsFactors = FALSE)
psiPlot(df,type='generic')
```

---

|                   |                          |
|-------------------|--------------------------|
| region_minus_exon | <i>region_minus_exon</i> |
|-------------------|--------------------------|

---

**Description**

region\_minus\_exon

**Examples**

```
data(region_minus_exon)
## maybe str(region_minus_exon) ; plot(region_minus_exon) ...
```

---

|              |                     |
|--------------|---------------------|
| removeRegion | <i>removeRegion</i> |
|--------------|---------------------|

---

**Description**

removes a region (exon) from a GRanges or GRangesList

**Usage**

```
removeRegion(subject, roi)
```

**Arguments**

|         |                                                                     |
|---------|---------------------------------------------------------------------|
| subject | GRanges or GrangesList object                                       |
| roi     | <a href="#">makeROI</a> object containing GRanges range (to remove) |

**Value**

GRanges object

**Author(s)**

Diana Low

```
# Removes the exon defined in roi GRanges object from a GRanges/GRangesList compatible_cds$hits[[1]]
region_minus_exon<-removeRegion(compatible_cds$hits[[1]],roi)
```

---

|          |                 |
|----------|-----------------|
| remvalue | <i>remvalue</i> |
|----------|-----------------|

---

**Description**

helper function to remove metadata from GRanges object used within metaremove

**Usage**

```
remvalue(x)
```

**Arguments**

|   |                        |
|---|------------------------|
| x | GRanges or GRangesList |
|---|------------------------|

**Value**

GRanges or GRangesList

---

|     |            |
|-----|------------|
| roi | <i>roi</i> |
|-----|------------|

---

**Description**

roi

**Usage**

```
data("roi")
```

**Value**

List containing region of interest information

**Examples**

```
data(roi)
```

---

|                 |                        |
|-----------------|------------------------|
| shapiroAcceptor | <i>shapiroAcceptor</i> |
|-----------------|------------------------|

---

**Description**

Shapiro's score of acceptor site (range is from -13 [intron] to +1 [exon]) is:  $100 * ((t1 - l1)/(h1 - l1) + (t2 - l2)/(h2 - l2))/2$ , where t1 is the sum of the best 8 of 10 percentages at positions -13 to -4, l1 is the sum of the lowest 8 of 10 percentages at position -13 to -4, h1 is the sum of the highest 8 of 10 percentages at positions -13 to -4, t2 is the sum of percentages at positions -3 to +1, l2 is the sum of the lowest percentages at positions -3 to +1, and h2 is the sum of the highest percentages at positions -3 to +1

**Usage**

```
shapiroAcceptor(reference_fasta, target_fasta)
```

**Arguments**

|                 |                                                            |
|-----------------|------------------------------------------------------------|
| reference_fasta |                                                            |
|                 | vector of strings or DNASTringSet of reference splice list |
| target_fasta    | vector of strings or DNASTringSet of fasta to score        |

**Value**

data.frame with Shapiro scores

**Author(s)**

Diana Low

**See Also**

<http://www.softberry.com/spldb/SpliceDB.html>

**Examples**

```
library(BSgenome.Mmusculus.UCSC.mm9)
bsgenome <- BSgenome.Mmusculus.UCSC.mm9
data_path<-system.file("extdata",package="SPLINTER")
splice_data<-extractSpliceEvents(data=paste(data_path,"/skipped_exons.txt",sep=""))
splice_sites<-extractSpliceSites(splice_data,site="acceptor")
acceptor.ss<-getSeq(bsgenome,splice_sites)
##sacceptor<-shapiroAcceptor(acceptor.m,acceptor.ss)
```

---

shapiroDensity

*shapiroDensity*

---

**Description**

convenience function for plotting Shapiro score density

**Usage**

```
shapiroDensity(ctrl_scores, treat_scores, sample = c(1, 2))
```

**Arguments**

|              |                                           |
|--------------|-------------------------------------------|
| ctrl_scores  | output of shapiroDonor or shapiroAcceptor |
| treat_scores | output of shapiroDonor or shapiroAcceptor |
| sample       | samplenames                               |

**Value**

density plot of Shapiro scores

**Author(s)**

Diana Low

---

`shapiroDonor`*shapiroDonor*

---

## Description

Shapiro and Senapathy (1987) have developed a method to score the strength of a splice site based on percentages of each nucleotide at each position. Shapiro's score of donor site (range is from -3 [exon] to +7 [intron]) is :  $100 * (t - \min) / (\max - \min)$ , where t is the sum of percentages at positions -3 to +7, min is the sum of the lowest percentages at positions -3 to +7, and max is the sum of the highest percentages at positions -3 to +7.

## Usage

```
shapiroDonor(reference_fasta, target_fasta)
```

## Arguments

`reference_fasta`      vector of strings or DNAStringSet of reference splice list

`target_fasta`      vector of strings or DNAStringSet of fasta to score

## Value

data.frame with Shapiro scores

## Author(s)

Diana Low

## See Also

<http://www.softberry.com/spldb/SpliceDB.html>

## Examples

```
library(BSgenome.Mmusculus.UCSC.mm9)
bsgenome <- BSgenome.Mmusculus.UCSC.mm9
data_path<-system.file("extdata",package="SPLINTER")
splice_data<-extractSpliceEvents(data=paste(data_path,"/skipped_exons.txt",sep=""))
splice_sites<-extractSpliceSites(splice_data)
donor.ss<-getSeq(bsgenome,splice_sites)
##sdonor<-shapiroDonor(donor.m,donor.ss)
```

---

|             |                    |
|-------------|--------------------|
| splice_data | <i>splice_data</i> |
|-------------|--------------------|

---

**Description**

splice\_data

**Usage**

```
data("splice_data")
```

**Value**

List containing splice event file information

**Examples**

```
data(splice_data)
```

---

|              |                     |
|--------------|---------------------|
| splice_fasta | <i>splice_fasta</i> |
|--------------|---------------------|

---

**Description**

splice\_fasta

**Usage**

```
data("splice_fasta")
```

**Format**

A data frame with 0 observations on the following 2 variables.

V1 a numeric vector

V2 a numeric vector

**Value**

Dataframe of region and fasta sequence

**Examples**

```
data(splice_fasta)
```

---

`splitPCRhit`*splitPCRhit*

---

**Description**

splits the PCR alignment into the two AS conditions

**Usage**

```
splitPCRhit(res, hitlist)
```

**Arguments**

|         |                                             |
|---------|---------------------------------------------|
| res     | result from <a href="#">getPCRsizes</a>     |
| hitlist | <a href="#">findCompatibleEvents</a> object |

**Value**

list of 2 data.frame objects with isoform name (ID) and length of PCR product (bp) matching Type 1 or Type 2 transcripts

**Author(s)**

Diana Low

**Examples**

```
## as getPCRsizes gives you all PCR bands when the primers are used,  
## splitPCRhit will determine which bands are relevant to the target  
relevant_pcr_bands<-splitPCRhit(pcr_result1,compatible_tx)
```

---

`thecds`*thecds*

---

**Description**

thecds

**Usage**

```
data("thecds")
```

**Value**

List containing GRanges info

**Examples**

```
data(thecds)
```

---

|          |                 |
|----------|-----------------|
| theexons | <i>theexons</i> |
|----------|-----------------|

---

**Description**

theexons

**Usage**

```
data("theexons")
```

**Value**

List containing GRanges info

**Examples**

```
data(theexons)
```

---

|           |                  |
|-----------|------------------|
| valid_cds | <i>valid_cds</i> |
|-----------|------------------|

---

**Description**

valid\_cds

**Usage**

```
data("valid_cds")
```

**Value**

GRangesList

**Examples**

```
data(valid_cds)
```

---

|          |                 |
|----------|-----------------|
| valid_tx | <i>valid_tx</i> |
|----------|-----------------|

---

**Description**

valid\_tx

**Value**

GRangesList

**Examples**

```
data(valid_tx)
## maybe str(valid_tx) ; plot(valid_tx) ...
```

# Index

## \* datasets

- acceptor.m, 3
- compatible\_cds, 6
- compatible\_tx, 7
- donor.m, 7
- pcr\_result1, 21
- primers, 22
- region\_minus\_exon, 23
- roi, 25
- splice\_data, 28
- splice\_fasta, 28
- thecds, 29
- theexons, 30
- valid\_cds, 30
- valid\_tx, 30

## \* internal

- findExactOverlaps, 15
- findTermination, 15
- matchExons, 20
- metaremove, 20
- remvalue, 24

- acceptor.m, 3
- addEnsemblAnnotation, 3
- annotateEvents, 4

- callPrimer3, 5, 6
- checkPrimer, 6
- compatible\_cds, 6
- compatible\_tx, 7

- donor.m, 7

- eventOutcomeCompare, 8
- eventOutcomeTranslate, 9
- eventPlot, 10
- extendROI, 11
- extractSpliceEvents, 3, 11, 19
- extractSpliceSites, 12

- findCompatibleEvents, 13, 29
- findCompatibleExon, 14
- findExactOverlaps, 15
- findTermination, 15
- findTX, 16

- getPCRsizes, 16, 29
- getRegionDNA, 17

- insertRegion, 18

- makeROI, 6, 11, 13, 14, 17, 18, 19, 24
- makeUniqueIDs, 19
- matchExons, 20
- metaremove, 20

- pcr\_result1, 21
- plot\_seqlogo, 21
- primers, 22
- psiPlot, 23

- region\_minus\_exon, 23
- removeRegion, 24
- remvalue, 24
- roi, 25

- shapiroAcceptor, 13, 25
- shapiroDensity, 26
- shapiroDonor, 13, 27
- splice\_data, 28
- splice\_fasta, 28
- splitPCRhit, 29

- thecds, 29
- theexons, 30

- valid\_cds, 30
- valid\_tx, 30