

Package ‘geva’

July 13, 2025

Type Package

Title Gene Expression Variation Analysis (GEVA)

Description Statistic methods to evaluate variations of differential expression (DE) between multiple biological conditions.

It takes into account the fold-changes and p-values from previous differential expression (DE) results that use large-scale data (*e.g.*, microarray and RNA-seq) and evaluates which genes would react in response to the distinct experiments.

This evaluation involves an unique pipeline of statistical methods, including weighted summarization,

quantile detection, cluster analysis, and ANOVA tests, in order to classify a subset of relevant genes

whose DE is similar or dependent to certain biological factors.

Version 1.16.0

URL <https://github.com/sbcbclab/geva>

BiocType Software

biocViews Classification, DifferentialExpression, GeneExpression, Microarray, MultipleComparison, RNASeq, SystemsBiology, Transcriptomics

License LGPL-3

Encoding UTF-8

Depends R (>= 4.1)

Imports grDevices, graphics, methods, stats, utils, dbscan, fastcluster, matrixStats

Suggests devtools, knitr, rmarkdown, roxygen2, limma, topGO, testthat (>= 3.0.0)

Roxygen list(markdown = TRUE)

RoxygenNote 7.1.1

VignetteBuilder knitr

Collate 'stringhelpers.R' 'callhelpers.R' 'vectorhelpers.R' 'printheelpers.R' 'asserts.R' 'usecasechecks.R' 'plotting.R' 'docheelpers.R' 'generics.R' 'classhelpers.R' 'c_SVTable.R'

```
'c_GEVAGroupSet.R' 'c_GEVACluster.R' 'funhelpers.R' 'linq.R'
'c_TypedList.R' 'c_SVAttribute.R' 'c_GEVAInput.R'
'c_GEVASummary.R' 'c_GEVAGroupedSummary.R' 'c_GEVAQuantiles.R'
'c_GEVAQuantilesAdjusted.R' 'c_GEVAResults.R' 'summarization.R'
'clusteringbase.R' 'matrixhelpers.R' 'statmath.R'
'dclustering.R' 'quantiles.R' 'factoring.R' 'scoremerge.R'
'finalize.R' 'geva-package.R' 'hclustering.R' 'idealtesting.R'
'input.R'
```

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/geva>

git_branch RELEASE_3_21

git_last_commit e0d0aef

git_last_commit_date 2025-04-15

Repository Bioconductor 3.21

Date/Publication 2025-07-13

Author Itamar José Guimarães Nunes [aut, cre] (ORCID:

<<https://orcid.org/0000-0002-6246-4658>>),

Murilo Zanini David [ctb],

Bruno César Feltes [ctb] (ORCID:

<<https://orcid.org/0000-0002-2825-8295>>),

Marcio Dorn [ctb] (ORCID: <<https://orcid.org/0000-0001-8534-3480>>)

Maintainer Itamar José Guimarães Nunes <nunesijg@gmail.com>

Contents

geva-package	3
generics	4
geva.cluster	6
geva.dcluster	8
geva.finalize	10
geva.hcluster	12
geva.ideal.example	14
geva.input.correct	15
geva.merge.input	17
geva.quantiles	21
geva.quick	23
geva.summarize	24
GEVACluster-class	26
GEVAGroupedSummary-class	27
GEVAGroupSet-class	28
GEVAInput-class	30
GEVAQuantiles-class	31
GEVAQuantilesAdjusted-class	33
GEVAResults-class	34
GEVASummary-class	35

<i>geva-package</i>	3
SVAttribute-class	37
SVTable-class	38
top.genes	40
TypedList-class	41
Index	43

<i>geva-package</i>	<i>geva: Gene Expression Variation Analysis (GEVA)</i>
---------------------	--

Description

Statistic methods to evaluate variations of differential expression (DE) between multiple biological conditions. It takes into account the fold-changes and p-values from previous differential expression (DE) results that use large-scale data (*e.g.*, microarray and RNA-seq) and evaluates which genes would react in response to the distinct experiments. This evaluation involves an unique pipeline of statistical methods, including weighted summarization, quantile detection, cluster analysis, and ANOVA tests, in order to classify a subset of relevant genes whose DE is similar or dependent to certain biological factors.

Statistic methods to evaluate variation between multiple biological conditions.

Author(s)

Maintainer: Itamar José Guimarães Nunes <nunesijg@gmail.com> ([ORCID](#))

Other contributors:

- Murilo Zanini David <zanini.murilo@gmail.com> [contributor]
- Bruno César Feltes <bcfeltes@gmail.com> ([ORCID](#)) [contributor]
- Marcio Dorn <mdorn@inf.ufrgs.br> ([ORCID](#)) [contributor]

See Also

Useful links:

- <https://github.com/sbcbclab/geva>

generics

GEVA Generic Methods

Description

Exhaustive list of generic methods exported from GEVA. Use `findMethods` to retrieve the specific usages.

Usage

```
inputvalues(object)

inputweights(object, normalized)

inputdata(object)

inputnames(object)

infolist(object, field, ...)

infolist(object) <- value

factors(object)

factors(object) <- value

classification.table(object)

classification.table(object) <- value

analysis.params(gobject)

featureTable(object)

featureTable(object) <- value

sv(object)

svattr(S, V)

elem.class(typedlist)

elem.class(typedlist) <- value

groupsets(object)

groupsets(object) <- value
```

```

groups(object)

scores(object, group)

centroids(object)

offsets(object)

sv.scores(object)

qindexes(object)

qareasizes(object)

qcount(object)

quantiles(object)

quantiles.method(object)

group.rels(object)

cluster.method(object)

results.table(gres)

sv.data(object)

variation(object, ...)

get.summary.method(x)

get.variation.method(x)

get.distance.method(x)

as.SVTable(x, ...)

```

Arguments

<code>object, x, gobject</code>	Primary object. See the documentation from each class for specific usages
<code>normalized</code>	<code>logical</code> , whether to return values in the normalized scale
<code>field</code>	When used with a information list, returns the information entry with the corresponding name
<code>...</code>	Additional parameters. If used with an imported S3 method, passes the arguments to the default vector, matrix or data.frame implementation

value	The value to be assigned
S	Vector to construct the S slot
V	Vector to construct the V slot
typedlist	A TypedList object
group	Character to filter the returned groups. Omit it to return all groups
gres	A GEVResults objec

Value

See the specific usages for each method.

Examples

```
# Returing analysis parameters from an object
gsummary <- geva.summarize(geva.ideal.example(),
                          summary.method="mean",
                          variation.method="sd")

anpars <- analysis.params(gsummary)
print(anpars)
# $summary.method
# [1] "mean"
# $variation.method
# [1] "sd"
```

geva.cluster

GEVA Cluster Analysis

Description

Performs a cluster analysis from summarized data.

Usage

```
geva.cluster(
  sv,
  cluster.method = options.cluster.method,
  cl.score.method = options.cl.score.method,
  resolution = 0.3,
  distance.method = options.distance,
  ...,
  grouped.return = FALSE
)

options.cluster.method
# c("hierarchical", "density", "quantiles")
```

```
options.cl.score.method
# c("auto", "hclust.height", "density", "centroid")
```

```
options.distance
# c("euclidean", "manhattan")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
cluster.method	character, one of the main grouping methods (see ‘Details’)
cl.score.method	character, method used to calculate the cluster scores for each point. Ignored if cluster.method is quantiles
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can be detected by the cluster.method, while 1 returns the maximum amount of clusters. Ignored if cluster.method is quantiles
distance.method	character, two-point distance calculation method. Options are "euclidean" or "manhattan" distances
...	further arguments passed to geva.dcluster() , geva.hcluster() , or geva.quantiles() . In addition, the following arguments are accepted: • eps : numeric, defines the <i>epsilon</i> coefficient for density clustering (see ‘Details’) • mink.p : numeric, parameter for the Minkowsky metric used in hierarchical clustering. Used as the p argument for fastcluster::hclust.vector() • verbose : logical, whether to print the current progress (default is TRUE)
grouped.return	logical, whether to concatenate the clustered and summarized data into a single object

Details

The `cluster.method` determines which grouping subroutine is used to classify the summarized data points based on distance and partitioning. Each option has their equivalent functions that can be called directly: "density" uses [geva.dcluster\(\)](#); "hierarchical" uses [geva.hcluster\(\)](#); and "quantiles" calls [geva.quantiles\(\)](#). However, this wrapper function can also be used to join [GEVASummary](#) and [GEVAGroupSet](#) objects into a single [GEVAGroupedSummary](#) object by setting `grouped.return` to TRUE.

The `cl.score.method` argument defines how scores are calculated for each SV point (row in `sv`) that was assigned to a cluster, (*i.e.*, excluding non-clustered points). If specified as "auto", the parameter will be selected based on the `cluster.method`: "density" (rate of neighbor points) for the density method; and "hclust.height" (local hierarchy height) for the hierarchical method. The "centroid" method calculates the scores based on the proportional distance between each point to its cluster's centroid. Note that the `cl.score.method` argument is ignored if `cluster.method` is "quantiles", since quantile scores are always based on their local centroid distances.

The `resolution` value is a more accessible way to define the cluster separation threshold used in density and hierarchical clustering methods. Density clusters uses an *epsilon* value that represents

the minimum distance of separation, whereas hierarchical clusters are defined by cutting the hierarchy tree wherever there is a minimum distance between two hierarchies. In this sense, resolution translates a value between 0 and 1 to proportional value for *epsilon* or hierarchical height (depending on the `cluster.method`) that would result in the least number of possible clusters for 0 and the highest number for 1. Nevertheless, if *epsilon* is specified as `eps` in the optional arguments, its value is used and resolution is ignored.

Value

This function produces a [GEVAGroupSet](#)-derived object, particularly a [GEVACluster](#) for the "hierarchical" and "density" cluster methods or a [GEVAQuantiles](#) for the "quantiles" method.

However, if `grouped.return` is TRUE and `sv` is a [GEVASummary](#) object, the produced [GEVAGroupSet](#) data will be concatenated to the input and returned as a [GEVAGroupedSummary](#)

See Also

Other `geva.cluster`: [geva.dcluster\(\)](#), [geva.hcluster\(\)](#), [geva.quantiles\(\)](#)

Examples

```
## Cluster analysis from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Hierarchical clustering
gclust <- geva.cluster(gsummary, cluster.method="hierarchical")
plot(gclust)

# Density clustering
gclust <- geva.cluster(gsummary, cluster.method="density")
plot(gclust)

# Density clustering with slightly more resolution
gclust <- geva.cluster(gsummary,
                      cluster.method="density",
                      resolution=0.35)

plot(gclust)
```

geva.dcluster

GEVA Density Clustering

Description

Performs a density cluster analysis from summarized data.

Usage

```
geva.dcluster(
  sv,
  resolution = 0.3,
  dcluster.method = options.dcluster.method,
  cl.score.method = options.cl.score.method,
  minpts = 2,
  ...,
  eps = NA_real_,
  include.raw.results = FALSE
)

options.dcluster.method
# c("dbscan", "optics")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can be detected, while 1 returns the maximum amount of detectable clusters. Ignored if eps is specified
dcluster.method	character, density-based method for cluster separation
cl.score.method	character, method used to calculate the cluster scores for each point. If "auto", the "density" method is selected
minpts	integer, minimum number of points required to form a cluster
...	additional arguments. Accepts verbose (logical, default is TRUE) to enable or disable printing the current progress
eps	numeric, maximum neighborhood distance between points to be clustered
include.raw.results	logical, whether to attach intermediate results to the returned object

Details

This function performs a density cluster analysis with the aid of implemented methods from the [dbscan::dbscan](#) package. The available methods for the `dcluster.method` arguments are "dbscan" and "options", which internally call [dbscan::dbscan\(\)](#) and [dbscan::optics\(\)](#), respectively.

The resolution value is an accessible way to define the cluster separation threshold used in density clustering. The *DBSCAN* algorithm uses an *epsilon* value that represents the minimum distance of separation, and resolution translates a value between 0 and 1 to a proportional value within the acceptable range of *epsilon* values. This allows defining the rate of clusters from 0 to 1, which results in the least number of possible clusters for 0 and the highest number for 1. Nevertheless, if *epsilon* is specified as `eps` in the optional arguments, its value is used and resolution is ignored.

The `cl.score.method` argument defines how scores are calculated for each SV point (row in `sv`) that was assigned to a cluster, (*i.e.*, excluding non-clustered points). If specified as "auto", the parameter will be selected based on the rate of neighbor points ("density").

If `include.raw.results` is `TRUE`, some additional data will be attached to the `info` slot of the returned `GEVACluster` objects, including the *kNN* tree generated during the intermediate steps.

Value

A `GEVACluster` object

Note

In density clustering, only the most dense points are clustered. For the unclustered points, the grouping value is set to `NA`.

See Also

Other `geva.cluster`: `geva.cluster()`, `geva.hcluster()`, `geva.quantiles()`

Examples

```
## Density clustering from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Density clustering
gclust <- geva.dcluster(gsummary)
plot(gclust)

# Density clustering with slightly more resolution
gclust <- geva.dcluster(gsummary, resolution=0.35)
plot(gclust)
```

`geva.finalize`

Concatenating GEVA calculations into the final results

Description

Merges the obtained information (Summarization, Clustering, and Quantiles), then applies the final steps to produce the classification results for the SV points (genes).

Usage

```
geva.finalize(
  gsummary,
  ...,
  p.value = 0.05,
  p.val.adjust = options.factorizing.p.adjust,
  constraint.factors = TRUE
```

```
)

options.factoring.p.adjust
# c("partial.quantiles", "holm", "hochberg", "hommel",
#   "bonferroni", "BH", "BY", "fdr", "none")
```

Arguments

<code>gsummary</code>	a GEVASummary object
<code>...</code>	Intermediate results produced from the <code>gsummary</code> object, such as clusters (GEVACluster), quantiles (GEVAQuantiles), or any other object inherited from GEVAGroupSet
<code>p.value</code>	numeric (0 to 1), p-value cutoff used in the ANOVA procedures (factor analysis only)
<code>p.val.adjust</code>	character, p-value correction method (factor analysis only). Possible values are: "partial.quantiles", "holm", "hochberg", "hommel", "bonferroni", "BH", "BY", "fdr", "none"
<code>constraint.factors</code>	logical. If TRUE, the S values are restricted to the range within the quantile centroids (factor analysis only)

Details

In this procedure, the SV points (*i.e.*, each row in the `GEVASummary` object) are classified according to the detected quantiles (see [geva.quantiles](#)), whose results can be adjusted using other grouping analysis results such as clusters (see [geva.cluster](#)). To achieve the best statistical accuracy, both `GEVAQuantiles` and `GEVACluster` objects must be given in the `...` as optional arguments. If a `GEVAQuantiles` argument is not present, it is automatically calculated using the default parameters.

If multiple factors are present in the `GEVASummary` object (retrieved by `factors(gsummary)`), a factor analysis is also performed, giving two additional possible classifications (*factor-dependent* and *factor-specific*) besides the default ones (*similar*, *basal*, and *sparse*).

In factor analysis, an ANOVA is applied for each gene using Fisher's and Levene's tests to distinguish genes whose *logFC* (differential expression) variation is dependent or specific to the analyzed factors based on the p-value cutoff. The `p.val.adjust` argument defines how these p-values will be adjusted: by quantile separation between each factor ("partial.quantiles" method); or by one of the default methods listed in [stats::p.adjust.methods](#).

The `constraint.factors` argument determines if the S values (summarized *logFC*) will be limited to the range between the quantile centroids during factor analysis. For example, if the quantile centroids were -0.90, 0.00, and 0.90 in the S axis, values such as -1.53 and 2.96 would be converted to -0.90 and 0.90, respectively. This constraint is particularly applied to avoid significant observations from ANOVA based on multiple degrees of differential expression.

In another example to illustrate the constraint of factors, given two sets of values: `A = (-1.00, -1.10, 0.00, 0.20, 1.00, 1.15)`, and `B = (0.00, 0.12, 1.11, 1.00, 1.95, 2.00)`, with the centroids located in `C = (-0.90, 0.00, 0.90)`, and the factors `F = (Cond1, Cond1, Cond2, Cond2, Cond3, Cond3)`. If `constraint.factors` is FALSE, both A and B are considered as significantly separated factors, whereas if TRUE, only A will present a significant separation, since in B the values 1.11, 1.00, 1.95, and 2.00 are converted to 0.90. In qualitative terms, if `constraint.factors` is TRUE, all values above 0.90 are considered the same over-expressed values, ensuring that they will fit in the same

degree of differential expression. Hence, in this example using the constrained values, B would not represent a significant separation between the factors Cond1, Cond2, and Cond3.

Value

A `GEVResults` object, containing the entire set of results. The relevant genes can be retrieved using `top.genes()`

Note

To perform factor analysis, the following observations must be considered:

- The factors must be defined in the provided data. They can be retrieved using the `factors` accessor. If factors are not present or are entirely composed by NA, they can be assigned through `factors<-` by providing a factor or character vector of the same length of the input columns;
- Each factor must include two or more values, since the factor analysis is based on ANOVA and at least two values are needed to variance calculation;
- Columns whose factor value is NA are not considered.

See Also

[p.adjust.methods](#)

Examples

```
## Finalizing example using a random generated input
ginput <- geva.ideal.example()      # Generates a random input (for testing purposes only)
gsummary <- geva.summarize(ginput)  # Summarizes the input
gquant <- geva.quantiles(gsummary)  # Calculates the quantiles
gclust <- geva.cluster(gsummary)    # Calculates the clusters
gresults <- geva.finalize(gsummary, gquant, gclust) # Finishes the results

head(top.genes(gresults))          # Prints the final results
plot(gresults)                     # Plots the final SV-plot
```

Description

Performs a hierarchical cluster analysis from summarized data.

Usage

```
geva.hcluster(
  sv,
  resolution = 0.3,
  hc.method = options.hc.method,
  hc.metric = options.hc.metric,
  cl.score.method = options.cl.score.method,
  ...,
  include.raw.results = FALSE
)

options.hc.metric
# c("euclidean", "maximum", "manhattan", "canberra",
#   "binary", "minkowski")

options.hc.method
# c("centroid", "median", "ward", "single")
```

Arguments

sv	a numeric SVTable object (usually GEVASummary)
resolution	numeric (0 to 1), used as a "zoom" parameter for cluster detection. A zero value returns the minimum number of clusters that can be detected, while 1 returns the maximum amount of detectable clusters
hc.method	character, the agglomeration method to be used. Used as the method argument for fastcluster::hclust.vector()
hc.metric	character, the distance measure to be used. Used as the metric argument for fastcluster::hclust.vector()
cl.score.method	character, method used to calculate the cluster scores for each point. If "auto", the "hclust.height" method is selected
...	additional arguments: • <code>mink.p</code> : numeric, parameter for the Minkowsky metric. Used as the p argument for fastcluster::hclust.vector() • <code>verbose</code> : logical, whether to print the current progress (default is TRUE)
include.raw.results	logical, whether to attach intermediate results to the returned object

Details

This function performs a hierarchical cluster analysis with the aid of implemented methods from the [fastcluster::fastcluster](#) package, particularly the [fastcluster::hclust.vector\(\)](#) function. The available methods for the `hc.method` and `hc.metric` are described in the function's documentation page (see [fastcluster::hclust.vector\(\)](#)).

The resolution value is an accessible way to define the cluster separation threshold used in hierarchical clustering. The algorithm produces a dendrogram-like hierarchy in which each level/node

is separated by a distance (sometimes called "height") to the next level/node, and the resolution translates a value between 0 and 1 to a proportional value within the total hierarchy height. This allows defining the rate of clusters from 0 to 1, which results in the least number of possible clusters (usually two) for 0, and the highest number (approximately one cluster per point) for 1.

If `include.raw.results` is TRUE, some additional data will be attached to the `info` slot of the returned `GEVACluster` objects, including the *kNN* tree generated during the intermediate steps.

Value

A `GEVACluster` object

Note

In hierarchical clustering, all points are clustered. Therefore, setting resolution to 1 will result into one cluster per point, where the cluster analysis may become pointless (no pun intended).

See Also

Other `geva.cluster`: `geva.cluster()`, `geva.dcluster()`, `geva.quantiles()`

Examples

```
## Hierarchical clustering from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Hierarchical clustering
gclust <- geva.hcluster(gsummary)
plot(gclust)

# Hierarchical clustering with slightly more resolution
gclust <- geva.hcluster(gsummary,
                        resolution=0.35)
plot(gclust)
```

geva.ideal.example	<i>GEVA “Ideal” Example for Package Testing</i>
--------------------	---

Description

Generates a random example of `GEVAInput` object that simulates an ideal analysis dataset. Used for testing purposes only.

Usage

```
geva.ideal.example(probecount = 10000, nfactors = 3, colspfactor = 3)
```

Arguments

probecount integer, number of probes (*i.e.*, table rows)
nfactors integer, number of factors (*e.g.*, experimental groups)
colspersfactor integer, number of columns (*e.g.*, experiments) per factor

Value

A [GEVAInput](#) object. The included tables are composed by probecount rows and nfactors * colspersfactor columns

See Also

[geva.summarize](#)

Examples

```
## "Ideal" input example
ginput <- geva.ideal.example()      # Generates a random example
gsummary <- geva.summarize(ginput) # Summarizes the generated data
plot(gsummary)                      # Plots the summarized data
```

geva.input.correct	<i>GEVA Input Post-processing</i>
--------------------	-----------------------------------

Description

Helper functions used to edit the contents from a [GEVAInput](#).

Usage

```
geva.input.correct(ginput, na.rm = TRUE, inf.rm = TRUE, invalid.col.rm = TRUE)

geva.input.filter(
  ginput,
  p.value.cutoff = 0.05,
  by.any = FALSE,
  na.val = 0,
  ...
)

geva.input.rename.rows(
  ginput,
  attr.column,
  dupl.rm.method = c("least.p.vals", "order")
)
```

Arguments

<code>ginput</code>	A GEVAInput object
<code>na.rm</code>	logical; if TRUE, removes all rows containing NA
<code>inf.rm</code>	logical; if TRUE, removes all rows containing infinite values (Inf or -Inf)
<code>invalid.col.rm</code>	logical; if TRUE, searches for any column that is entirely composed by invalid values (according to the other arguments) and removes it before checking the rows
<code>p.value.cutoff</code>	numeric (0 to 1), the p-value cutoff. Rows containing values above this threshold are removed
<code>by.any</code>	logical, set to TRUE to delete the rows with at least one occurrence above the cutoff; or FALSE to delete only those rows in which all values are above the specified threshold
<code>na.val</code>	numeric, the replacement for NA values
<code>...</code>	optional arguments. Accepts <code>verbose</code> (logical, default is TRUE) to enable or disable printing the progress
<code>attr.column</code>	character, target column with the values that will replace the current row names
<code>dupl.rm.method</code>	character, method to remove duplicate names. The possible options are: • <code>"least.p.vals"</code> : Keeps the duplicate that contains the least sum of p-values • <code>"order"</code> : Keeps the first occurrence of the duplicate in the current row order

Details

`geva.input.correct` corrects the numeric input data (values and weights), removing rows that include invalid values such as NA or infinite.

`geva.input.filter` attempts to select the most relevant part of the input data, removing rows containing p.values (1 - weights) above a specific threshold.

`geva.input.rename.rows` replaces the row names with a column from the feature table (see [GEVAInput](#)). The column name specified for `attr.column` must be included in the `names(featureTable(ginput))`. Any duplicates are removed according to the `dupl.rm.method`, and the selected duplicates are stored as a new column named `"renamed_id"` inside the feature table from the returned object.

Value

A modified [GEVAInput](#) object

Examples

```
## geva.input.correct example
colexample1 <- runif(1000, -1, 1)      # Random column 1
colexample2 <- runif(1000, -1, 1)      # Random column 2
colexample3 <- runif(1000, -1, 1)      # Random column 3
colexample3[runif(1000, -1, 1) < 0] = NA # Random NA's
```

```

ginput = geva.merge.input(col1=colexample1,
                          col2=colexample2,
                          col3=colexample3)

# Before the correction:
print(nrow(ginput))    # Returns 1000
# Applies the correction (removes rows with NA's)
ginput <- geva.input.correct(ginput)
# After the correction:
print(nrow(ginput))    # Returns less than 1000

## ---
## geva.input.filter example
ginput <- geva.ideal.example(1000) # Generates a random input
# Before the filter:
print(nrow(ginput))    # Returns 1000
# Applies the filter
ginput <- geva.input.filter(ginput)
# After the filter:
print(nrow(ginput))    # Returns less than 1000

## ---
## geva.input.rename.rows example
ginput <- geva.ideal.example() # Generates a random input
# Renames to 'Symbol'
ginput <- geva.input.rename.rows(ginput,
                                attr.column = "Symbol")
print(head(ginput))      # The row names are set now as the gene symbols

```

geva.merge.input

GEVA Input Processing and Merge

Description

Functions to read, load, and concatenate the experimental comparisons from the data input. This is the initial step to proceed with any GEVA analysis.

Usage

```

geva.merge.input(
  ...,
  col.values = "logFC",
  col.pvals = "adj.P.Val",
  col.other = NULL
)

geva.read.tables(
  filenames = NULL,
  dirname = ".",

```

```

col.values = "logFC",
col.pvals = "adj.P.Val",
col.other = NULL,
...,
files.pattern = "\\..txt$",
p.value.cutoff = 0.05,
read.args = list()
)

```

Arguments

...	multiple matrix or data.frame objects. At least two arguments are required for <code>geva.merge.input</code> , but it's optional for <code>geva.read.tables</code> . The optional arguments in <code>geva.read.tables</code> are also passed to its internal call to <code>geva.merge.input</code> and geva.input.filter . In addition, the following optional arguments are accepted: <code>na.val</code> : (numeric) value between 0 and 1 used as replacement when a p-value column is not present (default is NA) <code>use.regex</code> : (logical) whether to match the column names using regular expressions (default is FALSE) <code>verbose</code> : (logical) whether to print the current loading and merge progress (default is TRUE)
<code>col.values</code>	character vector, possible name(s) to match the <i>logFC</i> column(s) from each table
<code>col.pvals</code>	character vector, possible name(s) to match the p-value column(s) from each table
<code>col.other</code>	character vector, name(s) to match additional columns (<i>e.g.</i> , gene symbols). Ignored if NULL
<code>filenames</code>	character vector with two or more file paths
<code>dirname</code>	single character, base directory containing the input files. Ignored if <code>filenames</code> is specified
<code>files.pattern</code>	single character, pattern used to filter the files inside <code>dirname</code> . Ignored if <code>filenames</code> is specified
<code>p.value.cutoff</code>	numeric (0 to 1), initial p-value threshold. Rows entirely composed by p-values above this cutoff (<i>i.e.</i> , no significant <i>logFC</i>) are removed after the final merge. Ignored if NA or NULL
<code>read.args</code>	list of additional arguments passed to utils::read.table

Details

The `geva.merge.input` function takes multiple tables as arguments (*e.g.*, matrix or data.frame objects), extracts the *logFC* columns from each table and merges them into a single [GEVAInput](#) dataset.

The column names are specified in the `col.values` and `col.pvals` arguments (character) and must correctly match the column names for *logFC* and p-value columns, respectively, in the inputs

to be extracted. Multiple values for column names can also be specified as valid name possibilities if they differ among the tables.

The function `geva.merge.input` reads multiple tab-delimited text files containing, extracts the *logFC* columns from each table and merges into a single [GEVAInput](#) dataset.

Value

A [GEVAInput](#) object

Note

The inclusion of p-value columns is not technically required, but strongly recommended as they improve the statistical accuracy in the summarization steps. If the p-value (or adjusted p-value) columns are present, their values are converted to weights by applying $1 - \text{pvalue}$ for each pvalue element, otherwise an optional `na.val` optional argument can be specified as replacement to the absent values (default is NA). Weights are used to accommodate the central *logFC* values towards the most significant observations and penalize potential statistical inaccuracies.

Examples

```
### EXAMPLE 1
## geva.merge.input example with three randomly generated tables
## (For demonstration purposes only)

# Number of rows
n <- 10000

# Random row (probe) names
probnms <- sprintf("PROBE_%s", 1:n)

# Random gene names (optional)
genenms <- paste0(sprintf("GENE_%s", 1:n), LETTERS[1:n %% (length(LETTERS)+1)])

# Random table 1
dt1 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)

# Random table 2
dt2 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)

# Random table 3
dt3 <- data.frame(row.names=probnms,
                  logfc=(rnorm(n, 0, sd=2) * rnorm(n, 0, sd=0.5)),
                  pvalues = runif(n, max=0.08),
                  genesymbol = genenms)

# Merges the three tables
ginput <- geva.merge.input(exp1=dt1, exp2=dt2, exp3=dt3,
```

```

col.values="logfc",
col.pvals="pvalues",
col.other="genesymbol")

# Prints the first rows from the merged table
print(head(ginput))          # values
print(head(inputweights(ginput))) # weights

# ---
## Not run:

### EXAMPLE 2
## geva.read.tables example with three tab-delimited files

# Table file examples. Each one has 3 columns: "logfc", "pvalues", and "genesymbol"
# Replace it with your tab-delimited files (e.g. exported from limma's topTable)
fnames <- c("dt1.txt", "dt2.txt", "dt3.txt")

ginput <- geva.read.tables(fnames,
                           col.values="logfc",
                           col.pvals="pvalues",
                           col.other="genesymbol")

# Prints the first rows from the merged table
print(head(ginput))          # values
print(head(inputweights(ginput))) # weights

# ---

### EXAMPLE 3
## geva.read.tables example with tab-delimited files in a directory

# Directory name (replace it with a directory containing the table files)
dirnm <- "C:/User/robertplant123/Documents/R/gevaexamples"

# In this example, table files contain 3 columns: "logfc", "pvalues", and "genesymbol"
# Reads all txt files in the directory
ginput <- geva.read.tables(dirname=dirnm,
                           col.values="logfc",
                           col.pvals="pvalues",
                           col.other="genesymbol")

# (Optional step)
# Let's assume that all table file names start with "dt" and ends with the ".txt" extension,
# such as dt1.txt, dt2.txt and so on...
fname_pattern <- c("^dt.+?\\.txt$") # Defines a RegEx pattern to find the files
# Loads only files that match the file name pattern
ginput <- geva.read.tables(dirname=dirnm,
                           files.pattern=fname_pattern,
                           col.values="logfc",
                           col.pvals="pvalues",
                           col.other="genesymbol")

```

```
# Prints the first rows from the merged table
print(head(ginput))          # values
print(head(inputweights(ginput))) # weights

## End(Not run)
```

geva.quantiles

GEVA Quantiles Detection

Description

Calculates the quantiles of a [SVTable](#).

Usage

```
geva.quantiles(
  sv,
  quantile.method = options.quantiles,
  initial.thresholds = c(S = NA_real_, V = NA_real_),
  nq.s = 3L,
  nq.v = 2L,
  comb.score.fn = prod,
  ...
)

options.quantiles
# c("range.slice", "proportional", "density", "k.max.sd",
#   "custom")
```

Arguments

sv	a SVTable object (usually GEVASummary)
quantile.method	character, method to detect the initial quantile thresholds. Ignored if <code>initial.thresholds</code> is specified with no NA elements
initial.thresholds	named numeric vector with the threshold that delimits the initial quantile
nq.s	integer, number of quantiles in S-axis (experimental, see ‘Note’)
nq.v	integer, number of quantiles in V-axis (experimental, see ‘Note’)
comb.score.fn	function applied to merge S and V score columns into a single column. The function must require only one argument of numeric vector type and return a single numeric value. Examples include <code>prod</code> or <code>mean</code>
...	additional arguments include:

- `qslice` : numeric (0 to 1), the axis fraction used by "range.slice" and "density" methods (see 'Details'). Default is 0.25
- `k` : integer, neighbor points used by "density" and "k.max.sd" methods (see 'Details'). Default is 16
- `verbose` : logical, whether to print the current progress. Default is TRUE

Details

The `quantile.method` defines how the initial quantile (usually the one at the bottom center) is calculated. Each method has a specific way to estimate the first spatial delimiter, as described below:

"range.slice" (**default**) Separation is set at the nearest point to a fraction of the spatial range. This fraction can be specified by the `qslice` optional argument (numeric, default is 0.25, or 25%);

"density" Separation is set at the point with the most proportional density by k neighbor points to its current spatial fraction. This method uses the optional arguments `qslice` (numeric, default is 0.25, or 25%) for the desired spatial fraction, and `k` (numeric, default is 16) for the number of neighbor points;

"k.max.sd" Separation is set at the point with the greatest standard deviation of distance to its k neighbor points. The number of neighbor points can be specified by the `k` optional argument (numeric, default is 16);

"proportional" Separation is set at the exact axis division so that all quantiles have the size;

"custom" Uses the values specified in the `initial.thresholds` argument.

A custom initial separation point can be specified in the `initial.thresholds` as a numeric vector of two elements, where the first element refers to S axis and the second, to V axis. If one of the elements is NA, the initial quantile is calculated for that axis only. If both values are not NA, the quantile separation method is ignored and automatically set to "custom".

The `nq.s` and `nq.v` arguments determine the number of quantiles for the S and V axes, respectively. These parameters can be used to increase the number of possible partitions in the SV space, but their applicability is currently being tested (see 'Note').

The `comb.score.fn` is a function applied to the partial scores for each SV point to combine them into a single value. The result value is defined as the "quantile score" for a SV point. The function is applied iteratively to two-element numeric vectors.

Note

Customizing the number of quantiles by `nq.s` and `nq.v` is a **experimental feature** and the remaining analysis steps are mostly based on the default parameters for these arguments. Tests are being conducted to determine this feature's applicability for the next releases.

See Also

[geva.cluster](#)

Other `geva.cluster`: [geva.cluster\(\)](#), [geva.dcluster\(\)](#), [geva.hcluster\(\)](#)

Examples

```
## Quantile detection from a randomly generated input

# Preparing the data
ginput <- geva.ideal.example()      # Generates a random input example
gsummary <- geva.summarize(ginput)  # Summarizes with the default parameters

# Default usage
gquants <- geva.quantiles(gsummary) # Detects the quantiles
plot(gquants)                       # Plots the quantiles

# Custom initial delimiters
gquants <- geva.quantiles(gsummary,
                          initial.thresholds = c(S=1.00, V=0.5))
plot(gquants)                       # Plots the quantiles

# Quantile detection using densities
gquants <- geva.quantiles(gsummary, quantile.method = 'density')
plot(gquants)                       # Plots the quantiles
```

geva.quick

All-In-One Function for GEVA Intermediate Procedures

Description

Given a [GEVAInput](#) object, applies the [geva.summarize\(\)](#), [geva.quantiles](#), [geva.cluster](#), and [geva.finalize](#) in a single call. Optional arguments are passed to the internal calls of these functions.

Usage

```
geva.quick(gobject, ...)
```

Arguments

gobject	A GEVAInput , or any object that returns a GEVAInput upon calling <code>inputdata(gobject)</code> (e.g., GEVASummary or GEVAResults).
...	Optional arguments passed to geva.summarize() , geva.quantiles() , geva.cluster() , and geva.finalize()

Details

This function performs the summarization, quantile detection, and clustering of an input data, then merges the results together and, if applicable, performs a factor analysis. If the `gobject` is not a [GEVAInput](#), it must provide a valid [GEVAInput](#) object when called by `inputdata(gobject)`. Moreover, all parameters used in previous analysis will be taken into account. For instance, if `gobject` is a [GEVASummary](#) obtained by using `variation.method='mad'`, the internal call to `geva.summarize`

in this function will use `variation.method='mad'` as well, unless if another parameter for `variation.method` is specified in the `...` arguments.

Therefore, this function can be useful not only as a shortcut to analyze `GEVAInput` but also for parameter testing when applied to a `GEVAResults` object, since the previous parameters are reused, while the specified parameters are overridden.

Value

A `GEVAResults` object

Examples

```
## Basic usage using a random generated input
ginput <- geva.ideal.example() # Generates a random input example
gresults <- geva.quick(ginput) # Performs the entire analysis (default parameters)

print(head(top.genes(gresults))) # Prints the results
plot(gresults)                  # Plots the final SV-plot

## Example with non-default parameters
ginput <- geva.ideal.example() # Generates a random input example
gresults <- geva.quick(ginput,
                        summary.method="median",
                        variation.method="mad",
                        quantiles.method="density",
                        cluster.method="density",
                        resolution=0.32)

print(head(top.genes(gresults))) # Prints the results
plot(gresults)                  # Plots the final SV-plot
```

geva.summarize

Summarizes the GEVAInput

Description

Performs the summarization step by calculating the central points and variation estimates of *logFC* values from the input data.

Usage

```
geva.summarize(
  ginput,
  summary.method = options.summary,
  variation.method = options.variation,
  ...
)
```

```
options.summary
# c("mean", "median")

options.variation
# c("sd", "var", "mad")
```

Arguments

<code>ginput</code>	a GEVAInput object
<code>summary.method</code>	single character, method used to calculate the central (summarized) <i>logFC</i> values
<code>variation.method</code>	single character, method used to calculate the distribution degree (variation) of the <i>logFC</i> values
<code>...</code>	additional arguments. Accepts <code>verbose</code> (logical, default is TRUE) to enable or disable printing the current progress

Details

The `options.summary` refer to the available operations to calculate central *logFC* values (mean or median), whereas `options.variation` presents three functions to calculate *logFC* variation (`sd`: Standard Deviation; `var`: Variance; and `mad`: Median Absolute Deviation). Moreover, all those operations include a weighted counterpart applied using the weights table from the [GEVAInput](#) object.

Value

A [GEVASummary](#) object

See Also

```
base::mean(), stats::median()

stats::var(), stats::sd(), stats::mad()
```

Examples

```
## Summarization of a randomly generated input
ginput <- geva.ideal.example() # Generates a random input example
gsummary <- geva.summarize(ginput) # Summarizes with the default parameters
plot(gsummary) # Plots the summarized data
```

GEVACluster-class	<i>GEVA Clustering Results</i>
-------------------	--------------------------------

Description

The GEVACluster class represents the classification results from a cluster analysis. For each probe/gene, there is a assigned cluster among the g defined clusters.

This class inherits from [GEVAGroupSet](#).

Value

A [GEVACluster](#) object

Slots

grouping factor (m elements, g levels), cluster assignment for each gene/probe
(Inherited from [GEVAGroupSet](#))

scores numeric vector (m elements) comprising a score value for each cluster assignment
(Inherited from [GEVAGroupSet](#))

fable data.frame (m lines) with additional cluster assignment features
(Inherited from [GEVAGroupSet](#))

centroids numeric SVTable (g lines) with the S and V centroid coordinates for each cluster
(Inherited from [GEVAGroupSet](#))

offsets numeric SVTable (m lines) with the S and V coordinate offsets each gene/probe from its cluster centroid
(Inherited from [GEVAGroupSet](#))

info list of supplementary information
(Inherited from [GEVAGroupSet](#))

cluster.method character, method used in the cluster analysis (see [geva.cluster](#))

Methods

(See also the inherited methods from [GEVAGroupSet](#))

Plotting

lines(x, ...) Draws convex hulls around the clustered points

plot(x, y, ...) Draws a SV-plot that highlights the clustered points. Convex hulls are included for visual purposes only and do not avoid enclosing points from other clusters on concave parts.
Can be combined with another SVTable or GEVAGroupSet given as the y argument to include additional graphical elements

GEVAGroupedSummary-class

GEVA Grouped Summary-Variation Table

Description

The GEVAGroupedSummary class inherits the [GEVASummary](#) class and includes group analysis data (e.g., clustering and quantile detection).

Value

A [GEVAGroupedSummary](#) object

Slots

`sv` numeric matrix composed by two columns: S (summary) and V (variation)
(Inherited from [SVTable](#))

`inputdata` GEVAInput-class with the data input
(Inherited from [GEVASummary](#))

`sv.method` Names of the statistical methods used to summarize data
(Inherited from [GEVASummary](#))

`info` list with additional information
(Inherited from [GEVASummary](#))

`groupsetlist` [TypedList](#) of [GEVAGroupSet](#) objects

Methods

(See also the inherited methods from [GEVASummary](#))

Conversion and coercion

`as.expression(x, ginput, ...)` Converts this object to expression

`as.matrix(x, ...)` Converts this object to matrix

Plotting

`lines(x, ...)` Draws delimiters within quantiles and convex hulls around the clustered points

`plot(x, y, ...)` Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V).

In addition, highlights the included group sets

`points(x, ...)` Generic points implementation for GEVAGroupedSummary

Properties

`analysis.params(gobject)` Returns a list of analysis parameters passed to `geva.cluster` to obtain this object

Sub-slot accessors

`cluster.method(object)` Gets a character vector listing the `cluster.method` from each group set

`quantiles(object)` Gets the `GEVAQuantiles`, or NULL if not present

GEVAGroupSet-class *GEVA Grouping Results*

Description

The `GEVAGroupSet` class represents the classification of summarized values from a `SVTable`, where each gene/probe has one assigned group among `g` defined groups. This is an abstract class. Inherits the `GEVACluster` and `GEVAQuantiles` classes.

Value

A `GEVAGroupSet` object

Slots

`grouping` factor (m elements, g levels) used to group the genes/probes

`scores` numeric vector (m elements) with the assigned grouping scores for each gene/probe

`ftable` data.frame (m lines) with additional grouping features

`centroids` numeric `SVTable` (g lines) with the S and V centroid coordinates for each group

`offsets` numeric `SVTable` (m lines) with the S and V coordinate offsets each gene/probe from its group centroid

`info` list of additional information

Methods

Alternative accessors

`levels(x)` Returns the unique group names included in the group set.
Equivalent to `levels(groups(x))`

Conversion and coercion

`as.data.frame(x, row.names = names(x), ...)` Returns a `data.frame` with the groups and scores slots as columns

`as.expression(x, sv, ...)` Gets the expression that reproduces this `GEVAGroupSet` object, including function parameters used by `geva.cluster`. The `sv` argument is optional but can be specified to replace the source `SVTable`

`as.SVTable(x, which = c("sv", "offsets", "centroids"), ...)` Retrieves a `SVTable` based on the contents indicated by `which`. The accepted arguments are: `sv` for the source data; `offsets` for the offsets slots; and `centroids` for the centroids slot

Dimension accessors

`length(x)` Returns the number of rows in the `sv` slot

`names(x)` Gets the assigned names by the classification and scores

Plotting

`color.values(x, point.col = NULL, ...)` Gets the colors associated to the grouped data points. If not present, generates random group colors. If `point.col` is a single character or an vector of the same length of data points, adjusts the color values to web RGBA

`plot(x, y, ...)` Draws a SV-plot that highlights the grouped information. Can be combined with another `SVTable` or `GEVAGroupSet` given as the `y` argument to include additional graphical elements

`points(x, ...)` Draws the grouped points

Properties

`analysis.params(gobject)` Returns a list of analysis parameters passed to `geva.cluster` to obtain this object

`cluster.method(object)` Returns the option used as the `cluster.method` argument when calling `geva.cluster`

Sub-slot accessors

`classification.table(object) <- value` Stores the classification data.frame on this object

`classification.table(object)` Returns a data.frame of predicted classifications, if supported by this object

`sv.data(object)` Returns a `SVTable` with the source SV coordinates

`sv(object)` Returns the numeric matrix in the `SVTable` from `sv.data(object)`

GEVAInput-class	<i>GEVA Input Data</i>
-----------------	------------------------

Description

The GEVAInput class contains the initial data for GEVA usage. It stores numeric matrices of *logFC* values from differential expression comparison results. Options for calculations and summarizing are also included.

Value

A [GEVAInput](#) object

Slots

`values` numeric matrix ($m*n$) of log-ratio values, usually *logFC*
`weights` numeric matrix ($m*n$) of weighted values. If not defined, all weight values are equal to 1
`factors` factor (n elements) representing the grouping of the n columns. If not defined, all factors are equal to NA
`ftable` data.frame with m rows containing attribute columns associated to the features (e.g., probes or genes)
`info` list of supplementary information related to the input

Methods

Alternative accessors

`levels(x)` Returns the unique values from the assigned factors; or NA if there are no assigned factors in `x`

Conversion and coercion

`as.array(x, ...)` Converts this object to array

Dimension accessors

`dim(x)` Gets the dimensions defined for both matrices in `values` and `weights` slots

`dimnames(x) <- value` Sets the list with the row and column names.

Individual dimension names can also be set using `rownames<-` and `colnames<-`

`dimnames(x)` Gets a list with the row and column names.

Individual dimension names can also be accessed through `rownames` and `colnames`

`inputnames(object)` Gets the input column names (same as `colnames(object)`)

`length(x)` Returns the number of rows in the `values` slot

`names(x)` Same as `inputnames`. For internal use

Plotting

`plot(x, y, ...)` Summarizes the input using the default parameters, then calls the `plot` on the returned `GEVASummary` object.

Not intended to regular use and will give a warning if called

Properties

`analysis.params(gobject)` Returns a list of analysis parameters passed to `geva.merge.input` or `geva.read.tables` to obtain this object

Subsetting

`head(x, n = 6L, ...)` Returns the first parts of the values table

`tail(x, n = 6L, ...)` Returns the last parts of the values table

GEVAQuantiles-class *GEVA Quantiles Grouping Results*

Description

The `GEVAQuantiles` class represents the results of a quantile detection analysis. For each probe/gene, there is a assigned quantile among the g defined quantiles.

This class inherits from `GEVAGroupSet` and is inherited by `GEVAQuantilesAdjusted`.

Value

A `GEVAQuantiles` object

Slots

`grouping` factor (m elements, g levels), quantile assignment for each gene/probe
(Inherited from `GEVAGroupSet`)

`scores` numeric vector (m elements) with the assigned quantile scores for each gene/probe
(Inherited from `GEVAGroupSet`)

`fable` `data.frame` (m lines) with additional quantile assignment features
(Inherited from `GEVAGroupSet`)

`centroids` numeric `SVTable` (g lines) with the S and V centroid coordinates for each quantile
(Inherited from `GEVAGroupSet`)

`offsets` numeric `SVTable` (m lines) with the S and V coordinate offsets each gene/probe from its quantile centroid
(Inherited from `GEVAGroupSet`)

`info` list of additional information
 (Inherited from [GEVAGroupSet](#))
`svscores` numeric [SVTable](#) (m lines) with individual partial scores for the assigned quantiles
`qareasizes` numeric [SVTable](#) (g lines) with the S and V sizes for each quantile
`qindexes` integer [SVTable](#) (g lines) representing the position index to each quantile, in terms of summary and variation
`qcount` integer attributes ([SVIntAttribute](#)) with the defined number of quantiles for the S and V axes
`qcutoff` numeric attributes ([SVNumAttribute](#)) with the initial quantile cutoff in S and V, starting from the point zero
`qmethod` character, method used to calculate the initial quantiles (see [geva.quantiles\(\)](#))

Methods

(See also the inherited methods from [GEVAGroupSet](#))

Conversion and coercion

`as.expression(x, sv, ...)` Converts this object to expression
`as.SVTable(x, which = c("sv", "offsets", "centroids", "qindexes"), ..., row.names = names(x))`
 Converts this object to [SVTable](#)

Plotting

`lines(x, ...)` Draws the quantile delimiter lines
`plot(x, y, ...)` Draws a SV-plot that highlights the points from each quantile. Dashed lines are included as the quantile delimiters.
 Can be combined with another [SVTable](#) or [GEVAGroupSet](#) given as the `y` argument to include additional graphical elements

Properties

`cluster.method(object)` Returns the option used as the `cluster.method` argument when calling `geva.cluster`.
 Instances of this object always return 'quantiles'

Sub-slot accessors

`classification.table(object) <- value` Sets the `data.frame` with the qualitative contrasts of classification relevance
`classification.table(object)` Gets a `data.frame` with the qualitative contrasts of classification relevance
`quantiles(object)` Gets the unique quantile names

GEVAQuantilesAdjusted-class

GEVA Adjusted Quantiles Results

Description

The GEVAQuantilesAdjusted class represents the results of a quantile detection analysis with adjusted assignments based on relationships with other GEVAGroupSet objects. For each probe/gene, there is a assigned quantile among the g defined quantiles.

This class inherits from [GEVAQuantiles](#).

Value

A [GEVAQuantilesAdjusted](#) object

Slots

grouping factor (m elements, g levels), quantile assignment for each gene/probe
(Inherited from [GEVAGroupSet](#))

scores numeric vector (m elements) with the assigned quantile scores for each gene/probe
(Inherited from [GEVAGroupSet](#))

fable data.frame (m lines) with additional quantile assignment data
(Inherited from [GEVAGroupSet](#))

centroids numeric SVTable (g lines) with the S and V centroid coordinates for each quantile
(Inherited from [GEVAGroupSet](#))

offsets numeric SVTable (m lines) with the S and V coordinate offsets each gene/probe from its quantile centroid
(Inherited from [GEVAGroupSet](#))

info list of additional information
(Inherited from [GEVAGroupSet](#))

svscores numeric [SVTable](#) (m lines) with individual partial scores for the assigned quantiles
(Inherited from [GEVAQuantiles](#))

qareasizes numeric [SVTable](#) (g lines) with the S and V sizes for each quantile
(Inherited from [GEVAQuantiles](#))

qindexes integer [SVTable](#) (g lines) representing the position index to each quantile, in terms of summary and variation
(Inherited from [GEVAQuantiles](#))

qcount integer attributes ([SVIntAttribute](#)) with the defined number of quantiles for the S and V axes
(Inherited from [GEVAQuantiles](#))

qcutoff numeric attributes ([SVNumAttribute](#)) with the initial quantile cutoff in S and V, starting from the point zero
(Inherited from [GEVAQuantiles](#))

grouprels [TypedList](#) of named factor elements representing external group relationships to the current quantiles

Methods

(See also the inherited methods from [GEVAQuantiles](#) and [GEVAGroupSet](#))

GEVAResults-class	<i>GEVA Results Table</i>
-------------------	---------------------------

Description

The GEVAResults class contains the final results from GEVA analyses. It represents the results of multiple statistical approaches from summary/variation data, clustering, quantile detection, and factor analysis (if applicable).

Value

A [GEVAResults](#) object

Slots

`resultstable` `data.frame` (m lines) with classification results for the genes/probes
`svdata` [GEVASummary](#) used as input
`quantdata` [GEVAQuantiles](#) or [GEVAQuantilesAdjusted](#) with the final quantile assignments for the summarized data
`factoring` `data.frame` (m lines) with detailed results for the factor analyses, such as p-values for each factor. If there was no factor analysis, this slot is NULL or empty
`classiftable` `data.frame` used as reference for the final classification
`info` list of supplementary information

Methods

Conversion and coercion

`as.expression(x, gsummary, gquants, ...)` Gets the expression that reproduces this GEVAResults object, including function parameters used by `geva.finalize`. The `gsummary` and `gquants` arguments are optional but can be specified to replace the internal `GEVASummary` and `GEVAQuantiles`, respectively

Dimension accessors

`dim(x)` Returns the dimensions from the `resultstable` slot
`dimnames(x)` Returns a list with the row and column names from the `results.table` slot.
 Individual dimension names can also be accessed through `rownames` and `colnames`
`length(x)` Returns the number of rows in the `resultstable` slot
`names(x)` Returns the column names from the `resultstable` slot

Plotting

`plot(x, y, ...)` Draws a SV-plot that highlights the relevant points from adjusted quantiles

`points(x, which, ..., classif)` Draws the results points.

If `which` (character vector) is given, plots only the matching genes/probes.

If `classif` (character vector) is given, plots only points with the matching classification

Properties

`x$name <- value` Extracts a column from the `resultstable` slot

`x[i, j, ..., drop=TRUE]` Extracts the contents from the `resultstable` slot

`analysis.params(gobject)` Returns a list of analysis parameters passed to [geva.finalize](#) or [geva.quick](#) to obtain this object

Sub-slot accessors

`featureTable(object)` Returns the features data.frame from the internal [GEVAInput](#)

`head(x, ...)` Returns the first lines of `results.table(x)`

`inputdata(object)` Returns the internal [GEVAInput](#)

`inputvalues(object)` Returns the values matrix from the internal [GEVAInput](#)

`inputweights(object, normalized)` Returns the weights matrix from the internal [GEVAInput](#)

`levels(x)` Returns the factors used in factor analysis, if present

GEVASummary-class

GEVA Summary-Variation Table

Description

The `GEVASummary` class represents the calculation results for summary and variation from a [GEVAInput](#).

This class inherits from [SVTable](#).

Value

A [GEVASummary](#) object

Slots

`sv` numeric matrix composed by two columns: S (summary) and V (variation)
(Inherited from [SVTable](#))

`inputdata` [GEVAInput](#)-class with the data input

`sv.method` Names of the statistical methods used to summarize data

`info` list with additional information

Methods

(See also the inherited methods from [SVTable](#))

Conversion and coercion

`as.expression(x, ginput, ...)` Gets the expression that reproduces this `GEVASummary` object, including function parameters used by `geva.summary`. The `ginput` argument is optional but can be specified to replace the internal `GEVAInput`

`as.matrix(x, ...)` Equivalent to `sv(x)`

Grouping

`groupsets(object) <- value` Converts this instance to [GEVAGroupedSummary](#) and sets the list of [GEVAGroupSet](#) objects. Can be used with `$<name>` to specify the object name in the list. If `value` is a `GEVAGroupSet`, inserts the element and sets the name based on the value call

`groupsets(object)` Gets the list of [GEVAGroupSet](#) objects attached to this instance. Only applicable for [GEVAGroupedSummary](#) objects

Plotting

`plot(x, y, ...)` Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V)

Properties

`analysis.params(gobject)` Returns a list of analysis parameters passed to [geva.summarize](#) to obtain this object

`get.summary.method(x)` Gets a character for the summarization method name

`get.variation.method(x)` Gets a character for the variation calculation method name

Sub-slot accessors

`factors(object) <- value` Sets the value to the factor slot in the internal [GEVAInput](#)

`factors(object)` Gets the factor defined in the factors slot in the internal [GEVAInput](#)

`featureTable(object)` Gets the data.frame from the ftable slot in the internal [GEVAInput](#)

`infolist(object, field = NULL, ...)` Gets the list from the info slot.

If recursive is TRUE, appends the contents from the info slot in the internal [GEVAInput](#)

`inputvalues(object)` Gets the matrix from the values slot in the internal [GEVAInput](#)

`inputweights(object, normalized)` Gets the matrix from the weights slot in the internal [GEVAInput](#)

SVAttribute-class	<i>Summary-Variation Attribute Field</i>
-------------------	--

Description

This S4 class stores two character slots representing attribute fields for summary and variation. The SVAttribute class is abstract and must be instantiated as SVChrAttribute (for character), SVNumAttribute (for numeric), or SVIntAttribute (for integer).

Arguments

S	the <i>summary</i> value
V	the <i>variation</i> value

Value

A `SVAttribute` object

Slots

S	either character or numeric or integer of length one
V	either character or numeric or integer of length one

Methods**Alternative accessors**

`summary(object, ...)` Returns the contents from S slot
`sv(object)` Returns the contents as a named vector
`variation(object, ...)` Returns the contents from S slot

Constructors

`sv.data(object)` For internal use. Returns the equivalent object
`svattr(S, V)` Creates a new SVAttribute

Conversion and coercion

`as.character(x, ...)` Converts this object to character
`as.vector(x, ...)` Converts this object to vector

Dimension accessors

`dim(x)` For internal use, always returns NULL

names(x) Returns the slot names (always c('S', 'V'))

Properties

x\$name <- value Queries the vector contents (equivalent to the indexer). Only accepts \$S and \$V
x[i, j, ..., drop=TRUE] Indexer to access the vector values. Only accepts 'S' or 'V' as i arguments

Note

The slots S and V must be of the same class (either character, numeric, or integer).

SVTable-class	Summary-Variation Table
---------------	-------------------------

Description

The SVTable class stores a matrix composed by two columns: S (for *summary*) and V (for *variation*).
This class is inherited by [GEVASummary](#).

Value

A [SVTable](#) object

Slots

sv matrix composed by two columns: S (summary) and V (variation)

Methods

Alternative accessors

summary(object, ...) Returns the S column
sv.data(object) Equivalent to returning this object itself
variation(object, ...) Returns the V column

Constructor

svtable(S, V, row.names = NULL) Creates a SVTable from the vectors S and V

Conversion and coercion

as.data.frame(x, ...) Converts this object to data.frame
as.matrix(x, ...) Converts this object to matrix

as.SVTable.data.frame(x, row.names = rownames(x), ...) Converts a data.frame to a SVTable
 as.SVTable.matrix(x, row.names = rownames(x), ...) Converts a matrix to a SVTable
 as.SVTable(x, ...) Returns the same object

Dimension accessors

dimnames(x) Gets a list with the row and column names from the sv slot.
 Individual dimension names can also be accessed through rownames and colnames
 dim(x) Gets the dimensions from the sv slot
 length(x) Returns the number of rows in the sv slot
 names(x) Always returns c('S', 'V')

Formatting and evaluation

format(x, ...) Generic format implementation for SVTable
 with(data, expr, ...) Generic with implementation for SVTable

Plotting

plot(x, y, ...) Draws a SV-plot. The horizontal axis is for *summary* (S) and the vertical axis is for *variation* (V)
 points(x, ...) Draws the SV points in the plot

Subsetting

head(x, n = 6L, ...) Returns the first parts of the matrix contents
 tail(x, n = 6L, ...) Returns the last parts of the matrix contents

Validation

is.na(x) Generic is.na implementation for SVTable

Note

The matrix from sv slot can be numeric, character, or any other supported type by matrix. The same slot from [GEVASummary](#), however, is always a numeric matrix.

Examples

```
## Creates a SV-table where:
# - S has elements from 1 to 10; and
# - V has elements from 10 to 1
svtab <- svtable(seq.int(1, 10), seq.int(10, 1))
```

top.genes

*Top Results from GEVA***Description**

Extracts the genes with a relevant classification according to the GEVA results.

Usage

```
top.genes(
  gevarresults,
  classif = c("similar", "factor-dependent", "factor-specific"),
  which.spec = levels(gevarresults),
  add.cols = NULL,
  ...,
  names.only = FALSE
)
```

Arguments

gevarresults	a GEVResults object
classif	character vector, filters the returned genes by their final classification. Possible options are "similar", "factor-dependent", "factor-specific", "sparse", and "basal". Multiple options can be combined
which.spec	factor, filters the specific factors to be returned
add.cols	character vector with column names from the feature table (accessed by <code>featureTable(gevarresults)</code>). The matching columns will be added to the returned table
...	optional arguments (not used in this version)
names.only	logical, set to TRUE to return only the table row names

Value

If `names.only` is FALSE (the default), returns a subset of the `resultstable` slot (`data.frame`) from the `gevarresults` that includes only the filtered genes according to the function parameters.

Otherwise, if `names.only` is TRUE, returns only the row names (character vector) of this table subset.

Examples

```
## Basic usage with a random generated input
ginput <- geva.ideal.example() # Generates a random input example
gresults <- geva.quick(ginput) # Performs the entire analysis (default parameters)

# Gets a table that includes all the top genes
dtgenes <- top.genes(gresults) # Gets the top genes table
head(dtgenes)                 # Prints the first results
```

```

# Appends the "Symbol" column to the results table
dtgenes <- top.genes(gresults, add.cols="Symbol")
head(dtgenes)           # Prints the first results

# Appends all feature columns to the results table
dtgenes <- top.genes(gresults, add.cols=names(featureTable(gresults)))
head(dtgenes)           # Prints the first results

# Gets only the factor-specific genes
dtgenes <- top.genes(gresults, "factor-specific")
head(dtgenes)           # Prints the first results

# Gets only the factor-specific genes for "Cond_1" factor (if any)
dtgenes <- top.genes(gresults, "factor-specific", "Cond_1")
head(dtgenes)           # Prints the first results

```

TypedList-class	<i>Type-strict List (TypedList-class)</i>
-----------------	---

Description

List containing elements of the same class or inheritance.

Value

A [TypedList](#) object

Slots

`.Data` list of internal contents. Elements must match or inherit a common class
(Inherited from list)

`elem.class` character representing the class related to the elements

Methods

Constructors

`typed.list(..., elem.class = NA_character_)` Creates a TypedList from the elements in ...
derived from the class `elem.class`

Conversion and coercion

`as.list(x, ...)` Converts this object to list

`as.typed.list.list(x, elem.class = NA_character_)` Converts a list to a TypedList if its
elements inherit the same type

`as.typed.list(x, elem.class = NA_character_)` Coerces a TypedList to support the inherited class indicated by `elem.class`

`as.typed.list.vector(x, elem.class = NA_character_)` Converts a vector to a TypedList

Properties

`x[i, j, ...] <- value` Sets a value to this list. The value argument must be compatible to the current list type

Examples

```
## Creates a TypedList that stores list-derived objects
tpls = typed.list(A=list(1L:5L),
                  B=data.frame(v1=LETTERS[1L:10L]),
                  elem.class = 'list')

# Note: The 'elem.class' above is optional, since the
# class is automatically detected from the first argument
```

Index

- * **datasets**
 - geva.cluster, 6
 - geva.dcluster, 8
 - geva.finalize, 10
 - geva.hcluster, 12
 - geva.quantiles, 21
 - geva.summarize, 24
- * **geva.cluster**
 - geva.cluster, 6
 - geva.dcluster, 8
 - geva.hcluster, 12
 - geva.quantiles, 21
- * **internal**
 - geva-package, 3
- [, GEVAInput, ANY, ANY, ANY-method (GEVAInput-class), 30
- [, GEVAQuantiles, ANY, ANY, ANY-method (GEVAQuantiles-class), 31
- [, GEVAREsults, ANY, ANY, ANY-method (GEVAREsults-class), 34
- [, SVAttribute, ANY, ANY, ANY-method (SVAttribute-class), 37
- [, SVTable, ANY, ANY, ANY-method (SVTable-class), 38
- [, TypedList, ANY, missing, missing-method (TypedList-class), 41
- [<-, TypedList, character, missing-method (TypedList-class), 41
- \$, GEVAREsults-method (GEVAREsults-class), 34
- \$, SVAttribute-method (SVAttribute-class), 37
- \$, SVTable-method (SVTable-class), 38
- analysis.params (generics), 4
- analysis.params, GEVAGroupedSummary-method (GEVAGroupedSummary-class), 27
- analysis.params, GEVAGroupSet-method (GEVAGroupSet-class), 28
- analysis.params, GEVAInput-method (GEVAInput-class), 30
- analysis.params, GEVAREsults-method (GEVAREsults-class), 34
- analysis.params, GEVASummary-method (GEVASummary-class), 35
- as.array.GEVAInput (GEVAInput-class), 30
- as.character.SVAttribute (SVAttribute-class), 37
- as.data.frame.GEVAGroupSet (GEVAGroupSet-class), 28
- as.data.frame.SVTable (SVTable-class), 38
- as.expression.GEVAGroupedSummary (GEVAGroupedSummary-class), 27
- as.expression.GEVAGroupSet (GEVAGroupSet-class), 28
- as.expression.GEVAQuantiles (GEVAQuantiles-class), 31
- as.expression.GEVAREsults (GEVAREsults-class), 34
- as.expression.GEVASummary (GEVASummary-class), 35
- as.list.TypedList (TypedList-class), 41
- as.matrix.GEVAGroupedSummary (GEVAGroupedSummary-class), 27
- as.matrix.GEVASummary (GEVASummary-class), 35
- as.matrix.SVTable (SVTable-class), 38
- as.SVTable (generics), 4
- as.SVTable.data.frame (SVTable-class), 38
- as.SVTable.GEVAGroupSet (GEVAGroupSet-class), 28
- as.SVTable.GEVAQuantiles (GEVAQuantiles-class), 31
- as.SVTable.matrix (SVTable-class), 38
- as.SVTable.SVTable (SVTable-class), 38
- as.typed.list.list (TypedList-class), 41

- as.typed.list.TypedList
(TypedList-class), 41
- as.typed.list.vector (TypedList-class),
41
- as.vector.SVAttribute
(SVAttribute-class), 37

- base::mean(), 25

- centroids (generics), 4
- centroids, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- classification.table (generics), 4
- classification.table, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- classification.table, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- classification.table<- (generics), 4
- classification.table<-, GEVAGroupSet, data.frame-method
(GEVAGroupSet-class), 28
- classification.table<-, GEVAQuantiles, data.frame-method
(GEVAQuantiles-class), 31
- cluster.method (generics), 4
- cluster.method, GEVACluster-method
(GEVACluster-class), 26
- cluster.method, GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 27
- cluster.method, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- cluster.method, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- color.values.GEVAGroupSet
(GEVAGroupSet-class), 28

- dbscan::dbscan, 9
- dbscan::dbscan(), 9
- dbscan::optics(), 9
- dim, GEVAInput-method (GEVAInput-class),
30
- dim, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- dim, GEVAResults-method
(GEVAResults-class), 34
- dim, SVAttribute-method
(SVAttribute-class), 37
- dim, SVTable-method (SVTable-class), 38
- dimnames, GEVAInput-method
(GEVAInput-class), 30
- dimnames, GEVAResults-method
(GEVAResults-class), 34
- dimnames, SVTable-method
(SVTable-class), 38
- dimnames<-, GEVAInput, list-method
(GEVAInput-class), 30

- elem.class (generics), 4
- elem.class, TypedList-method
(TypedList-class), 41
- elem.class<- (generics), 4
- elem.class<-, TypedList, character-method
(TypedList-class), 41

- factors, 12
- factors (generics), 4
- factors, GEVAInput-method
(GEVAInput-class), 30
- factors, GEVASummary-method
(GEVASummary-class), 35
- factors (generics), 4
- factors<-, GEVAInput, character-method
(GEVAInput-class), 30
- factors<-, GEVAInput, factor-method
(GEVAInput-class), 30
- factors<-, GEVASummary, character-method
(GEVASummary-class), 35
- factors<-, GEVASummary, factor-method
(GEVASummary-class), 35
- fastcluster::fastcluster, 13
- fastcluster::hclust.vector(), 7, 13
- featureTable (generics), 4
- featureTable, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- featureTable, GEVAInput-method
(GEVAInput-class), 30
- featureTable, GEVAResults-method
(GEVAResults-class), 34
- featureTable, GEVASummary-method
(GEVASummary-class), 35
- featureTable<- (generics), 4
- featureTable<-, GEVAInput, data.frame-method
(GEVAInput-class), 30
- format.SVTable (SVTable-class), 38

- generics, 4
- get.distance.method (generics), 4
- get.summary.method (generics), 4

- get.summary.method.GEVASummary
(GEVASummary-class), 35
- get.variation.method(generics), 4
- get.variation.method.GEVASummary
(GEVASummary-class), 35
- geva (geva-package), 3
- geva-package, 3
- geva.cluster, 6, 10, 11, 14, 22, 23, 26, 28, 29
- geva.cluster(), 23
- geva.dcluster, 8, 8, 14, 22
- geva.dcluster(), 7
- geva.finalize, 10, 23, 35
- geva.finalize(), 23
- geva.hcluster, 8, 10, 12, 22
- geva.hcluster(), 7
- geva.ideal.example, 14
- geva.input.correct, 15
- geva.input.filter, 18
- geva.input.filter (geva.input.correct),
15
- geva.input.rename.rows
(geva.input.correct), 15
- geva.merge.input, 17, 31
- geva.quantiles, 8, 10, 11, 14, 21, 23
- geva.quantiles(), 7, 23, 32
- geva.quick, 23, 35
- geva.read.tables, 31
- geva.read.tables (geva.merge.input), 17
- geva.summarize, 15, 24, 36
- geva.summarize(), 23
- GEVACluster, 8, 10, 11, 14, 26, 28
- GEVACluster-class, 26
- GEVAGroupedSummary, 8, 27, 36
- GEVAGroupedSummary-class, 27
- GEVAGroupSet, 8, 11, 26–28, 31–34, 36
- GEVAGroupSet-class, 28
- GEVAInput, 15, 16, 18, 19, 23, 25, 30, 35, 36
- GEVAInput-class, 30
- GEVAQuantiles, 8, 11, 28, 31, 33, 34
- GEVAQuantiles-class, 31
- GEVAQuantilesAdjusted, 31, 33, 34
- GEVAQuantilesAdjusted-class, 33
- GEVAResults, 6, 12, 23, 24, 34, 40
- GEVAResults-class, 34
- GEVASummary, 7–9, 11, 13, 21, 23, 25, 27, 34,
35, 38, 39
- GEVASummary-class, 35
- group.rels (generics), 4
- group.rels, GEVAQuantilesAdjusted-method
(GEVAQuantilesAdjusted-class),
33
- groups (generics), 4
- groups, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- groupsets (generics), 4
- groupsets, GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 27
- groupsets, GEVASummary-method
(GEVASummary-class), 35
- groupsets<- (generics), 4
- groupsets<- , GEVAGroupedSummary, GEVAGroupSet-method
(GEVAGroupedSummary-class), 27
- groupsets<- , GEVASummary, GEVAGroupSet-method
(GEVASummary-class), 35
- groupsets<- , GEVASummary, TypedList-method
(GEVASummary-class), 35
- head.GEVAInput (GEVAInput-class), 30
- head.GEVAResults (GEVAResults-class), 34
- head.SVTable (SVTable-class), 38
- infolist (generics), 4
- infolist, GEVAGroupSet, character-method
(GEVAGroupSet-class), 28
- infolist, GEVAGroupSet, missing-method
(GEVAGroupSet-class), 28
- infolist, GEVAInput, character-method
(GEVAInput-class), 30
- infolist, GEVAInput, missing-method
(GEVAInput-class), 30
- infolist, GEVAResults, character-method
(GEVAResults-class), 34
- infolist, GEVAResults, missing-method
(GEVAResults-class), 34
- infolist, GEVASummary, missing-method
(GEVASummary-class), 35
- infolist<- (generics), 4
- infolist<- , GEVAGroupSet, list-method
(GEVAGroupSet-class), 28
- infolist<- , GEVAInput, list-method
(GEVAInput-class), 30
- infolist<- , GEVASummary, list-method
(GEVASummary-class), 35
- inputdata (generics), 4
- inputdata, GEVAInput-method
(GEVAInput-class), 30

- inputdata, GEVResults-method
(GEVResults-class), 34
- inputdata, GEVSummary-method
(GEVSummary-class), 35
- inputnames (generics), 4
- inputnames, GEVAInput-method
(GEVAInput-class), 30
- inputnames, GEVSummary-method
(GEVSummary-class), 35
- inputvalues (generics), 4
- inputvalues, GEVAInput-method
(GEVAInput-class), 30
- inputvalues, GEVResults-method
(GEVResults-class), 34
- inputvalues, GEVSummary-method
(GEVSummary-class), 35
- inputweights (generics), 4
- inputweights, GEVAInput, logical-method
(GEVAInput-class), 30
- inputweights, GEVAInput, missing-method
(GEVAInput-class), 30
- inputweights, GEVResults, logical-method
(GEVResults-class), 34
- inputweights, GEVResults, missing-method
(GEVResults-class), 34
- inputweights, GEVSummary, logical-method
(GEVSummary-class), 35
- inputweights, GEVSummary, missing-method
(GEVSummary-class), 35
- is.na.SVTable (SVTable-class), 38

- length, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- length, GEVAInput-method
(GEVAInput-class), 30
- length, GEVResults-method
(GEVResults-class), 34
- length, SVTable-method (SVTable-class),
38
- levels, GEVAGroupSet
(GEVAGroupSet-class), 28
- levels, GEVAInput (GEVAInput-class), 30
- levels, GEVResults (GEVResults-class),
34
- lines.GEVACluster (GEVACluster-class),
26
- lines.GEVAGroupedSummary
(GEVAGroupedSummary-class), 27

- lines.GEVAQuantiles
(GEVAQuantiles-class), 31

- names, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- names, GEVAInput-method
(GEVAInput-class), 30
- names, GEVResults-method
(GEVResults-class), 34
- names, SVAttribute-method
(SVAttribute-class), 37
- names, SVTable-method (SVTable-class), 38

- offsets (generics), 4
- offsets, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- options.cl.score.method (geva.cluster),
6
- options.cluster.method (geva.cluster), 6
- options.dcluster.method
(geva.dcluster), 8
- options.distance (geva.cluster), 6
- options.factoring.p.adjust
(geva.finalize), 10
- options.hc.method (geva.hcluster), 12
- options.hc.metric (geva.hcluster), 12
- options.quantiles (geva.quantiles), 21
- options.summary (geva.summarize), 24
- options.variation (geva.summarize), 24

- p.adjust.methods, 12
- plot, GEVACluster, SVTable-method
(GEVACluster-class), 26
- plot, GEVAGroupedSummary, missing-method
(GEVAGroupedSummary-class), 27
- plot, GEVAGroupSet, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- plot, GEVAGroupSet, missing-method
(GEVAGroupSet-class), 28
- plot, GEVAGroupSet, SVTable-method
(GEVAGroupSet-class), 28
- plot, GEVAInput, missing-method
(GEVAInput-class), 30
- plot, GEVAQuantiles, SVTable-method
(GEVAQuantiles-class), 31
- plot, GEVResults, missing-method
(GEVResults-class), 34
- plot, GEVSummary, missing-method
(GEVSummary-class), 35

- plot, SVTable, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- plot, SVTable, missing-method
(SVTable-class), 38
- points.GEVAGroupedSummary
(GEVAGroupedSummary-class), 27
- points.GEVAGroupSet
(GEVAGroupSet-class), 28
- points.GEVAResults (GEVAResults-class), 34
- points.SVTable (SVTable-class), 38
- qareasizes (generics), 4
- qareasizes, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- qcount (generics), 4
- qcount, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- qindexes (generics), 4
- qindexes, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- quantiles (generics), 4
- quantiles, GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 27
- quantiles, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- quantiles, GEVAResults-method
(GEVAResults-class), 34
- quantiles, GEVASummary-method
(GEVASummary-class), 35
- quantiles.method, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- regular expressions, 18
- results.table (generics), 4
- results.table, GEVAResults-method
(GEVAResults-class), 34
- scores (generics), 4
- scores, GEVAGroupSet, character-method
(GEVAGroupSet-class), 28
- scores, GEVAGroupSet, missing-method
(GEVAGroupSet-class), 28
- show, GEVACluster-method
(GEVACluster-class), 26
- show, GEVAGroupedSummary-method
(GEVAGroupedSummary-class), 27
- show, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- show, GEVAInput-method
(GEVAInput-class), 30
- show, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- show, GEVAQuantilesAdjusted-method
(GEVAQuantilesAdjusted-class), 33
- show, GEVAResults-method
(GEVAResults-class), 34
- show, GEVASummary-method
(GEVASummary-class), 35
- show, SVAttribute-method
(SVAttribute-class), 37
- show, SVTable-method (SVTable-class), 38
- show, TypedList-method
(TypedList-class), 41
- stats::mad(), 25
- stats::median(), 25
- stats::p.adjust.methods, 11
- stats::sd(), 25
- stats::var(), 25
- summary.SVAttribute
(SVAttribute-class), 37
- summary.SVTable (SVTable-class), 38
- sv (generics), 4
- sv, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- sv, GEVAResults-method
(GEVAResults-class), 34
- sv, SVAttribute-method
(SVAttribute-class), 37
- sv, SVTable-method (SVTable-class), 38
- sv.data, GEVAGroupSet-method
(GEVAGroupSet-class), 28
- sv.data, GEVAResults-method
(GEVAResults-class), 34
- sv.data, SVAttribute-method
(SVAttribute-class), 37
- sv.data, SVTable-method (SVTable-class), 38
- sv.scores, GEVAQuantiles-method
(GEVAQuantiles-class), 31
- svattr (generics), 4
- svattr, character, character-method
(SVAttribute-class), 37
- svattr, integer, integer-method
(SVAttribute-class), 37
- svattr, numeric, numeric-method

- (SVAttribute-class), 37
- SVAttribute, 37
- SVAttribute (SVAttribute-class), 37
- SVAttribute-class, 37
- SVChrAttribute (SVAttribute-class), 37
- SVChrAttribute-class
 - (SVAttribute-class), 37
- SVIntAttribute, 32, 33
- SVIntAttribute (SVAttribute-class), 37
- SVIntAttribute-class
 - (SVAttribute-class), 37
- SVNumAttribute, 32, 33
- SVNumAttribute (SVAttribute-class), 37
- SVNumAttribute-class
 - (SVAttribute-class), 37
- SVTable, 7, 9, 13, 21, 27, 28, 32, 33, 35, 36, 38
- SVTable (SVTable-class), 38
- svtable (SVTable-class), 38
- SVTable-class, 38
- tail.GEVAInput (GEVAInput-class), 30
- tail.SVTable (SVTable-class), 38
- top.genes, 40
- top.genes(), 12
- typed.list (TypedList-class), 41
- TypedList, 6, 27, 33, 41
- TypedList-class, 41
- utils::read.table, 18
- variation (generics), 4
- variation.SVAttribute
 - (SVAttribute-class), 37
- variation.SVTable (SVTable-class), 38
- with.SVTable (SVTable-class), 38