

Package ‘bclogit’

February 25, 2026

Title Conditional Logistic Regression

Version 1.0

Author Adam Kapelner [aut, cre] (ORCID:
<<https://orcid.org/0000-0001-5985-6792>>),
Jacob Tennenbaum [aut] (ORCID: <<https://orcid.org/0009-0006-1408-5035>>)

Maintainer Adam Kapelner <kapelner@qc.cuny.edu>

Description Performs inference for Bayesian conditional logistic regression with informative priors built from the concordant pair data. We include many options to build the priors. And we include many options during the inference step for estimation, testing and confidence set creation. For details, see Kapelner and Tennenbaum (2026) ``Improved Conditional Logistic Regression using Information in Concordant Pairs with Software" <[doi:10.48550/arXiv.2602.08212](https://doi.org/10.48550/arXiv.2602.08212)>.

SystemRequirements GNU make

License GPL-3

Encoding UTF-8

LazyData true

Depends R (>= 4.0), Rcpp (>= 1.0.14)

Imports checkmate, coda, fastLogisticRegressionWrap, geepack, glmmTMB,
methods, RcppParallel (>= 5.0.1), rstan (>= 2.18.1), rstantools
(>= 2.6.0)

Suggests testthat (>= 3.0.0), survival, ggdist, data.table

LinkingTo BH (>= 1.66.0), Rcpp (>= 0.12.0), RcppEigen (>= 0.3.3.3.0),
RcppParallel (>= 5.0.1), rstan (>= 2.18.1), StanHeaders (>= 2.18.0)

URL https://github.com/Tennenbaum-J/bclogit_package_and_paper_repo

BugReports https://github.com/Tennenbaum-J/bclogit_package_and_paper_repo/issues

RoxygenNote 7.3.3

Biarch true

NeedsCompilation yes

Repository CRAN

Date/Publication 2026-02-25 10:00:14 UTC

Contents

bclogit-package	2
bclogit.formula	3
clogit.default	6
coef.bclogit	9
coef.clogit_bclogit	10
confint.bclogit	10
fhs	11
formula.bclogit	13
print.summary.bclogit	13
print.summary.clogit_bclogit	14
summary.bclogit	14
summary.clogit_bclogit	15
vcov.bclogit	16
vcov.clogit_bclogit	17

Index	18
--------------	-----------

bclogit-package	<i>Bayesian Conditional Logistic Regression with Concordant Pairs</i>
-----------------	---

Description

bclogit

Details

Fits a conditional logistic regression model to incidence data. Allows for use of the concordant pairs in the fitting.

Author(s)

Jacob Tennenbaum \email{Jacob.Tennenbaum51@gmail.cuny.edu}

Adam Kapelner \email{kapelner@qc.cuny.edu}

References

Jacob Tennenbaum and Adam Kapelner (2026). "Improved Conditional Logistic Regression using Information

See Also

Useful links:

- https://github.com/Tennenbaum-J/bclogit_package_and_paper_repo

bclogit.formula	<i>Initialize a new bclogit model</i>
-----------------	---------------------------------------

Description

This function fits a Bayesian conditional logistic regression model, incorporating information from concordant pairs to improve estimation.

Usage

```
## S3 method for class 'formula'
bclogit(
  formula,
  data,
  treatment = NULL,
  strata = NULL,
  subset = NULL,
  na.action = NULL,
  concordant_method = "GLM",
  prior_type = "Naive",
  chains = 4,
  return_raw_stan_output = FALSE,
  prior_variance_treatment = 100,
  stan_refresh = 0,
  ...
)

bclogit(
  formula,
  data,
  treatment = NULL,
  strata = NULL,
  subset = NULL,
  na.action = NULL,
  concordant_method = "GLM",
  prior_type = "Naive",
  chains = 4,
  return_raw_stan_output = FALSE,
  prior_variance_treatment = 100,
  stan_refresh = 0,
  ...
)

## Default S3 method:
bclogit(
  formula = NULL,
  data = NULL,
```

```

treatment = NULL,
strata = NULL,
subset = NULL,
na.action = NULL,
concordant_method = "GLM",
prior_type = "Naive",
chains = 4,
return_raw_stan_output = FALSE,
prior_variance_treatment = 100,
stan_refresh = 0,
...,
y = NULL,
X = NULL,
treatment_name = NULL,
call = NULL
)

```

Arguments

formula	For the formula method, a symbolic description of the model to be fitted.
data	A data.frame, data.table, or model.matrix containing the variables (optional for formula method).
treatment	Optional vector specifying the treatment variable (required for default method, or can be specified in formula method).
strata	Vector specifying the strata (matched pairs).
subset	An optional vector specifying a subset of observations.
na.action	A function which indicates what should happen when the data contain NAs.
concordant_method	The method to use for fitting the concordant pairs and reservoir. Options are "GLM", "GEE", and "GLMM".
prior_type	The type of prior to use for the discordant pairs. Options are "Naive", "G prior", "PMP", and "Hybrid".
chains	Number of chains for Stan sampling. Default is 4.
return_raw_stan_output	Logical; if TRUE, the raw Stan posterior samples (iterations x chains x parameters) are stored in the returned object. Default FALSE.
prior_variance_treatment	Prior variance for the treatment coefficient in the covariance matrix Sigma_con. Default is 100.
stan_refresh	How often Stan reports sampling progress (in iterations). Default is 0 (silent). Set to a positive integer (e.g., 1 or 100) to see progress.
...	Additional arguments passed to rstan::sampling (e.g., iter, warmup, thin, seed, control).
y	For the default method, a binary (0,1) vector containing the response of each subject.

X	A data.frame, data.table, or model.matrix containing the variables.
treatment_name	Optional string name for the treatment variable.
call	Optional call object to store in the result.

Value

An object of class "bclogit".

A list of class bclogit containing:

coefficients	Estimated coefficients (posterior means).
var	Variance-covariance matrix of coefficients.
model	The fitted Stan model object.
posterior_samples	Raw posterior samples as a 3D array (iterations x chains x parameters) from <code>rstan::extract(model, permuted = FALSE)</code> . Only populated when <code>return_raw_stan_output = TRUE</code> ; NULL otherwise.
concordant_model	The fitted model object for the concordant pairs/reservoir (GLM/GEE/GLMM).
matched_data	The processed matched pairs data from the premodeling step.
prior_info	Information about the prior derived from concordant pairs.
call	The function call.
terms	The model terms.
num_discordant	Number of discordant pairs used.
num_concordant	Number of concordant pairs/reservoir entries used.

A list of class "bclogit" containing:

coefficients	Estimated coefficients (posterior means).
var	Variance-covariance matrix of the coefficients (posterior covariance).
model	The fitted Stan model object for the discordant pairs.
posterior_samples	Raw posterior samples as a 3D array (iterations x chains x parameters) from <code>rstan::extract(model, permuted = FALSE)</code> . Only populated when <code>return_raw_stan_output = TRUE</code> ; NULL otherwise.
concordant_model	The fitted model object for the concordant pairs (GLM, GEE, or GLMM).
matched_data	The processed matched pairs data from the C++ pre-modeling step.
prior_info	A list with elements <code>mu</code> (prior mean vector) and <code>Sigma</code> (prior covariance matrix) derived from the concordant pairs model.
call	The function call.
terms	The model terms.
xlevels	Factor level information (always NULL for this method).
n	Total number of observations.

num_discordant Number of discordant pairs used for fitting.
 num_concordant Number of concordant pairs used for the prior.
 X_model_matrix_col_names
 Column names of the covariate model matrix.
 treatment_name Name of the treatment variable.

Methods (by class)

- `bclogit(formula)`: Formula method
- `bclogit(default)`: Default method for matrix/data input.

See Also

[summary.bclogit](#), [confint.bclogit](#), [vcov.bclogit](#), [coef.bclogit](#)

Examples

```
# Example usage
data("fhs")
fit <- bclogit(PREVHYP ~ TOTCHOL + CIGPDAY + BMI + HEARTRTE,
  data = fhs, treatment = PERIOD, strata = RANDID)
summary(fit)
```

clogit.default

Frequentist Conditional Logistic Regression

Description

Fits a conditional logistic regression model for matched pairs using the discordant-pair GLM trick. This is a fast frequentist alternative to `bclogit`.

Usage

```
## Default S3 method:
clogit(
  formula = NULL,
  data = NULL,
  treatment = NULL,
  strata = NULL,
  subset = NULL,
  na.action = NULL,
  do_inference_on_var = "all",
  ...,
  y = NULL,
  X = NULL,
  treatment_name = NULL,
```

```

    call = NULL
  )

## S3 method for class 'formula'
clogit(
  formula,
  data,
  treatment = NULL,
  strata = NULL,
  subset = NULL,
  na.action = NULL,
  do_inference_on_var = "all",
  ...
)

clogit(
  formula,
  data,
  treatment = NULL,
  strata = NULL,
  subset = NULL,
  na.action = NULL,
  do_inference_on_var = "all",
  ...
)

```

Arguments

formula	For the formula method, a symbolic description of the model.
data	A data frame containing the variables (for formula method).
treatment	Vector specifying the treatment variable.
strata	Vector specifying the strata (matched pairs).
subset	An optional vector specifying a subset of observations to be used in the fitting process.
na.action	A function which indicates what should happen when the data contain NAs.
do_inference_on_var	Which variable(s) to compute standard errors for. "all" (default) computes SEs for all coefficients. An integer j computes the SE only for the jth coefficient (1 = treatment, then covariates in order). "none" skips inference entirely.
...	Additional arguments passed to methods.
y	For the default method, a binary (0,1) response vector.
X	A data.frame, data.table, or model.matrix containing the variables.
treatment_name	Optional string name for the treatment variable.
call	Optional call object to store in the result.

Value

A list of class "clogit_bclogit" containing:

coefficients	Estimated coefficients (posterior means).
var	Variance-covariance matrix of the coefficients (diagonal, built from standard errors). NULL when do_inference_on_var is not "all".
flr_model	The fitted fast logistic regression model object returned by fastLogisticRegressionWrap::fast_logis
call	The function call.
terms	The model terms.
n	Total number of observations.
num_discordant	Number of discordant pairs used for fitting.
num_concordant	Number of concordant pairs.
X_model_matrix_col_names	Column names of the covariate model matrix.
treatment_name	Name of the treatment variable.
se	Standard errors of the coefficients.
z	Z-statistics for each coefficient.
pval	Approximate p-values for each coefficient.
do_inference_on_var	The value of the do_inference_on_var argument.

An object of class "clogit_bclogit".

An object of class "clogit_bclogit".

Methods (by class)

- clogit(default): Default method for matrix/data input.
- clogit(formula): Formula method

See Also

[bclogit](#), [summary.clogit_bclogit](#)

Examples

```
data("fhs")
fit <- clogit(PREHVYP ~ TOTCHOL + CIGPDAY + BMI + HEARTRTE,
  data = fhs, treatment = PERIOD, strata = RANDID)
summary(fit)
n <- 200
dat <- data.frame(
  y = rbinom(n, 1, 0.5),
  x1 = rnorm(n),
  treatment = rep(c(0, 1), n / 2),
  strata = rep(1:(n / 2), each = 2)
)
```

```
fit <- clogit(y ~ x1, data = dat, treatment = treatment, strata = strata)
# Inference on treatment only (faster):
fit2 <- clogit(y ~ x1, data = dat, treatment = treatment, strata = strata,
              do_inference_on_var = 1)
n <- 200
dat <- data.frame(
  y = rbinom(n, 1, 0.5),
  x1 = rnorm(n),
  x2 = rnorm(n),
  treatment = rep(c(0, 1), n / 2),
  strata = rep(1:(n / 2), each = 2)
)
fit <- clogit(y ~ x1 + x2, data = dat, treatment = treatment, strata = strata)
summary(fit)
coef(fit)
vcov(fit)
```

`coef.bclogit`*Extract coefficients from a bclogit model*

Description

Extract coefficients from a bclogit model

Usage

```
## S3 method for class 'bclogit'
coef(object, ...)
```

Arguments

<code>object</code>	A bclogit object.
<code>...</code>	Additional arguments.

Value

Numeric vector of coefficients.

`coef.clogit_bclogit` *Extract coefficients from a clogit_bclogit model*

Description

Extract coefficients from a clogit_bclogit model

Usage

```
## S3 method for class 'clogit_bclogit'
coef(object, ...)
```

Arguments

`object` A clogit_bclogit object.
`...` Additional arguments.

Value

Numeric vector of coefficients.

Examples

```
n <- 200
dat <- data.frame(
  y = rbinom(n, 1, 0.5), x1 = rnorm(n),
  treatment = rep(c(0, 1), n / 2),
  strata = rep(1:(n / 2), each = 2)
)
fit <- clogit(y ~ x1, data = dat, treatment = treatment, strata = strata)
coef(fit)
```

`confint.bclogit` *Credible Intervals for bclogit Parameters*

Description

Computes Bayesian credible intervals for the model parameters.

Usage

```
## S3 method for class 'bclogit'
confint(object, parm, level = 0.95, type = c("HPD_one", "CR", "HPD_many"), ...)
```

Arguments

object	A <code>bclogit</code> object.
parm	A specification of which parameters to be given credible intervals, either a vector of numbers or a vector of names. If missing, all parameters are considered.
level	The confidence level required (default 0.95).
type	Type of interval to compute: "HPD_one" (default unimodal HPD interval via coda), "CR" (equal-tailed credible region), "HPD_many" (multimodal HPD interval via ggdist).
...	Additional arguments.

Value

A matrix with columns `lower` and `upper`. For "HPD_many", a parameter may appear on multiple rows when the interval is disjoint. The matrix has a `Probability` attribute.

fhs	<i>Framingham Heart Study Dataset</i>
-----	---------------------------------------

Description

A subset of the Framingham Heart Study data.

Usage

fhs

Format

A data frame with 5944 rows and 39 variables:

RANDID Unique identification number for each participant. (This is the strata for the matched pairs).

PERIOD Examination Cycle where 0 = baseline, 1 = endpoint (the treatment variable)

SEX Participant sex (1 = Male, 2 = Female).

TOTCHOL Total serum cholesterol (mg/dL).

AGE Age at exam (years).

SYSBP Systolic blood pressure (mmHg).

DIABP Diastolic blood pressure (mmHg).

CURSMOKE Current smoking status (0 = No, 1 = Yes).

CIGPDAY Number of cigarettes smoked per day.

BMI Body Mass Index (kg/m²).

DIABETES Diabetes status (0 = No, 1 = Yes).

BPMEDS Use of Anti-hypertensive medication (0 = No, 1 = Yes).

HEARTRTE Heart rate (beats/minute).
GLUCOSE Fast blood glucose (mg/dL).
educ Education level.
PREVCHD Prevalence of Coronary Heart Disease.
PREVAP Prevalence of Angina Pectoris.
PREVMI Prevalence of Myocardial Infarction.
PREVSTRK Prevalence of Stroke.
PREVHYP Prevalence of Hypertension.
TIME Number of days since baseline exam.
HDLC High Density Lipoprotein Cholesterol.
LDLC Low Density Lipoprotein Cholesterol.
DEATH Death status.
ANGINA Angina Pectoris status.
HOSPMI Hospitalized Myocardial Infarction.
MI_FCHD Myocardial Infarction or Fatal Coronary Heart Disease.
ANYCHD Any Coronary Heart Disease event.
STROKE Stroke status.
CVD Cardiovascular Disease status.
HYPERTEN Hypertension status.
TIMEAP Time to Angina Pectoris.
TIMEMI Time to Myocardial Infarction.
TIMEMIFC Time to Myocardial Infarction or Fatal CHD.
TIMECHD Time to Any CHD.
TIMESTRK Time to Stroke.
TIMECVD Time to Cardiovascular Disease.
TIMEDTH Time to Death.
TIMEHYP Time to Hypertension.

Details

This dataset was constructed by running the following code:

```

pacman::p_load(riskCommunicator, data.table)
data("framingham")
D = data.table(framingham)
D = D[!is.na(CIGPDAY)] #we drop missing data in covariates
D = D[!is.na(BMI)]
D = D[!is.na(HEARTRTE)]
D = D[!is.na(TOTCHOL)]
Dba = D[PERIOD %in% c(1,3)] #we drop intermediate periods so we have matched pairs
Dba[PERIOD == 1, PERIOD := 0]
Dba[PERIOD == 3, PERIOD := 1]
Dba[, num_periods_per_id := .N, by = RANDID]
Dba = Dba[num_periods_per_id == 2] #we drop intermediate periods so we have matched pairs
Dba[, num_periods_per_id := NULL]
  
```

Source

<https://biolincc.nhlbi.nih.gov/teaching/>

formula.bclogit	<i>Extract model formula</i>
-----------------	------------------------------

Description

Extract model formula

Usage

```
## S3 method for class 'bclogit'
formula(x, ...)
```

Arguments

x	A bclogit object.
...	Additional arguments.

Value

The formula used in the model.

print.summary.bclogit	<i>Print summary of a bclogit model</i>
-----------------------	---

Description

Print summary of a bclogit model

Usage

```
## S3 method for class 'summary.bclogit'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	A summary.bclogit object.
digits	Number of significant digits to print.
...	Additional arguments.

Value

Invisibly returns x.

```
print.summary.clogit_bclogit
      Print summary of a clogit_bclogit model
```

Description

Print summary of a clogit_bclogit model

Usage

```
## S3 method for class 'summary.clogit_bclogit'
print(x, digits = max(3, getOption("digits") - 3), ...)
```

Arguments

x	A summary.clogit_bclogit object.
digits	Number of significant digits to print.
...	Additional arguments.

Value

Invisibly returns x.

Examples

```
n <- 200
dat <- data.frame(
  y = rbinom(n, 1, 0.5), x1 = rnorm(n),
  treatment = rep(c(0, 1), n / 2),
  strata = rep(1:(n / 2), each = 2)
)
fit <- clogit(y ~ x1, data = dat, treatment = treatment, strata = strata)
print(summary(fit))
```

```
summary.bclogit      Summarize a bclogit model
```

Description

Summarize a bclogit model

Usage

```
## S3 method for class 'bclogit'
summary(object, level = 0.95, inference_method = "HPD_one", ...)
```

Arguments

object	A <code>bcligit</code> object.
level	Confidence level for credible intervals (default 0.95).
inference_method	Method used for both the displayed confidence set bounds and the p-value (computed via bisection over alpha). Options are: "HPD_one" (default) uses unimodal HPD intervals (C++) with 20 bisection iterations, "HPD_many" uses <code>ggdist::hdi</code> which supports disjoint (multimodal) HPD regions, with 50 bisection iterations (requires the ggdist package). Confidence set bounds are shown when the HPD is a single interval; if disjoint, they are set to NA (use <code>confint.bcligit</code> with <code>type = "HPD_many"</code> to see all intervals), "CR" uses equal-tailed credible intervals (quantile-based, C++) with 20 bisection iterations.
...	Additional arguments (not used).

Value

A list of class "summary.bcligit" containing:

call	The original function call.
coefficients	A matrix with one row per parameter and columns for the posterior mean estimate, posterior median estimate, standard error, lower and upper credible interval bounds, optionally <code>Rhat</code> and <code>n_eff</code> convergence diagnostics (when available from Stan), and $\Pr(tx \neq 0)$ (the Bayesian p-value).
num_discordant	Number of discordant pairs used for fitting.
num_concordant	Number of concordant pairs used for the prior.
level	The credible interval level used.
inference_method	The inference method used for interval and p-value computation.
prior_info	A list with elements <code>mu</code> and <code>Sigma</code> describing the prior derived from the concordant pairs model.
treatment_name	Name of the treatment variable.

```
summary.clogit_bcligit
```

Summarize a clogit_bcligit model

Description

Summarize a `clogit_bcligit` model

Usage

```
## S3 method for class 'clogit_bcligit'
summary(object, ...)
```

Arguments

object A clogit_bclogit object.
 ... Additional arguments (not used).

Value

A list of class "summary.clogit_bclogit" containing:

call The original function call.
 coefficients A matrix with one row per parameter and columns Estimate, Std. Error, z value, and Pr(>|z|).
 num_discordant Number of discordant pairs used for fitting.
 num_concordant Number of concordant pairs.
 n Total number of observations.
 treatment_name Name of the treatment variable.
 do_inference_on_var
 The value of the do_inference_on_var argument.

vcov.bclogit

Extract variance-covariance matrix from a bclogit model

Description

Extract variance-covariance matrix from a bclogit model

Usage

```
## S3 method for class 'bclogit'
vcov(object, ...)
```

Arguments

object A bclogit object.
 ... Additional arguments.

Value

A matrix of the estimated covariance of the coefficients.

vcov.clogit_bclgfit *Extract variance-covariance matrix from a clogit_bclgfit model*

Description

Extract variance-covariance matrix from a clogit_bclgfit model

Usage

```
## S3 method for class 'clogit_bclgfit'  
vcov(object, ...)
```

Arguments

object	A clogit_bclgfit object.
...	Additional arguments.

Value

A matrix of the estimated covariance of the coefficients.

Index

- * **Conditional**

- bclogit-package, 2

- * **Logistic**

- bclogit-package, 2

- * **Regression**

- bclogit-package, 2

- * **datasets**

- fhs, 11

bclogit, 6, 8

bclogit(bclogit.formula), 3

bclogit-package, 2

bclogit.formula, 3

clogit(clogit.default), 6

clogit.default, 6

coef.bclogit, 6, 9

coef.clogit_bclogit, 10

confint.bclogit, 6, 10, 15

fhs, 11

formula.bclogit, 13

print.summary.bclogit, 13

print.summary.clogit_bclogit, 14

summary.bclogit, 6, 14

summary.clogit_bclogit, 8, 15

vcov.bclogit, 6, 16

vcov.clogit_bclogit, 17