

Package ‘gge’

July 22, 2025

Type Package

Title Genotype Plus Genotype-by-Environment Biplots

Version 1.9

Description Create biplots for GGE (genotype plus genotype-by-environment) and GGB (genotype plus genotype-by-block-of-environments) models. See Laffont et al. (2013) <[doi:10.2135/cropsci2013.03.0178](https://doi.org/10.2135/cropsci2013.03.0178)>.

License MIT + file LICENSE

URL <https://kwstat.github.io/gge/>, <http://kwstat.github.io/gge/>

BugReports <https://github.com/kwstat/gge/issues>

Imports nipals, reshape2

Suggests agridat, knitr, lattice, rgl, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.2

NeedsCompilation no

Author Kevin Wright [aut, cre, cph] (ORCID: <<https://orcid.org/0000-0002-0617-8673>>), Jean-Louis Laffont [aut]

Maintainer Kevin Wright <kw.stat@gmail.com>

Repository CRAN

Date/Publication 2024-10-28 20:20:06 UTC

Contents

gge	2
RedGrayBlue	6
Index	7

`gge`*GGE and GGB biplots*

Description

Fit a GGE (genotype + genotype * environment) model and display the results.

Usage

```
gge(x, ...)  
  
## S3 method for class 'data.frame'  
gge(x, formula, gen.group = NULL, env.group = NULL, ggb = FALSE, ...)  
  
## S3 method for class 'formula'  
gge(formula, data, gen.group = NULL, env.group = NULL, ggb = FALSE, ...)  
  
## S3 method for class 'matrix'  
gge(  
  x,  
  center = TRUE,  
  scale = TRUE,  
  gen.group = NULL,  
  env.group = NULL,  
  ggb = FALSE,  
  comps = c(1, 2),  
  method = "svd",  
  ...  
)  
  
## S3 method for class 'gge'  
plot(x, main = substitute(x), ...)  
  
## S3 method for class 'gge'  
biplot(  
  x,  
  main = substitute(x),  
  subtitle = "",  
  xlab = "auto",  
  ylab = "auto",  
  cex.gen = 0.6,  
  cex.env = 0.5,  
  col.gen = "darkgreen",  
  col.env = "orange3",  
  pch.gen = 1,  
  lab.env = TRUE,  
  comps = 1:2,
```

```

    flip = "auto",
    origin = "auto",
    res.vec = TRUE,
    hull = FALSE,
    zoom.gen = 1,
    zoom.env = 1,
    ...
)

biplot3d(x, ...)

## S3 method for class 'gge'
biplot3d(
  x,
  cex.gen = 0.6,
  cex.env = 0.5,
  col.gen = "darkgreen",
  col.env = "orange3",
  comps = 1:3,
  lab.env = TRUE,
  res.vec = TRUE,
  zoom.gen = 1,
  ...
)

```

Arguments

x	A matrix or data.frame.
...	Other arguments (e.g. maxiter, gramschmidt)
formula	A formula
gen.group	genotype group
env.group	env group
ggb	If TRUE, fit a GGB biplot model.
data	Data frame
center	If TRUE, center values for each environment
scale	If TRUE, scale values for each environment
comps	Principal components to use for the biplot. Default c(1,2).
method	method used to find principal component directions. Either "svd" or "nipals".
main	Title, by default the name of the data. Use NULL to suppress the title.
subtitle	Subtitle to put in front of options. Use NULL to suppress the subtitle.
xlab	Label along axis. Default "auto" shows percent of variation explained. Use NULL to suppress.
ylab	Label along axis. Default "auto" shows percent of variation explained. Use NULL to suppress.

<code>cex.gen</code>	Character expansion for genotype labels, default 0.6. Use 0 to omit genotype labels.
<code>cex.env</code>	Character expansion for environment labels/symbols. Use <code>lab.env=FALSE</code> to omit labels.
<code>col.gen</code>	Color for genotype labels. May be a single color for all genotypes, or a vector of colors for each genotype.
<code>col.env</code>	Color for environments. May be a single color for all environments, or a vector of colors for each environment.
<code>pch.gen</code>	Plot character for genotypes
<code>lab.env</code>	Label environments if TRUE.
<code>flip</code>	If "auto" then each axis is flipped so that the genotype ordinate is positively correlated with genotype means. Can also be a vector like <code>c(TRUE,FALSE)</code> for manual control.
<code>origin</code>	If "auto", the plotting window is centered on genotypes, otherwise the origin is at the middle of the window.
<code>res.vec</code>	If TRUE, for each group, draw residual vectors from the mean of the locs to the individual locs.
<code>hull</code>	If TRUE, show a which-won-where polygon.
<code>zoom.gen</code>	Zoom factor for manual control of genotype <code>xlim,ylim</code> . The default is 1. Values less than 1 may be useful if genotype names are long.
<code>zoom.env</code>	Zoom factor for manual control of environment <code>xlim,ylim</code> . The default is 1. Values less than 1 may be useful if environment names are long. Not used for 3D biplots.

Details

If there is replication in G*E, then the replications are averaged together before constructing the biplot.

The singular value decomposition of `x` is used to calculate the principal components for the biplot. Missing values are NOT allowed.

The argument `method` can be either `'svd'` for complete-data or `'nipals'` for missing-data.

Value

A list of class `gge` containing:

<code>x</code>	The filled-in data
<code>x.orig</code>	The original data
<code>genCoord</code>	genotype coordinates
<code>locCoord</code>	loc coordinates
<code>blockCoord</code>	block coordinates
<code>gen.group</code>	If not NULL, use this to specify a column of the <code>data.frame</code> to classify genotypes into groups.

env.group	If not NULL, use this to specify a column of the data.frame to classify environments into groups.
ggb	If TRUE, create a GGB biplot
genMeans	genotype means
mosdat	mosaic plot data
R2	variation explained by each PC
center	Data centered?
scale	Data scaled?
method	Method used to calculate principal components.
pctMiss	Percent of x that is missing values
maxPCs	Maximum number of PCs

Author(s)

Kevin Wright, Jean-Louis Laffont
Jean-Louis Laffont, Kevin Wright

References

Jean-Louis Laffont, Kevin Wright and Mohamed Hanafi (2013). Genotype + Genotype x Block of Environments (GGB) Biplots. *Crop Science*, 53, 2332-2341. doi:10.2135/cropsci2013.03.0178.

Kroonenberg, Pieter M. (1997). *Introduction to Biplots for GxE Tables*, Research Report 51, Centre for Statistics, The University of Queensland, Brisbane, Australia. <https://three-mode.leidenuniv.nl/document/biplot.pdf>

Yan, W. and Kang, M.S. (2003). *GGE Biplot Analysis*. CRC Press.

Examples

```
# Example 1. Data is a data.frame in 'matrix' format
B <- matrix(c(50, 67, 90, 98, 120,
             55, 71, 93, 102, 129,
             65, 76, 95, 105, 134,
             50, 80, 102, 130, 138,
             60, 82, 97, 135, 151,
             65, 89, 106, 137, 153,
             75, 95, 117, 133, 155), ncol=5, byrow=TRUE)
rownames(B) <- c("G1", "G2", "G3", "G4", "G5", "G6", "G7")
colnames(B) <- c("E1", "E2", "E3", "E4", "E5")

library(gge)
m1 = gge(B)
plot(m1)
biplot(m1, main="Example biplot")
# biplot3d(m1)

if(require(agridat)){
  # crossa.wheat biplot
```

```
# Specify env.group as column in data frame
data(crossa.wheat)
dat2 <- crossa.wheat
m2 <- gge(dat2, yield~gen*loc, env.group=locgroup, scale=FALSE)
plot(m2)
biplot(m2, lab.env=TRUE, main="crossa.wheat")
# biplot3d(m2)
}
```

RedGrayBlue

Function to create a Red-Gray-Blue palette

Description

A function to create a Red-Gray-Blue palette.

Usage

```
RedGrayBlue(n)
```

Arguments

n Number of colors to create

Details

Using gray instead of white allows missing values to appear as white (actually, transparent).

Value

A vector of n colors.

Author(s)

Kevin Wright

Examples

```
pie(rep(1,11), col=RedGrayBlue(11))
title("RedGrayBlue(11)")
```

Index

`biplot.gge` (`gge`), 2
`biplot3d` (`gge`), 2

`gge`, 2
`gge-package` (`gge`), 2
`gge.data.frame` (`gge`), 2
`gge.formula` (`gge`), 2
`gge.matrix` (`gge`), 2

`plot.gge` (`gge`), 2

`RedGrayBlue`, 6