Package 'GEEmediate'

January 20, 2025

Title Mediation Analysis for Generalized Linear Models Using the Difference Method

Description Causal mediation analysis for a single exposure/treatment and a single mediator, both allowed to be either continuous or binary. The package implements the difference method and provides point and interval estimates as well as testing for the natural direct and indirect effects and the mediation proportion. Nevo, Xiao and Spiegelman (2017) <doi:10.1515/ijb-2017-0006>.

Version 1.1.4

Date 2023-01-16

Depends R (>= 3.3.0)

Imports gee

License GPL (>= 3)

NeedsCompilation no

RoxygenNote 7.2.0

BugReports https://github.com/daniel258/GEEMediate/issues

Encoding UTF-8

Author Daniel Nevo [aut, cre]

Maintainer Daniel Nevo <danielnevo@gmail.com>

Repository CRAN

Date/Publication 2023-01-16 16:50:05 UTC

Contents

GEEmediate		2
------------	--	---

4

Index

GEEmediate

Description

Estimation of natural direct and indirect effects for generalized linear models. The function utilizes a data-duplication algorithm to fit marginal and conditional GLMs in a way that allow for consistent variance estimation. The function produces point estimates, confidence intervals and p-values for the natural indirect effect and the mediation proportion

Usage

```
GEEmediate(
   formula,
   exposure,
   mediator,
   df,
   family = gaussian,
   corstr = "independence",
   conf.level = 0.95,
   surv = F,
   pres = "sep",
   niealternative = "two-sided",
   ....
)
```

Arguments

formula	A formula expression as for other regression models, of the form response \sim predictors. See the documentation of 1m and formula for details. predictors should include exposure/treatment and mediator.
exposure	The exposure (string).
mediator	The mediator (string).
df	A name of a data frame where all variables mentioned in formula are stored.
family	A family object to be used in gee: a list of functions and expressions for defin- ing link and variance functions see the gee documentation. Default is gaussian. See also gee and glm.
corstr	A working correlation structure. See gee and glm.
conf.level	Confidence level for all confidence intervals (default 0.95)
surv	Is the outcome survival (not supported)
pres	Presentation of the coefficient tables. "tog" for a single table, "sep" for two separated tables.
niealternative	Alternative hypothesis for testing that the nie=0. Either "two-sided" (default) or "one-sided" for alternative nie>0.
	Further arguments for the gee call.

GEEmediate

Value

The output contains the following components:

call	The call.
GEE.fit	Results of fitting the GEE for the duplicated data.
nie	The natural indirect effect estimate. NIE and NDE are reported on the coefficient scale
nie.pval	P-value for tesing mediation using the NIE.
nde	The natural direct effect estimate.
nie.ci	Confidence interval in for the NIE in confidence level conf.level.
pm	The mediation proportion estimate.
pm.pval	P-value for tesing one-sided mediation using the mediation proportion.
pm.ci	Confidence interval for the mediation proportion in confidence level conf.level.

References

Nevo, Liao and Spiegelman, *Estimation and infernece for the mediation proportion*, International Journal of Biostatistics (2017+)

Examples

```
## Not run:
SimNormalData <- function(n,beta1.star = 1, p = 0.3, rho =0.4, inter = 0)
{
beta2 <- (p/rho)*beta1.star
beta1 <- (1-p)*beta1.star</pre>
 XM <- MASS::mvrnorm(n, mu = c(0,0), Sigma = matrix(c(1,rho,rho,1),2,2))</pre>
 X <- XM[,1]
 M <- XM[,2]
 beta <- c(inter, beta1, beta2)</pre>
 print(beta)
 Y <- cbind(rep(1,n),XM)%*%beta+rnorm(n,0,sd = 1)</pre>
 return(data.frame(X = X, M = M, Y = Y))
}
set.seed(314)
df <- SimNormalData(500)</pre>
GEEmediate(Y ~ X + M, exposure = "X", mediator = "M", df = df)
```

End(Not run)

Index

formula, 2
gee, 2
GEEmediate, 2
glm, 2