

Package ‘TGST’

January 20, 2025

Title Targeted Gold Standard Testing

Version 1.0

Description Functions for implementing the targeted gold standard (GS) testing. You provide the true disease or treatment failure status and the risk score, tell ‘TGST’ the availability of GS tests and which method to use, and it returns the optimal tripartite rules. Please refer to Liu et al. (2013) <[doi:10.1080/01621459.2013.810149](https://doi.org/10.1080/01621459.2013.810149)> for more details.

Depends R (>= 3.2.0)

License GPL-3

LazyData true

Suggests rmarkdown

VignetteBuilder knitr

Imports ggplot2, methods, graphics, knitr

RoxygenNote 7.1.0

NeedsCompilation no

Author Yizhen Xu [aut, cre],
Tao Liu [aut]

Maintainer Yizhen Xu <yizhen_xu@alumni.brown.edu>

Repository CRAN

Date/Publication 2020-11-23 09:50:05 UTC

Contents

cal.AUC	2
Check.exp.tilt	3
CV.TGST	3
nonpar.fnr.fpr	4
nonpar.rules	5
Opt.nonpar.rule	6
Opt.semipar.rule	6
OptimalRule	7
Output-class	8

plot	8
ROC.nonpar	9
ROC.semipar	10
ROCAnalysis	10
Semi.par.rule	11
semipar.fnr.fpr	12
Simdata	13
summary	13
TGST	14
TGST-class	15
TGST.summ	15
Index	17

cal.AUC*Calculate AUC*

Description

This function gives you the AUC associated with the rules set.

Usage

```
cal.AUC(Z, S, l, u)
```

Arguments

Z	True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
S	Risk score.
l	Lower cutoff of all possible tripartite rules.
u	Upper cutoff of all possible tripartite rules.

Value

AUC.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
rules = nonpar.rules( Z, S, phi)
cal.AUC(Z,S,rules[,1],rules[,2])
```

Check.exp.tilt	<i>Check exponential tilt model assumption</i>
----------------	--

Description

This function provides graphical assessment to the suitability of the exponential tilt model for risk score in finding optimal tripartite rules by semiparametric approach.

$$g1(s) = \exp(\tilde{\beta}_0 + \beta_1 * s) * g0(s)$$

Usage

```
Check.exp.tilt(Z, S)
```

Arguments

- | | |
|---|---|
| Z | True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1). |
| S | Risk score. |

Value

Plot of empirical density for risk score S, joint empirical density for (S,Z=1) and (S,Z=0), and the density under the exponential tilt model assumption for (S,Z=1) and (S,Z=0).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
Check.exp.tilt( Z, S)
```

Description

This function allows you to compute the average of misdiagnoses rate for viral failure and the optimal risk under min- λ rules from K-fold cross-validation.

Usage

```
CV.TGST(Obj, lambda, K = 10)
```

Arguments

Obj	An object of class TGST.
lambda	A user-specified weight that reflects relative loss for the two types of misdiagnoses, taking value in [0, 1]. $Loss = \lambda * I(FN) + (1 - \lambda) * I(FP)$.
K	Number of folds in cross validation. The default is 10.

Value

Cross-validation results.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
Obj = TGST(Z, S, phi, method="nonpar")
lambda = 0.8
CV.TGST(Obj, lambda, K=10)
```

nonpar.fnr.fpr

Nonparametric FNR FPR of the rules

Description

This function gives you the nonparametric FNR and FPR associated with a given tripartite rule.

Usage

```
nonpar.fnr.fpr(Z, S, l, u)
```

Arguments

Z	True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
S	Risk score.
l	Lower cutoff of tripartite rule.
u	Upper cutoff of tripartite rule.

Value

Matrix with 2 columns. Each row is a set of nonparametric (FNR, FPR) on an associated tripartite rule.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
rules = nonpar.rules( Z, S, phi)
nonpar.fnr.fpr(Z,S,rules[1,1],rules[1,2])
```

nonpar.rules

Nonparametric Rules Set

Description

This function gives you all possible cutoffs $[l, u]$ for tripartite rules, by applying nonparametric search to the given data.

$$P(S \in [l, u]) \leq \phi$$

Usage

```
nonpar.rules(Z, S, phi)
```

Arguments

- | | |
|-----|---|
| Z | True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1). |
| S | Risk score. |
| phi | Percentage of patients taking viral load test. |

Value

Matrix with 2 columns. Each row is a possible tripartite rule, with output on lower and upper cutoff.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
nonpar.rules( Z, S, phi)
```

<code>Opt.nonpar.rule</code>	<i>Optimal Nonparametric Rule</i>
------------------------------	-----------------------------------

Description

This function gives you the optimal nonparametric tripartite rule that minimizes the min- λ rules.

Usage

```
Opt.nonpar.rule(Z, S, phi, lambda)
```

Arguments

<code>Z</code>	True disease status (No disease / treatment success coded as $Z=0$, diseased / treatment failure coded as $Z=1$).
<code>S</code>	Risk score.
<code>phi</code>	Percentage of patients taking viral load test.
<code>lambda</code>	A user-specified weight that reflects relative loss for the two types of misdiagnoses, taking value in $[0, 1]$. $Loss = \lambda * I(FN) + (1 - \lambda) * I(FP)$.

Value

Optimal nonparametric rule and its associated misclassification rates (FNR, FPR), optimal lambda risk, and total misclassification rate (TMR).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
lambda = 0.5
Opt.nonpar.rule( Z, S, phi, lambda)
```

<code>Opt.semipar.rule</code>	<i>Optimal Semiparametric Rule</i>
-------------------------------	------------------------------------

Description

This function gives you the optimal semiparametric tripartite rule that minimizes the min- λ rules.

Usage

```
Opt.semipar.rule(Z, S, phi, lambda)
```

Arguments

Z	True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
S	Risk score.
phi	Percentage of patients taking viral load test.
lambda	A user-specified weight that reflects relative loss for the two types of misdiagnoses, taking value in [0, 1]. $Loss = \lambda * I(FN) + (1 - \lambda) * I(FP)$.

Value

Optimal semiparametric rule and its associated misclassification rates (FNR, FPR), optimal lambda risk, and total misclassification rate (TMR).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
lambda = 0.5
Opt.semipar.rule( Z, S, phi, lambda)
```

OptimalRule

Optimal Tripartite Rule

Description

OptimalRule is the main function of TGST and it gives you the optimal tripartite rule that minimizes the min- λ risk based on the type of user selected approach. The function takes the risk score and true disease status from a training data set and returns the optimal tripartite rule under the specified proportion of patients able to take gold standard test.

Usage

```
OptimalRule(Obj, lambda)
```

Arguments

Obj	An object of class TGST.
lambda	A user-specified weight that reflects relative loss for the two types of misdiagnoses, taking value in [0, 1]. $Loss = \lambda * I(FN) + (1 - \lambda) * I(FP)$.

Value

Optimal tripartite rule.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
lambda = 0.5
Obj = TGST(Z, S, phi, method="nonpar")
OptimalRule(Obj, lambda)
```

Output-class	<i>Constructor of Output class</i>
--------------	------------------------------------

Description

This class contains invisible results of OptimalRule function.

Details

- phi** Percentage of patients taking viral load test.
- Z** A vector of true disease status (Failure Status coded as Z=1).
- S** A vector of risk Score.
- Rules** A matrix of all possible tripartite rules (two cutoffs) derived from the training data set.
- Nonparametric** A boolean indicating if nonparametric approach should be used in calculating the misclassification rates. If FALSE, semiparametric approach would be used.
- FNR.FPR** A matrix with two columns of misclassification rates, FNR and FPR.
- OptRule** A numeric vector with two elements, the lower and upper cutoffs of the optimal tripartite rule.

The Output class adds optimal rule to the TGST class.

plot	<i>plot function.</i>
------	-----------------------

Description

This function This function gives visualize object of class TGST or Output.

This function This function gives visualize object of class TGST or Output.

Usage

```
## S4 method for signature 'TGST'
plot(x)

## S4 method for signature 'Output'
plot(x)
```

Arguments

- x Output object from [TGST](#) or [Output](#).

Value

Distribution plot.

Distribution plot.

ROC.nonpar

*Nonparametric ROC Analysis***Description**

This function performs ROC analysis for tripartite rules by nonparametric approach. If *plot* = *TRUE*, the ROC curve is returned.

Usage

```
ROC.nonpar(Z, S, phi, plot = TRUE)
```

Arguments

- | | |
|------|--|
| Z | True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1). |
| S | Risk score. |
| phi | Percentage of patients taking viral load test. |
| plot | Logical parameter indicating if ROC curve should be plotted. Default is <i>plot</i> = <i>TRUE</i> . If false, then only AUC is calculated. |

Value

AUC The area under the ROC curve. FNR Misdiagnoses rate for viral failure (false negative rate).
FPR Misdiagnoses rate for treatment failure (false positive rate).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
a = ROC.nonpar( Z, S, phi,plot=TRUE)
a$AUC
a$FNR
a$FPR
```

ROC.semipar

*Semiparametric ROC Analysis***Description**

This function performs ROC analysis on the rules from nonparametric approach. If $plot = TRUE$, the ROC curve is returned.

Usage

```
ROC.semipar(Z, S, phi, plot = TRUE)
```

Arguments

Z	True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
S	Risk score.
phi	Percentage of patients taking viral load test.
plot	Logical parameter indicating if ROC curve should be plotted. Default is $plot=TRUE$. If false, then only AUC is calculated.

Value

AUC The area under the ROC curve. FNR Misdiagnoses rate for viral failure (false negative rate).
FPR Misdiagnoses rate for treatment failure (false positive rate).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
a = ROC.semipar( Z, S, phi, plot=TRUE)
a$AUC
a$FNR
a$FPR
```

ROCAnalysis

*ROC Analysis***Description**

This function performs ROC analysis for tripartite rules. If $plot = TRUE$, the ROC curve is returned.

Usage

```
ROCAnalysis(Obj, plot = TRUE)
```

Arguments

- Obj** An object of class TGST.
plot Logical parameter indicating if ROC curve should be plotted. Default is plot=TRUE. If false, then only AUC is calculated.

Value

AUC (the area under ROC curve) and ROC curve.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
lambda = 0.5
Obj = TGST(Z, S, phi, method="nonpar")
ROCAnalysis(Obj, plot=TRUE)
```

Description

This function gives you the optimal semiparametric tripartite rule that minimizes TMR (total misclassification risk).

Usage

```
Semi.par.rule(Z, S, phi)
```

Arguments

- Z** True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
S Risk score.
phi Percentage of patients taking viral load test.

Value

Semiparametric rule and its associated TMR.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
Semi.par.rule( Z, S, phi)
```

semipar.fnr.fpr

Semiparametric FNR FPR of the rules

Description

This function gives you the semiparametric FNR and FPR associated with a given tripartite rule.

Usage

```
semipar.fnr.fpr(Z, S, l, u)
```

Arguments

- | | |
|---|---|
| Z | True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1). |
| S | Risk score. |
| l | Lower cutoff of tripartite rule. |
| u | Upper cutoff of tripartite rule. |

Value

Matrix with 2 columns. Each row is a set of semiparametric (FNR, FPR) on an associated tripartite rule.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
rules = nonpar.rules( Z, S, phi)
semipar.fnr.fpr(Z,S,rules[1,1],rules[1,2])
```

Simdata*Simulated data for package illustration*

Description

A simulated dataset containing true disease status and risk score. See details for simulation setting.

Usage

```
data(Simdata)
```

Format

A data frame with 8000 simulated observations on the following 2 variables.

- Z True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).
- S Risk score. Higher risk score indicates larger tendency of diseased / treatment failure.

Details

We first simulate viral status Z assuming $Z \sim Bernoulli(p)$ with $p = 0.25$; and then conditional on Z , simulate $S|Z = z = ceiling(W)$ with $W \sim Gamma(\eta_z, \kappa_z)$ where η and κ are shape and scale parameters. $(\eta_0, \kappa_0) = (2.3, 80)$ and $(\eta_1, \kappa_1) = (9.2, 62)$.

Examples

```
data(Simdata)
## maybe str(Simdata) ; plot(Simdata) ...
```

summary*summary function.*

Description

This function gives the summary of the data from **TGST**.

Usage

```
## S4 method for signature 'TGST'
summary(object)
```

Arguments

object	Output object from TGST .
--------	----------------------------------

Value

Percentage of treatment failure; Summary statistics (mean, standard deviation, minimum, median, maximum and IQR) of risk score by true disease status; Distribution plot.

TGST

*Create a TGST Object***Description**

Create a TGST object, usually used as an input for optimal rule search and ROC analysis.

Usage

```
TGST(Z, S, phi, method = "nonpar")
```

Arguments

- | | |
|--------|---|
| Z | A vector of true disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1). |
| S | A vector of risk Score. |
| phi | Percentage of patients taking gold standard test. |
| method | Method for searching for the optimal tripartite rule, options are "nonpar" (default) and "semipar". |

Value

An object of class TGST. The class contains 6 slots: phi (percentage of gold standard tests), Z (true failure status), S (risk score), Rules (all possible tripartite rules), Nonparametric (logical indicator of the approach), and FNR.FPR (misclassification rates).

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
phi = 0.1 #10% of patients taking viral load test
TGST( Z, S, phi, method="nonpar")
```

TGST-class	<i>Constructor of TGST class</i>
-------------------	----------------------------------

Description

This class contains results of a run to search for all possible rules.

Details

phi Percentage of patients taking viral load test.

Z A vector of true disease status (Failure Status coded as Z=1).

S A vector of risk Score.

Rules A matrix of all possible tripartite rules (two cutoffs) derived from the training data set.

Nonparametric A boolean indicating if nonparametric approach should be used in calculating the misclassification rates. If FALSE, semiparametric approach would be used.

FNR.FPR A matrix with two columns of misclassification rates, FNR and FPR.

If res is the result of rankclust(), each slot of results can be reached by res[k]@slotname, where k is the number of clusters and slotname is the name of the slot we want to reach (see [Output-class](#)). For the slots ll, bic, icl, res["slotname"] returns a vector of size K containing the values of the slot for each number of clusters.

TGST.summ	<i>Summary of Disease Status and Risk Score</i>
------------------	---

Description

This function allows you to compute the percentage of diseased (equivalent to treatment failure Z=1) and show distribution summary of risk score (S) by the true disease status (Z).

Usage

```
TGST.summ(Z, S)
```

Arguments

Z True disease status (No disease / treatment success coded as Z=0, diseased / treatment failure coded as Z=1).

S Risk score.

Value

Percentage of treatment failure; Summary statistics (mean, standard deviation, minimum, median, maximum and IQR) of risk score by true disease status; Distribution plot.

Examples

```
d = Simdata
Z = d$Z # True Disease Status
S = d$S # Risk Score
TGST.summ(Z,S)
```

Index

* **AUC**
 cal.AUC, 2
 ROC.nonpar, 9
 ROC.semipar, 10

* **ROC**
 ROCAnalysis, 10

* **datasets**
 Simdata, 13

* **nonparametric**
 nonpar.fnr.fpr, 4
 nonpar.rules, 5
 Opt.nonpar.rule, 6
 ROC.nonpar, 9

* **risk**
 CV.TGST, 3

* **rules**
 nonpar.fnr.fpr, 4
 nonpar.rules, 5
 Opt.nonpar.rule, 6
 Opt.semipar.rule, 6
 OptimalRule, 7
 Semi.par.rule, 11
 semipar.fnr.fpr, 12
 TGST, 14

* **semiparametric**
 Check.exp.tilt, 3
 Opt.semipar.rule, 6
 ROC.semipar, 10
 Semi.par.rule, 11
 semipar.fnr.fpr, 12

* **summary**
 TGST.summ, 15

* **validation**
 CV.TGST, 3

cal.AUC, 2
Check.exp.tilt, 3
CV.TGST, 3

nonpar.fnr.fpr, 4

nonpar.rules, 5
Opt.nonpar.rule, 6
Opt.semipar.rule, 6
OptimalRule, 7
Output, 9
Output-class, 8, 15

plot, 8
plot,Output-method (plot), 8
plot,TGST-method (plot), 8

ROC.nonpar, 9
ROC.semipar, 10
ROCAnalysis, 10

Semi.par.rule, 11
semipar.fnr.fpr, 12
Simdata, 13
summary, 13
summary,TGST-method (summary), 13

TGST, 9, 13, 14
TGST-class, 15
TGST.summ, 15